

Experimental measurements of the bacterial oxidation of HT in soils: impact over a zone influenced by an industrial release of tritium in HT form.

Olivier Connan, Hugo Renard, Severine Le Dizes-Maurel, Luc Solier, Didier Hebert, Olivier Cazimajou, Philippe Laguionie, Denis Maro

▶ To cite this version:

Olivier Connan, Hugo Renard, Severine Le Dizes-Maurel, Luc Solier, Didier Hebert, et al.. Experimental measurements of the bacterial oxidation of HT in soils: impact over a zone influenced by an industrial release of tritium in HT form.. Journal of Environmental Radioactivity, 2022, 242, pp.106779. 10.1016/j.jenvrad.2021.106779. hal-03541784

HAL Id: hal-03541784 https://hal.science/hal-03541784

Submitted on 5 Jan 2024 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

- 1 Experimental measurements of the bacterial oxidation of HT in soils:
- 2 impact over a zone influenced by an industrial release of tritium in HT
- 3 **form.**
- 4 ⁽¹⁾Renard H., ⁽¹⁾ Connan O., ⁽²⁾Le Dizes S., ⁽¹⁾Solier L., ⁽¹⁾Hébert D., ⁽¹⁾Cazimajou O., 5 ⁽¹⁾Laguionie P., ⁽¹⁾Maro D
- 6 ⁽¹⁾Institut de Radioprotection et de Sûreté Nucléaire (IRSN), PSE-ENV/SRTE/LRC, BP 10, rue Max Pol
- 7 Fouchet, 50130 Cherbourg-En-Cotentin, France.
- 8 ⁽²⁾Institut de Radioprotection et de Sûreté Nucléaire (IRSN), PSE-ENV/SRTE/LR2T, BP 3, 13115 Saint Paul
- 9 Lez Durance, France
- 10 * Corresponding author:
- 11 E-mail adress: olivier.connan@irsn.fr
- 12 IRSN
- 13 Cherbourg-En-Cotentin Radioecology Laboratory
- 14 Rue Max Pol Fouchet
- 15 BP10
- 16 50130 Cherbourg En Cotentin
- 17 *Tel (33) 2 33 01 41 08*
- 18
- 19

1 Experimental measurements of the bacterial oxidation of HT in soils:

2 impact over a zone influenced by an industrial release of tritium in HT

3 **form.**

4 Abstract

5 Tritium is a radionuclide released to the atmosphere by nuclear industries in various forms, 6 mainly HTO and to a lesser extent HT. However, some nuclear sites may emit predominantly 7 HT in the atmosphere. The HT is oxidized to HTO essentially in the top cm of soils, and that 8 the formed HTO is then possibly released into the atmosphere. HTO is an assimilable form by 9 plants. Therefore, it is important to understand the environmental behaviour of HT.

In this work, we adapt the bacterial oxidation model of HT in soils of Ota *et al.* (2007) by laboratory experiments on soils typical of western France, and we have in particular adapted the frequency factor A and the Michaelis-Menten enzymatic reaction parameter (Km) on the basis of an Arrhenius equation in function of the porosity of the soil.

We then applied this model to the environment near the reprocessing plant of Orano la Hague 14 (France), which emits a significant amount of HT. Based on the adapted model, and knowing 15 the atmospheric variations of HTO and HT over the period 2013-2016, we estimated that the 16 mean HTO activity in soil due to atmospheric HT reached 0.6 Bq.L⁻¹ (with a peak value of 5 17 Bq.L⁻¹) while the mean value with all sources taken into account is 6.2 Bq.L⁻¹. Then, in an 18 19 environment such as that surrounding the Orano La Hague plant, where near-field atmospheric HT activity is very high, the bacterial oxydation contribution to produce HTO in 20 21 the soil can be considered as approximately 10%. The flux to the atmosphere from these source representing approximately. 1.5 Bq.m⁻².d⁻¹. If we consider an area of 2 km around the 22 plant (i.e. 13 km²), we estimate 218 Bq.s⁻¹ of HTO was released by the soil, representing less 23 than 0.1% of the direct atmospheric release of HTO around the site. From this work, it 24 appears clear that this secondary source term from the soil is insignificant at this specific site. 25

Keyword : HT, bacterial oxydation in soil, soil texture, reprocessing plant.

27

28

29 **1. Introduction**

Tritium (³H) is a low energy β -emitting radionuclide with a half-life of 12.32 years. Tritium is 30 produced by naturally-occurring processes through the interaction of gases and cosmic 31 radiation. Natural abundance is estimated at about 4.5 kg of tritium, produced at an average 32 rate of 0.32 atom cm⁻²·s⁻¹ of earth surface (Masarik and Beer, 2009, UNSCEAR, 2016), 33 corresponding to ≈ 258 g y⁻¹ (Oms *et al.*, 2019). Atmospheric tests of nuclear weapons 34 between 1945 and 1980 led to an estimated release of 668 kg, corresponding to about 242x10⁶ 35 TBq during that period (Okada and Momoshima, 1993; UNSCEAR, 2000); in 2016, the 36 tritium remaining from the fallout from atmospheric nuclear weapons testing is estimated to 37 be 22-23.5 kg (Oms et al., 2019). Today, ³H is mainly released into the environment by 38 nuclear power plants, military nuclear facilities and nuclear reprocessing plants (CNSC, 2009; 39 ASN, 2010). Atmospheric releases of tritium to the world's nuclear power plants range from 40 500 to 600 TBq.y⁻¹ (1.4-1.7 g.y⁻¹). At country scale, for example in France, the 58 reactors 41 (PWR Pressurized Water Reactor) from nuclear power plants release approximately 34 42 TBq.y⁻¹ (~0.1 g) of tritium gas and 1000 TBq.y⁻¹ (~3 g) of tritium liquid (Oms *et al*, 2019). 43 Spent fuel reprocessing plants (Orano La Hague in France, Sellafield in UK, Tokai-Mura in 44 Japan) released approximately 200 to 300 TBq.y⁻¹ in gaseous form between 1995 and 2007 45 (IRSN, 2009). These three plants in the world contribute proportionally strongly to the release 46 47 of tritium to the atmosphere if we compare with the large number of Nuclear Power plants. Since 2010, Orano La Hague (France) has released 64 TBq.y⁻¹ of gaseous tritium annually on 48 average, and a major part of this release is in HT form (85%, Connan et al, 2017). Many 49 facilities other than nuclear power plants and fuel reprocessing plants may release tritium in 50 gaseous form, such as military weapons manufacturing plants, or tritium plants in the 51 luminescent product industry (mainly in Canada). For the luminescent produce industry, in 52 2006, gaseous releases were estimated at 300 TBq.y⁻¹ (ASN, 2010). Military weapons plants 53 can also release gaseous tritium. Thus in France, the Valduc and Marcoule factories releases 54 about 200 TBq.y⁻¹ (IRSN, 2018). In the future, the construction of new nuclear facilities (e.g. 55 European Pressurized Reactor, International Thermonuclear Experimental Reactor ITER) as 56 well as changes in nuclear fuel management may lead to an increase in ³H released from the 57 nuclear industry. For example, ITER in the south of France could release between 220 and 58 900 TBq.y⁻¹ (Cortes, 2015) and we cannot exclude, on a global scale, the possibility of HT 59

releases related to tritium production and underground tests by countries that are activelydeveloping nuclear weapons programs.

While the HT form is not the dominant content of these releases, it is important to understand 62 the behaviour of this HT form when oxided in the top cm of soils, because this tritium can 63 then be released into the atmosphere in assimilable HTO form. The HT form is not directly 64 65 bio-available in the ecosystem for plants, but becomes bio-available after oxidation into HTO (Sweet and Murphy, 1981, Conrad et al., 1983, Dunstall et al., 1985, Bunnenberg et al., 1986, 66 Spencer and Vereecken-Sheehan, 1994, Golubev et al., 2001, Peterson and Davis, 2002, Kim 67 et al., 2014). In HTO form, tritium can be readily exchanged with hydrogen atoms in the 68 environment, thus entering the hydrological cycle, and then can enter the human/biological 69 body through ingestion and inhalation (Belot, 1986). 70

HT can oxidize into HTO in the environment at atmospheric level (Clerc *et al.*, 1988, Ota *et al.*, 2007, Ehalt and Rohrer, 2009) and on the surface of a plant leaf (Cline, 1953, Dunstall *et al.*, 1985, Ichimasa *et al.*, 1989, 1995). However, HT mainly oxidizes in the top centimeters of soil due to bacterial action (McFarlane *et al.*, 1978, Schuler and Conrad, 1991, Spencer et Dunsdall, 1986, Kim *et al.*, 2014) and, to a lesser extent, under the effect of abiotic enzymes in the soil (Conrad et Seiler, 1981, Schuler et Conrad, 1991).

HT bacterial oxidation can be anaerobic or aerobic (Popelier et al., 1985, Schuler et Conrad, 77 78 1991, Libert et al., 2000, Piché-Choquette et al., 2016), but it has been shown that, in soil, 79 aerobic bacteria are the most active type (Schuler et Conrad, 1991). Ota et al. (2007) proposed 80 an empirical equation to quantify the oxidation of HT into HTO in soil. This reference equation for the scientific community is based on deuterium oxidation works carried out in 81 controlled laboratory conditions for a given soil type. However, it has been shown that the 82 83 oxidation rate of HT varies depending to the soil type (Conrad et al., 1983, Golubev et al., 2001, Kim et al., 2014) and it is important to adapt the work of Ota et al. (2007) to soils 84 85 corresponding to all existing environment.

In this study, to begin with, we started with laboratory experiments focusing on the oxidation of HT to HTO for several soil types typical of north-west France, and corresponding to the soils we found around the Orano La Hague spent fuel reprocessing plant. We particularly attempted to better integrate the influence of the soil texture on the rate of HTO production from atmospheric HT. The aim was to improve the precision of the current bacterial oxidation equation used by Ota *et al.* (2017) and, in addition, to generally apply this equation to any soil
type depending on porosity estimated from soil fractions (silt, loam, clay).

Our subsidiary and more operational aim was to improve forecasts for HTO stock potentially "generated" in the soils in the immediate environment of the Orano La Hague plant, which could be available for atmospheric release based on precise available information on variation in HT activity. The idea behind the work is, as the Orano la Hague plant releases 85% of tritium in HT form, to estimate the ability of soils to convert this HT form into HTO, and to compare this "new stock" of HTO from bacterial oxidation with usual direct atmospheric releases of HTO.

100

2. Modelling HT oxidation in soil and expressing the frequency factor A as a function of soil porosity

HT oxidation in soil is mainly driven by the hydrogen oxidation enzymes (hydrogenesis) contained in the streptomyces (Komuro *et al.*, 2002). The generation of HTO by HT oxidation is considered as an enzymatic reaction (Ota *et al.*, 2007), and the kinetics are described by the Michaelis-Menten equation (Quinlan, 1981):

$$V_{oxi} = V_{max} \cdot \frac{[HT]}{[HT] + K_M} \tag{1}$$

107

The terms of the equations in this section are described in Table 1. It has been proven that the 108 bacterial oxidation of HT depends on temperature, water content, porosity and the vertical 109 distribution of oxidizing micro-organisms (bacterial concentration gradient) in the soil profile 110 (Sweet and Murphy, 1981, Conrad et al., 1983, Dunstall et al., 1985, Bunnenberg et al., 1986, 111 Spencer and Vereecken-Sheehan, 1994, Peterson and Davis, 2002, Ota et al., 2007). These 112 113 different factors affect the rate of an enzymatic reaction V_{max} and were defined by Ota et al (2007) using the equation (2). The parameters $f_W(\theta)$. $f_T(T)$. $f_Z(Z)$ are defined in Table 1 and 114 readers should refer to Ota et al. (2007) for a detailed parametrization of these factors. 115

$$V_{max} = V_{ref}.f_W(\theta).f_T(T).f_Z(Z)$$
⁽²⁾

The Michaelis-Menten enzymatic reaction parameter (Km) for equation 1 is expressed as a
function of the temperature on the basis of an Arrhenius equation (Quinlan, 1980, Ota *et al.*,
2007) according to equation (3):

$$K_M = A. e^{\left(\frac{-E}{RT}\right)} \tag{3}$$

In the model of Ota et al. (2007), the parameters A and E are determined by adjusting 119 120 according to experiments for a given soil type. The activation energy of the bacterial reaction of the HT (noted E) exclusively depends on the type of catalysing enzyme and the substrate 121 (Triebwasser-Freese et al., 2015, Bock et al., 2019). We postulate that E is identical for all 122 pedological soil types as, for our study, hydrogenesis is assumed as the type of catalysing 123 enzyme and HT is assumed for the substrate, for all soil types (Conrad et al., 1983). A is 124 defined as a frequency factor, integrating steric effects and the probability of collision 125 between an oxidizing enzyme and HT (Hupp et Weaver, 1983, Weilandt et Hatzimanikatis, 126 2019). On this basis, parameter A will depend on soil porosity and type and is likely to differ 127 depending on the pedological characteristics of the soil: this parameter A must be adjusted to 128 refine the oxidation model. 129

The process applied in this context, to express frequency factor A for any soil type, includesseveral stages:

- Measuring particle distribution and expressing soil porosity;

- Performing bacterial oxidation laboratory experiments with HT for different soil types,
 using soils from our local environment and air enriched in HT sampled from the
 Orano La Hague plant stack plume;
- Calculating the value of A according to equation (3) by adjusting the outputs from the
 model (equation 1) and the HTO activity produced based on experimental
 measurements;

- Expressing A as a function of soil porosity.

140

141 **3. Experimental design and methodology**

142 **<u>3.1 Soil samples</u>**

The soils used for laboratory experiments were taken *in situ* in zones outside of the influence of the sites releasing tritium in the north-west region of France (Table 2) in order to obtain initial HTO activity values less than 1 Bq.L⁻¹. Samples were taken using PVC tubes with a diameter of 10 cm, and a depth varying between 5 and 15 cm. Each soil sample (see characteristics in Tables 2 and 3) corresponds to a meadow type farming soil, planted with

- 148 ray-grass. The granulometric characteristics of the 5 soil types studied can be found in Table
- 149 2. Analyses were performed according to standards NF ISO 11464 and NF X 31 107 by an
- 150 external laboratory (National Institute of Agronomical Research, INRA, France).
- 151 During this study, three types of soil cores were systematically sampled at each site:
- 152 One core intended to check the absence of HTO in the sample;
- One core containing grass intended to determine the bacterial oxidation of HT in the
 top centimetres of soil, in laboratory conditions;
- One core without grass intended to study the bacterial oxidation of HT for bare soil
 (soil in which the top 4 cm, corresponding to grass roots, have been removed).

The cores are isolated from the environment by attaching a sleeve (PVC) to the "root" end of the core sampling tube and a parafilm to the "surface" end of the core sampling tube. Once the core has been isolated from contact with ambient air, it is stored in a chiller during transport, and then in a freezer prior to use in laboratory experiments.

161 **<u>3.2 Calculating soil porosity</u>**

162 The soil porosity index for our 5 experiments was calculated in several stages. The apparent 163 bulk density of the soil, noted $density_{bulk}$, and expressed in kg.m⁻³, corresponding to the 164 mass of soil contained in a given volume, including the volume of interstitial air, is 165 determined using equation 4.

166

$$density_{bulk} = fraction_{clay}. density_{clay} + fraction_{silt}. density_{silt} + fraction_{sand}. density_{sand}$$
(4)

167

Where the term fraction corresponds to the share of a type of particle i (i = clay, silt, sand) in kg_i.kg soil⁻¹ and density_i is the apparent density of a particle i. The different types of soil particle (Clay, Silt, Sand) and their apparent densities can be found in the website (Density of Sand, dry in 285 units and reference information (aqua-calc.com); Table A1).

The density of a soil particle (density_{particle}) corresponding to the mean mass of a soil particle per unit of volume is then calculated. Schjønning *et al.* (2017) propose equation 5 to determine density_{particle} from the fraction of clay in the soil (fraction_{clay}).

$$density_{particule} = fraction_{clay}.2.86 + (1 - fraction_{clay}).2.65$$
(5)

Finally, porosity (equal to the volume of porous space per volume of soil) stated in m³ space m⁻³ soil) is determined from the two terms calculated earlier, $density_{bulk}$ and *density*_{particule} by equation 6 (Chaudhari *et al.*, 2013).

178

$$porosity = 1 - \frac{density_{bulk}}{density_{particule}}$$
(6)

179

180 **<u>3.3 Sampling of air enriched with HT</u>**

The aim in this context is to circulate air enriched with tritium in HT form in the laboratory in 181 order to observe the incorporation of HT in the soil and oxidation into HTO. The volumes of 182 air containing high concentrations of atmospheric HT are sampled in the environment near to 183 the Orano La Hague (France) spent fuel reprocessing plant, which releases tritium in HT and 184 HTO forms (Connan et al., 2017) during its industrial processes. These tritium releases are 185 concomitant with the ⁸⁵Kr releases. This gas can be measured in real time, which allows 186 samples to be specifically taken during periods with high HT activity. Air samples containing 187 HT were therefore taken downwind from the Orano la Hague plant, making sure that the air 188 sampled was enriched in tritium thanks to the ⁸⁵Kr measurements, using an air compressor 189 (Bauer compressor Junior). Several B20 type (4 m³) gas cylinders were prepared with a 190 191 vacuum prior to sampling for the purposes of these experiments; the air sampled for our experiments contained HT levels between 1 and 23 Bq.m⁻³. Due to the compression sampling 192 technique, ambient humidity (water vapour containing tritium in HTO form) is eliminated and 193 the air only contains HT. 194

195 In order to determine the exact HT content of the air used for the experiments, the protocol described by Connan et al. (2017) was applied; For HT measurements, the volume of air 196 197 collected in the pressurized container was transferred to gas treatment lines in order to obtain the HT concentration after transformation to HTO. The air passed successively at a rate of 20 198 L.h⁻¹ through an activated charcoal trap made of two carbon canisters (ACR, Agilent 199 technologies), which trap volatile organic compounds; two first bubblers (Bubbler N°1 and 200 201 $N^{\circ}2$) filled with 150 cm³ of tritium-free water (Abatilles spring water) are used to eliminate any residual tritiated water vapor after compressing while sampling. A heated 200°C catalysis 202 oven (palladium pellets SDEC, France) was then used to oxidize the HT to HTO (Bubblers 203

N°3 and N°4). After the passage of a volume of about 500 L of air (depending on the 204 expected level), air without ³H was injected (flow: 30 L.h⁻¹) to purge the pipes and ovens of 205 all traces of ³H in order to prevent any cross-contamination between the different samples. 206 During this step, which lasts 60 minutes, both ovens were heated to a temperature of 450°C. 207 208 Then, after these different steps, a volume of water was collected from the bubbler for measuring purposes. After storage in darkness at 4 °C prior to analysis, water (10 mL) was 209 mixed with a liquid scintillator (10 mL) to allow for measurements by liquid scintillation 210 211 counting.

212

213 <u>3.4 HT bacterial oxidation chamber</u>

The experimental set-up includes a leaktight bag containing soil cores, and HT is injected into 214 this bag at a constant rate (0.2 L.min^{-1}) . The oxidation kinetics of HT driven by soil bacteria is 215 quantified by measuring the HTO produced in the soil core after a given period. The 216 experimental set-up is described in Figure 1. The oxidation chamber consists of a 217 300x400x500 mm³ airlock in leaktight Tedlar in which the soil cores taken from the 218 environment are introduced. The full length of the bag is open so that cores can be added or 219 220 removed, and a clip system is used to ensure leaktightness. The HT is injected into the experimental set-up using a B20 (4m³) cylinder with known HT activity (see table 6 for HT 221 activities in the cylinder). The injection flow is controlled by a pressure gauge to maintain a 222 223 constant pressure at equilibrium. To avoid any contamination of the bag by traces of HTO, an upstream bubbler-type system containing Abatilles spring water is inserted between the gas 224 cylinder and the bag. This ensures that only the HT hydrogen form is injected into the bag. 225 The same set-up is placed downstream of the bag to prevent external air backflow and to 226 227 evacuation any extra air inside the oxidation chamber. During the experiments, temperature and humidity sensors (WATCHDOG, SDEC France) are placed in the soil cores and in the 228 229 oxidation chamber to track temperature and water-content changes. A beta radioactivity meter (LB123, Berthold Technology Germany) is also placed against the bag to track ⁸⁵Kr activity 230 (present in the air injected containing the HT) in real time. The real time ⁸⁵Kr measurements 231 can be used, by analogy, to monitor and avoid any sudden change in HT activity in the bag. 232

233

234 **<u>3.5 Processing soil after exposure to HT:</u>**

After a few days, when the HT soil contamination experiments have been completed, the 235 core(s) are removed from the bag (cores can be removed at different times as part of the same 236 experiment). The soil sample is then wrapped in parafilm and temporarily stored in a cold 237 chamber at 4°C. Each core is then opened and placed on an aluminium tray with a diameter of 238 20 cm, and then vacuum packed to avoid any contamination, and frozen for 48h at -80 °C. 239 This freezing phase optimises the upcoming lyophilization process. Samples are then 240 lyophilized (ThermoElectron HETO PowerDry PL3000) in order to remove the HTO from the 241 soil produced during HT oxidation. After 24 to 72 h of lyophilization, the water from the soil 242 243 is recovered and the HTO will be measured by liquid scintillation counting of 10 mL of water 244 (Maro *et al.*, 2017).

245 <u>3.6 Tritium measurements</u>

Tritium activity (HTO) was measured by liquid scintillation counting (TRI-CARB 3180 246 TRSL, PerkinElmer) with a counting time of 16 hours per sample. For HTO measurements, a 247 volume of 10 cm³ of collected water was placed in a vial with 10 cm³ of liquid scintillation 248 249 cocktail (Ultima gold LTT). Measurement uncertainty depends on the counting time and level 250 of activity. Typically, for the levels to be measured, uncertainty was 3-10%. The background count rate and counting efficiency were 2.09 cpm and 14.9%. Our measurement practices are 251 252 regularly validated by comparison exercises between French and international laboratories. Limit of detection are 1 Bq. L^{-1} . 253

254 3.7 Application of the methodology to the Orano La Hague reprocessing plant site

The Orano La Hague reprocessing plant (49.677 °N, -1.883°W) is located in North-West 255 France, in the Normandy region. Reprocessing releases ³H into the environment, mainly 256 257 through two main discharge stacks at the UP2-800 and UP3 plants. For example, in 2016, 66 TBq of tritium was released into the atmosphere, with 85% in HT form and 15% in HTO form 258 259 (Connan et al., 2017). As part of earlier works, for an experimental study site around the Orano site, located at 2 km from the plant (Plateforme Technique Instrumenté de La Hague 260 (La Hague Instrument-fitted Technical Platform), PTILH, 49.694°N, -1.873°W), we 261 developed tools which can be used to reconstruct atmospheric variation in HT and HTO 262 activity, over specific time periods, by measuring ⁸⁵Kr, HTO and HT activity at minute, 263 weekly and monthly intervals respectively, as these elements are discharged simultaneously at 264 265 the main stacks (Maro et al, 2017, Le Dizès et al., 2017, Renard, 2017). On this basis, we can 266 access highly precise timelines for some past periods. Further to the adjustments made, based

on these experiments, to the relationship between soil porosity and factor A used to complete 267 the oxidation model proposed by Ota et al. (2017), we attempted to calculate the variation in 268 HTO activity induced by bacterial oxidation in soil in the immediate environment around the 269 Orano plant, when ambient HT activity is known. We used the TOCCATA- γ transfer model 270 for ³H (and ¹⁴C) in terrestrial ecosystems, developed by the IRSN (Radiation Protection and 271 Nuclear Safety Institute) (Le Dizès et al., 2017, Renard, 2017), for this purpose. This 272 compartmented model covers specific time periods and integrates the day/night cycle inherent 273 in the physiological behavior of plants based on a simplified grassland model (Riedo et al., 274 275 1998, Le Dizès et al., 2017). The pool of tritium in soil is considered to exclusively comprise tritiated water dissolved in the unsaturated soil compartment. Soil HTO activity concentration 276 277 is expressed as a function of (1) a (net) exchange process with an exchange velocity rate at the soil/air interface, (2) percolation (downward migration) of rainwater in soil, (3) root uptake of 278 279 soil HTO and (4) soil HT oxidation. Similarly, soil water content results from the integration of precipitation over time minus water losses by percolation and root uptake, which is 280 281 estimated using the Penman-Monteith model (Allen et al., 1998) and a soil water stress factor that also possibly affects stomatal conductance (Le Dizès et al., 2017, Renard, 2017). 282

283

4. Results and discussion

285 **4.1 Soil granulometry**

The different proportions of clay, total loam and total sand can be used to characterize the soil type with reference to the texture triangle proposed by USDA (Table 4, United States Department of Agriculture, USDA). The soils we focused on were loam or silt loam type, with clay content of less than 19%, sand content varying between 25 and 51% and loam content varying between 40 and 57%.

291

292 **<u>4.2 Porosity of the soil types studied</u>**

The porosities of the soil types covered by our study have been estimated using equations 4, 5 and 6 and the respective proportions of clay/loam/sand measured (Table 5); we also ran the same calculations for various works found in the literature, as mentioned in table 5, and which allow us to complete this project by extending the soil types considered. Porosity varies from 0.43 to 0.44 for the soil types covered by our experiments. For the studies in the literaturementioned in this paper for the purpose of comparison, porosities vary from 0.39 to 0.46.

299

300 **4.3. Determining the frequency factor A**

Frequency factor A (defined by equation 3) was calculated for our soil types based on the rate at which HTO is generated by soil bacteria (V_{oxi}) calculated using equations 1, 2 and 3, and which depends, in situ, on the HTO activity measured at the end of the HT exposure experiments. The oxidation rate is initially determined by measuring the HTO activity in the water in the soil produced by bacterial HT oxidation (Table 6) at the end of the experiment, with a known period of exposure given in hours (Table 3 and 6). It has been demonstrated that the rate of bacterial HT oxidation varies linearly over time (Piché-Choquette *et al.*, 2016).

308 During our experiments with soils with initial HTO values < 1 Bq.L⁻¹, the activity measured 309 at the end of the experiments reached values between 6.6 and 32 Bq.L⁻¹, directly influenced 310 by HT activity (from 1.1 to 23.0 Bq.m⁻³) and exposure time (224 to 1224 h). The rate of 311 production of HTO in soil in the experimental system of HTO varied from 8 to 64 mBq.L⁻¹.h⁻ 312 ¹, which is equivalent to 0.2-1.54 Bq.L⁻¹.d⁻¹.

The frequency factor A is then calculated by minimizing errors between the model (equation 1) and the measurements (Table 6) using an Excel solver. The frequency factors for our experiments vary between 6.97×10^4 and 3.06×10^5 ppm.mol.m⁻³.

For soil types from the same sampling site (Experiments 1, 4 and 5), the frequency factors A obtained are similar, despite different core coverage (Table 3). The minor variation in A between these 3 soil types sampled at the same location indicate that the plant cover does not play a significant role in the rate of bacterial oxidation of HT.

This methodology was applied to data taken from the literature if sufficient experimental details were available in the original publications. Table 7 combines different values for frequency factor A calculated using the associated soil types.

According to Table 7, the highest A values are found in sandy soils and the lowest A values are found in loamy to silt-loam soils. According to equations 1 and 3, this means that the rate of HT oxidation by soil bacteria is faster in loamy soils than in sandy soils in equal experimental conditions (temperature, water content, HT concentration, soil depth, plant 327 cover). This pedological variability in the frequency factor reflects the impact of soil porosity328 on A:

- For a soil with low porosity levels (e.g. sandy soil): steric repulsion and the probability
 of collision between an oxidizing enzyme and HT will be high;
- For a soil with high porosity levels (e.g. very fine loamy/silty soil): steric repulsion
- and the probability of collision between an oxidizing enzyme and HT will be low.
- 333

334 **4.4. Relationship between frequency factor A and soil porosity**

The frequency factor was plotted as a function of soil porosity (Figure 2) using the data in tables 5 and 7 (porosity calculated for all soil types in our study and in the literature and A calculations). By using data from the literature and our experimental data, we cover a soil porosity range of 0.39 - 0.46, and a second degree polynomial type equation is proposed (Figure 2). This equation can also be written in canonical form as equation 7): on this basis, the minimum theoretical value of A is 8.19x10⁴ ppm.mol.m⁻³ (calculated as the minimum of the regression function in Figure 2), which is reached when soil porosity is equal to 0.44.

$$A = 4.43 \times 10^9. (porosity - 0.44)^2 + 8.19 \times 10^4$$
(7)

342

By using this equation, which depends on the soil porosity calculated according to Eq. 6 with standard particle density values for each soil type listed according to USDA (Table 5), we can estimate the frequency factor A for each potential existing soil type (Table 4). The frequency factor will vary by a factor of 46 between the sand, which has the highest factor A (1.00x10⁷ ppm.mol.m⁻³), and the Silty Clay, which has the lowest factor A (2.19x10⁵ ppm.mol.m⁻³).

348

5. Operational application in the Orano La Hague environment

Our operational aim behind this experiment was to determine the ability of the soil in the immediate environment around the Orano La Hague reprocessing plant to "generate" HTO from release of HT. As previously mentioned, tritium is released into the atmosphere during the process as gaseous HTO (15%) but mostly HT form (85%) representing about 60 - 70 TBq.y⁻¹ (Connan *et al.*, 2017).

355 <u>5.1 Theoretical simulation for air HT activity = 1 Bq m⁻³, for all soil types</u>

In this environment with a high ambient HT activity, it is worth preparing a report and estimating if the HTO stock generated by bacteria in soil is significant on an annual scale, and must be considered (as this stock could be re-released to the atmosphere) or if, on the contrary, it can be ignored versus the HTO already present in the soil (from a different origin). We calculated the formation of HTO in soil by the bacterial oxidation of HT for this purpose, based on equations (1), (2) and (3) and the data from Table 4.

To begin, the calculation was run assuming a constant atmospheric HT activity of 1 Bq.m⁻³ (Table 8), for all potential soil types (including types which are not present in the immediate environment around the plant, Figure 3), using mean water density and temperatures for 4 seasons (Table 8) obtained in previous works (Maro *et al.*, 2017). On this basis, equation 8 can be used - after calculating the oxidation rate - to convert a mole of HT in the soil (mol HT.kg⁻¹ dry soil) into a mole of HT per surface area depending on soil type (mol HT.m⁻²).

368

$$V_{oxi_surface} = V_{oxi}. density_{bulk}. z$$
(8)

369

Where z is the depth of soil (we use a value of z = 0.05 m to represent the top cm of soil, corresponding to the soil thicknesses on which we based our experiments, and because this slice contains nearly 70% of oxidizing soil bacteria, Komuro et al 2002) and $V_{oxi_surface}$ is the oxidation rate for superficial HT (mol.m⁻²). *density*_{bulk} is determined using equation (5).

The HTO formation values obtained vary from 0.14 to 5.86 Bq.m⁻².d⁻¹ during the winter and 374 from 0.15 to 6.86 Bg.m⁻².d⁻¹ during the summer (Table 8), i.e. the differences between the 375 seasons are minor, however significant deviations are recorded depending on soil types. 376 Figure 3 shows HTO activities obtained by bacterial oxidation (for 1 Bq.m⁻³ of HT) for a 377 temperature of 12°C and a soil water content of 22.5% by volume, to illustrate the clear 378 differences between soil types. SiC (Silty Clay) type soil is the most productive in terms of 379 380 HTO formation by bacterial oxidation, followed by SiCL (Silty Clay Loam) and L (Loam) soils. The most common soil types are Loam and Silt Loam in our focus area. 381

382

383 <u>5.2 Simulation for real ambient HT activities over the 2013-2016 period</u>

For the 2013-2016 period, hourly atmospheric HT content varied from 0.01 to 28.7 Bq.m⁻³ 384 around the industrial site covered (Maro et al., 2017). We also considered a Loam soil type 385 with porosity of 0.428 and a frequency factor of 3.92×10^5 . Soil temperatures and water 386 content per volume are taken from data measured for each time period (Maro et al., 2017). 387 Bacterial oxidation calculations (improved by this work) using the TOCCATA- χ model were 388 initially performed exclusively using this source of atmospheric HT, and after we carried out 389 an identical simulation, but added to the atmospheric HT the contents for atmospheric HTO 390 and HTO in rainwater (the atmospheric concentrations of the various tritated forms present on 391 the La Hague site from 2013 to 2016 are present Appendix 2). The results can be found in 392 Figure 4. If we exclusively consider HT and therefore bacterial production, it appears that a 393 significant percentage of HTO is produced in this way (blue line), but we can see that the 394 HTO in the soil is mainly from other atmospheric sources (HTO and rainwater, black line). 395 Over the 2013-2016 period, the mean HTO activity from atmospheric HT reached 0.57 Bq.L⁻¹ 396 (with a peak value of 5 Bq.L⁻¹) while the mean value for all sources is 6.21 Bq.L⁻¹ with peak 397 values in excess of 20 Bq.L⁻¹. Over this period, the contribution of atmospheric HT to the 398 HTO value in Bq.L⁻¹ in soils is calculated as 9.1%. In an environment such as that 399 surrounding the Orano La Hague plant, where near-field atmospheric HT activity is high, the 400 contribution of the oxidation of HT to HTO in soil represents only about 10% of the total 401 available HTO stock in soil. 402

The aim of this work is to allow for the quantification of the impact of atmospheric HT once 403 404 converted into HTO and then re-released to the atmosphere, if necessary. The contribution of 405 HT to the radiation dose is lower than that of HTO, therefore it is worth obtaining information 406 on the conversion of HT into HTO in the soil and then subsequently on re-release to the atmosphere as HTO. For the 2013-2016 period, and on the basis of data on HTO in soils 407 produced by the bacterial oxidation of HT (blue line, Figure 4), we used the TOCCATA- χ 408 model to calculate the HTO exchanged at the soil-atmosphere interface (calculation with the 409 limiting condition that the air contains no prior HTO). Figure 5 shows the results obtained, 410 which indicate mean ambient release levels from the soil of 1.5 Bq.m⁻².d⁻¹ with occasional 411 peak values of 15 Bq.m⁻².d⁻¹ over some periods. 412

413 This HTO flow released by the soil representing approx. 1.5 $Bq.m^{-2}.d^{-1}$ must be compared 414 with the annual quantities of HTO released directly into the atmosphere from plant stacks.

Over the 2012-2019 period, the Orano La Hague fuel reprocessing plant discharged 66.7 415 TBq.y⁻¹ (\pm 11%) of tritium on average. Based on weekly measurements at outlets in 2014-416 2015, mean HTO and HT sources are evaluated at 3.9×10^5 Bq.s⁻¹ and 1.7×10^6 Bq.s⁻¹ 417 respectively over this period. Soil release of HTO generated by the bacterial oxidation of HT 418 was compared with this mean value for the direct ambient release of HTO; for this purpose, 419 we considered a circular surface area with a 2 km radius around the site (i.e. 12.57 km²), 420 which appeared a pertinent value in view of the sea to the north, south and west, at a distance 421 of approximately 2 km. For 12.57 km², 218 Bq.s⁻¹ of HTO was released by the soil, 422 representing only 0.06% of available ambient stock. If we refer to the maximum possible 423 releases from the soil (15 $Bq.m^{-2}.d^{-1}$) and we extrapolate to produce a constant release over 424 time, the influence of the soil would represent 0.6% of available ambient stock around Orano 425 La Hague. Although this calculation is clearly subject to extensive uncertainty (with respect to 426 427 the soil surface area to be considered, and the fact that releases in the form of plant transpiration are also ignored), it appears clear that this secondary source term from the soil is 428 429 insignificant at this specific site, due to the relatively abundant levels of existing HTO in the atmosphere and despite high HT releases, compared to other nuclear sites, which could reach 430 431 the soil.

432

433 **6.** Conclusions

This work was started in order to improve our ability to forecast the bacterial oxidation of HT in soils for all soil types. Our second aim was to quantity the amount of HTO produced in soils, and then re-released into the air around a nuclear site generating high levels of atmospheric HT activity (Orano La Hague spent fuel reprocessing plant, North west France, Europe) and to compare this amount with existing HTO activity in the atmosphere and considered in impact calculations.

To begin with, and on the basis of the model prepared by Ota *et al.* (2007) and laboratory experiments, we proposed an equation which can be used to estimate the frequency factor for bacterial oxidation after calculating soil porosity. These porosity and frequency factor parameters are suitable for the soils found in our working environment and were entered as input for the TOCATTA- χ model (Le Disez *et al.*, 2017, Renard, 2017) used by our teams. To begin with, this work demonstrated that bacterial oxidation is the dominant factor, for exposure to a constant value of HT, for a Silty Clay (SiC) soil type, followed by Silty Clay

Loam (SiCl), Loam (L) and Silt loam (SiL) with HTO values produced for ambient HT 447 activity of 1 Bq m⁻³ in excess of 2 Bq HTO.m⁻² for soil activity. For the most frequent soil 448 types around the Orano La Hague nuclear plant (Loam and Silt Loam), using the actual HT 449 activities measured over the 2013-2016 period, mean inducted HTO activity exclusively 450 attributable to bacterial oxidation represents 0.6 Bq.L-1 on average in the soil, with peak 451 values of approx. 5 Bq.L⁻¹. These values represent approx. 10% of the HTO activity measured 452 in Bq.L⁻¹ in these soils. In other words, even in this environment where ambient HT activity is 453 high versus HTO activity (85% of total tritium, i.e. factor 6), the HTO contribution (via the 454 atmosphere and rain) remains dominant over the activity measured in the soil. Secondly, 455 thanks to the TOCATTA- χ model, we were able to calculate bacterial HTO released from the 456 soil into the atmosphere during the 2013-2016 period, in Bq.m⁻².d⁻¹, by clearly taking a 457 circular area with a 2 km radius around the nuclear site studied. Using this approach, we were 458 459 able to compare this secondary soil source with the main source of HTO released directly into the atmosphere by the Orano La Hague site. This secondary source is insignificant and 460 461 represents less than 0.1% of the main source, and less than 1% if we use the highest possible values. These results ultimately reflect the low level of HT converted to HTO, approximately 462 463 1%, and are consistent with the results proposed by Kim et al. (2014), even if the approach is not entirely identical. 464

465 Our works showed that the soil is not a significant secondary source of HTO for the 466 atmosphere, on a preliminary basis, in the immediate environment of the Orano la Hague 467 reprocessing plant. It is now necessary to focus on a possible marine source. Liquid releases 468 in the marine environment are higher than atmospheric releases. Very low emission levels at 469 the sea - atmosphere interface could be increase HTO activity on the coast.

470 Acknowledgements

The authors thank Orano for their partnership during this research and for providing the stackmeasurement data.

473

474 **7. References**

Allen R.G., Pereira, L.S., Raes, D., Smith, M., 1998. Crop Evapotranspiration: Guidelines for
Computing Crop Water Requirements. FAO Irrigation and Drainage Papers, Rome, Italy, p. 328

477 ASN, 2010. French Nuclear Safety - Livre blanc du tritium (http://livre-blanc478 tritium.asn.fr/fichiers/Tritium_CHAP_5-5.pdf) 278p.

- Belot, Y., 1996. Comportement du tritium dans l'environnement. In: Belot, Y., Roy, M., Metivier, H.,
 Le tritium de l'Environnement à l'Homme. Editions de Physique, Paris, pp. 39-76.
- Bunnenberg, C., Feinhals, J., & Wiener, B., 1986. Differences in the Behaviour of HTO and H2O in
 Soil After Condensation from the Atmosphere and Conversion of HT to HTO and OBT in Soil
 Relative to Moisture Content and Pore Volume. Radiation Protection Dosimetry, 16(1-2), 83-87.
- Bock, C., Zollmann, T., Lindt, KA., Tampé, R., Abele, R., 2019. Peptide translocation by the
 lysosomal ABC transporter TAPL is regulated by coupling efficiency and activation energy. Scientific
 Reports 9(1), 1-12.
- 487 Chaudhari P.R., Ahire D.V., Ahire V.D, Chkravarty M., Maity M. 2013. Soil Bulk Density as related
- to Soil Texture, Organic Matter Content and available total Nutrients of Coimbatore Soil. International
- 489 Journal of Scientific and Research Publications, 3, 2, 2250-2258.
- Clerc, H., Calando, J., Paillard, P., Gros, R., Hircq, B., 1988. The experimental determination of the
 oxidation rate of tritium in the atmosphere, Radiation protection practice.
- Cline, J.F., 1953. Absorption and metabolism of tritium oxide and tritium gas by bean plants. Plant
 Physiology, 28: 717-723.
- 494 CNSC, 2009. Rejet de tritium et conséquences sur les doses au Canada en 2006. INFO-0793. 48pp.
- 495 Connan O, Hebert D., Solier L., Maro D., Pellerin G., Voiseux C., Lamotte M., Laguionie P., 2017.
- 496 Atmospheric tritium concentrations under influence of AREVA NC La Hague reprocessing plant
 497 (France) and background levels. Journal of Environmental Radioactivity, 177, 184-193.
- 498 Conrad R., Seiler W., 1981. Decomposition of atmospheric hydrogen by soil microorganisms and soil
 499 enzymes. Soil. Biol. Biochem. 13, 43-49.
- Conrad, R., Weber, M., Seiler, W., 1983. Kinetics and electron transport of soil hydrogenases
 catalyzing the oxidation of atmospheric hydrogen. Soil Biology and Biochemistry 15, 167-173.
- 502 Cortes, P., 2015. Rejets liquides et gazeux de l'installation experimentale ITER en fonctionnement de
 503 routine. SFRP, Paris, 5-/6 Novembre 2015.
- 504 Dunstall, T., Ogram, G.L., Spencer, F., 1985. Elemental tritium deposition and conversion in the 505 terrestrial environment. Fusion Science and Technology 8, 2551-2556.
- 506 Ehhalt, D.H., Rohrer, F., 2009. The tropospheric cycle of H2 a critical review. Tellus 61B, 50-535.
- 507 Golubev, A., Glagolev, M., & Misatyuk, C., 2001. Studies of HTO transport and oxidation in 508 unsaturated soil. ECORAD, Aix-en-Provance, France, September, 3-7.
- Hupp, J., Weaver, M., 1983. The frequency factor for outer-sphere electrochemical reactions. Journal
 of Electroanalytical Chemistry and Interfacial Electrochemistry, 152(1-2), 1-14.
- 511 Ichimasa M., Ichimasa Y., Akita Y., 1989. In vivo fixation of atmospheric tritium gas in pine and
 512 Zelkova trees and their surroundings. J. Radiat. Res. 30, 330-337.

- Ichimasa Y., Ichimasa M., Jiang H., Katsuno K., Noguchi H., Yokoyama S., Amano H., Atarashi M.,
 1995. In vitro determination of HT oxidation activity and tritium concentration in soil and vegetation
 during the chronic HT release experiment at Chalk river. Fusion Technol. 28, 877-882.
- IRSN, 2009. Le tritium dans l'environnement : synthèse critique des connaissances et perspectives de
 recherches. Rapport IRSN/DEI, 105 pp.
- IRSN, 2017. Actualisation des connaissances acquises sur le tritium dans l'environnement « 7 ans
 après le livre blanc de l'ASN : que sait-on de plus et que reste-il à faire ? », Rapport PRPENV/SERIS/2017-004.
- 521 IRSN, 2018. Bilan de l'état radiologique de l'environnement français de 2015 à 2017., 354 pp.
- Kim, S.B., Stuart, M., Bredlaw, M., Festarini, A., Beaton, D., 2014. HT to HTO conversion and field
 experiments near Darlington Nuclear Power Generating Station (DNPGS) site. J. Environ. Radioact.
 132, 73-80.
- Komuro, M., Ichimasa, Y., Ichimasa, M., 2002. HT oxidation in soils in Ibaraki and isolation,
 identification of HT oxidizing soil bacteria. Fusion science and technology 41, 422-426.
- 527 Le Dizès, S., Aulagnier, C., Maro, D., Rozet, M., Vermorel, F., Hébert, D., Voiseux, C., Solier, L.,
- 528 Godinot, C., Fievet, B., Laguionie P., Connan O., Cazimajou O., Morillon M., 2017. The VATO
- 529 project: Development and validation of a dynamic transfer model of tritium in grassland ecosystem.530 Journal of Environmental Radioactivity 171, 83-92.
- Libert, M., Sellier, R., Marty, V., Camaro, S., 2000. Development of hydrogen oxidizing bacteria
 using hydrogen from radiolysis or metal corrosion.
- Maro D., Vermorel F., Rozet M., Aulagnier C., Hebert D., Le Dizes S., Voiseux C., Solier L.,
 Cossonnet C., Godinot C., Fievet B., Laguionie P., Connan O., Cazimajou O., Morillon M., Lamotte
 M., 2017. An original methodology to study the transfer of tritium as HT and HTO in grassland
 ecosystem. Journal of Environmental Radioactivity, 167, 235-248.
- Masarik, J., Beer, J., 2009. An updated simulation of particle fluxes and cosmogenic nuclide
 production in the Earth's atmosphere. Journal of Geophysical Research: Atmospheres, 114(D11).
- McFarlane, J.C., R.D. Rodgers and D.V. Bradley Jr. 1978. Environmental tritium oxidation in surface
 soil. Environ. Sci. Technol., 12: 590-593.
- 541 Okada S., Momoshima N., 1993. Overview of tritum : characteristics, sources, and problems. Health
 542 Physics, 6, 595-609.
- 543 Oms P.E., Bailly Du Bois P., Dumas F., Lazure P., Morillon M., Voiseux C., Le Corre C., Cossonet
 544 C., Solier L., Morin P., 2019. Inventory and distribution of tritium in the oceans in 2016. Science of
- 545 the Total Environment, 656, 1289-1303.
- Ota, M., Yamazawa, H., Moriizumi, J., Iida, T., 2007. Measurement and modeling of oxidation rate of
 hydrogen isotopic gases by soil. Journal of environmental radioactivity 97, 103-115.
- Peterson, S. R., Davis, P. A., 2002. Tritium doses from chronic atmospheric releases: a new approach
 proposed for regulatory compliance. Health Physics, 82(2), 213-225.
- Piché-Choquette, S., Tremblay, J., Tringe, S.G., Constant, P., 2016. H2-saturation of high affinity H2oxidizing bacteria alters the ecological niche of soil microorganisms unevenly among taxonomic
 groups. PeerJ 4, e1782.
- Popelier, F., Liessens, J., Verstraete, W., 1985. Soil H2-uptake in relation to soil properties and
 rhizobial H2-production. Plant and soil 85, 85-96.

- Quinlan, A. V., 1980. The thermal sensitivity of Michaelis-Menten kinetics as a function of substrate
 concentration. Journal of the Franklin Institute, 310 (6), 325-342.
- Renard, H., 2017. Modélisation à pas de temps horaire des transferts de tritium au sein d'un
 écosystèlme prairial (in French), Thesis, Université d'Aix-Marseille.
- Riedo M., Grub, A., Rosset, M., Fuhrer, J., 1998. A pasture simulation model for dry matter
 production and fluxes of carbon, nitrogen, water and energy. Ecol. Model., 105, pp. 141-183
- Schuler, S., Conrad, R., 1991. Soils contain two different activities for oxidation of hydrogen. FEMS
 Microbiol. Ecol. 73, 77-84.
- Spencer F.S., Dunstall T.G., 1986. Molecular tritium conversion in vegetation, litter and soil. Radiat.
 Prot. Dosimetry 16, 89-93.
- Spencer F.S., Vereecken-Sheehan L., 1994. HTO Concentration Relationships Between Air, Soil and
 Vegetation and Seasonal Dependence of HT Deposition to Soil. Ontario Hydro Technologies, Report
 No. A-NBP-94-36-K.
- Sweet, C.W., Murphy, C.E., 1981. Oxidation of molecular tritium by intact soils. Environmental
 Science & Technology 15, 1485-1487.
- 570 Triebwasser-Freese, D. J., Tharayil, N., Preston, C. M., Gerard, P. G.,2015. Catalytic kinetics and 571 activation energy of soil peroxidases across ecosystems of differing lignin 572 chemistries. Biogeochemistry, 124(1), 113-129.
- 573 UNSCEAR, 2016. Sources, effects and risks of Ionizing Radiation. In Annex C, biological effects of
 574 selected internal emitters, tritium, UNSCEAR United Nations Scientific Committee on the Effects of
 575 Atomic Radiation, 122 pp.
- 576 UNSCEAR, 2000. Sources and effects of ionizing radiation, Vol 1 Sources: United Nations Scientific
 577 Committee on the effects of Atomic Radiation. UNSCEAR United Nations Scientific Committee on
 578 the Effects of Atomic Radiation, 659 pp.
- 579USDA(U.S.DepartmentofAgriculture),web.580https://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/survey/?cid=nrcs142p2_054167.web.
- Weilandt, D., Hatzimanikatis, V., 2019. Particle-based simulation reveals macromolecular crowding
 effects on the Michaelis-Menten mechanism. Biophysical journal, 117(2), 355-368.
- 583

Figure 1 : Schematic representation of the experimental oxidation device. a: HT air canister; b: upstream bubblers (trapping of HTO traces); c: core soil samples (5 cm); d: clip; e: ⁸⁵Kr detector (LB123); f: reading acquisition station (⁸⁵Kr , temperature, water content); g: downstream bubbler.



Figure 2 : Expression of frequency factor A as a function of soil porosity. White circles are data from this study. Grey squares are data from the literature.



Figure 3 : Modelling of annual production of HTO by bacterial oxidation of 1 Bq.m⁻³ HT in air, with average annual soil water content and temperature for differents type of soil (C= Clay, SC= Sandy Clay, CL= Clay Loam, SiCL= Silt Clay Loam, SiC= Silt Clay, SCL= Sandy Clay Loam, L= Loam, SL= Sandy Loam, SiL= Silty Loam, Si= Silty, LS= Loamy Sand, S=Sand).



Figure 4 : Evolution of HTO in soil (Bq.L⁻¹) for 2013-2016 period, calculate from TOCATTA- χ model, taken into account only atmospheric measurements of HT in air (blue line) and taken into account all sources of tritium (HTO and HT in air, HTO in rainwater, black line) for site 2 km from Orano La Hague reprocessing plant.



Figure 5 : Exchange of HTO between soil and atmosphere (Bq.m⁻².d⁻¹) for 2013-2016 period, calculate from TOCATTA- χ model, with only atmospheric measurements of HT in air for site 2 km from Orano La Hague reprocessing plant. Positive values indicate flux of HTO from soil to atmosphere, and negative values indicates flux of HTO from atmosphere to soil.



Table 1 : Description of the parameters used to calculate the oxidation rate of HT in HTO in so	ils.

Symbol	Meaning	Units
[HT]	HT concentration in soil air	mol.m ⁻³
Α	frequency factor	ppm.mol.m ⁻³
Ε	reaction activation energy	J.mol ⁻¹
$f_T(T)$	soil temperature-dependant weighting factor	-
$f_W(\theta)$	soil water content-dependant weighting factor	-
$f_Z(Z)$	soil depth-dependant weighting factor	-
K_M	Michaelis-Menten parameter	ppm.mol.m ⁻³
R	gas constant	J.mol ⁻¹ .K ⁻¹
Т	absolute temperature	К
V_{max}	initial maximal HT oxydation velocity	mol.kg ⁻¹ dry soil.s ⁻¹
V _{oxi}	actual HT oxydation velocity	mol.kg ⁻¹ dry soil.s ⁻¹
V_{ref}	reference HT oxydation velocity	mol.kg ⁻¹ dry soil.s ⁻¹

Experiment	Sampling	Latitude/longitude	Location Name	Clay content	Total loam content	Total sand content	Type of soil
	date	(DD)		(kg _{sands} .kg _{dry soil} -1)	(kg _{sands} .kg _{dry soil} -1)	(kg _{sands} .kg _{dry soil} -1)	
1	25/05/2016	49.618°N/-1.351°W	Le Vast (France)	0.183	0.476	0.341	Loam
2	29/06/2016	49.646°N/-1.644°W	Equeurdreville (France)	0.090	0.399	0.511	Loam
3	04/04/2016	48.781°N/-0.678°W	Fresnes (France)	0.189	0.567	0.244	Silt loam
4	15/11/2018	49.618°N/-1.351°W	Le Vast (France)	0.170	0.472	0.358	Loam
5	19/11/2019	49.618°N/-1.351°W	Le Vast (France)	0.169	0.501	0.330	Loam

1 Table 2: Characteristics of the core sampling of the soils used for the oxidation laboratory experiments.

Experiment	Sample soil surface	Duration	Massique soil water content	Average Air temperature	Sample height	Sample depth from surface
-	-	hour	kg.kg⁻¹	°C	cm	cm
1	Grass	264.0	0.176	20.3	5	0
2	Grass	576.0	0.188	20.9	5	0
3	Grass	305.4	0.265	19.6	5	0
4	Bare soil	504.0	0.133	22.0	5	4
5	Bare soil	1224.0	0.168	17.0	5	4

Table 3: Experimental characteristics measured during the laboratory testing of HT bacterial oxidation in the first centimeters from natural soil.

Soil type	Clay content	Silt content	Sand content	t Soil porosity Frequency fac	
-	%	%	%	-	HT ppm.mol.m ⁻³
Clay	60	20	20	0.416	1.94x10 ⁶
Silty Clay	45	50	5	0.442	2.19x10 ⁵
Sandy Clay	40	5	55	0.398	6.75x10 ⁶
Clay Loam	35	30	35	0.421	1.14x10 ⁶
Silty Clay Loam	35	55	10	0.446	4.23x10 ⁵
Sandy Clay Loam	30	10	60	0.401	5.81x10 ⁶
Loam	20	40	40	0.428	3.92x10 ⁵
Silt Loam	15	60	25	0.447	5.56x10 ⁵
Silt	5	90	5	0.475	6.68x10 ⁶
Sandy Loam	10	25	65	0.412	2.89x10 ⁶
Loamy Sand	5	10	85	0.396	7.57x10 ⁶
Sand	4	4	92	0.389	1.00x10 ⁷

Table 4: Granulometric characteristics, porosity (according to Eq 6) and frequency factor A (according to Eq 5) of the different soils.

Table 5: Estimation of soil porosity from apparent density and theoretical particle density for soilsresulting from HT bacterial oxidation experiments in this study or present in the literature.

Source	Bulk density	Theorical particule density	Soil porosity
-	kg.m⁻³	kg.m⁻³	-
Experiment 1	1.52x10 ³	2.69x10 ³	0.44
Experiment 2	1.53x10 ³	2.67x10 ³	0.43
Experiment 3	1.49x10 ³	2.69x10 ³	0.44
Experiment 4	1.52x10 ³	2.69x10 ³	0.43
Experiment 5	1.51x10 ³	2.69x10 ³	0.44
Conrad <i>et al.,</i> 1982	1.44x10 ³	2.69x10 ³	0.46
Conrad <i>et al.,</i> 1982	1.44x10 ³	2.69x10 ³	0.46
Conrad <i>et al.,</i> 1982	1.61x10 ³	2.66x10 ³	0.39
Conrad <i>et al.,</i> 1982	1.61x10 ³	2.66x10 ³	0.39
Dong et Layzell 2001	1.62x10 ³	2.66x10 ³	0.39
Ota <i>et al.,</i> 2007	1.61x10 ³	2.66x10 ³	0.39
Piché-Choquette <i>et al.</i> , 2016	1.57x10 ³	2.67x10 ³	0.41

Experiment	Air HT activity	Initial HTO activity	Final HTO activity	Rate of HTO	
	in the bag	in soil water	in soil water	production in soil water	
-	Bq.m⁻³	Bq.L ⁻¹	Bq.L⁻¹	Bq.L ⁻¹ .h ⁻¹	
1	1.1±0.1	<1	8.4±0.9	3.2x10 ⁻² ±3.4x10 ⁻³	
2	1.1±0.1	<1	6.6±1.4	1.2x10 ⁻² ±2.4x10 ⁻³	
3	5.8±0.3	<1	7.0±0.9	2.3x10 ⁻² ±3.0x10 ⁻³	
4	23.0±1.4	<1	32.2±1.5	6.4x10 ⁻² ±3.0x10 ⁻³	
5	7.8±0.7	<1	10.3±1.2	8.4x10 ⁻³ ±9.8x10 ⁻⁴	

Table 6: Tritium activity measured during the laboratory experiments of HT bacterial oxidation.

Table 7: Soil particle size and A-frequency factor from HT bacterial oxidation experiments in soil conducted in this study or from the literature.

Source	Sand content	Loam content	Clay content	Soil type	Frequency factor A
	%	%	%	-	HT ppm.mol.m ⁻³
Experiment 1	34	48	18	Loam	6.97x10 ⁴
Experiment 2	51	40	9	Loam	1.85x10 ⁵
Experiment 3	24	57	19	Silt Loam	3.06x10 ⁵
Experiment 4	36	47	17	Silt Loam	7.89x10 ⁴
Experiment 5	33	50	17	Silt Loam	1.99x10 ⁵
Conrad <i>et al.,</i> 1982	5 ^b	77 ^b	18 ^b	Silt Loam	2.84x10 ^{6a}
Conrad <i>et al.,</i> 1982	5 ^b	77 ^b	18 ^b	Silt Loam	4.12x10 ^{6a}
Conrad <i>et al.,</i> 1982	88 ^b	9 ^b	3 ^b	Loamy Sand	8.22x10 ^{6a}
Conrad <i>et al.,</i> 1982	88 ^b	9 ^b	3 ^b	Loamy Sand	6.86x10 ^{6a}
Dong et Layzell 2001	90 ^e	7 ^e	3 ^e	Sand	9.92x10 ^{6a}
Ota <i>et al.,</i> 2007	88 ^c	9 ^c	3 ^c	Sand	7.90x10 ⁶
Piché-Choquette et al., 2016	64 ^d	26 ^d	10 ^d	Loamy Sand	3.21x10 ^{6a}

^aTemperature is assumed to be 25°C if not indicated in the literature; ^bSeiler *et al.*, 1977; ^cSince the soil in this study is physically apparent to that described by Conrad et Seiler (1982), this soil is considered to have the same particule size composition; ^dAverage value for this particule size range; ^eThe type of land is issued by Info-sols.ca and the location of the soil sample indicated. The fraction of silica added to the mixture (1/3) is assimilated to pure sand particules.

Soil Type	Bulk density		Soil	нто	
-	Kg.m⁻³				
Season		Spring ^a	Summer ^b	Autumn ^c	Winter ^d
Clay (C)	1621	0.73	0.65	0.73	0.68
Silty clay (SiC)	1530	6.23	6.26	6.16	5.86
Sandy clay (SC)	1646	0.20	0.16	0.20	0.14
Clay loam (CL)	1576	1.15	1.00	1.09	0.62
Silty clay loam (SiCL)	1510	3.19	3.23	3.15	2.99
Sandy clay loam (SCL)	1626	0.24	0.24	0.23	0.18
Loam (L)	1539	3.51	3.58	3.46	3.29
Silt loam (SiL)	1483	2.39	2.46	2.36	2.25
Silt (Si)	1396	0.19	0.19	0.18	0.18
Sandy loam (SL)	1572	0.49	0.49	0.48	0.45
Loamy sand (LS)	1608	0.19	0.19	0.19	0.18
Sand (S)	1623	0.15	0.15	0.14	0.14

Table 8 : Estimated production of soil HTO (Bq.m ⁻²) for different soil types under a La Hague climat
type following the 24-hour presence of a HT plume with a concentration of 1 Bq.m ⁻³ .

^atemperature and average volumic water content of soil: 12.6°C and 21.5%; ^btemperature and average volumic water content of soil: 16.6°C and 15.2%; ^ctemperature and average volumic water content of soil: 11.3°C and 24.5%; ^dtemperature and average volumic water content of soil: 7.5°C and 28.8%. The data mentionned ^a, ^b, ^c and ^d come from hourly measurements over the period 2013 to 2019 (Maro *et al.*, 2017).