

Effectiveness of a novel polyaniline@Fe-ZSM-5 hybrid composite for Orange G dye removal from aqueous media: Experimental study and advanced statistical physics insights

Abdelaziz Imgharn, Lahoucine Anchoum, Abdelghani Hsini, Yassine Naciri, Mohamed Laabd, Mohamed Mobarak, Nouh Aarab, Asmae Bouziani, Sabine Szunerits, Rabah Boukherroub, et al.

▶ To cite this version:

Abdelaziz Imgharn, Lahoucine Anchoum, Abdelghani Hsini, Yassine Naciri, Mohamed Laabd, et al.. Effectiveness of a novel polyaniline@Fe-ZSM-5 hybrid composite for Orange G dye removal from aqueous media: Experimental study and advanced statistical physics insights. Chemosphere, 2022, 295, pp.133786. 10.1016/j.chemosphere.2022.133786. hal-03561674

HAL Id: hal-03561674 https://hal.science/hal-03561674v1

Submitted on 7 Nov 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Effectiveness of a novel polyaniline@Fe-ZSM-5 hybrid composite for Orange G dye removal from aqueous media: Experimental study and advanced statistical physics insights

Abdelaziz Imgharn, Lahoucine Anchoum, Abdelghani Hsini, Yassine Naciri, Mohamed Laabd, Mohamed Mobarak, Nouh Aarab, Asmae Bouziani, Sabine Szunerits, Rabah Boukherroub, Rajae Lakhmiri, Abdallah Albourine

PII: S0045-6535(22)00279-X

DOI: https://doi.org/10.1016/j.chemosphere.2022.133786

Reference: CHEM 133786

To appear in: ECSN

Received Date: 25 September 2021

Revised Date: 5 January 2022

Accepted Date: 27 January 2022

Please cite this article as: Imgharn, A., Anchoum, L., Hsini, A., Naciri, Y., Laabd, M., Mobarak, M., Aarab, N., Bouziani, A., Szunerits, S., Boukherroub, R., Lakhmiri, R., Albourine, A., Effectiveness of a novel polyaniline@Fe-ZSM-5 hybrid composite for Orange G dye removal from aqueous media: Experimental study and advanced statistical physics insights, *Chemosphere* (2022), doi: https://doi.org/10.1016/j.chemosphere.2022.133786.

This is a PDF file of an article that has undergone enhancements after acceptance, such as the addition of a cover page and metadata, and formatting for readability, but it is not yet the definitive version of record. This version will undergo additional copyediting, typesetting and review before it is published in its final form, but we are providing this version to give early visibility of the article. Please note that, during the production process, errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

© 2022 Published by Elsevier Ltd.



539 120012


Chemosphere

Author Contributions Statement

Abdelaziz Imgharn: Formal analysis, Data curation, Writing-original draft. **Lahoucine Anchoum:** Investigation. **Abdelghani Hsini:** Methology, Formal analysis, Data curation, Writing-review & editing. **Yassine Naciri:** Methodology, Investigation, Writing-review & editing. **Mohamed Laabd:** Validation, Writing-review & editing. **Mohamed Mobarak:** Formal analysis, Data curation. **Nouh Aarab:** Investigation. **Asmae Bouziani:** Writing-review & editing. **Sabine Szunerits:** Investigation, Methodology. **Rabah Boukherroub:** Conceptualization, Validation, Writing-review & editing. **Rajae Lakhmiri:** revision, editing. **Abdallah Albourine:** Conceptualization, Validation, revision, editing, Supervision, Project administration.

Journal Prert

Graphical abstract



ourn	121	110		110		
			P -			

1	Effectiveness of a novel polyaniline@Fe-ZSM-5 hybrid composite for Orange
2	G dye removal from aqueous media: Experimental study and advanced
3	statistical physics insights
4	Abdelaziz Imgharnª, *, Lahoucine Anchoumª, Abdelghani Hsiniª, Yassine Naciriª , Mohamed
5	Laabdª, Mohamed Mobarak ^b , Nouh Aarabª, Asmae Bouziani ^c , Sabine Szunerits ^d , Rabah
6	Boukherroub ^d , Rajae Lakhmiri ^e , Abdallah Albourine ^{a,*}
7	^a Laboratory of Materials and Environment, Faculty of Sciences, Ibn Zohr University, Agadir, Morocco.
8	^b Physics Department, Faculty of Science, Beni-Suef University, Beni-Suef 62511, Egypt.
9	^c Chemical Engineering Department, Middle East Technical University, Ankara, Turkey.
10	d Univ. Lille, CNRS, Centrale Lille, Univ. Polytechnique Hauts-de-France, UMR 8520 - IEMN, Lille F-
11	59000, France.
12	^e Laboratory of Chemical Engineering and Valorization Resources, Faculty of Sciences and Techniques,
13	Abdelmalek Essaadi University, Tangier, Morocco.
14	* Corresponding authors:
15	E-mail address: <u>abdelaziz.imgharn@edu.uiz.ac.ma (</u> A. Imgharn)
16	E-mail address: <u>albourine@yahoo.fr (</u> A. Albourine)
17	
18	
19	
20	
21	
22	

23 Abstract

A polyaniline@Fe-ZSM-5 composite was synthesized via an in situ interfacial 24 polymerization procedure. The morphology, crystallinity, and structural features of the 25 as-developed PANI@Fe-ZSM-5 composite were assessed using scanning electron 26 microscopy - energy dispersive spectroscopy (SEM-EDS), X-ray diffraction (XRD), 27 Fourier-transform infrared (FTIR) spectroscopy, and X-ray photoelectron spectroscopy 28 (XPS). The composite was efficiently employed for the first time as an adsorbent to adsorb 29 Orange G (OG) dvestuff from water. The OG dve adsorption performance was investigated 30 as a function of several operating conditions. The kinetic study demonstrated that a 31 pseudo-second-order model was appropriate to anticipate the OG adsorption process. The 32 maximum adsorption capacity was found to be 217 mg/g. The adsorption equilibrium data 33 at different temperatures were calculated *via* advanced statistical physics formalism. The 34 entropy function indicated that the disorder of OG molecules improved at low 35 concentrations and lessened at high concentrations. The free enthalpy and internal energy 36 functions suggested that the OG adsorption was a spontaneous process and physisorption 37 in nature. Regeneration investigation showed that the PANI@Fe-ZSM-5 could be 38 effectively reused up to five cycles. The main results of this work provided a deep insight 39 40 on the experimental study supported by advanced statistical physics prediction for the adsorption of Orange G dye onto the novel polyaniline@Fe-ZSM-5 hybrid composite. 41 42 Additionally, the experimental and advanced statistical physics findings stated in this study may arouse research interest in the field of wastewater treatment. 43

Keywords: Polyaniline; Fe-ZSM-5; Composite; Dye removal; Advanced statistical
physics; Regeneration.

46 **1. Introduction**

Many industries use synthetic dyes to color their final product, including food, drugs, 47 cosmetics, paper, leather, plastics, and textile (Abbasi, 2017). Dyes often exhibit 48 persistence to biodegradation and significant toxic, carcinogenic, and mutagenic effects 49 on aquatic organisms and humans, which has become a severe environmental problem in 50 the world (Belbachir and Makhoukhi, 2017; Gottlieb et al., 2003). Therefore, the discharge 51 of dyes in wastewater, even in a small amount, is unpleasant and should be removed 52 before they enter the environment. In this context, several treatment processes, including 53 coagulation-flocculation (Renault et al., 2009), photocatalysis (Akhsassi et al., 2021; 54 Fahoul et al., 2022; Mimouni et al., 2021; Naciri et al., 2021), ion exchange (Hassan and 55 Carr, 2018), membrane filtration, and adsorption (Amjlef et al., 2021; Imgharn et al., 56 2021; Njoya et al., 2020) have been implemented to clean up colored effluents. Adsorption 57 is considered an effective, green, and low-cost approach used for dye elimination from 58 aqueous solutions. Therefore, the last decades have witnessed a huge interest in the 59 development of efficient adsorbent materials. The performance of adsorbents depends on 60 their physicochemical characteristics like porosity, particle size, surface functional groups, 61 62 and chemical stability (Benjelloun et al., 2021; Laabd et al., 2021).

π-Conjugated polymers including polyaniline (PANI), polythiophene (PTh), and
polypyrrole (PPy) have been widely employed in many fields like gas sensors, tissue
engineering, photovoltaic cells, batteries, and wastewater purification (Liao et al., 2019).
PANI is considered as the most promising conductive polymer among these polymers due
to its particular characteristics: good redox reversibility, low-cost, environmental
friendliness, excellent stability, good conductivity, and easy synthesis (Laabd et al., 2017;

Naciri et al., 2022). In addition, the uptake of organic dyes and heavy metal ions by PANI 69 is high. The ion exchange property, porous structure as well as the presence of a large 70 amount of protonated amine and imine groups on the surface of PANI are the reasons for 71 its high adsorption capacity. However, the small particle size and poor physical 72 (mechanical and thermal) properties of PANI seriously hinder its use in large scale 73 74 wastewater purification systems (Sahu et al., 2019). In order to counterbalance these 75 limitations, PANI-based composites using different reinforcing substrates like mineral clays (Zhou et al., 2017), natural lignocellulosic wastes (Kumar et al., 2008), activated 76 carbon (Ansari et al., 2017) and zeolites (Abdellaoui et al., 2020; Shyaa et al., 2015) have 77 been developed. 78

Zeolite has a tridimensional form of crystalline aluminosilicate, an open anionic 79 framework consisting of tetrahedral oxygen-sharing TO₄, in which AlO₄ and SiO₄ are 80 covalently linked to each other (Ba Mohammed et al., 2020; Shyaa et al., 2015). Besides, 81 the zeolitic materials are microporous with a uniform pore distribution. As evidenced from 82 the literature, the properties of zeolites can be enhanced by integrating different metals 83 into their matrices. Incorporation of iron into adsorbents is highly preferred due to its 84 economic, eco-friendly and semiconducting properties (Saifuddin et al., 2019). Several 85 works focused on the optimization of the adsorption parameters and discussed the 86 physical aspects of the process. However, only a restricted number of studies are available 87 which decipher the main role of the active metal ions of the zeolite structure in the 88 adsorption phenomenon. 89

Herein, we synthesized PANI@Fe-ZSM-5 zeolite hybrid composite through an oxidative
polymerization route and characterized by SEM coupled with EDS, XRD, FTIR and XPS

analysis. The initial Orange G (OG) concentration, dosage of adsorbent, contact time, 92 initial pH value of the solution and temperature were optimized to evaluate the 93 effectiveness of the synthesized PANI@Fe-ZSM-5 composite for OG removal. The 94 modeling of the equilibrium isotherms and adsorption kinetics of the OG dye on the 95 composite was also evaluated. Furthermore, the theoretical predication of the OG 96 97 molecules' binding on the surface of PANI@Fe-ZSM-5 was calculated using advanced 98 statistical physics applied to the adsorption equilibrium. In addition, the effect of coexisting ions was assessed. Finally, the regeneration of PANI@Fe-ZSM-5 composite was 99 performed to evaluate its reusability for OG dyestuff removal. 100

101 2. Experimental

-

102 **2.1. Chemicals**

Aniline monomer (Sigma-Aldrich) was used after distillation. Sodium persulfate (Na₂S₂O₈), acetone, ethanol, tetrapropylammonium bromide (C₁₂H₂₈NBr, 98 %), iron (III) nitrate pentahydrate (Fe (NO₃)₃·5H₂O, \geq 99.95 %), sulfuric acid (H₂SO₄, \geq 95 %), sodium metasilicate (Na₂SiO₃, \geq 98 %), hydrochloric acid (HCl, 37 %), sodium hydroxide (NaOH, \geq 97 %), sodium chloride (NaCl, \geq 99 %), and orange G (OG) dye were of analytical grade and purchased from Sigma-Aldrich. The dye solution was prepared by dissolving the accurately weighted dye in distilled water.

110

2.2. Preparation of Fe-ZSM-5 zeolite

111 The Fe-ZSM-5 zeolite synthesis was conducted using the procedure reported by Ba 112 Mohammed et al. (Ba Mohammed et al., 2020). Briefly, 10 g of sodium metasilicate as a 113 silicon precursor were dissolved in 25 mL of distilled water, and then 2 g of 114 tetrapropylammonium bromide were added to the suspension under magnetic stirring

until the solution became uniform with a pH value of 10. The obtained solution was called 115 first solution. A second solution was produced by dissolving 1 g of ferric nitrate 116 pentahydrate in 10 mL of distilled water; then, the resulting solution was acidified using 117 2 ml of H₂SO₄ (0.01 M). This solution was poured dropwise into the first one and kept 118 under stirring for 2 h. The formed gel was placed in a Teflon autoclave at 180 °C for 48 h. 119 120 The resulting suspension was filtered and washed several times with acetone and distilled 121 water. Finally, the as-prepared material was kept at 100 °C overnight to dry then calcined at 550 °C for 6 h. 122

123

2.3. Elaboration of PANI@Fe-ZSM-5

The PANI@Fe-ZSM-5 hybrid composite was prepared via an *in situ* oxidative 124 polymerization of aniline with Fe-ZSM-5 particles in an acidic medium using Na₂S₂O₈ as 125 oxidant, according to the procedure in (Hsini et al., 2021b): 1g of Fe-ZSM-5 was dispersed 126 in 100 mL of a hydrochloric acid solution (1M) under stirring for 6 h. Then, 0.5 mL of 127 aniline was added to the suspension under stirring for 3 h. A 50 mL solution of HCl (1 M) 128 containing sodium persulfate (with a 0.5 monomer/oxidant molar ratio) was added 129 dropwise into the mixture under agitation. A green suspension was obtained after 12 h, 130 indicating the formation of doped PANI on the Fe-ZSM-5 particles. The resulting 131 precipitate was filtered and washed with distilled water and acetone. The PANI@Fe-ZSM-132 5 composite was dried at 70 °C overnight. 133

134

2.4. Characterization of the adsorbent

To check out the hybrid composite crystal structure, X-ray powder diffraction (XRD) analyses were carried out with a BRUKER D8 ADVANCE TWIN diffractometer. The Fe-ZSM-5 surface morphology before and after polymerization was systematically

characterized by scanning electron microscopy (SEM) coupled with energy dispersive X-138 ray spectrometry (EDS) analysis (SEM, JEOL, JSM-IT200). X-ray photoelectron 139 spectroscopy (XPS) analysis of the as-prepared PANI@Fe-ZSM5 composite was acquired 140 using an ESCALAB 220 XL spectrometer equipped with a monochromatic Al Ka X-ray 141 radiation source at 1486.6 eV. The binding energies were calibrated to the C1s peak at 142 143 284.6 eV. Fourier-transform infrared (FTIR) spectra of the obtained materials were 144 acquired using KBr pellets using FTIR spectroscopy (ALPHA-Bruker Optics, Germany) in a wavenumber ranging from 400 to 4000 cm⁻¹. 145

The zero charge point (PZC) of the PANI@Fe-ZSM-5 composite was determined via potentiometric titration method reported by Fiol and Villaescusa (Fiol and Villaescusa, 2009). In short, 0.025 g of PANI@Fe-ZSM-5 was added to 50 mL of KNO₃ (0.03 M) solution and the pH of the solution was adjusted from 2 to 12 by adding HCl (0.1 M) or NaOH (0.1 M) aqueous solutions. The mixtures were stirred for 24 h at ambient temperature. The final pH_f of each solution was assessed. Then, the PZC was identified as pH_i when Δ pH is zero.

153 **2.5.** Adsorption experiments and regeneration

The OG dye adsorption onto PANI@Fe-ZSM-5 hybrid composite was conducted in a batch reactor under various operational conditions. To evaluate the effect of adsorbent dose, various amounts of PANI@Fe-ZSM-5 composite (0.2-2 g/L) were introduced into 50 mL of OG dye solution at 20 mg/L initial concentration for 180 min at pH 6.0 and 25 °C. The influence of pH on the OG dye removal efficiency was studied by changing the solution pH from 2 to 12 with an adsorbent dose of 0.5 g/L. Under the same experimental conditions, the influence of initial concentration of OG dye (from 20 to 500 mg/L), contact time and

temperature was also assessed. After adsorption, the adsorbent was removed from adsorbate solution by filtration on Millipore filters (0.45 μ m). The equilibrium concentration of OG dye was quantified by UV2300 spectrophotometer at 476 nm.

164 The absorbed percentage R(%) and the adsorption capacity $Q_e(mg/g)$ were calculated by 165 the following relations (Ait Haki et al., 2021; Brini et al., 2021b):

166
$$R\% = \frac{(C_0 - C_e)}{C_0} \times 100 \quad (1)$$

167
$$Q_e = \frac{(C_0 - C_e).V}{m}$$
(2)

Where $C_0 (mg/L)$ is the initial OG concentration, $C_e (mg/L)$ is the OG concentration at equilibrium, m (g) is the mass of the PANI@Fe-ZSM-5 composite, and V (L) is the volume of the solution.

In order to bring up the adsorption process more economically reliable and eco-friendly, 171 172 the regeneration of PANI@Fe-ZSM-5 composite after the adsorption experiment is a very important aspect. For desorption/adsorption study, 0.3 g of PANI@Fe-ZSM-5 was 173 introduced in 0.6 L of 20 mg/L OG dye solution. After 180 min of sorption, desorption 174 175 experiment was performed using 0.5 M NaOH as eluent solution for 6 h. After that, the regenerated PANI@Fe-ZSM-5 composite was washed with distilled water, and then 176 redoped with 1 M HCl solution. The fresh PANI@Fe-ZSM-5 composite was used for a 177 subsequent OG adsorption cycle. In this work, five regeneration cycles were carried out. 178

179 2.6. Theoretical background

The statistical physics theory is an emerging effective approach to deeply illuminate the
adsorption mechanisms at the liquid-solid interface (Mobarak et al., 2019b, 2019a;

Mohamed et al., 2020). The adsorption performance of OG dye on the PANI@Fe-ZSM-5 hybrid composite was examined by applying five statistical physics models to the experimental equilibrium data.

First model (M1): Monolayer model with similar receptor sites. This model assumes
 that the adsorption process occurs by the formation of a monolayer on the adsorbent
 surface with one type of adsorption sites (Mobarak et al., 2019b, 2019a). The
 analytical expression of the M1 model is given by Eq. (3):

189
$$Q_e = nN_o = \frac{nN_M}{1 + \left(\frac{C_{1/2}}{C_e}\right)^n} = \frac{Q_{sat}}{1 + \left(\frac{C_{1/2}}{C_e}\right)^n}$$
(3)

where $Q_e (mg/g)$ and $C_e (mg/L)$ denote the equilibrium adsorbed amount and equilibrium concentration, respectively; n represents the number of adsorbed molecules per binding site; N_M (mg/g) is the active sites density; Q_{sat} (mg/g) is the adsorption capacity at saturation; C_{1/2} (mg/L) is the adsorbate concentration at half-saturation.

Second model (M2): Double-layer model with similar receptor sites. This model is
 appropriate to describe the double-layer adsorption process over the adsorbent surface
 with identical binding sites. The formalism of the M2 model is presented by Eq. (4):

197
$$Q_e = nN_M \frac{\left(\frac{C_e}{C_{1/2}}\right)^n + 2\left(\frac{C_e}{C_{1/2}}\right)^{2n}}{1 + \left(\frac{C_e}{C_{1/2}}\right)^n + \left(\frac{C_e}{C_{1/2}}\right)^{2n}}$$
(4)

Third model (M3): Monolayer model with two different energies. This model is
 established on the hypothesis that the adsorption process is a monolayer coverage over
 two kinds of adsorbent active sites (with different energies) (Mobarak et al., 2019b,
 201 2019a).

$$Q_e = \frac{n_1 N_{1M}}{1 + (C_1 / C_e)^{n_1}} + \frac{n_2 N_{2M}}{1 + (C_2 / C_e)^{n_2}}$$
(5)

where C_1 and C_2 (mg/L) are the half-saturation concentrations for the first and the second adsorption sites, respectively; N_{1M} and N_{2M} (mg/g) are the receptor site densities of the first and the second kinds of active sites, respectively; n_1 and n_2 are the number of adsorbed molecules by each binding site for the first and the second kinds of active sites, respectively.

Fourth model (M4): Double-layer model with two different energies. This model is
 suitable to predict the double-layer adsorption on the two different types of adsorbent
 active sites. The equation of the M4 model is given as:

211
$$Q_e = nN_M \frac{\left(\frac{c}{c_1}\right)^n + 2\left(\frac{c}{c_2}\right)^{2n}}{1 + \left(\frac{c}{c_1}\right)^n + \left(\frac{c}{c_2}\right)^{2n}} \qquad (6)$$

where **C** (mg/L) denotes the equilibrium concentration; N_M (mg/g) refers to receptor sites density; **C**₁ and **C**₂(mg/L) correspond to the concentrations at half-saturation for the first and the second type of active sites, respectively.

o Fifth model (M5): Finite multi-layer model. This model suggests the occurrence of
 multilayer adsorption process. The formalism of the M5 model is expressed as follows:

217
$$Q_e = nN_M \frac{\left(\frac{c}{c_1}\right)^n \left(1 - (N_\ell + 1)\left[\frac{c}{c_2}\right]^{nN_\ell} + N_\ell \left[\frac{c}{c_2}\right]^{n(N_\ell + 1)}\right)}{\left(1 - \left[\frac{c}{c_2}\right]^n\right) \left(1 - \left[\frac{c}{c_2}\right]^n + \left[\frac{c}{c_1}\right]^n - \left[\frac{c}{c_2}\right]^{nN_\ell}\right)}$$
(7)

where $(N_1 + 1)$ represents the number of adsorption layers; **n** refers to the number of ions per adsorption site; N_M (mg/g) refers to receptor sites density; C_1 and C_2 (mg/L)

220 correspond to the concentrations at half-saturation for the first and the second type of

221 active sites, respectively.

The equations of the above-presented statistical physics models were derived from the corresponding grand-canonical partition functions in the statistical physics (Mobarak et al., 2019b, 2019a). These models were fitted to the experimental results of OG dye adsorption onto PANI@Fe-ZSM-5 composite using Mathematica 11 program. The appropriateness of the selected models was evaluated based on the correlation coefficient (R²) and root mean squared error (RMSE) values (Mobarak et al., 2019b).

228
$$RMSE = \sqrt{\frac{\sum_{i=1}^{m} (Q_{i cal} - Q_{i exp})^{2}}{p-q}}$$
(8)

where p and q represent the number of actual data and adjustable parameters, respectively. $Q_{i cal}$ and $Q_{i exp}$ denote the computed and the experimental OG dye uptake capacities, respectively.

232 3. Results and discussion

3.1. Surface characterization and XRD analysis

Fig. 1 depicts the morphology and elemental analysis of Fe-ZSM-5 particles before and after the polymerization of aniline. According to **Fig. 1(a)**, the SEM image of Fe-ZSM-5 features smooth agglomerated spheres with a size ranging from 1 to 5 μm. **Fig. 1(b)** confirms the deposition of polyaniline onto the Fe-ZSM-5 surface with a flake-like structure. This surface morphology may constitute a good platform for the removal of pollutants from aqueous media. In addition, the acquired textural information reveals good adhesion of PANI onto the Fe-ZSM-5 surface. This may be due to interactions

(hydrogen bonds) between the amine groups of aniline and the hydroxyl groups (Si-OH) 241 of the Fe-ZSM-5 zeolite (Ba Mohammed et al., 2020). From Figs. 1(c) and (d), the 242 elemental analysis of the Fe-ZSM-5 zeolite by EDS proves the existence of the following 243 elements: oxygen (50.51%), silicon (41.98%), iron (5.23%) and sodium (2.28%). This 244 result indicates that silicon oxide (SiO₂) is the major phase of the Fe-ZSM-5 zeolite. After 245 the polymerization of aniline on the surface of Fe-ZSM-5 zeolite, the EDS spectrum shows 246 the appearance of carbon (38.06%). In addition, the EDS spectrum of PANI@Fe-ZSM-5 247 features other characteristic elements (N, Cl and S), which affirms that the surface of Fe-248 ZSM-5 is well-coated by PANI. 249




Fig. 1. (a) SEM micrographs of Fe-ZSM-5, (b) PANI@Fe-ZSM-5 and (c and d) their
 respective EDS elemental spectra.

X-ray diffraction is an important technique used to identify the crystalline phases and 253 254 structural properties of solid materials. Therefore, the as-prepared Fe-ZSM-5 zeolite and PANI@Fe-ZSM-5 composite were analyzed by this technique and the obtained XRD 255 patterns are displayed in Fig. 2(a). The synthesized Fe-ZSM-5 zeolite sample exhibited 256 peaks at $2\theta = 7.95^{\circ}$, 8.80°, 23.10°, 23.94° and 24.40° associated with [0 1 1], [0 2 0], [0 5 257 258 1], [0 3 3] and [3 1 3] planes, with corresponding d-spacing values of 1.11, 1.00, 0.38, 0.37 and 0.36 nm, respectively. These values are in good agreement with the peaks of Fe-ZSM-259 5 zeolite (JCPDS no. 43-0321) with a well-resolved mordenite framework inverted (MFI) 260 261 structure (Chemical formula: H_{0.32}Al_{0.32}Si_{95.68}O₁₉₂, Crystal system: Monoclinic and Space group: P21/n) (Narayanan et al., 2015). Moreover, the sharpness of the peaks of the 262 diffraction peaks suggests that the as-prepared Fe-ZSM-5 sample has a more crystalline 263 nature and no other peaks appeared, which discloses that the as-prepared Fe-ZSM-5 264 material does not contain any impurities (Liu et al., 2011). Compared with bare Fe-ZSM-265 5 sample, the peak intensities of the [0 1 1] and [0 2 0] planes of PANI@Fe-ZSM-5 266 composite were markedly decreased due to the PANI coating on the Fe-ZSM-5 surface, 267 but their crystal framework structure was preserved. Moreover, no characteristic 268 diffraction peaks of PANI were detected in PANI@ZSM-5 composite, because PANI was 269 in amorphous phase. Furthermore, the absence of impurity phases in the XRD curves 270 indicates the successful synthesis of PANI@Fe-ZSM-5 composite. 271

272 **3.2.** FTIR data analysis

The FTIR spectrum of Fe-ZSM-5 and PANI@Fe-ZSM-5 are depicted in Fig. 2(b). The 273 FTIR spectrum of Fe-ZSM-5 exhibits a characteristic peak at about 3854 cm⁻¹ ascribed to 274 the silanol groups of Si-OH. The absorption bands at 2915 and 2840 cm⁻¹ can be assigned 275 to the residual methyl (-CH₃) and methylene (-CH₂) vibrations of tetrapropylammonium 276 bromide precursor (Kachangoon et al., 2020). The peak located at 1631 cm⁻¹ is ascribed 277 278 to the stretching bending of adsorbed water molecules. The symmetric stretching of 279 external linkages of the tetrahedron appears at around 792 cm⁻¹ (Liu et al., 2011). Also, the spectrum comprises a peak at 556 cm⁻¹ assigned to the stretching vibrations of Fe–O 280 of Fe₂O₃ (Suresh et al., 2014). The peaks at 477 and 1220 cm⁻¹ are attributed to the Si–O 281 bending vibrations of SiO₄ internal tetrahedral (Doula, 2007), (Niu et al., 2017). The FTIR 282 spectrum of PANI@Fe-ZSM-5 reveals the appearance of a new peak at 3520 cm⁻¹ assigned 283 to the N–H stretching vibration, indicating the existence of amine groups. Besides, the 284 vibration bands at 1580 and 1440 cm⁻¹ are ascribed to the stretching vibration C=C in 285 quinoid and benzenoid structure of doped PANI, respectively (Xu et al., 2014). These 286 findings confirm that the PANI was well-incorporated onto the surface of Fe-ZSM-5 287 particles. 288

289 **3.3. XPS analysis**

290 XPS analysis was performed to assess the chemical composition and chemical state of the 291 PANI@Fe-ZSM5 surface. The full survey XPS survey of PANI@Fe-ZSM5 composite is 292 depicted in **Fig. 2(c)**. The spectrum revealed the presence of O_{1s} (531.5 eV), N_{1s} (397.9 eV) 293 and C_{1s} (283.6 eV) as the main components of the PANI@Fe-ZSM5 surface (Abdel Hamid 294 et al., 2019). Besides, the presence of three weak peaks confirmed the occurrence of silicon 295 (Si2p and Si2s at 101.9 and 152.6 eV, respectively), sulfur (S_{2p} at 168.1 eV) and chlorine

(Cl_{2p} at 199.4 eV) elements on the PANI@Fe-ZSM-5 surface (Abdel Hamid et al., 2019; 296 Ravelo-Acuña et al., 2019; Zhang et al., 2016). The Si element is related to the silica in the 297 ZSM-5 zeolite. The other elements (e.g., Fe and Al) of Fe-ZSM-5 zeolite were not detected, 298 which eventually due to the formation of thick PANI layer on the surface of Fe-ZSM-5 299 zeolite (penetration depth of the X-ray beam does not exceed 10 nm). The Cl and S 300 301 elements are indicative of the existence of chloride anion doping (Cl-) and oxidizing agent 302 (sodium persulfate) on the PANI@Fe-ZSM-5 surface. From Fig. 2(d), the C_{1s} high resolution spectrum was fitted with three peaks located at 284.9 (C-C/C-H), 285.7 (C-303 N/C=N) and 287.1 eV (C-N $^+$ /C=N $^+$) (Chan et al., 1992; Wang et al., 2015). The positively 304 charged N-containing functional groups indicated the doping of PANI chains by sulfate 305 and chloride ions generated from the oxidant and HCl acid (Wang et al., 2005). Fig. 2(e) 306 shows that the N1s spectrum which can be deconvoluted into two peaks at 398.4 and 399.6 307 eV ascribed to amine (-NH-) and doped quinonoid imine (-NH⁺=) of benzenoid ring, 308 respectively (Bhaumik et al., 2021). The XPS results demonstrated that the PANI 309 Emeraldine salt (doped form) was successfully coated on the Fe-ZSM-5 zeolite. 310




Fig.2. (a) XRD patterns of Fe-ZSM-5 and PANI@Fe-ZSM-5 composite; (b) FTIR
spectra of Fe-ZSM-5 zeolite and PANI@Fe-ZSM-5 composite; (c) XPS wide scan
spectrum; (d) C_{1s} and (e) N_{1s} core level spectra of the PANI@Fe-ZSM-5 composite.

316 3.4. Adsorption study

317 **3.4.1.** Effects of adsorbent dosage and pH

The influence of sorbent dosage on the OG dye adsorption was investigated in the 0.2 to 318 2.0 g/L concentration range. Fig. 3(a) displays the removal efficiency and uptake 319 capacity of OG onto PANI@Fe-ZSM-5 at different adsorbent doses. The adsorption 320 percentage was increased up to 96.37 % with the increase of PANI@Fe-ZSM-5 dose from 321 0.2 to 0.5 g/L. This might be due to the increment in the number of adsorbate binding 322 sites available for OG dve removing (Hsini et al., 2020). Increasing the PANI@Fe-ZSM-5 323 dosage beyond 0.5 g/L did not affect the OG dye adsorption efficiency. This trend may be 324 due to the exhaustion of OG dye molecules. Besides, the uptake capacity was decreased, 325 owing to the formation of adsorbent particles aggregates, which could minimize the 326 availability of surface sites for OG dye adsorption (Hsini et al., 2021d; Tu et al., 2020). 327

It is widely-known that the solution pH is a key operating condition in adsorption 328 processes (Hsini et al., 2021a). The surface charge of the PANI@Fe-ZSM-5 composite was 329 investigated as a function of pH (inset of Fig. 3(b)). The PZC value of PANI@Fe-ZSM-5 330 composite was found to be 3.75. This means that the as-prepared PANI@Fe-ZSM-5 331 material surface is positively charged at pH below 3.75, while the surface becomes 332 333 negatively charged at pH above 3.75. The influence of the solution pH on the adsorption process over the pH range 2–12 is displayed in Fig. 3(b). As a result, the maximum 334 removal percentage of OG dye was achieved at low pH values. That could be elucidated by 335 the protonation of adsorbent sites (protonated silanol and amine groups), which results 336 in the increment of the electrostatic interactions between anionic OG dye and positively 337 charged PANI@Fe-ZSM-5 surface (Ba Mohammed et al., 2020). Whilst, at higher pH, the 338


OG dye adsorption efficiency decreased due to a decline of the number of positively 339 charged sites. Therefore, we can conclude that the adsorption of OG dve on the as-340 prepared adsorbent surface is executed through electrostatic interactions (Yeamin et al., 341 2021), as well as the involvement of π - π ones (Nasar and Mashkoor, 2019). Besides, under 342 alkaline conditions, the competitive adsorption of OH⁻ ions with OG anions could be 343 another reason to explain the observed downward trend of OG dye removal efficiency. In 344 345 the next adsorption experiments, the pH value of OG solutions was maintained at 6.0 to minimize the costs related to the pH adjustment. It is worth highlighting the pivotal role 346 347 of electrostatic and π - π interactions in the OG dye adsorption mechanism. Based on the above discussion, a binding mechanism of OG dye on the PANI@Fe-ZSM-5 surface is 348 proposed in Fig. 6(d). To further confirm the adsorption of OG dye, the adsorbent surface 349 after adsorption was analyzed by the FTIR technique. The FTIR spectra of PANI@Fe-350 ZSM-5 before and after OG dye removal are depicted in Fig. 6(c). As a result, the FTIR 351 data showed that there is no obvious shift in the bands of the functional groups on the 352 PANI@Fe-ZSM-5 surface after adsorption, indicating that the molecular structure of the 353 PANI@Fe-ZSM-5 composite remained unaltered after OG dve removal. Furthermore, 354 no new peak was observed after OG adsorption, suggesting that there is no chemical 355 interaction of OG molecules with PANI@Fe-ZSM-5. Therefore, it can be concluded that 356 the binding of OG dye molecule on the PANI@Fe-ZSM-5 surface sites takes place via 357 physical interactions (e.g., electrostatic forces and π - π interactions). In light of the above 358 presented discussion, a graphical illustration of the proposed adsorption mechanism is 359 presented in Fig. 6(d). 360

362 3.4.2. Adsorption kinetics

The result of adsorbent/adsorbate contact time on the removal of OG dye by PANI@Fe-363 ZSM-5 composite surface was investigated by plotting the adsorption capacity of OG dye 364 365 versus contact time (from 2 to 180 min). The adsorbent dosage of 0.5 g/L was used in 100 mL of OG solution with 20 mg/L initial concentration at pH 6 and 25 °C. From Fig. 3(c), 366 it can be seen that upon increasing the contact time, the OG dye uptake was improved. In 367 the first 60 min, the increase was rapid then it became slow, and the equilibrium was 368 369 reached after 120 min. Thus, the removal ability of PANI@Fe-ZSM-5 composite was related to the binding sites availability on the PANI@Fe-ZSM-5 surface for OG textile dye 370 removal (Tu et al., 2020). The pseudo-first-order, pseudo-second-order, and intra-371 372 particle diffusion kinetic models were used to fit the kinetic data to evaluate the kinetic mechanism of OG adsorption on the PANI@Fe-ZSM-5 composite (Abbasi, 2017). The 373 nonlinear equations and the corresponding fitting parameters of pseudo-first-order and 374 pseudo-second-order kinetic models are summated in Table S1 and Fig. 3(c). As shown 375 in Fig. 3(c), the pseudo-second-order model with R² of 0.97 is the model which had the 376 highest correlation coefficient than the pseudo-first-order model (0.91). Furthermore, the 377 adsorption capacity, calculated from pseudo-second-order model (37.99 mg/g), was 378 found to be close to the experimentally-determined one (37.15 mg/g), confirming that the 379 OG dye adsorption process was better described by this kinetic model. 380

In order to investigate the mass transfer mechanism that occurred during the adsorption process, the intraparticle diffusion model was applied to the actual removal data (Tang and Zhang, 2016). The fitting parameters are listed in **Table S1**. **Fig. 3(d)** illustrated that the removal of OG dye by the PANI@Fe-ZSM-5 composite consisted in three successive

stages. The first one was ascribed to the diffusion of OG dye molecules from the aqueous phase to the external surface sites of as-prepared composite. The second stage implicates the intra-particle diffusion as rate-controlling step. In the last stage the intraparticle diffusion rate decreased, because of the extremely low concentration of OG (Tang and Zhang, 2016). Besides, these results were supported by the reduction of rate constant values when going from the first stage to the last one.



400 temperature = 25 °C); (b) Adsorption efficiency of the OG dye onto PANI@Fe-ZSM-5 at
401 different pH values (inset: PZC determination of the PANI@Fe-ZSM-5 composite), (c)
402 Pseudo-first-order and pseudo-second-order kinetics models; (d) intraparticle diffusion
403 model.

404

405

3.5. Advanced statistical physics interpretation

The fitting of the considered statistical physics models to the experimental data for OG 406 dye removal by the PANI@Fe-ZSM-5 composite was evaluated based on the 407 determination of R² coefficient and RMSE values. From Table S2, it is clear that the M3 408 model (monolayer model with two different energies) demonstrated good correlation with 409 OG dve adsorption data (high R² values and low RMSE values) for all tested temperatures 410 (Fig. 4(a)). Therefore, the M3 model was chosen as the best fitting statistical physics 411 model to elucidate the macroscopic and microscopic properties of the OG dye removal 412 process by the PANI@Fe-ZSM-5 composite. 413

414 3.5.1. Statistical physics parameters

To shed light on the orientation of OG dye molecules on the PANI@Fe-ZSM-5 surface, the 415 values of the stoichiometric coefficient (n) were calculated at different temperatures (Fig. 416 **4(b) and Table S3)**. On the one hand, n₁ values (for the first type of active sites) are less 417 than 1, indicating that the OG dye molecules adsorbed parallelly on the first type of active 418 surface sites of PANI@Fe-ZSM-5 composite. In addition, each receptor site (first type) of 419 PANI@Fe-ZSM-5 composite adsorbs more than one OG dye molecule, suggesting a multi-420 docking adsorption mechanism (Sellaoui et al., 2015). This adsorption behavior becomes 421 more pronounced with increasing temperature (n_1 values decreased). On the other hand, 422 the n_2 values (for the second type of active sites) are superior to unity, revealing that the 423 OG dye molecules adsorbed perpendicularly via a multimolecular mechanism on the 424 second type of active sites of PANI@Fe-ZSM-5 composite (Laabd et al., 2022). Moreover, 425 it is worth noticing that the n_2 values increased with the increase of temperature, 426

highlighting that the thermal agitation results in the decrease in the aggregation of the OG
dye molecules in the liquid phase (Li et al., 2019).

The density of active sites (N_M) is a crucial parameter governing the removal performance. 429 The temperature dependence of N_M parameter for OG dye removal by PANI@Fe-ZSM-5 430 composite surface is presented in Fig. 4(c). It can be observed that the N_{1M} (for the first 431 432 type of active sites) and N_{2M} (for the second type of active sites) parameters follow an inverse trend compared to n₁ and n₂ stoichiometric coefficients, respectively. This result 433 could be attributed to steric-hindrance effect of OG dye molecules during the adsorption 434 435 process onto the PANI@Fe-ZSM-5 surface (Sellaoui et al., 2017b). Indeed, as the number of adsorbed OG dye molecules per active site (n) decreases, the number of available 436 adsorption sites increases, thus leading to an increase in the density of active sites (N_M), 437 and vice versa. 438

The saturation uptake capacity (Q_{sat} in mg/g) of the PANI@Fe-ZSM-5 composite for OG dye adsorption depends on the stoichiometric coefficient (n) and density of active sites ($Q_{sat} = nN_M$). From **Fig. 4(d)**, it is convenient to mention that the adsorbed amounts (Q_1 and Q_2) increased with raising the temperature (endothermic process), confirming that the total OG dye adsorption capacity (Q_{sat}) is predominantly affected by the density of active sites (N_M) rather than the stoichiometric coefficient (n).

From an energetic point of view, the removal of OG dye by the PANI@Fe-ZSM-5 composite was assessed by calculating the adsorption energies E1 and E2 for the first and second types of active sites, respectively. The values of E1 and E2 can be computed by the following Eqs.:

449
$$E_1 = \operatorname{RTln}\left(\frac{C_s}{C_1}\right)$$
 (9)

450
$$E_2 = \operatorname{RTln}\left(\frac{C_s}{C_2}\right)$$
 (10)

where Cs (mg/L) is the aqueous solubility of OG dye. C_1 and C_2 represent the halfsaturation concentrations (mg/L) for the first and the second types of adsorption sites, respectively. R (8.314 J/mol K) is the universal gas constant and T is the temperature (K).

Fig. 4(e) shows the influence of temperature on the removal energy. It is noteworthy 454 that the values of adsorption energies are positive and increased with temperature, 455 proving that the OG dye removal by the PANI@Fe-ZSM-5 composite is an endothermic 456 process. Therefore, the adsorption method is favorable at higher temperatures, which 457 is in concordance with the saturation adsorption capacity. Moreover, the figure shows 458 that E1 is higher than E2, which confirm that PANI@Fe-ZSM-5 459 has a higher interaction with OG dye. From the calculated values of adsorption energies, we deduce 460 that the adsorption was a physical process since these values are <40 kJ/mol (Seliem 461 and Mobarak, 2019). The adsorption formed bonds could be a hydrogen bonds or Van 462 der Waals or dipole-dipole interactions (Wjihi et al., 2020, 2017), reinforcing that the 463 OG dye adsorption is physisorption in nature (Sellaoui et al., 2016). 464




Fig. 4. (a) Fitting of actual equilibrium data of OG dye removal by the PANI@Fe-ZSM-5
composite to the M3 model (best fitted model); (b) The stoichiometric coefficient; (c)
the density of active sites; (d) the saturation uptake capacity and (e) the adsorption
energy for OG dye removal by the PANI@Fe-ZSM-5 composite at different
temperatures.

471 **3.5.2.** *Thermodynamic functions*

The thermodynamic functions (entropy, free enthalpy and internal energy) related to the OG dye adsorption on the PANI@Fe-ZSM-5 composite were calculated using the monolayer layer model with the different energy sites (**M3**). The entropy function is of prime importance to predict the randomness of OG dye molecules at the solutionadsorbent interface. This thermodynamic function was calculated according to the following Eq. (Seliem and Mobarak, 2019):

$$478 \qquad \frac{S}{k_B} = \frac{-Q_{sat.1} \left[\frac{c}{c_1}\right]^{n_1} \ln\left[\frac{c}{c_1}\right] + Q_{sat.2} \left[\frac{c}{c_2}\right]^{n_2} \ln\left[\frac{c}{c_2}\right] + \left[\frac{c}{c_1}\right]^{n_1} \left[\frac{c}{c_2}\right]^{n_2} \left(Q_{sat.1} \ln\left[\frac{c}{c_1}\right] + Q_{sat.2} \ln\left[\frac{c}{c_2}\right]\right)}{\left(1 + \left[\frac{c}{c_1}\right]^{n_1}\right) \left(1 + \left[\frac{c}{c_2}\right]^{n_2}\right) + \ln\left(\left(1 + \left[\frac{c}{c_1}\right]^{n_1}\right)^{N_{1M}} \left(1 + \left[\frac{c}{c_2}\right]^{n_2}\right)^{N_{2M}}\right)}$$
(11)

To evaluate the spontaneity of the OG dye adsorption system, the free enthalpy functionis computed as follows (Ayachi et al., 2019):

481
$$\frac{G}{k_B T} = \ln \left[\frac{\mu}{Z_{tr}} \right] \left(\frac{Q_{sat.1}}{1 + \left[\frac{C_1}{C} \right]^{n_1}} + \frac{Q_{sat.2}}{1 + \left[\frac{C_2}{C} \right]^{n_2}} \right)$$
 (12)

The internal energy (E_{int}) represents the sum of energies in the adsorption system. This
thermodynamic function is written as follows (Seliem and Mobarak, 2019):


$$484 \qquad \frac{E_{int}}{k_B T} = \frac{-N_{1M} \left[\frac{c}{c_1}\right]^{n_1} \left(n_1 \ln \left[\frac{c}{c_1}\right] - \mu\right) + N_{2M} \left[\frac{c}{c_2}\right]^{n_2} \left(n_2 \ln \left[\frac{c}{c_2}\right] - \mu\right) + \left[\frac{c}{c_1}\right]^{n_1} \left[\frac{c}{c_2}\right]^{n_2} \left(N_{1M} \left(n_1 \ln \left[\frac{c}{c_1}\right] - \mu\right) + N_{2M} \left(n_2 \ln \left[\frac{c}{c_2}\right] - \mu\right)\right)}{\left(1 + \left[\frac{c}{c_1}\right]^{n_1}\right) \left(1 + \left[\frac{c}{c_2}\right]^{n_2}\right)}$$
(13)

485 In Eqs. (11-13), k_B , μ and Z_{tr} are the Boltzmann constant, chemical potential and 486 translation partition function, respectively.

The evolution of the entropy function during the OG dye adsorption versus equilibrium
OG dye concentration at different temperatures (298, 308 and 318 K) is displayed in Fig.

5(a). From this figure, the entropy function exhibited similar trend for all studied 489 temperatures. In addition, we can see that, with increasing the equilibrium OG dve 490 concentration, the entropy of OG dye removal system increased until a maximum at the 491 half-saturation concentration and then decreased. At lower OG dye concentrations, the 492 OG molecules possessed high probability to select an active site on the PANI@Fe-ZSM-5 493 494 surface, resulting in an increase of disorder at the solution-adsorbent interface. At higher 495 OG dye concentrations, the PANI@Fe-ZSM-5 surface tended to the saturation and the probability of OG molecules to find a vacant adsorption site was significantly decreased. 496 Therefore, the entropy shifted towards lower values (decrease of disorder). 497

Fig. 5(b) represents the evolution of the free enthalpy as a function of OG dye 498 concentration. As a result, the negative values of the free enthalpy function revealed that 499 the OG adsorption on the PANI@Fe-ZSM-5 composite is a spontaneous process for all 500 501 investigated temperatures (Sellaoui et al., 2016). Besides, it can be seen that the free enthalpy decreases with increasing temperature and OG dye concentration. Thus, we can 502 conclude that the OG dye adsorption process is more favorable at higher temperatures 503 (endothermic process) and higher OG dye concentrations (increase in the concentration 504 gradient). Fig. 5(c) displays the variation of internal energy versus equilibrium OG 505 506 concentration at different temperatures. The negative values of the internal energy during 507 the OG dye adsorption on the PANI@Fe-ZSM-5 composite confirms its spontaneous 508 nature (Sellaoui et al., 2017a), reflecting that the OG dye molecules exhibited good binding affinity with the PANI@Fe-ZSM-5 surface. Moreover, the internal energy tremendously 509 decreases with OG concentration at low concentration range, which indicates that the OG 510 dye molecules target the most active sites on the PANI@Fe-ZSM-5 surface. When the OG 511 dye concentration is increased, the availability of PANI@Fe-ZSM-5 surface sites decreases 512






Fig. 5. Thermodynamic functions: (a) entropy; (b) free enthalpy and (c) internal
energy for OG dye adsorption on the PANI@Fe-ZSM-5 composite.


519 **3.6. Effect of co-existing ions and Regeneration**

It has been known that the wastewaters are polluted not only by dyes, but also by other organic and inorganic pollutants (Ansari et al., 2017). Thus, it is necessary to assess the influence of coexisting ions. For this goal, a series of adsorption tests were carried out by keeping the concentration of OG dye constant at 20 mg/L while varying the concentration of coexisting ions (PO_4^{2-} , SO_4^{2-} , CO_3^{2-} and NO_3^{-}) from 20 to 60 mg/L. The operating

525

526 PANI@Fe-ZSM-5 composite (Laabd et al., 2021). The presence of SO₄²⁻, CO₃²⁻ and NO₃⁻ 527 ions did not influence the OG removal and the adsorption capacity remained at 37.15 528 mg/g. In contrast, the presence of $PO_{4^{3-}}$ ions had a considerable effect on the performance 529 530 of OG adsorption. The increase of concentration of $PO_{4^{2-}}$ resulted in a decrease of the 531 amount of OG adsorbed until 17.03 mg/g. This adsorption behavior could be ascribed to the affinity of PANI@Fe-ZSM-5 surface for PO₄³⁻ ions, and subsequently the competition 532 between OG dye and PO₄²⁻ anions significantly inhibited the OG adsorption (Banerjee et 533 al., 2019). 534

For regeneration and reuse of PANI@Fe-ZSM-5, NaOH (0.5 M) was used as a 535 regenerating agent. Further, it was reported in the literature that NaOH is the best suitable 536 agent for desorbing OG dye from the adsorbent surfaces (Brini et al., 2021a; Hsini et al., 537 2021c; Xu et al., 2020). In this study, the recyclability of PANI@Fe-ZSM-5 composite for 538 OG dye removal efficiency was evaluated up to five adsorption-desorption cycles. Fig. 539 **6(b)** depicts that the adsorption efficiency of OG dye from aqueous solutions was still 540 above 86-% in the first four desorption/adsorption cycles. However, in the fifth 541 regeneration cycle, the OG dye removal performance (38%) decreases significantly owing 542 to the possible accumulation of OG molecules on the PANI@Fe-ZSM-5 surface. Overall, 543 the experimental results revealed that the PANI@Fe-ZSM-5 composite owns excellent 544 reusability and could be reused as an efficient and inexpensive adsorbent to eliminate of 545 OG dye from aqueous solutions. 546



549	Fig. 6. (a) Effect of coexisting ions on the removal of OG dye by PANI@Fe-ZSM-5:
550	adsorbent dose = 0.5 g/L; pH= 6.0; 20 mg/L OG dye concentration; T=25°C; (b)
551	Adsorption efficiency of OG dye by PANI@Fe-ZSM-5 composite for 5 regeneration
552	cycles; (c) FT-IR spectral data of PANI@Fe-ZSM-5 before and after adsorption of OG
553	dye, and (d) Schematic presentation of the proposed adsorption mechanism.

554

3.7. Comparison with other adsorbents

To evaluate the adsorption performance of PANI@Fe-ZSM-5, it is important to figure out 555 its position compared with other adsorbents. From a literature survey, many studies 556 reported the OG dye adsorption from water using different adsorbent materials. As shown 557 in Table 1, it is evident that the PANI@Fe-ZSM-5 composite demonstrated an excellent 558 559 maximum uptake capacity (217 mg/g) for OG dye removal compared with reported adsorbents. Thus, we conclude that the as-synthesized adsorbent may be a useful material 560 for efficient OG dye removal. Finally, the as-developed PANI@Fe-ZSM-5 hybrid material 561 can be recommended as a potential and inexpensive adsorbent to clean up OG dye from 562 wastewaters. 563

Table 1. Comparison of the maximum uptake capacities of PANI@Fe-ZSM-5 for OGremoval and other adsorbents addressed in the previously published studies.

566

567

Adsorbent	Q _{max} (mg g ⁻¹)	Operating conditions			Reference
		Equilibrium	Dose	pН	-
		time (min)	(g L-1)		
FSMD MNPs	109.1	60	1	3	(Zheng et al., 2019)
Alumina nanoparticles	93.3	45	1	2.5	(Banerjee et al., 2019)
Cts(x)-g-PNVP	63.7	175	10	3	(Sutirman et al., 2019)
Monoamine-modified silica	36.3	300	1	3	(Donia et al., 2009)
Prussian-Blue nanoparticles supported over alumina	44.4	100	6.5	3	(Doumic et al., 2015)
AC from coffee grounds	100	180	1	3	(Laksaci et al., 2019)
Modified montmorillonite nanoclay	3 9.4	60	2.5	8	(Salam et al., 2017)
PANI@Walnut shells	17.24	90	1	6	(Imgharn et al., 2021)
Bagasse fly ash	18.79	200	2	4	(Mall et al., 2006)
Kapok fiber oriented polyaniline	192.3	240	1	6	(Zheng et al., 2012)
H-MIL -53(Fe)	163.9	300		4	(Feng et al., 2020)

		Journal Pre-proof			
PANI@AS biocomposite	190.98	100	0.5	5	(Hsini et al., 2020)
Cucumber peels	37.8	60	0.5	6	(Stavrinou et al., 2018)
PANI@Fe-ZSM-5 composite	217	120	0.5	5	Current study

569

570 Conclusion

In this contribution, PANI@Fe-ZSM-5 composite was synthesized, characterized and used 571 for OG dye removal from water. The adsorption study established that the PANI@Fe-572 ZSM-5 composite as an effective adsorbent for the removal of OG dye from aqueous 573 solutions. Based on the results obtained for pH influence on the adsorption process and 574 PZC of PANI@Fe-ZSM-5 composite, electrostatic interactions were likely the main forces 575 576 governing the OG dye adsorption mechanism. The kinetic data for OG dye removal by the 577 PANI@Fe-ZSM-5 composite was well-fitted by the pseudo-second-order model. The mass transfer process of OG dye from the solution to the PANI@Fe-ZSM-5 surface occurred via 578 three consecutive stages: (i) external diffusion, (ii) intraparticle diffusion and (iii) final 579 adsorption equilibrium. The OG dye binding mechanism and associated thermodynamic 580 behavior were evaluated on the basis of advanced statistical physics theory. Among the 581 fitted statistical physics models to the experimental findings, the M3 model (monolayer 582 layer model with the different energy sites) is the best one to describe the OG dye 583 adsorption process. Based on this model, the macroscopic and microscopic aspects related 584 to the adsorption system were assessed. The OG dye molecules were adsorbed in the 585 perpendicular (multi-docking) and parallel (multimolecular) modes on the first $(n_1 < 1)$ 586

587	and second ($n_2 > 1$) types of active sites in the PANI@Fe-ZSM-5 surface. The
588	thermodynamic functions confirmed the feasibility of OG adsorption onto PANI@Fe-
589	ZSM-5 composite through physical interactions. The theoretical data are in satisfactory
590	concordance with experimental results. Finally, we can conclude that the as-developed
591	PANI@Fe-ZSM-5 material can be applied as an efficient and regenerable adsorbent for
592	treating the textile effluents.

593 **References**

- Abbasi, M., 2017. Synthesis and characterization of magnetic nanocomposite of
 chitosan/SiO₂/carbon nanotubes and its application for dyes removal. J. Clean.
 Prod. 145, 105–113. https://doi.org/10.1016/j.jclepro.2017.01.046
- Abdel Hamid, Z., Hasan Gomaa, M., S. Abdel Rehim, S., Abdel Hamid, M., Ibrahim, A.,
 2019. Synthesis and Characterization of Nanostructured Polyaniline Thin Films
 with Superhydrophobic Properties. Coatings 9, 748.
- 600 https://doi.org/10.3390/coatings9110748
- Abdellaoui, Y., Gamero-Melo, P., Díaz-Jiménez, L., Ponce-Caballero, C., GiácomanVallejos, G., 2020. Synthesis and Surface Modification of Small Pore Size Zeolite
 W for Improving Removal Efficiency of Anionic Contaminants from Water. Bull.
 Environ. Contam. Toxicol. 105, 934–940. https://doi.org/10.1007/s00128-02003036-z
- Ait Haki, M., Imgharn, A., Aarab, N., Hsini, A., Essekri, A., Laabd, M., El Jazouli, H.,
 Elamine, M., Lakhmiri, R., Albourine, A., 2021. Efficient removal of crystal violet
 dye from aqueous solutions using sodium hydroxide modified avocado shells:
 kinetics and isotherms modeling. Water Sci. Technol. wst2021451.
- 610 https://doi.org/10.2166/wst.2021.451
- Akhsassi, B., Bouddouch, A., Naciri, Y., Bakiz, B., Taoufyq, A., Favotto, C., Villain, S.,
 Guinneton, F., Benlhachemi, A., 2021. Enhanced photocatalytic activity of
 Zn₃(PO₄)₂/ZnO composite semiconductor prepared by different methods. Chem.
- 614 Phys. Lett. 783, 139046. https://doi.org/10.1016/j.cplett.2021.139046
- Amjlef, A., Khrach, S., Ait El Fakir, A., Farsad, S., Et-Taleb, S., El Alem, N., 2021.
 Adsorptive properties investigation of natural sand as adsorbent for methylene
 blue removal from contaminated water. Nanotechnol. Environ. Eng. 6, 26.
 https://doi.org/10.1007/s41204-021-00119-y
- Ansari, M.O., Kumar, R., Ansari, S.A., Ansari, S.P., Barakat, M.A., Alshahrie, A., Cho,
 M.H., 2017. Anion selective pTSA doped polyaniline@graphene oxide multiwalled carbon nanotube composite for Cr(VI) and Congo red adsorption. J.
 Colloid Interface Sci. 496, 407–415. https://doi.org/10.1016/j.jcis.2017.02.034
- Ayachi, F., Z. Kyzas, G., Aatrous, M., Sakly, A., Ben Lamine, A., 2019. Evaluating the
 adsorption of Ni(II) and Cu(II) on spirulina biomass by statistical physics

formalism. J. Ind. Eng. Chem. 80, 461-470. 625 https://doi.org/10.1016/j.jiec.2019.05.044 626 Ba Mohammed, B., Hsini, A., Abdellaoui, Y., Abou Oualid, H., Laabd, M., El Ouardi, M., 627 Ait Addi, A., Yamni, K., Tijani, N., 2020. Fe-ZSM-5 zeolite for efficient removal of 628 basic Fuchsin dye from aqueous solutions: Synthesis, characterization and 629 adsorption process optimization using BBD-RSM modeling. J. Environ. Chem. 630 Eng. 8, 104419. https://doi.org/10.1016/j.jece.2020.104419 631 Banerjee, S., Dubey, S., Gautam, R.K., Chattopadhyaya, M.C., Sharma, Y.C., 2019. 632 Adsorption characteristics of alumina nanoparticles for the removal of hazardous 633 dve. Orange G from aqueous solutions. Arab. J. Chem. 12, 5339-5354. 634 635 https://doi.org/10.1016/j.arabjc.2016.12.016 Belbachir, I., Makhoukhi, B., 2017. Adsorption of Bezathren dyes onto sodic bentonite 636 637 from aqueous solutions. J. Taiwan Inst. Chem. Eng. 75, 105–111. 638 https://doi.org/10.1016/j.jtice.2016.09.042 Benjelloun, M., Miyah, Y., Akdemir Evrendilek, G., Zerroug, F., Lairini, S., 2021. Recent 639 Advances in Adsorption Kinetic Models: Their Application to Dye Types. Arab. J. 640 641 Chem. 14, 103031. https://doi.org/10.1016/j.arabjc.2021.103031 Bhaumik, M., Maity, A., Brink, H.G., 2021. Zero valent nickel nanoparticles decorated 642 polyaniline nanotubes for the efficient removal of Pb(II) from aqueous solution: 643 Synthesis, characterization and mechanism investigation. Chem. Eng. J. 417, 644 127910. https://doi.org/10.1016/j.cej.2020.127910 645 Brini, L., H'Maida, K., Imgharn, A., Hsini, A., Naciri, Y., Ajmal, Z., Bouziani, A., 646 Boulahya, A., Arahou, M., Bakiz, B., Albourine, A., Fekhaoui, M., 2021a. Synthesis 647 and characterisation of PANI- coated Heliotrope Leaves (PANI@HL) with high 648 649 clean-up capacity for Orange G dye from aqueous media. Int. J. Environ. Anal. Chem. 1-17. https://doi.org/10.1080/03067319.2021.1994557 650 Brini, L., Hsini, A., Naciri, Y., Bouziani, A., Ajmal, Z., H'Maida, K., Boulahya, A., Arahou, 651 M., Bakiz, B., Albourine, A., Fekhaoui, M., 2021b. Synthesis and characterization 652 of arginine-doped heliotrope leaves with high clean-up capacity for crystal violet 653 dye from aqueous media. Water Sci. Technol. 84, 2265–2277. 654 https://doi.org/10.2166/wst.2021.446 655 656 Chan, H.S.O., Ng, S.C., Sim, W.S., Tan, K.L., Tan, B.T.G., 1992. Preparation and characterization of electrically conducting copolymers of aniline and anthranilic 657 acid: evidence for self-doping by x-ray photoelectron spectroscopy. 658 Macromolecules 25, 6029-6034. https://doi.org/10.1021/ma00048a026 659 Donia, A.M., Atia, A.A., Al-amrani, W.A., El-Nahas, A.M., 2009. Effect of structural 660 properties of acid dyes on their adsorption behaviour from aqueous solutions by 661 amine modified silica. J. Hazard. Mater. 161, 1544-1550. 662 https://doi.org/10.1016/j.jhazmat.2008.05.042 663 Doula, M.K., 2007. Synthesis of a clinoptilolite-Fe system with high Cu sorption 664 capacity. Chemosphere 67, 731-740. 665 https://doi.org/10.1016/j.chemosphere.2006.10.072 666 Doumic, L., Salierno, G., Cassanello, M., Haure, P., Ayude, M., 2015. Efficient removal of 667 Orange G using Prussian Blue nanoparticles supported over alumina. Catal. 668 Today 240, 67–72. https://doi.org/10.1016/j.cattod.2014.03.064 669 Fahoul, Y., Tanji, K., Zouheir, M., Mrabet, I.E., Naciri, Y., Hsini, A., Nahali, L., 670 671 Kherbeche, A., 2022. Novel River Sediment@ZnO Co nanocomposite for

672	photocatalytic degradation and COD reduction of crystal violet under visible light.
673	J. Mol. Struct. 1253, 132298. https://doi.org/10.1016/j.molstruc.2021.132298
674	Feng, T., Bavumiragira, J.P., Wambui, M.A., Kabtamu, D.M., László, K., Wang, Y., Li, F.,
675	2020. Hierarchical porous induced competent removal of low concentration azo
676	dye molecules by generating a leachy crystalline structure H-MIL-53(Fe). Chin.
677	Chem. Lett. 31, 2717–2720. https://doi.org/10.1016/j.cclet.2020.04.044
678	Fiol, N., Villaescusa, I., 2009. Determination of sorbent point zero charge: usefulness in
679	sorption studies. Environ. Chem. Lett. 7, 79–84. https://doi.org/10.1007/s10311-
680	008-0139-0
681	Gottlieb, A., Shaw, C., Smith, A., Wheatley, A., Forsythe, S., 2003. The toxicity of textile
682	reactive azo dyes after hydrolysis and decolourisation. J. Biotechnol. 101, 49–56.
683	https://doi.org/10.1016/S0168-1656(02)00302-4
684	Hassan, M.M., Carr, C.M., 2018. A critical review on recent advancements of the removal
685	of reactive dyes from dyehouse effluent by ion-exchange adsorbents.
686	Chemosphere 209, 201–219.
687	https://doi.org/10.1016/j.chemosphere.2018.06.043
688	Hsini, A., Benafqir, M., Naciri, Y., Laabd, M., Bouziani, A., Ez-zahery, M., Lakhmiri, R.,
689	Alem, N.E., Albourine, A., 2021a. Synthesis of an arginine-functionalized
690	polyaniline@FeOOH composite with high removal performance of hexavalent
691	chromium ions from water: Adsorption behavior, regeneration and process
692	capability studies. Colloids Surf. Physicochem. Eng. Asp. 617, 126274.
693	https://doi.org/10.1016/j.colsurfa.2021.126274
694	Hsini, A., Essekri, A., Aarab, N., Laabd, M., Ait Addi, A., Lakhmiri, R., Albourine, A.,
695	2020. Elaboration of novel polyaniline@Almond shell biocomposite for effective
696	removal of hexavalent chromium ions and Orange G dye from aqueous solutions.
697	Environ. Sci. Pollut. Res. 27, 15245–15258. https://doi.org/10.1007/s11356-020-
698	08039-1
699	Hsini, A., Naciri, Y., Benafqir, M., Ajmal, Z., Aarab, N., Laabd, M., Navío, J.A., Puga, F.,
700	Boukherroub, R., Bakiz, B., Albourine, A., 2021b. Facile synthesis and
701	characterization of a novel 1,2,4,5-benzene tetracarboxylic acid doped
702	polyaniline@zinc phosphate nanocomposite for highly efficient removal of
703	hazardous hexavalent chromium ions from water. J. Colloid Interface Sci. 585,
704	560–573. https://doi.org/10.1016/j.jcis.2020.10.036
705	Hsini, A., Naciri, Y., Bouziani, A., Aarab, N., Essekri, A., Imgharn, A., Laabd, M., Navío,
706	J.A., Puga, F., Lakhmiri, R., Albourine, A., 2021c. Polyaniline coated tungsten
707	trioxide as an effective adsorbent for the removal of orange G dye from aqueous
708	media. RSC Adv. 11, 31272–31283. https://doi.org/10.1039/D1RA04135E
709	Hsini, A., Naciri, Y., Laabd, M., Bouziani, A., Navío, J.A., Puga, F., Boukherroub, R.,
710	Lakhmiri, R., Albourine, A., 2021d. Development of a novel PANI@WO $_3$ hybrid
711	composite and its application as a promising adsorbent for Cr(VI) ions removal. J.
712	Environ. Chem. Eng. 9, 105885. https://doi.org/10.1016/j.jece.2021.105885
713	Imgharn, A., ighnih, H., Hsini, A., Naciri, Y., Laabd, M., Kabli, H., Elamine, M.,
714	Lakhmiri, R., Souhail, B., Albourine, A., 2021. Synthesis and characterization of
715	polyaniline-based biocomposites and their application for effective removal of
716	Orange G dye using Adsorption in dynamic regime. Chem. Phys. Lett. 138811.
717	https://doi.org/10.1016/j.cplett.2021.138811

718	Kachangoon, R., Vichapong, J., Santaladchaiyakit, Y., Burakham, R., Srijaranai, S.,
719	2020. An Eco-Friendly Hydrophobic Deep Eutectic Solvent-Based Dispersive
720	Liquid–Liquid Microextraction for the Determination of Neonicotinoid
721	Insecticide Residues in Water, Soil and Egg Yolk Samples. Molecules 25, 2785.
722	https://doi.org/10.3390/molecules25122785
723	Khalfaoui, M., Ghali, A.E., Aguir, C., Mohamed, Z., Baouab, M.H.V., Lamine, A.B., 2015.
724	Study on adsorption of herbicide onto functionalized cellulose extracted from
725	Juncus acutus L. plant: Experimental results and theoretical modeling. Ind. Crops
726	Prod. 67, 169–178. https://doi.org/10.1016/j.indcrop.2015.01.032
727	Kumar, P.A., Chakraborty, S., Ray, M., 2008. Removal and recovery of chromium from
728	wastewater using short chain polyaniline synthesized on jute fiber. Chem. Eng. J.
729	141, 130–140. https://doi.org/10.1016/j.cej.2007.11.004
730	Laabd, M., Brahmi, Y., El Ibrahimi, B., Hsini, A., Toufik, E., Abdellaoui, Y., Abou Oualid,
731	H., El Ouardi, M., Albourine, A., 2021. A novel mesoporous
732	Hydroxyapatite@Montmorillonite hybrid composite for high-performance
733	removal of emerging Ciprofloxacin antibiotic from water: Integrated experimental
734	and Monte Carlo computational assessment. J. Mol. Liq. 338, 116705.
735	https://doi.org/10.1016/j.molliq.2021.116705
736	Laabd, M., Chafai, H., Essekri, A., Elamine, M., Al-Muhtaseb, S.A., Lakhmiri, R.,
737	Albourine, A., 2017. Single and multi-component adsorption of aromatic acids
738	using an eco-friendly polyaniline-based biocomposite. Sustain. Mater. Technol.
739	12, 35–43. https://doi.org/10.1016/j.susmat.2017.04.004
740	Laabd, M., Imgharn, A., Hsini, A., Naciri, Y., Mobarak, M., Szunerits, S., Boukherroub,
741	R., Albourine, A., 2022. Efficient detoxification of Cr(VI)-containing effluents by
742	sequential adsorption and reduction using a novel cysteine-doped
743	PANi@faujasite composite: Experimental study supported by advanced statistical
744	physics prediction. J. Hazard. Mater. 422, 126857.
745	https://doi.org/10.1016/j.jhazmat.2021.126857
746 747	Laksaci, H., Khelifi, A., Belhamdi, B., Trari, M., 2019. The use of prepared activated carbon as adsorbent for the removal of orange G from aqueous solution.
747 748	Microchem. J. 145, 908–913. https://doi.org/10.1016/j.microc.2018.12.001
748	Li, Z., Sellaoui, L., Dotto, G.L., Lamine, A.B., Bonilla-Petriciolet, A., Hanafy, H.,
750	Belmabrouk, H., Netto, M.S., Erto, A., 2019. Interpretation of the adsorption
751	mechanism of Reactive Black 5 and Ponceau 4R dyes on chitosan/polyamide
752	nanofibers via advanced statistical physics model. J. Mol. Liq. 285, 165–170.
753	https://doi.org/10.1016/j.molliq.2019.04.091
754	Liao, G., Li, Q., Xu, Z., 2019. The chemical modification of polyaniline with enhanced
755	properties: A review. Prog. Org. Coat. 126, 35–43.
756	https://doi.org/10.1016/j.porgcoat.2018.10.018
757	Liu, G., Xiangli, F., Wei, W., Liu, S., Jin, W., 2011. Improved performance of
758	PDMS/ceramic composite pervaporation membranes by ZSM-5 homogeneously
759	dispersed in PDMS via a surface graft/coating approach. Chem. Eng. J. 174, 495–
760	503. https://doi.org/10.1016/j.cej.2011.06.004
761	Mall, I.D., Srivastava, V.C., Agarwal, N.K., 2006. Removal of Orange-G and Methyl
762	Violet dyes by adsorption onto bagasse fly ash—kinetic study and equilibrium
763	isotherm analyses. Dyes Pigments 69, 210–223.
764	https://doi.org/10.1016/j.dyepig.2005.03.013

- Mimouni, I., Bouziani, A., Naciri, Y., Boujnah, M., El Belghiti, M.A., El Azzouzi, M., 765 2021. Effect of heat treatment on the photocatalytic activity of α -Fe₂O₃ 766 nanoparticles: towards diclofenac elimination. Environ. Sci. Pollut. Res. 767 https://doi.org/10.1007/s11356-021-16146-w 768 Mobarak, M., Mohamed, E.A., Selim, A.Q., Eissa, M.F., Seliem, M.K., 2019a. 769 Experimental results and theoretical statistical modeling of malachite green 770 adsorption onto MCM-41 silica/rice husk composite modified by beta radiation. 771 J. Mol. Liq. 273, 68-82. https://doi.org/10.1016/j.molliq.2018.09.132 772 Mobarak, M., Mohamed, E.A., Selim, A.Q., Mohamed, F.M., Sellaoui, L., Bonilla-773 Petriciolet, A., Seliem, M.K., 2019b. Statistical physics modeling and 774 775 interpretation of methyl orange adsorption on high-order mesoporous composite of MCM-48 silica with treated rice husk. J. Mol. Liq. 285, 678-687. 776 777 https://doi.org/10.1016/j.molliq.2019.04.116 Mohamed, E.A., Mobarak, M., Kumar, R., Barakat, M.A., Bonilla-Petriciolet, A., Seliem, 778 779 M.K., Selim, A.Q., 2020. Novel hybrid multifunctional composite of chitosan and altered basalt for barium adsorption: Experimental and theoretical studies. 780 781 Colloids Surf. Physicochem. Eng. Asp. 593, 124613. https://doi.org/10.1016/j.colsurfa.2020.124613 782 Naciri, Y., Hsini, A., Bouziani, A., Djellabi, R., Ajmal, Z., Laabd, M., Navío, J.A., Mills, A., 783 Bianchi, C.L., Li, H., Bakiz, B., Albourine, A., 2021. Photocatalytic oxidation of 784 pollutants in gas-phase via Ag₃PO₄ -based semiconductor photocatalysts: Recent 785 progress, new trends, and future perspectives. Crit. Rev. Environ. Sci. Technol. 1-786 44. https://doi.org/10.1080/10643389.2021.1877977 787 Naciri, Y., Hsini, A., Bouziani, A., Tanji, K., El Ibrahimi, B., Ghazzal, M.N., Bakiz, B., 788 789 Albourine, A., Benlhachemi, A., Navío, J.A., Li, H., 2022. Z-scheme WO₃/PANI heterojunctions with enhanced photocatalytic activity under visible light: A depth 790 experimental and DFT studies. Chemosphere 292, 133468. 791 https://doi.org/10.1016/j.chemosphere.2021.133468 792 Narayanan, S., Vijaya, J.J., Sivasanker, S., Kennedy, L.J., Jesudoss, S.K., 2015. 793 794 Structural, morphological and catalytic investigations on hierarchical ZSM-5 zeolite hexagonal cubes by surfactant assisted hydrothermal method. Powder 795 796 Technol. 274, 338-348. https://doi.org/10.1016/j.powtec.2015.01.054 Nasar, A., Mashkoor, F., 2019. Application of polyaniline-based adsorbents for dve 797 798 removal from water and wastewater—a review. Environ. Sci. Pollut. Res. 26, 5333-5356. https://doi.org/10.1007/s11356-018-3990-y 799 800 Niu, X.R., Li, J., Zhang, L., Lei, Z.T., Zhao, X.L., Yang, C.H., 2017. ZSM-5 functionalized in situ with manganese ions for the catalytic oxidation of cyclohexane. RSC Adv 7, 801 802 50619-50625. https://doi.org/10.1039/C7RA10771D Njoya, O., Zhao, S., Qu, Y., Shen, J., Wang, B., Shi, H., Chen, Z., 2020. Performance and 803 804 potential mechanism of Cr(VI) reduction and subsequent Cr(III) precipitation using sodium borohydride driven by oxalate. J. Environ. Manage. 275, 111165. 805 https://doi.org/10.1016/j.jenvman.2020.111165 806 Ravelo-Acuña, D., Fuentes-García, J.A., Yee-Madeira, H.T., Diaz-Cano, A.I., Goya, G.F., 807 808 Santoyo-Salazar, J., 2019. Sonochemical magnetite encapsulation in silica at low irradiation power. Mater. Lett. 250, 103-107. 809
- 810 https://doi.org/10.1016/j.matlet.2019.04.073

811	Renault, F., Sancey, B., Badot, PM., Crini, G., 2009. Chitosan for
812	coagulation/flocculation processes – An eco-friendly approach. Eur. Polym. J. 45,
813	1337–1348. https://doi.org/10.1016/j.eurpolymj.2008.12.027
814	Sahu, S., Sahu, U.K., Patel, R.K., 2019. Modified Thorium Oxide Polyaniline Core–Shell
815	Nanocomposite and Its Application for the Efficient Removal of Cr(VI). J. Chem.
816	Eng. Data 64, 1294–1304. https://doi.org/10.1021/acs.jced.8b01225
817	Saifuddin, M., Bae, J., Kim, K.S., 2019. Role of Fe, Na and Al in Fe-Zeolite-A for
818	adsorption and desorption of phosphate from aqueous solution. Water Res. 158,
819	246–256. https://doi.org/10.1016/j.watres.2019.03.045
820	Salam, M.A., Kosa, S.A., Al-Beladi, A.A., 2017. Application of nanoclay for the adsorptive
821	removal of Orange G dye from aqueous solution. J. Mol. Liq. 241, 469–477.
822	https://doi.org/10.1016/j.molliq.2017.06.055
823	Seliem, M.K., Mobarak, M., 2019. Cr(VI) uptake by a new adsorbent of CTAB-modified
824	carbonized coal: Experimental and advanced statistical physics studies. J. Mol.
825	Liq. 294, 111676. https://doi.org/10.1016/j.molliq.2019.111676
826	Sellaoui, L., Depci, T., Kul, A.R., Knani, S., Ben Lamine, A., 2016. A new statistical
827	physics model to interpret the binary adsorption isotherms of lead and zinc on
828	activated carbon. J. Mol. Liq. 214, 220–230.
829	https://doi.org/10.1016/j.molliq.2015.12.080
830	Sellaoui, L., Dotto, G.L., Wjihi, S., Gonçalves, J.O., Pinto, L.A.A., Lamine, A.B., Erto, A.,
831	2017a. Thermodynamic analysis of single and binary adsorption of Food Yellow 4
832	and Food Blue 2 on CC-chitosan: Application of statistical physics and IAST
833	models. J. Mol. Liq. 232, 499–505. https://doi.org/10.1016/j.molliq.2017.02.103
834	Sellaoui, L., Guedidi, H., Knani, S., Reinert, L., Duclaux, L., Ben Lamine, A., 2015.
835	Application of statistical physics formalism to the modeling of adsorption
836	isotherms of ibuprofen on activated carbon. Fluid Phase Equilibria 387, 103–110.
837	https://doi.org/10.1016/j.fluid.2014.12.018
838	Sellaoui, L., Mechi, N., Lima, É.C., Dotto, G.L., Ben Lamine, A., 2017b. Adsorption of
839	diclofenac and nimesulide on activated carbon: Statistical physics modeling and
840	effect of adsorbate size. J. Phys. Chem. Solids 109, 117–123.
841	https://doi.org/10.1016/j.jpcs.2017.05.019
842	Shyaa, A.A., Hasan, O.A., Abbas, A.M., 2015. Synthesis and characterization of
843	polyaniline/zeolite nanocomposite for the removal of chromium(VI) from
844	aqueous solution. J. Saudi Chem. Soc. 19, 101–107.
845	https://doi.org/10.1016/j.jscs.2012.01.001
846	Stavrinou, A., Aggelopoulos, C.A., Tsakiroglou, C.D., 2018. Exploring the adsorption
847	mechanisms of cationic and anionic dyes onto agricultural waste peels of banana,
848	cucumber and potato: Adsorption kinetics and equilibrium isotherms as a tool. J.
849	Environ. Chem. Eng. 6, 6958–6970. https://doi.org/10.1016/j.jece.2018.10.063
850	Suresh, R., Giribabu, K., Manigandan, R., Stephen, A., Narayanan, V., 2014. Fabrication
851	of Ni–Fe2O3 magnetic nanorods and application to the detection of uric acid.
852	RSC Adv. 4, 17146. https://doi.org/10.1039/c4ra00725e
853	Sutirman, Z.A., Sanagi, M.M., Abd Karim, K.J., Abu Naim, A., Wan Ibrahim, W.A., 2019.
854	Enhanced removal of Orange G from aqueous solutions by modified chitosan
855	beads: Performance and mechanism. Int. J. Biol. Macromol. 133, 1260–1267.
050	https://doi.org/10.1016/j.jibiomaa.0010.04.199

856 https://doi.org/10.1016/j.ijbiomac.2019.04.188

- Tang, D., Zhang, G., 2016. Efficient removal of fluoride by hierarchical Ce–Fe bimetal
 oxides adsorbent: Thermodynamics, kinetics and mechanism. Chem. Eng. J. 283,
 721–729. https://doi.org/10.1016/j.cej.2015.08.019
- Tu, B., Wen, R., Wang, K., Cheng, Y., Deng, Y., Cao, W., Zhang, K., Tao, H., 2020.
 Efficient removal of aqueous hexavalent chromium by activated carbon derived from Bermuda grass. J. Colloid Interface Sci. 560, 649–658.
- 863 https://doi.org/10.1016/j.jcis.2019.10.103
- Wang, Q., Qiu, S., Wang, S., Shang, J., Zhao, R., Wu, X., Chen, W., Zhou, H., Wang, X.,
 2015. Graphene oxide/polyaniline nanotube composites synthesized in alkaline
 aqueous solution. Synth. Met. 210, 314–322.
- 867 https://doi.org/10.1016/j.synthmet.2015.10.017
- Wang, X., Liu, N., Yan, X., Zhang, W., Wei, Y., 2005. Alkali-guided Synthesis of
 Polyaniline Hollow Microspheres. Chem. Lett. 34, 42–43.
 https://doi.org/10.1246/cl.2005.42
- Wjihi, S., Aouaini, F., Almuqrin, A.H., Lamine, A.B., 2020. Physicochemical assessment
 of prednisone adsorption on two molecular composites using statistical physics
 formalism in cosmetics. Arab. J. Chem. 13, 6876–6886.
- 874 https://doi.org/10.1016/j.arabjc.2020.06.040
- Wjihi, S., Sellaoui, L., Bouzid, M., Dhaou, H., Knani, S., Jemni, A., Ben Lamine, A., 2017.
 Theoretical study of hydrogen sorption on LaNi₅ using statistical physics
 treatment: microscopic and macroscopic investigation. Int. J. Hydrog. Energy 42,
 2699–2712. https://doi.org/10.1016/j.ijhydene.2016.10.102
- Xu, H., Zhang, J., Chen, Y., Lu, H., Zhuang, J., Li, J., 2014. Synthesis of polyaniline modified MnO₂ composite nanorods and their photocatalytic application. Mater.
 Lett. 117, 21–23. https://doi.org/10.1016/j.matlet.2013.11.089
- Xu, M.-Y., Jiang, H.-L., Xie, Z.-W., Li, Z.-T., Xu, D., He, F.-A., 2020. Highly efficient
 selective adsorption of anionic dyes by modified β-cyclodextrin polymers. J.
 Taiwan Inst. Chem. Eng. 108, 114–128.
- 885 https://doi.org/10.1016/j.jtice.2020.01.005
- Yeamin, Md.B., Islam, Md.M., Chowdhury, A.-N., Awual, Md.R., 2021. Efficient
 encapsulation of toxic dyes from wastewater using several biodegradable natural
 polymers and their composites. J. Clean. Prod. 291, 125920.
- 889 https://doi.org/10.1016/j.jclepro.2021.125920
- Zhang, J., Gao, J., Song, Q., Guo, Z., Chen, A., Chen, G., Zhou, S., 2016. N-substituted
 Carboxyl Polyaniline Covalent Grafting Reduced Graphene Oxide
 Nanocomposites and Its Application in Supercapacitor. Electrochimica Acta 199,
- 893 70–79. https://doi.org/10.1016/j.electacta.2016.03.003
- Zheng, X., Zheng, H., Zhou, Y., Sun, Y., Zhao, R., Liu, Y., Zhang, S., 2019. Enhanced
 adsorption of Orange G from aqueous solutions by quaternary ammonium grouprich magnetic nanoparticles. Colloids Surf. Physicochem. Eng. Asp. 580, 123746.
 https://doi.org/10.1016/j.colsurfa.2019.123746
- Zheng, Y., Liu, Y., Wang, A., 2012. Kapok Fiber Oriented Polyaniline for Removal of
 Sulfonated Dyes. Ind. Eng. Chem. Res. 51, 10079–10087.
 https://doi.org/10.1021/ie300246m
- Zhou, T., Li, C., Jin, H., Lian, Y., Han, W., 2017. Effective Adsorption/Reduction of
 Cr(VI) Oxyanion by Halloysite@Polyaniline Hybrid Nanotubes. ACS Appl. Mater.
 Interfaces 9, 6030–6043. https://doi.org/10.1021/acsami.6b14079

904

Journal Pre-proof

Highlights

- ✓ A novel PANI@Fe-ZSM-5 hybrid composite was easily elaborated and fully characterized.
- ✓ The adsorption performance of PANI@Fe-ZSM-5 towards OG dye was investigated.
- ✓ The OG dye binding mechanism was assessed by advanced statistical physics modeling.
- ✓ Statistical physics parameters and thermodynamic functions of the adsorption system were studied.
- ✓ PANI@Fe-ZSM-5 composite has excellent adsorption ability and satisfactory reusability.

Johngible

Declaration of Interest Statement

• The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Journal Prevention