



HAL
open science

On prefix palindromic length of automatic words

Anna Frid, Enzo Laborde, Jarkko Peltomäki

► **To cite this version:**

Anna Frid, Enzo Laborde, Jarkko Peltomäki. On prefix palindromic length of automatic words. Theoretical Computer Science, 2021, 891, pp.13-23. 10.1016/j.tcs.2021.08.016 . hal-03572854

HAL Id: hal-03572854

<https://hal.science/hal-03572854>

Submitted on 16 Oct 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

On prefix palindromic length of automatic words

Anna E. Frid^a, Enzo Laborde^a, Jarkko Peltomäki^b

^a*Aix Marseille Univ, CNRS, Centrale Marseille, I2M, Marseille, France*

^b*The Turku Collegium for Science and Medicine TCSM, University of Turku, Turku, Finland; Turku Centre for Computer Science TUCS, Turku, Finland; University of Turku, Department of Mathematics and Statistics, Turku, Finland*

Abstract

The prefix palindromic length $\text{PPL}_{\mathbf{u}}(n)$ of an infinite word \mathbf{u} is the minimal number of concatenated palindromes needed to express the prefix of length n of \mathbf{u} . Since 2013, it is still unknown if $\text{PPL}_{\mathbf{u}}(n)$ is unbounded for every aperiodic infinite word \mathbf{u} , even though this has been proven for almost all aperiodic words. At the same time, the only well-known nontrivial infinite word for which the function $\text{PPL}_{\mathbf{u}}(n)$ has been precisely computed is the Thue-Morse word \mathbf{t} . This word is 2-automatic and, predictably, its function $\text{PPL}_{\mathbf{t}}(n)$ is 2-regular, but is this the case for all automatic words?

In this paper, we prove that this function is k -regular for every k -automatic word containing only a finite number of palindromes. For two such words, namely the paperfolding word and the Rudin-Shapiro word, we derive a formula for this function. Our computational experiments suggest that generally this is not true: for the period-doubling word, the prefix palindromic length does not look 2-regular, and for the Fibonacci word, it does not look Fibonacci-regular. If proven, these results would give rare (if not first) examples of a natural function of an automatic word which is not regular.

Keywords: palindrome, palindromic length, prefix palindromic length, k -automatic word, k -regular sequence, paperfolding word, Rudin-Shapiro word, period-doubling word, Fibonacci word, Fibonacci-automatic word
2010 MSC: 68R15, 68Q45

Email addresses: anna.e.frid@gmail.com (Anna E. Frid),
enzo.laborde_etu.univ-amu@outlook.fr (Enzo Laborde), r@turambar.org (Jarkko Peltomäki)

URL: <http://iml.univ-mrs.fr/~frid/> (Anna E. Frid),
<https://www.utu.fi/en/people/jarkko-peltomaki> (Jarkko Peltomäki)

Preprint submitted to Theoretical Computer Science

August 9, 2021

1. Introduction

A *palindrome* is a finite word $p = p[1] \dots p[n]$ such that $p[i] = p[n-i+1]$ for every i , like *level* or *abba*. We consider decompositions, or factorizations, of a finite word as a concatenation of palindromes. In particular, we are interested in the minimal number of palindromes needed for such a decomposition, which we call the *palindromic length* of a word. For example, the palindromic length of *abbaba* is 3 since this word is not a concatenation of two palindromes, but $abbaba = (abba)(b)(a) = (a)(bb)(aba)$.

In this paper, we consider the palindromic length of prefixes of infinite words. This function of an infinite word $\mathbf{u} = \mathbf{u}[0] \dots \mathbf{u}[n] \dots$ is denoted by $\text{PPL}_{\mathbf{u}}$: here $\text{PPL}_{\mathbf{u}}(n)$ is defined as the palindromic length of the prefix $\mathbf{u}[0] \dots \mathbf{u}[n-1]$ of length n of \mathbf{u} .

The following conjecture was first formulated, in slightly different terms, in a 2013 paper by Puzynina, Zamboni, and the first author [16].

Conjecture 1. *For every aperiodic word \mathbf{u} , the function $\text{PPL}_{\mathbf{u}}(n)$ is unbounded.*

In fact, the paper [16] contains two versions of the conjecture: one with the prefix palindromic length and the other with the palindromic length of any factor of \mathbf{u} . Saarela later proved the equivalence of these two statements [22].

In the same initial paper [16], the conjecture was proven for the case when \mathbf{u} is p -power-free for some p , as well as for a more general case covering almost all aperiodic infinite words. Its proof for all Sturmian words required a special technique [14]. The full conjecture remains unsolved.

While upper bounds on the prefix palindromic length can be obtained by usual techniques [6], any lower bounds [12, 17] or precise formulas for $\text{PPL}_{\mathbf{u}}(n)$ are astonishingly difficult to obtain, except for the following trivial observation.

Remark 1. *If an infinite word \mathbf{u} contains palindromes of length at most K , then $\text{PPL}_{\mathbf{u}}(n) \geq n/K$ for all n .*

Up to our knowledge, the only nontrivial previously known infinite word whose prefix palindromic length has been found precisely [13] is the Thue-Morse word with its many beautiful properties [5]. This sequence is 2-automatic, and so it was not surprising that its prefix palindromic length

is 2-regular and its first differences are 2-automatic. Although the prefix palindromic length does not fall into the class of functions of k -automatic words which are known to always be k -regular [8], we are not aware of any natural functions which would not have this property.

In this paper, we explore the limits of the method used for the Thue-Morse word by considering other automatic words. We prove that $\text{PPL}(n)$ is k -regular for every k -automatic word containing a finite number of distinct palindromes and find this function for the paperfolding word and the Rudin-Shapiro word. At the same time, we also give computational results allowing to conjecture that for the period-doubling word, which contains infinitely many palindromes, the prefix palindromic length is *not* 2-regular, and for the Fibonacci word, it is not Fibonacci-regular. At the very least, if a regularity exists, it must be very complicated. If in at least one of these examples the function will be proven to be not regular, it would give a first example of a reasonable easily defined function of an automatic word which is not regular.

2. Automatic words

Throughout this paper, we use the notation $u[i..j] = u[i] \dots u[j]$ for a factor of a finite or infinite word u starting at position i and ending at j . Note that for technical reasons, we start numbering symbols of finite words with 1 and of infinite words with 0.

Definition 1. Let \mathbf{u} be an infinite word. Then we define the *PPL-difference sequence* $d_{\mathbf{u}}$ of \mathbf{u} by setting $d_{\mathbf{u}}(n) = \text{PPL}_{\mathbf{u}}(n+1) - \text{PPL}_{\mathbf{u}}(n)$ for $n \geq 0$. Notice that we always have $\text{PPL}_{\mathbf{u}}(1) = 1$, and setting $\text{PPL}_{\mathbf{u}}(0) = 0$ by convention, we get $d_{\mathbf{u}}(0) = 1$.

The following lemma was first proven in the 2015 conference version of the paper [20] and then generalised by Saarela [22, Lemma 6].

Lemma 1. *For every word \mathbf{u} and for every $n \geq 0$, we have*

$$\text{PPL}_{\mathbf{u}}(n) - 1 \leq \text{PPL}_{\mathbf{u}}(n+1) \leq \text{PPL}_{\mathbf{u}}(n) + 1.$$

Therefore a PPL-difference sequence can only take the values -1 , 0 , or 1 . We prefer to use the alphabet $\{-, 0, +\}$ in place of $\{-1, 0, 1\}$. So, the PPL-difference can be considered as an infinite word over a three-letter alphabet; in particular, this word is useful for many algorithms related to palindromes [7].

As the name suggests, a word $\mathbf{u} = \mathbf{u}[0] \cdots \mathbf{u}[n] \cdots$ is called *k-automatic* if there exists a deterministic finite automaton A such that every symbol $\mathbf{u}[n]$ of \mathbf{u} can be obtained as the output of A with the base- k representation of n as the input. For the technical details of this definition and for basic examples, we refer the reader to [3]. In this paper, we mostly do not use this definition but several equivalent ones. To introduce them, we need more notions.

Definition 2. A *morphism* $\varphi: \Sigma^* \rightarrow \Delta^*$ is a map satisfying $\varphi(xy) = \varphi(x)\varphi(y)$ for all words $x, y \in \Sigma^*$. Clearly, a morphism is uniquely determined by images of symbols of Σ and can be naturally extended to the set of infinite words over Σ . If there exists a k such that all images of symbols are of length k , the morphism is called *k-uniform*; a 1-uniform morphism is called a *coding*.

If for some morphism $\varphi: \Sigma^* \rightarrow \Sigma^*$ and for a letter $a \in \Sigma$ the image $\varphi(a)$ starts with a , then there exists at least one finite or infinite word u starting with a which is a fixed point of φ , that is, it satisfies the equation $u = \varphi(u)$. If in addition φ is k -uniform for $k \geq 2$, the fixed point starting with a is unique and is denoted as $\varphi^\omega(a)$.

The following statement is a combination of two results. The case when ψ is a coding is Cobham's theorem [9], which can also be found in the monograph of Allouche and Shallit [3] as Theorem 6.3.2. The case when ψ is a m -uniform morphism for $m > 1$ is a combination of Cobham's theorem and Corollary 6.8.3 of the same monograph.

Theorem 1. *An infinite word \mathbf{u} is k-automatic if and only if $\mathbf{u} = \psi(\varphi^\omega(a))$ for some k-uniform morphism φ and a uniform morphism ψ . Moreover, the morphisms can always be chosen so that ψ is a coding.*

If $\mathbf{u} = \psi(\varphi^\omega(a))$, where the morphisms φ and ψ are not obliged to be uniform, the word \mathbf{u} is called *morphic*. As the previous theorem shows, the class of morphic words includes all k -automatic words for all k .

Definition 3. The *k-kernel* $\ker_k(\mathbf{u})$ of an infinite word $\mathbf{u} = \mathbf{u}[0] \cdots \mathbf{u}[n] \cdots$ is the set of arithmetic subsequences of \mathbf{u} with differences of the form k^e and starting positions inferior to the difference:

$$\ker_k(\mathbf{u}) = \{(\mathbf{u}[k^e n + b])_{n \geq 0} : e \geq 0, 0 \leq b < k^e\}.$$

An infinite word \mathbf{u} is k -automatic if and only if $\ker_k(\mathbf{u})$ is finite [3, Thm. 6.6.2].

In what follows, we will need and use the equivalent definitions of a k -automatic words based on uniform morphisms and on the k -kernel.

Example 1. For the Thue-Morse word $\mathbf{t} = 0110100110010110 \cdots$, which is 2-automatic, the three definitions work as follows:

- The definition involving the automaton: the symbol $\mathbf{t}[n]$, $n = 0, 1, \dots$, is 0 if the number of 1's in the binary representation of n is even and 1 if it is odd.
- The definition involving morphisms: $\mathbf{t} = \sigma^\omega(0)$, where $\sigma(0) = 01$ and $\sigma(1) = 10$; the coding ψ from the formula $\mathbf{t} = \psi(\sigma^\omega(0))$ here is trivial ($\psi(0) = 0$, $\psi(1) = 1$) and can be omitted.
- The definition involving the 2-kernel: \mathbf{t} can be described as *the* word starting with 01 and obtained by alternating the symbols of \mathbf{t} and of the word $\bar{\mathbf{t}} = 1001 \cdots$ obtained from \mathbf{t} by exchanging 0's and 1's. It is not difficult to see that the 2-kernel of \mathbf{t} contains only two elements: \mathbf{t} and $\bar{\mathbf{t}}$.

The following definition is closely related to automatic words.

Definition 4. A \mathbb{Z} -valued sequence is k -regular if the \mathbb{Z} -module generated by its k -kernel is finitely generated.

This definition implies in particular that k -automatic sequences are k -regular (we may always assume that a word is over an integer alphabet). A sequence is k -automatic if and only if it is a bounded k -regular sequence [3, Thm. 16.1.5].

Many sequences related to k -automatic sequences are k -regular, as it follows from an important decidability result by Charlier, Rampersad, and Shallit [8]. In particular, this is true for the function of factor complexity defined as the number of factors of length n of the word for each n and for the number of distinct palindromes of length n in the word. In fact, the latter function is even k -automatic since it is bounded [2]. Thus it is natural to ask if the sequence $\text{PPL}_{\mathbf{u}}$ is k -regular when \mathbf{u} is k -automatic. The next lemma shows that in order to study this question, it suffices to study the PPL-difference sequence.

Lemma 2. *Let \mathbf{u} be an infinite word. Then the sequence $\text{PPL}_{\mathbf{u}}$ is k -regular if and only if the PPL-difference sequence $d_{\mathbf{u}}$ is k -automatic.*

Proof. The set of k -regular sequences over \mathbb{Z} is closed under componentwise shift, sum, and difference [3, Thm. 16.2.1, Thm. 16.2.5]. Therefore $\text{PPL}_{\mathbf{u}}$ is k -regular if and only if $d_{\mathbf{u}}$ is k -regular. By Lemma 1, the sequence $d_{\mathbf{u}}$ is bounded. The conclusion follows from the above-cited fact that a bounded k -regular sequence is k -automatic [3, Thm. 16.1.5]. \square

The first author studied in [12, 13] the PPL-difference sequence $d_{\mathbf{t}}$ of the Thue-Morse word \mathbf{t} from Example 1 and characterized it as the fixed point of the following 4-uniform morphism:

$$\begin{cases} + \mapsto ++0-, \\ 0 \mapsto ++--, \\ - \mapsto +0--. \end{cases}$$

This means in particular that $d_{\mathbf{t}}$ is 4-automatic and thus 2-automatic [3, Thm. 6.6.4]. Hence $\text{PPL}_{\mathbf{t}}$ is 2-regular. This result is so far the only one that completely determines the functions $\text{PPL}_{\mathbf{u}}$ and $d_{\mathbf{u}}$ for any nontrivial infinite word \mathbf{u} .

Notice that the result on the Thue-Morse word is not covered by the main result of this paper, since the Thue-Morse word contains infinitely many palindromes. Every prefix of length 4^n of the Thue-Morse word is a palindrome, so Theorem 2 below does not apply to it.

3. Automatic first differences

The following theorem is the main result of this paper.

Theorem 2. *If a k -automatic word \mathbf{u} contains a finite number of distinct palindromes, then the PPL-difference sequence $d_{\mathbf{u}}$ is k -automatic.*

Proof. Let p be the length of the longest palindrome in \mathbf{u} . Then for every index n , the last palindrome in an optimal decomposition of $\mathbf{u}[0..n-1]$ as a product of palindromes starts at one of the positions $\mathbf{u}[n-p]$, \dots , $\mathbf{u}[n-1]$. Thus $\text{PPL}_{\mathbf{u}}(n)$ is determined by $\text{PPL}(n-p)$, \dots , $\text{PPL}(n-1)$ and the word $\mathbf{u}[n-p..n-1]$ (we will often omit the subscripts in proofs to improve readability). This simple consideration is a base for the following proposition.

Proposition 1. *For every n such that $n \geq m + p$, the number $\text{PPL}_{\mathbf{u}}(n)$ is uniquely determined by the numbers $\text{PPL}_{\mathbf{u}}(m)$, $d_{\mathbf{u}}(m)$, $d_{\mathbf{u}}(m + 1)$, \dots , $d_{\mathbf{u}}(m + p - 1)$, and the word $\mathbf{u}[m..n - 1]$. The number $d_{\mathbf{u}}(n)$ is uniquely determined by $d_{\mathbf{u}}(m)$, $d_{\mathbf{u}}(m + 1)$, \dots , $d_{\mathbf{u}}(m + p - 1)$, and the word $\mathbf{u}[m..n]$.*

Proof. Let us prove the first statement. Clearly, for every i such that $i \leq p$, we have

$$\text{PPL}(m + i) = \text{PPL}(m) + d(m) + d(m + 1) + \dots + d(m + i - 1),$$

so that $\text{PPL}(m + 1)$, \dots , $\text{PPL}(m + p)$ can be reconstructed from $\text{PPL}(m)$, $d(m)$, $d(m + 1)$, \dots , $d(m + p - 1)$. Now let us proceed by induction on $n \geq m + p$. The preceding computation establishes the base case. Since there are no palindromes in \mathbf{u} of length greater than p , we have

$$\text{PPL}(n) = \min\{\text{PPL}(n - k) + 1 : k = 1, \dots, p, \mathbf{u}[n - k..n - 1] \text{ is a palindrome}\}. \quad (1)$$

The numbers $\text{PPL}(n - k) + 1$ are determined by $\text{PPL}(m)$, $d(m)$, \dots , $d(m + p - 1)$, and $\mathbf{u}[n - p..n - 1]$ by hypothesis. The induction step is complete.

To prove the second statement, we replace $\text{PPL}(m)$ in the previous paragraph by a parameter P and let $\text{PPL}(m + i) - P = D(i)$ for all $i \geq 0$, so that $D(i) = d(m) + d(m + 1) + \dots + d(m + i - 1)$. Then for $i \leq p$, the number $D(i)$ can be found directly as the sum of the known values of the sequence d . Now for $n \geq m + p$, that is, for $i = n - m \geq p$, suppose that the values of $D(j)$ are known for all $j < i$. The claim is true for $i = p$, that is, for $n = m + p$, establishing the base case. For the induction step, it suffices to rewrite (1) as

$$P + D(i) = \min\{P + D(i - k) + 1 : k = 1, \dots, p, \mathbf{u}[n - k..n +] \text{ is a palindrome}\}$$

and to subtract P to obtain $D(i)$ as a function of the previous values of D and the word $\mathbf{u}[n - p..n - 1]$:

$$D(i) = \min\{D(i - k) + 1 : k = 1, \dots, p, \mathbf{u}[n - k..n - 1] \text{ is a palindrome}\}.$$

Now it remains to combine this expression for i and for $i + 1$ and to use the formula $d(n) = D(i + 1) - D(i)$ to obtain the needed statement. \square

By Theorem 1, we may suppose that $\mathbf{u} = \psi(\varphi^\omega(a))$, where $\psi: \Sigma \rightarrow \Delta$ is a coding and $\varphi: \Sigma \rightarrow \Sigma^k$ is a k -uniform morphism over an alphabet Σ .

Without loss of generality, by passing from φ to a power of φ if necessary, we may assume that $p < k$. Let

$$\Lambda = \{\psi(\varphi(a)) : a \in \Sigma\}.$$

The word \mathbf{u} is a concatenation of these Λ -blocks of length k , and we consider \mathbf{u} as $\mathbf{u} = U[0] \cdots U[N] \cdots$ with $U[i] \in \Lambda$.

Consider an occurrence $\mathbf{u}[m..n]$, where $n \geq m + p$, of a factor v of \mathbf{u} . We define the *type* of this occurrence as the sequence $d_{\mathbf{u}}[m..m+p-1]$. Clearly, for each word v , its occurrences have at most 3^p different types; we denote the set of possible types of v by $T(v)$. Notice that the words $U[0], U[1], \dots$ have types because their lengths are greater than p .

The following proposition is a direct corollary of Proposition 1.

Proposition 2. *For every $N > 0$, the type of the occurrence $U[N]$ is determined by the word $U[N]$, the word $U[N-1]$, and the type of $U[N-1]$.*

This proposition can be interpreted as follows: given a word $U[0] \cdots U[N] \cdots$ and the type of $U[0]$, we can uniquely determine the types of $U[1], U[2]$ and so on, and thus, due to Proposition 1, find the PPL-difference sequence d . The process can be described by a transducer with

- set of states $\{(A, t) : A \in \Lambda, t \in T(A)\} \cup \{S\}$, where S is a special starting state;
- input alphabet Λ ;
- output set $\{-, 0, +\}^k$; and
- set of transitions defined as follows:
 - The starting transition marked as $U[0]|d_{\mathbf{u}}[0..k-1]$ goes from S to the state $(U[0], d[0..p-1])$;
 - A state (A, t) is linked to a state (B, t') by a transition marked as $B|w$ if a Λ -block A of type t is followed by a Λ -block B of type t' in \mathbf{u} and the respective block of length k in d is w (meaning in particular that t' is a prefix of w).

The transitions are well defined due to Propositions 1 and 2, and the number of states is finite as $\#\Lambda \leq \#\Sigma$ and each word in Λ has at most 3^p types. It is

evident that the transducer describes the construction of d from the Λ -blocks of \mathbf{u} .

Since the sequence of Λ -blocks of \mathbf{u} is k -automatic by the construction, we see that the sequence d is obtained by feeding it to a uniform transducer (a uniform transducer outputs only words of common length). By a theorem of Cobham [9] (see also [3, Thm. 6.9.2] and the discussion preceding it), a uniform transduction of a k -automatic sequence is again k -automatic, so we conclude that d is k -automatic. Notice that if we replaced k by its power, we still obtain the same conclusion as a sequence is k^ℓ -automatic if and only if it is k -automatic [3, Thm. 6.6.4]. \square

Example 2. Consider the 2-automatic fixed point

$$\mathbf{u} = \mu^\omega(a) = abbcbccabccacaab \cdots$$

of the morphism

$$\mu: \begin{cases} a \mapsto ab, \\ b \mapsto bc, \\ c \mapsto ca. \end{cases}$$

It is not difficult to see that the longest palindromes in \mathbf{u} are of length 3, so, in order to construct the transducer of the proof of Theorem 2, we consider \mathbf{u} as a fixed point of the 4-uniform morphism

$$\mu^2: \begin{cases} a \rightarrow abbc, \\ b \rightarrow bcca, \\ c \rightarrow caab. \end{cases}$$

For the alphabet Λ , we now have $\Lambda = \{A, B, C\}$ where $A = abbc$, $B = bcca$, $C = caab$. The first values of $\text{PPL}_{\mathbf{u}}(n)$ starting from $n = 0$ are 0, 1, 2, 2, 3, 3, 3, 4, 5, and thus the sequence $d_{\mathbf{u}}$ starts with ++0+00++. Hence the first transition of the transducer is

$$S \xrightarrow{A|++0+} (A, ++0).$$

The next transition should describe the first differences in B which follows an occurrence of A with type ++0. It can be checked that it is

$$(A, ++0) \xrightarrow{B|00++} (B, 00+).$$

Continuing to consider blocks and their types in their order of appearance in \mathbf{u} , we can analogously find that every symbol of Λ can have four types $++0$, $00+$, $0+0$, $-+0$. Thus the transducer has 13 states. The possible transitions from A are the following:

$$\begin{aligned} (A, 00+) &\xrightarrow{A|++0+} (A, ++0), & (A, 0+0) &\xrightarrow{B|00++} (B, 00+), \\ (A, 00+) &\xrightarrow{B|-+0+} (B, -+0), & (A, ++0) &\xrightarrow{B|00++} (B, 00+), \\ (A, 00+) &\xrightarrow{C|0+0+} (C, 0+0), & (A, -+0) &\xrightarrow{B|00++} (B, 00+). \end{aligned}$$

In particular, a block A of any type except for $00+$ can be followed only by the block B of type $00+$.

The remaining transitions are obtained by changing the letters in the above transitions according to the cycle $A \rightarrow B \rightarrow C \rightarrow A$ since the initial morphism μ is symmetric with respect to this cycle. For example, from the transition

$$(A, 00+) \xrightarrow{A|++0+} (A, ++0)$$

we obtain in this fashion the transition

$$(B, 00+) \xrightarrow{B|++0+} (B, ++0).$$

This gives a total of 19 transitions. To be completely rigorous, we should prove that no additional states and transitions exist. Suppose the opposite and consider the first transition which is not as above. Let it be a transition from $(A, 0+0)$ to (A, t) for some t (any other combination can be considered analogously). The first time this transition is taken must be preceded by a transition from the list, that is, by the transition $(B, 00+) \rightarrow (A, 0+0)$. Hence BAA should be a factor of \mathbf{u} , but it is easy to check that this is not the case. Similarly if there is a transition $(A, 0+0) \rightarrow (C, t)$, then we find that \mathbf{u} should contain the forbidden factor BAC , and so on.

It can be shown that the output of the transducer equals the infinite word $\psi_{\mathbf{u}}(\varphi_{\mathbf{u}}^{\omega}(s))$, where

$$\varphi_{\mathbf{u}}: \begin{cases} s \mapsto su, \\ u \mapsto eu, \\ e \mapsto du, \\ d \mapsto hu, \\ h \mapsto eu \end{cases}$$

and

$$\psi_{\mathbf{u}}: \begin{cases} s, e \mapsto ++0+, \\ d \mapsto 0+0+, \\ u \mapsto 00++, \\ h \mapsto -+0+. \end{cases}$$

Here the symbols s, d, e, u, h mean respectively the starting block s of \mathbf{u} , the situation when the next block of \mathbf{u} is down (d), equal (e) or up (u) to the previous block according to the cyclic order $A < B < C < A$. And h (for “high”) stands for the situation when the block is exactly the third in an ascending sequence of blocks.

In this example, we managed to construct the morphisms for $d_{\mathbf{u}}$ because we understand the underlying structure. Unfortunately, Cobham’s theorem used in the proof of Theorem 2 only gives a hyperexponential bound on the number of the states of an automaton generating $d_{\mathbf{u}}$. Hence the theorem itself does not give a practical way to find $d_{\mathbf{u}}$ and the associated morphisms. In what follows, we consider two well-known examples and find their prefix palindromic length “by hand”.

4. Classic examples

The examples considered in this section, namely, the paperfolding word and the Rudin-Shapiro word, are closely related to each other, and are known to contain a finite number of distinct palindromes [1].

4.1. Paperfolding word

Recall that the paperfolding word \mathbf{u}_{pf} is the 2-automatic word

$$\mathbf{u}_{pf} = \psi(\varphi_{pf}^\omega(a)) = 0010011000110110 \dots ,$$

where

$$\varphi_{pf}: \begin{cases} a \mapsto ab, \\ b \mapsto cb, \\ c \mapsto ad, \\ d \mapsto cd, \end{cases}$$

and the coding ψ is defined as $\psi(a) = \psi(b) = 0, \psi(c) = \psi(d) = 1$.

The longest palindromes in the paperfolding word are of length 13, so Theorem 2 can be applied to it: its first difference sequence d_{pf} is 2-automatic. The blocks considered in the proof of Theorem 2 could be of length 16, since it is the smallest integer power of 2 which exceeds the length of the longest palindrome. However, to simplify the transducer, it is more convenient to consider blocks of length 64.

Theorem 3. *The sequence d_{pf} over the alphabet $\{-, 0, +\}$ is equal to $d_{pf} = \gamma_{pf}(\mu_{pf}^\omega(a_0))$, where*

$$\mu_{pf}: \begin{cases} a_0 \mapsto a_0b_a, \\ a_b \mapsto a_b b_a, & b_a \mapsto c_b b_c, & c_b \mapsto a_b d_a, & d_a \mapsto c_b d_c, \\ a_d \mapsto a_d b_a, & b_c \mapsto c_d b_c, & c_d \mapsto a_d d_a, & d_c \mapsto c_d d_c \end{cases}$$

and

$$\gamma_{pf}: \begin{cases} a_0 \mapsto +0+0-+0+000-++0--P00+00+0-+000+000+00000-0++-+0-, \\ a_b \mapsto 0+++0+00+00-0+0000P00+00+0-+000+000+00000-0++-+0-, \\ a_d \mapsto 0+00000+00000+000-P00+00+0-+000+000+00000-0++-+0-, \\ b_a \mapsto 0+++0+00+00-0+0000P+-+0-0+000+000+0+-+0-000+000+0-, \\ b_c \mapsto +00+-00+0000+0000-P+-+0-0+000+000+0+-+0-000+000+0-, \\ c_b \mapsto 0+++0+00+00-0+0000P00+00+0-+000+000+00000-0++-+00, \\ c_d \mapsto 0+00000+00000+000-P00+00+0-+000+000+00000-0++-+00, \\ d_a \mapsto 0+++0+00+00-0+0000P+-+0-0+000+000+0+-+0-000+000+00, \\ d_c \mapsto +00+-00+0000+0000-P+-+0-0+000+000+0+-+0-000+000+00 \end{cases}$$

with $P = 0+00+00-0++-0+0$.

Proof. Let \mathbf{v} be the fixed point $\varphi_{pf}^\omega(a)$ of φ_{pf} and \mathbf{w} be the fixed point μ_{pf}^ω of μ_{pf} starting with a_0 . The word \mathbf{v} is obtained from \mathbf{w} by the identification $a_0, a_b, a_d \mapsto a$, $b_a, b_c \mapsto b$, $c_b, c_d \mapsto c$, $d_a, d_c \mapsto d$. The subscript of a letter occurring in \mathbf{w} indicates that the letter (after identification) in \mathbf{v} is preceded by the letter indicated by the subscript, that is, a_b corresponds to a preceded by b in \mathbf{v} etc. The letter a_0 simply corresponds to the first occurrence of a in \mathbf{v} .

We know by Theorem 2 that a transducer T mapping \mathbf{u}_{pf} to d_{pf} exists. Here we set the parameter k of the proof of Theorem 2 to equal 2^6 . This

means that T outputs blocks of length 64. Write $\mathbf{u}_{pf} = U[0]U[1]\cdots$ as a concatenation of Λ -blocks $U[i]$. For the claim, it suffices to prove that the output of T on $U[0]U[1]\cdots U[n]$ equals $\gamma_{pf}(\mathbf{w}[0..n])$ for all n .

The factors of \mathbf{v} of length 2 appear in its prefix of length 13. This means that the prefix of \mathbf{u}_{pf} of length 13×2^6 , which is a concatenation of Λ -blocks, contains all possible adjacent Λ -blocks at least once. We can directly check that $\gamma_{pf}(\mathbf{w}[0..12])$ coincides with the prefix of d_{pf} of length 13×2^6 meaning that $\gamma_{pf}(\mathbf{w}[0..12])$ equals the output of T on $U[0]\cdots U[12]$. Let us now make the following observation. The prefix of length 18 of each γ_{pf} -image is followed by the word $P = 0+00+00-0+-0+0$ of length 15. Since the longest palindrome in \mathbf{u}_{pf} has length 13, Proposition 1 implies that for $n = 1, \dots, 12$, the type of $U[n]$ depends on P and $U[n-1]$, not on the type of $U[n-1]$. Since P occurs in the same position in every γ_{pf} -image, we see that the type of $U[n]$ depends only on $U[n-1]$.

Let $k \geq 12$ be such that the type of $U[n]$ depends only on $U[n-1]$ and that the output of T on $U[0]\cdots U[n]$ matches $\gamma_{pf}(\mathbf{w}[0..n])$ for all $n = 1, \dots, k$. By Proposition 1, the type of $U[n+1]$ is determined by $U[n]$ and its type. Since T outputs $\gamma_{pf}(\mathbf{w}[n])$ when reading $U[n]$ and $\gamma_{pf}(\mathbf{w}[n])$ contains P at position 18 independently of the letter $\mathbf{w}[n]$, it follows from Proposition 1 that the type of $U[n+1]$ depends only on $U[n]$. Since $k \geq 12$ and all factors of \mathbf{v} of length 2 appear in its prefix of length 13, there exists $t \leq 11$ such that $U[t] = U[n]$ and $U[t+1] = U[n+1]$. The output of T on the transition $U[n] \rightarrow U[n+1]$ must match that of $U[t] \rightarrow U[t+1]$ because T is deterministic and the type of the Λ -block is irrelevant in both cases. Therefore T outputs $\gamma_{df}(\mathbf{w}[t+1])$ when reading $U[n+1]$. It now suffices to show that $\mathbf{w}[n+1] = \mathbf{w}[t+1]$ in order to conclude by induction that $d_{pf} = \gamma_{pf}(\mathbf{w})$.

We have $U[i] = \psi(\varphi_{pf}^6(\mathbf{v}[i]))$ for all i . It is straightforward to verify that ψ is injective on the set of Λ -blocks and that φ_{pf}^6 is injective, so we deduce from the equalities $U[n] = U[t]$ and $U[n+1] = U[t+1]$ that $\mathbf{v}[n] = \mathbf{v}[t]$ and $\mathbf{v}[n+1] = \mathbf{v}[t+1]$. From the first paragraph of the proof, we infer that $\mathbf{w}[n+1] = \mathbf{w}[t+1]$. The claim follows. \square

4.2. Rudin-Shapiro word

The Rudin-Shapiro word \mathbf{u}_{rs} is the 2-automatic word

$$\mathbf{u}_{rs} = \psi(\varphi_{rs}^\omega(a)) = 00010010000111010\cdots,$$

where

$$\varphi_{rs}: \begin{cases} a \rightarrow ab, \\ b \rightarrow ac, \\ c \rightarrow db, \\ d \rightarrow dc, \end{cases}$$

and the coding ψ is defined by $\psi(a) = \psi(b) = 0$, $\psi(c) = \psi(d) = 1$.

The longest palindromes in the Rudin-Shapiro word are of length 14, so Theorem 2 can be applied to it: its first difference sequence d_{rs} is 2-automatic. The following theorem describes it.

Theorem 4. *The sequence d_{rs} over the alphabet $\{-, 0, +\}$ is equal to*

$$d_{rs} = \gamma_{rs}(\mu_{rs}^\omega(A)),$$

where

$$\mu_{rs}: \begin{cases} A \rightarrow AB, \\ B \rightarrow CD, \\ C \rightarrow EB, \\ D \rightarrow ED, \\ E \rightarrow CB \end{cases}$$

and

$$\gamma_{rs}: \begin{cases} A \mapsto +00+00000-++00-++00-+0+00+00+00+-0+00-+00+-0+0+0-0+0P, \\ B \mapsto 0+0-0++-00+0+0-++00-+0+00+00+00+0+0-0++-00+0+0-+000P, \\ C \mapsto -0+00-+00+-0+0+00+00-++-+00+000+0-+000+-+0-0+0+0-0+0P, \\ D \mapsto -0+00-+00+-0+0+00+00-++-+00+000+0+0-0+-00+0+0-+000P, \\ E \mapsto 0+0-0++-00+0+0-++00-+0+00+00+00+-0+00-+00+-0+0+0-0+0P. \end{cases}$$

with $P = 0-+00+00+00+$.

Proof. As previously for the paperfolding word, we define a new morphism ν_{rs} obtained from φ_{rs} by adding to each letter information on the preceding one:

$$\nu_{rs}: \begin{cases} a_0 \rightarrow a_0b_a; \\ a_b \rightarrow a_cb_a; & b_a \rightarrow a_bcb_a; & c_a \rightarrow d_bbd; & d_b \rightarrow d_ccd; \\ a_c \rightarrow a_bbd; & b_d \rightarrow a_cca; & c_d \rightarrow d_cb_d; & d_c \rightarrow d_bcd. \end{cases}$$

The morphism φ_{rs} and its fixed point \mathbf{v} are obtained from ν_{rs} and its fixed point \mathbf{w} by the identification $a_0, a_b, a_c \mapsto a, b_a, b_d \mapsto b, c_a, c_d \mapsto c, d_b, d_c \mapsto d$.

We proceed as in the proof of Theorem 3. We set the parameter k of the proof of Theorem 2 to equal 2^6 . Write $\mathbf{u}_{rs} = U[0]U[1] \cdots$ as a concatenation of Λ -blocks $U[i]$. All factors of \mathbf{v} of length 2 appear in its prefix of length 14, so all adjacent Λ -block appear in the prefix of \mathbf{u}_{rs} of length 14×2^6 . Taking the prefix of length 14×2^6 of d_{rs} , we observe that it coincides with the word $\delta_{rs}(\mathbf{w}[0..13])$ where

$$\delta_{rs}: \begin{cases} a_0 \mapsto & +00+00000-++00-++00-++00+00+00+00+-0+00-+00+-0+0+0-0+00-+00+00+00+, \\ b_a, c_d \mapsto & 0+0-0+-00+0+0-++00-++00+00+00+0+0-0+-00+0+0-+000+0-+00+00+00+, \\ a_b, d_c \mapsto & -0+00-+00+-0+0+00+00-++-+00+000+0-+000+-+0-0+0+0-0+00-+00+00+00+, \\ c_a, b_d \mapsto & -0+00-+00+-0+0+00+00-++-+00+000+0+0-0+-00+0+0-+000+0-+00+00+00+, \\ a_c, d_b \mapsto & 0+0-0+-00+0+0-++00-++00+00+00+0+-0+00-+00+-0+0+0-0+00-+00+00+00+. \end{cases}$$

Each δ_{rs} -image of a letter ends with the word $0-+00+00+00+$ of length 12. This word P is shorter than the longest palindrome in \mathbf{u}_{rs} , so we cannot directly deduce that the type of the block $U[n]$ depends only on $U[n-1]$. By Proposition 1, the number $d_{rs}((n-1)2^6)$ depends on the previous 14 values of d_{rs} that correspond to a palindrome ending at position $(n-1)2^6$ of \mathbf{u}_{rs} . We claim that such a palindrome has length at most 12. This implies that $d_{rs}((n-1)2^6)$ is determined by the previous 12 values of d_{rs} . If such a palindrome has length greater than 12, it must be of length 14 as \mathbf{u}_{rs} contains no palindromes of length 13. Two of the Λ -blocks end with 110100011101 and the remaining two end with 001011100010. It is straightforward to see that neither suffix can be covered by a palindrome of length 14 in the required way. Thus the palindrome has length at most 12. A similar argument can be repeated for the number $d_{rs}((n-1)2^6 + 1)$. Since each δ_{rs} -image ends with P of length 12, we deduce by Proposition 1 that the type of $U[n]$ depends only on $U[n-1]$ not on its type. We may now repeat the arguments of the proof of Theorem 3 and conclude that $d_{rs} = \delta_{rs}(\mathbf{w})$ (indeed φ_{rs} is injective and ψ is injective on the set of Λ -blocks).

To prove the theorem, it remains to notice the symmetry in δ_{rs} and identify b_a, c_d as B, a_b, d_c as C, c_a, b_d as D, a_c, d_b as E . After renaming a_0 as A , we see that $\nu_{rs}^\omega(a_0)$ equals $\mu_{rs}^\omega(A)$ after this identification. Thus $\delta_{rs}(\nu_{rs}^\omega(a_0)) = \gamma_{rs}(\mu_{rs}^\omega(A))$ and the claim follows. \square

5. Computational results and conjectures

This section contains results of computational experiments which thus do not give any theorems but only conjectures. For a fast computation of the prefix palindromic length, we used an implementation [24] of the Eertree data structure [20]; see also [21] for related algorithms.

5.1. Period-doubling word

Theorem 2 and the result for the Thue-Morse word allow to conjecture that the PPL-difference sequence $d_{\mathbf{u}}$ of a k -automatic word is always k -automatic. The following example, however, suggests that this is not the case.

The period-doubling word \mathbf{u}_{pd} is the 2-automatic word

$$\mathbf{u}_{pd} = \varphi_{pd}^\omega(a) = abaaabababaaabaa \cdots,$$

where

$$\varphi_{pd}: \begin{cases} a \rightarrow ab, \\ b \rightarrow aa. \end{cases}$$

Clearly, it contains infinitely many palindromes, including all prefixes of length $2^n - 1$. Thus Theorem 2 does not apply to it.

In our computational experiment, we estimate the cardinality of the 2-kernel of the PPL-difference sequence d_{pd} of \mathbf{u}_{pd} . If d_{pd} is 2-automatic, its 2-kernel must be finite. We estimate the number of its elements as follows.

Let $m \geq 1$. Consider a sequence $(d_{pd}[2^e n + b])_n$ from the 2-kernel of d_{pd} and compute its prefix $d_{e,b}$ such that $2^e n + b \leq 4^m$. Only finitely many different words $d_{e,b}$ are nonempty: in particular, all such words of length at least 2 correspond to $e < 2m$, so there are finitely many parameters to consider. Then we exclude from the set of words $d_{e,b}$ those which are proper prefixes of another word of this set. Let k_m be the number of nonempty words $d_{e,b}$ that remain. Then, clearly, the 2-kernel of d_{pd} contains at least k_m elements.

The following table collects the values of k_m for $m = 1, \dots, 11$.

4^m	4	4^2	4^3	4^4	4^5	4^6	4^7	4^8	4^9	4^{10}	$4^{11} = 4194304$
k_m	2	9	22	66	145	297	584	1046	1816	3047	5051
k_m/k_{m-1}		4.5	2.444	3.0	2.197	2.048	1.966	1.791	1.736	1.678	1.658

Our data thus indicates that the 2-kernel of \mathbf{u}_{pd} contains at least 5051 distinct sequences. Moreover, a four times longer prefix gives at least 1.65 times larger 2-kernel, and the ratio decreases too slowly to conjecture that it would tend to 1. This makes an impressive contrast with all the previous examples where the size of the kernel rapidly stabilizes. Based on this, we formulate the following conjecture.

Conjecture 2. *The sequence d_{pd} of the period-doubling word \mathbf{u}_{pd} is not 2-automatic, and so the prefix palindromic length $\text{PPL}_{pd}(n)$ of \mathbf{u}_{pd} is not 2-regular.*

Another way to show that a sequence is not automatic would be to prove that it has superlinear factor complexity function [3, Thm. 10.3.1]. However, it does not look to be the case : we computed the factor complexity of d_{pd} for lengths up to 500 and found that, except for initial values, the values closely follow a straight line with slope about 200. So, we could suggest that even if the PPL-difference function of the period-doubling word is not 2-automatic, it can still be morphic.

5.2. Fibonacci word

The Fibonacci word $\mathbf{u}_f = abaababaabaab \cdots$ is the fixed point $\varphi_f^\omega(a)$ of the morphism

$$\varphi_f: \begin{cases} a \rightarrow ab, \\ b \rightarrow a. \end{cases}$$

The Fibonacci word is a classic example of an infinite word; it is not k -automatic for any k but is *Fibonacci-automatic* in the sense which we explain below.

As usual, we define the Fibonacci numbers by the recurrence relation $F_0 = 0$, $F_1 = 1$, and $F_n = F_{n-1} + F_{n-2}$ for $n \geq 2$. Every positive integer n can be uniquely expressed as $n = \sum_{0 \leq i \leq r} a_i F_{i+2}$ with $a_i \in \{0, 1\}$, $a_r = 1$, and $a_i a_{i+1} = 0$ for $0 \leq i < r$. In this case, we call the word $a_r a_{r-1} \cdots a_0$ the *Fibonacci representation* of n and use the notation $(n)_F = a_r a_{r-1} \cdots a_0$. For example, we have $(3)_F = 100$ and $(12)_F = 10101$. We also fix $(0)_F = 0$.

As is well-known, $\mathbf{u}_f[n] = b$ if and only if $(n)_F$ ends with 1; in the opposite case, we have $\mathbf{u}_f[n] = a$. Thus every symbol of the Fibonacci word can be computed from the Fibonacci representation of its index by a simple automaton. This means that the Fibonacci word is *Fibonacci-automatic*. In general, an infinite word \mathbf{x} is Fibonacci-automatic if there exists a deterministic finite

automaton A such that every symbol $\mathbf{x}[n]$ is the output of A with input $(n)_F$. Many functions of the Fibonacci word are known to be Fibonacci-automatic or Fibonacci-regular; for the definition and discussions of Fibonacci-regular sequences, see [19, 10].

Analogously to a k -kernel for k -automatic sequences, we define the *Fibonacci-kernel* of a sequence \mathbf{w} as follows. For every finite word $s \in \{0, 1\}^*$, define (i_s) as the increasing sequence of all numbers n such that $(n)_F$ ends with the suffix s . For example, $(i_\varepsilon) = 0, 1, 2, \dots$, $(i_0) = 0, 2, 3, 5, 7, \dots$, $(i_1) = 1, 4, 6, 9, 12, \dots$, and (i_{11}) is empty since the Fibonacci representation cannot contain two consecutive 1's.

Now we define a sequence $\mathbf{w}(s)$ as the subsequence of \mathbf{w} with indices from (i_s) , namely, $\mathbf{w}(s) = \mathbf{w}[i_s[0]]\mathbf{w}[i_s[1]]\mathbf{w}[i_s[2]] \dots$. At last we define the *Fibonacci-kernel* of \mathbf{w} as the set of nonempty sequences $\mathbf{w}(s)$ for all $s \in \{0, 1\}^*$.

For example, the Fibonacci-kernel of the Fibonacci word \mathbf{u}_f consists of three elements: the Fibonacci word $\mathbf{u}_f = \mathbf{u}_f(\varepsilon)$ itself and the sequences $aa \dots a \dots = \mathbf{u}_f(0)$ and $bb \dots b \dots = \mathbf{u}_f(1)$. Indeed, we have $\mathbf{u}_f(p0) = aa \dots a \dots = \mathbf{u}_f(0)$ and $\mathbf{u}_f(p1) = bb \dots b \dots = \mathbf{u}_f(1)$ for every finite word p (or the sequences $\mathbf{u}_f(p0)$ and $\mathbf{u}_f(p1)$ are empty).

Notice that the Fibonacci-kernel of an infinite word always contains the empty sequence because 11 does not occur in Fibonacci representations. We largely ignore this fact.

Analogously to the proof for k -automatic words, it can be shown that a sequence is Fibonacci-automatic if and only if its Fibonacci-kernel is finite.

The existing family of decidability results on Fibonacci-automatic words [19, 10] is mostly analogous to the k -automatic case. It would be interesting to find an example of a reasonable function of the Fibonacci word which takes a finite number of values and is not Fibonacci-automatic. It seems that the PPL-difference sequence d_f of the Fibonacci word is a good candidate for that.

Similar to the period-doubling word from the previous subsection, we consider words determined by the (nonempty) sequences of the Fibonacci-kernel of d_f and the prefix of d_f of length $|\varphi_f^{3m}(a)|$ for $m = 1, 2, \dots$. Let again k_m be the number of the corresponding nonempty words that are not prefixes of each other. Our computations give the following values for k_m for $m = 1, \dots, 8$.

$ \varphi_f^{3m}(a) $	5	21	89	377	1597	6765	28657	121393
k_m	3	11	31	88	207	504	1139	2377
k_m/k_{m-1}		3.67	2.82	2.85	2.35	2.43	2.26	2.09

While this evidence is not as strong as in the case of the period-doubling word, we conclude that the Fibonacci-kernel of d_f has at least 2377 elements and the kernel does not seem to stabilize. We make the following conjecture.

Conjecture 3. *The sequence d_f of the Fibonacci word \mathbf{u}_f is not Fibonacci-automatic, and so the prefix palindromic length $\text{PPL}_f(n)$ of \mathbf{u}_f is not Fibonacci-regular.*

All Fibonacci-automatic words have linear factor complexity [18, Thm. 3.4], so, as for the period-doubling word, a superlinear factor complexity function would give another evidence supporting the conjecture. However, the sequence d_f seems to have linear factor complexity based on the first 500 values, and so, can still be morphic even if not Fibonacci-automatic.

6. Conclusion

In this paper, we have proven a general theorem on the prefix palindromic length of automatic words containing finitely many distinct palindromes and considered in detail two particular cases when this theorem is applicable. These results were somehow predictable since they state that a reasonable function of a k -automatic word is k -regular. What is more surprising is the computational evidence that in some other situations this is not the case: it seems that there exist simple k -automatic words, such as the period-doubling word, such that their prefix palindromic length is not k -regular. If proven, this result would enrich the whole theory of k -regularity.

References

- [1] J.-P. Allouche. Schrödinger operators with Rudin-Shapiro potentials are not palindromic. *J. Math. Phys.* 38 (1997), 1843–1848. DOI:10.1063/1.531916.
- [2] J.-P. Allouche, M. Baake, J. Cassaigne, D. Damanik. Palindrome complexity. *Theoret. Comput. Sci.* 292 (2003), 9–31. DOI:10.1016/S0304-3975(01)00212-2.

- [3] J.-P. Allouche, J. Shallit. *Automatic Sequences: Theory, Applications, Generalizations*. Cambridge University Press, 2003.
- [4] J.-P. Allouche, J. Shallit. The ring of k -regular sequences. *Theoret. Comput. Sci.* **98.2** (1992), 163–197. DOI:10.1016/0304-3975(92)90001-V.
- [5] J.-P. Allouche, J. Shallit. The ubiquitous Prouhet-Thue-Morse sequence. In: C. Ding, T. Hellesest and H. Niederreiter, eds., *Sequences and Their Applications: Proc. SETA 1998*, Springer, 1999, pp. 1–16.
- [6] P. Ambrož, O. Kadlec, Z. Masáková, E. Pelantová. Palindromic length of words and morphisms in class \mathcal{P} . *Theoret. Comp. Sci.* **780** (2019), 74–83. DOI:10.1016/j.tcs.2019.02.024.
- [7] K. Borozdin, D. Kosolobov, M. Rubinchik, A. M. Shur. Palindromic length in linear time. In: J. Kärkkäinen, J. Radoszewski, and W. Rytter, eds., *Proc. CPM 2017*, Dagstuhl Publishing, 2017, pp. 23:1–23:12.
- [8] E. Charlier, N. Rampersad, J. Shallit. Enumeration and decidable properties of automatic sequences, *Int. J. Found. Comput. Sci.* **23** (2012), 1035–1066. DOI:10.1142/S0129054112400448.
- [9] A. Cobham. Uniform tag sequences. *Math. Systems Theory* **6** (1972), 164–192. DOI:10.1007/BF01706087.
- [10] C. F. Du, H. Mousavi, L. Schaeffer, J. Shallit. Decision algorithms for Fibonacci-automatic words, III: Enumeration and abelian properties. *Int. J. Found. Comput. Sci.* **27** (2016), 943–963. DOI:10.1142/S0129054116500386.
- [11] G. Fici, T. Gagie, J. Kärkkäinen, D. Kempa. A subquadratic algorithm for minimum palindromic factorization. *J. Discr. Alg.* **28** (2014), 41–48. DOI:10.1016/j.jda.2014.08.001.
- [12] A. E. Frid. First lower bounds on palindromic length. In: *Developments in Language Theory: Proc. DLT 2019*, Lect. Notes in Comp. Sci., Vol. 11647, Springer, 2019, pp. 234–243. DOI:10.1007/978-3-030-24886-4_17.
- [13] A. E. Frid. Prefix palindromic length of the Thue-Morse word. *J. Integer Seq.* V. 22 (2019), Article 19.7.8.

- [14] A. E. Frid. Sturmian numeration systems and decompositions to palindromes. *European J. Combin.* **71** (2018), 202–212. DOI:10.1016/j.ejc.2018.04.003.
- [15] A. E. Frid. Representations of palindromes in the Fibonacci word. In: *Proc. Numeration 2018*, 2018, pp. 9–12, https://numeration2018.sciencesconf.org/data/pages/num18_abstracts.pdf.
- [16] A. E. Frid, S. Puzynina, L. Zamboni. On palindromic factorization of words. *Adv. Appl. Math.* **50** (2013), 737–748. DOI:10.1016/j.aam.2013.01.002.
- [17] S. Li. Palindromic length sequence of the ruler sequence and of the period-doubling sequence. Preprint (2020). <https://arxiv.org/abs/2007.08317>.
- [18] A. Massuir, J. Peltomäki, M. Rigo. Automatic sequences based on Parry or Bertrand numeration systems. *Adv. Appl. Math.*, **108** (2019), 11–30. DOI:10.1016/j.aam.2019.03.003.
- [19] H. Mousavi, L. Schaeffer and J. Shallit, Decision algorithms for Fibonacci-Automatic Words, I: Basic results. *RAIRO Inform. Théorique* 50 (2016), 39–66.
- [20] M. Rubinchik, A. M. Shur. EERTREE: An efficient data structure for processing palindromes in strings. *European J. Combin.* **68** (2018), 249–265. DOI:10.1016/j.ejc.2017.07.021.
- [21] M. Rubinchik, A. M. Shur. Palindromic k -Factorization in pure linear time. In: *45th International Symposium on Mathematical Foundations of Computer Science (MFCS 2020)*, Leibniz International Proceedings in Informatics (LIPIcs), Vol. 170, Schloss Dagstuhl–Leibniz-Zentrum für Informatik, 2020, pp. 81:1–81:14. DOI:10.4230/LIPIcs.MFCS.2020.81.
- [22] A. Saarela. Palindromic length in free monoids and free groups. In: *Proc. WORDS 2017*, Lect. Notes in Comp. Sci., Vol. 10432, Springer 2017, pp. 203–213. DOI:10.1007/978-3-319-66396-8_19.
- [23] N. J. A. Sloane et al. The On-Line Encyclopedia of Integer Sequences, <https://oeis.org>.
- [24] <https://rosettacode.org/wiki/Eertree>.

Declaration of interests

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

The authors declare the following financial interests/personal relationships which may be considered as potential competing interests: