



HAL
open science

Combined effect of anisotropy and uncertainty on the safe mud pressure window of horizontal wellbore drilled in anisotropic saturated rock

Nam Hung Tran, Do Duc Phi, Minh Ngoc Vu, Thi Thu Nga Nguyen, Duc Tho Pham, Hung Truong Trieu

► To cite this version:

Nam Hung Tran, Do Duc Phi, Minh Ngoc Vu, Thi Thu Nga Nguyen, Duc Tho Pham, et al.. Combined effect of anisotropy and uncertainty on the safe mud pressure window of horizontal wellbore drilled in anisotropic saturated rock. *International Journal of Rock Mechanics and Mining Sciences*, 2022, 152, pp.105061. 10.1016/j.ijrmms.2022.105061 . hal-03589167

HAL Id: hal-03589167

<https://hal.science/hal-03589167v1>

Submitted on 22 Jul 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

1 **Combined effect of anisotropy and uncertainty on the safe mud pressure** 2 **window of horizontal wellbore drilled in anisotropic saturated rock**

3 **Nam Hung Tran¹, Duc Phi Do^{2,*}, Minh Ngoc Vu^{3,4}, Thi Thu Nga Nguyen¹, Duc Tho Pham⁵, Hung Truong Trieu⁵**

4 ¹ *Le Quy Don Technical University, Institute of Technique for Special Engineering, Hanoi, Vietnam*

5 ² *Univ Orléans, Univ Tours, INSA CVL, Lamé, EA 7494, France*

6 ³ *Division of Construction Computation, Institute for Computational Science, Ton Duc Thang University, Ho Chi Minh City, Viet Nam*

7 ⁴ *Faculty of Civil Engineering, Ton Duc Thang University, Ho Chi Minh City, Viet Nam*

8 ⁵ *Hanoi University of Mining and Geology, Hanoi, Viet Nam*

9 * *Corresponding author. Tel: +33 2 38 49 27 72, Email-address: duc-phi.do@univ-orleans.fr*

10

11 **Abstract**

12 The investigation of safe mud pressure window of horizontal wellbore drilled in the saturated rock by accounting
13 for the combined effect of anisotropy and uncertainty is the main purpose of this work. To this aim, the
14 deterministic solution of collapse and fracture initiation pressures are firstly presented in three cases that describe
15 the behavior of wellbore: (1) immediately after drilling (i.e., undrained problem); (2) at long term due to the
16 steady-state fluid flow (permeable boundary case) and (3) by neglecting the variation of initial pore pressure
17 (i.e., impermeable boundary condition case). Based on these deterministic solutions, the key parameters of
18 different sources of anisotropy (initial stress state, poro-elastic and strength properties of rock mass) are
19 highlighted through sensitivity analysis. Then, the famous Monte Carlo Simulation (MCS) is undertaken to
20 quantify the uncertainty effect on the probability of success of safe mud pressure window of the wellbore. We
21 also present an adaptation of the Kriging metamodeling technique to study the stability of wellbore. In
22 comparison with the referent solution of MCS, the Kriging metamodel provides a high accuracy and can be used
23 as a performant tool for the probabilistic assessment of wellbore. The consideration of anisotropy combined with
24 uncertainty, and the hydraulically boundary condition around wellbore in this work allows us to complete the
25 contributions in the literature and confirm their strong effect on the design of wellbore.

26

27 **Keywords:** *Safe mud pressure window, horizontal wellbore, anisotropic rock, sensitivity analysis, stochastic*
28 *analysis, Monte Carlo Simulation, Kriging metamodeling technique.*

29

30 **1. Introduction**

31 The accurate prediction of safe mud pressure window is the most important task in wellbore design.
32 Traditionally, the estimation of mud weights to ensure the stability of wellbore against shear and tensile failure is
33 widely undertaken under the hypothesis of isotropic behavior of geological rock formation. In addition, collapse
34 and fracture initiation pressures in the wellbore result from the deterministic calculation with the fixed values of
35 input data [1-3].

36 It has been shown in many works that the anisotropic behavior of rocks (e.g., sedimentary and metamorphic
37 foliated rock) can significantly affect the distribution of stress state around the wellbore [4-8]. For example,
38 Aadnoy [9] and then Hefny and Lo [10] determined the stress state around the horizontal borehole drilled in
39 transversely isotropic rock by using the complex stress functions of Lekhnitskii [11, 12]. The problem is then
40 extensively considered in the more general case of inclined wellbore drilled in the anisotropic rock (see [13, 14]
41 and references therein) based on the Lekhnitskii-Amadei solution [15]. These studies highlighted the strong
42 dependence of stress state and hence of the safe mud pressure window on the elastic properties of anisotropic
43 rocks. Further, the anisotropy of tensile and shear strengths of rocks also presents an essential role on the
44 stability of the wellbore [13, 14, 16-18]. Especially, in the bedded rocks like shale, the strength of planes of
45 weakness can be the critical parameter. Combined with the wellbore inclinations and the three-dimensional stress
46 state, the effect of weak planes may lead to severe collapse of the wellbore [13, 16, 17]. In their work, Setiawan
47 and Zimmerman [14] demonstrated the pronounced effect of plane of weakness as well as the intermediate stress
48 on the wellbore stability by using the both well-known Mogi-Coulomb and Jaeger models as failure criteria of
49 intact rock and the bedding plane.

50 Whilst most the contributions as cited above focus in the case of dry rock, the effect of pore pressure in the
51 anisotropic saturated rock has been recently received more attention. For instance, in their work, Do and his co-
52 workers used the well-known complex potential approach to derive the closed-form solution of effective stresses
53 around the wellbore drilled in the transversely isotropic poro-elastic rock [19-22]. Unlike the case of the
54 wellbore in isotropic rock, the explicit expressions of effective radial and tangential stresses depend on the poro-
55 elastic properties of anisotropic rock. Consequently, in the application of wellbore design, Do et al. [7-8] pointed
56 out that the anisotropic poro-elastic properties of rock mass combined with the anisotropy in the in-situ stress
57 state and that in the tensile and shear strengths, result in the remarkable difference of mud pressure windows in
58 comparison with ones calculated from the isotropic rock. Furthermore, the hydraulic boundary prescribed on the
59 borehole wall can also present a pronounced impact on the collapse and fracture pressures in the wellbore.

60 The heterogeneous characteristic in nature and the lack of knowledge related to the limitation test data induce the
61 inherent uncertainty in rock properties. Therefore, there is an increasing interest in modeling of uncertainties
62 propagation on the stability and optimization design of the underground structure in rock engineering [23-25]. In
63 petroleum application, the stochastic analysis has been intensively considered to assess the optimal mud pressure
64 windows by accounting for the uncertainty of input data like in-situ stress state, initial pore pressure, and
65 strength properties of the surrounding rock. For example, several studies used the quantitative risk assessment to
66 study the stability and optimize the mud weight windows [26-29]. The Monte Carlo Simulation (MCS) has been
67 generally chosen in these previous studies to quantify the uncertainties and the associated probability of success
68 in wellbore collapse and lost circulation pressures [30-37]. However, to the best of the authors' knowledge, the
69 entire stochastic assessment of wellbore has been limited in the case of isotropic rocks.

70 The aim of this work consists in assessing the safe mud pressure windows of the horizontal wellbore drilled in
71 anisotropic saturated rock by accounting for the uncertainty combined with anisotropy of input data including the
72 anisotropic in-situ stress, anisotropic poro-elastic properties, as well as the anisotropic strengths of rock mass.

73 In the following, the paper will be organized into three main parts. Firstly, the deterministic solution of safe mud
74 pressure windows derived from the closed-form solution of stress state around the horizontal wellbore for the

75 chosen tensile and shear failure of anisotropic poro-elastic rock is shown. Then, the sensitivity analysis and the
 76 probabilistic assessment based on the MCS are undertaken by accounting for the uncertainty of different
 77 anisotropic sources. An adaptation and validation of the well-known Kriging metamodeling technique for the
 78 stability analysis of such wellbore are also presented in this section. Essential conclusions are finally made from
 79 the results drawn throughout the manuscript.

80

81 **2. Tensile and collapse pressures of horizontal wellbore in transversely isotropic rock**

82 In this section, the deterministic solution of the tensile and collapse pressures of the horizontal wellbore
 83 drilled in the transversely isotropic rock with a vertical axis of symmetry (VTI) is briefly presented. The solution
 84 of this deterministic problem is key issue to conduct the probabilistic analysis using the MCS.

85

86 **2.1. Closed-form solution of stress state around wellbore in transversely isotropic saturated rock**

87 Considering a circular horizontal wellbore drilled in a transversely isotropic poro-elastic rock, with the
 88 assumption that the longitudinal axis of the wellbore lies on the horizontal plane and coincides with one principal
 89 horizontal stress axis as shown in Fig. 1a. The angle between the normal to the bedding plane and the principal
 90 vertical stress is β (Fig.1b). The rock formation around the wellbore is saturated with an initial pore pressure p_{ff}
 91 whilst the mud pressure in wellbore P_w acts as radial stress on the wall of the wellbore. In the case of highly
 92 permeable rock, the mud pressure can also act as pore pressure on the well wall [7, 38]. Thus, by noting p_0 as the
 93 pore pressure on the circumference of the wellbore, we have $p_0=p_{ff}$ if the variation of pore pressure is neglected
 94 (called as impermeable boundary case of wellbore) while $p_0=P_w$ if the boundary of wellbore is permeable [7].

95 Adopting the 2D plane strain hypothesis (i.e., the component $\varepsilon_z, \varepsilon_{xz}$ and ε_{yz} vanish everywhere), this initial
 96 problem can be transformed into the equivalent problem in the symmetric coordinate system of the VTI medium
 97 (Fig.1c). In this 2D plane strain equivalent problem, the far-field stress reads:

$$\begin{aligned}\sigma_v &= \frac{1}{2}(1+K_0)\sigma_v^{ff} + \frac{1}{2}(1-K_0)\sigma_v^{ff} \cos 2\beta, \\ \sigma_h &= \frac{1}{2}(1+K_0)\sigma_v^{ff} - \frac{1}{2}(1-K_0)\sigma_v^{ff} \cos 2\beta, \\ \tau_{vh} &= \frac{1}{2}(1-K_0)\sigma_v^{ff} \sin 2\beta,\end{aligned}\tag{1}$$

98 with $K_0 = \sigma_h^{ff} / \sigma_v^{ff}$

99 The determination of the stress state around the wellbore consists in solving the following differential equations:

100 - The 2D plane strain equilibrium equation:

$$\frac{\partial \sigma_x}{\partial x} + \frac{\partial \tau_{xy}}{\partial y} = 0, \quad \frac{\partial \tau_{yx}}{\partial x} + \frac{\partial \sigma_y}{\partial y} = 0,\tag{2}$$

101 - The strain compatibility equation:

$$2\frac{\partial^2 \varepsilon_{xy}}{\partial x \partial y} = \frac{\partial^2 \varepsilon_x}{\partial y^2} + \frac{\partial^2 \varepsilon_y}{\partial x^2}, \quad (3)$$

102 where the Hooke's law written in 2D plan strain conditions is:

$$\begin{pmatrix} \varepsilon_x \\ \varepsilon_y \\ \varepsilon_{xy} \end{pmatrix} = \begin{pmatrix} s_{11} & s_{12} & 0 \\ s_{21} & s_{22} & 0 \\ 0 & 0 & s_{33} \end{pmatrix} \begin{pmatrix} \sigma'_x \\ \sigma'_y \\ \tau'_{xy} \end{pmatrix}, \quad (4)$$

103 - The fluid flow in the porous rock is characterized by the diffusion equation:

$$k_x \frac{\partial^2 P}{\partial x^2} + k_y \frac{\partial^2 P}{\partial y^2} = \gamma_w \frac{\partial \chi}{\partial t}, \quad (5)$$

104 where k_x and k_y are hydraulic conductivities in the horizontal x -direction and vertical y -direction respectively and
 105 γ_w is the unit weight of the pore fluid. The variation of fluid volume per unit volume of the porous material χ is
 106 defined as:

$$\chi = \frac{P}{M} + (\alpha_x \varepsilon_x + \alpha_y \varepsilon_y), \quad (6)$$

107 where the parameter M is the well-known Biot's modulus whilst the second term in brackets presents change of
 108 fluid volume due to volumetric strain by accounting for the mechanical effect.

109 In Eq. (4), the notion of effective stress based on the Biot's theory is used to characterize the influence of the
 110 pore pressure on the mechanical response:

$$\sigma'_x = \sigma_x + \alpha_x p, \quad \sigma'_y = \sigma_y + \alpha_y p, \quad (7)$$

111 with σ', σ are respectively the effective and the total stresses; α_x, α_y are the Biot coefficients in the horizontal
 112 and vertical directions. Herein, we note that the tensile stress and pressure are considered positive.

113 The compliance coefficients ($s_{11}, s_{12}, s_{21}, s_{22}, s_{33}$) in Eq. (4) and the Biot coefficients are calculated from the
 114 five independent elastic parameters of transversely isotropic rock which are respectively: the horizontal and
 115 vertical Young's moduli (E_x, E_y), the Poisson's ratios in the isotropic plane and anisotropic plane (ν_x, ν_{yx}) and
 116 the shear modulus G_{xy} in the anisotropic plane:

$$\begin{aligned} s_{11} &= \frac{1-\nu_{xz}^2}{E_x}, & s_{12} &= s_{21} = -\frac{\nu_{xy}(1+\nu_{xz})}{E_x}, & s_{22} &= \frac{1-\nu_{xy}\nu_{yx}}{E_y}, & s_{33} &= \frac{1}{G_{xy}}, & \nu_{yx} &= \nu_{xy} k_E, & k_E &= \frac{E_y}{E_x}; \\ \alpha_x &= 1 + \frac{E_x E_y (1+\nu_{yx})}{3K_s [2E_x \nu_{yx}^2 - E_y (1-\nu_{xz})]} = 1 - \frac{k_E E_x (1+\nu_{yx})}{3K_s [k_E (1-\nu_{xz}) - 2\nu_{yx}^2]}, \\ \alpha_y &= 1 + \frac{E_y (E_y - E_y \nu_{xz} + 2E_x \nu_{yx})}{3K_s [2E_x \nu_{yx}^2 - E_y (1-\nu_{xz})]} = 1 + \frac{(1-\alpha_x) [k_E (1-\nu_{xz}) + 2\nu_{yx}]}{(1+\nu_{yx})}, \end{aligned} \quad (8)$$

117 Note that the independent elastic parameters of the transversely isotropic rock verify the following
 118 thermodynamic conditions:

$$k_E(1-\nu_{xz})-2\nu_{yx}^2 > 0, \quad (9)$$

119 So far, the derivation of the analytical resolution for the anisotropic poro-elastic problem above has been always
 120 a great challenging. As pointed out by Kanfa et al. [6], most studies in the literature assume that the pore
 121 pressure is the initial reservoir pressure around the borehole wall to simplify the problem. The effect of pore
 122 pressure variation due to the steady flow on the wellbore stability was recently considered by Do et al. [7]. An
 123 extension of this analytical solution was then conducted in [8] in which the one-way hydro-mechanical (HM)
 124 coupling was adopted by neglecting the mechanical effect (i.e., the second term in brackets in Eq. (6)) on the
 125 variation of pore pressure. Following that, the closed-form solution of this last problem was derived by these
 126 authors using the well-known complex potential approach introduced by Lekhnitskii [11]. As a function of time,
 127 the solution of this uncoupled problem approaches the fully coupled problem and attains the solution of steady
 128 state at long term [19].

129 The stability of the wellbore immediately after the quick extraction for the low permeable rocks like shale is
 130 another important case that the closed-form solution can be derived. This phenomenon is referred to as the
 131 “undrained” drilling effect when the change of stresses (i.e., rate of loading) is much faster than the capacity of
 132 the rock to dissipate induced excess pore pressure which is calculated as follows [22, 39]:

$$\Delta p = -\frac{\beta_1 \sigma_x + \beta_2 \sigma_y}{\beta_3}, \quad (10)$$

$$\beta_1 = s_{11} \alpha_x + s_{12} \alpha_y, \quad \beta_2 = s_{12} \alpha_x + s_{22} \alpha_y, \quad \beta_3 = \frac{1}{M} + \alpha_x \beta_1 + \alpha_y \beta_2,$$

133 In this study, three cases are considered relating to the pore pressure state around the wellbore. The first case
 134 adopts the initial uniform pore pressure by ignoring the fluid flow in the rock formation. This case, as usually
 135 accepted in the literature, will be noted hereafter as the impermeable boundary problem. The second one, called
 136 the permeable boundary problem, considers the effect of steady flow on the mechanical behavior of the wellbore.
 137 The last case consists in the undrained problem to consider the stability of the wellbore immediately after
 138 drilling.

139 To simplify the presentation, only the final expressions of the effective radial and tangential stresses on the wall
 140 of the wellbore of these cases are summarized in Appendices A and B. For more details about the derivation of
 141 these closed-form solutions, the interested readers can refer to [7, 8, 19, 20, 22, 39]. The effective radial and
 142 tangential stresses at a point on the well wall, characterized by an inclination angle θ ($\theta \in [0, \pi]$) with respect to
 143 the horizontal axis Ox as shown in Fig. 2, depend on the initial pore pressure p_{ff} , the wellbore pressure P_w , the
 144 initial far-field stress, as well as the anisotropic poro-elastic properties of the surrounding rock:

$$\begin{aligned} \sigma'_\theta &= f(E_x, E_y, \nu_{xy}, \nu_{xz}, G_{xy}, k_x, k_y, \theta, \beta, K_0, \sigma_v^{ff}, \alpha_x, \alpha_y, M, p_0, p_{ff}, P_w), \\ \sigma'_r &= -P_w + (\alpha_x \cdot \cos^2 \theta + \alpha_y \cdot \sin^2 \theta) p_0, \end{aligned} \quad (11)$$

145 with the pore pressure on the well wall $p_0 = P_w$ for the case of permeable boundary, $p_0 = p_{ff}$ for the case of
 146 impermeable boundary, or $p_0 = p_{ff} + \Delta p$ for the undrained case.

147 2.2. Fracture initiation pressure

148 It has been largely accepted that tensile failure occurs when the effective tangential stress on the well wall
 149 exceeds the tensile strength of the massif. Among different models to characterize tensile strength of transversely
 150 isotropic rock, the well-known model of Nova and Zaninetti [7, 40, 41] is chosen in this work to calculate the
 151 fracture initiation pressure. According to this model, the tensile strength for an inclined plane, characterized by
 152 the angle θ_t ($\theta \in [0, \pi/2]$) between its normal vector $\mathbf{n} = (-\sin \theta_t, \cos \theta_t, 0)$ with respect to the normal vector of the
 153 bedding plane, is defined as:

$$T(\theta_t) = \frac{T_{90} + T_0}{2} - \frac{T_{90} - T_0}{2} \cos 2\theta_t = \frac{(k_T + 1)T_0}{2} - \frac{(k_T - 1)T_0}{2} \cos 2\theta_t, \quad (12)$$

154 where T_0 and T_{90} are respectively the tensile strengths of the plane parallel and perpendicular to the bedding
 155 plane; and $k_T = T_{90}/T_0$ represents the anisotropic degree of the tensile strength for the transversely isotropic
 156 medium. Note that, the inclination angle θ_t relates to θ as follows:

$$\theta_t = \begin{cases} \theta & \text{if } \theta \in [0, \pi/2] \\ \pi - \theta & \text{if } \theta \in [\pi/2, \pi] \end{cases} \quad (13)$$

158 The combination of Eqs. (11, 12) yields the expression of the fracture initiation pressure $P_{w\theta}^{ini}$ at a point
 159 characterized by an angle θ on the wellbore wall:

$$\sigma'_\theta(E_x, E_y, \nu_{xy}, \nu_{xz}, G_{xy}, k_x, k_y, \theta, \beta, K_0, \sigma_v^{ff}, \alpha_x, \alpha_y, M, p_{ff}, P_w) = T(\theta), \quad (14)$$

160 Due to the dependence of the effective tangential stress on anisotropic poro-elastic properties, the anisotropic
 161 tensile strength of the rock, the initial far-field stresses, and the orientation of the bedding plane, the solution of
 162 tensile pressure $P_{w\theta}^{fra}$ at each inclined plane θ depends also on these parameters and can be expressed in the
 163 following form:

$$P_{w\theta}^{fra}(\theta) = g(E_x, E_y, \nu_{xy}, \nu_{xz}, G_{xy}, k_x, k_y, \theta, \beta, K_0, \sigma_v^{ff}, \alpha_x, \alpha_y, M, p_{ff}, k_T, T_0), \quad (15)$$

164 The fracture initiation pressure is then determined as the minimum value of $P_{w\theta}^{fra}(\theta)$ with $\theta \in [0, \pi]$:

$$P_w^{fra} = \underset{\theta \in [0, \pi]}{\text{Min}} [P_{w\theta}^{fra}(\theta)] = [P_{w\theta}^{fra}(\theta_c)], \quad (16)$$

165 where the critical plane characterized by θ_c at which the fracturing initiates is determined from the following
 166 equation:

$$\left. \frac{\partial P_{w\theta}^{fra}(\theta)}{\partial \theta} \right|_{\theta=\theta_c} = 0 \quad (17)$$

167

168 2.3. Collapse pressure

169 The instability of the wellbore due to collapse occurs when the surrounding stress state exceeds the shear
170 strength of the rock formation. Thus, the determination of collapse pressure depends strongly on the chosen
171 criterion of shear failure.

172 Research on the shear failure of anisotropic rock remains an active topic despite numerous contributions in the
173 literature. Several sophisticated models have been developed to reproduce the laboratory and in-situ observation
174 [4, 41-47]. However, their application in practical petroleum engineering seems limited because of their high
175 number of associated parameters whose physical meaning and calibration are not simple to be evaluated.

176 In the present paper, the model of Jaeger [42, 46] is chosen to evaluate the collapse pressure. As a reminder,
177 Jaeger [42] used the Mohr-Coulomb failure criterion to define the shear strength of the rock mass having a set of
178 parallel planes of weakness. Also known as the single weakness plane theory, this model supposes that failure
179 can take place in the weak plane characterized by its shear strength or in the other planes characterized by the
180 strength of the intact rock. So far, the application of the Jaeger model has been largely used and discussed in the
181 literature. For example, in [5], the author showed that the shear failure in a sample under the compressive test
182 can occur in the plane of weakness if the inclination angle θ (i.e. angle between the direction of the maximum
183 compressive stress and the normal of the plane of weakness) varies from the friction angle of the plane of
184 weakness ϕ_w to 90° . Outside this range, the orientation of the failure plane (i.e. the critical plane ϕ_c) can be
185 different from that of the weakness plane and is controlled by the strength of intact matrix rock (see Fig. 2).
186 From the triaxial compressive tests performed on a shale rock, the authors in [17] observed the ‘U-shaped’ of
187 curve between compressive strength with respect to the inclination angle θ . The minimum value of strength is
188 found at 55° while the strength is maximum at $\theta=0^\circ$ and 90° . This ‘U-shaped’ is also remarked in the previous
189 contribution of Aadnoy et al. [16]. Application in the context of stability of inclined wellbore and under the
190 three-dimensional stress state, these last authors reveal the conditions where the plane of weakness control
191 wellbore failure. Following that, the wellbore failure at the plane of weakness depends not only on the shear
192 strength of the bedding plane but also on the combinations of borehole orientation and magnitude of the in-situ
193 stresses. Always in the condition of three-dimensional stress state of inclined wellbore, Setiawan and
194 Zimmerman [14] used the Mogi-Coulomb and Jaeger models to describe the failure criteria of intact rock and the
195 bedding plane. In addition to the high effect of plane of weakness, they also demonstrated the important role of
196 the intermediate stress on the stability of wellbore. In comparison with this last contribution and for the sake of
197 clarity, we note here that the Mohr-Coulomb model is also chosen as failure criterion of intact rock regarding
198 with our plane strain assumption for the considered horizontal wellbore.

199 Mathematically, the shear failure of intact rock is described by two well-known parameters: the cohesion C_i and
200 friction angle ϕ_i according to the Mohr-Coulomb model:

$$\frac{(\sigma'_r - \sigma'_\theta)}{2} + \frac{(\sigma'_r + \sigma'_\theta) \sin(\phi_i)}{2} - C_i \cos(\phi_i) = 0 \quad (18)$$

201 In Eq. (18), the two major and minor principal stresses are directly replaced by the effective radial and tangential
202 stresses and the compressive stress is negative as assumed previously.

203 Correspondingly, the shear failure at the weak plane, characterized by the inclined angle $\theta_w \in [0, \pi/2]$, depends on
 204 the cohesion C_w and the friction angle ϕ_w which are lower than the ones of the intact rock (i.e., $C_w < C_i$, $\tan(\phi_w) <$
 205 $\tan(\phi_i)$) :

$$\frac{(\sigma'_r - \sigma'_\theta) \sin(2\theta_w)}{2} = C_w - (\sigma'_r \sin(\theta_w)^2 + \sigma'_\theta \cos(\theta_w)^2) \tan(\phi_w) \quad (19)$$

206 with

$$\theta_w = \begin{cases} \theta & \text{if } \theta \in [0, \pi/2] \\ \pi - \theta & \text{if } \theta \in [\pi/2, \pi] \end{cases} \quad (20)$$

207 From Eqs. (18, 19), we can deduce the following collapse pressure $P_{w\theta}^{col}$ with respect to θ (with $\theta \in [0, \pi]$) :

$$P_{w\theta}^{col}(\theta) = \text{Max}(P_{w\theta}^{int}(\theta), P_{w\theta}^{wp}(\theta)) \quad (21)$$

208 where $P_{w\theta}^{wp}(\theta)$, $P_{w\theta}^{int}(\theta)$ are the collapse pressure corresponding to the shear failure of the bedding plane and of
 209 intact rock.

210 Finally, the collapse pressure that ensures the stability of wellbore from shear failure is evaluated from the
 211 maximum value of $P_{w\theta}^{col}(\theta)$ calculated from Eq. (21) with $\theta \in [0, \pi]$:

$$P_w^{col} = \text{Max}_{\theta \in [0, \pi]}(P_{w\theta}^{col}(\theta)) \quad (22)$$

212

213 3. Safe mud pressure window of horizontal wellbore in anisotropic rock

214 The heterogeneous characteristic in nature of rock mass, as well as the deficiencies in human knowledge
 215 due to the limitation or lack of test data, are considered as the principal uncertainty sources of input parameters
 216 in rock engineering design. In petroleum-related applications, logs data are widely used to calibrate the input
 217 parameters against core data. The logs data involve different sources of uncertainty related to the malfunctioning
 218 of the device and human error during acquisition and interpretation. This paper does not intend to discuss the
 219 uncertainty of the calibrated input parameters (e.g., the in-situ stress state, pore pressure, the mechanical
 220 properties of rock mass) by log-based correlations which were largely pointed out by many previous studies [2,
 221 28, 29, 33, 37, 48]. It is worth also noting that the characterization of the transversely isotropic rock remains
 222 nowadays a challenging issue and the associated uncertainty could be much higher when the anisotropic effect is
 223 accounted for.

224 From the methodology point of view, the traditional wellbore pressure design bases on the deterministic solution,
 225 which can highly underestimate the collapse pressure and overestimate the fracture initiation pressure resulting
 226 in a large mud weight window [1, 2, 38]. By using the probabilistic analysis that can consider the uncertainty of
 227 input parameters to verify the reliability of the deterministic results, different studies highlighted much narrower
 228 safe pressure windows [26-36, 48]. Consequently, the consideration of uncertainty through the probabilistic
 229 assessment (also called the risk or stochastic analysis) seems extremely necessary for the optimization design of

230 the wellbore. Among various probabilistic analysis methods, the Monte Carlo Simulation (MCS) is the most
231 widely used and can be chosen as the referent approach to validate the other stochastic techniques [24, 25]. The
232 main idea of the MCS is to construct the limit state functions (LSF) that separate the safe and failure domains by
233 point-by-point evaluations from the large random samples of input variables. In the present work, this well-
234 known probabilistic analysis method is also chosen to quantify the uncertainty effect on the safe mud pressure
235 window as well as to validate the Kriging metamodeling technique which is firstly adapted to solve the
236 stochastic analysis of wellbore.

237

238 3.1. Deterministic results

239 Before performing the sensitivity and probabilistic analysis, we discuss firstly the results of the
240 deterministic problem. For this purpose, the stability of the horizontal wellbore drilled in a VTI rock like
241 Tournemire shale at a depth of 1000 m is considered. The transversely poro-elastic properties of this argillaceous
242 rock are taken in the previous studies [49-53] whilst their corresponding anisotropic tensile and shear strengths
243 are extracted from [45]. Table 1 summaries the adopted hydro-mechanical properties of this shale rock, as well
244 as the stress state and pore pressure at the far-field. In addition, due to the lack of the statistical data, these
245 parameters are considered as the mean values while the same coefficient of variation COV=30% is assumed in
246 this work to characterize the uncertainty of these input parameters. For the sensitivity analysis and then for the
247 stochastic analysis in the next parts, the normal distribution of each input parameter A is truncated at 95%
248 confidence interval thus the corresponding minimum and maximum values ($A_{min} = (1-1.96COV) \cdot A_{mean}$ and A_{max}
249 $= (1+1.96COV) \cdot A_{mean}$) can be calculated and are also detailed in Table 1.

250 Fig. 3 presents the deterministic solution of collapse and fracture pressures versus the inclination angle θ
251 ($\theta \in [0, \pi]$) for three considered cases of the horizontal well (i.e., impermeable boundary, permeable boundary,
252 and undrained cases). The results calculated from the mean value of input parameters show that the anisotropic
253 behavior of shale rock and the adopted state of pore pressure around the well wall can significantly affect the
254 distribution of fracture and collapse pressures in the wellbore. For the case of uniform initial pore pressure by
255 neglecting the effect of hydro-mechanical coupling, the values of 8.99 MPa and 49.65 MPa can be noted as the
256 safe mud pressure window corresponding to the shear and tensile failure of the horizontal wellbore. Those values
257 are respectively equal to 8.66 MPa and 45.37 MPa in the case of a permeable boundary at the well wall (i.e., case
258 of steady fluid flow) whilst the mud pressure in the range of 6.76 MPa to 53.96 MPa ensures the stability of the
259 wellbore immediately after drilling by adopting the undrained condition. Thus, these deterministic results
260 highlight that the mud pressure window is largest in the undrained case representing by the lowest collapse
261 pressure and highest fracture pressure. The comparison between the impermeable and permeable boundary
262 conditions at the well wall shows that both the collapse and fracture pressures in the wellbore are higher in the
263 former case and the difference seems more pronounced on the fracture pressure than the collapse pressure. This
264 can be explained by the high contrast between the fracture pressure in the wellbore and the initial pore pressure
265 of rock mass that induces a significant variation of stress state on the circumference of horizontal well.

266 Fig. 4 highlights the distributions of effective stress state on the wall of the wellbore corresponding to the
267 fracture initiation pressure P_w^{fra} and the collapse pressure P_w^{col} in cases of impermeable and permeable boundary

268 conditions, as well as the undrained problem. For the two former cases, the results of stress state at the shear
269 failure are quite similar (Fig. 4a) but their difference becomes much stronger for the tensile failure state (Fig.
270 4b). This can be explained by the fact that the higher wellbore pressure increases the compressive radial stress
271 but decreases the compressive tangential stress on the well wall. Further, this variation is much more
272 pronounced in the permeable boundary condition especially at the horizontal and vertical planes (e.g., $\theta=0$ and
273 $\theta=\pi/2$) of the wellbore. Although in both cases of impermeable and permeable boundary conditions, a fracture
274 can initiate at the horizontal plane ($\theta=0$), we can note however that the maximum tensile stress in the permeable
275 rock is located at $\theta=\pi/2$ whose value is however still lower than the tensile strength of this vertical plane. The
276 results of this deterministic problem confirm the important effect of anisotropy and the interaction of different
277 input parameters on the distribution of stress state and failure of the wellbore as demonstrated in [7, 8].
278 Regarding the results of the undrained case, we can observe a similar tendency of stress distribution as the two
279 previous cases using the fracture pressure in the wellbore. However, the maximum tensile strength located at
280 $\theta=\pi/2$ exceeds the tensile strength in this undrained case which induces the tensile failure in the vertical plane
281 instead of the horizontal plane as depicted in Fig. 3c. The difference of the undrained response of the wellbore in
282 comparison with the impermeable and permeable boundary conditions is clearer when the collapse pressure is
283 taken in the wellbore. Following that, the non-uniform excess pore pressure in the undrained case (Fig. 5) can
284 significantly affect the distribution of effective stresses on the well wall when the maximum compressive stress
285 is located at the vertical plane $\theta=\pi/2$ for both the radial and tangential stresses.

286 Now we compare these deterministic results of collapse and fracture pressures of anisotropic rock with the ones
287 calculated for the isotropic rock. For this purpose, the mechanical properties extracted from the vertical direction
288 of the Tournemire shale are chosen for the isotropic rock. Following that, the Young's modulus and Poisson ratio
289 of the isotropic rock are chosen $E=E_y$, $\nu=\nu_{yx}$ whilst its corresponding parameters characterize the tensile and
290 shear strengths are equal to the ones of the bedding plane of the anisotropic rock (see Table 2). Note that, for the
291 sake of clarity, the classical expressions of stress state and pressures at failure of wellbore drilled in the isotropic
292 rock and under different conditions of impermeable and permeable boundaries as well as undrained behavior are
293 summarized in Appendix C.

294 Fig. 6 illustrates the evolution of collapse and fracture pressures of the wellbore drilled in this isotropic rock.
295 Due to the higher compressive stress in the horizontal direction at far-field, the highest collapse pressure is found
296 at $\theta=\pi/2$ whilst lowest fracture pressure is at $\theta=0$ for all three cases of impermeable, permeable boundaries and
297 undrained rock. Like the anisotropic rock, these results reveal that the permeable boundary case presents the
298 narrowest safe mud pressure window which ranges from 10.72 MPa to 49.18 MPa. However, both these last
299 values are higher than the ones calculated from the anisotropic rock.

300

301 3.2. Sensitivity analysis

302 The sensitivity analysis is undertaken in this part to determine the role of each parameter on the variation of
303 the safe pressure window of wellbore in the anisotropic rock. The sensitivity analysis is essential since it helps
304 the experimental campaign to put more effort into the parameters significantly affecting the safe pressure
305 window variation. For this purpose, the mono-parametric investigation is conducted by considering only the
306 variation of each considered parameter whilst all the other properties are fixed.

307 To simplify the presentation, only the results of the key parameters such as the initial stress state, pore pressure
308 (Fig. 7), poro-elastic properties (Fig. 8), and strength properties (Fig. 9) of rocks are shown. The first remark is
309 made on the important effect of the initial stress state on the variation of collapse and fracture pressures. By
310 varying the value of the initial vertical stress σ_v^0 or the anisotropic coefficient K_0 , the mud pressure window
311 changes considerably. Follow that, the decrease of σ_v^0 induces a strong decrease of both collapse and fracture
312 pressures in the horizontal wellbore (Fig. 7a). The increase of K_0 reveals an increase of collapse pressure in the
313 wellbore whilst the fracture pressure can become smaller at the high degree of anisotropy of the initial stress
314 state (Fig. 7b). However, it seems that the variation of pore pressure in the rock mass affects quite slightly the
315 evolution of mud pressure window (Fig. 7c) while the variation of the inclination angle of bedding plane β in the
316 range of $[4.12^\circ, 15.88^\circ]$ does not affect the safe mud pressure window in all cases (Fig. 7d).

317 Among different poro-elastic properties of the transversely isotropic rocks, the influence of shear modulus G_{xy} ,
318 horizontal Young' modulus E_x and the ratio E_y/E_x are the most pronounced (Fig. 8). A higher value of shear
319 modulus G_{xy} results in higher fracture pressures (Fig. 8a). Inversely, an increase of Young's modulus in the
320 horizontal or vertical direction (represented by a higher value of E_y/E_x) reduces the safe mud pressures in the
321 wellbore (Figs. 8b, c). By varying the Biot coefficient in the range $\alpha_x \in [0.17, 0.27]$, its effect on the wellbore
322 pressures seems moderate in all cases of impermeable and permeable boundary conditions, as well as the
323 undrained problem (Fig. 8d). The same remark can be noted for the permeability's ratio k_y/k_x (or the Biot
324 modulus M) when the higher value of this parameter can increase slightly the fracture pressure of wellbore in the
325 permeable boundary (or undrained case) as illustrated in Figs. 8e, f.

326 Regarding the strength properties of shale rock, the cohesion of the weak plane C_w affects the most the variation
327 of collapse pressure in the wellbore (Fig. 9a). The decrease of this last pressure is remarkable when the value C_w
328 attains its maximum value. In comparison with the cohesion, the influence of friction angle of the weakness
329 plane ϕ_w is smaller (Fig. 9b). The anisotropic effect of shear strength is characterized by the two ratios C_v/C_w and
330 ϕ_v/ϕ_w . The results exhibited in Fig. 9c show that a ratio of C_v/C_w approaches to 1 can significantly increase the
331 collapse pressure in the wellbore. In this case, the shear failure on the well wall does not occur at the plane of
332 weakness but at the vertical plane of the intact rock ($\theta=\pi/2$). The other ratio ϕ_v/ϕ_w does not present any effect on
333 the mud pressure window of the wellbore (Fig. 9d). Concerning the effect of tensile properties of the Tournemire
334 shale, we observe that the tensile strength of the horizontal plane T_0 presents its considerable effect on the
335 variation of fracture pressure in all considered cases of the wellbore (Fig. 9e). The influence of the anisotropic
336 tensile strength characterized by the parameter k_T seems slight in the impermeable and permeable boundary
337 conditions but significant in the undrained case (Fig. 9f).

338 The results of the sensitivity analysis can also be represented in the well-known Tornado chart for parameter
339 ranking (Figs. 10 and 11). From these diagrams, one can conclude that the initial stress state characterized by the
340 vertical stress σ_v^0 and the anisotropic coefficient K_0 is the most sensitive parameters on the safe mud pressure
341 windows of the horizontal well drilled in the Tournemire shale. Indeed, the variation of σ_v^0 results in a wide
342 range of fracture and collapse pressures representing a strong variation of the safe mud weight window. It
343 indicates that the influence of the shear strength of the weak plane (e.g., C_w , ϕ_w) on the collapse pressure is
344 higher than the ones of the anisotropic elastic properties (e.g., G_{xy} , E_x , E_y/E_x). In turn, these later parameters have

345 more effect on the fracture initiation pressure than the tensile strength parameters (T_0 , k_T). The role of the pore
346 pressure and coefficient of Biot α_x on the results of safe mud weight window is moderate. It is also the case of
347 the permeable ratio k_v/k_x and Biot modulus M when they can impact slightly on the variation of the fracture
348 pressure in the permeable boundary and undrained cases. From the results of this sensitivity study, it indicates
349 that the effects of the other parameters like the inclination angle of bedding plane β , and the ratio of friction
350 angle ϕ_i/ϕ_w are negligible and can be omitted in the stochastic assessment for the horizontal wellbore drilled in
351 Tournemire shale. The sensitivity analysis performed in this work allows us to confirm and extend the
352 conclusion of various works in the literature, which however are mainly limited in the case of isotropic poro-
353 elastic rocks [26-34, 48].

354 In general, the deterministic results and the sensitivity analysis conducted in this section show that the safe mud
355 pressure window in the wellbore is largest in the undrained case. Furthermore, in comparison with the
356 impermeable boundary case, where the variation of pore pressure around the wellbore is neglected, the mud
357 pressure window seems narrower when the variation of pore pressure due to the steady-state flow is accounted
358 for (i.e., permeable boundary case).

359

360 3.3. *Quantification of uncertainty effect*

361 In this part, the probabilistic analysis of wellbore stability is carried out by using firstly MCS to quantify
362 the uncertainty effect combined with the anisotropy of input parameters on the safe mud weight windows.
363 Following that, ten thousand samples of each input parameter A are randomly generated in the range $[A_{min}, A_{max}]$
364 as summarized in Table 1. We remind that this range is truncated at a 95% confidence interval by assuming the
365 same coefficient of variation COV=30% for all parameters as mentioned above. Note also that the sensitivity
366 analysis in the previous section reveals the insignificant effect of the friction angle ratio ϕ_i/ϕ_w and the inclination
367 angle β , thus their variations are not considered in the stochastic analysis. Similarly, the effect of the variability
368 in Poisson's ratio on the stress distribution around the wellbore and the mud pressures is also negligible [7, 8,
369 19]. As an illustration, we present in Fig. 12 the histogram of the initial stress state and pore pressure, the poro-
370 elastic and strength properties of the generated samples of Tournemire shale rock.

371 Using the closed-form solution of the deterministic problem, the MCS allows calculating the safe mud pressure
372 window of each considered case and for each random sample. Fig. 13 depicts the probability distribution
373 function and the cumulative likelihood of success of the mud pressures of the three considered cases (i.e.,
374 impermeable and permeable boundary conditions, as well as the undrained behavior case). In addition, for the
375 comparison purpose, Table 3 recapitulates the safe mud pressure windows evaluated from the deterministic
376 problem and stochastic analysis taken at different confidence of levels (CL). By adopting the higher value of
377 CL, the safe window provided by the probabilistic analysis becomes narrower. For example, at CL=60% the safe
378 mud window of [13.41 MPa, 35.74 MPa] reduces strongly to [23.71 MPa, 24.31 MPa] at CL=88% in the case of
379 permeable boundary. Especially, an intersection of the probability of success curves obtained from the fracture
380 and collapse stochastic analysis can be observed at CL=88.44% in this last case, which signifies that the safe
381 mud pressure window is not available.

382 The comparison of the results calculated from the three considered cases of wellbore shows that the safe mud
383 pressure window is the largest in the undrained case and the narrowest in the permeable case for all values of
384 CL. For instance, at CL=88%, the possibility to obtain the safe mud pressure calculated as the difference
385 between the fracture and collapse pressures is about 0.6 MPa for the permeable boundary case whilst this value
386 for the impermeable boundary and undrained cases are about 6.59 MPa and 8.66 MPa respectively. The critical
387 confidence of level is also higher in these two latter cases which are about 92.71% for the impermeable boundary
388 case and 93.78% for the undrained one.

389 Like the deterministic analysis, we also compare these results of the probabilistic analysis with the one estimated
390 by MCS method for the isotropic rock. The corresponding probabilistic distribution function and the cumulative
391 likelihood of success for the three considered cases of this isotropic rock are depicted in Fig. 14. In comparison
392 with the results illustrated in Fig. 13d of the anisotropic rock, the similar tendency of the likelihood of success
393 can be stated for the isotropic rock formation (see Fig. 14d). More precisely, with the increase of CL, the safe
394 mud pressure window decreases with the narrowest corresponds to the case of the permeable boundary of rock.
395 The recapitulated values in Table 4 show a higher collapse and fracture pressures in all three considered cases of
396 the isotropic rock comparing with the ones of anisotropic rock at the same CL. A lower critical confidence of
397 level at about 84% is also observed in the permeable boundary condition of the isotropic. At this critical level,
398 the same value of collapse and fracture pressures (about 26.7 MPa) is higher than the one calculated from the
399 anisotropic rock (about 24 MPa). In general, with respect to the specific considered rock in this work, the
400 difference of safe mud pressure windows of horizontal wellbore drilled in the VTI rock and in the isotropic rock
401 whose properties are extracted from the ones in the vertical direction of the initial anisotropic rock seems
402 moderate. This statement is consistent with the previous sensitivity analysis when the most effect factors on the
403 collapse and fractures pressure in the wellbore are the initial stress state and the strength parameters of the
404 bedding plane.

405 The strong difference of safe mud pressure windows calculated from the deterministic and stochastic analysis
406 elucidates the crucial role of uncertainty on the wellbore design. It is important to note here that, due to the limit
407 of the analytical approach, the effect of anisotropic hydro-mechanical (HM) coupling on the safe mud pressure
408 window was only considered at short term (i.e., undrained behavior of wellbore immediately after drilling) and at
409 long term (i.e., at steady state regime of fluid flow) whilst the fully HM coupling in the transient state remains a
410 grand challenge. However, thanks to these closed-form solutions, the computational expensive MCS method can
411 be conducted and their results can be used as the reference to investigate the performance of the other techniques
412 in the stochastic analysis of wellbore in the complex contexts (e.g. the fully HM coupling problem, the
413 consideration of thermal and/or chemical effect in anisotropic rocks) that the analytical solutions are no longer
414 available. As an example, in the recent contribution of [Do et al. \[24\]](#), the Kriging metamodeling technique was
415 successfully adopted to study the failure probability at long term of underground structure constructed in a
416 viscoelastic rock. The efficiency of this metamodel was demonstrated by comparing with the referent results
417 provided by MCS. An extension of Kriging surrogate was then presented in [\[25\]](#) to assess the probabilistic
418 behavior of a deep drift excavated in the visco-plastic rock in which the deterministic problem must be solved by
419 the numerical simulation.

420 If the performance of the Kriging metamodel has been revealed in the purely mechanical problem as mentioned
 421 above, its applicability to treat the coupling problem in rock mechanical engineering has not yet discussed in the
 422 literature. Thus, an adaptation of this metamodeling technique to assess the probabilistic results of safe mud
 423 pressure window of the horizontal wellbore drilled in the anisotropic saturated rock, even in the simple case of
 424 one-way HM coupling, is extremely useful for the future applications.

425 As detailed in [24, 25], the principal idea of Kriging metamodel consists of approximating each limit state
 426 function (LSF) $G(\mathbf{X})$ that separates the safety ($G(\mathbf{X}) > 0$) and failure domains ($G(\mathbf{X}) \leq 0$) in the space of random
 427 input variables gathered in the vector \mathbf{X} by a Gaussian process:

$$G(\mathbf{X}) \approx \bar{G}(\mathbf{X}) = \mathbf{k}(\mathbf{X})^T \boldsymbol{\beta} + Z(\mathbf{X}) \quad (23)$$

428 The first term $\mathbf{k}(\mathbf{X})^T \boldsymbol{\beta}$ of the Kriging metamodel $\bar{G}(\mathbf{X})$ represents the mean value whilst the second term $Z(\mathbf{X})$ is
 429 assumed to have the zero-mean stationary Gaussian process. This metamodel can be built iteratively by
 430 determining the unknown parameters $\boldsymbol{\beta}, \sigma_Z^2, \boldsymbol{\theta}$ in which σ_Z^2 is the constant process variance and $\boldsymbol{\theta}$ is the
 431 hyperparameter vector of the kernel function $R(\boldsymbol{\theta}, \mathbf{X}, \mathbf{X}')$. To this end, an optimization process is carried out
 432 using the exact results of the performance function $G(\mathbf{X})$ at different training points of the Design of
 433 Experiment (DoE). This DoE, generated from the Latin Hypercube Sampling (LHS) technique at the initial step,
 434 will be iteratively updated by adding the new training points thank for using a so-called learning function. The
 435 procedure will be repeated until the stopping criterion (the convergence) is verified. The interested reader can
 436 refer to [24, 25] for more details.

437 The constructed Kriging metamodel $\bar{G}(\mathbf{X})$ is then used as the predictor to calculate the results of LSF at each
 438 random realization of \mathbf{X} through which the MCS can be applied to calculate the failure probability:

$$P_f \approx \frac{1}{N_{MCS}} \sum_{i=1}^{N_{MCS}} \mathbf{I}(\bar{G}(\mathbf{X}^{(i)})), \quad \mathbf{I}(\bar{G}(\mathbf{X}^{(i)})) = \begin{cases} 1 & \text{if } \mu_{\bar{G}}(\mathbf{X}^{(i)}) \leq 0 \\ 0 & \text{if } \mu_{\bar{G}}(\mathbf{X}^{(i)}) > 0 \end{cases} \quad (24)$$

439 where:

$$\mu_{\bar{G}}(\mathbf{X}) = \mathbf{k}(\mathbf{X})^T \bar{\boldsymbol{\beta}} + \mathbf{r}(\mathbf{X})^T \mathbf{R}^{-1}(\mathbf{y} - \mathbf{K} \bar{\boldsymbol{\beta}}) \quad (25)$$

440 For the concerned problem of wellbore stability in the anisotropic rock, before the application of the Kriging
 441 metamodeling technique to determine the safe mud pressure window, two LSF corresponding to the two failure
 442 modes (i.e., tensile and shear failures) must be defined. From the Eq. (14) that characterizes the tensile failure of
 443 wellbore, one can propose the first LSF as follows:

$$G_{tensile}(P_w, \mathbf{X}) = T - \sigma'_\theta(P_w, \mathbf{X}), \quad (26)$$

444 Respectively, for the shear failure of wellbore using the Jeager model as defined in Eqs. (18, 19), we adopt the
 445 following second LSF:

$$G_{shear}(P_w, \mathbf{X}) = \text{Max} \left\{ \begin{array}{l} -\frac{(\sigma'_r - \sigma'_\theta)}{2} - \frac{(\sigma'_r + \sigma'_\theta) \sin(\phi_i)}{2} + C_i \cos(\phi_i) \\ -\frac{(\sigma'_r - \sigma'_\theta) \sin(2\theta_w)}{2} - (\sigma'_r \cdot \sin(\theta_w)^2 + \sigma'_\theta \cdot \cos(\theta_w)^2) \tan(\phi_w) + C_w \end{array} \right. \quad (27)$$

446 In Eqs. (26, 27) all the random variables (i.e., anisotropic in-situ stress state, anisotropic poroelastic properties,
 447 anisotropic tensile or shear strength of rock mass) as defined previously are gathered in the vector \mathbf{X} whilst the
 448 constant mud pressure P_w in wellbore plays the role of the design parameter. Note that, to simplify the
 449 presentation, the inclined angle θ is omitted in Eqs. (26, 27) but keeping in mind that the two LSFs must be
 450 determined at the critical plane at which the value of each LSF $G(\mathbf{X})$ must be maximal. For the current problem
 451 that bases on the closed-form solutions, this critical plane (and hence the maximal value of $G(\mathbf{X})$) can be
 452 analytically evaluated. But, for the more complex problems in which the deterministic problem must be solved
 453 numerically, the post processing around well wall is necessary to determine this maximum value of $G(\mathbf{X})$ as well
 454 as critical position [25].

455 In Fig. 15, the numerical applications of the Kriging metamodeling technique to determine the likelihood of
 456 success of two failure modes in wellbore are highlighted and compared with the results provided from the MCS.
 457 To simplify the presentation, only the undrained and permeable boundary cases are considered. In these
 458 calculations, the Kriging metamodel is built from 48 training points (generated by LHS technique) in the initial
 459 DoE while the same number of random samples (ten thousand realizations) as the direct MCS is chosen for the
 460 evaluation of failure probability by interpolation (Eq. 24). In all the calculations, the number of iterations at
 461 convergence is less than 35. Thus, the total number of the direct evaluations of the wellbore response is about 83.
 462 A very good agreement between the Kriging metamodel and the MCS confirms the applicability and efficiency
 463 of this metamodeling technique on the probabilistic assessment of wellbore.

464 However, as observed in Fig. 15, for an arbitrary value of CL, the safe mud pressure window cannot be accessed
 465 directly by the Kriging-based stochastic analysis. Unlike the MCS in which the safe mud pressure window can
 466 be determined easily from the statistical processing of the exact results of wellbore response thanks to the direct
 467 evaluation of all random samples (ten thousand), in the Kriging metamodeling technique, the safe mud pressure
 468 window corresponding to a predefined CL must be calculated iteratively through an optimization procedure [54].
 469 This problem, known also as the reliability-based design optimization of safe mud pressure window of wellbore
 470 using metamodeling technique will be discussed in our future work. Nevertheless, the proposition of the failure
 471 criteria and the adaptation with high accuracy of the Kriging metamodel in this study provide a useful tool for
 472 the probabilistic analysis of wellbore. Further, an extension in the future of this technique by accounting for the
 473 time-dependent effect allows treating the problem in different complex contexts such as the fully HM coupling
 474 in the transient state of the anisotropic rock as well as their interaction with the thermal and/or chemical
 475 phenomena. Combining with an appropriate optimization algorithm such as the Quantile Monte Carlo approach
 476 [55, 56], the Kriging metamodel allows a quick estimation of safe mud pressure window which is particularly
 477 important in wellbore design.

478

479 4. Conclusion

480 In this study, the investigation of the safe mud pressure window of the horizontal wellbore is conducted
481 considering the combined effect of anisotropy and uncertainty, which has not been studied in the literature yet.
482 For this aim, the deterministic results of the fracture and collapse pressures in the wellbore are derived using the
483 available analytical solutions of stress state on the well wall and two well-known anisotropic models describing
484 the tensile strength (the Nova and Zaninetti model) and shear strength (the single weakness plane model of
485 Jaeger) of rock. Three cases are considered which describe the behavior of wellbore immediately after drilling
486 (i.e., undrained problem) and at long term due to the steady-state fluid flow (permeable boundary case) or by
487 ignoring the variation of initial pore pressure (i.e., impermeable boundary condition case).

488 The numerical applications are carried out for the VTI Tournemire shale rock whose hydro-mechanical
489 properties are taken from the literature. The sensitivity analysis in this specific rock shows that the in-situ stress
490 state is the most sensitive factor with respect to the safe mud pressure windows. It seems that the shear strength
491 parameters (e.g., the cohesion, the friction angle) of the weak plane have more effect than the anisotropic elastic
492 properties, which in turn affect more significantly than the tensile strength parameters. The effect of initial pore
493 pressure, Biot coefficient and Biot modulus presents a moderate impact on the variation of mud weight windows.
494 The stochastic analysis by MCS elucidates a strong uncertainty of the safe mud weight windows which are much
495 narrower than the deterministic results and can be vanished beyond a critical value of the confidence level. It is
496 worth noting that the results of safe mud pressure windows depend on the adopted hydraulically boundary
497 condition at the circumference of well wall. Among the considered cases, the results show that the safe mud
498 pressure window is the largest in the undrained case and narrowest when the steady fluid flow around the
499 wellbore is accounted for. The safe mud pressure windows of the three cases are also calculated for the isotropic
500 rock whose mechanical properties are extracted from the vertical direction of the VTI rock whilst the tensile and
501 shear strengths corresponding to the ones of the bedding plane. In comparison with the initial anisotropic rock,
502 the safe mud pressure windows of isotropic rock provide a moderate difference with higher values of both
503 collapse and fracture pressures.

504 Finally, a proposition of the two limit state functions characterizing the tensile and shear failure modes allows us
505 to adapt the Kriging metamodeling technique in the stochastic analysis of wellbore. The performance of this
506 technique was demonstrated by comparing with the MCS. The study conducted in this work confirms the crucial
507 role of uncertainty combined with anisotropic effect on the stability of wellbore whilst the Kriging metamodeling
508 can provide an efficient tool for the probabilistic assessment of the safe mud pressure window.

509

510 **Acknowledgements**

511 This research is funded by Vietnam National Foundation for Science and Technology Development
512 (NAFOSTED), under grant number 105.99-2020.21.

513

514 **References**

515

- 516 1. Fjaer E, Holt RM, Raaen AM, Risnes R. *Petroleum Related rock mechanics*. 2nd Edition, Elsevier,
517 Developments in Petroleum Science; 2008.
- 518 2. Aadnoy SB, Looyeh R. *Petroleum rock mechanics: drilling operation and well design*. Elsevier publication,
519 Amsterdam; 2010.
- 520 3. Darvishpour A, Cheraghi SM, Wood DA, Ghorbani H. Wellbore stability analysis to determine the safe mud
521 weight window for sandstone layers. *Petrol. Explor. Develop.* 2019; 46: 1031-1038.
- 522 4. Gupta D, Zaman M. Stability of borehole in a geologic medium including the effects of anisotropy. *Applied*
523 *Math. Mech.* 1999; 20: 837-866.
- 524 5. Zhang J. Borehole stability analysis accounting for anisotropies in drilling to weak bedding planes. *Int. Jour.*
525 *Rock Mech. Min. Scien.* 2013; 60: 160-170.
- 526 6. Kanfar MF, Chen Z, Rahman SS. Risk-controlled wellbore stability analysis in anisotropic formations. *Jour.*
527 *Petro. Scien. Engin.* 2015; 134: 214-222.
- 528 7. Do DP, Tran NH, Hoxha D, Dang HL. Assessment of the influence of hydraulic and mechanical anisotropy on
529 the fracture initiation pressure in permeable rocks using a complex potential approach. *Int. Jour. Rock Mech. &*
530 *Min. Scien.* 2017; 100: 108-123.
- 531 8. Do DP, Tran NH, Dang HL, Hoxha D. Closed-form solution of stress state and stability analysis of wellbore
532 in anisotropic permeable rocks. *Int. Jour. Rock Mech. Min. Scien.* 2019; 113: 11-23.
- 533 9. Aadnoy BS. Stress around horizontal boreholes drilled in sedimentary rocks. *Jour. Petro. Sci. Eng.* 1989; 2:
534 349-360.
- 535 10. Hefny AM, Lo KY. Analytical solutions for stresses and displacements around tunnels driven in cross-
536 anisotropic rocks. *Int. Jour. Num. Ana. Meth. Geomech.* 1999; 23: 161-177.
- 537 11. Lekhnitskii SG. *Theory of elasticity of an anisotropic elastic body*. San Francisco: Holden-Day, Inc; 1963.
- 538 12. Lekhnitskii SG. *Anisotropic plates*. New York, Gordon and Breach; 1968.
- 539 13. Aadnoy BS. Modeling of the stability of highly inclined boreholes in anisotropic rock formations. *SPE Dril*
540 *Eng.* 1988 ; 3: 259-268.
- 541 14. Setiawan NB, Zimmerman RW. Wellbore breakout prediction in transversely isotropic rocks using true-
542 triaxial failure criteria. *Int. Jour. Rock Mech. Min. Scien.* 2018; 112: 313-322.
- 543 15. Amadei B. *Rock anisotropy and the theory of stress measurements*. Berlin: Springer-Verlag; 1983.
- 544 16. Aadnoy B, Hareland G, Kustamsi A, de Freitas T, Hayes J. Borehole failure related to bedding plane. In: *43rd*
545 *US Rock Mechanics Symposium & 4th US-Canada Rock Mechanics Symposium*. June 2009, Asheville, North
546 Carolina. Paper ARMA-09-106.
- 547 17. Liu X, Zeng W, Liang L, Lei M. Wellbore stability analysis for horizontal wells in shale formations. *Jour.*
548 *Natur. Gas Sci. Eng.* 2016; 31: 1-8.
- 549 18. Ma T, Zhang QB, Chen P, Yang C & Zhao J. Fracture pressure model for inclined wells in layered
550 formations with anisotropic rock strengths. *Jour. Petro. Scien. Engin.* 2017; 149: 393-408.
- 551 19. Tran NH. Hydro-mechanical behavior of deep tunnels in anisotropic poroelastic medium. *PhD dissertation*.
552 University of Orléans, France, 2016.
- 553 20. Tran, NH, Do DP, Hoxha D. A closed-form hydro-mechanical solution for deep tunnels in elastic anisotropic
554 rock. *Euro. Jour. Envir. Civil Engin.* 2017; 1-17.

- 555 21. Do DP, Tran NH, Hoxha D. Behavior of horizontal borehole in anisotropic poro-elastic media with transient
556 fluid flow: a closed-form solution based on the complex potential approach. In: *Proceedings of the Sixth Biot*
557 *Conference on Poromechanics*. 9-13 July 2017, Paris.
- 558 22. Vu MN, Guayacán Carrillo LM, Armand G. Excavation induced over pore pressure around drifts in the
559 Callovo-Oxfordian claystone. *Euro. Jour. Envir. Civil Engin.* 2020; 1-16.
560 doi.org/10.1080/19648189.2020.1784800.
- 561 23. Do DP, Tran NT, Mai VT, Hoxha D, Vu MN. Time-dependent reliability analysis of deep tunnel in the
562 viscoelastic Burger rock with the sequential installation of liners. *Rock Mech. Rock Eng.* 2019; 53: 1259-1285.
- 563 24. Do DP, Vu MN, Tran NT, Armand, G. Closed-form solution and reliability analysis of deep tunnel supported
564 by a concrete liner and a covered compressible layer within the viscoelastic Burger rock. *Rock Mech. Rock Eng.*
565 2021; 54: 2311-2334.
- 566 25. Tran NT, Do DP, Hoxha D, Vu MN, Armand G. Kriging-based reliability analysis of the long-term stability
567 of a deep drift constructed in the Callovo-Oxfordian claystone. *Jour. Rock Mech. Geotech. Eng.* 2021;
568 doi.org/10.1016/j.jrmge.2021.06.009.
- 569 26. Ottesen RH, Zheng RH, McCann RC. Borehole stability assessment using quantitative risk analysis. In:
570 *SPE/IADC Drilling Conference*. March 1999. Paper SPE-52864-MS.
- 571 27. Moos D, Peska P, Finkbeiner T, Zoback M. Comprehensive wellbore stability analysis utilizing quantitative
572 risk assessment. *Jour. Petro. Scien. Engin.* 2003; 38: 97-109.
- 573 28. Gholami R, Rabiei M, Rasouli V, Aadnoy BS, Fakhari N. Application of quantitative risk assessment in
574 wellbore stability analysis. *Jour. Petro. Scien. Engin.* 2015; 135: 185-200.
- 575 29. Mondal S, Chatterjee R. Quantitative risk assessment for optimum mud weight window design: a case study.
576 *Jour. Petro. Scien. Engin.* 2019; 176: 800-810.
- 577 30. Udegbunam JE, Aadnoy BS, Fjelde KK. Uncertainty evaluation of wellbore stability model predictions.
578 *Jour. Petro. Scien. Engin.* 2014; 124: 254-263.
- 579 31. Eshiet KII, Sheng Y. The performance of stochastic designs in wellbore drilling operations. *Petro. Scien.*
580 2018; 15: 335-365.
- 581 32. Zhang L, Bian Y, Zhang S, Yan Y. A new analytical model to evaluate uncertainty of wellbore collapse
582 pressure based on advantageous synergies of different strength criteria. *Rock Mech. Rock Engin.* 2019; 52: 2649-
583 2664.
- 584 33. Al-Ajmi AM, Al-Harthy MH. Probabilistic wellbore collapse analysis. *Jour. Petro. Scien. Engin.* 2010; 74:
585 171-177.
- 586 34. Nino FAP. Wellbore stability analysis based on sensitivity and uncertainty analysis. In: *SPE Annual*
587 *Technical Conference and Exhibition*. September 2016, Dubai, UAE. Paper SPE-184480-STU.
- 588 35. Ma Y, Yu R. New analytical methods to evaluate uncertainty of wellbore stability. *Jour. Petro. Scien. Engin.*
589 2019; 180: 268-277.
- 590 36. Ma T, Tang T, Chen P, Yang C. Uncertainty evaluation of safe mud weight window utilizing the reliability
591 assessment method. *Energies* 2019, 12, 942.
- 592 37. Han W, Yan Y, Yan X. Uncertainty and sensitivity analysis of in-situ stress in deep inclined strata. *Geotech.*
593 *Geol. Eng.* 2020; 38: 2699-2712.

- 594 38. Zhang J, Bai M, Roegiers JC. Dual-porosity poroelastic analyses of wellbore stability. *Int. Jour. Rock Mech.*
595 *Min. Scien.* 2003; 40: 473-483.
- 596 39. Bobet A, Yu H. Stress field near the tip of a crack in a poroelastic transversely anisotropic saturated rock.
597 *Eng. Fract. Mech.* 2015; 141: 1-18.
- 598 40. Nova R, Zaninetti A. An investigation into the tensile behavior of a schistose rock. *Int. Jour. Rock Mech.*
599 *Min. Scien. Geomech.* 1990; 27: 231-242.
- 600 41. Lee YK, Pietruszczak S. Tensile failure criterion for transversely isotropic rocks. *Int. Jour. Rock Mech. Min.*
601 *Scien.* 2015; 79: 205-215.
- 602 42. Jaeger JC. Shear failure of anisotropic rocks. *Geol. Mag.* 1960; 97: 65-72.
- 603 43. Pietruszczak S, Pande GN. Description of soil anisotropy based on multi-laminate framework. *Int. Jour.*
604 *Num. Ana. Methods Geomech.* 2001; 25: 197-206.
- 605 44. Pietruszczak S, Mroz Z. On failure criteria for anisotropic cohesive-frictional materials. *Int. Jour. Num. Ana.*
606 *Methods Geomech.* 2001; 25: 509-524.
- 607 45. Mroz Z, Maciejewski J. Failure criteria of anisotropically damaged materials based on the critical plane
608 concept. *Int. Jour. Num and Ana. Meth. Geo.* 2002; 26: 407-431.
- 609 46. Jaeger JC, Cook NGW, Zimmerman W. *Fundamentals of rock mechanics*. Fourth Edition, Blackwell
610 Publishing; 2007.
- 611 47. Chen X, Yang Q, Qui KB, Feng JL. An anisotropic strength criterion for jointed rock masses and its
612 application in wellbore stability analyses. *Int. Jour. Num. Ana. Methods Geomech.* 2008; 32: 607-631.
- 613 48. Aadnoy BS. Quality assurance of wellbore stability analyses. In: *SPE/IADC Drilling Conference and*
614 *Exhibition*. March 2011, Amsterdam, The Netherlands. Paper SPE-140205-MS.
- 615 49. Niandou HJ. Etude du comportement rhéologique et modélisation de l'argilite de Tournemire. Application à
616 la stabilité d'ouvrages souterrains (in French). *PhD dissertation*, Université des Sciences et Technologies de
617 Lille, France, 1994.
- 618 50. Niandou HJ, Shao JF, Henry JP, Fourmaintraux D. Laboratory investigation of the mechanical behaviour of
619 Tournemire shale. *Int. Jour. Rock Mech. & Min. Scien.* 1997; 34: 3-16.
- 620 51. Cosenza P, Ghoreychi M, de Marsily G, Vasseur G, Violette S. Theoretical prediction of poroelastic
621 properties of argillaceous rocks from in situ specific storage coefficient. *Water Resources Research.* 2002; 38,
622 1207.
- 623 52. Valès F, Nguyen Minh D, Gharbi H, Rejeb A. Experimental study of the influence of the degree of saturation
624 on physical and mechanical properties in Tournemire shale (France). *Applied Clay Science.* 2004; 26: 197-207.
- 625 53. Noiret A. Contribution à la caractérisation du comportement géomécanique des roches couverture des
626 réservoirs pétroliers (in French). *PhD dissertation*, Institut National Polytechnique de Lorraine, France, 2009.
- 627 54. Tran N T, Do DP, Hoxha D, Vu MN. Reliability-based design of deep tunnel excavated in the viscoelastic
628 Burger rocks. In: *Geotech. Sustain. Infrastruct. Dev.* 2020, Springer, p. 375-382. doi.org/10.1007/978-981-15-2184-
629 3_48.
- 630 55. Moustapha M, Sudret B, Bourinet JM, Guillaume B. Quantile-based optimization under uncertainties using
631 adaptive Kriging surrogate models. *Struct. Multidisc. Optim.* 2016; 54: 1403-1421.

632 56. Do DP, Tran NT, Hoxha D, Vu MN, Armand G. Kriging-based optimization design of deep tunnel in the
633 rheological Burger rock. *IOP Conf. Ser. : Earth Environ. Sci.* 2021. 833, 012155.
634 57. Detournay E, Cheng AHD. Poroelastic response of a borehole in a non-hydrostatic stress field. *Int. J. Rock*
635 *Mech. Min. Sci. & Geomech.* 1988; 25: 171-182.

636

637 **Appendix A: Expression of radial and tangential stresses on the wellbore wall by accounting for the steady**
638 **fluid flow**

639 This appendix presents the closed-form solution of the principal (i.e. tangential and radial) stresses
640 determined on the well wall by accounting for the variation of pore pressure in the steady state. This solution is
641 synthetized from [7].

642 The total stresses around the wellbore are expressed in the forms:

$$\begin{aligned}\sigma_x &= \sigma_x^{Ia} + (\sigma_x^{Ib} + \sigma_x^{II}) + \sigma_x^{Ipp} + \sigma_x^{Iph} \\ \sigma_y &= \sigma_y^{Ia} + (\sigma_y^{Ib} + \sigma_y^{II}) + \sigma_y^{Ipp} + \sigma_y^{Iph} \\ \tau_{xy} &= \tau_{xy}^{Ia} + (\tau_{xy}^{Ib} + \tau_{xy}^{II}) + \tau_{xy}^{Ipp} + \tau_{xy}^{Iph}\end{aligned}\tag{A1}$$

643 in which

$$\sigma_x^{Ia} = \sigma_h, \quad \sigma_y^{Ia} = \sigma_v, \quad \tau_{xy}^{Ia} = \tau_{vh}\tag{A2}$$

644 The solution of total stresses with superscripts *Ib* and *II* are derived from:

$$\sigma_x^{Ib} + \sigma_x^{II} = 2 \operatorname{Re} [\mu_1^2 \Phi_1' + \mu_2^2 \Phi_2'], \quad \sigma_y^{Ib} + \sigma_y^{II} = 2 \operatorname{Re} [\Phi_1' + \Phi_2'], \quad \tau_{xy}^{Ib} + \tau_{xy}^{II} = -2 \operatorname{Re} [\mu_1 \Phi_1' + \mu_2 \Phi_2']\tag{A3}$$

645 In Eq. (A3), the two potentials Φ_1, Φ_2 and their derivatives are expressed in the form:

$$\begin{aligned}\Phi_1 &= \Phi_1^{Ib} + \Phi_1^{II} = \frac{1}{2} \frac{r_0}{\mu_1 - \mu_2} [(1 - i\mu_2)\tau_{vh} + \mu_2\sigma_v - i\sigma_h + r_0 P_w (\mu_2 - i)] \frac{1}{\zeta_1}, \\ \Phi_2 &= \Phi_2^{Ib} + \Phi_2^{II} = \frac{1}{2} \frac{r_0}{\mu_2 - \mu_1} [(1 - i\mu_1)\tau_{vh} + \mu_1\sigma_v - i\sigma_h + r_0 P_w (\mu_1 - i)] \frac{1}{\zeta_2}, \\ \Phi_1' &= \frac{A_1 + iB_1}{C_1 + iD_1} = \frac{(A_1 C_1 + B_1 D_1) + i(B_1 C_1 - A_1 D_1)}{C_1^2 + D_1^2}, \\ \Phi_2' &= \frac{A_2 + iB_2}{C_2 + iD_2} = \frac{(A_2 C_2 + B_2 D_2) + i(B_2 C_2 - A_2 D_2)}{C_2^2 + D_2^2}\end{aligned}\tag{A4}$$

646 Thus :

647

$$\begin{aligned}
\sigma_x^{lb} + \sigma_x^{ll} &= 2 \left[\frac{(\mu_{11}^2 - \mu_{12}^2)(A_1 \cdot C_1 + B_1 \cdot D_1) - 2\mu_{11}\mu_{12}(B_1 \cdot C_1 - A_1 \cdot D_1)}{C_1^2 + D_1^2} + \frac{(\mu_{21}^2 - \mu_{22}^2)(A_2 \cdot C_2 + B_2 \cdot D_2) - 2\mu_{21}\mu_{22}(B_2 \cdot C_2 - A_2 \cdot D_2)}{C_2^2 + D_2^2} \right], \\
\sigma_y^{lb} + \sigma_y^{ll} &= 2 \left[\frac{A_1 \cdot C_1 + B_1 \cdot D_1}{C_1^2 + D_1^2} + \frac{A_2 \cdot C_2 + B_2 \cdot D_2}{C_2^2 + D_2^2} \right], \\
\tau_{xy}^{lb} + \tau_{xy}^{ll} &= -2 \left[\frac{\mu_{11}(A_1 \cdot C_1 + B_1 \cdot D_1) - \mu_{12}(B_1 \cdot C_1 - A_1 \cdot D_1)}{C_1^2 + D_1^2} + \frac{\mu_{21}(A_2 \cdot C_2 + B_2 \cdot D_2) - \mu_{22}(B_2 \cdot C_2 - A_2 \cdot D_2)}{C_2^2 + D_2^2} \right]
\end{aligned} \tag{A5}$$

648 where

$$\begin{aligned}
A_1 &= [P_w(\mu_{22} - 1) - \sigma_h + \mu_{22} \cdot \sigma_v - \mu_{21} \cdot \tau_{vh}] \cos \theta - [\mu_{21}(P_w + \sigma_v) + (1 + \mu_{22})\tau_{vh}] \sin \theta, \\
A_2 &= [P_w(1 - \mu_{12}) + \sigma_h - \mu_{12} \cdot \sigma_v + \mu_{11} \cdot \tau_{vh}] \cos \theta + [\mu_{11}(P_w + \sigma_v) + (1 + \mu_{12})\tau_{vh}] \sin \theta, \\
B_1 &= -[\mu_{21}(P_w + \sigma_v) + (1 + \mu_{22})\tau_{vh}] \cos \theta + [P_w(1 - \mu_{22}) + \sigma_h - \mu_{22} \cdot \sigma_v + \mu_{21} \cdot \tau_{vh}] \sin \theta, \\
B_2 &= [\mu_{11}(P_w + \sigma_v) + (1 + \mu_{12})\tau_{vh}] \cos \theta + [P_w(\mu_{12} - 1) - \sigma_h + \mu_{12} \cdot \sigma_v - \mu_{11} \cdot \tau_{vh}] \sin \theta, \\
C_1 &= 2[\mu_{11}^2 - \mu_{11}\mu_{21} + \mu_{12}(\mu_{22} - \mu_{12})] \cos \theta + 2(\mu_{21} - \mu_{11}) \sin \theta, \\
C_2 &= 2[\mu_{22}^2 - \mu_{12}\mu_{22} + \mu_{21}(\mu_{11} - \mu_{21})] \cos \theta + 2(\mu_{21} - \mu_{11}) \sin \theta, \\
D_1 &= 2[2\mu_{11}\mu_{12} - \mu_{12}\mu_{21} - \mu_{11}\mu_{22}] \cos \theta + 2(\mu_{22} - \mu_{12}) \sin \theta, \\
D_2 &= 2[2\mu_{11}\mu_{12} - \mu_{12}\mu_{21} - \mu_{11}\mu_{22}] \cos \theta + 2(\mu_{22} - \mu_{12}) \sin \theta,
\end{aligned} \tag{A6}$$

649 The other solutions of stress state are written as:

$$\begin{aligned}
\sigma_x^{lpp} = \Sigma_x &= (p_0 - p_{ff})(2N_{12} \cdot \mu_{11} \cdot \mu_{12} + N_{11} \cdot (\mu_{12}^2 - \mu_{11}^2) + N_{21} \cdot (\mu_{22}^2 - \mu_{21}^2) + 2N_{22} \cdot \mu_{21} \cdot \mu_{22} + \eta \cdot \mu_{w2}^2); \\
\sigma_y^{lpp} = \Sigma_y &= -(p_0 - p_{ff})(N_{11} + N_{21} + \eta); \\
\tau_{xy}^{lpp} = T_{xy} &= -(p_0 - p_{ff})(N_{12} \cdot \mu_{12} - N_{11} \cdot \mu_{11} + N_{22} \cdot \mu_{22} - N_{21} \cdot \mu_{21});
\end{aligned} \tag{A7}$$

650 and:

$$\begin{aligned}
\sigma_x^{lph} &= 2 \operatorname{Re} [\mu_1^2 \cdot \Phi_1^{lph} + \mu_2^2 \cdot \Phi_2^{lph}] = 2 \frac{(\mu_{11}^2 - \mu_{12}^2)(E_1 \cdot C_1 + F_1 \cdot D_1) - 2\mu_{11}\mu_{12}(F_1 \cdot C_1 - E_1 \cdot D_1)}{C_1^2 + D_1^2} \\
&+ 2 \frac{(\mu_{21}^2 - \mu_{22}^2)(E_2 \cdot C_2 + F_2 \cdot D_2) - 2\mu_{21}\mu_{22}(F_2 \cdot C_2 - E_2 \cdot D_2)}{C_2^2 + D_2^2}, \\
\sigma_y^{lph} &= 2 \operatorname{Re} [\Phi_1^{lph} + \Phi_2^{lph}] = 2 \left[\frac{E_1 \cdot C_1 + F_1 \cdot D_1}{C_1^2 + D_1^2} + \frac{E_2 \cdot C_2 + F_2 \cdot D_2}{C_2^2 + D_2^2} \right], \\
\tau_{xy}^{lph} &= -2 \operatorname{Re} [\mu_1 \cdot \Phi_1^{lph} + \mu_2 \cdot \Phi_2^{lph}] = -2 \frac{\mu_{11}(A_1 \cdot C_1 + B_1 \cdot D_1) - \mu_{12}(B_1 \cdot C_1 - A_1 \cdot D_1)}{C_1^2 + D_1^2} \\
&+ 2 \frac{\mu_{21}(A_2 \cdot C_2 + B_2 \cdot D_2) - \mu_{22}(B_2 \cdot C_2 - A_2 \cdot D_2)}{C_2^2 + D_2^2}
\end{aligned} \tag{A8}$$

651 The parameters E_1, E_2, F_1, F_2 are defined as:

$$\begin{aligned}
E_1 &= -(\Sigma_x + \mu_{21} \cdot T_{xy} - \mu_{22} \cdot \Sigma_y) \cos \theta - (\mu_{21} \cdot \Sigma_y + (1 + \mu_{22})T_{xy}) \sin \theta, \\
E_2 &= (\Sigma_x + \mu_{11} \cdot T_{xy} - \mu_{12} \cdot \Sigma_y) \cos \theta + (\mu_{11} \cdot \Sigma_y + (1 + \mu_{12})T_{xy}) \sin \theta, \\
F_1 &= -(\mu_{21} \cdot \Sigma_y + (1 + \mu_{22})T_{xy}) \cos \theta + (\Sigma_x + \mu_{21} \cdot T_{xy} - \mu_{22} \cdot \Sigma_y) \sin \theta, \\
F_2 &= (\mu_{11} \cdot \Sigma_y + (1 + \mu_{12})T_{xy}) \cos \theta - (\Sigma_x + \mu_{11} \cdot T_{xy} - \mu_{12} \cdot \Sigma_y) \sin \theta
\end{aligned} \tag{A9}$$

652 The parameters μ_{11} , μ_{21} and μ_{12} , μ_{22} in Eqs. (A5 to A9) are the real and imaginary part of two complex roots μ_1 ,
 653 μ_2 (with positive imaginary part) of the characteristic equation:

$$s_{11}\mu^4 + (2s_{12} + s_{33})\mu^2 + s_{22} = 0 \quad (\text{A10})$$

654 In Eq. (A7) the real parameter η is calculated from:

$$\eta = -\frac{\beta_1\mu_w^2 + \beta_2}{s_{11}\mu_w^4 + (2s_{12} + s_{33})\mu_w^2 + s_{22}} \quad (\text{A11})$$

655 and $\mu_{w2} = \sqrt{k_x/k_y}$ is the imaginary part of the purely imaginary parameter μ_w . The other parameters N_{11} , N_{21} and
 656 N_{12} , N_{22} are the real and imaginary part of two complex constants N_1 , N_2 which are determined from the
 657 following system of equations (see Appendix A of [7]):

$$\begin{aligned} \text{Im}[\mu_1^2 N_1 + \mu_2^2 N_2 + \mu_w^2 \eta] &= 0, \\ \text{Im}[N_1 + N_2 + \eta] &= 0, \\ \text{Im}[\mu_1 N_1 + \mu_2 N_2 + \mu_w \eta] &= 0, \\ \text{Im}[q_1 N_1 + q_2 N_2 + q_w \eta - \beta_2 / \mu_w] &= 0 \end{aligned} \quad (\text{A12})$$

658 In case that the roots μ_1 , μ_2 of the characteristic equation are purely imaginary, the following expressions of N_1 ,
 659 N_2 are derived in ([20]):

$$\begin{aligned} N_{11} &= -\frac{-(\beta_2 + \eta q_{w2} \mu_{w2}) \mu_{22} + \eta q_{22} \mu_{w2}^2}{(q_{22} \mu_{12} - q_{12} \mu_{22}) \mu_{w2}}, \quad N_{12} = 0, \\ N_{21} &= -\frac{(\beta_2 + \eta q_{w2} \mu_{w2}) \mu_{12} - \eta q_{12} \mu_{w2}^2}{(q_{22} \mu_{12} - q_{12} \mu_{22}) \mu_{w2}}, \quad N_{22} = 0, \\ p_i &= s_{11} \mu_i^2 + s_{12}, \quad q_i = s_{12} \mu_i + \frac{s_{22}}{\mu_i}, \quad (i = 1, 2, w) \end{aligned} \quad (\text{A13})$$

660 Finally, the effective tangential and radial stress on the wall of wellbore are deduced as follows by using the
 661 Biot's theory:

$$\begin{aligned} \sigma'_x &= \sigma_x + \alpha_x p_0, \quad \sigma'_y = \sigma_y + \alpha_y p_0, \\ \sigma'_\theta &= \frac{\sigma'_x + \sigma'_y}{2} - \frac{\sigma'_x - \sigma'_y}{2} \cos 2\theta - \tau_{xy} \sin 2\theta, \\ \sigma'_r &= \frac{\sigma'_x + \sigma'_y}{2} + \frac{\sigma'_x - \sigma'_y}{2} \cos 2\theta + \tau_{xy} \sin 2\theta, \end{aligned} \quad (\text{A14})$$

662 with $p_0 = P_w$ (case permeable boundary) or $p_0 = p_{ff}$ (case impermeable boundary).

663

664 **Appendix B: Closed-form solution of stress state around wellbore in the undrained case**

665 For the undrained case, the behavior of wellbore is purely mechanical by accounting for the effect of initial
 666 and excess pore pressure in the calculation of effective stress state. Thus, with respect to the previous case
 667 defined in Appendix A, only the solution of problem *I*, *Ib* and *II* are necessary.

668 The solution of problem *I* as expressed in Eq. (A2) is remained as it represents the initial stress state around
 669 wellbore before excavation. For the excavation problem with wellbore pressure P_w (problem *Ib* and *II*), by
 670 substituting the total stress defined in Eq. (A3) in Eq. (10) the following excess pore pressure can be obtained:

$$\Delta p = 2 \operatorname{Re} \left[-\frac{\beta_1 \mu_1^2 + \beta_2}{\beta_3} \Phi_1 - \frac{\beta_1 \mu_2^2 + \beta_2}{\beta_3} \Phi_2 \right], \quad (\text{B1})$$

671 The expressions of the two potentials Φ_1, Φ_2 and their derivatives are similar with ones defined in Eq. (A4) but the
 672 complex roots μ_1, μ_2 are now determined from the following characteristic equation (see also Bobet and Yu, 2015):

$$A_{11} \mu^4 + (2A_{12} + A_{33}) \mu^2 + A_{22} = 0, \quad (\text{B2})$$

673 where:

$$A_{11} = s_{11} - \frac{\beta_1^2}{\beta_3}, \quad A_{12} = s_{12} - \frac{\beta_1 \beta_2}{\beta_3}, \quad A_{33} = s_{33}, \quad A_{22} = s_{22} - \frac{\beta_2^2}{\beta_3}, \quad (\text{B3})$$

674 Thus, one can deduce the effective tangential and radial stress on the wall of wellbore as defined in Eq. (A14) in
 675 which $p_0 = p_{ff} + \Delta p$.

676

677 **Appendix C: Analytical solutions of stress state around the wellbore in the isotropic rock**

678 For the comparison purpose, the analytical solutions of stress state and the safe mud pressure windows of
 679 wellbore in the isotropic rock, which have been derived since the long time, are rewritten in this appendix.
 680 Following that, the solution for the case of wellbore in the dry rock will be firstly captured and then extended in
 681 the other cases (i.e., permeable boundary, impermeable boundary, and undrained rocks) as considered in the
 682 anisotropic part. The interested reader can refer to the well-known contributions ([5, 13, 57]) for more details of
 683 the developments of these solutions.

684 - Case of dry rock:

$$\begin{aligned} \sigma_\theta &= \sigma_v^{ff} + \sigma_h^{ff} + P_w - 2(\sigma_h^{ff} - \sigma_v^{ff}) \cos(2\theta); \\ \sigma_r &= -P_w; \\ \sigma'_\theta &= \sigma_\theta; \\ \sigma'_r &= \sigma_r; \end{aligned} \quad (\text{C1})$$

685 - Case of impermeable boundary (i.e., constant pore pressure in the rock mass):

$$\begin{aligned} \sigma_\theta &= \sigma_v^{ff} + \sigma_h^{ff} + P_w - 2(\sigma_h^{ff} - \sigma_v^{ff}) \cos(2\theta); \\ \sigma_r &= -P_w; \\ \sigma'_\theta &= \sigma_\theta + \alpha p_{ff}; \\ \sigma'_r &= \sigma_r + \alpha p_{ff}; \end{aligned} \quad (\text{C2})$$

686 - Case of permeable boundary:

$$\begin{aligned}\sigma_{\theta} &= \sigma_v^{ff} + \sigma_h^{ff} + P_w - 2(\sigma_h^{ff} - \sigma_v^{ff})\cos(2\theta) - 2\frac{\alpha(1-2\nu)}{2(1-\nu)}(P_w - p_{ff}); \\ \sigma_r &= -P_w; \\ \sigma'_{\theta} &= \sigma_{\theta} + \alpha P_w; \\ \sigma'_r &= \sigma_r + \alpha P_w;\end{aligned}\tag{C3}$$

687 - Undrained case:

$$\begin{aligned}\sigma_{\theta} &= \sigma_v^{ff} + \sigma_h^{ff} + P_w - 2(\sigma_h^{ff} - \sigma_v^{ff})\cos(2\theta); \\ \sigma_r &= -P_w; \\ \delta p &= \frac{\alpha M}{\lambda + \alpha^2 M + G}(\sigma_h^{ff} - \sigma_v^{ff})\cos(2\theta); \\ \sigma'_{\theta} &= \sigma_{\theta} + \alpha(p_{ff} + \delta p); \\ \sigma'_r &= \sigma_r + \alpha(p_{ff} + \delta p);\end{aligned}\tag{C4}$$

688 In Eq. (C4), λ and G are the two Lamé parameters.

689 It is important to remind here that the compressive stress is negative in this study while the wellbore and pore
690 pressures are positives.

691 From these explicit expressions of effective stresses in the well wall, the fracture initiation pressure and collapse
692 pressure can be deduced without difficulty using the following conditions:

$$\begin{aligned}\sigma'_{\theta} &= T, \\ \frac{(\sigma'_r - \sigma'_{\theta})}{2} + \frac{(\sigma'_r + \sigma'_{\theta})\sin(\phi)}{2} - C\cos(\phi) &= 0,\end{aligned}\tag{C5}$$

693 where T is the tensile strength while C and ϕ are the Mohr Coulomb parameters of the isotropic rock.

694

695

696 List of table headings

697

698 **Table 1.** In-situ stress state, pore pressure and mechanical properties of the transversely isotropic Tournemire
699 shale.

700

701 **Table 2.** Mechanical properties of the isotropic rock using the ones of the vertical direction of the Tournemire
702 shale.

703

704 **Table 3.** Safe mud pressure windows in the deterministic problem and probabilistic assessment evaluated at
705 confidence level (CL) in the permeable and impermeable boundary and undrained cases.

706

707 **Table 4.** Safe mud pressure windows in the deterministic problem and probabilistic assessment evaluated at
708 confidence level (CL) in the permeable and impermeable boundary and undrained cases of the isotropic rock.

709
710

711 **List of figures captions**

712

713 **Fig. 1.** Geometry of horizontal wellbore drilled in transversely anisotropic formation (a) whose bedding plane
714 inclined an angle β with the principal stress axis at the far-field (b), equivalent problem after the rotation (c).

715

716 **Fig. 2.** Critical plane characterized by the inclined angle φ_c at which the shear failure initiates. This critical plane
717 can coincide (i.e., $\varphi_c = \theta$) or have different orientation (i.e., $\varphi_c \neq \theta$) with respect to the weak plane according to
718 the Jaeger model.

719

720 **Fig. 3.** Evolution of collapse pressures $P_{w\theta}^{col}(\theta)$ and fracture pressure $P_{w\theta}^{fra}(\theta)$ versus inclination angle θ in the
721 case: impermeable boundary (a), permeable boundary (b) and undrained problem (c).

722

723 **Fig. 4.** Distribution of effective tangential and radial stresses on the well wall using fracture pressure P_w^{fra} (a)
724 and collapse pressure P_w^{col} (b) in the wellbore.

725

726 **Fig. 5.** Distribution of excess pore pressure on the well wall in the undrained case using fracture pressure P_w^{fra}
727 (a) and collapse pressure P_w^{col} (b) in the wellbore.

728

729 **Fig. 6.** Evolution of collapse pressures $P_{w\theta}^{col}(\theta)$ and fracture pressure $P_{w\theta}^{fra}(\theta)$ versus inclination angle θ in the
730 case: impermeable boundary (a), permeable boundary (b) and undrained problem (c) of the isotropic rock.

731

732 **Fig. 7.** Effect of vertical initial stress σ_v^{ff} (a), initial stress ratio K_0 (b), initial pore pressure p_{ff} (c) and inclination
733 angle β (d) on the safe mud pressure window of wellbore in the impermeable boundary, permeable boundary,
734 and undrained cases.

735

736 **Fig. 8.** Effect of shear modulus G_{xy} (a), Young's modulus E_x (b), Young's modulus ratio E_y/E_x (c), coefficient of
737 Biot α_x (d), permeability ratio k_y/k_x (e) and Biot modulus M (f) on the safe mud pressure window of wellbore in
738 the impermeable boundary, permeable boundary, and undrained cases.

739

740 **Fig. 9.** Effect of shear strength parameters like cohesion C_w (a), friction angle of the weak plane ϕ_w (b),
741 cohesion's ratio C_i/C_w (c), friction angle ratio ϕ_i/ϕ_w (d) on the collapse pressure and tensile strength T_0 (e), k_T (f)

742 on the fracture initiation pressure of wellbore in the impermeable boundary, permeable boundary, and undrained
743 cases.

744

745 **Fig. 10.** Sensitivity analysis of collapse pressure in wellbore exhibited in tornado graph: permeable boundary
746 (a), undrained problem (b) and impermeable boundary (c).

747

748 **Fig. 11.** Sensitivity analysis of fracture initiation pressure in wellbore exhibited in tornado graph: permeable
749 boundary (a), undrained problem (b) and impermeable boundary (c).

750

751 **Fig. 12.** Probability distribution function (PDF) of ten thousand randomly generated samples used in the MCS:
752 initial stress state and pore pressure (a), poro-elastic properties (b), shear strength parameters (c) and tensile
753 strength properties (d) of Tournemire shale rock.

754

755 **Fig. 13.** Probability distribution function (PDF) of wellbore pressure in the impermeable boundary (a),
756 permeable boundary (b), undrained case (c) and their likelihood of success (d).

757

758 **Fig. 14.** Probability distribution function (PDF) of wellbore pressure in the impermeable boundary (a),
759 permeable boundary (b), undrained case (c) and their likelihood of success (d) in the isotropic rock.

760

761 **Fig. 15.** Likelihood of success of mud pressure window calculated by Kriging metamodeling technique and
762 MCS: permeable boundary (a), undrained case (b).

763

Table 1

In-situ stress state, pore pressure and mechanical properties of the transversely isotropic Tournemire shale.

Initial stress state and pore pressure				Poro-elastic properties			
Parameter	Mean	Min	Max	Parameter	Mean	Min	Max
σ_v^{ff} (MPa)	-26.5	-10.92	-42.08	E_x (GPa)	27.93	11.51	44.35
$K_0 = \sigma_h^{ff} / \sigma_v^{ff}$	1.05	0.43	1.67	$k_E = E_y / E_x$	0.33	0.14	0.52
p_{ff} (MPa)	10	4.12	15.88	G_{xy} (GPa)	3.9	1.61	6.19
β (°)	10	4.12	15.88	α_x	0.17	0.07	0.27
Tensile and shear strengths				M (GPa)	17.14	7.06	27.22
T_0 (MPa)	8	3.30	12.70	k_y / k_x	0.5	0.21	0.79
k_T	2.17	1	3.45	k_x (10^{-13} m/s)	5.5	2.27	8.73
C_w (MPa)	10.88	4.48	17.28	v_{xz}	0.17	0.07	0.27
ϕ_w (°)	19.36	7.98	30.74	v_{yx}	0.2	0.08	0.32
C_f / C_w	1.65	1	2.62				
ϕ_f / ϕ_w	1.24	1	1.97				

Table 2

Mechanical properties of the isotropic rock using the ones of the vertical direction of the Tournemire shale.

Parameters	E (GPa)	ν	α	M (GPa)	k (10^{-13} m/s)	T (MPa)	C (MPa)	ϕ ($^{\circ}$)
Mean	9.22	0.2	0.53	17.14	2.75	8	10.88	19.36
Min	3.80	0.08	0.22	7.06	1.13	3.30	4.48	7.98
Max	14.64	0.32	0.84	27.22	4.37	12.79	17.28	30.74

Table 3

Safe mud pressure windows in the deterministic problem and probabilistic assessment evaluated at confidence level (CL) in the permeable and impermeable boundary and undrained cases.

Case	Permeable boundary		Impermeable boundary		Undrained case	
	P_w^{col} (MPa)	P_w^{fra} (MPa)	P_w^{col} (MPa)	P_w^{fra} (MPa)	P_w^{col} (MPa)	P_w^{fra} (MPa)
Deterministic	8.66	45.37	8.99	49.65	6.76	53.96
CL=60%	13.41	35.74	12.70	40.35	10.63	41.80
CL=70%	16.39	32.32	14.93	36.45	13.06	37.46
CL=80%	19.88	28.46	17.79	31.99	16.04	32.58
CL=88%	23.71	24.31	20.83	27.40	19.45	28.11

Table 4

Safe mud pressure windows in the deterministic problem and probabilistic assessment evaluated at confidence level (CL) in the permeable and impermeable boundary and undrained cases of the isotropic rock.

Case	Permeable boundary		Impermeable boundary		Undrained case	
	P_w^{col} (MPa)	P_w^{fra} (MPa)	P_w^{col} (MPa)	P_w^{fra} (MPa)	P_w^{col} (MPa)	P_w^{fra} (MPa)
Deterministic	10.72	49.18	10.49	54.38	10.68	54.94
CL=60%	17.09	37.10	14.89	40.78	15.72	43.21
CL=70%	20.36	33.25	17.07	36.32	18.09	38.81
CL=80%	24.66	28.80	20.02	31.32	21.16	33.82
CL=84%	26.70	26.73	21.46	29.03	22.71	31.57