



HAL
open science

Approximating SDP solutions with linear programs and simplex-like algorithm

Kirschner Felix, Arnaud Lazare, Ismaël Aliouat, Michaël Gabay

► **To cite this version:**

Kirschner Felix, Arnaud Lazare, Ismaël Aliouat, Michaël Gabay. Approximating SDP solutions with linear programs and simplex-like algorithm. 23ème congrès annuel de la Société Française de Recherche Opérationnelle et d'Aide à la Décision, INSA Lyon, Feb 2022, Villeurbanne - Lyon, France. hal-03595250

HAL Id: hal-03595250

<https://hal.science/hal-03595250v1>

Submitted on 3 Mar 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Approximating SDP solutions with linear programs and simplex-like algorithm

Felix Kirschner¹, Arnaud Lazare², Ismaël Aliouat², Michaël Gabay²

¹ Tilburg University, 5037AB Tilbourg, Netherlands

F.C.Kirschner@tilburguniversity.edu

² Artelys Paris, 75009 Paris, France

{arnaud.lazare,ismael.aliouat,michael.gabay}@artelys.com

Mots-clés : *Semidefinite programming, linear programming, simplex.*

1 Introduction

The scope of this paper is to compute tight upper bounds of standard semidefinite programs of the form :

$$(SDP) \begin{cases} \sup \langle C, X \rangle \\ \text{s.t.} \\ \langle A_i, X \rangle = b_i, \quad i = 1, \dots, m \\ X \succeq 0 \\ X \in \mathcal{S}^n \end{cases} \quad (1)$$

Where C, A_i for $i = 1, \dots, m$ are symmetric $n \times n$ matrices, \mathcal{S}^n is the cone of symmetric matrices of dimension n and \mathcal{S}_+^n the cone of positive semidefinite matrices.

Semidefinite programming has been widely studied and numerous algorithms have been designed to solve (SDP) [1]. However, in this paper, we focus on analyzing an approach leading to tight upper bounds using linear programming.

2 Hierarchy of linear programs

The underlying idea of the approach we intend to study was published in [2]. One considers an easier version of (1) by replacing the semidefiniteness constraint by a more tractable one, i.e., X being *diagonally dominant* (resp. *scaled diagonally dominant*). The resulting problem is an LP (resp. SOCP). In the following, we describe an iterative method that approximate the optimal solution of (1) by using diagonally dominant matrices and by changing basis at each iteration. This approach was first published in [3].

First, note that the dual to (1) is given by

$$\begin{aligned} \inf y^T b \\ \text{s.t. } C - \sum_{i=1}^m y_i A_i \succeq 0. \end{aligned} \quad (2)$$

Consider the following DD strengthening for an SDP of the form (2) with optimal value d^*

$$\begin{aligned} d_0^* = \inf y^T b \\ \text{s.t. } \sum_{i=1}^m y_i A_i - C \text{ is } DD. \end{aligned} \quad (3)$$

Let $\tilde{Y} = \sum_{i=1}^m y_i A_i - C$ be an optimal solution with objective value $d_0^* \geq d^*$. Then there exists a matrix P such that $P^T \tilde{Y} P$ is a *diagonal* matrix. Thus, consider the second iteration

$$\begin{aligned} d_1^* &= \inf y^T b \\ \text{s.t. } & P^T \left(\sum_{i=1}^m y_i A_i - C \right) P \text{ is } DD \end{aligned} \quad (4)$$

Since there exists a feasible solution that is diagonal (the previous optimal solution), it readily follows that $d^* \leq d_1^* \leq d_0^*$. The only difference with the previous program is that, here we have a "better" basis P , meaning a basis such that $d_1 \leq d_0$.

Let now \tilde{y} be optimal for (4) and compute a matrix Q such that $Q^T (\sum_{i=1}^m \tilde{y}_i A_i - C) Q$ is diagonal. Then \tilde{y} is feasible for

$$\begin{aligned} d_2^* &= \inf y^T b \\ \text{s.t. } & Q^T \left(\sum_{i=1}^m y_i A_i - C \right) Q \text{ is } DD, \end{aligned} \quad (5)$$

and so $d^* \leq d_2^* \leq d_1^* \leq d_0^*$.

By continuing this hierarchy, we keep changing basis in order to improve the upper bounds for (1). We will present numerical experiments along with a discussion about convergence issues.

3 Conclusions and perspectives

In this abstract, we presented an algorithm to compute upper bounds to semidefinite programs thanks to a hierarchy of linear programs. At each iteration, we find an optimal basis for the next iteration as it is the case in the simplex algorithm for the linear case. Our aim is to analyze the numerical properties and convergence behavior of this method.

Références

- [1] Wolkowicz, Henry and Saigal, Romesh and Vandenberghe, Lieven. *Handbook of semidefinite programming*. Theory, algorithms, and applications. 2000 10.1007/978-1-4615-4381-7.
- [2] Ahmadi, Amir Ali and Majumdar, Anirudha. *DSOS and SDSOS optimization : LP and SOCP-based alternatives to sum of squares optimization*. 48th Annual Conference on Information Sciences and Systems (CISS) 2014, p.1-5, 10.1109/CISS.2014.6814141
- [3] Amir Ali Ahmadi and Georgina Hall. *Sum of Squares Basis Pursuit with Linear and Second Order Cone Programming*. arXiv, math.OA, 1510.01597, 2016