

MILP algorithm for outlet temperature optimization of a hybrid concentrated solar system for SHIP considering a 1D solar field and a dual phase thermocline storage

Simon Kamerling, Valéry Vuillerme, Sylvain Rodat

▶ To cite this version:

Simon Kamerling, Valéry Vuillerme, Sylvain Rodat. MILP algorithm for outlet temperature optimization of a hybrid concentrated solar system for SHIP considering a 1D solar field and a dual phase thermocline storage. 2021 Solar World Congress (SWC 2021), Oct 2021, online, Germany. hal-03608861

HAL Id: hal-03608861 https://hal.science/hal-03608861

Submitted on 15 Mar 2022 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



MILP ALGORITHM FOR OUTLET TEMPERATURE OPTIMIZATION OF A HYBRID CONCENTRATED SOLAR SYSTEM FOR SHIP CONSIDERING A 1D SOLAR FIELD AND A DUAL PHASE THERMOCLINE STORAGE

Simon Kamerling^{1,2}, Valéry Vuillerme¹ and Sylvain Rodat³ ¹Université Savoie Mont-Blanc, USMB(France) ²Université Grenoble Alpes, CEA, LITEN, INES, L2TS (France) ³CNRS-PROMES (France)

Funding: This work has received funding from the Ministère de l'Enseignement Supérieur, de la Recherche et de l'Innovation (MESRI), along with support from the European Union's Horizon 2020 research and innovation programme under grant agreement No 884213 (project FRIENDSHIP).



SYSTEM



REFERENCE: Kamerling, S., Vuillerme, V., Rodat, S., 2021. Solar Field Output Temperature Optimization Using a MILP Algorithm and a 0D Model in the Case of a Hybrid Concentrated Solar Thermal Power Plant for SHIP Applications. Energies 14, 3731. https://doi.org/10.3390/en14133731

CONTEXT

Heat for industry represent 25% of total final energy need; while electricity represent 20%: renewable solar heat is a promising option for process heat

METHOD

MAIN HYPOTHESIS = SOLAR FLUX KNOWN





TECHNOLOGIES

Industrial Process

(SHIP)



- MILP g. $\tau_{storage}(\%)$ Fig.1. $Q_{pailer}(MWh) \stackrel{1}{\rightarrow} Q_{defocused}(MWh)$ 10 20 30 40 10 20 $\tau_{storage}$ (%) 0.4 MILP CA1 **Fig.2**. $d. Q_{defocused}(MWh/month)$ c. Qlosses (MWh/month) 200





PROBLEMATIC

Parabolic dish



Hybridization: biomass,

RESULTS

gas, coal

Inlet data

system hybridized for SHIP?

How to optimize a solar

Efficiency of solar field increases with decreasing outlet temperature : Flexible Heat Integration

Fig.1. February 25th at Tarragona. Fig.2. Yearly results.

Optimization of SF's outlet temperature (Fig.1.f.) with the MILP algorithm, which in winter lowers heat losses (Fig.1.i. and 2.c) and maximizes storage use (Fig.1.g. and 2.b), as compared with Control Approach 1 (CA1) which always tries to work at process temperature. In summer, heat losses of the storage are minimized through defocalization in the

morning and storing only in the afternoon.

Solar fraction (Fig.2.a.): part of the energy supplied to the process from the sun, improved from **28.5**% (CA1) to **30.9**% thanks to the MILP algorithm.