

# Simulation of Transport and Impact of Moisture Content on the Biodegradation

Florent Hénon, Gerald Debenest, Xavier Lefebvre, Sébastien Pommier,

Damien Chenu, Michel Quintard

# ► To cite this version:

Florent Hénon, Gerald Debenest, Xavier Lefebvre, Sébastien Pommier, Damien Chenu, et al.. Simulation of Transport and Impact of Moisture Content on the Biodegradation. HPM4 2011, Apr 2011, Santander, Spain. pp.0. hal-03617735

# HAL Id: hal-03617735 https://hal.science/hal-03617735

Submitted on 23 Mar 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



# Open Archive TOULOUSE Archive Ouverte (OATAO)

OATAO is an open access repository that collects the work of Toulouse researchers and makes it freely available over the web where possible.

This is an author-deposited version published in : <u>http://oatao.univ-toulouse.fr/</u> Eprints ID : 5222

**To cite this version :** Henon, F. and Debenest, G. and Lefebvre, X. and Pommier, S. and Chenu, D. and Quintard, M. *Simulation of Transport and Impact of Moisture Content on the Biodegradation.* In: HPM4 2011, 27-28 Apr 2011, Santander, Spain.

# SIMULATION OF TRANSPORT AND IMPACT OF MOISTURE CONTENT ON THE BIODEGRADATION

# F. Henon, G. Debenest

Université de Toulouse ; INPT, UPS ; IMFT (Institut de Mécanique des Fluides de Toulouse) ; Allée Camille Soula, F-31400 Toulouse, France Email : fhenon@imft.fr

# X. Lefebvre, S. Pommier

Université de Toulouse, INSA, UPS, LISBP, 135 Avenue de Rangueil, F-31077 Toulouse, France INRA, UMR792, Ingénierie des Systèmes Biologiques et des Procédés, F-31400 Toulouse, France CNRS, UMR5504, F-31400 Toulouse, France

## D. Chenu

Veolia Environnement Recherche et Innovation ; 291 Avenus Dreyfous Ducas, 78520 Limay, France

## **M.** Quintard

Université de Toulouse ; INPT, UPS ; IMFT (Institut de Mécanique des Fluides de Toulouse) ; Allée Camille Soula, F-31400 Toulouse, France CNRS ; IMFT ; F-31400 Toulouse, France

SUMMARY: A large scale averaging method is used to study and simulate the influence of water on the solid waste biodegradation kinetics in landfill context. The basic process of interest is a two-phase flow transport model in homogeneous porous medium coupled with a hydrolysis biological reaction. The hydrolysis kinetic is weighted by a Heaviside function which depends on the local saturation level linked to the global moisture content. The shape of the large scale weighting function is in correlation with the experimental linear relationship described in literature for many solid wastes.

### **1. INTRODUCTION**

In Landfills, water content is a major ecological parameter of the anaerobic biodegradation of the solid waste into biogas (Farquhar and Rovers, 1973; Rees, 1980; Kasali et al., 1990; Gurijala and Suflita, 1993). The value of water content under which no biodegradation activity is observed ranged from 0.15 to 0.5 expressed as g water/g dried waste (Buivid et al., 1981; Barlaz et al., 1990; Yang and Chang, 1998; Rodriguez et al., 2001). In practice, the fresh refuse

moisture ranges from 0.25 to 0.65 (Owens and Chynoweth, 1993; Aguilar et al., 1999; Barina et al., 2003; Lefebvre et al., 2003). Therefore, in a standard situation, biological reactions in landfills may be strongly water limited. Besides, biodegradation improvement by increasing the waste water with leachate injection has been widely demonstrated (Barlaz et al., 1990; Metha et al., 2002, Benbelkacem et al., 2010). In the landfill context, the cellulosic materials in paper or cardboard form are mainly concerned since initially very deficient water and concentrating the major part of the biodegradable organic matter.

The optimisation of the leachate recirculation monitoring need a good description of both the water transport inside such porous system and the water mediated biological reactions. At the scale of the landfill, the water transport are generally considered in the macro-porosity defined by the space between the waste particles (Rosqvist and Destouni, 2000; Hartmann et al, 2004; Rosqvist et al., 2005). However, the biological reaction scale is mainly at the surface and above all inside the organic particles that are micro-porous (especially paper, cardboard). Also, the water transport inside an organic particle needs to be introduced.

At the laboratory experimental observation scale ( $L \approx 10cm$ ), a linear dependency of both the biodegradation kinetic rates and the amount of biodegraded organic waste with the global water content is generally proposed. This linear correlation is defined between a minimal moisture content and an optimal one (Bogner, 1990; Aran et al., 1999; Pommier et al., 2007). These observations consolidate the assumption of a waste activation controlled by the local moisture content: the solid needs to be wet enough to be available for biological reactions. At larger scale, this concept of activation has been modeled by a linear factor describing the waste bioavailability and applied to the amount of solid matter accessible for biodegradation, as reported by Pommier et al. (2007). At local scale this activation concept amounts to segregating the solid matter into active matter and inactive matter, the state of a local elementary volume being governed by its moisture content (or its saturation level). For that, a critical moisture content could be defined, below which the solid matter is considered as inactive, and above which the solid matter is considered as active.

In this paper, transport and biodegradation reaction at the particle dimension are focused. A cotton paper strip is used as cellulosic matter. Mechanisms are modelled at the local-scale (Darcy's scale) both for the unsaturated flow and water transfer into a waste particle and for the biological hydrolysis reaction. Results of simulations are discussed and compared to the global experimental relationship between water content and biodegradation yield, proposed in literature.

#### 2. THEORETICAL ELEMENTS

For an effective medium, the flow is considered governed at low Reynolds values by a Darcy's equation. For an unsaturated flow, two main methods are usually used: two Darcy's equations for liquid and gas phase and the Richards's equation. The first method has often been discussed in the literature (Withaker, 1986; Auriault, 1987; Lasseux et al., 1996; Hassanizadeh and Gray, 1997; Hilfer, 1998; Wang, 2000). Here, the second approach Richards equation is preferred because the processes are slow enough to neglect pressure gradients in the gas phase ( $\gamma$ -phase). Assuming Darcy's law is valid, Richards equations can be used to describe the water flow in unsaturated porous medium (Richards, 1931). This assumption has been developed in Chenu, 2007, and the validity of Richards equation is discussed herein. Therefore, for a single porosity domain, the water transport equation is given by the following equation (1)

$$\varepsilon \partial_{t} S_{\beta} + \nabla \cdot \left[ -\frac{\mathbf{K} k_{r\beta} (S_{\beta})}{\mu_{\beta}} \rho_{\beta} \cdot \nabla \left( \frac{p_{c} (S_{\beta})}{\rho_{\beta}} + gz \right) \right] = 0, \qquad (1)$$

where  $S_{\beta}$  is the local water saturation and  $\varepsilon$  the total porosity of the medium. In eqn (1), **K** represents Darcy's law permeability tensor (Whitaker, 1986),  $k_{r\beta}$  is the classic relative permeability for the water phase ( $\beta$ -phase) and g is gravity. To describe  $p_c(S_{\beta})$ , different models exist. In this work, the capillary pressure  $p_c(S_{\beta}) = p_{\beta} - p_{\gamma}$  is linked with  $S_{\beta}$  and  $k_{r\beta}$  through the classic Van Genuchten Relationship [Eqns (2), (3)],

$$Se_{\beta} = \frac{S_{\beta} - S_{ir}}{S_{sat} - S_{ir}} = \left[1 + (\alpha | p_c|)^n\right]^{-m}, \qquad p_c < 0, \qquad (2a)$$

$$Se_{\beta} = 1,$$
  $p_c \ge 0,$  (2b)

$$k_{r\beta} = Se_{\beta}^{l} \left[ 1 - \left( 1 - Se^{1/m} \right)^{m} \right]^{2}, \qquad p_{c} < 0, \qquad (3a)$$

$$k_{r\beta} = 1, \qquad p_c \ge 0, \qquad (3b)$$

where  $Se_{\beta}$  is the local effective water saturation,  $S_{sat}$  is the saturated saturation,  $S_{ir}$  is the irreducible saturation,  $\alpha$  is the inverse of a specific pressure, n is the pore size distribution index which determines the slope of the retention curve, m = 1 - 1/n, l is the tortuosity parameter. In equation (1), the term,  $-\nabla p_c (S_{\beta})/\rho_{\beta}$  represent the capillary mass force tending to produce a motion of water in the porous medium. The velocity and acceleration of the capillary water are everywhere zero when the capillary mass force just balances gravity. This configuration is called capillary equilibrium. As the capillary equilibrium is not reached, there is a resultant watermoving force and then a capillary flow.

The cellulose anaerobic degradation is known to be controlled by its hydrolysis into monomers. Such a biological mechanism is commonly described by a first order reactive scheme relative to cellulose content. Also, hydrolysis reaction at the local-scale is given by Eqn (4),

$$\partial_t Xs(t) = -k_h h(S_\beta(\mathbf{x}, t)) Xs(t), \tag{4}$$

where Xs is the quantity of hydrolysable matter present in the medium and  $k_h$  is the hydrolysis constant. The first order kinetics is weighted by a Heaviside function  $h = h(S_{\beta}(\mathbf{x},t))$  with threshold depending of a local specific activation saturation,  $S_{act}$  (Figure 1).

#### Insert Figure 1

Figure 1. Weighting function  $h = h(S_{\beta}(\mathbf{x}, t))$  of the hydrolysis reaction. The weighting function is equal to zero for  $S_{\beta} < S_{act}$  and equal to 1 for  $S_{\beta} > S_{act}$ .

The matrix zone where the local saturation is greater than the local activation saturation is

referred as activated volume since the hydrolysis reaction can start while it is completely bypassed elsewhere.

In the paper, the smallest pores are often less than  $0.1\mu m$  and larger pores may be of the order of 1mm according the manufacturing process. The smallest bacteria have a size of 0.1 to  $0.2\mu m$ and the larger ones can reach a size of 0.75mm. In this work, the transport of bacteria is considered totally coupled with the water transport and the sizes of meso-pores and micro-pores are not an obstacle for the migration of bacteria. It means that bacteria are transported in the water phase without any coupling with viscosity and density. It is considered as dilute species.

The local specific activation saturation depends upon both the physicochemical properties of the porous medium and to the micro-organisms growth capacities in such limited water environment. At this point, it is more convenient to describe what is called by local-scale and large-scale. Local-scale is a sufficient number of micro-pores and meso-pores so that Darcy's law is valid [Figure 2 (b)]. From a reactive point of view, since the reaction rate is closely related to the water content, the radius of the volume characterizing the local-scale should be large enough in relation to the variations of the water content at the pore-scale. Large-scale is a volume containing a large number of volumes characterizing the local-scale and can be represent an individual particle of waste of volume  $V_{\infty}$  [Figure 2 (a)].

#### Insert Figure 2

Figure 2. (a) Particle of waste, slip of paper (large-scale). (b) Large number of meso and micropores of the paper (local-scale). (c) Micro-porosity, primary fibers of the paper. Photos: Coste, G., INP-Pagora, Grenoble, <u>http://cerig.efpg.inpg.fr</u>, 02/2011.

Following this description, it is possible to introduce the large-scale spatial average of a localscale generic function  $\psi(\mathbf{x}, t)$  by

$$\psi^*(t) = \frac{1}{V_{\infty}} \int_{V_{\infty}} \psi(\mathbf{x}, t) dV .$$
(5)

The large-scale spatial average of the hydrolysable matter and the effective weighting function  $(Xs^* \text{ and } h^*)$  including the effect of saturation heterogeneities on a volume corresponding to the volume  $V_{\infty}$ , shown in Figure 2(a), are sought.

The large-scale spatial average of saturation is related to the global water content by applying Eqn (6).

$$w^* = \frac{1000}{\rho_{DM}} \varepsilon S^*_{\beta} \tag{6}$$

Then, the value of the large-scale spatial average of weighting function can be expressed in terms of the global water content for the water content initially injected into  $V_{\infty}$  [Figure 2(d)]. For each initial amount of water injected into  $V_{\infty}$ , this approach is repeated to obtain the shape of the large-scale spatial average of the weighting function depending on the global water content of  $V_{\infty}$  [Figure 2(d)].

#### **3. BIOCHEMICAL AND PHYSICAL PROPERTIES FOR SIMULATION**

The system taken into consideration is a cellulosic strip whose dimensions are  $1cm \times 5cm \times 0.7cm$  see pictures below. This paper was manufactured from cotton without additives. The biochemical and physical properties used for simulations are given in **Erreur**! Source du renvoi introuvable.

#### **Insert Picture 1**

Picture 1. Cotton paper strip of dimension  $1cm \times 5cm \times 0.7cm$ .

In such matrix, the micro-pores are formed by the entanglement of the primary fibers [Figure 2 (c)] while the meso-pores result from the manufacturing process or from mechanical stresses undergone during the life of the waste [Figure 2 (b), Picture 1]. As described previously, the water transport dynamics inside the porous solid are controlled both by the permeability K and, especially, by the capillary properties. The Darcy's law permeability tensor is considered as isotropic [Eqn (7)]

$$\mathbf{K} = K \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix},$$
(7)

where *K* is the absolute permeability. This is an assumption which could be discussed, but our samples do not show any anisotropic behaviour. They seem to be homogeneous as there is no preferential orientation. Given the wide variety of existing paper, it is not easy to define a value for *K*. The values listed in literature range from  $1 \times 10^{-12} m^2$  to  $1 \times 10^{-15} m^2$  depending of the variety of paper (Lindsay, 1988; Nilsson and Strenström, 1997). In Lindsay (1988), transverse permeabilities are measured for different linearboard handsheets compressed to porosities between 0.6 and 0.9. Permeability values are reported as a function of the porosity through an exponential function. For sheets with a porosity between 0.85 and 0.9, the value of transverse permeability is of the order of  $K = 1 \times 10^{-12} m^2$ . Although the studied paper is really different, simulations where made with a value of  $K = 1 \times 10^{-12} m^2$ .

The capillary properties of this paper have been approximated by an inverse numerical method from the characteristic scale of the capillary fringe observed during the imbibition experiments. The capillary curve obtained by this method is given in Figure 3.

#### Insert Figure 3

Figure 3. Imbibition curve of the cotton paper.

The irreducible saturation  $S_{ir}$  is considered as immobile water quantity highly bounded to the cellulose fibers. Here, a value is deduced from the measurement of the sorption isotherm curve given in the Figure 4. Experimental data are compared to literature data (Parker et al., 2006). Similar profiles are obtained whatever the kind of paper or cardboard. The irreducible locale-scale water content,  $w_{ir}$  is supposed to be near the water content when the water activity  $a_w$  is equal to 1. For our cellulose matter, the value is measured at 0.28 g/g.  $S_{ir}$  is also calculated by the relationship between moisture content and saturation Eqn (8).

$$S_{ir} = \frac{W_{ir}\rho_{DM}}{\varepsilon},\tag{8}$$

where  $\rho_{\rm DM}$  is the density of the dried matter (expressed in  $g \cdot cm^{-3}$ ) and  $\varepsilon$  its porosity.

Finally, in biological reaction point of view, value for the  $S_{act}$  parameter is necessary for simulation. No experimental values are available. Indeed, the local reaction scale is very smaller than the scale that can be directly and experimentally observed. Consequently, the value of  $S_{act}$  used here for simulations was chosen to be consistent with the experimental results obtained at the large scale.  $S_{act}$  is fixed at 0.22 which corresponds to a local-scale water content of 0.95 g water / g DM.

#### Insert Figure 4

Figure 4. Sorption isotherm curve of the cotton paper comparison to literature data (from Parker et al., 2006).

Table 1. Experimental data for	model parameters	
Experimental data	Unit	Value
Water content, $w(1)$	%, g_water / g_ <i>DM</i>	3.5
Organic matter (1)	%, DM	99.00
Mineral matter (1)	%, <i>DM</i>	1.00
COD / DM (1)	g / g	1.09
<b>BMP</b> (2)	NmL CH4 / g_COD	321
Biodegradability (2)	%, DCO	92
Kinetic rate, $k_h(2)$	$s^{-1}$	8.10-7
Porosity, $\Box$ (3)	-	0.85
Absolute permeability, K	$m^2$	$1 \times 10^{-12}$
Density of dried matter,	$g.cm^{-3}$	0.197
$\boldsymbol{ ho}_{DM}\left( l ight)$		
Wir	$g_water / g_DM$	0.28
$S_{ir}$	-	0.065
α	$Pa^{-1}$	$4.5 \times 10^{-3}$
l	-	0.5
m	-	0.6
n	-	2.5
Sact		0.22

Table 1. Experimental data for model parameters

(1) Standard methods (2) according Pommier et al. (2007) (3) Imbibition method

#### 4. NUMERICAL RESULTS

For the numerical simulations, a 2D cotton paper strip is considered. The dimensions are  $1cm \times 5cm$ . This strip is submitted to gravitational field. Starting from water saturation near the irreducible saturation [Figure 5(a)], a defined water amount is injected into the medium [Figure 5(b)]. The capillary equilibrium is reached by solving Eqn (1) [Figure 5(c)] and is achieved in short time ( $\approx 10d$ ) compared to the biological degradation time of the hydrolysable matter (100*d*). The water spatial distribution dynamic can be considered as quasi decoupled from the biodegradation process kinetics and the local-scale fields obtained [Figure 5(d)] can be used

to obtain the large-scale spatial averages fields with Eqn (5).

#### Insert Figure 5

Figure 5. (a) Initial local water saturation field. (b) Local water saturation field after an injection of water of 5h 33mn. (c) Local water saturation field after capillary equilibrium. (d) Hydrolyzed quantity of hydrolysable matter after 100 days (in %).

Then, successive similar water additions are simulated up to reach the value of  $S_{sat}$  of the cotton paper strip. For each  $w^*$ , the simulation gives a value for  $h^*$  and  $1 - Xs^*/Xs^*_{ini}$  which is the large-scale spatial average of the hydrolyzed quantity of hydrolysable matter. In Figure 6,  $h^*$  and  $1 - Xs^*/Xs^*_{ini}$  are plotted versus  $w^*$ .

#### Insert Figure 6

Figure 6. Large-scale spatial average of the weighting function of the hydrolysis reaction,  $h^*$ , and large-scale spatial average of the hydrolyzed quantity of hydrolysable matter,  $1 - Xs^*/Xs^*_{ini}$ , in terms of global water content  $w^*$  in a strip of paper measuring  $1cm \times 5cm$ . Normalized maximum biogas production for paper/cardboard (Pommier et al., 2007)  $CH_4$  max/ $CH_4$  out, in terms of global water content  $w^*$ .

Starting at the local scale with the local-scale weighting function, *h*, the large-scale spatial average of the weighting function,  $h^*$ , and the large-scale spatial average of the hydrolysed matter,  $1 - Xs^*/Xs^*_{ini}$ , are directly calculated from Eqn (5). The shapes of  $h^*$  and  $1 - Xs^*/Xs^*_{ini}$  are in good agreement with the experimental relationship between water content and biodegradation yield, listed in literature. The analogy may, for example, be made by comparing  $1 - Xs^*/Xs^*_{ini}$  to the normalized maximum biogas production for paper/cardboard,  $CH_4 _{max}/CH_4 _{opt}$ , obtained by Pommier et al., (2007). It appears that these relationships are not completely linear because of capillary effects, which are not either. In Figure 6,  $h^*$  is different from  $1 - Xs^*/Xs^*_{ini}$  for values of  $w^*$  between 0 and 1 because, for these values, the capillary equilibrium time become not negligible compared to the biological degradation time of the hydrolysable matter. A relatively large amount of matter is then hydrolysed during the capillary equilibrium time in the area where  $S_{\beta} > S_{sat}$  and  $1 - Xs^*/Xs^*_{ini}$  is decoupled from  $h^*$ . The capillary equilibrium time mostly depend of the absolute permeability of the medium and pilot the coupling or decoupling between the water spatial distribution dynamic and the biologgradation process kinetics.

Moreover, a sensitivity analysis on different parameters show that the dominant parameters on the shape of  $h^*$  and  $1 - Xs^*/Xs^*_{ini}$  are the Van Genuchten parameters,  $l, m, \alpha$ , and the local-scale activation water saturation,  $S_{sat}$ . For a fixed spatial characteristic scale of the paper strip, Van Genuchten parameters control the slope of the curve, while the local-scale activation water saturation controls the position of the curve on the global water content axis, that is to say, the values of  $w^*_{min}$  and  $w^*_{opt}$ .

From this model, it is possible to simulate the evolution of a cellulose particle biodegradation with time in function of its global water content  $w^*$ . The curves in Figure 7 have similar profiles

corresponding to a first order reaction but are different from the maximal amount of degraded substrates.

#### Insert Figure 7

Figure 7. Simulated hydrolysable matter production kinetics at different water contents.

This points out the relevance of the model developed and especially the mechanisms considered. It is possible to take into account the physical properties of the porous matrix, the heterogeneity of the water inside this matrix and consequently the local bio-accessibility of cellulose substrate. One of the critical parameter is the value of  $S_{act}$ . No data are available, because the experimental scale is always larger than the reaction scale. Here, an inverse method was adopted. Indeed the value was approximated from the value of  $w_{min}^*$  and  $w_{opt}^*$  measured at the experimental large-scale.

The model shows also the importance of the solid dimension L on the slope of the relationship at the large-scale. Figure 8 gives an example for two cellulose strips whose L are 1cm and 5cm. As the capillary fringe is large compared to L, the heterogeneities of saturation are reduced into the cellulose and the profile of  $h^*$  comes closer to a Heaviside function local form. In contrast, when L is large enough compared to the capillary fringe, the profile of  $h^*$  is independent of L. However, whatever the dimension L, all the curves  $h^* = f(w^*)$  have a same and unique intersection point corresponding to the activation saturation  $S_{act}$ . From two dimensions L, it should be possible to obtain an experimental estimation of  $S_{act}$  by the identification of the intersection point.

#### **Insert Figure 8**

Figure 8. Large-scale spatial average of the weighting function of the hydrolysis reaction,  $h^*$ , in terms of global water content of the strip of paper,  $w^*$ , for strips of paper with a spatial characteristic scale of 1cm and 5cm.

#### **5. CONCLUSIONS**

The relationship between the local water content and the biological activity is modelled and simulated at the particles scale. The model couples two-phase flow and reactive transport. The reaction rate is controlled by the water saturation at each scale. The main assumption is that, at the local-scale, the reaction is weighted by a Heaviside function which depends on the local saturation level.

The determination of the limitation law for hydrolysis reactions at the large-scale, have showed that it depends on several parameters: capillary properties,  $S_{act}$  and transport properties. All these parameters are identifiable from experimental measurements.

If a general law is used in landfills biodegradation, this reaction scheme and the limitation could be estimated using the approach developed in this paper. Simulations are in good agreement with the experimental data. The model succeeds to predict the impact of water content on waste anaerobic biodegradation at the particle scale. The effects of scale and especially the downscaling to investigate the local scale effects (i.e dimensions less than 1cm) will be made in

a forthcoming paper in order to conclude on the result showed in Figure 8.

#### ACKNOWLEDGEMENTS

This work was supported by the French National Research Agency (ANR) and the French National Agency for Energy and Environment (ADEME). The Authors wish to thank Mr. Gérard Coste from INP-Pagora Grenoble (France) for photos of paper obtained by electron microscopy.

#### REFERENCES

- Aguilar, O., Aran, C., Houi D. (1999). Effects of landfill operations on temperature rise. Proceedings Sardinia 99, Seven Waste Management and Landfill Symposium, Cagliari, Italy. 559–566.
- Aran, C., Lefebvre, X., Bacon, G., Houi, D. (1999). Modelisation of mass and heat transfers in sanitary landfills. II8 International Symposium Anaerobic Digestion of Solid Waste, June 15–18, Barcelona, Spain. 252–257.
- Auriault, J.-L. (1987). Nonsaturated deformable porous media : Quasistatics. Transport in Porous Media, V2(1) :45–64.
- Barina, G., Gisber, T., Puglierin, L., Boin, B., Lefebvre, X., Gemignani, A. (2003). Integrated study of waste characteristics, effluents and waste mass evolution after 4 years of large scale recirculation. Proceedings Sardinia 2003, 9th International Landfill Symposium, CISA publisher, Cagliari, Italy.
- Barlaz, M.A., Ham, R.K., Shaefer, D.M. (1990). Methane production from municipal refuse: A review of enhancement techniques and microbial dynamics. Crit Rev Environ Control 19:557–584.
- Benbelkacem, H., Bayard, R., Habdelhay, A., Zhang, Y., Gourdon, R. (2010). Effect of leachate injection modes on municipal solid waste degradation in anaerobic bioreactor. Bioresource Technology 101:5206–5212.
- Bogner, J.E. (1990). Controlled study of landfill biodegradation rates using modified BMP assays. Waste Management Res 8:329–352.
- Buivid, M.G., Wise, D.L., Blanchet, M.J., Remedios, E.C., Jenkins, B.M., Boyd, W.F., Pacey, J.G. (1981). Fuel gas enhancement by controlled landfilling of municipal solid waste. Resour Conserv 6:3–20.
- Chenu, D. (2007). Modélisation des transferts réactifs de masse et de chaleur dans les installations de stockage de déchets ménagers : application aux installations de type bioréacteur. PhD Thesis, Institut National Polytechnique de Toulouse.
- Coste, G., INP-Pagora, Grenoble, http://cerig.efpg.inpg.fr, 02/2011.
- Farquhar, G.J., Rovers, F.A. (1973). Gas production during refuse decomposition. Water Air Soil Pollut 2:483–495.
- Gurijala, K.R., Suflita, J.M. (1993). Environmental factors influencing methanogenesis from refuse in landfill samples. Environ Sci Technol 27:1176–1181.
- Hassanizadeh, S. M. and Gray, W. G. (1997). Fluid Transport in Porous Media. Advances in Fluid Mechanics, chapter Recent Advances in Theories of Two-Phase Flow in Porous Media, pages 105–160. Computational Mechanics Publications, Boston.
- Hartmann, F., Bader, H.-P., and Scheidegger, R. (2004). Model simulations for describing water transport in a landfill with bottom ash from a municipal solid waste incinerator (MSWI): model validation and scenarios. Waste Management Research, 22(5) :324–333.
- Hilfer, R. (1998). Macroscopic equations of motion for two-phase flow in porous media. Phys.

Rev. E, 58(2) :2090–2096.

- Kasali, G.B., Senior, E., Watson-Craik, I.A. (1990). Solid state refuse promotion methanogenic fermentation: Control and promotion by water addition. Lett Appl Microbiol 11:22–26.
- Lasseux, D., Quintard, M., and Whitaker, S. (1996). Determination of permeability tensors for two-phase flow in homogeneous porous media: Theory. Transport in Porous Media, V24(2): 107–137.
- Lefebvre, X., Budka, A., Galtier, L., Barina, G., Puglierin, L. (2003). Assessment of the evolution of waste biodegradability with time and operation conditions. Proceedings Sardinia 2003, 9th International Landfill Symposium, CISA publisher, Cagliari, Italy.
- Lindsay, J. D. (1988). The anisotropic permeability of paper: theory, measurements, and analytical tools. IPC Technical Paper Series Number 298. The Institute of Paper Chemistry, Appleton, Wisconsin.
- Mehta, R., Barlaz, M.A., Yazdani, R., Augenstein, D., Bryars, M., Sinderson, L. (2002). Refuse decomposition in the presence and absence of leachate recirculation. J Environ Eng 128(3):228–236.
- Nilsson, L. and Stenström, S. (1997). A study of the permeability of pulp and paper. Int. J. Multiphase Flow 23(1):131-153.
- Owens, J.M., Chynoweth, D.P. (1993). Biochemical methane potential of municipal solid waste (MSW) components. Water Sci Technol 27(2):1–14.
- Parker ME, Bronlund JE, Mawson AJ. (2006). Moisture sorption isotherms for paper and paperboard in food chain conditions. Packaging Technology and Science 19(4):193–209.
- Pommier, S., Chenu, D., Quintard, M., Lefebvre, X. (2007). A logistic model for the prediction of the influence of water on the solid waste methanization in landfills. Biotechnol. Bioeng. 97, 473-482.
- Rees, J.F. (1980). Optimisation of methane production and refuse decomposition in landfills by temperature control. J Chem Technol Biotechnol 30:458–465.

Richards, L.A., (1931). Capillary conduction of liquids in porous media. Physics 1, 318–333.

- Rodriguez, C., Hiligsmann, S., Lardinois, M., Destain, J., Radu, J., Charlier, R., Thonart, P. (2001). Cellulose enzymatic availability in solid waste Proceedings 8th International Waste Management and Landfill Symposium, Sardinia 2001.
- Rosqvist, H., and Destouni, G. (2000). Solute transport through preferential pathways in municipal solid waste. Journal of Contaminant Hydrology, 46(1-2):39–60.
- Rosqvist, N. H., Dollar, L. H., and Fourie, A. B. (2005). Preferential flow in municipal solid waste and implications for long-term leachate quality : valuation of laboratoryscale experiments. Waste Management Research, 23(4) :367–380.
- Wang, L. (2000). Flows through porous media : A theoretical development at macroscale. Transport in Porous Media, V39(1):1–24.
- Whitaker, S. (1986). Flow in porous media II: the governing equations for immiscible, two-phase flow. Transport in Porous Media, 1(1):105–125.
- Yang, S.S., Chang, H.L. (1998). Effect of environmental conditions on methane production and emission from paddy soil. Agric Ecosyst Environ 69:69–80.

#### NOMENCLATURE

$a_w$	water activity
DM	dry matter
8	gravity, $m \cdot s^{-2}$
Xs	hydrolyzable matter, % DM

$Xs^*$	large-scale spatial average of hydrolyzable matter, % DM
$h^*$	large-scale spatial average of the weighting function of the hydrolysis
reaction	large-scale spatial average of the weighting function of the hydrorysis
K	Darcy's law permeability tensor, $m^2$
Κ	absolute permeability, $m^2$
$k_h$	local-scale hydrolysis constant, $s^{-1}$
$k_{r\beta}$	relative permeability for the water phase
L	Spatial characteristic scale of the strip of paper, m
l	tortuosity parameter
п	pore size distribution index
$p_c$	local-scale capillary pressure, <i>Pa</i>
$p_{\beta}$	local-scale water pressure, <i>Pa</i>
$p_{\gamma}$	local-scale gas pressure, <i>Pa</i>
$S_{act}$	local-scale activation water saturation
$S_{ir}$	irreducible saturation
$S_{sat}$	maximal saturation
$Se_{\beta}$	local-scale effective water saturation
$S_{\beta}$	local-scale water saturation
$S^*_eta$	large-scale spatial average of water saturation
$V_{\infty}$	large-scale averaging volume, $m^3$
W	local-scale water content, g water / g DM
$w^{*}$	global water content, g water / g DM
W <sub>ir</sub>	irreducible locale-scale water content, $g$ water / $g$ DM
$w^*_{\min}$	large-scale minimum water content, g water / g DM
$W_{opt}^{*}$	large-scale optimum water content, g water / g DM
Z.	height from reference level, m
α	Van Genuchten parameter, $Pa^{-1}$
ε	total porosity
$\mu_{eta}$	dynamic viscosity of water, $kg \cdot m^{-1} \cdot s^{-1}$
$ ho_{\scriptscriptstyle DM}$	density of dried matter, $kg \cdot m^{-3}$
$ ho_{\scriptscriptstyleeta}$	density of water,