



# Robust Global Asymptotic Stabilization of Linear Cascade Systems with Hysteresis Interconnection

Alessandro Bosso, Luca Zaccarian, Andrea Tilli, Matteo Barbieri

## ► To cite this version:

Alessandro Bosso, Luca Zaccarian, Andrea Tilli, Matteo Barbieri. Robust Global Asymptotic Stabilization of Linear Cascade Systems with Hysteresis Interconnection. IEEE Control Systems Letters, 2022, 7, pp.337 - 342. 10.1109/LCSYS.2022.3188748 . hal-03622392

HAL Id: hal-03622392

<https://hal.science/hal-03622392>

Submitted on 29 Mar 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Robust Global Asymptotic Stabilization of Linear Cascade Systems with Hysteresis Interconnection

Alessandro Bosso<sup>1</sup>, Luca Zaccarian<sup>2</sup>, Andrea Tilli<sup>1</sup>, and Matteo Barbieri<sup>1</sup>

**Abstract**—We address the problem of setpoint regulation for cascaded minimum-phase linear systems interconnected through a scalar hysteresis, modeled as a Prandtl-Ishlinskii operator. Employing well-posed constrained differential inclusions to represent the hysteretic dynamics, we formulate the control problem in terms of stabilization of a compact set of equilibria depending on the hysteresis states. For our design, we firstly consider a proportional-integral controller for linear systems with hysteretic input, and provide model-free sufficient conditions based on high-gain arguments for closed-loop stability. Then, the controller is dynamically extended to obtain an inversion-free stabilizer of the overall cascade. For the presented schemes, we prove robust global asymptotic stability of a compact set that ensures setpoint regulation, regardless of the hysteresis states.

## I. INTRODUCTION

Smart materials are becoming widespread nowadays due to their unique sensing and actuation capabilities [1], leading to innovative solutions in several application domains such as next-generation mechatronic technologies. For control systems involving smart materials, one of the major challenges is the typical presence of hysteretic behaviors, causing performance deterioration if not correctly addressed. In this context, the control-theoretical literature has dedicated several works to hystereses represented with the Prandtl-Ishlinskii (PI) operator [2], particularly useful given the existence of its analytical inverse [3]. Numerous control strategies have been developed based on the explicit inversion of the PI operator [4], [5], [6]. However, the computational burden or the inversion inaccuracy has led to inversion-free or implicit inversion solutions, involving integral control [7], adaptive control [8], or adaptive conditional servo-compensation [9].

All the works mentioned above consider systems with hysteretic inputs. In this note, instead, we address inversion-free setpoint regulation for linear cascade systems where a finite-dimensional PI operator affects the interconnection. This problem is inspired by operator-based models of thermal shape memory alloys (SMAs), comprising a thermal and a mechanical subsystem where the temperature influences the elastic behavior through a hysteresis [10], [11]. Although highly nonlinear and coupled models typically describe thermal SMAs, we believe that the methodologies developed in this work are instrumental in addressing those systems,




Fig. 1. Block representation of system (1).

paving the way towards robust controllers for a large class of smart actuators. Specifically, we consider a cascade where the system affecting the hysteresis input is an integrator (see Fig. 1). This choice is made to streamline the presentation, as the proposed strategy is straightforwardly extended to any linear system that can be robustly stabilized by output feedback. On the other hand, we require that the system with hysteretic input has minimum phase and relative degree 1, while we aim to relax this assumption in future works.

Our design is based on the representation of the PI operator as a sum of stop operators, which can then be modeled as a well-posed differential inclusion constrained in a compact set [12, Ch. 2]. In this setting, we develop a setpoint regulation framework based on the analysis tools for hybrid dynamical systems [13]. We firstly address the scenario wherein the hysteresis input can be assigned as a control input. In that context, we show that a proportional controller ensures practical regulation, whereas the inclusion of an integral action enables global exponential stabilization. As compared to the integrator-based approach of [7], we do not rely on an LMI to tune the control gains. Instead, we provide high-gain arguments that ensure quadratic stability without any knowledge of the system matrices and of the hysteresis. The proportional-integral controller is then combined with a high-gain filter of the regulation error to obtain the design for the overall cascade. For the closed-loop dynamics, we prove the existence of a globally robustly asymptotically stable attractor ensuring setpoint regulation, regardless of the hysteresis states.

The paper is organized as follows. First, in Section II, we introduce the considered class of systems, present the state-space hysteresis model, and define the control problem. Section III is dedicated to the control design for linear systems with hysteretic input. Next, Section IV develops the overall control scheme and provides the main stability result. Finally, Section V reports numerical simulations and Section VI concludes the paper.

## II. LINEAR CASCADE SYSTEMS WITH HYSTERESIS INTERCONNECTION

### A. Model Description

We consider a class of systems comprising two linear subsystems, having states  $\xi \in \mathbb{R}^n$  and  $\zeta \in \mathbb{R}$ , interconnected

<sup>1</sup>A. Bosso, A. Tilli, and M. Barbieri are with the Department of Electrical, Electronic, and Information Engineering (DEI), University of Bologna, Italy. Email: {alessandro.bosso, andrea.tilli, matteo.barbieri15}@unibo.it

<sup>2</sup>L. Zaccarian is with LAAS-CNRS, Université de Toulouse, and the Department of Industrial Engineering, University of Trento, Italy. Email: zaccarian@laas.fr




Fig. 2. Left: representation of a play operator. Right: behavior of a Prandtl-Ishlinskii operator with input  $\zeta(t) = 0.04t \sin(t)$ .

through a scalar hysteresis  $\Gamma[\cdot]$ , as shown in Fig. 1:

$$\begin{aligned} \dot{\xi} &= A\xi + b\Gamma[\zeta] \\ \dot{\zeta} &= u \end{aligned} \quad y_a := \begin{bmatrix} y \\ \zeta \end{bmatrix} := \begin{bmatrix} c^\top \xi \\ \zeta \end{bmatrix}, \quad (1)$$

with control input  $u \in \mathbb{R}$  and available output  $y_a \in \mathbb{R}^2$ . In (1), matrix  $A$  and vectors  $b$  and  $c$  have appropriate dimensions, while hysteresis  $\Gamma[\cdot]$  has been indicated in square brackets to highlight its intrinsically dynamic behavior.

For plant (1), we design a controller ensuring asymptotic setpoint regulation of constant reference signals for the output  $y$  of the  $\xi$ -subsystem, without any knowledge of matrices  $A$ ,  $b$ , and  $c$  (except for the sign of  $c^\top b$ ) or of the hysteresis  $\Gamma[\cdot]$ . This objective is addressed under the following assumptions.

**Assumption 1.** Pair  $(A, b)$  is reachable and pair  $(c^\top, A)$  is observable.

**Assumption 2.** System  $\dot{\xi} = A\xi + bv$  with output  $y = c^\top \xi$  has relative degree 1 and is minimum phase. Furthermore, it holds that  $c^\top b > 0$ .

### B. Prandtl-Ishlinskii Operator

We model hysteresis  $\Gamma[\cdot]$  in (1) as a finite-dimensional Prandtl-Ishlinskii (PI) operator, given by a weighted sum of basic hysteresis functions known as play operators. Specifically, following [14] and [7], for any continuous input  $\zeta(\cdot)$  that is monotone in each interval  $t \in [t_{i-1}, t_i]$  of the partition  $0 = t_0 < t_1 < \dots < t_j = T$ , the output  $\phi(\cdot)$  of a play operator  $P_r[\cdot]$ , with constant radius  $r \geq 0$ , is given by:

$$\phi(t) = \max\{\min\{\zeta(t) + r, \phi(t_{i-1})\}, \zeta(t) - r\}. \quad (2)$$

See Fig. 2 for a depiction of the play operator. The finite-dimensional Prandtl-Ishlinskii operator is then defined as [7]:

$$\Gamma[\zeta] := \mu_0\zeta + \sum_{i=1}^p \mu_i P_{r_i}[\zeta], \quad (3)$$

where  $P_{r_i}[\cdot]$ ,  $i \in \{1, \dots, p\}$ , are play operators with constant radii  $r_i$ , while  $\mu_i$ ,  $i \in \{0, \dots, p\}$ , are constant scalar weights. Note that the linear term multiplying  $\mu_0$  corresponds to the output of a play operator with radius  $r_0 = 0$ . For simplicity, we consider the case where the radii satisfy  $0 < r_1 < \dots < r_p$ , while for weights  $\mu_i$  we require the following property.

**Assumption 3.** The weights of the Prandtl-Ishlinskii operator in (3) satisfy  $\mu_i > 0$ , for all  $i \in \{0, \dots, p\}$ .

In Fig. 2, we report the behavior of a Prandtl-Ishlinskii operator for an illustrative input signal.

### C. State-Space Representation via Constrained Differential Inclusions

We provide a state-space representation of the PI operator (3) based on the reformulation proposed in [12, Ch. 2] of the play operator as a constrained differential inclusion. Specifically, we employ the complement of the play operator  $P_r[\cdot]$ , called stop operator and denoted by  $S_r[\cdot]$ . Indeed, for all  $i \in \{1, \dots, p\}$  and for an appropriate initialization of the operators, it holds that  $P_{r_i}[\zeta] + S_{r_i}[\zeta] = \zeta$ , where  $\delta_i := S_{r_i}[\zeta]$  has a dynamic behavior modeled as [12, Ch. 2]:

$$\dot{\delta}_i \in \begin{cases} \overline{\text{co}}\{\dot{\zeta}, \max\{\dot{\zeta}, 0\}\} & \delta_i = -r_i, \\ \dot{\zeta} & \delta_i \in (-r_i, r_i), \\ \overline{\text{co}}\{\dot{\zeta}, \min\{\dot{\zeta}, 0\}\} & \delta_i = r_i, \end{cases} \quad (4)$$

$$\delta_i \in \Delta_i := [-r_i, r_i],$$

where  $\overline{\text{co}}\{\cdot\}$  denotes the closed convex hull operation. System (4) can be rewritten in compact form as the constrained differential inclusion  $\dot{\delta}_i \in F_{r_i}(\delta_i, \dot{\zeta})$ ,  $\delta_i \in \Delta_i$ , where the set-valued map  $F_{r_i}(\delta_i, \dot{\zeta})$  is outer semicontinuous, locally bounded relative to  $\Delta_i \times \mathbb{R}$ , and for each  $(\delta_i, \dot{\zeta}) \in \Delta_i \times \mathbb{R}$  it is nonempty and convex. These properties are particularly meaningful because, with the selection of an appropriate control strategy, it is possible to obtain a closed-loop system whose data satisfy the so-called hybrid basic assumptions [13, As. 6.5]. Under these assumptions, global asymptotic stability of a compact set implies robust global  $\mathcal{KL}$  asymptotic stability in the presence of fairly general perturbations of the dynamics [13, Def. 7.18]. From (4),  $\Gamma[\zeta]$  in (3) can be defined through the dynamical system

$$\dot{\delta} \in F_\Gamma(\delta, \dot{\zeta}) := \begin{bmatrix} F_{r_1}(\delta_1, \dot{\zeta}) \\ \vdots \\ F_{r_p}(\delta_p, \dot{\zeta}) \end{bmatrix}, \quad \delta \in \Delta := \prod_{i=1}^p \Delta_i, \quad (5)$$

having state  $\delta := (\delta_1, \dots, \delta_p)$  and output map

$$\Gamma[\zeta] := \sum_{i=0}^p \mu_i \zeta - \sum_{i=1}^p \mu_i \delta_i = \gamma \zeta - \mu^\top \delta, \quad \gamma := \sum_{i=0}^p \mu_i, \quad (6)$$

where  $\mu := [\mu_1 \dots \mu_p]^\top$  is a constant vector of positive parameters. Note that  $\gamma > 0$  in (6) by Assumption 3.

The state-space representation of system (1) is given by the following well-posed constrained differential inclusion:

$$\begin{aligned} \dot{\xi} &= A\xi + b(\gamma\zeta - \mu^\top \delta) \\ \dot{\delta} &\in F_\Gamma(\delta, u) \\ \dot{\zeta} &= u \end{aligned} \quad \begin{bmatrix} \xi \\ \delta \\ \zeta \end{bmatrix} \in \mathbb{R}^n \times \Delta \times \mathbb{R}. \quad (7)$$

### D. Problem Statement

For systems expressed in the form (7), we consider the problem of output-feedback setpoint regulation of constant references for the output  $y := c^\top \xi$ . More specifically, our objective is to design an output feedback control law for  $u$ , based on the available signals  $y_a := (c^\top \xi, \zeta)$  and under Assumptions 1, 2, and 3, such that:

$$\lim_{t \rightarrow \infty} y(t) = y^*, \quad (8)$$

for any constant reference  $y^* \in \mathbb{R}$ . We intend to achieve this objective through robust asymptotic stabilization of a compact set depending on  $y^*$ , so that suitable stability properties will be ensured, in addition to the convergence in (8). Among other things, stability will imply uniformity of the convergence (8). To this aim, we inspect the effect of  $\delta$  on the equilibria of (7) ensuring  $y = y^*$ . By Assumptions 1 and 2, the system of equations

$$A\xi + bv = 0, \quad c^\top \xi - y^* = 0, \quad (9)$$

admits a unique equilibrium pair  $(\xi^*, v^*)$ . To evaluate the steady-state value for  $\zeta$ , we consider then equation

$$\gamma\zeta - \mu^\top \delta = v^*, \quad (10)$$

which can be solved because  $\gamma > 0$  by Assumption 3, but whose solution is not unique due to the presence of the hysteresis state  $\delta$ . More precisely, all equilibria of (7) satisfying (10) correspond to elements of the compact set

$$\mathcal{E}_\delta := \{(\delta, \zeta) \in \Delta \times \mathbb{R} : \gamma\zeta = \mu^\top \delta + v^*\}. \quad (11)$$

Note that  $\mathcal{E}_\delta$  is a set of equilibria because, by Assumption 3 and  $\dot{\delta}_i \in \overline{\text{co}}\{0, \dot{\zeta}\}$ , the definitions of  $\gamma$  and  $\mu$  in (6) (with  $\mu_0 > 0$ ) imply that  $(\delta, \zeta) \in \mathcal{E}_\delta$  (satisfying  $\gamma\dot{\zeta} = \mu^\top \dot{\delta}$ ) holds only if  $\dot{\delta} = 0$  and  $\dot{\zeta} = 0$ .

Therefore, we can reformulate goal (8) by ensuring appropriate attractivity properties of the following compact regulation set:

$$\begin{aligned} \mathcal{E} := & \{(\xi, \delta, \zeta) \in \mathbb{R}^n \times \Delta \times \mathbb{R} : \\ & A\xi + b(\zeta - \mu^\top \delta) = 0, c^\top \xi = y^*\} = \{\xi^*\} \times \mathcal{E}_\delta, \end{aligned} \quad (12)$$

for which we will also achieve a suitable stability property.

We are now ready to provide a precise statement for the considered control problem.

**Problem 1.** Under Assumptions 1, 2, and 3, design a controller for the input  $u$  such that the closed-loop system admits a compact attractor that is robustly globally  $\mathcal{KL}$  asymptotically stable in the sense of [13, Def. 7.18] and whose projection in the plant state directions coincides with the regulation set (12).

### III. SETPOINT REGULATION FOR SYSTEMS WITH HYSTERETIC INPUT

This section considers a simplified scenario wherein  $\zeta$  of (7) can be assigned algebraically as a differentiable control input (so that  $\dot{\zeta}$  is well defined). In other words, we address the setpoint regulation objective  $y \rightarrow y^*$  in (8) for system

$$\begin{aligned} \dot{\xi} &= A\xi + b(\gamma\zeta - \mu^\top \delta) \\ \dot{\delta} &\in F_\Gamma(\delta, \dot{\zeta}) \\ y &= c^\top \xi \end{aligned} \quad \begin{bmatrix} \xi \\ \delta \end{bmatrix} \in \mathbb{R}^n \times \Delta, \quad (13)$$

with control input  $\zeta \in \mathbb{R}$ . Given the equilibrium pair  $(\xi^*, v^*)$  of (9), define  $\xi := \xi - \xi^*$ ,  $e := y - y^*$ . From  $A\xi^* + bv^* = 0$  due to (9), we compute the error dynamics for the  $\xi$ -subsystem as

$$\dot{\xi} = A\tilde{\xi} + b(\gamma\zeta - \mu^\top \delta - v^*), \quad e = c^\top \tilde{\xi}. \quad (14)$$

Due to the relative degree 1 assumption, under a suitable change of coordinates [15, Rem. 4.3.1], [16, §1.5], system (14) can be rewritten as

$$\begin{aligned} \dot{z} &= A_z z + b_z e \\ \dot{e} &= c_z^\top z + \alpha e + \beta \left( \zeta - (\mu^\top \delta + v^*)/\gamma \right), \end{aligned} \quad (15)$$

where  $z \in \mathbb{R}^{n-1}$  is the state of the internal dynamics,  $A_z$ ,  $b_z$ ,  $c_z$ , and  $\alpha$  are matrices of suitable dimensions, while  $\beta := \gamma c_z^\top b > 0$  is the high-frequency gain. Due to Assumption 2,  $A_z$  is Hurwitz, thus there exists  $P_z = P_z^\top > 0$  such that:

$$P_z A_z + A_z^\top P_z = -I_{n-1}. \quad (16)$$

#### A. Proportional Control Law

Consider the proportional controller

$$\zeta = -ke, \quad (17)$$

where  $k$  is a positive gain. The resulting closed-loop system, obtained from the interconnection between (13) and (17), is the following constrained differential inclusion

$$\begin{aligned} \dot{z} &= A_z z + b_z e \\ \dot{e} &= c_z^\top z - (\beta k - \alpha)e - \beta(\mu^\top \delta + v^*)/\gamma \\ \dot{\delta} &\in F_\Gamma(\delta, -k(c_z^\top z - (\beta k - \alpha)e - \beta(\mu^\top \delta + v^*)/\gamma)), \end{aligned} \quad (18)$$

with  $(z, e, \delta) \in \mathbb{R}^n \times \Delta$ . Since  $\delta$  belongs to the compact set  $\Delta$ , the  $(z, e)$ -subsystem is a linear system with bounded input disturbance  $\mu^\top \delta + v^*$ . Due to its structure, it is possible to choose  $k$  sufficiently large to ensure that its solutions are bounded. To show this property, consider the Lyapunov function  $V_k(z, e) := z^\top P_z z + e^2$ , with  $P_z = P_z^\top > 0$  selected as in (16). Choose the proportional gain

$$k > k^* := \frac{1}{\beta}(\alpha + |P_z b_z + c_z|^2). \quad (19)$$

Then, along the solutions of (18), we obtain

$$\begin{aligned} \dot{V}_k &= -|z|^2 + 2z^\top (P_z b_z + c_z) e - 2(\beta k - \alpha)e^2 \\ &\quad - 2\beta e(\mu^\top \delta + v^*)/\gamma \\ &\leq -\frac{1}{2}|z|^2 - 2\beta|e|((k - k^*)|e| - |\mu^\top \delta + v^*|/\gamma), \end{aligned}$$

which implies, from the boundedness of  $\delta \in \Delta$  and  $v^*$ :

$$\begin{aligned} |e| > e_M := \frac{\max_{\delta \in \Delta} \{|\mu^\top \delta + v^*|\}}{\gamma(k - k^*)} &\implies \dot{V}_k < 0, \\ |z| > \frac{2 \max_{\delta \in \Delta} \{|\mu^\top \delta + v^*|\}}{\gamma \sqrt{(k - k^*)/\beta}} &\implies \dot{V}_k < 0, \end{aligned} \quad (20)$$

with the second inequality obtained by splitting the analysis in  $|e| \geq e_M$  and  $|e| \leq e_M$ . From (20),  $(z, e)$  eventually converges to compact sublevel sets of  $V_k$ , thus the solutions of (18) are bounded. Moreover,  $(z, e)$  approaches an arbitrarily small neighborhood of  $(0, 0)$  (i.e.,  $\xi$  approaches an arbitrarily small neighborhood of  $\xi^*$ ) for  $k > 0$  sufficiently large.

### B. Proportional-Integral Control Law

We have shown that controller (17) ensures global boundedness of solutions but cannot achieve  $(z, e) \rightarrow 0$ . Thus, in place of (17), consider a controller with an integral action:

$$\dot{\sigma} = -he, \quad \zeta = \sigma - ke, \quad (21)$$

where  $\sigma \in \mathbb{R}$  is the integrator state and  $k, h$  are the proportional and integral gains. Define  $\tilde{\sigma} := \sigma - (\mu^\top \delta + v^*)/\gamma$ . Using (15), the interconnection among (13) and (21) yields:

$$\begin{aligned} \dot{z} &= A_z z + b_z e \\ \dot{e} &= c_z^\top z - (\beta k - \alpha)e + \beta \tilde{\sigma} \\ \dot{\tilde{\sigma}} &= -he - \frac{\mu^\top}{\gamma} F_\Gamma(\delta, -he - k(c_z^\top z - (\beta k - \alpha)e + \beta \tilde{\sigma})) \\ \dot{\delta} &\in F_\Gamma(\delta, -he - k(c_z^\top z - (\beta k - \alpha)e + \beta \tilde{\sigma})), \end{aligned} \quad (22)$$

with  $(z, e, \tilde{\sigma}, \delta) \in \mathbb{R}^{n+1} \times \Delta$ . We now expand the dynamics of  $\tilde{\sigma}$  in terms of the components  $\delta_i$  that lie in the linear region. Namely, inspired by (4), introduce

$$q_i(\delta_i, \dot{\zeta}) := \begin{cases} 0, & \text{if } |\delta_i| = r_i \text{ and } \delta_i \dot{\zeta} \geq 0, \\ 1, & \text{otherwise,} \end{cases} \quad (23)$$

so that we can write  $\dot{\delta}_i = q_i(\delta_i, \dot{\zeta}) \dot{\zeta}$ , then define

$$q(\delta, \dot{\zeta}) := \frac{1}{\gamma} \sum_{i=1}^p \mu_i q_i(\delta_i, \dot{\zeta}). \quad (24)$$

Note that, by Assumption 3 and from (6),

$$0 \leq q \leq q_{\max} := \frac{1}{\gamma} \sum_{i=1}^p \mu_i < 1. \quad (25)$$

Using (22) and (24), we obtain

$$\begin{aligned} \dot{\tilde{\sigma}} &= -he - \mu^\top \dot{\delta}/\gamma = -he - q \dot{\zeta} \\ &= -he - q(-he - k(c_z^\top z - (\beta k - \alpha)e + \beta \tilde{\sigma})) \\ &= -(h(1-q) + kq(\beta k - \alpha))e + k\beta q \tilde{\sigma} + q k c_z^\top z. \end{aligned} \quad (26)$$

Thus, the  $(z, e, \tilde{\sigma})$ -subsystem in (22) can be written as

$$\begin{bmatrix} \dot{z} \\ \dot{e} \\ \dot{\tilde{\sigma}} \end{bmatrix} = \underbrace{\begin{bmatrix} A_z & b_z & 0 \\ c_z^\top & -(\beta k - \alpha) & \beta \\ q k c_z^\top & \left( -h(1-q) + kq(\beta k - \alpha) \right) & k\beta q \end{bmatrix}}_{:= A_s(q)} \begin{bmatrix} z \\ e \\ \tilde{\sigma} \end{bmatrix}, \quad (27)$$

with the time-varying input  $q \in [0, q_{\max}] \subset [0, 1]$  due to (25). For system (22), we provide the following relevant result.

**Theorem 1.** Let  $k = \nu \bar{k}$  and  $h = \nu^2 \bar{h}$ , with gains  $\nu > 0$ ,  $\bar{h} > 0$ , and  $\bar{k}$  such that

$$\bar{k} \geq \frac{\alpha + \sqrt{\beta \bar{h}(2 - q_{\max})}}{\beta(1 - q_{\max})}. \quad (28)$$

Then, there exists  $\nu^* > 0$  such that, for all  $\nu > \nu^*$ , the compact attractor  $\mathcal{A}_\sigma := \{(z, e, \tilde{\sigma}, \delta) \in \mathbb{R}^{n+1} \times \Delta : (z, e, \tilde{\sigma}) = 0\}$  is globally exponentially stable for (22).

*Proof:* Define  $\bar{\sigma} := \tilde{\sigma}/\nu$  and  $\chi := (e, \bar{\sigma}) \in \mathbb{R}^2$ . Then, using (27), system (22) can be rewritten as

$$\begin{aligned} \dot{z} &= A_z z + [b_z \ 0] \chi \\ \dot{\chi} &= \nu A(q, \nu^{-1}) \chi + B(q) z, \quad q \in [0, q_{\max}] \\ \dot{\delta} &\in F_\Gamma(\delta, -he - k(c_z^\top z - (\beta k - \alpha)e + \beta \nu \bar{\sigma})), \end{aligned} \quad (29)$$

with  $(z, \chi, \delta) \in \mathbb{R}^{n+1} \times \Delta$ ,  $B(q) := [c_z \ \bar{k} q c_z]^\top$  and

$$A(q, \nu^{-1}) := \begin{bmatrix} -(\beta \bar{k} - \alpha \nu^{-1}) & \beta \\ -\bar{h}(1-q) - \bar{k} q (\beta \bar{k} - \alpha \nu^{-1}) & \bar{k} q \beta \end{bmatrix}. \quad (30)$$

Consider the auxiliary switching system:

$$\dot{\psi} = A(q, \nu^{-1}) \psi, \quad q(t) \in \mathcal{Q}, \quad (31)$$

where  $\mathcal{Q} := \{q \in \mathbb{R} : q = \sum_{i \in \mathcal{I}} \mu_i, \mathcal{I} \subset \{1, \dots, p\}\}$ . Below, we show that the origin of system (31) is GES for all  $\nu \geq 1$  and for any switching sequence  $t \mapsto q(t)$ . Notice that the characteristic polynomial of  $A(q, \nu^{-1})$  is  $\lambda^2 + \lambda(\beta \bar{k}(1-q) - \alpha \nu^{-1}) + \beta \bar{h}(1-q)$ , therefore, by (28),  $A(q, \nu^{-1})$  is Hurwitz for all  $(q, \nu) \in [0, q_{\max}] \times [1, \infty)$  because  $q_{\max} < 1$  and

$$\bar{k} > \frac{\alpha}{\beta(1 - q_{\max})} \geq \frac{\alpha \nu^{-1}}{\beta(1 - q)}, \quad \bar{h} > 0. \quad (32)$$

By [7] and [17], (31) admits a Common Quadratic Lyapunov Function (CQLF) if there exists  $P_\chi = P_\chi^\top > 0$  such that:

$$\begin{aligned} P_\chi A(0, \nu^{-1}) + A(0, \nu^{-1})^\top P_\chi &\leq -I_2 \\ P_\chi A(q_{\max}, \nu^{-1}) + A(q_{\max}, \nu^{-1})^\top P_\chi &\leq -I_2. \end{aligned} \quad (33)$$

Since  $\text{rank}(A(0, \nu^{-1}) - A(q_{\max}, \nu^{-1})) = 1$ , from [18], we have that matrix  $P_\chi$  exists if and only if the matrix pencil  $\Pi(g) := \beta \bar{h} A(0, \nu^{-1})^{-1} + g A(q_{\max}, \nu^{-1})$  is invertible, for all  $g \geq 0$ . Straightforward computations show that

$$\begin{aligned} \det(\Pi(g)) &= \beta \bar{h}(1 - q_{\max})g^2 + \beta \bar{h} \\ &+ ((\beta \bar{k} - \alpha \nu^{-1})(\beta \bar{k}(1 - q_{\max}) - \alpha \nu^{-1}) - \beta \bar{h}(2 - q_{\max}))g. \end{aligned}$$

As  $\det(\Pi(0)) > 0$ , it is sufficient to verify that  $(\beta \bar{k} - \alpha \nu^{-1})(\beta \bar{k}(1 - q_{\max}) - \alpha \nu^{-1}) - \beta \bar{h}(2 - q_{\max}) > 0$ , which is ensured for any  $\nu \geq 1$  by choosing  $\bar{h} > 0$  and  $\bar{k}$  according to (28). Returning to system (29), define

$$V_\sigma(z, \chi) := z^\top P_z z + \chi^\top P_\chi \chi, \quad (34)$$

which is positive definite and radially unbounded with respect to  $\mathcal{A}_\sigma$ . Along the solutions of (29), it holds that

$$\begin{aligned} \dot{V}_\sigma &\leq -|z|^2 - \nu|\chi|^2 + 2z^\top (P_z b_z [1 \ 0] + B(q)^\top P_\chi) \chi \\ &\leq -\frac{1}{2}|z|^2 - (\nu - 4|P_z b_z|^2 - 4|P_\chi B(q)|^2)|\chi|^2. \end{aligned}$$

Therefore, selecting  $\nu$  according to

$$\nu > \nu^* := 4|P_z b_z|^2 + 4|P_\chi|^2 |c_z|^2 (1 + \bar{k}^2 q_{\max}^2) \quad (35)$$

ensures that  $V_\sigma$  is a CQLF for  $\mathcal{A}_\sigma$ , which implies GES.  $\square$  From (28), (35), there always exist  $k > 0$ ,  $h > 0$  sufficiently large such that attractor  $\mathcal{A}_\sigma$  of Theorem 1 is GES. The next corollary is a direct consequence of the proof of Theorem 1.

**Corollary 1.** Choose gains  $k$  and  $h$  so that Theorem 1 establishes GES of  $\mathcal{A}_\sigma$ . Then, there exists a CQLF for (22). Namely, there exists  $P_s = P_s^\top > 0$  such that  $P_s A_s(q) + A_s(q)^\top P_s \leq -I_{n+1}$ , for all  $q \in [0, q_{\max}] \subset [0, 1]$ , with  $A_s(q)$  defined in (27).

#### IV. SETPOINT REGULATION FOR CASCADE SYSTEMS WITH HYSTERESIS INTERCONNECTION

We return to the problem of setpoint regulation for system (1), i.e., we address the problem of designing an input  $u$  such that  $y \rightarrow y^*$ . The key idea proposed here is to first generate a reference  $\zeta^*$  that solves the regulation problem for the reduced plant (13), then impose  $\zeta \rightarrow \zeta^*$  by a suitable selection of  $u$  for the complete plant (7). To achieve this objective, we require  $\dot{\zeta}^*$  to be well defined and available for control, which implies that (21) cannot be employed directly as  $\dot{e}$  is unknown. Thus, we assign  $\zeta^*$  through a modified version of (21) comprising a filter of the tracking error:

$$\dot{\sigma} = -h\eta, \quad \dot{\eta} = -\ell(\eta - e), \quad \zeta^* = \sigma - k\eta, \quad (36)$$

where  $\sigma \in \mathbb{R}$  is the integrator state,  $\eta \in \mathbb{R}$  is the filter state, while  $\ell$ ,  $h$ , and  $k$  are positive scalar gains. For convenience in the analysis, we define the error variables

$$\tilde{\sigma} := \sigma - (\mu^\top \delta + v^*)/\gamma, \quad \tilde{\eta} := \eta - e. \quad (37)$$

Then, using (15), (24), and  $\zeta = \sigma - k\eta + \zeta - \zeta^*$ , we can write the interconnection between plant (7) and controller (36) as

$$\begin{aligned} \dot{z} &= A_z z + b_z e \\ \dot{e} &= -(\beta k - \alpha)e + \beta\tilde{\sigma} + c_z^\top z - \beta k\tilde{\eta} + \beta(\zeta - \zeta^*) \\ \dot{\tilde{\sigma}} &= -h\eta - q\dot{\zeta} \\ \dot{\tilde{\eta}} &= -(\ell\tilde{\eta} - (\beta k - \alpha)e + \beta\tilde{\sigma} + c_z^\top z - \beta k\tilde{\eta} + \beta(\zeta - \zeta^*)) \\ \dot{\zeta} &= u \\ \dot{\delta} &\in F_\Gamma(\delta, \dot{\zeta}), \end{aligned} \quad (38)$$

with  $(z, e, \tilde{\sigma}, \tilde{\eta}, \zeta, \delta) \in \mathbb{R}^{n+3} \times \Delta$ .

##### A. Stability Analysis of the Reduced System

We study system (38) under the assumption that

$$\zeta = \zeta^* = \sigma - k\eta \quad (39)$$

is satisfied at all times. This reduction argument is instrumental to introducing the controller of Section IV-B. Define:

$$x_f := \ell\tilde{\eta} - (\beta k - \alpha)e + \beta\tilde{\sigma} + c_z^\top z. \quad (40)$$

With (36), (37) we have  $\dot{\zeta} = \dot{\zeta}^* = -h\eta + k\ell\tilde{\eta}$ , and then using (39), (40) we can follow similar computations to (26) exploiting  $\mu^\top \dot{\delta}/\gamma = q\dot{\zeta}$  to show that

$$\begin{aligned} \dot{\tilde{\sigma}} &= -(h(1-q) + kq(\beta k - \alpha))e + k\beta q\tilde{\sigma} + qkc_z^\top z \\ &- qkx_f - \ell^{-1}h(1-q)(x_f + (\beta k - \alpha)e - \beta\tilde{\sigma} - c_z^\top z). \end{aligned} \quad (41)$$

Define  $x_s := (z, e, \tilde{\sigma}) \in \mathbb{R}^{n+1}$ . Then, in the coordinates  $x := (x_s, x_f)$ , system (38) with condition (39) reads as

$$\begin{aligned} \dot{x}_s &= A_s(q)x_s + B_s(q)x_f + \ell^{-1}D_s(q)x \\ \dot{x}_f &= -\ell x_f + D_f(q, \ell^{-1})x \\ \dot{\delta} &\in F_\Gamma(\delta, \dot{\zeta}) \end{aligned} \quad (42)$$

where  $A_s(q)$  is found in (27),  $B_s(q) := [0^\top 0 \ -qk]^\top$ , while  $D_s(q)$  and  $D_f(q, \ell^{-1})$  are matrices of appropriate dimensions. In particular,  $D_f(q, \ell^{-1})$  is an affine function of  $\ell^{-1}$ , so that its entries are bounded as  $\ell \rightarrow \infty$ .

Using  $\ell$ , the analysis of (42) can be performed via timescale separation, where the  $x_f$ -subsystem (the fast subsystem) is made arbitrarily fast with respect to the  $x_s$ -subsystem (the slow subsystem) by selecting  $\ell > 0$  sufficiently large. These arguments lead to the following result.

**Proposition 1.** Choose gains  $k$  and  $h$  so that Theorem 1 establishes GES of  $\mathcal{A}_\sigma$ . Then, there exists  $\ell^* > 0$  such that, for all  $\ell > \ell^*$ , attractor  $\mathcal{A}_\eta := \{(x_s, x_f, \delta) \in \mathbb{R}^{n+2} \times \Delta : (x_s, x_f) = 0\}$  is GES for system (42).

*Proof:* Pick  $P_s$  from Corollary 1, then define  $d := 2|P_s|^2 k^2 q_{\max}^2 \geq 2|P_s B_s(q)|^2$  for all  $q \in [0, q_{\max}]$  and

$$V_\eta(x) := x_s^\top P_s x_s + d\ell^{-1} x_f^2, \quad (43)$$

which is positive definite and radially unbounded with respect to  $\mathcal{A}_\eta$ . Then, we obtain:

$$\begin{aligned} \dot{V}_\eta &\leq -|x_s|^2 + 2x_s^\top P_s B_s x_f - 2d x_f^2 \\ &\quad + 2\ell^{-1}(x_s^\top P_s D_s + d x_f D_f) x \\ &\leq -\min\{\frac{1}{2}, d\}|x|^2 + 2\ell^{-1}(|P_s D_s| + d|D_f|)|x|^2. \end{aligned} \quad (44)$$

Recalling that  $\lim_{\ell \rightarrow \infty} \ell^{-1}(|P_s D_s(q)| + d|D_f(q, \ell^{-1})|) = 0$ , for  $\ell > 0$  sufficiently large,  $\dot{V}_\eta$  can be made quadratically negative definite, ensuring that  $V_\eta$  is a CQLF for  $\mathcal{A}_\eta$ .  $\square$

##### B. Main Result

Differently from (39), we now address the general case of the augmented plant (38) by removing the assumption that  $\zeta = \zeta^*$ . Thus, we define the error  $\tilde{\zeta} := \zeta - \zeta^*$ , whose dynamics are given, by (38) with (36) and (37), as  $\dot{\tilde{\zeta}} = u - \dot{\zeta}^* = u + h\eta - k\ell(\eta - e)$ . Therefore, we can ensure  $\tilde{\zeta} \rightarrow 0$  by selecting  $u = \dot{\zeta}^* - k_\zeta \tilde{\zeta}$ , with gain  $k_\zeta$ , leading to:

$$\dot{\tilde{\zeta}} = -k_\zeta \tilde{\zeta}. \quad (45)$$

Using (36), this yields the following controller for plant (7):

$$\begin{aligned} \dot{\eta} &= -\ell(\eta - e) \\ \dot{\sigma} &= -h\eta \\ u &= -h\eta + k\ell(\eta - e) - k_\zeta(\zeta - \sigma + k\eta), \end{aligned} \quad (46)$$

with positive gains  $\ell$ ,  $h$ ,  $k$ , and  $k_\zeta$ . The following statement, which confirms that controller (46) provides a solution for Problem 1, is the main result of this work.

**Theorem 2.** Choose any gain  $k_\zeta > 0$  and positive gains  $k$ ,  $h$ ,  $\ell$  such that  $\mathcal{A}_\eta$  of Proposition 1 is GES. Then, attractor  $\mathcal{A} := \{(\xi, \delta, \zeta, \eta, \sigma) \in \mathbb{R}^n \times \Delta \times \mathbb{R}^3 : (\xi, \delta, \zeta) \in \mathcal{E}, \eta = 0, \sigma = \zeta\}$ , with  $\mathcal{E}$  being the regulation set of (12), is robustly globally  $\mathcal{KL}$  asymptotically stable for the interconnection between system (7) and controller (46).

*Proof:* The closed-loop system can be seen as the cascade interconnection of (45) and (42) perturbed by  $\tilde{\zeta}$ . Namely, the  $x$ -subsystem can be rewritten as

$$\dot{x} = A_x(q)x + B_x(q)\tilde{\zeta}. \quad (47)$$




Fig. 3. Closed-loop simulation results. (a): reference  $y^*$  and output  $y$ . (b): input  $u$ . (c): error  $e$  and filter state  $\eta$ . (d): reference  $\zeta^*$ , state  $\zeta$ , and integrator state  $\sigma$ . (e): equilibrium  $\xi^*$  and states  $\xi$ . (f): hysteresis states  $\delta$ .

Consider the Lyapunov function  $V := V_\eta + \rho\tilde{\zeta}^2$ , where  $V_\eta$  is defined in (43) and  $\rho > 0$ . By Proposition 1, there exists a constant matrix  $Q_x = Q_x^\top > 0$  such that

$$\dot{V} \leq -x^\top Q_x x + \tilde{\zeta} B_x(q)x - 2\rho k_\zeta \tilde{\zeta}^2. \quad (48)$$

Choosing  $\rho > 0$  sufficiently large, we conclude that  $\mathcal{A}$  is GES. Finally, we note that system (7), (46) can be regarded as a hybrid system, with empty jump set and jump map, satisfying the hybrid basic conditions. Thus, from [13, Thm. 7.21],  $\mathcal{A}$  is robustly globally  $\mathcal{KL}$  asymptotically stable.  $\square$

## V. NUMERICAL RESULTS

We perform a numerical analysis to illustrate our theoretical results. Following the structure depicted in (1) and Assumptions 1 and 2, we consider a  $\xi$ -subsystem having transfer function

$$G(s) = \frac{(s+3)(s+1)}{(s-5)(s^2+2s+4)}. \quad (49)$$

Matrices  $A, b, c$  are then obtained as the minimal realization of (49) in controllability canonical form. The Prandtl-Ishlinskii operator  $\Gamma[\zeta]$ , whose behavior is shown in Fig. 2, is implemented according to (5) using  $p = 5$  stop operators. The weights are given by  $\mu = [0.1 \ 0.325 \ 0.55 \ 0.775 \ 1]^\top$ ,  $\mu_0 = 1$ , while the radii values are  $r_i = \mu_i$ ,  $i \in \{1, \dots, 5\}$ . The feedback law is the one in (46) with tuning parameters selected as  $\nu = 20$ ,  $k = 20$ ,  $h = 200$ ,  $\ell = 75$ , and  $k_\zeta = 5$ . Simulations have all the system states initialized randomly, and setpoint  $y^* = 1$ . The results obtained for a single run are shown in Fig. 3.

## VI. CONCLUSION

We provided a robust control strategy for linear cascade systems with a hysteretic interconnection. Employing a well-posed constrained differential inclusion to represent the Prandtl-Ishlinskii operator, we formulated the regulation problem by defining a compact set of equilibria depending

on the hysteresis states. Then, relying on high-gain arguments and the properties of well-posed hybrid dynamical systems, we proved that the closed-loop system admits a robustly globally asymptotically stable compact attractor for a simple selection of the controller gains. This result was achieved without any parametric knowledge of the system or the hysteresis. Future works will focus on generalizing the cascade dynamics and the hysteresis model, and applying the results to thermal shape memory alloy technologies.

## REFERENCES

- [1] R. C. Smith, *Smart material systems: model development*. SIAM, 2005.
- [2] M. Al Janaideh, S. Rakheja, and C.-Y. Su, “A generalized Prandtl–Ishlinskii model for characterizing the hysteresis and saturation nonlinearities of smart actuators,” *Smart Materials and Structures*, vol. 18, no. 4, p. 045001, 2009.
- [3] K. Kuhnen, “Modeling, identification and compensation of complex hysteresis nonlinearities: A modified Prandtl–Ishlinskii approach,” *European journal of control*, vol. 9, no. 4, pp. 407–418, 2003.
- [4] A. H. El-Shaer, M. A. Janaideh, P. Krejčí, and M. Tomizuka, “Robust performance enhancement using disturbance observers for hysteresis compensation based on generalized Prandtl–Ishlinskii model,” *Journal of Dynamic Systems, Measurement, and Control*, vol. 135, no. 5, p. 051008, 2013.
- [5] S. Liu, C.-Y. Su, and Z. Li, “Robust adaptive inverse control of a class of nonlinear systems with Prandtl–Ishlinskii hysteresis model,” *IEEE Transactions on Automatic Control*, vol. 59, no. 8, pp. 2170–2175, 2014.
- [6] Y. K. Al-Nadawi, X. Tan, and H. K. Khalil, “Inversion-based hysteresis compensation using adaptive conditional servocompensator for nanopositioning systems,” *Journal of Dynamic Systems, Measurement, and Control*, vol. 143, no. 12, p. 121007, 2021.
- [7] A. Esbrook, X. Tan, and H. K. Khalil, “Inversion-free stabilization and regulation of systems with hysteresis via integral action,” *Automatica*, vol. 50, no. 4, pp. 1017–1025, 2014.
- [8] X. Chen, T. Hisayama, and C.-Y. Su, “Adaptive control for uncertain continuous-time systems using implicit inversion of Prandtl–Ishlinskii hysteresis representation,” *IEEE Transactions on Automatic Control*, vol. 55, no. 10, pp. 2357–2363, 2010.
- [9] Y. K. Al-Nadawi, X. Tan, and H. K. Khalil, “Inversion-free hysteresis compensation via adaptive conditional servomechanism with application to nanopositioning control,” *IEEE Transactions on Control Systems Technology*, vol. 29, no. 5, pp. 1922–1935, 2021.
- [10] S. M. Dutta and F. H. Ghorbel, “Differential hysteresis modeling of a shape memory alloy wire actuator,” *IEEE/ASME Transactions on Mechatronics*, vol. 10, no. 2, pp. 189–197, 2005.
- [11] R. Romano and E. A. Tannuri, “Modeling, control and experimental validation of a novel actuator based on shape memory alloys,” *Mechatronics*, vol. 19, no. 7, pp. 1169–1177, 2009.
- [12] M. Cocetti, “Nonlinear and hybrid feedbacks with continuous-time linear systems,” Ph.D. dissertation, University of Trento, 2019.
- [13] R. Goebel, R. G. Sanfelice, and A. R. Teel, *Hybrid Dynamical Systems: Modeling Stability, and Robustness*. Princeton University Press, Princeton, NJ, 2012.
- [14] M. Al Janaideh, R. Naldi, L. Marconi, and P. Krejčí, “A hybrid system for a class of hysteresis nonlinearity: modeling and compensation,” in *2012 IEEE 51st IEEE Conference on Decision and Control (CDC)*, 2012, pp. 5380–5385.
- [15] A. Isidori, *Nonlinear Control Systems*. Springer, London, 1995.
- [16] A. Isidori, L. Marconi, and A. Serrani, *Robust autonomous guidance: an internal model approach*. Springer Science & Business Media, 2003.
- [17] S. Boyd, L. El Ghaoui, E. Feron, and V. Balakrishnan, *Linear matrix inequalities in system and control theory*. SIAM, 1994.
- [18] R. N. Shorten, O. Mason, F. O’Cairbre, and P. Curran, “A unifying framework for the SISO circle criterion and other quadratic stability criteria,” *International Journal of Control*, vol. 77, no. 1, pp. 1–8, 2004.