

Two-player Boundedness Counter Games

Emmanuel Filiot, Edwin Hamel-de Le Court

▶ To cite this version:

Emmanuel Filiot, Edwin Hamel-de Le Court. Two-player Boundedness Counter Games. 2022. hal-03626782

HAL Id: hal-03626782 https://hal.science/hal-03626782

Preprint submitted on 31 Mar 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Two-player Boundedness Counter Games

² Emmanuel Filiot

- ³ Université libre de Bruxelles, Belgium
- 4 efiliot@ulb.ac.be

5 Edwin Hamel-de le Court

- 6 Université libre de Bruxelles, Belgium
- 7 edwin.hamel.de.le.court@ulb.be

Base Abstract -

We consider two-player zero-sum games with winning objectives beyond regular languages, expressed 9 as a parity condition in conjunction with a Boolean combination of boundedness conditions on 10 a finite set of counters which can be incremented, reset to 0, but not tested. A boundedness 11 condition requires that a given counter is bounded along the play. Such games are decidable, though 12 with non-optimal complexity, by an encoding into the logic WMSO with the unbounded and path 13 quantifiers, which is known to be decidable over infinite trees. Our objective is to give tight or tighter 14 complexity results for particular classes of counter games with boundedness conditions, and study 15 their strategy complexity. In particular, counter games with conjunction of boundedness conditions 16 are easily seen to be equivalent to Streett games, so, they are CONP-c. Moreover, finite-memory 17 strategies suffice for Eve and memoryless strategies suffice for Adam. For counter games with a 18 disjunction of boundedness conditions, we prove that they are in solvable in $NP \cap CONP$, and in 19 PTIME if the parity condition is fixed. In that case memoryless strategies suffice for Eve while 20 infinite memory strategies might be necessary for Adam. Finally, we consider an extension of those 21 games with a max operation. In that case, the complexity increases: for conjunctions of boundedness 22 conditions, counter games are EXPTIME-c. 23

²⁴ 2012 ACM Subject Classification Theory of computation \rightarrow Logic and verification; Theory of ²⁵ computation \rightarrow Automata over infinite objects

- 26 Keywords and phrases Controller synthesis, Game theory, Counter Games, Boundedness objectives
- 27 Digital Object Identifier 10.4230/LIPIcs...

28 1 Introduction

Games on graphs are a popular mathematical framework to reason on reactive synthesis 29 problems [1, 8]: the system to synthesize is seen as a protagonist which must enforce a given 30 specification (its winning objective) against any adversarial behaviour of its environment. In 31 this framework, executions of reactive systems are modelled as infinite sequences alternating 32 between actions of the systems and actions of its environment. In the ω -regular setting, 33 the set of correct executions of reactive systems is modelled as an automaton, for example, 34 a non-deterministic Büchi automaton, then determinized into a parity automaton. The 35 synthesis problem then boils down to solving a game played on the graph of the parity 36 automaton, where the goal of the protagonist (Eve) is to satisfy, in the long run, the parity 37 condition whatever her opponent (Adam) does. Motivated by the synthesis of more complex 38 systems, the literature is rich in extensions of this basic two-player zero-sum ω -regular setting: 39 multiple players, imperfect information, quantitative objectives, infinite graphs ... (see [1, 8]40 for some references). In this paper, we follow this line of work and consider an extension of 41 two-player games beyond ω -regularity: counter games with boundedness conditions. 42

⁴³ **Counter games** In this paper, a *two-player counter game with boundedness objectives*, ⁴⁴ only called counter game hereafter, is given by a finite arena, called counter arena, whose ⁴⁵ vertices are labelled by counter operations over a finite set of counters C. Those operations



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY Leibniz International Proceedings in Informatics

can: increment a counter, reset it, or skip it (i.e. leave its value unchanged). We consider 46 objectives given as Boolean combinations of counter boundedness conditions. For $c \in C$, the 47 condition $\mathbb{B}(c)$ is satisfied by all infinite paths $\pi = v_0 v_1 \dots$, called plays, such that for some 48 $N \in \mathbb{N}$, the value of c along π is bounded by N. Note that the bound N is not uniform, in 49 the sense that it depends on π , and as a consequence, the set of plays satisfying $\mathbb{B}(c)$ is not 50 ω -regular in general. In this paper, we consider particular classes of Boolean combinations of 51 boundedness conditions. Since they do not necessarily capture all ω -regular objectives, we 52 also, by default, equip counter games with a parity condition. 53

Given an objective W as a Boolean formula Φ over atoms $\mathbb{B}(c)$ for all $c \in C$, the goal of the protagonist, Eve, is to enforce plays which satisfy W and the parity condition, whatever the adversary, Adam, does. If she has a strategy to meet this objective, she is said to win the game. Counter games are zero-sum, meaning that the goal of Adam is to enforce the complementary objective. The goal of this paper is to study the complexity of deciding, given a counter game G, if Eve wins G.

Motivations On infinite words, classes of counter automata with boundedness conditions 60 have appeared in various papers, e.g. in [5, 14, 2, 7]. The most relevant models in the 61 context of counter games are the ω BS-automata of [5] and the max-automata of [7]. They 62 are equipped with the same counter operations as the counter games of this paper, plus 63 a max operation in the case of max-automata, and some boundedness conditions. As a 64 consequence, winning objectives in counter games can naturally be expressed with these 65 automata. However, while they are known to have decidable emptiness problem, not much is 66 known when they are used to define objectives in two-player games. A motivation for this 67 paper is to investigate this question, for games where the winning conditions is not given by 68 such an automaton but where counter operations are explicitly given in the arena. 69

In the same line of works, max-automata, which are deterministic, are known by [2] to 70 correspond to the logic WMSO+U, which extends weak MSO on infinite words with the 71 unbounded quantifier UX. A formula $UX.\phi(X)$ holds if there are arbitrarily large sets X 72 satisfying ϕ . An important result by Bojańczyk states that the extension of WMSO+U to 73 infinite binary trees and with a path quantifier which allows to quantify over infinite paths, 74 has decidable satisfiability problem [6]. Since strategies are definable, modulo a tree encoding, 75 in this latter logic, a direct consequence of this result is that two-player games with objectives 76 given by max-automata are decidable (see also Example 2 of [6]). As a consequence, counter 77 games with boundedness conditions are decidable, though with non-elementary complexity. 78 Another motivation for our work is to obtain tight complexity results for particular classes of 79 counter games with boundedness conditions, with the goal of providing conceptually simpler 80 decidability proofs and insights for these particular instances, instead of using the general 81 result of [6]. 82

Finally, counter games with boundedness objectives are closely related to synthesis 83 problems over infinite alphabets of data. In particular, the problem of synthesising Mealy 84 machines with *registers* satisfying specifications given as deterministic register automata 85 over $(\mathbb{N}, <, 0)$, has recently been studied in [18]. It is shown that this problem is decidable, 86 and, even though the decidability proof is not based on counter games, it is proved that 87 the synthesis problem reduces to a game with winning conditions given as a (deterministic) 88 max-automaton whose acceptance is a disjunction of a parity condition and a condition of 89 the form "counter c is unbounded". Here, we also study the complexity of counter games 90 with max operation, giving an alternative procedure to decide the former synthesis problem. 91



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY Leibniz International Proceedings in Informatics

Contributions Our contributions are summarized in Fig. 1. We consider objectives given 92 as a conjunction of a parity condition and a formula over atoms $\mathbb{B}(c)$ in the following classes: 93 conjunctions, disjunctions, disjunctions of conjunctions, and negation-free formulas. We also 94 consider the extension of counter games with a max operator which can assign a counter with 95 the maximal value of several counters. The table also mentions the strategy complexity. For 96 conditions in $\bigwedge \mathbb{B}$, counter games are easily proved to be interreducible in polynomial time 97 to Streett games, yielding CoNP-completeness [20]. More interestingly, we prove that when 98 the number of counters is fixed, then, they are interreducible to parity games in polynomial 99 time, using another reduction (Thm 6). 100

We then prove, in it is our main contribution, that for conditions in $\bigvee \mathbb{B}$, counter games 101 are solvable in $NP \cap CONP$ and in polynomial time when the index of the parity function 102 is fixed. To prove this result, we introduce the notion of *finitely switching strategies* which 103 are, to the best of our knowledge new, and we believe, interesting on their own. This notion 104 is specifically designed for disjunctions of prefix-independent objectives (which is the case 105 of counter boundedness conditions): in a finitely switching strategy, Eve announces which 106 objective from the disjunction she aims to satisfy, and she can change her mind along the 107 play, but only a finite number of times. Eventually, she is bound to satisfy one the objectives. 108 We give general conditions to decide whether Eve has a finitely switching strategy in a 109 two-player game with a disjunction of prefix-independent objectives, and prove that such 110 strategies are sufficient for Eve to win objectives in $\bigvee \mathbb{B}$ and more generally in $\bigvee \bigwedge \mathbb{B}$. 111

Related works Two-player games with boundedness conditions have been studied in the 112 literature, first as finitary parity and Streett games [11], then generalized to cost-parity and 113 cost-Streett games [19]. Finitary parity- and Streett-games are request-response games [12], 114 with the additional constraint that the delay (number of edges) between a request and its 115 response is bounded (by a bound which depends on the play). For cost-parity and cost-Streett, 116 instead of the number of edges, costs (including 0) label edges and the delay is defined as 117 the sum of the costs. Cost-parity and cost-Streett games can be encoded as counter games 118 with conditions in $\Lambda \mathbb{B}$, though with an exponential blowup. The difference between those 119 counter games and finitary- and cost-games can be seen in their complexity: counter games 120 with conditions in $A\mathbb{B}$ are CONP-c, finitary parity games are in PTIME, cost-parity in 121 NP \cap CoNP, and finitary Streett and cost-Streett are ExpTIME-c. 122

Delay games with objectives given by a max-automaton have been proved to be decidable in [24]. This result is orthogonal to ours: first, those games allow for some delay, here in the sense that Eve has some look-ahead on Adam's future actions. Second, the decision procedure is non-elementary and rely on an encoding into WMSO+UP on infinite trees, some argument we avoid here, but for less expressive boundedness objectives.

Finally, infinite-state games with boundedness conditions have been considered in [10], over pushdown arenas. Finitary games over these arenas are shown to be decidable, as well as (pushdown) counter games with conditions in $\bigwedge \mathbb{B}$, without complexity results. Interestingly, it is shown that those games are equivalent to games where the objective of Eve is to uniformly bound all counters, for a bound which only depends on her strategy, and not on the plays. For counter games in $\bigwedge \mathbb{B}$ over a *finite* arena, this result can easily be seen as a consequence that finite-memory strategies suffice for Eve.



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY Leibniz International Proceedings in Informatics

Winning objective	Complexity	Memory of	Memory of	Theorem
parity∧		Eve	Adam	
$\bigwedge \mathbb{B}$	CONP-C	Finite	none	Th 4
$\bigvee \mathbb{B}$	$\mathrm{NP}\cap\mathrm{CoNP}$	Parity Index	Infinite	Th 13
	PTIME for fixed index			
$\bigvee \bigwedge \mathbb{B}$	CONP-C	Finite	Infinite	Th 14
$\operatorname{Bool}^+(\mathbb{B})$	PSPACE, CoNP-н	Finite	Infinite	Th 15
$\bigwedge \mathbb{B} + max$	EXPTIME-C	Finite	Finite	Th 16
$\boxed{\operatorname{Bool}(\mathbb{B}) + max}$	Decidable	Infinite	Infinite	from $[4]$

Figure 1 Complexity of deciding whether Eve has a winning strategy in a counter game for various winning objectives, always taken in conjunction with a parity objective. Bool⁺(\mathbb{B}) means any negation-free Boolean combination of objectives of the form $\mathbb{B}(c)$. Hardness results hold for any parity function of fixed constant index. The notation +max indicates that counter games are also equipped with a max operation. Since counter games with boundedness objectives are determined, this yields the complexity of deciding whether Eve wins for the complementary objectives: for example, it is NP-c for objectives parity $\vee \bigvee \mathbb{U}$ and memoryless strategies are sufficient for Eve, and in PTIME for parity $\vee \bigwedge \mathbb{U}$ but infinite memory might be necessary for Eve.

¹³⁵ **2** Preliminaries

In this paper, for any set Σ , we denote by Σ^* (resp. Σ^{ω}) the finite (resp. infinite) sequences of elements of Σ .

Two-player arenas A two-player arena is a tuple $\mathcal{A} = (V, E, V_{\exists}, V_{\forall}, v_0)$, where V is finite 138 set, $E \subseteq V \times V$, and V_{\exists} and V_{\forall} are two subsets of V such that $\{V_{\exists}, V_{\forall}\}$ is a partition of 139 V, and v_0 is an initial vertex. In this paper, we assume that arenas are deadlock-free, *i.e.* 140 that for any $v \in V$, there exists $v' \in V$ such that $(v, v') \in E$. Given $v \in V$, we denote 141 $\mathcal{A}[v] = (V, E, V_{\forall}, V_{\forall}, v)$ the areas \mathcal{A} where v_0 has been substituted by v. A play ρ of \mathcal{A} is a 142 mapping from N to V such that $(\rho(i), \rho(i+1)) \in E$, for all integer $i \in \mathbb{N}$. The set of plays is 143 denoted by $Plays(\mathcal{A})$. Any play can also be seen as an element of V^{ω} , and we call a history 144 any finite prefix of a play, and denote by $\operatorname{Hist}(\mathcal{A})$ the set of histories of \mathcal{A} . 145

146 **Strategies and finite-memory** A strategy for Eve (resp. Adam) is a function σ from 147 Hist(\mathcal{A}) to V defined for all histories $h = h_0 \cdots h_n$ with $h_n \in V_{\exists}$ (resp. $h_n \in V_{\forall}$), and 148 such that $(h_n, \sigma(h)) \in E$. A play ρ is consistent with a strategy for Eve (resp. Adam) if, 149 for any integer n such that $\rho(n) \in V_{\exists}$ (resp. $\rho(n) \in V_{\forall}$), σ is defined on $\rho(0) \cdots \rho(n)$, and 150 $\rho(n+1) = \sigma(\rho(0) \cdots \rho(n))$. We let Plays(\mathcal{A}, σ) (or just Plays(σ) when \mathcal{A} is clear from the 151 context) the set of plays consistent with σ .

A strategy σ of Eve (resp. Adam) is said to be *finite-memory* if there exists a finite set M, an element $m_I \in M$, a mapping δ from $V \times M$ to V, and a mapping g from $V \times M$ to M such that the following is true. When $h = v_0 v_1 \cdots v_l$ is a prefix of a play consistent with σ such that $v_l \in V_{\exists}$ (resp. $v_l \in V_{\forall}$), and the sequence m_0, m_1, \dots, m_l is determined by $m_0 = m_I$ and $m_{i+1} = g(v_i, m_i)$, then $\sigma(w) = \delta(v_l, m_l)$. In that case, we say that (δ, g) is a *memory mapping pair* of σ , and that m_l is the memory state of g at move l. We also say that σ is of memory |M|, and *memoryless* if it is of memory 1. Note that a memoryless



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

159 strategy can just be identified with a mapping from V to V.

Two-player games A winning condition for \mathcal{A} is a subset $W \subseteq V^{\omega}$. A strategy σ of Eve or Adam is said to be winning for objective W if $Plays(\sigma) \subseteq W$. A two-player game is a pair $G = (\mathcal{A}, W)$ where \mathcal{A} is an arena and W is a winning condition. We say that a strategy (of Eve or Adam) is winning in G if it is winning for W. A game $G = (\mathcal{A}, W)$ is determined if either Eve wins G or Adam wins $(\mathcal{A}, V^{\omega} \setminus W)$.

In this paper, we consider the problem of deciding, given a game G with a finitely represented winning condition, whether Eve wins G. For a complexity class C and a class of games \mathcal{G} , we say that games in \mathcal{G} are in \mathcal{C} (resp. C-hard, C-complete) if the latter problem for games $G \in \mathcal{G}$ is in \mathcal{C} (resp. \mathcal{C} -hard, \mathcal{C} -complete).

We also consider the complexity of strategies sufficient or necessary for Eve and Adam to win a game. We say that finite-memory strategies are *sufficient* for Eve (resp. Adam) to win \mathcal{G} if for all $G \in \mathcal{G}$, whenever Eve (resp. Adam) wins G, she has (resp. he has) a finite-memory winning strategy in G. We say that finite-memory is necessary for Eve (resp. Adam) to win \mathcal{G} if memoryless strategies do not suffice for Eve (resp. Adam) to win \mathcal{G} . Finally, we say that infinite-memory is necessary for Eve (resp. Adam) to win \mathcal{G} if finite-memory strategies do not suffice for Eve (resp. Adam) to win \mathcal{G} .

Parity games Let \mathcal{A} be an arena with set of vertices V. Let $Q \subseteq \mathbb{N}$ be a finite set of 176 elements called *colours* and $\kappa: V \to Q$ a mapping from vertices to colours called *parity* 177 function or priority function. The size |Q| of Q is called the *index* of κ . The mapping κ 178 defines a winning condition denoted Parity(κ), called a *parity condition*, as follows: Parity(κ) 179 is the set of all infinite words $w = w_0 w_1 \dots \in V^{\omega}$ such that the greatest colour occurring an 180 infinitely often in $\kappa(w_0)\kappa(w_1)\cdots$ is even. A parity game is a game whose winning condition is 181 a parity condition. We refer to $\mathcal{A}' = (\mathcal{A}, Q, \kappa)$ as a coloured arena, and also denote Parity(κ) 182 as Parity(\mathcal{A}') to avoid an explicit mention of the colouring κ . Note that a coloured arena 183 $\mathcal{A}' = (\mathcal{A}, Q, \kappa)$ uniquely defines a parity game $G = (\mathcal{A}, \operatorname{Parity}(\mathcal{A}'))$. It is well-known that 184 parity games are in NP \cap CoNP [16], and even solvable in quasi-polynomial time [9]. 185

Counter operations Our goal is now to define counter games. First, we introduce counter 186 operations and their semantics. In the rest of the paper, we fix a countable set \mathcal{C} whose 187 elements are called *counters*. A *counter operation* is a mapping from a finite subset C of 188 \mathcal{C} to {i, r, skip}. We let Op(C) denote the set of counter operations over $C \subseteq \mathcal{C}$. A counter 189 valuation is a mapping ν from C to N. For any infinite word $w \in \mathsf{Op}(C)^{\omega}$, we define $\lambda(w)$ 190 as the infinite sequence of counter valuations $\nu_0, \nu_1, \nu_2, \ldots$ such that for any counter $c \in C$, 191 $\nu_0(c) = 0$ and for any non-negative integer $n, \nu_{n+1}(c) = \nu_n(c) + 1$ if $w_n(c) = i, \nu_{n+1}(c) = 0$ 192 if $w_n(c) = \mathsf{r}$ and $\nu_{n+1}(c) = \nu_n(c)$ if $w_n(c) = \mathsf{skip}$. We define $\lambda(w)$ for $w \in \mathsf{Op}(C)^*$. To ease 193 notations, we write $\lambda(w,c)_i$ instead of $\lambda(w)_i(c)$. We say that λ is the *evaluation* of w. 194

Counter games with boundedness objectives Let \mathcal{A}' be an arena with set of vertices V, $C \subseteq \mathcal{C}$ a finite set of counters, and $\zeta : V \to \mathsf{Op}(C)$ a mapping from vertices to counter operations, called *vertex labeling*. Let Q be a set of colours and $\kappa : V \to Q$ be a colouring of V. To avoid cumbersome notations, for any vertex $v \in V$ and counter $c \in C$, we let $\zeta_c(v)$ denote $(\zeta(v))(c)$. We refer to $\mathcal{A} = (\mathcal{A}', C, \zeta, Q, \kappa)$ as a *counter arena*, to \mathcal{A}' as its *underlying arena* and to (\mathcal{A}, Q, κ) as its underlying coloured arena. We let Parity $(\mathcal{A}) = \text{Parity}(\kappa)$.

We consider a particular type of winning objective for counter games, called boundedness conditions, always together with a parity condition. Let $c \in C$. We let $\mathbb{B}(c)$ be an atomic



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics



Figure 2 Counter arena $\mathcal{A} = (V, E, V_{\exists}, V_{\forall}, v)$ with $V = \{1, 2, 3, 4\}$, $V_{\exists} = \{1, 3\}$, $V_{\forall} = \{2, 4\}$, v = 1. There are two counters (c, d) whose updates are represented on the figure as pairs. We assume no parity condition and a counter condition $\mathbb{B}(c) \vee \mathbb{B}(d)$. From vertex 3, Eve has a memoryless winning strategy σ : always move to 4. However, she does not have a strategy from 1 to bound counter *c*, neither does she have a strategy from 1 to bound *d*. However, she has a memoryless strategy β winning for $\mathbb{B}(c) \vee \mathbb{B}(d)$: from 1, she moves to 2, and from 3 she moves to 4. If the play stays in $\{1, 2\}$, then *d* is bounded, and if the play eventually moves to 3, then *c* is bounded.

formula which intuitively requires that counter c is bounded along a play, by some constant. Formally, $\mathbb{B}(c)$ is interpreted in \mathcal{A} by the set of plays ρ of \mathcal{A} , denoted $Plays(\mathcal{A}, \mathbb{B}(c))$, such that the sequence $\lambda(\zeta(\rho), c)$ is bounded, *i.e.*

$$Plays\left(\mathcal{A}, \mathbb{B}(c)\right) = \{\rho \in Plays(\mathcal{A}) \mid \exists N \in \mathbb{N}, \forall n \in \mathbb{N}, \lambda(\zeta(\rho), c)_n \leq N\}$$

The set $Plays(\mathcal{A}, \mathbb{B}(c))$ is called a *boundedness condition*. We let $\mathbb{U}(c)$ as a shortcut for $\neg \mathbb{B}(c)$. A *counter condition* for \mathcal{A} is a Boolean formula ϕ over the set of propositions $\{\mathbb{B}(c) \mid c \in C\}$. Its interpretation $Plays(\mathcal{A}, \phi) \subseteq Plays(\mathcal{A})$ over \mathcal{A} is defined naturally.

Given a counter condition ϕ , the pair $G = (\mathcal{A}, \phi)$ is called a *counter game*. The game *induced* by $G = (\mathcal{A}, \phi)$ is the game $G_{\phi} = (\mathcal{A}', Plays(\mathcal{A}, \phi) \cap Parity(\mathcal{A}))$. Note that in a counter game, both the counter condition and the parity condition must be satisfied. The notion of strategies and winning strategies carry over to counter games by considering the games they induce. In particular, Eve wins G if she wins G_{ϕ} , i.e., she has a strategy winning for the objective $Plays(\mathcal{A}, \phi) \cap Parity(\mathcal{A})$.

In this paper, we consider several classes of counter conditions. The class of counter conditions of the form $\bigwedge_{c \in C} \mathbb{B}(c)$ for some finite set $C \subseteq C$ is denoted $\bigwedge \mathbb{B}$. Similarly, we denote by $\bigvee \mathbb{B}$, $\bigvee \bigwedge \mathbb{B}$ and $Bool^+(\mathbb{B})$ the classes of counter conditions which are respectively, disjunctions of atoms $\mathbb{B}(c)$, disjunction of conjunctions of atoms $\mathbb{B}(c)$ (DNF), any negation-free Boolean formula.

Example 1. First, Fig. 2 illustrates an example with a disjunction of boundedness objectives. 215 Our second example is given by an arena with two counters and a single state controlled 216 by Adam. At each step, Adam can either increment c_1 and leave c_2 unchanged (called 217 transitions t_1), or increment c_2 and leave c_1 unchanged (called transition t_2). Clearly, Eve 218 has a strategy to win the objective $\bigvee_{i=1,2} \mathbb{U}(c_i)$. Indeed, in any play, there exists i such that 219 t_i is taken infinitely many times, and therefore c_i is unbounded. Suppose now that Adam 220 wants to win objectives $\bigwedge_{i=1,2} \mathbb{U}(c_i)$. He can do so by playing longer and longer sequences of 221 transition t_1 in alternation with longer and longer sequences of transition t_2 , which requires 222 infinite memory. 223

▶ Lemma 2. Counter games (with Boolean combinations of boundedness objectives) are determined and decidable.

Proof. Given a counter arena \mathcal{A} and a counter c of \mathcal{A} , the set $Plays(\mathcal{A}, \mathbb{B}(c))$ is a Borel set.



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY Leibniz International Proceedings in Informatics

Indeed, it is equal to the countable union for all $N \ge 0$ of the sets

 $\operatorname{Plays}_{N}(\mathcal{A}, \mathbb{B}(c)) = \{ \rho \in \operatorname{Plays}(\mathcal{A}) \mid \forall n \in \mathbb{N}, \lambda(\zeta(\rho), c)_{n} \leq N \}$

which are ω -regular. Indeed, a Büchi automaton needs $|V| \times N \times |C|$ states to recognize Plays_N($\mathcal{A}, \mathbb{B}(c)$). Since ω -regular sets are Borel, so is Plays ($\mathcal{A}, \mathbb{B}(c)$), as well as any Boolean combination of the latter. By Martin's determinacy theorem [22], the result follows.

To prove decidability, it suffices to notice that winning strategies in counter games are 229 infinite trees such that all of their branches are accepted by a deterministic max-automaton as 230 defined in [2]: such automata have a finite set of counters which can be incremented, reset to 0, 231 and take the maximal value of several counters and put it in another one. Such automata are 232 closed under intersection and can recognize any regular language, so, we can encode the parity 233 condition as well as the counter operations. Deterministic max-automata corresponds exactly 234 to the logic WMSO+U over infinite words (weak MSO with the unbounding quantifier). 235 WMSO+U has been extended to WMSO+UP on infinite trees with an additional quantifier 236 over infinite paths (P). Therefore, winning strategies of two-player games with winning 237 conditions definable in WMSO+U over infinite words are definable in WMSO+UP (see 238 Example 2 of [4]). The result follows since WMSO+UP has decidable satisfiability problem, 239 again by [4]. 240

²⁴¹ **3** Counter games with conjunctions of boundedness conditions

In this section, we study games with counter conditions in the class $\bigwedge \mathbb{B}$. Such games 242 are easily shown to be decidable using known results. Indeed, we prove that they are 243 equivalent in polynomial time to Streett games, known to be CONP-complete [17]. Let 244 us define Streett games. Given an arena \mathcal{A} with set of vertices V, and a set of k pairs 245 $S = \{(E_i, F_i) \mid 1 \leq i \leq k, E_i, F_i \subseteq V\}$, we let $\mathsf{Streett}(S)$ be the set of words $w \in V^{\omega}$ such 246 that for all $i = 1, \ldots, k$, if w contains infinitely many occurrences of some $e \in E_i$, then it must 247 contain infinitely many occurrences of some $f \in F_i$. A Streett game is a pair $G = (\mathcal{A}, W)$ 248 where W is given as set of k Streett pairs S, i.e., $W = \mathsf{Streett}(S)$. We prove that $\bigwedge \mathbb{B}$ -counter 249 games are interreducible to Streett games in polynomial time. 250

Lemma 3. There is a bijection Ψ from counter games with condition in $\Lambda \mathbb{B}$ to Streett games such that Ψ is computable in PTIME, such that for all counter games G, Eve wins G iff she wins the Streett game $\Psi(G)$, and such that for all Streett game G', $\Psi^{-1}(G')$ has a trivial parity function (with color 0 only).

Proof. Let G be a counter game over an underlying areas \mathcal{A} and a set of counters C, with 255 winning condition of the form $\bigwedge_{c \in C'} \mathbb{B}(c)$ for some $C' \subseteq C$. To simplify our explanations, 256 we first assume that G does not contain any parity condition. To construct a Streett game 257 G', we keep the same area \mathcal{A} and construct, for all $c \in C'$, a Streett pair (E_c, F_c) which 258 is satisfied by all sequences of counter operations such that if c is incremented infinitely 259 often, then c is also reset infinitely often. So, E_c is the set of vertices where c is incremented, 260 while F_c are those where c is reset. Let σ be a winning strategy for Eve in G and suppose 261 it is not winning in G', then it means that there exists some play $\rho \in \text{Plays}(\mathcal{A}, \sigma)$ and a 262 counter $c \in C'$ which is incremented infinitely often but reset finitely often. So, its value is 263 not bounded along ρ , contradicting that σ is winning. 264

The converse uses the fact that finite-memory strategies suffice to win Streett games: let σ be a finite-memory strategy winning for Eve in G'. Suppose it is not winning in G. Then, there is some play $\rho \in \text{Plays}(\mathcal{A}, \sigma)$ and a counter $c \in C'$ whose value is unbounded along ρ .



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

Therefore, ρ increases c infinitely many times. Since σ is winning for G', ρ resets c infinitely 268 many times. So, it can be decomposed into infinitely many fragments ending with a reset of 260 $c: \rho = \rho_1 v_1 \rho_2 v_2 \dots$ such that each ρ_i does not contain a reset of c and v_i resets c. Since the 270 value of c is unbounded, the ρ_i contains an arbitrarily large number of increments of c: for 271 all $n \in \mathbb{N}$, there exists i such that ρ_i increments c at least n times. By taking n large enough, 272 there is necessarily some ρ_i which can be decomposed into $\pi_1 \pi_2 \pi_3$ such that π_2 increments c 273 at least once, and the strategy σ cycles on π_2 , i.e., has the same memory state and vertex 274 before and after π_2 . This can be seen using standard pumping arguments. Indeed, if k is 275 the number of memory states of σ , there are at most k|V| positions of ρ_i which are not on a 276 cycle. So, if the number of increments is bigger than k|V|, there is a cycle π_2 which contains 277 an increment. Therefore, $\rho_1 v_1 \dots \rho_{i-1} v_{i-1} \pi_1 \pi_2^{\omega} \in \text{Plays}(\mathcal{A}, \sigma)$, it increments infinitely many 278 times c, and resets c finitely many times, contradicting that σ is winning in G'. 279

If now G also has a parity condition with x colors, we add x Streett pairs to the latter game G', using a standard parity-to-Streett conversion: those Streett pairs enforce that if an odd color α is seen infinitely often, then some even color $\beta > \alpha$ is seen infinitely often.

Conversely, let us explain how to convert any Streett game into a $\bigwedge \mathbb{B}$ -counter game. As a matter of fact, the latter reduction is a bijection, so, it suffices to apply its inverse, which we explicit here. If there are k Streett pairs, then we introduce k counters $C = \{c_1, \ldots, c_k\}$. No parity condition is needed in the resulting counter game (formally, we introduce a trivial colouring which colors all vertices by 0). If (E_i, F_i) is a Streett pair, we assume wlog that $E_i \cap F_i = \emptyset$, and for any vertex v, we add the following operation on c_i to v: increments c_i if $v \in E_i$, reset it if $v \in F_i$, and skip otherwise. The counter condition is $\bigwedge_{i=1}^k \mathbb{B}(c_i)$.

As a corollary of the latter Lemma, by applying $\Psi^{-1} \circ \Psi$ to a counter game in $\bigwedge \mathbb{B}$, we get in polynomial time an equivalent counter game in $\bigwedge \mathbb{B}$ with a trivial parity condition. Streett games are known to be CONP-complete and in PTIME for a fixed number of Streett pairs [23], and finite-memory strategies suffice for Eve while memoryless strategies suffice for Adam. Therefore, Lemma 3 immediately yields the following result:

▶ Theorem 4. Counter games with winning conditions in $\bigwedge \mathbb{B}$ are CONP-complete, and in PTIME if both the index of the priority function and the number of counters are fixed constants. Finite memory suffice for Eve and memoryless strategies suffice for Adam. CONPhardness holds even if the index of the parity function is any fixed constant.

The latter theorem does not cover the case where only the number of counters is fixed. 299 We prove that in this case, the complexity is at most NP \cap coNP. The proof of Theorem 4 300 is based on Lemma 3 which explicits a bijection between counter games in $\bigwedge \mathbb{B}$ and Streett 301 games. In particular, it constructs a game whose winning condition is a conjunction of |C|302 Streett conditions and a parity condition (which is then itself converted as Streett pairs). 303 Each Streett pair can be seen as a parity condition over colors $\{0, 1, 2\}$. Therefore, when the 304 number of counters is fixed, the reduction of Lemma 3 yields a game with a winning condition 305 which is a conjunction of a fixed number ℓ of parity conditions over colors $\{0, 1, 2\}$ and a 306 single arbitrary parity condition. We prove that such games are reducible in polynomial time 307 to parity games for $\ell = 1$ in the following lemma, later on applied recursively to show the 308 result the result for any fixed ℓ (Theorem 6). 309

▶ Lemma 5. Games of the form $G = (\mathcal{A}, W)$ where $W = Parity(\kappa) \cap Parity(\kappa_3)$ for κ an arbitrary colouring of index k and κ_3 a colouring in $\{0, 1, 2\}$, reduce in polynomial time to parity games of index 2k + 1. Moreover, finite-memory strategies of memory size equal to k are sufficient for Eve to win G.



© Emmanuel Filiot and Edwin Hamel-de le Court;

licensed under Creative Commons License CC-BY Leibniz International Proceedings in Informatics

Proof. Let V be the set of vertices of \mathcal{A} , Q the set of colours of κ and m the minimal 314 even number greater than or equal to every element of Q. We construct in polynomial 315 time a parity game G' over a coloured arena $\mathcal{A}' = (V', E', V_{\exists}, V_{\forall}, Q', \kappa', v_0')$ such that Eve 316 wins G iff she wins G', and such that the index of κ' is equal to 2k + 1. To prove that 317 finite-memory strategies of memory size equal to k suffice to win G', we use the known 318 result that memoryless strategies suffice to win parity games, and prove that any memoryless 319 winning strategy in G' can be translated back to a finite-memory winning strategy in G with 320 memory size equal to k. 321

The construction of G' is as follows. We let $V' = V \times Q$ and $Q' = \{0, \ldots, 2m + 2\}$ with the following parity function κ' : any vertex $(u, q) \in V'$ is coloured by

$$\kappa'(u,q) = \begin{cases} \kappa(u) & \text{if } \kappa_3(u) = 0\\ m+1 & \text{if } \kappa_3(u) = 1\\ m+2 + \max\{\kappa(u),q\} & \text{if } \kappa_3(u) = 2 \end{cases}$$

Before defining the transitions, let us prove some property (called P) about the colouring κ' . Let $\pi = v_0 v_1 \cdots \in \text{Plays}(\mathcal{A})$. For all $i \geq 0$, we let q_i be the color by κ seen since the last vertex v_j , j < i, such that $\kappa_3(v_j) = 2$. Formally, j is the largest integer such that j < iand $\kappa_3(v_j) = 2$, and we let $q_i = \max\{\kappa(v_k) \mid j \leq k < i\}$. If j does not exist, then $q_i = 0$. Let $\pi' = (v_0, q_0)(v_1, q_1) \dots$ We prove that $\pi \in W$ iff $\pi' \in \text{Parity}(\kappa')$. Let x be the maximal priority occurring infinitely often in $\kappa_3(\pi)$ (κ_3 here, is extended morphically to sequences in V^{ω}). We consider three cases:

If x = 0, then $\kappa'(\pi') = \kappa(\pi)$, so, $\pi \in W$ iff $\pi \in \text{Parity}(\kappa)$ iff $\pi' \in \text{Parity}(\kappa')$.

If x = 1, then $\kappa'(\pi')$ sees m+1 (which is odd) infinitely often, and therefore $\pi' \notin \text{Parity}(\kappa')$ and $\pi \notin W$.

If x = 2, this is the most interesting case. In that case, π can be decomposed into fragments $\pi = f_1 f_2 f_3 \dots$ such that each f_i contains exactly one node v, at its end, such that $\kappa_3(v) = 2$. Let α_i be the maximal color of fragment f_i . Then, the maximal colour seen infinitely often in $\kappa'(\pi')$ is the same as in the sequence $(m + 2 + \alpha_1)(m + 2 + \alpha_2) \dots$, which is equal to $m + 2 + \alpha$, where α is the maximal color occurring infinitely often in $\kappa(\pi)$. As m is even, $\pi' \in \text{Parity}(\kappa')$ iff $\pi \in \text{Parity}(\kappa)$ iff $\pi \in W$.

The transitions of \mathcal{A}' are constructed so that any play $\pi \in \operatorname{Plays}(\mathcal{A})$ bijectively corresponds 338 to the play π' defined above. In particular, when a vertex (v,q) such that $\kappa_3(v) = 2$ is 339 visited and there is a transition (v, v') in \mathcal{A}, q is reset to 0 (we add a transition to (v', 0) in 340 \mathcal{A}' , and if $\kappa_3(v) \neq 2$, we add a transition to $(v', \max(\kappa(v), q))$. Such a construction ensures 341 that there is a bijection Ψ between $\operatorname{Plays}(\mathcal{A})$ and $\operatorname{Plays}(\mathcal{A}')$ such that, by property P above, 342 $\pi \in \operatorname{Parity}(\kappa) \cap \operatorname{Parity}(\kappa_3)$ iff $\Psi(\pi) \in \operatorname{Parity}(\kappa')$, so, correctness follows. Moreover, any 343 memoryless strategy in G' is translated into a finite-memory strategy in G with a memory 344 size equal to the index of κ , concluding the proof. 345

Note that Lemma 5 entails that games with a conjunction of a parity condition of index k and a fixed number N of parity conditions over colors $\{0, 1, 2\}$ are solvable in NP \cap CoNP. Indeed, by iterating Lemma 5 N times, the latter games reduce to parity games of index $2^{N}(k+1) - 1$. Games with Boolean combinations of parity objectives have been studied in [13]. However, the former complexity result is not covered by [13]. As explained before, Lemma 5 together with the bijection of Lemma 3 imply the following theorem:

Theorem 6. For any fixed positive integer N, counter games of parity index k with winning conditions in $\bigwedge \mathbb{B}$ and at most N counters, are in NP \cap CONP (and parity-hard). Finite memory strategies with memory size $2^{N-1}(k+1) - 1$ suffice for Eve and Adam.



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

Finitely switching strategies for games with disjunction of prefix-independent objectives

Let \mathcal{A} be an arena, let V be its set of vertices, and let \mathcal{W} be a finite set of prefix-independent¹ winning conditions for \mathcal{A} , i.e., $\mathcal{W} \subseteq 2^V$. We let $\bigvee \mathcal{W} = \bigcup \{W \mid W \in \mathcal{W}\}$. In this section, we consider a class of strategies for Eve, called *finitely switching*, whose existence entail that she wins $(\mathcal{A}, \bigvee \mathcal{W})$. We characterize the existence of finitely switching strategies via a least fixpoint and, for some particular classes of winning objectives $\bigvee \mathcal{W}$ of interest in this paper, prove that such strategies suffice for Eve to win $(\mathcal{A}, \bigvee \mathcal{W})$. The complexity of computing the fixpoint for those particular classes of objectives is deferred to Section 5.

Let us first give intuition on the notion of finitely switching strategies. In such a strategy, Eve announces an initial goal $W \in W$ she wants to satisfy, but she may switch her mind during the play, i.e., announce another goal $W' \in W$, depending on what Adam does. She can do this only a finite number of times and eventually keep the same goal forever and satisfy it. Formally, for $k \ge 0$, a k-switching strategy for Eve is a strategy σ such that there exists a mapping goal from finite histories of σ to W such that for all $\pi = v_1 v_2 \cdots \in \text{Plays}(\sigma)$, there exists $W_1, \ldots, W_{k+1} \in W$ such that $\pi \in W_{k+1}$ and

 $goal(v_0)goal(v_0v_1)goal(v_0v_1v_2)\cdots \in W_1^*W_2^*\ldots W_k^*W_{k+1}^{\omega}$

The goal W_{k+1} is called the *ultimate* goal of π . We say that σ is finitely switching if it is *k*-switching for some $k \ge 0$.

Example 7. Consider the example of Fig. 2. The described strategy β is 1-switching for $\mathcal{W} = \{\mathbb{B}(c), \mathbb{B}(d)\}$: initially, her goal is $\mathbb{B}(d)$. If Adam ever tries to make it so that counter dbecomes unbounded, by going to vertex 3 from vertex 2, Eve can now set her new goal to $\mathbb{B}(c)$.

Consider now the single-state area of Example 1 in which Eve wants to satisfy $\bigvee_{c=1,2} \mathbb{U}(c)$. 370 She has no finitely switching strategy: whenever she announces she wants to satisfy $\mathbb{U}(c_i)$ 371 for some i, Adam loops on transition t_{3-i} until Eve switches her mind. If her ultimate goal 372 is $\mathbb{U}(c_i)$ for some *i*, then Adam will loop forever on t_{3-i} and c_i will be bounded, so that 373 Eve does not meet the ultimate goal she announced. By seeing operations on c_1 and c_2 as 374 priority functions, this example also shows that finitely switching strategies are not sufficient 375 to win disjunctions of parity objectives in general. More precisely, for i = 1, 2, we can define 376 the priority functions p_i , here on transitions, which colors transition t_i by 0 and transition 377 t_{3-i} by 1. If she ultimately announces her goal is to satisfy priority p_i , then Adam takes 378 transition t_{3-i} forever and p_i sees infinitely many times color 1. 379

Since in a finitely switching strategy, any play consistent with that strategy must satisfy its ultimate goal, the following result is immediate:

Lemma 8 (Soundness). Any finitely switching strategy for Eve in \mathcal{A} is winning for $(\mathcal{A}, \bigvee \mathcal{W})$.

We will see later on that the converse holds for some particular classes of boundedness objectives, but for now, let us characterize the existence of finitely switching strategies via some least fixpoint. For a set $X \subseteq V$, we denote the objective of reaching X by Reach $(X) = V^*XV^{\omega}$. We let f be the function which associates any $X \subseteq V$ to the set of vertices u from which Eve can win the objective $W \cup \text{Reach}(X)$ for some $W \in \mathcal{W}$. Formally,

¹ A winning condition W is prefix-independent if, for all $(w, u) \in (V^{\omega}, V^{\star}), w \in W$ iff $uw \in W$.



[©] Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

LIPICS Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

 $f(X) = \{u \in V \mid \exists W \in \mathcal{W}, \text{ Eve wins } (\mathcal{A}[u], W \cup \mathsf{Reach}(X))\}.$ Note that $X \subseteq f(X)$ for all $X \subseteq V$. Indeed, if $u \in X$, then Eve has a trivial strategy from u to reach X, and so 380 $u \in f(X)$. Since $(2^V, \subseteq)$ is a complete lattice, by Knaster–Tarski theorem, f has a unique 390 least fixpoint denoted $S^{\mathcal{W}}$. To compute $S^{\mathcal{W}}$, it suffices to compute the following sequence of 391 sets until it stabilizes: 392

 $\blacksquare \mathsf{S}_0^{\mathcal{W}} = \emptyset,$ 393

for $i \ge 0$, $\mathsf{S}_{i+1}^{\mathcal{W}} = \{u \in V \mid \exists W \in \mathcal{W}, \text{ Eve wins } (\mathcal{A}[u], W \cup \mathsf{Reach}(\mathsf{S}_{i}^{\mathcal{W}}))\}.$ 394

For all $i \ge 1$ and $u \in \mathsf{S}_i^{\mathcal{W}}$ (if it exists), we denote by $\sigma_{u,i}$ a strategy for Eve winning in the 395 game $(\mathcal{A}[u], W \cup \mathsf{Reach}(\mathsf{S}_{i-1}^{\mathcal{W}}))$ for some $W \in \mathcal{W}$. It exists by definition of $\mathsf{S}_{i}^{\mathcal{W}}$. 396

We now prove the following characterization. 397

Lemma 9 (Fixpoint characterization of finitely switching strategies). Let \mathcal{A} be an arena with 398 set of vertices V and \mathcal{W} a finite set of prefix-independent winning conditions for \mathcal{A} . For all 399 $u \in V$, the following are equivalent: 400

- **1.** Eve has a finitely switching strategy from u 401
- **2.** Eve has a |V|-switching strategy from u 402

Proof. Clearly $2 \Rightarrow 1$. We first prove $1 \Rightarrow 3$ and then $3 \Rightarrow 2$. 404

Let σ be a k-switching strategy for some $k \geq 0$. By induction on k, we prove that 405 $u \in \mathsf{S}_{k+1}^{\mathcal{W}}$. This implies the claim as $\mathsf{S}_{k+1}^{\mathcal{W}} \subseteq \mathsf{S}^{\mathcal{W}}$. 406

If k = 0, then Eve never changes her mind and therefore all plays of (σ) are in goal(u)407 (the history with only the vertex u), so, $u \in S_1^{\mathcal{W}}$. Suppose that k > 0. We take $W = \operatorname{goal}(u)$. 408 Let $\pi \in \text{Plays}\sigma$. We prove that $\pi \in W \cup \text{Reach}(\mathsf{S}_k^{\mathcal{W}})$. If Eve never switches her mind during 409 π , then $\pi \in W$. Otherwise, let h the smallest prefix of π such that $goal(h) \neq W$. Let v be 410 the last vertex of h. Note that the strategy² $\sigma|_h$ is a (k-1)-switching strategy from v. By 411 IH, $v \in \mathsf{Reach}(\mathsf{S}_k^{\mathcal{W}})$, which means that $\pi \in \mathsf{Reach}(\mathsf{S}_k^{\mathcal{W}})$ and we are done. 412

We now prove $3 \Rightarrow 2$. Let $u \in S^{\mathcal{W}}$. Let *i* be smallest index such that $u \in S_i^{\mathcal{W}}$. Note that 413 $i \leq |V|$. We prove by induction on i that Eve has an (i-1)-switching strategy $\beta_{u,i}$ witnessed 414 by a goal function $\operatorname{goal}_{u,i}$. If $u \in S_1^{\mathcal{W}}$, then $\sigma_{u,1}$ wins $(\mathcal{A}[u], W)$ for some $W \in \mathcal{W}$ and so we 415 let $\operatorname{goal}_{u,1}(h) = W$ for any history h of $\sigma_{u,1}$. 416

Suppose that i > 1 and $u \in \mathsf{S}_i^{\mathcal{W}}$. Remind that the strategy $\sigma_{u,i}$ wins $(\mathcal{A}[u], W \cup$ 417 Reach($S_{i-1}^{\mathcal{W}}$)). We modify $\sigma_{u,i}$ into a strategy $\beta_{u,i}$ as follows: $\beta_{u,i}$ is the same as $\sigma_{u,i}$ as long as $S_{i-1}^{\mathcal{W}}$ has not been reached. If eventually $S_{i-1}^{\mathcal{W}}$ is reached, say at a vertex v, then $\beta_{u,i}$ plays 418 419 according to $\beta_{v,i-1}$ (which exists by IH). 420

We prove that $\beta_{u,i}$ is (i-1)-switching. We let $\operatorname{goal}_{u,i}(h) = W$ for any history h which 421 does not visit $S_{i-1}^{\mathcal{W}}$. For any history $h = h_1 v h_2$ such that $|h_1|$ is minimal and $v \in S_{i-1}^{\mathcal{W}}$, we 422 let $\operatorname{goal}_{u,i}(h) = \operatorname{goal}_{u,i-1}(vh_2)$. Let $\pi \in \operatorname{Plays}(\beta_{u,i})$. If $\pi = v_0 v_1 \dots$ never visits $\mathsf{S}_{i-1}^{\mathcal{W}}$, then 423 $goal(v_0)goal(v_0v_1)\dots \in W^{\omega}$, and $\pi \in W^{\omega}$. If there exists j minimal such that $v_j \in \mathsf{S}_{i-1}^{\mathcal{W}}$, 424 then, by HI, there exists $W_1, \ldots, W_i \in \mathcal{W}$ such that $\operatorname{goal}_{v_i, i-1}(v_j) \operatorname{goal}_{v_i, i-1}(v_j v_{j+1}) \cdots \in \mathcal{W}$ 425 $W_1^* \dots W_{i-1}^* W_i^{\omega}$. By definition of $\operatorname{goal}_{u,i}$, we obtain that $\operatorname{goal}_{u,i}(v_0) \operatorname{goal}_{u,i}(v_0 v_1) \dots \in \mathcal{V}_{i-1}$ 426 $W^*W_1^* \dots W_{i-1}^*W_i^{\omega}$. Finally, it remains to prove that $\pi \in W_i$: by IH, its suffix $v_i v_{i+1} \dots$ is 427 in W_i , and since W_i is prefix-independent, so is π , concluding the proof. 428

² The restriction $\sigma|_h$ is defined by $\sigma|_h(h') = \sigma(hh')$ for all h'.



© Emmanuel Filiot and Edwin Hamel-de le Court: licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

^{3.} $u \in S^{\mathcal{W}}$ 403

LIPICS Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

According to Lemma 9, when Eve has a finitely switching strategy, then she has a Algo |V|-switching strategy. Interestingly, observe that the number of times she possibly needs to Algo switch her mind does not depend on the number of winning objectives in W.

The proof of Lemma 9 constructs, for all $1 \le i \le |V|$ and $u \in S_i^W$, a finitely switching strategy $\beta_{u,i}$, which either mimics $\sigma_{u,i}$ or switch to a strategy $\beta_{v,i-1}$. So, Eve needs to remember the current vertex u and index i, in order to know whether she must play according to $\sigma_{u,i}$ or to switch to a strategy $\beta_{v,i-1}$. So, even if for some N, all the strategies $\sigma_{u,i}$ are finite-memory of size at most N, $\beta_{u,i}$ needs memory $O(N.|V|^2)$ in general. We now prove that Eve can do better.

Lemma 10 (Memory transfer). Let \mathcal{A} be a counter arena, V be its set of vertices, and \mathcal{W} a finite set of prefix-independent winning conditions for \mathcal{A} . Let $N \in \mathbb{N}$ and suppose that for all $X \subseteq V$, $u \in V$ and $W \in \mathcal{W}$, strategies of memory size at most N suffice for Eve to win $(\mathcal{A}[u], W \cup \text{Reach}(X))$. Then for all $u \in S^{\mathcal{W}}$, Eve wins $(\mathcal{A}[u], \bigvee \mathcal{W})$ with memory at most N.

Proof. For all $1 \le i \le |V|$ and $u \in \mathsf{S}_i^{\mathcal{W}}$, we assume the existence of a strategy $\sigma_{u,i}$ winning 442 in $(\mathcal{A}[u], W \cup \mathsf{Reach}(\mathsf{S}_i^{\mathcal{W}}))$ for some $W \in \mathcal{W}$, of memory states $\{1, \ldots, N\}$. Note that the $\sigma_{u,i}$ 443 share the same memory states. The main idea of the proof is to provide a way for Eve, given 444 a current vertex $v \in S^{\mathcal{W}}$ and a memory state m, to uniquely identify the (finite memory) 445 strategy $\sigma_{u,i}$ according to she must play in vertex v and state m. Given v, we take i to 446 be the smallest integer such that $v \in S_i^{\mathcal{W}} \setminus S_{i-1}^{\mathcal{W}}$. To identify u, we take the smallest vertex 447 u according to an arbitrary linear order on V such that $u \in S_i^W \setminus S_{i-1}^W$ and v is reachable 448 from u by a finite path p consistent with $\sigma_{u,i}$, such that if $\sigma_{u,i}$ is in its initial memory state 449 m_0 at u, then after p, it is in memory state m. Then, Eve moves to vertex g(v,m), for 450 (δ, g) the memory mapping of $\sigma_{u,i}$. Intuitively, if Eve stays forever in $\mathsf{S}_i^{\mathcal{W}} \setminus \mathsf{S}_{i-1}^{\mathcal{W}}$, she will by 451 monotonicity eventually always play according to the same strategy $\sigma_{u,i}$, and so satisfy some 452 W, as conditions in \mathcal{W} are prefix-independent. Otherwise, she will reach another $\mathsf{S}_{j}^{\mathcal{W}} \backslash \mathsf{S}_{j-1}^{\mathcal{W}}$ 453 for some j < i and we make the same reasoning inductively. See Appendix for details. 454

The converse of Lemma 8 does not hold in general, as illustrated in Example 1 for disjunction of unboundedness objectives. However, we show here that it holds for disjunctions of conjunctions of boundedness objectives.

⁴⁵⁸ ► Lemma 11 (Completeness for boundedness conditions in DNF). Let \mathcal{A} be a counter arena and ⁴⁵⁹ C its set of counters. Let \mathcal{W} be a finite subset of counter conditions for \mathcal{A} in Parity $(\mathcal{A}) \land \land \mathbb{B}$. ⁴⁶⁰ If Eve wins $(\mathcal{A}, \lor \mathcal{W})$, then she has a finitely switching strategy.

Front. Let C₁,...,C_p be subsets of C such that W is the set of all counter conditions Λ_{c∈C_i} B(c), for i ∈ {1,...,p}. Suppose that Eve does not have a finitely switching strategy from the initial vertex v₀. This means, by Lemma 9, that v₀ ∉ S^W. We construct a winning strategy for Adam for the complementary objective Comp = ∩_{i∈{1,...,p}} ∪_{c∈C_i} U(c) ∪ Parity(A). By definition of S^W, f(S^W) = S^W. Therefore, for any v ∈ V\S^W and i ∈ {1,...,p}, Eve does not win the counter game (A[v], (Parity(A[v])) ∩ ∩_{c∈C_i} B(c)) ∪ Reach(S^W))). Thus, by determinacy (Lemma 2), Adam has a winning strategy σ_{v,i} in A[v] for the complementary objective (U_{c∈C_i} U(c) ∪ Parity(A[v])) ∩ Reach(S^W).

⁴⁶⁹ Intuitively, a strategy for Adam winning for *Comp* could be defined by breaking it down ⁴⁷⁰ into the following steps:

Adam begins by step (1, 1): he follows strategy $\sigma_{v_0,1}$ until the play of the game reaches a vertex where the value of a counter of C_1 is 1. If that is never the case, then Adam



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

follows $\sigma_{v_0,1}$ ad. infinitum. Notice that, if the value of every counter of C_1 is bounded by a certain integer, Adam wins, since the play does not belong to Parity(\mathcal{A}).

- 475 After completing step (i, j) in a vertex v, two cases arise:
- ⁴⁷⁶ = If j < p, then Adam carries out step (i, j + 1) by following $\sigma_{v,j+1}$ until the play of the ⁴⁷⁷ game reaches a vertex where the value of a counter of C_{j+1} is *i*. If that is never the ⁴⁷⁸ case, Adam follows $\sigma_{v,j+1}$ ad. infinitum.
- ⁴⁷⁹ = If j = p, then Adam carries out step (i + 1, 1) by following $\sigma_{v,1}$ until the play of the ⁴⁸⁰ game reaches a vertex where the value of a counter of C_1 is i + 1. If that is never the ⁴⁸¹ case, Adam follows $\sigma_{v,1}$ ad. infinitum.

⁴⁸² See the Appendix for a complete proof.

483 **5** Complexity of games with disjunctions of boundedness conditions

The next result gives sufficient conditions on a class of games \mathcal{G} , to guarantee decidability of the problem of deciding if Eve has a finitely switching strategy for a disjunction of objectives in the class. In this result, we assume that the winning objectives of \mathcal{G} are finitely represented in some way. This is the case of all classes to which we apply this lemma in the paper.

▶ Lemma 12. Let $C \in \{PTIME, NP, CONP, EXPTIME\}$. Let G be a class of games with prefix-independent objectives, such that deciding whether, given $(\mathcal{A}, W) \in \mathcal{G}$, a vertex v of \mathcal{A} , and a subset X of vertices of \mathcal{A} , Eve wins $(\mathcal{A}[v], W \cup Reach(X))$, is in C. Then, deciding, given an arena \mathcal{A} and a finite subset of winning conditions W such that $\{(\mathcal{A}, W) \mid W \in W\} \subseteq \mathcal{G}$, whether Eve has a winning finitely switching strategy for $(\mathcal{A}, \bigvee W)$, is in C.

Proof. Suppose first that $\mathcal{C} = \text{PTIME}$. From Lemma 9, Eve has a winning finitely switching 493 strategy for $(\mathcal{A}, \bigvee \mathcal{W})$ if and only if the initial vertex v_0 of \mathcal{A} is in $S^{\mathcal{W}}$. Thus, we can decide 494 whether Eve has a finitely switching strategy by recursively computing the $S_i^{\mathcal{W}}$, one after the other, until $S_i^{\mathcal{W}} = S_{i+1}^{\mathcal{W}} = S^{\mathcal{W}}$. In order to compute $S_{i+1}^{\mathcal{W}}$ from $S_i^{\mathcal{W}}$, we check for every vertex v of \mathcal{A} whether Eve wins the game $(\mathcal{A}[v], W \cup \text{Reach}(S_i^{\mathcal{W}}))$. Thus, since $S_{|V|}^{\mathcal{W}} = S^{\mathcal{W}}$, 495 496 497 in order to compute $S^{\mathcal{W}}$, we only need to check, in ptime, whether Eve wins a game of the 498 form $(\mathcal{A}[v], W \cup \mathsf{Reach}(X))$ at most $|V| \times |V| \times |W|$ times. As a consequence, the problem of 499 deciding whether Eve has a winning finitely switching strategy for $(\mathcal{A}, \bigvee \mathcal{W})$ is in PTIME. 500 We present this generic fixpoint algorithm in Fig. 3, as it is useful to treat the case 501 $\mathcal{C} = NP$. In that figure, slv is an algorithm that terminates in polynomial time, and such 502 that $slv(\mathcal{A}, v, W, H)$ returns true if and only if Eve wins $(\mathcal{A}[v], W \cup \mathsf{Reach}(H))$. The case 503 where $\mathcal{C} = \text{EXPTIME}$ is similar. In the case where $\mathcal{C} = \text{NP}$, we transform the algorithm 504 SOLVE into an ptime algorithm VERIF (given in Appendix), which is defined as the 505 algorithm SOLVE, except that line 7 is replaced by a call to a ptime verifier that Eve wins 506 $(\mathcal{A}[v_i], W_i \cup \mathsf{Reach}(H_\alpha))$ given a certificate. All the certificates needed for each call at line 507 7 are taken as input of the algorithm VERIF. This approach works because the algorithm 508 VERIF returns **True** if and only if the answers to some well-chosen questions of the type 509 "Does Eve win $(\mathcal{A}[v], W \cup \mathsf{Reach}(X))$?" are true. The case where $\mathcal{C} = \mathrm{CoNP}$ is done in a 510 similar way, but this time by guessing the complement of $S^{\mathcal{W}}$. See Appendix for details. 511

 $SOLVE(\mathcal{A}, \mathcal{W})$ We are now ready to prove complexity results for solving 512 //v is the initial vertex of \mathcal{A} counter games with disjunction of boundedness objectives. 513 $//V = \{v_1, \ldots, v_n\}$ We start with the case of $\bigvee \mathbb{B}$. 514 $\begin{array}{c} W = \{ W_{1} \\ W_{2} \\ W_{2} \\ W_{3} \\ W_{4} \\ W_{1} \\ H_{2} \\ W_{3} \\ W_{4} \\$ **3.** $H_0, H_1, \ldots, H_N \leftarrow \emptyset$ 4. While $\alpha < n$ 5 For $i = 1, \ldots, n$ 6. For j = 1, ..., p7. If $\operatorname{slv}(\mathcal{A}, v_i, W_j, H_\alpha)$

- Theorem 13. Counter games with counter conditions in ∨ B are in NP ∩ CONP, and are in PTIME if the index of the colouring is fixed. A memory of size equal to the index of the colouring suffices for Eve, and infinite memory is required for Adam.
 Proof. Let G be a game over counter arena A with set of counters C, initial vertex v and objective ∨W where W = {Parity(A) ∩ B(c) | c ∈ C'} for some C' ⊆ C. It
 - $\mathcal{W} = \{ \operatorname{Parity}(\mathcal{A}) \cap \mathbb{B}(c) \mid c \in C' \}$ for some $C' \subseteq C$. It should be clear that those conditions are prefix-independent, therefore, by Lemma 9 and Lemma 11, Eve wins G iff she has a finitely switching strategy iff $v \in S^{\mathcal{W}}$. So, to check whether Eve wins G, it suffices to compute the fixpoint $S^{\mathcal{W}}$. We prove that each step of the fixpoint computation

(line 7 in algorithm SOLVE) is done in NP \cap coNP, and in PTIME if the index of the 528 colouring is fixed. By Lemma 12, the complexity statement of the theorem follows. It 529 remains to show that for all subset $X \subseteq V$, any vertex $u \in V$ and any counter $c \in C'$, 530 it is decidable in $NP \cap CONP$ (and in ptime for fixed parity) whether Eve wins the game 531 $(\mathcal{A}[u], (\operatorname{Parity}(\mathcal{A}) \cap \mathbb{B}(c)) \cup \operatorname{Reach}(X))$. First, we evacuate the reachability condition, i.e., 532 reduce in ptime the latter problem to solving a game $(\mathcal{A}', \operatorname{Parity}(\mathcal{A}') \cap \mathbb{B}(c))$. This is easily 533 done by adding a sink state to \mathcal{A} reached whenever X is visited, with operation skip on c and 534 priority 0. This reduction works for more general boundedness conditions (see Lemma 17 in 535 Appendix). Finally, the game $(\mathcal{A}', \operatorname{Parity}(\mathcal{A}') \cap \mathbb{B}(c))$ is solvable in NP \cap coNP by Theorem 6, 536 and in ptime for fixed parity, which is the case of \mathcal{A}' when the index of \mathcal{A} is fixed, because 537 they have the same colours. 538

For Adam, infinite memory might be necessary to enforce the complementary objective, as illustrated by Example 1. For Eve, Theorem 6 states that a memory of size the index of the parity function is sufficient to solve the "local" games $(\mathcal{A}', \operatorname{Parity}(\mathcal{A}') \cap \mathbb{B}(c))$, which can be translated back to strategies of same size in $(\mathcal{A}[u], (\operatorname{Parity}(\mathcal{A}) \cap \mathbb{B}(c)) \cup \operatorname{Reach}(X))$. Therefore, the memory transfer lemma (Lemma 10) yields the result.

We now turn to games on arenas \mathcal{A} with conditions in $\bigvee \bigwedge \mathbb{B}$, i.e., where $\mathcal{W} = \{\text{Parity}(\mathcal{A}) \land \bigwedge_{c \in C_i} \mathbb{B}(c) \mid i = 1, ..., n\}$ for $C_1, ..., C_n$ finite subsets of counters. The same reasoning as in the proof of Theorem 13 applies. The only difference here is that, to solve the "local" games of the fixpoint computation (line 7 of algorithm SOLVE), we rely on Theorem 4.

548 • Theorem 14. Counter games with winning conditions in $\bigvee \bigwedge \mathbb{B}$ are CONP-complete. 549 Finite memory suffices for Eve, and infinite memory is required for Adam.

⁵⁵⁰ We conclude this section by the case of Boolean combination of boundedness objectives.

Theorem 15. Counter games with winning conditions in $Bool^+(\mathbb{B})$ are in PSPACE and CONP-hard. Finite memory suffices for Eve, and infinite memory is required for Adam.

Proof. Any counter condition which is a positive boolean combination $\phi \in Bool^+(\mathbb{B})$ can be written in disjunctive normal form $\psi = \bigvee_{i \in \{1,...,p\}} \bigwedge_{c \in C_i} \mathbb{B}(c)$, where the C_i are subsets of \mathcal{C} . Let $\mathcal{W} = \{\text{Parity}(\mathcal{A}) \land \bigwedge_{c \in C_i} \mathbb{B}(c) \mid i = 1,...,n\}$. A direct application of Theorem 14 yields a CoNExpTime, because p might be exponential. Instead, we do not construct ψ explicitly. Recall that, from Theorem 4, counter games with counter conditions in $\bigwedge \mathbb{B}$ are in coNP, and thus in PSPACE. Thus, since it is well-known that, even if p may be exponential in the size of ϕ , we can enumerate \mathcal{W} in polynomial space, we can use this enumeration algorithm



515

516

517

518

519

520

521

522

523

524

525

526

527

© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

at line 6 of algorithm SOLVE in Fig. 3 to compute the fixpoint $S^{\mathcal{W}}$ in polynomial space. As 560 a consequence, the problem of deciding whether Eve has a winning finitely switching strategy 561 for counter games with winning conditions in $Bool^+(\mathbb{B})$ is in PSPACE. Hence, the result 562 follows because, as for Theorem 14, these strategies suffice for Eve. 563

6 Extensions of counter games with max operation 564

In this section, we consider counter games where the players can, in addition, put into a 565 counter the maximum value of a subset of counters. In other words, max-counter games are 566 defined in the same exact way as counter games, the only difference being *counter operations* 567 are now mappings from a finite subset C of C to $\{i, r, skip\} \cup \{\max_{c \in S}(c) \mid S \subseteq C\}$. 568

▶ **Theorem 16.** Let \mathcal{G} be the class of counter games G with counter condition $\bigwedge_{c \in C} \mathbb{B}(c)$, 569 where C is the set of counters of G. Given a game G in \mathcal{G} , the problem of deciding whether 570 Eve wins G is EXPTIME-c. Finite memory is sufficient for Eve and Adam. 571

Proof. For hardness, we reduce the emptiness problem of the intersection of n deterministic 572 top-down tree automata, which is known to be EXPTIME-hard [15]. We first show PSPACE-573 hardness if the case of arenas where Adam plays no role, i.e., $V_{\forall} = \emptyset$. The proof is by 574 reduction from the emptiness problem of the intersection of n DFA. The latter reduction 575 is inspired from the proof that deterministic min-automata have PSPACE-c emptiness 576 problem [7]. Using the fact that strategies are trees, we lift the latter reduction to tree 577 automata. The detailed proof is in Appendix, in Lemma 18. 578

It remains to show that solving a game in \mathcal{G} can be done in exponential time. The 579 difficulty for solving a game G of \mathcal{G} comes from the fact that counters interact with each 580 other, since the value of counters can "flow" from one to another via the max operation. That 581 was not case for $\bigwedge \mathbb{B}$ -counter games without max, which are CONP-C, and we could track 582 each counter separately, replacing each boundedness condition by a condition of the form 583 "if c is incremented infinitely often, then it is reset infinitely often". Here, we need to track 584 sequences of counters that flow one into another, called traces. We rather solve games with 585 the complementary objective, which is correct since max-counter games are determined (see 586 Lemma 19 in Appendix). We define a (non-deterministic) automaton \mathcal{B} with a single counter 587 d that guesses either a new trace, or a valid continuation to the current trace, at every move 588 of a play of \mathcal{G} . Every operation on the counters of the trace are mimicked on d, and it accepts 589 a play iff there exists a run such that d is unbounded. That same idea is already used in 590 the proof of Theorem 1 of [3], from which this proof is inspired. So, solving G boils down 591 to solving a game on the same arena but with objective given by the language $L(\mathcal{B})$. To 592 solve the latter, we convert \mathcal{B} into a non-deterministic parity automaton \mathcal{T} , which does not 593 preserve the language, but preserves the existence of winning strategy for Eve: when playing 594 on the area of G, Eve wins the objective $\mathcal{L}(\mathcal{B})$ if and only if she wins the objective $\mathcal{L}(\mathcal{T})$. 595 Correctness is ensured by a pumping-like argument based on the fact that finite-memory 596 strategies are sufficient to win ω -regular games, an argument very similar to the one used in 597 the proof of Lemma 3. The automata \mathcal{B} and \mathcal{T} are constructed in ptime from G. Then we 598 determinize \mathcal{T} in exponential time, take its product with G, and obtain a classical parity 599 game of exponential size and linear index. We can conclude since parity games with m edges, 600 n vertices and index k can be solved in $O(mn^k)$ (see e.g. [13]). The detailed proof is in the 601 Appendix, in Lemma 16. 602



© Emmanuel Filiot and Edwin Hamel-de le Court: licensed under Creative Commons License CC-BY Leibniz International Proceedings in Informatics LIPICS Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

7 Future work

In this paper, we have proved new complexity results for counter games and important classes 604 of boundedness conditions. Beyond the objective of having an exhaustive complexity table, we 605 believe that considering those different classes advance our understanding of those games, as 606 the techniques required to solve conjunctions and disjunctions are different. By determinacy, 607 those results also yield complexity bounds for the complementary classes of unboundedness 608 objectives. For example, we get that games with conjunctions of objectives of the form 609 $\mathbb{U}(c)$ can be solved in NP \cap CONP and that infinite memory is required. However, note that 610 our counter games are always taken in conjunction with a parity condition. Therefore, in 611 the complementary objectives, this parity condition is now taken in disjunction. We leave 612 conjunction of parity and unboundedness objectives as future work. Another important 613 direction is to consider classes of conditions that mix boundedness and unboundedness 614 objectives. Since the techniques used to solve them individually are different, this would 615 require new techniques. More generally, the only known upper bound for any Boolean 616 combination (not necessarily negation-free) of boundedness objective is non-elementary. We 617 believe there is space for improvement. 618

⁶¹⁹ — References

 Roderick Bloem, Krishnendu Chatterjee, and Barbara Jobstmann. Graph games and reactive synthesis. In Edmund M. Clarke, Thomas A. Henzinger, Helmut Veith, and Roderick Bloem, editors, *Handbook of Model Checking*, pages 921–962. Springer, 2018. doi:10.1007/978-3-319-10575-8_27.
 Mikolaj Bojanczyk. Weak MSO with the unbounding quantifier. *Theory Comput. Syst.*,

⁶²⁴ 2 Mikolaj Bojanczyk. Weak MSO with the unbounding quantifier. *Theory Comput. Syst.*,
 ⁶²⁵ 48(3):554–576, 2011. doi:10.1007/s00224-010-9279-2.

- Mikolaj Bojanczyk. Weak MSO with the unbounding quantifier. Theory Comput. Syst., 48(3):554–576, 2011.
- Mikolaj Bojanczyk. Weak MSO+U with path quantifiers over infinite trees. In Javier Esparza,
 Pierre Fraigniaud, Thore Husfeldt, and Elias Koutsoupias, editors, Automata, Languages, and
 Programming 41st International Colloquium, ICALP 2014, Copenhagen, Denmark, July 8-11,
 2014, Proceedings, Part II, volume 8573 of Lecture Notes in Computer Science, pages 38–49.
 Springer, 2014. doi:10.1007/978-3-662-43951-7_4.
- Mikolaj Bojanczyk and Thomas Colcombet. Bounds in w-regularity. In 21th IEEE Symposium
 on Logic in Computer Science (LICS 2006), 12-15 August 2006, Seattle, WA, USA, Proceedings,
 pages 285–296. IEEE Computer Society, 2006. doi:10.1109/LICS.2006.17.
- 6 Mikolaj Bojanczyk, Tomasz Gogacz, Henryk Michalewski, and Michal Skrzypczak. On
 ⁶³⁷ the decidability of MSO+U on infinite trees. In Javier Esparza, Pierre Fraigniaud, Thore
 ⁶³⁸ Husfeldt, and Elias Koutsoupias, editors, Automata, Languages, and Programming 41st
 ⁶³⁹ International Colloquium, ICALP 2014, Copenhagen, Denmark, July 8-11, 2014, Proceedings,
 ⁶⁴⁰ Part II, volume 8573 of Lecture Notes in Computer Science, pages 50-61. Springer, 2014.
 ⁶⁴¹ doi:10.1007/978-3-662-43951-7_5.
- Mikolaj Bojanczyk and Szymon Torunczyk. Deterministic automata and extensions of
 weak MSO. In Ravi Kannan and K. Narayan Kumar, editors, *IARCS Annual Conference* on Foundations of Software Technology and Theoretical Computer Science, FSTTCS 2009,
 December 15-17, 2009, IIT Kanpur, India, volume 4 of LIPIcs, pages 73–84. Schloss Dagstuhl
 Leibniz-Zentrum für Informatik, 2009. doi:10.4230/LIPIcs.FSTTCS.2009.2308.
- Véronique Bruyère. Computer aided synthesis: A game-theoretic approach. In Émilie
 Charlier, Julien Leroy, and Michel Rigo, editors, Developments in Language Theory 21st
 International Conference, DLT 2017, Liège, Belgium, August 7-11, 2017, Proceedings, volume
 10396 of Lecture Notes in Computer Science, pages 3-35. Springer, 2017. doi:10.1007/
 978-3-319-62809-7_1.



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

- G52
 9 Cristian S. Calude, Sanjay Jain, Bakhadyr Khoussainov, Wei Li, and Frank Stephan. Deciding
 G53 parity games in quasipolynomial time. In STOC, pages 252–263, 2017.
- Krishnendu Chatterjee and Nathanaël Fijalkow. Infinite-state games with finitary conditions.
 In Simona Ronchi Della Rocca, editor, Computer Science Logic 2013 (CSL 2013), CSL 2013, September 2-5, 2013, Torino, Italy, volume 23 of LIPIcs, pages 181–196. Schloss Dagstuhl -Leibniz-Zentrum für Informatik, 2013. doi:10.4230/LIPIcs.CSL.2013.181.
- Krishnendu Chatterjee, Thomas A. Henzinger, and Florian Horn. Finitary winning in omega regular games. ACM Trans. Comput. Log., 11(1):1:1-1:27, 2009. doi:10.1145/1614431.
 1614432.
- Krishnendu Chatterjee, Thomas A. Henzinger, and Florian Horn. The complexity of request response games. In *LATA*, volume 6638, pages 227–237, 2011.
- Krishnendu Chatterjee, Thomas A. Henzinger, and Nir Piterman. Generalized parity games.
 In Helmut Seidl, editor, Foundations of Software Science and Computational Structures, 10th
 International Conference, FOSSACS 2007, Held as Part of the Joint European Conferences
 on Theory and Practice of Software, ETAPS 2007, Braga, Portugal, March 24-April 1, 2007,
 Proceedings, volume 4423 of Lecture Notes in Computer Science, pages 153–167. Springer,
 2007. URL: https://doi.org/10.1007/978-3-540-71389-0_12.
- Thomas Colcombet and Christof Löding. The non-deterministic mostowski hierarchy and distance-parity automata. In Luca Aceto, Ivan Damgård, Leslie Ann Goldberg, Magnús M.
 Halldórsson, Anna Ingólfsdóttir, and Igor Walukiewicz, editors, Automata, Languages and Programming, 35th International Colloquium, ICALP 2008, Reykjavik, Iceland, July 7-11, 2008, Proceedings, Part II Track B: Logic, Semantics, and Theory of Programming & Track C: Security and Cryptography Foundations, volume 5126 of Lecture Notes in Computer Science, pages 398–409. Springer, 2008.
- Hubert Comon-Lundh, Max Dauchet, Rémi Gilleron, Cristof Löding, Florent Jacquemard,
 Denis Lugiez, Sophie Tison, and Marc Tommasi. Tree Automata Techniques and Applications.
 November 2007. URL: http://www.grappa.univ-lille3.fr/tata/.
- E. Allen Emerson and Charanjit S. Jutla. Tree automata, mu-calculus and determinacy
 (extended abstract). In 32nd Annual Symposium on Foundations of Computer Science, San
 Juan, Puerto Rico, 1-4 October 1991, pages 368-377. IEEE Computer Society, 1991.
- E. Allen Emerson and Charanjit S. Jutla. The complexity of tree automata and logics of
 programs. SIAM J. Comput., 29(1):132–158, 1999.
- Léo Exibard, Emmanuel Filiot, and Ayrat Khalimov. Church synthesis on register automata
 over linearly ordered data domains. In Markus Bläser and Benjamin Monmege, editors,
 38th International Symposium on Theoretical Aspects of Computer Science, STACS 2021, March 16-19, 2021, Saarbrücken, Germany (Virtual Conference), volume 187 of *LIPIcs*, pages
 28:1–28:16. Schloss Dagstuhl Leibniz-Zentrum für Informatik, 2021.
- Nathanaël Fijalkow and Martin Zimmermann. Cost-parity and cost-streett games. In Deepak D'Souza, Telikepalli Kavitha, and Jaikumar Radhakrishnan, editors, *IARCS Annual Conference on Foundations of Software Technology and Theoretical Computer Science, FSTTCS 2012, December 15-17, 2012, Hyderabad, India*, volume 18 of *LIPIcs*, pages 124–135. Schloss Dagstuhl
 Leibniz-Zentrum für Informatik, 2012. URL: https://doi.org/10.4230/LIPIcs.FSTTCS 2012, 2012.124.
- E. Grädel, W. Thomas, and T. Wilke. Automata, logics, and infinite games. a guide to current
 research. volume 2500. LNCS, Springer, 2002.
- ⁶⁹⁷ 21 Orna Kupferman, Nir Piterman, and Moshe Y. Vardi. Pushdown specifications. In LPAR,
 ⁶⁹⁸ volume 2514, pages 262–277, 2002.
- ⁶⁹⁹ 22 Donald A. Martin. Borel determinacy. Annals of Mathematics, 102(2):363–371, 1975.
- Nir Piterman and Amir Pnueli. Faster solutions of rabin and streett games. In *LICS*, pages 275–284, 2006.
- Martin Zimmermann. Delay games with WMSO+U winning conditions. *RAIRO Theor. Informatics Appl.*, 50(2):145–165, 2016. doi:10.1051/ita/2016018.



© Emmanuel Filiot and Edwin Hamel-de le Court;

licensed under Creative Commons License CC-BY Leibniz International Proceedings in Informatics

Appendix 704

Detailed proofs of section 4 705

Lemma 10 (Memory transfer). Let \mathcal{A} be a counter arena, V be its set of vertices, and \mathcal{W} 706 a finite set of prefix-independent winning conditions for \mathcal{A} . Let $N \in \mathbb{N}$ and suppose that for 707 all $X \subseteq V$, $u \in V$ and $W \in W$, strategies of memory size at most N suffice for Eve to win 708 $(\mathcal{A}[u], W \cup \mathsf{Reach}(X))$. Then for all $u \in S^{\mathcal{W}}$, Eve wins $(\mathcal{A}[u], \bigvee \mathcal{W})$ with memory at most N. 709

Proof. Let us recall that the strategies $\beta_{u,i}$ constructed in the proof of Lemma 9 (implication 710 $3 \Rightarrow 2$) are inductively defined as follows: Eve follows $\sigma_{u,i}$ as long as $\mathsf{S}_{i-1}^{\mathcal{W}}$ is not reached. As 711 soon as she reach a vertex $v \in \mathsf{S}_{i-1}^{\mathcal{W}}$, she applies $\beta_{v,i-1}$. We let $\beta = \beta_{u,|V|}$ for some $u \in \mathsf{S}^{\mathcal{W}}$, 712 which is a finitely switching strategy, and winning in $(\mathcal{A}[u], \bigvee \mathcal{W})$ according to Lemma 9. 713 Note that by construction of the family of strategies $\beta_{u,i}$, in any arbitrary vertex v Eve has 714 reached by playing β , she is always playing according to some local strategy $\sigma_{w,i}$ for some w 715 and j. It means that Eve has to remember w and j, but this costs $|V|^2$ states. Instead, we 716 show a different way of constructing a finitely switching strategy γ in $(\mathcal{A}[u], \bigvee \mathcal{W})$ for any 717 $u \in \mathsf{S}^{\mathcal{W}}$ as follows. Let us fix $u \in \mathsf{S}^{\mathcal{W}}$ in the rest of the proof. 718

We take an arbitrary linear order $\langle V \rangle$ on V. The memory of γ is $\{1, \ldots, N\}$, just as the 719 finite-memory strategies $(\sigma_{v,i})_{v,i}$. For all v, i, we let $(\delta_{v,i}, g_{v,i})$ be the memory mapping of 720 $\sigma_{v,i}$. Remind that $\delta_{v,i}$ updates the states while $g_{v,i}$ defines the moves. We define γ as follows, 721 with the invariant that all states γ reaches are in $S^{\mathcal{W}}$. Let *i* be the smallest integer such that 722 $u \in \mathsf{S}_{i}^{\mathcal{W}} \setminus \mathsf{S}_{i-1}^{\mathcal{W}}$. It exists since $u \in \mathsf{S}^{\mathcal{W}}$. The initial state of γ is the initial state m_0 of $\sigma_{u,i}$. 723

Now, let $v \in V_{\exists} \cap S^{\mathcal{W}}$ and *m* a memory state of γ . We define how γ plays when it is in *v* 724 with memory state m. We let i_v be the smallest integer such that $v \in \mathsf{S}_{i_v}^{\mathcal{W}} \setminus \mathsf{S}_{i_v-1}^{\mathcal{W}}$. We let u_v 725 the smallest vertex such that 726

1. $u_v \in \mathsf{S}_{i_v}^{\mathcal{W}} \backslash \mathsf{S}_{i_v-1}^{\mathcal{W}}$ 727

2. there exists a finite path h from u_v to v consistent with σ_{u_v,i_v} such that $\delta^*_{u_v,i_v}(q_0,h) = m$, 728 where $\delta^*_{u_v,i_v}(h)$ is the memory state of σ_{u_v,i_v} after h, starting in its initial state q_0 at 729 vertex u_v . 730

Then, γ at vertex v in memory state m plays $g_{u_v,i_v}(v,m)$ and moves to state $\delta_{u_v,i_v}(v,m)$. 731 Note that γ is well-defined: by construction, all the vertices v it reaches have been reached 732 following some strategy $\sigma_{v,i}$ and hence, there exists always a path h satisfying the conditions 733 of point 2 above, for such vertices v. 734

We prove that γ wins $(\mathcal{A}[u], \bigvee \mathcal{W})$. Take a play $\pi = v_1 v_2 v_3 \dots$ consistent with γ . Let 735 $m_0 m_1 m_2 \dots$ the sequence of states of γ on π . First, note that by definition of γ , there exists 736 n such that all the vertices v visited by π after at least n steps all belong to the same part 737 $S_{i^*}^{\mathcal{W}} \setminus S_{i^*-1}^{\mathcal{W}}$ for some i^* . It means that for all $k \ge n$, $i_{v_k} = i_{v_{k+1}} = i^*$. To simplify notations, 738 for all $k \ge n$, let $i_k = i_{v_k}$ and $u_k = u_{v_k}$. Consider the sequence $(u_k)_{k\ge n}$. By definition of 739 γ , it is decreasing for $\langle V \rangle$. Indeed, let $k \geq n$. Then, there exists a finite path h_k from u_k 740 to v_k consistent with σ_{u_k,i_k} . By definition of γ , v_{k+1} is defined by σ_{u_k,i_k} at state v_k and 741 memory m_k . Therefore, $h_k v_{k+1}$ is consistent with σ_{u_k,i_k} , so, u_k meets the requirements of 742 point 2 above. Since we want a minimal node, we obtain that $u_{k+1} \leq_V u_k$. Since there are 743 finitely many vertices, eventually, the sequence $(u_k)_{k\geq n}$ stabilizes on the same vertex u^* , i.e., 744 there exists l such that for all $k \geq l$, $u_k = u^*$. From that point on, γ always applies strategy 745 σ_{u^*,i^*} . Formally, it means that the infinite prefix $v_l v_{l+1} \dots$ is consistent with σ_{u^*,i^*} . We 746 can conclude since σ_{u^*,i^*} is winning in $(\mathcal{A}[u^*], W \cup \mathsf{Reach}(\mathsf{S}_{i^*-1}^{\mathcal{W}})$ for some $W \in \mathcal{W}$, and since 747 π never visits $S_{i^*-1}^{\mathcal{W}}$ by definition of $i^*, v_j v_{j+1} \cdots \in W$, and since W is prefix-independent, 748 $\pi \in W.$ 749



© Emmanuel Filiot and Edwin Hamel-de le Court: licensed under Creative Commons License CC-BY Leibniz International Proceedings in Informatics

Lemma 11 (Completeness for boundedness conditions in DNF). Let \mathcal{A} be a counter arena and C its set of counters. Let \mathcal{W} be a finite subset of counter conditions for \mathcal{A} in $Parity(\mathcal{A}) \land \bigwedge \mathbb{B}$. If Eve wins $(\mathcal{A}, \bigvee \mathcal{W})$, then she has a finitely switching strategy.

Proof. Let C_1, \ldots, C_p be subsets of C such that \mathcal{W} is the set of all counter conditions 753 $\bigwedge_{c \in C_i} \mathbb{B}(c)$, for $i \in \{1, \ldots, p\}$. Suppose that Eve does not have a finitely switching strategy 754 from the initial vertex v_0 . This means, by Lemma 9, that $v_0 \notin S^{\mathcal{W}}$. We construct a 755 winning strategy for Adam for the complementary objective $Comp = \bigcap_{i \in \{1,...,p\}} \bigcup_{c \in C_i} \mathbb{U}(c) \cup$ 756 $\overline{\text{Parity}(\mathcal{A})}. \text{ By definition of } \mathsf{S}^{\mathcal{W}}, \ f(\mathsf{S}^{\mathcal{W}}) = \mathsf{S}^{\mathcal{W}}. \text{ Therefore, for any } v \in V \backslash \mathsf{S}^{\mathcal{W}} \text{ and } i \in \mathcal{S}^{\mathcal{W}}.$ 757 $\{1,\ldots,p\}$, Eve does not win the counter game $(\mathcal{A}[v], \operatorname{Parity}(\mathcal{A}) \cap (\bigcap_{c \in C_i} \mathbb{B}(c) \cup \operatorname{Reach}(\mathsf{S}^{\mathcal{W}})))$. 758 Thus, by determinacy (Lemma 2), Adam has a winning strategy $\sigma_{v,i}$ in $\mathcal{A}[v]$ for the 759 complementary objective $\bigcup_{c \in C_i} \mathbb{U}(c) \cap \mathsf{Reach}(\mathsf{S}^{\mathcal{W}}) \cup \overline{\mathrm{Parity}(\mathcal{A}[v])}$. We now define a well-suited 760 decomposition of every history and play. To that aim, we define a successor function on 761 every element of the set $(\mathbb{N} \setminus \{0\}) \times \{1, \ldots, p\}$. For any positive integer *i* and any integer 762 $j \in \{1, \ldots, p\}$, we thus define s(i, j) as (i, j+1) if j < p, and as (i+1, 1) if j = p. We define 763 the counting decomposition of a history or a play w as the sequence $(w_i)_{i \in E}$ that satisfies 764 the following properties: 765

E is either equal to $\{1, \ldots, n\}$ for some $n \in \mathbb{N}$ or equal to $\mathbb{N} \setminus \{0\}$,

 $w = w_1 \cdots w_n,$

⁷⁶⁸ for any integer $i \in E$,

 $w \neq w_1 \cdots w_{i-1},$

770 771

772

and, if we let (k,l) denote $s^{i-1}(1,1)$, h_i is equal to the longest non-empty prefix h' of $(h_1 \cdots h_{i-1})^{-1}h$ such that, for any non-negative m with $m \leq |h'|$, we have $\lambda(\zeta(h'), c)_m < k$ for any $c \in C_l$ (h' can be an infinite word).

Notice that the counting decomposition $(h_i)_{i \in \{1,...,n\}}$ of any history h is indeed unique, ria since every h_i is unique by induction on i.

Using the above definitions, we formally define a winning strategy σ' of Adam in the following way.

For any history h, if we let $(h_i)_{i \in \{1,...,n\}}$ denote the counting decomposition of h, v denote 777 the first letter of h_n , and (k,l) denote $s^{n-1}(1,1)$, we define $\sigma'(h)$ as $\sigma_{v,l}(h_n)$. We show that 778 σ' is a winning strategy for Adam for \overline{G} (game area of G with objective the complement 779 of G's objective). Let ρ be a play consistent with σ' , and let $(h_i)_{i \in E}$ denote the counting 780 decomposition of ρ . Let us suppose that there exists $n \in \mathbb{N}$ such that $E = \{1, \ldots, n\}$. By 781 definition of σ' , if we let v denote the first letter of h_n and (k, l) denote $s^{n-1}(1, 1)$, h_n is 782 consistent with $\sigma_{v,l}$. However, since $\rho = h_1 \cdots h_n$, by definition of the counting decomposition, 783 for any $m \in \mathbb{N}$, we have $\lambda(\zeta(h_n), c)_m < k$ for any $c \in C_l$. Since $\sigma_{v,l}$ is a winning strategy 784 of Adam for $\overline{G}_l, h_n \notin \text{Parity}(\mathcal{A})$, and as a consequence, $\rho \notin \text{Parity}(\mathcal{A})$ either. Thus, if 785 $\rho \in \operatorname{Parity}(\mathcal{A})$, we have $E = \mathbb{N}$. 786

Furthermore, by definition of the counting decomposition, for any $i \in \mathbb{N}$, if we let (k,l) denote $s^{i-1}(1,1)$ and v' denote the first letter of h_{i+1} , there exists $c \in C_l$ such that $\lambda(\zeta(h_0 \cdots h_i v'), c_l)_{|h_i|+1} = k$. Thus, since every C_l is finite, for any $l \in \{1, \ldots, p\}$, there exists $c \in C_l$ such that, for any integer k, there exists an integer j with $\lambda(\zeta(\rho), c)_j \geq k$. To conclude, σ' is a winning strategy of Adam for \overline{G} .

⁷⁹² **B** Detailed proofs of section 5

▶ Lemma 12. Let $C \in \{PTIME, NP, CONP, EXPTIME\}$. Let G be a class of games with prefix-independent objectives, such that deciding whether, given $(A, W) \in G$, a vertex v of A,



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

and a subset X of vertices of A, Eve wins $(\mathcal{A}[v], W \cup \mathsf{Reach}(X))$, is in C. Then, deciding, given an arena A and a finite subset of winning conditions W such that $\{(\mathcal{A}, W) \mid W \in W\} \subseteq \mathcal{G}$, whether Eve has a winning finitely switching strategy for $(\mathcal{A}, \bigvee W)$, is in C.

Proof. Suppose first that C = PTIME. From Lemma 9, Eve has a winning finitely switching 798 strategy for $(\mathcal{A}, \bigvee \mathcal{W})$ if and only if the initial vertex v_0 of \mathcal{A} is in $S^{\mathcal{W}}$. Thus, we can decide 799 whether Eve has a finitely switching strategy by recursively computing the $S_i^{\mathcal{W}}$, one after the other, until $S_i^{\mathcal{W}} = S_{i+1}^{\mathcal{W}} = S^{\mathcal{W}}$. In order to compute $S_{i+1}^{\mathcal{W}}$ from $S_i^{\mathcal{W}}$, we check for every vertex v of \mathcal{A} whether Eve wins the game $(\mathcal{A}[v], W \cup \text{Reach}(S_i^{\mathcal{W}}))$. Thus, since $S_{|V|}^{\mathcal{W}} = S^{\mathcal{W}}$, 800 801 802 in order to compute $S^{\mathcal{W}}$, we only need to check whether Eve wins a game of the form 803 $(\mathcal{A}[v], W \cup \mathsf{Reach}(X))$ at most $|V| \times |V| \times |\mathcal{W}|$ times. As a consequence, the problem of 804 deciding whether Eve has a winning finitely switching strategy for $(\mathcal{A}, \mathcal{V}\mathcal{W})$ is in PTIME. 805 In order to better explain the case where $\mathcal{C} = NP$, we give the full algorithm SOLVE $(\mathcal{A}, \mathcal{W})$ 806 in Figure 4. In that figure, slv is an algorithm that terminates in polynomial time, and such 807 that $slv(\mathcal{A}, v, W, H)$ returns true if and only if Eve wins $(\mathcal{A}[v], W \cup \mathsf{Reach}(H))$. The case 808 where C = EXPTIME is similar. 809

Suppose now that $\mathcal{C} = NP$. Intuitively, we can use a very similar algorithm to the one 810 we used in the previous case: the only difference is that we guess the certificates needed 811 to check if Eve wins the games of the form $(\mathcal{A}[v], W \cup \mathsf{Reach}(X))$. This approach works 812 because the algorithm returns **True** if and only if the answers to some well-chosen questions 813 of the type "Does Eve win $(\mathcal{A}[v], W \cup \mathsf{Reach}(X))$?" are true. In order to formalize this idea, 814 for any arena \mathcal{A} , and any set \mathcal{W} such that $\{(\mathcal{A}, \mathcal{W}) \mid \mathcal{W} \in \mathcal{W}\} \subseteq \mathcal{G}$, we let size $(\mathcal{A}, \mathcal{W})$ 815 denote the size of a coding of the arena \mathcal{A} and of the set of winning conditions \mathcal{W} . There 816 exists an algorithm vrfE such that $vrfE(\mathcal{A}, v, W, H, w)$ verifies in polynomial time if Eve wins 817 $(\mathcal{A}[v], W \cup \mathsf{Reach}(\mathsf{S}_i^{\mathcal{W}}))$ using the certificate w. More precisely, vrfE terminates in polynomial 818 time, and there exists a polynomial P, such that for any game $(\mathcal{A}, w) \in \mathcal{G}$, the following is 819 true: there exists w of length $P(\text{size}(\mathcal{A}, \mathcal{W}))$ such that $\text{vrfE}(H, W, \mathcal{A}, v, w)$ returns **True** if 820 and only if Eve wins $(\mathcal{A}[v], W \cup \mathsf{Reach}(H))$. An algorithm VERIF_EVE that checks whether 821 Eve has a winning finitely switching strategy for $(\mathcal{A}, \bigvee \mathcal{W})$, given a certificate w of size 822 $P(\text{size}(\mathcal{A}, \mathcal{W})) \times |V|^2 \times |\mathcal{W}|$ (where V is the set of vertices of \mathcal{A}), VERIF_EVE($\mathcal{A}, \mathcal{W}, w$), is 823 precisely described in Figure 5. In the algorithm, for any integer k and any sequence of words 824 $(l_i)_{i \in \{1,\dots,k\}}$, we use the notation $\prod_{i=1,\dots,k} l_i$ for $l_1 \cdots l_n$. It is easy to see that, if the initial 825

vertex v of \mathcal{A} is in $S^{\mathcal{W}}$, then there exists a certificate w of size $P(\text{size}(\mathcal{A}, \mathcal{W})) \times |V|^2 \times |\mathcal{W}|$ such that $\text{VERIF}(\mathcal{A}, \mathcal{W}, w)$ returns **True**. The converse directly comes the fact that, for any certificate w, during a run of $\text{VERIF}_\text{EVE}(\mathcal{A}, \mathcal{W}, w)$, we always have $H_{\alpha+1} \subseteq f(H_{\alpha})$, and that we thus have $H_n \subseteq S^{\mathcal{W}}$.

Suppose now that $\mathcal{C} = \text{CONP}$. We show that the problem of deciding whether Eve does 830 not win $(\mathcal{A}, \bigvee \mathcal{W})$ is in NP, using the same idea as in the previous case, that is by computing 831 $\mathsf{S}^{\mathcal{W}}$ in a non-deterministic way, with an algorithm that returns \mathbf{True} if and only if the answers 832 to some well-chosen questions (in fact, to all of the questions in this case) of the type "Does 833 Eve win $(\mathcal{A}[v], W \cup \mathsf{Reach}(X))$?" are false. However, in this case, we compute $\mathsf{S}^{\mathcal{W}}$ by guessing 834 its complement. There exists an algorithm vrfA such that $vrfA(\mathcal{A}, v, W, H, w)$ verifies in 835 polynomial time if Eve does not win $(\mathcal{A}[v], W \cup \mathsf{Reach}(\mathsf{S}_i^{\mathcal{W}}))$ using the certificate w. More 836 precisely, vrfA terminates in polynomial time, and there exists a polynomial P, such that for 837 any game $(\mathcal{A}, w) \in \mathcal{G}$, the following is true: there exists w of length $P(\text{size}(\mathcal{A}, \mathcal{W}))$ such that 838 $vrfA(H, W, \mathcal{A}, v, w)$ returns **True** if and only if Eve does not win $(\mathcal{A}[v], W \cup \mathsf{Reach}(H))$. An 839 algorithm VERIF_ADAM that checks whether Eve does not have winning finitely switching 840 strategy for $(\mathcal{A}, \bigvee \mathcal{W})$, given a certificate w of size $|V| + P(\text{size}(\mathcal{A}, \mathcal{W})) \times |V| \times |\mathcal{W}|$ (where 841



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

SOLVE(
$$\mathcal{A}, \mathcal{W}$$
)
// v is the initial vertex of \mathcal{A}
// $V = \{v_1, \dots, v_n\}$
// $W = \{W_1, \dots, W_p\}$
// $W = \{W_1, \dots,$

V is the set of vertices of \mathcal{A}), VERIF ADAM($\mathcal{A}, \mathcal{W}, w$), is precisely described in Figure 6. 842 For any certificate w, if VERIF_ADAM($\mathcal{A}, \mathcal{W}, w$) returns **True**, if we let S' denote the value 843 of the set S at the beginning of line 4 of a run of VERIF ADAM($\mathcal{A}, \mathcal{W}, w$), we always have, 844 for any $u \in S'$ and for any $W \in W$, Eve does not win $(\mathcal{A}[u], W \cup \operatorname{Reach}(V \setminus S'))$. Suppose now that $S' \cap S^{\mathcal{W}} \neq \emptyset$, and let k be the smallest integer such that $S_k^{\mathcal{W}} = S_{k+1}^{\mathcal{W}}$. We show by induction on i that, for any $i \in \{0, \ldots, k\}, S' \cap S_{k-i}^{\mathcal{W}} \neq \emptyset$. Indeed, the property is obvious for 845 846 847 Induction on i that, for any $i \in \{0, ..., \kappa\}$, $S \cap S_{k-i} \neq \emptyset$. Indeed, the property is defined for k = 0 since $S_k^{\mathcal{W}} = S^{\mathcal{W}}$. Furthermore, if there exists u such that $u \in S' \cap S_{k-i}^{\mathcal{W}}$, then Eve wins $(\mathcal{A}[u], W \cup \mathsf{Reach}(S_{k-i-1}^{\mathcal{W}}))$, but Eve does not win $(\mathcal{A}[u], W \cup \mathsf{Reach}(V \setminus S'))$. As a consequence, $S_{k-i-1}^{\mathcal{W}}$ is not a subset of $V \setminus S'$, and thus $S_{k-i-1}^{\mathcal{W}} \cap S' \neq \emptyset$. Therefore, $S_0^{\mathcal{W}} \cap S' \neq \emptyset$, which is impossible since $S_0^{\mathcal{W}} = \emptyset$. Thus, we have $S' \subseteq V \setminus S^{\mathcal{W}}$. As a consequence, if there exists 848 849 850 851 a certificate w such that VERIF ADAM $(\mathcal{A}, \mathcal{W}, w)$ returns **True**, then Eve does not have 852 a winning finitely switching strategy for $(\mathcal{A}, \bigvee \mathcal{W})$. The converse is straightforward. To 853 conclude, the problem of deciding whether Eve does not win $(\mathcal{A}, \bigvee \mathcal{W})$ is in NP. 854 855

The following lemma assesses the complexity of games of the form $(\mathcal{A}[v], W \cup \mathsf{Reach}(X))$. We show that, when W comes from a counter condition, we can reduce games of the form $(\mathcal{A}[v], W \cup \mathsf{Reach}(X))$ to a game (\mathcal{A}', W) in polynomial time.

▶ Lemma 17. Let \mathcal{A} be a counter arena, V be its set of vertices, v be a vertex in V, X be a subset of V, and W be a counter condition for \mathcal{A} . We can construct a counter arena \mathcal{A}' in polynomial time with respect to |V|, such that Eve wins $(\mathcal{A}[v], (Plays(\mathcal{A}, W) \cap$ Parity $(\mathcal{A})) \cup \text{Reach}(X))$ if and only if Eve wins (\mathcal{A}', W) . Furthermore, if strategies with memory size at most N suffice for (\mathcal{A}', W) , then strategies with memory size at most Nsuffice for $(\mathcal{A}[v], (Plays(\mathcal{A}, W) \cap Parity(\mathcal{A})) \cup \text{Reach}(X))$.

Proof. The idea is to construct an arena \mathcal{A}' that comes from \mathcal{A} by replacing all the elements of



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY Leibniz International Proceedings in Informatics

VERIF_ADAM($\mathcal{A}, \mathcal{W}, w$)

 $//V = \{v_1, \ldots, v_n\}$ $//\mathcal{W} = \{W_1, \ldots, W_p\}$ //v is the initial vertex of \mathcal{A} $//w = w_1 w_2$, with $//w_1 = \underbrace{u_1 \# u_2 \# \cdots u_n}_{\alpha = 1, \dots, n} \prod_{j=1, \dots, p} w_{i,j},$ $//w_1 = \underbrace{\prod_{\alpha = 1, \dots, n}}_{\alpha = 1, \dots, n} \prod_{j=1, \dots, p} w_{i,j},$ $//w_1 = \underbrace{\prod_{\alpha = 1, \dots, n}}_{\alpha = 1, \dots, n} \prod_{j=1, \dots, p} w_{i,j},$ $//w_1 = \underbrace{\prod_{\alpha = 1, \dots, n}}_{\alpha = 1, \dots, n} \prod_{j=1, \dots, p} w_{i,j},$ 1. $S \leftarrow \emptyset$ **2.** For i = 1, ..., n $S = S \cup \{u_i\}$ 3. **4.** For i = 1, ..., nFor $j = 1, \ldots, p$ 5. If vrfA($\mathcal{A}, v_i, W_i, V \setminus S, w_{i,j}$) returns **False** 6. 7. ${\rm Return}\ {\bf False}$ 8. Return True

Figure 6 An algorithm in NP for the complement problem, for the case C = CONP

⁸⁶⁶ X by a single one, that we call -1. When a play would reach X in \mathcal{A} , there is a corresponding ⁸⁶⁷ play in \mathcal{A}' with the same previous history, that reaches -1, and that subsequently stays at ⁸⁶⁸ that vertex *ad. infinitum.* Furthermore, the labeling and colouring of the vertex -1 are ⁸⁶⁹ defined appropriately so that, if a play stays at the vertex $\{-1\}$, it is always winning for Eve.

Let C be the counter the set of counters of \mathcal{A} . Since W is a counter condition, it is a boolean formula ϕ over the set of propositions $\{\mathbb{B}(c) \mid c \in C\}$. If $v \in V$, then any strategy of Eve is winning for $(\mathcal{A}[v], (Plays(\mathcal{A}, W) \cap \text{Parity}(\mathcal{A})) \cup \text{Reach}(X))$. We thus suppose in the following that $v \notin V$.

Suppose now that ϕ is not satisfiable, then $Plays(\mathcal{A}, W)$ is empty. As a consequence, Eve wins $(\mathcal{A}[v], (Plays(\mathcal{A}, W) \cap \text{Parity}(\mathcal{A})) \cup \text{Reach}(X))$ if and only if Eve wins $(\mathcal{A}[v], \text{Reach}(X))$. Since deciding reachability in two-player games can done in polynomial time, and since memoryless strategies are sufficient for Eve and for Adam [20], the theorem follows.

We can thus suppose that ϕ is satisfiable. Then ϕ is implied by some condition of the form $\bigwedge_{c \in C_1} \mathbb{B}(c) \land \bigwedge_{c \in C_2} \mathbb{U}(c)$, with $C_1, C_2 \subseteq \mathcal{C}$. Let $(V, E, V_\exists, V_\forall, u)$ be the underlying two-player arena of \mathcal{A} , let ζ be the vertex labeling of A, and κ be its vertex colouring. We can suppose without loss of generality that -1 is not in V. We let V' denote $X \cup \{-1\}$, and E' denote the union of the following sets:

 $= \text{the set } (E \cap ((V \setminus X) \times (V \setminus X)))$

the set of all pair of vertices (u, -1) such that there exists $t \in X$ such that $(u, t) \in E$ the singleton $\{(-1, -1)\}$.

Furthermore, we let V_{\exists}' denote the set $V_{\exists} \cup \{-1\}$, Q' denote $Q \cup \{0\}$, κ' denote the vertex colouring equal to κ on X, and such that $\kappa(-1) = 0$, and ζ' denote the vertex labeling equal to ζ on X and such that

$$\zeta_c(-1) = \begin{cases} \mathsf{r} & \text{if } c \in C_1 \\ \mathsf{i} & \text{if } c \in C_2. \end{cases}$$



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

Finally, we let \mathcal{A}' denote the counter arena with underlying two-player arena equal to $(V', E', V'_{\exists}, V_{\forall} \cap X, v)$, set of counters C, vertex labeling ζ' , set of colours Q' and colouring κ' .

The lemma is direct consequence of the fact that, if σ and σ' are two strategies of Eve for the game $(\mathcal{A}[v], (Plays(\mathcal{A}, W) \cap \text{Parity}(\mathcal{A})) \cup \text{Reach}(X))$ and for the counter game (\mathcal{A}', W) respectively that are equal on $(V \setminus X)^{\omega}$, then σ is winning if and only if σ' is winning.

C Detailed proofs of section 6

▶ **Theorem 16.** Let \mathcal{G} be the class of counter games G with counter condition $\bigwedge_{c \in C} \mathbb{B}(c)$, where C is the set of counters of G. Given a game G in \mathcal{G} , the problem of deciding whether Eve wins G is EXPTIME-c. Finite memory is sufficient for Eve and Adam.

The proof of Theorem 16 is split into two parts, each covered by a different lemma. Lemma 18 gives the EXPTIME-hardness, and Lemma 20 gives the EXPTIME-easyness.

Lemma 18. Max-counter games with a single winning condition $\mathbb{B}(c)$ for some counter c, and no parity condition, are EXPTIME-hard.

Proof of Lemma 18. We prove EXPTIME-hardness of max-counter games with no parity condition and a conjunction of boundedness conditions $\bigwedge_{c \in C} \mathbb{B}(c)$. This entails the result because one can always add a counter c_m which takes the maximal value of all other counters $c \in C$ at each step, so that $\bigwedge_{c \in C} \mathbb{B}(c)$ is satisfied iff $\mathbb{B}(c_m)$ is satisfied.

To prove the theorem for conjunctions of boundedness conditions, we reduce the problem, 905 called $\bigcap_n DTOP$, of deciding if the intersection of n languages recognized by deterministic 906 top-down tree automata (DTOP) is empty, which is known to be EXPTIME-c [21]. Before 907 giving the EXPTIME-hardness proof, we first prove PSPACE-hardness for the particular 908 class of counter games where $V_{\forall} = \emptyset$, i.e., where Adam plays no role. We reduce the problem 909 of deciding if the intersection of n languages recognized by deterministic finite-automata 910 (DFA) is empty. We call the latter problem $\bigcap_n DFA$. The proof is inspired by a PSPACE-911 hardness proof of deciding non-emptiness of the language recognized by a deterministic 912 min-automaton [7]. Then we lift the reduction from $\bigcap_n DFA$ to the problem $\bigcap_n DTOP$, 913 i.e., to trees, by using the branching nature of counter games induced by Adam. 914

Consider an alphabet Σ and n complete DFA $D_i = (\Sigma, Q_i, q_i^0, F_i, \delta_i)$ such that all Q_i are 915 pairwise disjoint. We construct a counter arena $\mathcal{A}[D_1, \ldots, D_n]$ with $V_{\forall} = \emptyset$ and a set C of 916 n+1 counters, and no parity condition, such that Eve has a strategy to satisfy objective 917 $\bigwedge_{c \in C} \mathbb{B}(c)$ iff $\bigcap_i L(D_i) \neq \emptyset$. This construction is similar to that of [7], which is a reduction 918 from the universality problem for NFA. We assume that Σ contains a symbol $\# \in \Sigma$ and 919 for all $i, L(D_i) \subseteq (\Sigma - \#)^* \#$. The counter areas $\mathcal{A}[D_1, \ldots, D_n]$ is defined by $V_{\exists} = \Sigma$ and 920 $V_{\forall} = \emptyset$, and the set of transitions is $E = V_{\exists} \times V_{\exists}$. The vertex # is initial. The set of counters 921 is $C = \{c_0\} \cup \{c_q \mid q \in Q_i, i = 1, \dots, n\}$, and they are updated as follows for $i = 1, \dots, n$, 922 where $\max(\emptyset) = 0$: 923

 $\begin{array}{l} \text{ on vertex } f \neq \#: \text{ for all } q \in Q_i, c_q := \max\{c_{q'} + 1 \mid \exists q' \in Q_i, \delta(q', f) = q\} \text{ and } c_0 := c_0 + 1 \\ \text{ on vertex } \#: c_{q_O^i} := \max\{c_q \mid q \in Q_{i'} \text{ for some } i' \text{ and } \delta_{i'}(q, \#) \notin F_{i'}\}, \text{ and the counters} \\ \text{ or all } q \in Q_i \setminus \{q_0^i\} \text{ are reset, as well as } c_0. \end{aligned}$

Note that for $f \neq \#$, two operations are performed at once: increment counters $c_{q'}$ and take the max. This is done to simplify the presentation and can be simulated by doubling the number of vertices of the arena.



licensed under Creative Commons License CC-BY Leibniz International Proceedings in Informatics

© Emmanuel Filiot and Edwin Hamel-de le Court:

Now, observe that $Plays(\mathcal{A}[D_1, \ldots, D_n]) = \#\Sigma^{\omega}$ and a strategy for Eve is nothing but an infinite word w in $\#\Sigma^{\omega}$. We prove the following claims:

⁹³² Claim 1 For all non-empty finite set $X \subseteq \bigcap_{i=1}^{n} L(D_i)$, any play in $\#.X^{\omega}$ satisfies $\bigwedge_{c \in C} \mathbb{B}(c)$.

⁹³⁴ Claim 2 No play in $\#.(\bigcup_{i=1}^{n}((\Sigma - \#)^*\#) \setminus L(D_i))^{\omega}$ satisfies $\bigwedge_{c \in C} \mathbb{B}(c)$.

Proof of Claim 1. Let $m = \max\{|u| \mid u \in X\}$. Let $w = \#u_1u_2...$ such that for all $j \ge 1$, $u_j \in X$. We prove that w, which is a play of $\mathcal{A}[D_1,...,D_n]$) satisfies that all the counters are bounded by 2m. First, note that each u_j is of the form $v_j \#$, because $u_j \in \bigcap_i L(D_i)$ and the DFA D_i are assumed to accept words where # is an endmarker. First, consider counter c_0 : it is reset every time # is read, so, its maximal value is bounded by m. Now, for all $j \ge 1$ and $q \in \bigcup_i Q_i$, we let $in_{j,q}$ be the value of counter c_q after prefix $\#u_1...u_{j-1}$ and $out_{j,q}$ is value after prefix $\#u_1...u_{j-1}v_j$. By definition of the counter updates, we have:

- 942 1. $in_{j,q} = 0$ for all $j \ge 1$ and q not initial
- 943 **2.** $in_{j,q_0^i} = \max\{out_{j-1,q} \mid q \in Q_{i'} \text{ for some } i' \text{ and } \delta_{i'}(q,\#) \notin F_{i'}\} \text{ for all } j \ge 1$
- 3. $out_{j,q} = in_{j,q_0^i} + |v_j|$ if $q \in Q_i$ for some *i* and there exists a run of D_i from q_0^i to q on v_j
- 945 4. otherwise, $out_{j,q} = |r|$ where r is a run of maximal length on a prefix of v_j , ending in q.

Let $q \in Q_i$ for some i such that $\delta_i(q, \#) \notin F_i$. For all $j \ge 1$, there is no run from q_0^i to qon v_j , since $u_j = v_j \# \in L(D_i)$. So, we are in case 4 above and we have $out_{j,q} \le |v_j| \le m$. From the latter fact and 2, we get that $in_{j,q_0^i} \le m$ for all i, j. From that and 3, we get that $out_{j,q} \le m + |v_j| \le 2m$ for all j. So, all the counter have value at most 2m after each v_j , which concludes the proof that they are bounded.

Proof of Claim 2. Let w be a play of $\mathcal{A}[D_1, \ldots, D_n]$ in $\# (\bigcup_{i=1}^n ((\Sigma - \#)^* \#) \setminus L(D_i))^{\omega}$. Then, 951 $w = \#w_1 \# w_2 \# w_3 \# \dots$ such that $w_j \in (\Sigma - \#)^*$ for all $j \ge 1$. Moreover, for all $j \ge 1$, there 952 exists $i_j \in \{1, \ldots, n\}$ such that $w_j \notin \not\in L(D_{i_j})$ and there exists a run of D_{i_j} on w_j from $q_0^{i_j}$ 953 to some non-accepting state q_{i_j} . Denote by $in(i_j)$ the value of counter $c_{q_{i_j}}^0$ before reading 954 $w_j \# w_{j+1} \dots$ in w, and by $out(i_j)$ the value of counter $c_{q_{i_j}}$ before reading $\# w_{j+1} \# w_{j+1} \dots$ in 955 w. By definition of the counter updates, we have $out(i_1) \ge in(i_1) + |u|, out(i_2) \ge in(i_2) + |u|,$ 956 and so on. Moreover, $in(i_2) \ge out(i_1)$, $in(i_3) \ge out(i_2)$, and so on, since the states q_{i_i} 957 are non-accepting. This yields that the sequence $(in(i_i))_i$ is unbounded, concluding the 958 proof. 959

As a side note, observe that the two claims imply the following: $\bigcap_{i=1}^{n} L(D_i) \neq \emptyset$ iff there exists a word $w \in \#\Sigma^{\omega}$ which satisfies $\bigwedge_{c \in C} \mathbb{B}(c)$. Indeed, if there exists $u \in \bigcap_{i=1}^{n} L(D_i)$, then it suffices to apply Claim 1 to $X = \{u\}$. Conversely, if $\bigcap_{i=1}^{n} L(D_i) = \emptyset$, then $(\bigcup_{i=1}^{n} (\Sigma^* \setminus L(D_i)))^{\omega} = \Sigma^{\omega}$ and Claim 2 implies that no word of Σ^{ω} satisfy $\bigwedge_{c \in C} \mathbb{B}(c)$.

We now lift the latter reduction to (binary) trees. We let Σ be a finite alphabet containing a symbol # called a constant symbol, and all other symbols are called *binary* symbols. We let $\Sigma_2 = \Sigma - \#$ be the set of binary symbols. A Σ -tree is defined as a term where terms tare inductively defined by $t, t_1, t_2 ::= \# \mid f(t_1, t_2), f \in \Sigma_2$. The set of branches of a Σ -tree tis inductively defined as $br(\#) = \{\#\}$, and $br(f(t_1, t_2)) = \{(f, d).b \mid d \in \{1, 2\}, b \in br(t_d)\}$.

A deterministic top-down tree automaton is a tuple $\mathcal{T} = (Q, q_0, F, \delta)$ where Q is a finite set of states, $q_0 \in Q$ the initial state, $F \subseteq Q$ the final states, and $\delta : Q \times (\{\#\} \cup (\Sigma_2 \times \{1, 2\})) \to Q$ is a (total) transition function. We see \mathcal{T} as a DFA $DFA(\mathcal{T})$ recognizing a language in $(\Sigma_2 \times \{1, 2\})^* \#$ naturally as follows: $DFA(\mathcal{T}) = (Q, q_0, F, \delta')$ where for all $q \in Q$, for all $(f, d) \in \Sigma_2 \times \{1, 2\}, \, \delta'(q, f) = \operatorname{proj}_d(\delta(q, f))$, with proj_d the *d*th projection, and



© Emmanuel Filiot and Edwin Hamel-de le Court; icensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics



Figure 7 Arena for the proof of Theorem 18, where $\Sigma = \{\#, f_1, \ldots, f_m\}$. Transitions in bold are in both directions. Square vertices are controlled by Adam, and the initial vertex is #. When Adam picks a direction $d \in \{1, 2\}$, then Eve is forced to pick a vertex in $\Sigma_2 \times \{d\}$, or #.

 $\delta'(q, \#) = \delta(q, \#)$, and we denote by $L_{br}(\mathcal{T})$ the language recognized by this DFA. The language of Σ -trees accepted by \mathcal{T} is the set

$$L(\mathcal{T}) = \{ t \in Trees_{\Sigma} \mid br(t) \subseteq L_{br}(\mathcal{T}) \}$$

Deciding³, given n DTOP $\mathcal{T}_1, \ldots, \mathcal{T}_n$, whether $\bigcap_{i=1}^n L(\mathcal{T}_i) = \emptyset$ is EXPTIME-c [15].

Given $\mathcal{T}_1, \ldots, \mathcal{T}_n$ such that $\mathcal{T}_i = (Q_i, q_0^i, F_i, \delta_i)$ for all *i*, we construct a max-counter game *G* winnable by Eve iff $\bigcap_{i=1}^n L(\mathcal{T}_i) \neq \emptyset$. The main idea of the proof is construct a game where Adam picks a direction $d \in \{1, 2\}$ (1 means left and 2 right), while Eve picks the labels in Σ . The arena $\mathcal{A}[\mathcal{T}_1, \ldots, \mathcal{T}_n]$ of *G* (without the counters) is depicted on Fig. 7.

We now define counter conditions which make sure that if Eve has a strategy to keep all the counters bounded iff there exists $t \in \bigcap_i L(\mathcal{T}_i)$. For all i, let $\mathcal{T}_i = (Q_i, q_0^i, F_i, \delta_i)$. The set of counters is $C = \{c_q \mid q \in \bigcup_i Q_i\} \cup \{c_0\}$ (we assume wlog that all the sets Q_i are pairwise disjoint). Let us define counter updates. They are defined as for the arena $\mathcal{A}[DFA(\mathcal{T}_1), \ldots, DFA(\mathcal{T}_n)]$. To simplify the presentation (and in particular the structure of the arena), we perform several operations at once. Let us define the updates, for all $1 \leq i \leq n$:

981 on vertex $(f, j) \in \Sigma_2 \times \{1, 2\}$: for all $q_j \in Q_i, c_{q_j} := \max\{c_q + 1 \mid \exists q, q_{3-j} \in Q_i, \delta(q, f) = (q_1, q_2)\}$ and $c_0 := c_0 + 1$

 $= \text{ on vertex } \#: c_{q_{O}^{i}} := \max\{c_{q} \mid q \in Q_{i'} \text{ for some } i' \text{ and } \delta_{i'}(q, \lambda) \notin F_{i'}\}, \text{ and the counters}$ $c_{q} \text{ for all } q \in Q_{i} \setminus \{q_{0}^{i}\} \text{ are reset, as well as } c_{0}.$

985 on vertices $i \in \{1, 2\}$: counters are unchanged.

There is no parity condition and the counter condition is that the counters in C must be bounded. Let G be the constructed max-counter game. Before showing correctness, let us introduce some useful notation. Note that the histories and plays of G are elements of $\# \cup \Sigma_2 \times \{1,2\}$ alternating with directions in $\{1,2\}$. The following function removes the

³ In [15], the definition of DTOP is slightly different, but less general: there are no accepting states but the transition function can be partial. A tree is accepted if there is a run on it which traverses the whole tree (it is not in an inner node). Those automata can easily be encoded into (our) DTOP by completing the transition function into a sink state q_s , declaring all states to be final but q_s .



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

LIPICS Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany



Figure 8 Strategy σ_t constructed from a Σ -tree t.

intermediate directions. Given $w = \lambda_1 d_1 \lambda_2 d_2 \dots \lambda_n d_n$ such that for all $i, \lambda_i \in \{\#\} \cup \Sigma_2 \times \{1, 2\}$ and $d_i \in \{1, 2\}$, we let $lab(w) = \lambda_1 \lambda_2 \dots \lambda_n$.

We now show correctness of the reduction. Suppose that there exists some $t \in \bigcap_i L(\mathcal{T}_i)$. We first define a strategy σ_t for Eve and then show it is winning in G. The strategy σ_t just mimics t: it plays as t dictates when a leaf of t is reached, its behaviour is reset to the root of t. It is illustrated on Fig.8. Formally, the construction of σ_t satisfies the following invariant: all histories ending with an Eve vertex are words of the form $h = \#h_1h_2 \dots h_kpd$ where:

- 997 all h_i are such that $lab(h_i) \in br(t)$,
- 998 = lab(p) is a prefix of a branch of t
- 999 $\blacksquare d \in \{1,2\}$

Given such a history h, we consider two cases: if $lab(p) \in br(t)$, then σ_t is reset to the root of t, 1000 which means that $\sigma_t(h) = (f, d)$ such that f is the label of the root of t. Otherwise, $\sigma_t(h) = \#$ 1001 if $lab(p) \notin br(t)$, and $\sigma_t(h) = (f, d)$ if $lab(p)(f, d) \in br(t)$. Let us show that σ_t is winning. 1002 Let $\pi \in \text{Plays}(\sigma_t)$. First, we observe that $lab(\pi)$ is a play of $\mathcal{A}[DFA(\mathcal{T}_1), \ldots, DFA(\mathcal{T}_n)]$. 1003 Let C' be the set of counters of the latter areaa. By definition of σ_t , $lab(\pi)$ is of the form 1004 $\#b_1\#b_2\#\ldots$ with infinitely many # such that for all $j \ge 1, b_j\#$ is a branch of t. Since 1005 $t \in \bigcap_i L(\mathcal{T}_i)$, we also get that $b_j \# \in \bigcap_i L(DFA(\mathcal{T}_i))$. The set $X = \{b_j \# \mid j \geq 1\}$ is 1006 finite since its elements correspond to branches of t. Therefore, by Claim 1, π satisfies 1007 $\bigwedge_{c \in C'} \mathbb{B}(c)$. We conclude by observing that C = C', that $\mathcal{A}[\mathcal{T}_1, \ldots, \mathcal{T}_n]$ has the same vertices 1008 as $\mathcal{A}[DFA(\mathcal{T}_1),\ldots,DFA(\mathcal{T}_n)]$ plus the two vertices 1 and 2, with the same counter updates 1009 for their common vertices and no update on 1 and 2. Therefore, π satisfies $\bigwedge_{c \in C} \mathbb{B}(c)$ in 1010 $\mathcal{A}[\mathcal{T}_1,\ldots,\mathcal{T}_n].$ 1011

Conversely, suppose that $\bigcap_i L(\mathcal{T}_i) = \emptyset$. Take an arbitrary strategy σ of Eve. We show 1012 it is not winning. Intuitively, σ can be seen as an infinite tree. If there is a branch of the 1013 tree which visits # finitely many times, then σ is not winning because by following the 1014 directions corresponding to that branch, Adam can guarantee that counter c_0 is unbounded. 1015 So, we can assume that σ is such that all plays consistent with it sees infinitely many #. We 1016 construct a play π of the form $\#h_1\#h_2\#\ldots$ such that for all $j \geq 1$, there exists i such that 1017 $lab(h_i) \notin \notin L(DFA(\mathcal{T}_i))$, and we conclude by Claim 2. The construction of π is illustrated 1018 on Fig.9. 1019

¹⁰²⁰ Consider the set of histories H_1 of σ which contains a # symbol only at their end. ¹⁰²¹ Clearly, H_1 can be identified with a Σ -tree t_1 . Since $t_1 \notin \bigcap_i L(\mathcal{T}_i)$, there exists i such



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics



Figure 9 Losing play $\pi = \#h_1 \# h_2 \# \dots$ constructed from a strategy σ , seen as a tree.

that $t_1 \notin L(\mathcal{T}_i)$ and therefore, a history $h_1 \# \in H_1$ such that $lab(h_1) \# \notin L(DFA(\mathcal{T}_i))$. To construct h_2, h_3, \ldots , we proceed similarly. Let us explain how to construct h_2 . We let H_2 be the set of histories of the form $h_1 \# g_2 \#$ such that $h_1 \# g_2 \#$ is a history of σ such that g_2 does not contain #. The set $(h_1 \#)^{-1} H_2$ can be identified with a Σ -tree t_2 . Now, it suffices to take $h_2 \# \in (h_1 \#)^{-1} H_2$ such that $lab(h_2 \#) \notin L(DFA(\mathcal{T}_i))$ for some $i = 1, \ldots, n$. It exists since $t_2 \notin \bigcap_i L(\mathcal{T}_i)$. This concludes the proof.

¹⁰²⁸ In order to prove Lemma 20, we first prove the following, in a very similar way to the ¹⁰²⁹ proof of Lemma 2.

Lemma 19. Max-counter games (with Boolean combinations of boundedness objectives)
 are determined.

Proof. Given a counter arena \mathcal{A} and a counter c of \mathcal{A} , the set $Plays(\mathcal{A}, \mathbb{B}(c))$ is a Borel set. Indeed, it is equal to the countable union for all $N \ge 0$ of the sets

 $\operatorname{Plays}_{N}(\mathcal{A}, \mathbb{B}(c)) = \{\rho \in \operatorname{Plays}(\mathcal{A}) \mid \forall n \in \mathbb{N}, \lambda(\zeta(\rho), c)_{n} \leq N\}$

which are ω -regular. Indeed, a Büchi automaton that stores, in every state, the maximums between N and the value of each counter of C needs $|V| \times N^{|C|}$ states to recognize Plays_N($\mathcal{A}, \mathbb{B}(c)$). Since ω -regular sets are Borel, so is Plays ($\mathcal{A}, \mathbb{B}(c)$), as well as any Boolean combination of the latter. By Martin's determinacy theorem [22], the result follows.

Lemma 20. Given a game in \mathcal{G} , the problem of deciding whether Eve wins \mathcal{G} is in EXPTIME. Finite memory is sufficient for Eve and Adam.

¹⁰³⁸ **Proof.** We show that counter games G with condition of the form $Plays\left(\mathcal{A}, \bigvee_{c \in C} \mathbb{U}(c)\right) \cup$

Parity(\mathcal{A}), where C is the set of counters of G, and \mathcal{A} its underlying two-player arena, can be solved in EXPTIME, which implies the theorem by Lemma 19.

¹⁰⁴¹ We construct, from a max-counter game G, a parity game G', of exponential size and ¹⁰⁴² linear index, such that Eve wins G' if and only if Eve wins G. To simplify the presentation, ¹⁰⁴³ we introduce an intermediate automata model, called UB-automata. A (non-deterministic) ¹⁰⁴⁴ UB-automaton \mathcal{B} is a pair (\mathcal{A}, W) , where



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics LIPICS Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

- $= \mathcal{A} \text{ is a counter arean without max where Adam plays no role } (V_{\forall} = \emptyset), \text{ where each edge is labeled by a letter of an alphabet } \Sigma, i.e.. the set of edges of the counter game is replaced by a subset <math>E$ of $V \times V \times \Sigma$, and where the domain of the colouring κ is Σ rather than
- V (we colour the edges rather than colouring the vertices)
- 1049 \blacksquare W is a winning condition for \mathcal{A} , *i.e.* a subset of V^{ω} .

A run in \mathcal{B} is an infinite word $\pi = y_0 y_1 \cdots \in Y^{\omega}$ such that the first element of y_0 is the 1050 initial vertex of \mathcal{B} , and such that the second element of each y_i is the first element of y_{i+1} 1051 for any non-negative integer i. We let $Play(\pi)$ denote the word $v_0v_1\cdots$, where each v_i is 1052 the first element of y_i , and we let $\text{Input}(\pi)$ denote the word $z_0 z_1 \cdots$, where each z_i is the 1053 third element of y_i (*i.e.* the label of the edge y_i). A word w is accepted by \mathcal{B} if Input(π) is 1054 in Parity(κ), or if there exists a run π of \mathcal{B} such that Input(π) = w, and such that Play(π) 1055 is winning in \mathcal{B} (*i.e.* satisfies the winning condition of \mathcal{B}). The language accepted by \mathcal{B} is 1056 the set of accepted words. 1057

Let G be a counter game with underlying two-player arena $\mathcal{A} = (V, E, V_{\exists}, V_{\forall}, v)$, vertex labeling ζ , set of colors Q, colouring κ , and winning condition $Plays\left(\mathcal{A}, \bigvee_{c \in C} \mathbb{U}(c)\right) \cup$ Parity(\mathcal{A}). We construct a UB-automaton \mathcal{B} , of size polynomial in |C|, with only one counter $d \notin C$, that recognizes the language of all words $w \in V^{\omega}$ such that either $w \in \text{Parity}(\kappa)$, or $\zeta(w)$ satisfies the condition $\bigvee_{c \in C} \mathbb{U}(c)$. To make the construction more easily understood, we

first introduce the notion of trace. A *trace* of a word $w = z_0 z_1 \cdots \in \mathbf{Op}(C)^{\omega}$ is a mapping θ from $\{i, \ldots, j\}$ to C, where $i \leq j$ are two integers, such that, for any $l \in \{i, \ldots, j-1\}$,

$$\begin{array}{ll} \text{1065} & = \text{either } \theta(l) = \theta(l+1) \text{ and } z_l(\theta(l)) \in \{i, \mathsf{r}, \mathsf{skip}\}, \\ \text{1066} & = \text{ or } \theta(l+1) \neq \theta(l) \text{ and } z_l(\theta(l+1)) = \max_{c \in S}(c) \text{ with } S \subseteq C \text{ and } \theta(l) \in S. \end{array}$$

The value of θ at move $t \in \{i, \ldots, j\}$ is defined inductively as 0 if t = i, one plus the value at 1067 move t-1 if $z_{t-1}(\theta(t-1)) = i$, 0 if $z_{t-1}(\theta(t-1)) = r$, and the value at move t-1 otherwise. 1068 If a counter c reaches a value $N \geq 1$ at some point in w, then it is always possible to "track 1069 back", with a trace of w, the sequence of counter operations which led to c having that value, 1070 by choosing, every time we go back to a previous counter operation of the type $c' = \max_{d \in S} (d)$ 1071 with $S \subseteq C$, the good counter d of S (the one with the maximum value), until reaching a 1072 counter whose value is 0. Thus, there exists a counter $c \in C$ and two integers t and N such 1073 that $\lambda(w,c)_t = N$ if and only if there exists a trace θ of w, such $\theta(t) = c$, and such that 1074 the value of θ at move t is N. As a consequence, there exists counter c such that $\lambda(w,c)$ is 1075 unbounded if and only if the values of the traces of w are unbounded. 1076

This result allows us to define \mathcal{B} in the following way. The UB-automaton \mathcal{B} works, on 1077 input w, by guessing all the possible traces of $\zeta(w)$, by using non-determinism. The value of 1078 a trace is stored inside the counter d. More precisely, every time \mathcal{B} reads a letter, it either 1079 guesses a new trace, or guesses the next counter c' of C of the trace it is following, while 1080 applying, if c' is equal to the current counter c of the trace, the operation over c induced by 1081 the letter read, to counter d. Thus, the UB-automaton \mathcal{B} is constructed so that the value of d 1082 is unbounded if and only if there are traces of its input of arbitrarily large values. Moreover, 1083 we set the colouring of \mathcal{B} as κ . Thus, \mathcal{B} recognizes the language of all words $w \in V^{\omega}$ such that 1084 either $w \in \text{Parity}(\kappa)$, or $\zeta(w)$ satisfies the condition $\bigvee \mathbb{U}(c)$, *i.e.* the language recognized 1085 $c \in C$

by \mathcal{B} is the winning condition of the game G. The precise definition of \mathcal{B} is given below.

We let $V_1 = C \times \{i, r, skip\}$, and $v_1 = (c, r)$ where c is any counter in C. Furthermore, we let ζ^1 denote the mapping from V_1 to $\mathbf{Op}(\{d\})$ such that $(\zeta^1(c, \alpha))(d) = \alpha$, and E_1 denote



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

the the smallest subset of $V_1 \times V_1 \times V$ such that, for any $\alpha \in \{i, r, skip\}$ and any $v \in V$, we have

¹⁰⁹¹ for any $c, c' \in C$, $((c, \alpha), (c', \mathbf{r}), v) \in E_1$ (this comes from the fact that \mathcal{B} should be able ¹⁰⁹² to guess a new trace at any time),

¹⁰⁹³ for any $c \in C$, if $\zeta_c(v) \in \{i, skip\}, ((c, \alpha), (c, \zeta_c(v)), v) \in E_1$ (the trace follows the increment ¹⁰⁹⁴ or skip operation of a counter while updating d),

¹⁰⁹⁵ for any $c \in C$, if $\zeta_c(v) = \max_{c' \in S}(c)$, then $((c', \alpha), (c, \mathsf{skip}), v)) \in E_1$, for any $c' \in S$ (the trace ¹⁰⁹⁶ changes counters on a max operation while leaving d unchanged).

¹⁰⁹⁷ The UB-automaton \mathcal{B} is the UB-automaton with set of vertexes V_1 , set of edges E_1 , initial ¹⁰⁹⁸ vertex v_1 , set of counters $\{d\}$, vertex labeling ζ_1 , set of colors Q, colouring κ , and its winning ¹⁰⁹⁹ condition is defined as the set of all words $w \in V_1^{\omega}$ that satisfy $\mathbb{U}(d)$.

We now transform $\mathcal B$ into a parity automaton. To achieve that goal, we first transform $\mathcal B$ 1100 into an automaton with two colourings and without counters. To simplify the presentation of 1101 that construction, we introduce the notion of dual parity automaton. A (non-deterministic) 1102 dual parity automaton is a two-player game \mathcal{T} where Adam plays no role, with an alphabet 1103 Σ , a set of colours P' in addition to the original set of colours P, a colouring η' over Σ in 1104 addition to the original colouring η over the set X of vertices of G, and where every edge is 1105 labeled by Σ (*i.e.* the set of edges of \mathcal{T} is a subset of $X \times X \times \Sigma$). Furthermore, a word 1106 $w = b_0 b_1 \cdots$ is accepted by \mathcal{T} if and only if either $b_0 b_1 \cdots$ is in Parity (η') , or there exists a 1107 run $(v_0, v_1, b_0)(v_1, v_2, b_1) \cdots$ of \mathcal{T} such that $v_0 v_1 \cdots$ is in Parity (η) . The language recognized 1108 by \mathcal{T} , denoted $\mathcal{L}(\mathcal{T})$, is the set of words accepted by \mathcal{T} . Notice that \mathcal{T} can be converted into 1109 a non-deterministic automaton \mathcal{T}_1 , with two colours whose domains are the set of vertexes, by 1110 copying each vertex for every edge that goes to it. The acceptation condition of \mathcal{T}_1 is expressed 1111 by the union of the parity conditions induced by its two colourings. That automaton \mathcal{T}_1 1112 can be further converted into a non-deterministic parity automaton \mathcal{T}_2 with a single colour 1113 and two initial states, by duplicating it, colouring the first copy with the first colouring and 1114 the second copy with the second colouring. Thus, there exists a parity automaton \mathcal{T}_2 that 1115 recognizes the same language as \mathcal{T} , and $\mathcal{L}(\mathcal{T})$ is thus an ω -regular language. 1116

We now define \mathcal{T} as the dual parity automaton with set of vertices $V_1 = V \times \{i, r, skip\}$, alphabet V, edges E_1 , initial vertex v_1 , colouring κ from V to Q, and colouring κ' from V_1 to $\{1, 2, 3\}$ such that

$$\kappa'(v,\alpha) = \begin{cases} 1 & \text{if } \alpha = \mathsf{skip} \\ 2 & \text{if } \alpha = \mathsf{i} \\ 3 & \text{if } \alpha = \mathsf{r} \end{cases}$$

Notice that \mathcal{T} and \mathcal{B} have the same edges with the same labels, and the same initial state We let $\mathcal{L}(\mathcal{B})$ denote the language accepted by \mathcal{B} . Since $\mathcal{L}(\mathcal{T}) \subseteq \mathcal{L}(\mathcal{B})$, Eve wins $(\mathcal{A}, \mathcal{L}(\mathcal{B}))$ if Eve wins $(\mathcal{A}, \mathcal{L}(\mathcal{T}))$. We now show the converse.

Suppose that Eve has a winning strategy σ for $(\mathcal{A}, \mathcal{L}(\mathcal{B}))$, and that Eve does not win ($\mathcal{A}, \mathcal{L}(\mathcal{T})$). Since $\mathcal{L}(\mathcal{T})$ is an ω -regular objective, $(\mathcal{A}, \mathcal{L}(\mathcal{T}))$ is determined, and Adam has a finite memory winning strategy τ with memory mapping pair (δ, g) and memory size N, for ($\mathcal{A}, V^{\omega} \setminus \mathcal{L}(\mathcal{T})$). Let ρ be a play of \mathcal{A} consistent with σ and τ . Then ρ satisfies both of the following properties:

(1) either $\rho \in \text{Parity}(\kappa)$, or there exists a run π in \mathcal{B} such that $\text{Input}(\pi) = \rho$ and $\text{Play}(\pi)$ satisfies $\mathbb{U}(d)$

¹¹²⁷ (2) $\rho \notin \text{Parity}(\kappa)$, and for any run π in \mathcal{T} such that $\text{Input}(\pi) = \rho$, the greatest colour ¹¹²⁸ appearing infinitely often in $\text{Play}(\pi)$ is odd.



© Emmanuel Filiot and Edwin Hamel-de le Court; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

If $\rho \in \text{Parity}(\kappa)$, then ρ cannot satisfy property (2). Thus, from property (1), there exists a 1129 counter $c \in C$, and a run π in \mathcal{B} such that input $(\pi) = \rho$ and play (π) satisfies $\mathbb{U}(d)$. Therefore, 1130 if we let $\mu_0 \mu_1 \cdots = \text{play}(\pi)$, there exists two integers i and j such that there is no occurrences 1131 of r in $\zeta_d(\mu_i \cdots \mu_i)$ but at least $N \times \#V \times \#V_1 + 1$ occurrences of i. As a consequence, there 1132 exists two integers i' and j' such that there is at least one occurrence of i in $\zeta_d(\mu_{i'}\cdots\mu_{j'})$ and 1133 no occurrences of r, such that $\mu_{i'} = \mu_{i'}$, such that the g-memory state of $play(\pi)$ at move i'1134 equal to the g-memory state of $play(\pi)$ at move j', and such that $\rho(i') = \rho(j')$. Thus, if we 1135 let π' denote the run $\pi(0) \cdots \pi(i'-1)(\pi(i') \cdots \pi(j'-1))^{\omega}$ (where $\pi(0)\pi(1) \cdots = \pi$), the play 1136 $\rho' = \rho(0) \cdots \rho(i'-1)(\rho(i') \cdots \rho(j'-1))^{\omega}$ is consistent with σ and τ , input $(\pi') = \rho'$, and the 1137 greatest colour occurring infinitely often in $play(\pi')$ is equal to 2, which is even. This directly 1138 contradicts property (2). Therefore, Eve wins $(\mathcal{A}, \mathcal{L}(\mathcal{B}))$ if and only if Eve wins $(\mathcal{A}, \mathcal{L}(\mathcal{T}))$. 1139

Eve thus wins G, if and only if Eve wins $(\mathcal{A}, \mathcal{L}(\mathcal{B}))$, if and only if Eve wins $(\mathcal{A}, \mathcal{L}(\mathcal{T}_2))$. We let k be the index of G, and n be the number of its vertices. Notice that \mathcal{T}_2 is a parity automaton with a polynomial size and index, with respect to nk. It is well-known that there is a deterministic parity automaton \mathcal{D} with an exponential size and polynomial index with respect to the product of the size and index of \mathcal{T}_2 , that recognizes the same language as \mathcal{T}_2 . Thus, \mathcal{D} has exponential size and polynomial index with respect to the size of G, and Eve wins G if and only if Eve wins $(\mathcal{A}, \mathcal{L}(\mathcal{D}))$.

We now construct a game G' as the product of G and \mathcal{D} . More precisely, if is $V_{\mathcal{D}}$ be the 1147 set of vertices of \mathcal{D} , $E_{\mathcal{D}}$ is its set of edges, $v_{\mathcal{D}}$ is its initial state, $Q_{\mathcal{D}}$ is its set of colours, 1148 and $\kappa_{\mathcal{D}}$ is its colouring, we let Z denote the set of all pairs $((u_1, v_1), (u_2, v_2))$ of elements of 1149 $V \times V_{\mathcal{D}}$ such that (u_1, u_2) is in E and (v_1, v_2, u_1) is in $E_{\mathcal{D}}$, and we let χ denote the mapping 1150 from $V \times V_{\mathcal{D}}$ to $Q_{\mathcal{D}}$ that maps (u, u') to $\kappa_{\mathcal{D}}(u')$. We define G' as the parity game with 1151 underlying two-player arena $(V \times V_{\mathcal{D}}, Y, V_{\exists} \times V_{\mathcal{D}}, V_{\forall} \times V_{\mathcal{D}}, (v, v_{\mathcal{D}}))$, set of colours $Q_{\mathcal{D}}$, and 1152 colouring χ . A play $(v_0, u_0)(v_1, u_1) \cdots$ is winning in G' if and only if $v_0 v_1 \cdots$ is winning in 1153 G. Thus, Eve wins G if and only if wins G'. Furthermore, since finite memory strategies are 1154 sufficient for Eve and Adam for G', finite memory strategies are also sufficient for Eve and 1155 Adam for G: the winning player of G only needs to simulate a winning play in G' with the 1156 help of a finite memory winning strategy for G', by remembering at every move the exact 1157 vertex the corresponding play of G' would be in. In addition, it is well-known that solving a 1158 parity game with m edges, n vertices, and index 2k can be done in $O(m(n^k))$. Therefore, 1159 G', can be solved in time $O((2^{P(n)})^{Q(n)})$, where P and Q are two polynomials. To conclude, 1160 max-counter games in \mathcal{G} can be solved in EXPTIME. 1161

