



**HAL**  
open science

## **Inputs of disinfection by-products to the marine environment from various industrial activities: Comparison to natural production**

Matthias Grote, Jean-Luc Boudenne, Jean-Philippe Croué, Beate Escher, Urs von Gunten, Josefine Hahn, Thomas Höfer, Henk Jenner, Jingyi Jiang, Tanju Karanfil, et al.

### ► To cite this version:

Matthias Grote, Jean-Luc Boudenne, Jean-Philippe Croué, Beate Escher, Urs von Gunten, et al.. Inputs of disinfection by-products to the marine environment from various industrial activities: Comparison to natural production. *Water Research*, 2022, 217 (118383), 10.1016/j.watres.2022.118383 . hal-03631273

**HAL Id: hal-03631273**

**<https://hal.science/hal-03631273>**

Submitted on 5 Apr 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Inputs of disinfection by-products to the marine environment from various industrial activities: Comparison to natural production

Authors: Matthias Grote<sup>1\*</sup>, Jean-Luc Boudenne<sup>2</sup>, Jean-Philippe Croué<sup>3</sup>, Beate I. Escher<sup>4,5</sup>, Urs von Gunten<sup>6,7</sup>, Josefine Hahn<sup>8</sup>, Thomas Höfer<sup>9</sup>, Henk Jenner<sup>10</sup>, Jingyi Jiang<sup>11</sup>, Tanju Karanfil<sup>12</sup>, Michel Khalanski<sup>13</sup>, Daekyun Kim<sup>12</sup>, Jan Linders<sup>14</sup>, Tarek Manasfi<sup>6</sup>, Harry Polman<sup>15</sup>, Birgit Quack<sup>16</sup>, Susann Tegtmeier<sup>17</sup>, Barbara Werschkun<sup>18</sup>, Xiangru Zhang<sup>11</sup>, Greg Ziegler<sup>19</sup>

<sup>1</sup> German Federal Institute for Risk Assessment, Unit Transport of Dangerous Goods and Chemical Exposure, Berlin, Germany

<sup>2</sup> Aix Marseille Univ, CNRS, LCE, Marseille, France

<sup>3</sup> Institut de Chimie des Milieux et des Matériaux IC2MP UMR 7285 CNRS, Université de Poitiers, Poitiers 86000, France

<sup>4</sup> Department of Cell Toxicology, Helmholtz Centre for Environmental Research - UFZ, Leipzig, Germany

<sup>5</sup> Environmental Toxicology, Center for Applied Geoscience, Eberhard Karls University, Tübingen, Germany

<sup>6</sup> Eawag, Swiss Federal Institute of Aquatic Science and Technology, CH-8600, Dübendorf, Switzerland

<sup>7</sup> School of Architecture, Civil and Environmental Engineering (ENAC), Ecole Polytechnique Fédérale de Lausanne (EPFL), CH-1015, Lausanne, Switzerland

<sup>8</sup> Helmholtz-Zentrum Hereon, Institute for Coastal Environmental Chemistry, Geesthacht, Germany

<sup>9</sup> Member of GESAMP, Berlin, Germany (retired)

<sup>10</sup> Aquator, Utrecht, The Netherlands

<sup>11</sup> Department of Civil and Environmental Engineering, Hong Kong University of Science and Technology, Hong Kong SAR, China

<sup>12</sup> Department of Environmental Engineering and Earth Sciences, Clemson University, Anderson, SC 29625, USA

<sup>13</sup> Houilles, France

<sup>14</sup> Member of GESAMP, GESAMP-BWWG, retired, formerly RIVM, De Waag 24, 3823 GE Amersfoort., The Netherlands

<sup>15</sup> H2O Biofouling Solutions, Bommel, The Netherlands

<sup>16</sup> GEOMAR Helmholtz Centre for Ocean Research, Kiel, Germany

<sup>17</sup> Institute of Space and Atmospheric Studies, University of Saskatchewan, Saskatoon, Canada

<sup>18</sup> Wissenschaftsbüro Dr. Barbara Werschkun, Monumentenstraße31a, D-10829 Berlin, Germany.

<sup>19</sup> University of Maryland, Queenstown, MD, USA

\*Corresponding author: Tel.+49-30-18412-23104, Email: [matthias.grote@bfr.bund.de](mailto:matthias.grote@bfr.bund.de)


## Highlights

- Overview on oxidative treatment processes for different industrial applications
- Compilation of disinfection by-product types/concentrations in marine water uses
- Estimation of global DBP inputs into marine water from different industries
- Comparison of anthropogenic bromoform production to emissions from natural sources

## Keywords

Disinfection by-products, oxidant treatment, marine water, cooling water, desalination, ballast water treatment

## Graphical Abstract



## ABSTRACT

Oxidative treatment of seawater in coastal and shipboard installations is applied to control biofouling and/or to minimize the input of noxious or invasive species into the marine environment. This treatment allows a safe and efficient operation of industrial installations and helps to protect human health from infectious diseases and to maintain the biodiversity in the marine environment. On the downside, the application of chemical oxidants generates undesired organic compounds, so-called disinfection by-products (DBPs), which are discharged into the marine environment. This article provides an overview on sources and quantities of DBP inputs, which could serve as basis for hazard analysis for the marine environment, human health and the atmosphere. During oxidation of marine water, mainly brominated DBPs are generated with bromoform ( $\text{CHBr}_3$ ) being the major DBP.  $\text{CHBr}_3$  has been used as an indicator to compare inputs from different sources. Total global annual volumes of treated seawater inputs resulting from cooling processes of coastal power stations, from desalination plants and from ballast water treatment in ships are estimated to be  $470 - 800 \times 10^9 \text{ m}^3$ ,  $46 \times 10^9 \text{ m}^3$  and  $3.5 \times 10^9 \text{ m}^3$ , respectively. Overall, the total estimated anthropogenic bromoform production and discharge adds up to  $13.5 - 21.8 \times 10^6 \text{ kg/a}$  (kg per year) with contributions of  $11.8 - 20.1 \times 10^6 \text{ kg/a}$  from cooling water treatment,  $0.89 \times 10^6 \text{ kg/a}$  from desalination and  $0.86 \times 10^6 \text{ kg/a}$  from ballast water treatment. This equals approximately 2 – 6 % of the natural bromoform emissions from marine water, which is estimated to be  $385 - 870 \times 10^6 \text{ kg/a}$ .

## 1 INTRODUCTION

Marine water is subject to disinfection for several purposes. In cooling water circuits, disinfection strives to mitigate biofouling and clogging to guarantee good thermal exchange efficiency and reduce maintenance efforts (Rajagopal 2012). In desalination plants for potable water production, disinfection seeks to limit biofouling and to avoid clogging of in-take pipes in membrane-based and thermal treatment trains (Kim et al. 2015). Ballast water treatment aims to prevent, minimize and ultimately eliminate the risks resulting from the discharge of potentially invasive and harmful aquatic organisms and pathogens from ships to the environment and to human health (David and Gollasch 2015). In municipal wastewater disinfection as well as for seawater toilet systems, which are used in some coastal areas with limited freshwater supply, with the city of Hong Kong being the only large-scale case worldwide, the main purpose of treatment is to limit the discharge of pathogens to the aquatic environment (Jacangelo and Trussell 2002, Liu et al. 2016, Ng 2015). Furthermore, oxidative treatment is performed in various sectors such as aquaculture and seawater aquaria to control animal diseases and improve water quality (Qiang et al. 2015). However, while these latter applications may be locally relevant, they are less important as sources of disinfection by-products (DBPs) on a global scale and are not further addressed here.

Different chemical oxidants can be used for disinfection purposes, they can either be added from storage tanks or be generated *in situ*. For treatment of ocean or brackish waters containing bromide, some

disinfection techniques (including electro-chlorination, chlorination and ozonation) generate hypobromous acid (HOBr) as secondary oxidant in ocean and brackish water (HOBr) and thus produce similar patterns of DBPs (Heeb et al. 2014). Other oxidation processes (e.g., chlorine dioxide, peracetic acid and hydrogen peroxide) typically produce different patterns of DBPs (Shah et al. 2015b). However, the relative composition and absolute concentrations of DBPs also depend on process parameters such as the concentration of active substances, reaction time, as well as the chemical and physical characteristics of the treated water (salinity, organic matter, temperature, etc.) (Shah et al. 2015a). Therefore, DBP generation typically varies between different applications and sites even if similar or identical processes are applied.

So far, more than 700 anthropogenic DBPs have been identified in oxidative water treatment, mainly haloorganic compounds (also named organohalogenes). Haloorganic compounds are also part of the spectrum of naturally generated compounds with more than 5000 compounds described to be formed by marine organisms (Gribble 2010). Most of these compounds are distinct from DBPs and are formed in small quantities by specialized organisms. However, some of the DBPs with the highest concentrations in oxidative seawater treatment are also produced as natural organohalogenes, with bromoform being a major DBP and similarly a major natural haloorganic product in the marine environment (Quack and Wallace 2003). Phytoplankton and macroalgae have been identified as main sources (Carpenter and Liss 2000, Hepach et al. 2015).

The aim of this study is to identify sources and quantify the inputs of major DBPs through anthropogenic activities such as industrial cooling units, desalination plants, ballast water treatment in ships and wastewater treatment/seawater toilets to the marine environment. To this end, an overview on the most prominent treatment processes and regimes, i.e. oxidant concentrations and reaction times is provided for the different industrial processes. Data on DBP concentrations from different industrial activities is provided with a focus on the most abundant DBPs of each compound class to enable a comparative assessment. Furthermore, as the major DBP, bromoform is also produced naturally in the marine environment, this study also provides an overview on its production from natural processes. A quantitative comparison of the anthropogenic bromoform production relative to its overall production is carried out, which could serve as a basis for the estimation of potentially harmful impact of anthropogenic DBPs to aquatic organisms in the marine environment, to human health and the atmosphere.

This study was initiated by the Joint Group of Experts on the Scientific Aspects of Marine Environmental Protection (GESAMP), an expert group of ten UN Organizations, which strives to support sustainable governance of the marine environment by providing a multidisciplinary, scientific advice on marine ecosystems and human activities that affect them. GESAMP is involved in the assessment of risks resulting from ballast water treatment. To broaden the perspective towards potential risks of DBP discharges to the marine environment from other sources, a workshop was organized involving experts from different backgrounds and a report on the outcomes will be published (GESAMP in preparation). The present study provides a comprehensive compilation of the main aspects related to the quantification of DBP inputs.

## 2 GENERATION OF DISINFECTION BY-PRODUCTS IN MARINE WATERS

Various chemical oxidants are used in water treatment for disinfection purposes, with chlorine ( $\text{Cl}_2$ ) being the most widely applied in large industrial processes. In marine and brackish waters, the applied oxidants react with bromide to form various bromine species with hypobromous acid/hypobromite ( $\text{HOBr}/\text{OBr}^-$ ) being the most important ones. The formation of bromine by chemical oxidants such as chlorine, ozone and peracetic acid and its reactions with inorganic and organic compounds have been reviewed by Heeb et al. (2014). Depending on the characteristics of treated waters, a large fraction of the applied or formed secondary oxidants reacts with dissolved organic matter (DOM) leading to the formation of DBPs. Processes involved in DBP formation through reaction with DOM have been reviewed (Li and Mitch 2018, Richardson and Ternes 2018, Sedlak and von Gunten 2011, von Gunten 2018). In waters with high bromide levels, mainly brominated DBPs are formed (Shah et al. 2015a).

Because DBPs were first discovered in chlorinated drinking water, most of the initially discovered DBPs were chlorine-containing (Rook 1974). Later on, when bromide-containing waters were investigated including marine waters, many bromo-analogues of chlorine-containing DBPs were identified (Rook et al. 1978). Bromine-containing compounds represent the largest group of DBPs detected in marine waters (Manasfi et al. 2019, Werschkun et al. 2012). The types and concentrations of the brominated DBPs depend strongly on the specific oxidation conditions (oxidant, dose, reaction time, temperature, etc.) and on the characteristics and the concentrations of the dissolved organic matter.

Trihalomethanes (THMs) are the most important group of DBPs generated during chlorination of both freshwater and marine water (WHO 2017). In freshwater containing low levels of bromide, chloroform ( $\text{CHCl}_3$ ) is the major THM generated, whereas its brominated analogue bromoform ( $\text{CHBr}_3$ ) predominates at high bromide levels (Richardson et al. 1999). The four major chlorinated/brominated THMs ( $\text{CHCl}_3$ ,  $\text{CHBrCl}_2$ ,  $\text{CHBr}_2\text{Cl}$  and  $\text{CHBr}_3$ ) have been detected in chlorinated marine water, with chloroform being very minor and bromoform being by far the major THM (Shah et al. 2015a).

Haloacetic acids (HAAs) typically represent the second largest group of DBPs formed in oxidative processes. In marine water, dibromoacetic acid (DBAA) is observed as the compound with the second highest concentration after bromoform followed by tribromoacetic acid (TBAA) (Shah et al. 2015a). Other HAAs can be detected in considerably lower concentrations, including monobromoacetic acid (MBAA), mono-, di- and trichloroacetic acid along with bromochloro-, bromodichloro- and dibromochloroacetic acids (Fabbricino and Korshin 2005). HAAs are often summarized as the sum parameter  $\text{HAA}_5$  (sum of concentrations of monochloroacetic acid (MCAA), dichloroacetic acid (DCAA), trichloroacetic acid (TCAA), MBAA and DBAA) or  $\text{HAA}_9$ , which include  $\text{HAA}_5$  and the sum of the concentrations of bromochloroacetic acid (BCAA), bromodichloroacetic acid, chlorodibromoacetic acid and TBAA.

Haloacetonitriles (HANs) typically occur at higher concentrations in chlorinated and chloraminated drinking waters than many other nitrogen-containing DBPs (*N*-DBPs) such as nitrosamines, halonitromethanes, and haloacetamides (Krasner et al. 2006). In chlorinated seawater, HANs constitute only a small portion of the formed halogenated DBPs with dibromoacetonitrile (DBAN) being the predominant HAN (Fabbricino and Korshin 2005). The formation of HANs is related to the presence of nitrogenous precursors (e.g., amino acids) in water.

Bromate formation mainly occurs during ozonation (Shah et al. 2015a, von Sonntag and von Gunten 2012). Chlorination typically does not lead to bromate formation, unless it is in electro-chlorination treatment or when the process is catalyzed by metal oxides such as copper oxide (Jung et al. 2014, Liu et al. 2012).

Numerous aromatic DBPs have been detected in chlorine-treated, bromide-rich drinking water samples (Pan and Zhang 2013) and disinfected saline wastewater effluents (Ding et al. 2013). In chlorinated seawater cooling effluents of power stations, 2,4,6-tribromophenol (TBP) has been detected as the most important aromatic DBP (Allonier et al. 1999b, Boudjellaba et al. 2016).

Since only a fraction of DBPs has been identified, sum parameters such as adsorbable organic halide (AOX) or total organic halide (TOX) are used to quantify the total organohalogen content (Hua and Reckhow 2006, Kristiana et al. 2009, Langsa et al. 2017). For the same source water, the toxic potency of the disinfected water has been reported to be positively correlated with the TOX level of the disinfected water (Han and Zhang 2018). The measured individual DBPs account for about 40 – 70% of TOX in chlorinated water (Chen et al. 2015, Krasner 2009). Hence, there is a need of sum parameters to evaluate the overall content of halogenated DBPs. One major challenge is that not all DBPs are amenable to extraction methods and chemical analyses commonly used in the determination of DBPs. Moreover, among the extracted DBPs many are still unknown. This results in a gap between quantified DBPs and the sum of organohalogens (e.g., TOX). Accordingly, a considerable portion of DBPs remains to be discovered by new analytical techniques including improved methods for sample preparation.

Chlorine is used as oxidant for most large-scale applications. However, because concentrations of generated DBPs and ratios of different DBPs depend on process parameters (oxidant concentration, reaction time, etc.) and water characteristics (DOM type and concentration, salinity, etc.), each technical installation likely generates specific levels of DBPs. In the subsequent sections, an overview on the process parameters, volumes of treated water and DBPs generated is provided for major technical applications of oxidative treatment of marine and brackish waters.

### 3 COOLING WATERS

All industrial cooling systems using seawater are affected by excessive macrofouling (settlement and development of sessile marine organisms such as barnacles and mussels) that may block condensers, or

microfouling (formation of biofilms) that limit heat exchange. Fossil fuel and nuclear power stations at the seaside are particularly affected by biofouling because of the large water volumes required and the large size and complexity of the cooling systems (Jenner et al. 1997). To maintain water flow and heat exchange at the required level and to avoid disruption of operation of the cooling systems, it is necessary to apply anti-fouling measures.

Hypochlorite addition represents the most common antifouling treatment in industrial cooling water systems (Rajagopal 2012), either injected from a hypochlorite storage tank or produced on-site electrochemically. A low-level chlorination process requires to maintain a residual oxidant concentration of about 0.2 mg Cl<sub>2</sub>/L at the outlet of all heat exchangers such as condensers and auxiliary exchangers (Khalanski and Jenner 2012). The applied chlorine dose depends on the water quality (such as dissolved organic carbon (DOC) concentration and oxidant demand), the growth pressure (such as concentration of organisms and season) and specificities of the circuits. Typical chlorine doses range between 0.5 – 1.5 mg Cl<sub>2</sub>/L.

The most extensive study on DBPs in power plant cooling water covers 90 analyses of cooling water in 10 different coastal power stations in the United Kingdom, France and the Netherlands (Jenner et al. 1997). Since then, some additional data from these sites and additional analyses were presented (Allonier et al. 1999a, Taylor 2006). Additionally, studies on cooling waters of two Korean, an Indian and a Swedish power station were published (Fogelqvist et al. 1982, Padhi et al. 2012, Sim et al. 2009, Yang 2001). The main results from these studies are summarized in Table 1. The analyses of chlorinated cooling water samples show large variations that are not only explained by differences in water quality but also by the variability in circuits' complexity and their operation. Furthermore, quantitative comparison of DBP concentrations produced is hampered by differences in study design and quality (grab samples vs. multiple sampling, information on target or effective chlorine dose). Despite the shortcomings of this heterogeneous data set, average concentrations reported are relatively consistent with estimated DBP concentrations based on formation yields of bromoform and other major DBPs linked to chlorine dosage assuming an average chlorine dose in power plant cooling water of 0.75 mg/L as described by Khalanski (2003). Average concentrations of selected DBPs representing different compound groups in power station effluents provided in Table 1 are used as reference for the assessment: 25 (3.1 – 100) µg/L for bromoform, 9 (7.4 – 10.3) µg/L for DBAA, 1.1 (<0.1 – 3.6) µg/L for DBAN and 0.16 (0.002 – 0.37) µg/L for TBP.

In 2016, approximately 25,000 terawatt hours (TWh) of electricity were produced worldwide (IEA 2018). In thermal electricity production accounting for 18,900 TWh, an important fraction of the energy is transformed to heat, which needs to be dissipated. In coastal power stations once-through cooling (so-called open loop) is used for cooling by heating water by  $\Delta T$  of 10 – 15 °C and subsequent rejection into the surrounding water. In total, the ratio of dissipated heat into cooling water compared to electricity produced amounts to 1.2 and 2.1 for fossil fuel and nuclear power stations, respectively (Hartmann et al. 2011). This results in water consumption of approximately 20 – 30 m<sup>3</sup>/s and 33 – 50 m<sup>3</sup>/s for fossil fuel or nuclear power stations of 1000 MW, respectively. The produced electricity thus allows an estimate of the dissipated heat and subsequently

the volumes of required cooling water. Based on an analysis of geographic information, Maas et al. (2021) identified that about one fourth of the power plant capacities are located at the coast and estimated a global volume of discharged cooling water of  $8 \times 10^{11} \text{ m}^3/\text{a}$  into the marine environment. This emission estimate is based on an assumption of a high cooling requirement independent of energy source. Taking into account the lower cooling requirements of fossil power production compared to nuclear power production, an alternative value for the annual discharge of  $4.7 \times 10^{11} \text{ m}^3$  was estimated. Details on this estimate are provided as supplementary information (Table S1 and associated text). These two values serve as an estimate of range of discharges into marine waters from energy production.

**Table 1: Overview of selected DBPs detected in power station effluents (extracted and amended from Jenner et al. (1997))**

Power station	Chlorine dose [mg Cl <sub>2</sub> /L ]	Bromoform [µg/L]	DBAA [µg/L]	DBAN [µg/L]	Tribromo-phenol [µg/L]	Reference
Heysham 2 (UK)	0.5 – 1.0	26.1		2.6		a
Dungeness (UK)	0.75 – 1.0	5.8		0.2		a
Wylfa (UK)	0.3 – 0.4	27.3		0.83		a
Bradwell (UK)	0.6 – 1.0	25		0.87		a
Hartlepool (UK)	0.5 – 1.0	3.5		<0.1		a
Sizewell A (UK)	0.6 – 1.0	14.5		<0.1		a
Paluel (FR)	0.37	3.1		0.1		a
	0.82	9.6		1.05		a
	0.2	26.8	10.3	2.8	0.14	b
Penly (FR)	0.62±0.1	13.4		NA		a
	0.5±0.08	15.0		NA		a
	0.57	7.4	7.4	0.94	0.10	b
Gravelines (FR)	0.64	6.4		NA		a
	0.8	18.6		NA		a
	0.77	26.8	9.5	3.6	0.37	b
Maasvlakte (NL)	0.8 – 1.5	11.5		0.83		a
	0.8-1.5	8.4		0.94		a



Madras (IND)	1.0	28.3				c
Youngkwang (ROK)	1	124				d
Ringhals (SWE)	1.5	100				e
Kori (ROK)					0.02	f
<b>All Data mean (range)</b>		<b>25.0 (3.1 – 100)</b>	<b>9.0 (7.4 – 10.3)</b>	<b>1.1 (&lt;0.1 – 3.6)</b>	<b>0.16 (0.02 -0.37)</b>	

NA: not available; to increase readability, in some cases values were averaged and/or standard deviations omitted  
 UK: United Kindom, FR: France, NL: Netherlands, IND: India, ROK: Republic of Korea, SWE: Sweden  
 Data extracted from: a Jenner et al. (1997), b Allonier et al. (1999), c Padhi et al. (2012), d Yang (2001), e Fogelqvist et al. (1982), f Sim et al. (2009)

## 4 DESALINATION

Desalination processes contribute to the water supply in arid regions around the world. The global capacity for water production by desalination has been estimated to be  $9.5 \times 10^7$  million m<sup>3</sup>/d in 2018 (Jones et al. 2019). However, capacity and production are predicted to rapidly increase in the future (Hanasaki et al. 2016) due to rapid population growth and droughts induced by climate change. The largest number of desalination plants is present in the Middle East including the Arabian Gulf, Saudi Arabia and the United Arab Emirates (Jones et al. 2019). Important capacities are installed in the Mediterranean Basin, East Asia and the Pacific as well as the United States (Jones et al. 2019). Before 2013, around 60% of global desalination capacity treated seawater; while the remainder treated brackish (21%) and less saline water (19%) (Bennett 2013). The share of seawater has become larger according to the more recent data published by Jones et al. (2019).

Desalination is either based on reverse osmosis (RO) or distillation (i.e., thermal desalination) representing 63% and 31% of the world's treatment capacity, respectively (Gude 2016). To prevent bacterial growth and biofouling in the intake structures and to improve the performance of filters, chemical disinfectants are used as a pre-treatment before multi-media filtration or membrane filtration. Hypochlorite is the most commonly used disinfectant for pre-treatment as well as final disinfection. Chloramine, ozone, and chlorine dioxide are alternative disinfectants used less frequently in this context, typically for specific treatment objectives (Kim et al. 2015). For RO desalination plants, the chlorine dose and contact time vary with the chlorination mode (continuous, intermittent or shock treatment), the location and the objectives (intake pipe can be used for other applications e.g., power plants). A dose in the range of 0.2 – 2 mg Cl<sub>2</sub>/L is typically applied continuously to protect the intake pipe, although doses of up to 5 mg Cl<sub>2</sub>/L are used in some installations (Kim et al. 2015). The chlorine contact time can reach 45 – 60 min followed by an injection of sulfite to quench residual chlorine

prior to RO filtration to avoid damage to membranes. For distillation plants, chlorine doses of approximately 2 mg Cl<sub>2</sub>/L are applied targeting a residual chlorine concentration of 0.2 – 0.3 mg Cl<sub>2</sub>/L at the heat rejection section and no sulfite injection is required in the production line. As a result of disinfection, DBPs are formed during desalination processes.

It is important to distinguish between the produced desalinated water, which might be dedicated to human consumption and the wastewater typically called brine, which is discharged into the sea. Depending on the treatment process, different concentrations of DBPs can accumulate in the different water fractions. In this paper, the brines are the main focus as they represent the main source of DBP inputs into the marine environment resulting from desalination. DBP occurrences in brine produced from distillation and RO seawater desalination plants from several previous publications are provided in Table 2. In addition to THMs, HAAs, and HANs, low levels of iodinated THMs and brominated phenols were reported in a few RO concentrates (Agus and Sedlak 2010, Le Roux et al. 2015). Due to the heterogeneity of the installations and studies, it is difficult to draw general conclusions on DBP concentrations in discharged brines. Therefore, systematic DBP studies in full-scale seawater desalination plants are warranted to provide generalizable information of THMs and HAAs as well as other DBPs for each process. From several available studies, mean concentrations of major DBPs were calculated (Table 2). Average concentrations of selected DBPs representing different compound groups in power station effluents provided in Table 2 are used as reference for the assessment: 19 (0.2 – 104) µg/L for bromoform, 3.6 (0.6 – 11.6) µg/L for DBAA, 0.7 (0 – 1.2) µg/L for DBAN and 0.75 (0.53 – 0.96) µg/L for TBP.

Jones et al. (2019). estimate a global brine production and discharge of  $1.42 \times 10^8$  m<sup>3</sup>/d taking into account specificities of combination of desalination technology and different feedwater qualities.  $1.25 \times 10^8$  m<sup>3</sup>/d comes from seawater desalination plants situated close to the coastline. This equals a total estimated discharge of treated water from desalination plants into the marine environment of  $4.6 \times 10^{10}$  m<sup>3</sup>/a.

## 5 BALLAST WATER TREATMENT

Ballast water is taken up by ships when cargo is unloaded and discharged when cargo is loaded. It is an essential measure to stabilize vessels at sea and it is therefore essential for safe and efficient shipping operations. However, discharged ballast water can lead to the introduction of non-indigenous species into the receiving environment, potentially becoming invasive and possibly causing severe ecological, economic and human health impacts (Gollasch 2006, Ruiz et al. 2000). To address this problem, the International Maritime Organization (IMO) adopted the *International Convention for the Control and Management of Ships' Ballast Water and Sediments* (BWMC 2004), which entered into force in 2017. The Convention sets a maximum permissible concentration standard for living organisms in discharged ballast water for all ships in international traffic.

**Table 2: Overview on DBP occurrences in thermal brines and reverse osmosis concentrates of desalination plants (extracted and amended from Kim et al. 2015).**

Source and location		TBM [µg/L]	TBM [µg/L]	DBCM [µg/L]	DCBM [µg/L]	TCM [µg/L]	HAAs [µg/L]	MBAA [µg/L]	DBAA [µg/L]	TBAA [µg/L]	HANs [µg/L]	DBAN [µg/L]	BCAN [µg/L]	Other DBPs [µg/L]	
<b>Thermal Brine</b>															
Red Sea coast, Saudi Arabia	Brine recycle	9.5	9.0	0.36	0.13	ND	5.5	0.2	4.4	0.88	1.46	1.03	0.43		a
	brine blowout	0.18	0.53	0.14	0.21	ND	4.5	ND	4.4	ND	0.50	0.50	ND		a
Ruwais, UAE	brine blowout	<1.0	<0.2-0.8	<0.2	<0.2	<0.2-0.23	<15.2	<1.0	<1.0-11.6	ND					b
Doha west and Al-Zor, Kuwait		1.0-2.0	1.8 0.7												c
Jeddah, Saudi Arabia		12.7-17.8	12.4-17.4	0.3-0.4											d
<b>RO concentrate</b>															
Red Sea coast, Saudi Arabia	1st pass conc. in plant 1	6.2	4.96	0.23	0.06	ND	0.78	0.17	0.61	ND	ND	ND	ND		a
	1st pass conc. in plant 2	22.6-52.9	51.3	1.48	0.06	ND	5.7-7.2	ND	2.52	3.67	0.6-1.2	1.17	0.04	1.6-2.0 (I-THMs)	a
Carlsbad, USA	fall	5.0 – 14	5 - 14			0.2-0.7	17 - 27				0.78 - 3.1			0.53 - 0.96 (Br-phenol)	e
	winter	29 - 61	10-20			20-41									e
Ebara Corp, Japan		24 - 39													f
Nuweibaa, Egypt		159	104	2.9	0.3	52									g
<b>Mean*</b>		<b>29.5</b>	<b>19.3</b>	<b>0.8</b>	<b>0.2</b>	<b>10.4</b>	<b>9.1</b>	<b>0.3</b>	<b>3.6</b>	<b>0.9</b>	<b>1.3</b>	<b>0.7</b>	<b>0.1</b>	<b>0.75 (Br-phenols)</b>	
<b>Range</b>		<b>0.2-159</b>	<b>0.2-104</b>	<b>0.23-2.9</b>	<b>0.06-0.3</b>	<b>ND-52</b>	<b>0.78-27</b>	<b>ND-0.17</b>	<b>0.6-11.6</b>	<b>ND-3.67</b>	<b>0.5-3.1</b>	<b>ND-1.2</b>	<b>ND-0.4</b>	<b>0.53 - 0.96</b>	

Data extracted from: (a) Le Roux et al. (2015), (b) Elshorbagy and Abdulkarim (2006), (c) Saeed et al. (1999), (d) Mayankutty et al. (1991), (e) Agus and Sedlak (2010), (f) Kojima et al. (1995), (g) calculated mean THM concentration from three outlets from Hamed et al. (2017), ND: not detected.

\* calculated from all values provided. If ranges are given, the mean value was used for the calculation. ND was set to 0 for purpose of calculation



Although, a wide range of treatment technologies have been assessed to meet the standards, two treatment technologies are currently evolving as the major market shares: ultraviolet radiation (UV) and chemical oxidation, mainly hypochlorite added as a chemical or generated *in situ* by electrolysis (i.e., electrochlorination), both combined with filtration. Typically, the treatment is performed during the uptake of the ballast water. Oxidant doses ranging from 2 – 20 mg Cl<sub>2</sub>/L are used in IMO-approved ballast water management systems (BWMS). The reaction in the ballast water tank continues as long as residual oxidants are available and can last up to the total holding time of the ballast water, which may be as long as 21 d. Many systems aim to maintain a certain concentration of residual oxidants over the total ballast water holding time to maintain the biocidal potential and prevent the re-growth of organisms. To prevent a release of residual oxidants into the environment, often reducing agents such as thiosulfate or sulfite are added prior to or during the discharge of treated ballast water.

**Table 3: Most frequently identified disinfection by-products in ballast water management systems (extracted from David et al. (2018))\***

DBP	Frequency of detection <sup>§</sup>	Discharge concentration in [µg/L]				
		Min	Max	Median	Mean	SD
Bromate	20	6.85	920	33.5	119.7	245.8
Bromochloroacetic acid	27	0.10	246.7	5.6	15.1	46.6
Bromoform	36	0.08	890	229	247.1	213.7
Dibromoacetic acid	34	0.14	230	32.8	48.7	50.9
Dibromoacetonitrile	17	0.28	133	12.9	23.3	32.5
Dibromochloroacetic acid	18	1.50	32.7	8.7	10.8	8.2
Dibromochloromethane	33	0.03	120	16	22.1	28.2
Dibromomethane	10	0.06	9.6	1.6	2.8	3.4
Dichloroacetic acid	21	0.10	77.5	2.96	11	18
Dichloroacetonitrile	11	0.01	9.2	0.19	1.9	3.1
Dichlorobromoacetic acid	19	0.10	27.7	3.4	5.9	7.8
Dichlorobromomethane	27	0.04	70.5	4.4	9.5	14.5
Monobromoacetic acid	30	0.20	191	3.1	15.5	37.8
Monochloroacetic acid	21	0.08	495	2.9	36.3	110.2
Tribromoacetic acid	26	0.10	970	19.3	103.4	197.8
Trichloroacetic acid	18	0.50	150	9.7	26.3	41.0
Trichloromethane	21	0.10	257	3.9	29.8	61.1
2,4,6-Tribromophenol	5	0.10	0.45	0.21	0.27	0.14

\* The selection of DBPs is limited to findings in 36 Final Approval dossiers as the test conditions are relatively close to a realistic operational ballast water treatment. § Number of dossiers listing the respective disinfection by-product. Means refer to samples where compounds were detected.

David et al. (2018) analyzed data on DBP concentrations in 36 BWMS submitted to the IMO approval process and assessed according to the established methodology (GESAMP 2019). Bromoform was detected in discharged water of all investigated BWMS, whereas DBAA, dibromochloromethane and MBAA were detected in the discharged water of 34, 33 and 30 out of the 36 BWMS, respectively. Less frequently, 24 other DBPs were detected. An overview on relative frequencies of occurrences and mean and maximum concentrations in ballast water discharge during the test scenarios is provided in Table 3. DBP formation depends on oxidant type and concentration with most DBPs formed in systems applying hypochlorite treatment. Due to more variable water quality characteristics resulting from ship movements compared to fixed installations, a higher variability of the extent of DBP formation can be expected in operating BWMS. It should be noted that IMO regulations require BWMS to be tested under most challenging conditions, including very high concentrations of organic matter. DBP concentrations observed under these conditions are likely higher than those generated under normal operating conditions of the BWMS in natural waters. Mean concentrations of selected DBPs representing different compound groups in ballast water from this analysis are used as reference for the assessment in this study: 247 (0.08 – 920) µg/L for bromoform, 49 (0.14 – 230) µg/L for DBAA, 23 (0.28 – 133) µg/L for DBAN and 0.27 (0.1 – 0.45) µg/L for 2,4,6-TBP.

The annual global ballast water discharge from vessels in the international seaborne trade was estimated as  $3.1 \times 10^9$  m<sup>3</sup> in 2013 (David 2015). Another estimate provides a value of  $10^{10}$  m<sup>3</sup> of ballast water per year (WHO 2011). Today, estimates from the IMO suggest that UV treatment or electro-chlorination systems have been installed on vessels as the dominant technologies with a market share of about one-third each. The use of oxidants and other disinfection processes might represent most of the rest. It is currently unclear what percentage of ballast water volumes will be treated with oxidants in 2024, when the whole fleet will have to be equipped with BWMS. For the assessment in this study, it is assumed that a total of  $7 \times 10^9$  m<sup>3</sup> of ballast water is taken from the aquatic environment by ships each year of which 50% is subject to oxidative treatment, resulting in an estimated total annual volume of  $3.5 \times 10^9$  m<sup>3</sup> by 2024.

## 6 WASTEWATER TREATMENT

Disinfection of wastewater prior to effluent discharge to the sea is used to preserve the health of the coastal marine environment (Yang et al. 2000) and to protect humans against exposure to waterborne pathogenic microorganisms, notably from fecal contamination (Mansilha et al. 2009). The most common treatments include oxidation (especially chlorination) and UV irradiation (Jacangelo and Trussell 2002).

Chlorination is still the most widely used method for disinfection of municipal wastewater effluents both in Europe (Collivignarelli et al. 2017) and the USA. Krasner et al. (2009) report that wastewater treatment plants apply median chlorine doses of 2.4 – 2.7 mg Cl<sub>2</sub>/L. In the USA, wastewater chlorination is commonly followed by a dechlorination step before the discharge of the effluents to the receiving waters.

Chlorine and to a lesser extent chloramines can react with organic matter present in municipal wastewater to produce various DBPs. The wide array of formed DBPs include THMs, HAAs, and halogenated nitrogenous DBPs (Sgroi et al. 2018). Krasner et al. (2009) showed that chlorination of wastewater resulted in different DBP formation patterns depending on whether or not the treatment plant achieved good nitrification. Some results from this study are provided in Table 4.

**Table 4: Concentrations of DBPs reported in wastewater effluents (extracted from Krasner et al. (2009))**

Disinfectant	DBP	Level in wastewater effluent
Chloramine (chlorine added to poorly nitrified wastewater)	THMs HAAs HANs	Median = 2 µg/L Median = 8.9 µg/L ND to 12 µg/L (median and 75th percentile levels of 0.3 and 0.8 µg/L, respectively)
Chlorine (chlorine added to well nitrified wastewater)	THMs HAAs HANs	11 to 92 µg/L (median = 57 µg/L) 13 to 136 µg/L (median = 70 µg/L) 0.9 to 30 µg/L (median = 16 µg/L)

ND: not detected

As stated above, disinfection of municipal wastewater is applied worldwide. However, as the information is patchy, it is difficult to quantify the total volumes treated and volumes entering the marine environment. Therefore, for this study, no reliable information on the volumes of oxidatively treated sewage water discharged into the marine environment could be compiled. Since the relevance of these inputs is unknown for estimating DBP inputs into the marine environment at this point, they are not further considered here.

## 7 SEAWATER TOILETS

To mitigate the shortage of freshwater supply, seawater is used for toilet flushing in different coastal areas including Hong Kong, the city of Avalon (California), and several Pacific regions including the Marshall Islands and Kiribati (Boehm et al. 2009, Mirti and Davies 2005, Tang et al. 2007). In Hong Kong, where this practice has been extensively implemented since the 1950s, a total of  $2.7 \times 10^8$  m<sup>3</sup> of seawater is supplied every year (HK WSD 2018). The seawater is treated with chlorine or hypochlorite generated on-site before being pumped to service reservoirs and distributed to consumers and then mixed with other domestic sewage and enters the sewage systems in Hong Kong where it is again treated with chlorine prior to discharge.

In Hong Kong's seawater supply, typical chlorine doses are reported as 3 – 6 mg Cl<sub>2</sub> /L for the intake of seawater, 15 mg Cl<sub>2</sub>/L (12 min contact time) for the disinfection of primary sewage effluent and 4 – 18 mg Cl<sub>2</sub> /L (15 – 30 min contact time) for the disinfection of secondary sewage effluent (Ding et al. 2013, Gong and

Zhang 2015). As the seawater after toilet flushing is mixed with other domestic sewage and enters the sewage systems in Hong Kong, very high levels of sea salts, particularly bromide are introduced into the sewage.

Due to the variety of dissolved organic matter, including compounds derived from microorganism metabolization along with human and industrial waste, a higher complexity of DBPs can be formed in chlorinated saline sewage effluents than in chlorinated marine water. Nevertheless, commonly known DBPs such as THMs and HAAs have been reported to form in chlorinated saline sewage effluents as major compounds (Sun et al. 2009, Yang et al. 2005). An overview of the typical levels of DBPs reported in chlorinated saline sewage effluents in Hong Kong is provided in Table 5. Many polar/semi-polar brominated and iodinated aromatic DBPs have also been detected (Ding et al. 2013, Gong and Zhang 2015, Gong et al. 2016). Mean concentrations of selected DBPs representing different compound groups in seawater toilet effluents are used as reference for the assessment in this study: 32 µg/L for bromoform, 9 µg/L for DBAA, and 0.97 µg/L for 2,4,6-TBP.

**Table 5: Concentrations of DBPs in chlorinated saline sewage effluents in Hong Kong.**

	Primary effluent		Secondary effluent		Reference*
	Chlorine dose and contact time	Levels [µg/L]	Chlorine dose and contact time	Levels [µg/L]	
Bromochloroacetic acid	15 mg/L NaOCl as Cl <sub>2</sub> for 2 h	4.2	6 mg/L NaOCl as Cl <sub>2</sub> for 2 h	1.4	a
Bromodichloroacetic acid		2.2		0.0	a
Bromoform		26.5		31.8	a
Chloroform		8.0		5.0	a
Dibromoacetic acid		6.0		8.6	a
Dibromochloroacetic acid		0.0		0.0	a
Dibromochloromethane		15.6		2.5	a
Dichloroacetic acid		6.8		3.3	a
Dichlorobromomethane		11.6		4.9	a
Tribromoacetic acid		8.0		2.8	a
Trichloroacetic acid		5.0		5.7	a
2,4,6-Tribromophenol					6 mg/L NaOCl as Cl <sub>2</sub> for 30 min

\*Chlorination of the primary and secondary effluents was conducted in batch tests in the laboratory. Data extracted from (a) Yang et al. (2005); (b) Ding et al. (2013);

To date, only a few coastal cities have adopted seawater toilets requiring saline sewage effluents and generating halogenated DBPs. The saline sewage discharge in Hong Kong has been estimated to be 1.0 x 10<sup>9</sup> m<sup>3</sup>/a. This likely represents one of the largest volumes of treated wastewater inputs into the marine environment, which might be considered as a local hotspot.



## 8 OVERVIEW ON TREATMENT PROCESSES, VOLUMES AND DBP CONCENTRATIONS

An overview on oxidant treatment conditions and estimated global volumes of water treated in the different industrial sectors is provided in Table 6. Treatment processes differ in typically applied oxidant doses and in reaction times. Along the coast, where water resources are abundant, billions of m<sup>3</sup> of seawater are used, mostly for cooling of power plants and other industrial installations and desalination. Global cooling water discharge to marine water is estimated in the range of  $4.7 \times 10^{11} - 8.0 \times 10^{11}$  m<sup>3</sup>/a. Desalination plants treat high amounts of marine water, mostly in arid regions. The global volume of discharged concentrate (brine) is estimated to be  $4.6 \times 10^{10}$  m<sup>3</sup>/a. More than 50% of discharge originates from desalination plants located on the Arabian Peninsula. Thus, other regions are considered to be less impacted from desalination discharge. Input of treated ballast water may add locally to the DBP concentrations around large ports (Maas et al. 2019). All applications are expected to expand due to increasing demand from economic development and population growth.

**Table 61: Oxidant doses, reaction times and total treated volumes for the different sectors**

Input	Estimated average oxidant dose [mg Cl <sub>2</sub> /L]	Reaction times	Estimated volumes [m <sup>3</sup> /a]
Cooling water	0.75 (0.5 – 1)	2 – 30 minutes	$4.7 - 8.0 \times 10^{11}$
Desalination	0.2 – 2	10 min–few hours	$4.6 \times 10^{10}$
Ballast water	10 (2 – 20)	1 – 21 days	$3.5 \times 10^9$ <sup>a</sup>
Seawater toilets: Saline sewage treatment	4 – 18	12 – 30 minutes	$1.0 \times 10^9$
Municipal wastewater treatment	2.4 – 2.7	no information	no information

<sup>a</sup>These volumes are estimated to be treated once the global merchant fleet is equipped with ballast water management systems (by 2024).

In Table 7, an overview is provided on the mean concentrations of selected DBPs representing different compound groups detected in the treated or discharged water of the different industrial activities. The data show that DBP concentrations are generally higher in ballast water compared to other sectors, e.g., for bromoform, the major DBP, a mean concentration of 247 µg/L was detected whereas only about 10% of this level is typically observed in power plant cooling water, desalination brine and wastewater effluent from seawater toilets. The relatively high concentration in ballast water is coherent with the high oxidant doses and long contact times for these treatments. Furthermore, DBPs containing chlorine, appear to be present in

relatively low concentrations in power plant cooling water (Jenner et al. 1997) compared to discharge from other sectors, possibly reflecting the more constant quality of marine water treated. Ballast water and municipal wastewater may be characterized by varying water qualities and thus also varying bromide concentrations, which might shift the spectrum of generated DBPs to chlorinated species (David et al. 2018).

**Table 7: Average concentrations and concentration ranges of selected DBPs representing different compound classes in the treated water (discharge concentrations)**

DBP	Cooling water Average (range) µg/L	Desalination Average (range) µg/L	Ballast water Average (range) µg/L	Seawater toilets (1 <sup>st</sup> /2 <sup>nd</sup> treatment cycle)
Bromoform	25 (3.1 – 100)	19.3 (0.2 – 104)	247 (6 – 920)	27/32
DBAA	9 (7.4 – 10.3)	3.6 (0.6 – 11.6)	49 (0.1 – 230)	6/9
DBAN	1.1 (<0.1 – 3.6)	0.7 (0 – 1.2)	23 (0.3 -133)	NA/NA
2,4,6-TBP	0.16 (0.02 – 0.37)	0.75 (0.53 – 0.96)	0.27 (0.1 – 0.45)	NA/0.97

a. "NA" indicated "not available".

Based on the volumes of treated water in the different sectors (Table 6) and the observed mean DBP concentrations in the treated water or discharge (Table 7) the global production of DBPs from industrial activities can be estimated. Table 8 provides the estimated global production for bromoform. It is assumed that the major part of the produced DBPs represents direct inputs into the marine environment. Since bromoform is the most prominent DBP it may serve as a proxy to compare the inputs from different sectors. The total estimated anthropogenic bromoform production and discharge adds up to  $1.35 \times 10^7$  –  $2.18 \times 10^7$  kg/a, with contributions of  $1.18 \times 10^7$  –  $2.01 \times 10^7$  kg/a from cooling water,  $8.9 \times 10^5$  kg/a from desalination,  $8.6 \times 10^5$  kg/a from ballast water and  $3.0 \times 10^4$  kg/a from saline sewage treatment (Hong Kong only). Most of the estimates are based on realistic assumptions for discharged water volumes and mean values for observed or estimated DBP concentrations. Therefore, this assessment does not represent a worst-case scenario.

**Table 8: Estimated global anthropogenic bromoform production by different industrial sectors**

	Bromoform [10 <sup>6</sup> kg/a]
Cooling water	11.8 – 20.1
Desalination	0.89
Ballast water	0.86
Seawater toilets: Saline wastewater treatment <sup>a</sup>	0.03
<b>Total anthropogenic production</b>	<b>13.5 – 21.8</b>

<sup>a</sup>For wastewater treatment, no estimation is possible.

Environmental concentrations of DBPs depend on the quantities emitted but also on the characteristics of the receiving environment and natural background concentrations. Furthermore, the fate of the individual DBPs in the surface water depends on the lifetime, solubility and volatility of the compound. The major DBP, bromoform, is volatile and expected to be outgassed relatively quickly and no long-term accumulation in the ocean is expected. Environmental concentrations can be assessed by measurements of DBPs in receiving environments or by predicting the estimated dilution of the effluents. Examples for measured environmental DBP concentrations have been reported for water in the vicinity of power plants (Polman 2018) and in receiving seawater for treated sewage effluents (Feng et al. 2019). Environmental concentrations can also be estimated based on the knowledge about DBP concentrations in effluents and on assumptions of specific or generic dilutions. Predicted Environmental Concentrations (PEC) have been established for cooling water on the local and regional scale assuming dilution factors of the effluent of 20 and 100, respectively (Khalanski 2003) and ballast water by model dilution of measured discharge concentrations in a generic harbour (David et al. 2018, GESAMP 2019).

On local and short-time scales of a few days, all DBP discharges from anthropogenic activities contribute to the concentration in the aquatic environment. In continuous discharges, transient concentrations may be established reflecting an equilibrium of inputs, dilution, evaporation and degradation of compounds. Hence, at large industrial sites where ports, power plants or desalination plants are located, the DBP inputs in discharged waters can sum up and significantly increase DBP concentrations in the coastal ocean. This is important for metropolitan areas in temperate zones like Europe and North America or tropical and subtropical regions, like East and Southeast Asia.

## 9 DISCUSSION

A quantitative comparison between DBP inputs from different industries is hampered by the heterogeneity of the analyzed studies having various objectives, analytical techniques, and sampling strategies. Furthermore, as characteristics of the treated water are known to influence DPB formation, generalizations have to be interpreted with caution. Information on the total generated concentrations of halogenated organic compounds (i.e. in form of sum parameters such as adsorbable organic halogen, AOX) that would allow a total measure of DBP inputs is typically not available. Additional uncertainties may exist. For instance, average bromoform concentrations observed in cooling water were used for the assessment, keeping in mind that the majority of available data was obtained from studies conducted in European power stations and may not be representative for power stations in other world regions. For a regional assessment, Maas et al. (2021) estimated higher bromoform emissions for East Asian power stations.

However, despite the uncertainties underlying the summarized data and the necessity of estimations to fill data gaps, general conclusions appear warranted when the orders of magnitude of inputs are considered.

Bromoform, which was used as a proxy for the input of DBPs into the marine environment, is also synthesized in large quantities by phytoplankton and macroalgae in the oceans (Quack and Wallace 2003). Furthermore, bromophenols (with 2,4,6-tribromophenol most often detected) are part of the natural bromine-containing compounds of marine origin (Gribble 2010). For most other DBPs, no or only very limited natural production has been described. Therefore, most DBPs have to be considered as mainly anthropogenic compounds with little overlap with natural compounds except for bromoform and bromophenols.

For local risk assessment for the aquatic environment typically measured or predicted environmental concentrations (PEC) of individual compounds are compared to their predicted no effect concentrations (PNEC) where a ratio of PEC/PNEC < 1 indicates that no unacceptable risks to the aquatic environment may be expected. PNEC values for the most important DBPs observed in marine water have been proposed by GESAMP (2019). As environmental DBP concentrations depend on specific discharge conditions and dilution in receiving waters, any risk assessment process is site- or scenario-specific. Thus, general conclusions on environmental risks of DBPs in marine water are not possible. Most known DBPs are not bioaccumulative and are quickly eliminated and thus not considered to bioconcentrate in aquatic organisms nor to biomagnify in the food chain (GESAMP 2019, Khalanski and Jenner 2012). The low bioaccumulation potential of major known DBPs and the important dilution rate in ocean water suggest that the risks for the aquatic environment posed by DBPs are low on larger scales and distances from discharge, although in specific exposure situation such as in harbours and close to industrial discharges, local effects on aquatic organisms may occur.

Similarly, for the human health risk assessment, estimated human exposure levels are compared to Derived No Effect Levels (DNEL) and Derived Minimal Effect Levels (DMEL) for non-carcinogenic and carcinogenic compounds, respectively, where a Risk Characterization Ratio (estimated exposure level / DNEL or DMEL) (RCR) < 1 indicates that no unacceptable risks for humans may be expected. DNEL and DMEL for major DBPs are proposed by Dock et al. (2019) and GESAMP (2019). For discharge of treated ballast water, exposure from two different scenarios covering direct contact, i.e. swimming near a ship during ballast water discharge, and seafood consumption did not indicate any significant health effects (Dock et al. 2019). Similar assessments are not available for discharges from other industrial applications.

Bromoform is a major carrier of bromine from the ocean to the atmosphere (Penkett et al. 1985). If it reaches the atmospheric boundary layer it is oxidized or photo-dissociated to reactive halogen species which contribute to the depletion of tropospheric and stratospheric ozone by catalytic cycles (Saiz-Lopez and von Glasow 2012, Tegtmeier et al. 2020, WMO 2018). The global bromoform emissions from marine water resulting from natural sources have been estimated to be  $3.85 \times 10^8$  –  $8.70 \times 10^8$  kg/a (Wang et al. 2019, Yokouchi et al. 2005). Therefore, based on the assessment in this study, anthropogenic bromoform discharge into the marine water resulting from the considered industrial treatments equals approximately 2 – 6 % of those global marine bromoform emissions depending on whether higher or lower boundaries are used (Table 8). This range reflects the uncertainty of the estimated anthropogenic inputs and natural production. Potentially, the inputs could be higher in case the conducted studies on DBP concentrations in cooling water

are not representative for other regions and other anthropogenic inputs may also be quantitatively relevant, e.g., emission from wastewater treatment, which could not be quantified due to missing data. Furthermore, anthropogenic emission to the atmosphere may be underestimated in this study focusing mainly on marine inputs as 90% of THMs produced in thermal desalination plants are rejected as vent gases (Le Roux et al. 2015). Therefore, an additional assessment of the overall THM production emitted to the atmosphere either from water or directly should be conducted when aiming to address potential effects on the atmosphere (Quivet et al., 2022).

## 10 CONCLUSIONS

This study identifies sources and quantities of inputs of major DBPs through oxidative industrial processes to marine water including industrial cooling, desalination, ballast water treatment and seawater toilets, with the following main outcomes:

- Disinfection by-products (DBPs) are produced during oxidative water treatment for disinfection purposes or biofouling control in industrial processes using marine or brackish water.
- Due to the high concentration of bromide, which is oxidized to hypobromous acid by many oxidants, brominated DBPs are most abundant in treated marine water.
- Bromoform has been identified as the major DBP in all industrial applications using oxidants in seawater. Furthermore, other DBPs, e.g., bromochloromethanes, haloacetic acids, haloacetonitriles and halophenols have been observed, with dibromoacetic acid, tribromoacetic acid, dibromoacetonitrile, 2,4,6-tribromophenol and bromate being often detected.
- Absolute concentrations and relative abundance of the different DBPs vary between different applications reflecting variable process parameters (e.g., oxidant dose and reaction time) and water quality parameters (e.g., characteristics and concentration of dissolved organic matter).
- A quantification of global discharges of DBPs from industrial processes showed that cooling water was the major anthropogenic source, followed by desalination brine and ballast water.
- Since bromoform is the most abundant DBP, it may serve as a proxy to compare the inputs from different sources. The total estimated anthropogenic bromoform discharged into marine water adds up to  $1.35 \times 10^7 - 2.18 \times 10^7$  kg/a which is considerably lower than the estimated natural emissions from marine water of  $3.85 \times 10^8 - 8.7 \times 10^8$  kg/a.
- Although there are high quality studies on individual sites, e.g., cooling circuits of some nuclear power plants and rather abundant information of DBP generation in ballast water treatment, a comprehensive risk or impact assessment is hampered by a lack of data.
- Uncertainties arise from missing information, e.g., volume of marine water used for cooling purposes worldwide, DBP concentrations in cooling water from not yet studied regions, and from unknown future developments, e.g., an increasing number of desalination plants or the fraction of ballast

water management systems using oxidants to be installed. Nevertheless, the estimates from this study suggest that industrial bromoform inputs into marine water are minor compared to the natural marine emission ( $\leq 10\%$ ).

More harmonized studies on the different major DBPs identified in oxidant-treated effluents are warranted to allow a more systematic overview on DBP variety in the different industries and regions. Strengthening of international efforts in ocean science to build up a better database on concentrations of halogenated organic compounds in the marine environment is advised.

## 11 ACKNOWLEDGEMENTS

This study is based on the result of and elaborated after an international GESAMP workshop held in Berlin, Germany, 22 – 23 November 2018 in cooperation with and financed by the German Federal Institute for Risk Assessment (BfR).

## 12 REFERENCES

- Agus, E. and Sedlak, D.L., 2010, Formation and fate of chlorination by-products in reverse osmosis desalination systems. *Water Res.* 44(5), 1616-1626.
- Allonier, A.-S., Khalanski, M., Camel, V. and Bermond, A., 1999a, Characterization of Chlorination By-products in Cooling Effluents of Coastal Nuclear Power Stations. *Mar. Pollut. Bull.* 38(12), 1232-1241.
- Allonier, A.-S., Khalanski, M., Camel, V. and Bermond, A., 1999b, Determination of dihaloacetonitriles and halophenols in chlorinated sea water. *Talanta* 50(1), 227-236.
- Bennett, A., 2013, 50th Anniversary: Desalination: 50 years of progress. *Filtration + Separation* 50(3), 32-39.
- Boehm, A.B., Yamahara, K.M., Love, D.C., Peterson, B.M., McNeill, K. and Nelson, K.L., 2009, Covariation and photoinactivation of traditional and novel indicator organisms and human viruses at a sewage-impacted marine beach. *Environ. Sci. Technol.* 43(21), 8046-8052.
- Boudjellaba, D., Dron, J., Revenko, G., Demelas, C. and Boudenne, J.L., 2016, Chlorination by-product concentration levels in seawater and fish of an industrialised bay (Gulf of Fos, France) exposed to multiple chlorinated effluents. *Science of the Total Environment* 541, 391-399.
- BWMC, 2004, International Convention for the Control and Management of Ships' Ballast Water and Sediments, IMO Document BWM/CONF/36, 16 February 2004.
- Carpenter, L.J. and Liss, P.S., 2000, On temperate sources of bromoform and other reactive organic bromine gases. *Journal of Geophysical Research: Atmospheres* 105(D16), 20539-20547.
- Chen, B., Zhang, T., Bond, T. and Gan, Y., 2015, Development of quantitative structure activity relationship (QSAR) model for disinfection byproduct (DBP) research: A review of methods and resources. *J. Hazard. Mater.* 299, 260-279.
- Collivignarelli, M.C., Abba, A., Alloisio, G., Gozio, E. and Benigna, I., 2017, Disinfection in Wastewater Treatment Plants: Evaluation of Effectiveness and Acute Toxicity Effects. *Sustainability-Basel* 9(10), 1704.
- David, M., 2015, Vessels and Ballast Water, in: *Global Maritime Transport and Ballast Water Management - Issues and Solutions*. David, M. and Gollasch, S. (eds), p. 13, Springer.
- David, M. and Gollasch, S., 2015, *Global Maritime Transport and Ballast Water Management - Issues and Solutions*, Springer.
- David, M., Linders, J., Gollasch, S. and David, J., 2018, Is the aquatic environment sufficiently protected from chemicals discharged with treated ballast water from vessels worldwide? - A decadal environmental perspective and risk assessment. *Chemosphere* 207, 590-600.
- Ding, G., Zhang, X., Yang, M. and Pan, Y., 2013, Formation of new brominated disinfection byproducts during chlorination of saline sewage effluents. *Water Res.* 47(8), 2710-2718.
- Dock, A., Linders, J., David, M., Gollasch, S. and David, J., 2019, Is human health sufficiently protected from chemicals discharged with treated ballast water from vessels worldwide? - A decadal perspective and risk assessment. *Chemosphere* 235, 194-204.
- Fabbricino, M. and Korshin, G.V., 2005, Formation of disinfection by-products and applicability of differential absorbance spectroscopy to monitor halogenation in chlorinated coastal and deep ocean seawater. *Desalination* 176(1-3), 57-69.
- Feng, H., Ruan, Y., Wu, R., Zhang, H. and Lam, P.K.S., 2019, Occurrence of disinfection by-products in sewage treatment plants and the marine environment in Hong Kong. *Ecotoxicol. Environ. Saf.* 181, 404-411.
- Fogelqvist, E., Josefsson, B. and Roos, C., 1982, Halocarbons as tracer substances in studies of the distribution patterns of chlorinated waters in coastal areas. *Environ. Sci. Technol.* 16(8), 479-482.
- GESAMP, 2019, Methodology for the evaluation of ballast water management systems using Active Substances.
- GESAMP, in preparation, Reports & Studies No. 108, Relevance of inputs of disinfection by-products into the marine environment. Grote, M. and Höfer, T. (eds), International Maritime Organization, London.
- Gollasch, S., 2006, Overview on introduced aquatic species in European navigational and adjacent waters. *Helgol. Mar. Res.* 60(2), 84-89.
- Gong, T. and Zhang, X., 2015, Detection, identification and formation of new iodinated disinfection byproducts in chlorinated saline wastewater effluents. *Water Res.* 68, 77-86.
- Gong, T., Zhang, X., Li, Y. and Xian, Q., 2016, Formation and toxicity of halogenated disinfection byproducts resulting from linear alkylbenzene sulfonates. *Chemosphere* 149, 70-75.
- Gribble, G.W., 2010, *Naturally Occurring Organohalogen Compounds - A Comprehensive Update*, Springer, Wien New York.

- Gude, V.G., 2016, Desalination and sustainability - An appraisal and current perspective. *Water Res.* 89, 87-106.
- Han, J. and Zhang, X., 2018, Evaluating the Comparative Toxicity of DBP Mixtures from Different Disinfection Scenarios: A New Approach by Combining Freeze-Drying or Rotoevaporation with a Marine Polychaete Bioassay. *Environmental Science and Technology* 52(18), 10552-10561.
- Hanasaki, N., Yoshikawa, S., Kakinuma, K. and Kanae, S., 2016, A seawater desalination scheme for global hydrological models. *Hydrology and Earth System Sciences* 20(10), 4143-4157.
- Hartmann, P., Bordet, F., Chevalier, C., Colin, J.-L. and Khalanski, M., 2011, Centrales nucléaires et environnement - Prélèvements d'eau et rejets, *EDP SCIENCES*.
- Heeb, M.B., Criquet, J., Zimmermann-Steffens, S.G. and von Gunten, U., 2014, Oxidative treatment of bromide-containing waters: Formation of bromine and its reactions with inorganic and organic compounds — A critical review. *Water Res.* 48, 15-42.
- Hepach, H., Quack, B., Raimund, S., Fischer, T., Atlas, E.L. and Bracher, A., 2015, Halocarbon emissions and sources in the equatorial Atlantic Cold Tongue. *Biogeosciences* 12(21), 6369-6387.
- HK WSD, 2018, Total Water Management Strategies. Retrieved from <https://www.wsd.gov.hk/en/core-businesses/total-water-management-strategy/seawater-for-flushing/index.html>.
- Hua, G. and Reckhow, D.A., 2006, Determination of TOCl, TOBr and TOI in drinking water by pyrolysis and off-line ion chromatography. *Analytical and Bioanalytical Chemistry* 384(2), 495-504.
- IEA, 2018, Key World Energy Statistics, International Energy Agency.
- Jacangelo, J.G. and Trussell, R.R., 2002, International report: Water and wastewater disinfection - Trends, issues and practices. *Water Science and Technology: Water Supply* 2(3), 147-157.
- Jenner, H.A., Taylor, C.J.L., van Donk, M. and Khalanski, M., 1997, Chlorination by-products in chlorinated cooling water of some European coastal power stations. *Marine Environmental Research* 43(4), 279-293.
- Jones, E., Qadir, M., van Vliet, M.T.H., Smakhtin, V. and Kang, S.-m., 2019, The state of desalination and brine production: A global outlook. *Science of The Total Environment* 657, 1343-1356.
- Jung, Y., Hong, E., Yoon, Y., Kwon, M. and Kang, J.-W., 2014, Formation of Bromate and Chlorate during Ozonation and Electrolysis in Seawater for Ballast Water Treatment. *Ozone: Science & Engineering* 36(6), 515-525.
- Khalanski, M., 2003, Organic products generated by the chlorination of cooling water at marine power stations. *Journées d'Etudes du Cebedeau: Tribune de l'Eau* 619-621, 24-39.
- Khalanski, M. and Jenner, H.A., 2012, Chlorination Chemistry and Ecotoxicology of the Marine Cooling Water Systems, in: *Operational and Environmental Consequences of Large Industrial Cooling Water Systems*. Rajagopal, S., Jenner, H.A. and Venugopalan, V.P. (eds), pp. 183-226, Springer, New York.
- Kim, D., Amy, G.L. and Karanfil, T., 2015, Disinfection by-product formation during seawater desalination: A review. *Water Res.* 81, 343-355.
- Krasner, S.W., 2009, The formation and control of emerging disinfection by-products of health concern. *Philosophical Transactions of the Royal Society a-Mathematical Physical and Engineering Sciences* 367(1904), 4077-4095.
- Krasner, S.W., Weinberg, H.S., Richardson, S.D., Pastor, S.J., Chinn, R., Scrimanti, M.J., Onstad, G.D. and Thruston, A.D., Jr., 2006, Occurrence of a new generation of disinfection byproducts. *Environ. Sci. Technol.* 40(23), 7175-7185.
- Krasner, S.W., Westerhoff, P., Chen, B., Rittmann, B.E. and Amy, G., 2009, Occurrence of disinfection byproducts in United States wastewater treatment plant effluents. *Environ. Sci. Technol.* 43(21), 8320-8325.
- Kristiana, I., Gallard, H., Joll, C. and Croué, J.-P., 2009, The formation of halogen-specific TOX from chlorination and chloramination of natural organic matter isolates. *Water Res.* 43(17), 4177-4186.
- Langsa, M., Heitz, A., Joll, C.A., von Gunten, U. and Allard, S., 2017, Mechanistic Aspects of the Formation of Adsorbable Organic Bromine during Chlorination of Bromide-containing Synthetic Waters. *Environ. Sci. Technol.* 51(9), 5146-5155.
- Le Roux, J., Nada, N., Khan, M.T. and Croué, J.-P., 2015, Tracing disinfection byproducts in full-scale desalination plants. *Desalination* 359, 141-148.
- Li, X.-F. and Mitch, W.A., 2018, Drinking Water Disinfection Byproducts (DBPs) and Human Health Effects: Multidisciplinary Challenges and Opportunities. *Environ. Sci. Technol.* 52(4), 1681-1689.
- Liu, C., von Gunten, U. and Croué, J.-P., 2012, Enhanced Bromate Formation during Chlorination of Bromide-Containing Waters in the Presence of CuO: Catalytic Disproportionation of Hypobromous Acid. *Environ. Sci. Technol.* 46(20), 11054-11061.



- Liu, X., Dai, J., Wu, D., Jiang, F., Chen, G., Chui, H.-K. and van Loosdrecht, M.C.M., 2016, Sustainable Application of a Novel Water Cycle Using Seawater for Toilet Flushing. *Engineering* 2(4), 460-469.
- Maas, J., Jia, Y., Quack, B., Durgadoo, J.V., Biastoch, A. and Tegtmeier, S., 2021, Simulations of anthropogenic bromoform indicate high emissions at the coast of East Asia. *Atmospheric Chemistry and Physics* 21(5), 4103-4121.
- Maas, J., Tegtmeier, S., Quack, B., Biastoch, A., Durgadoo, J.V., Rühls, S., Gollasch, S. and David, M., 2019, Simulating the spread of disinfection by-products and anthropogenic bromoform emissions from ballast water discharge in Southeast Asia. *Ocean Sci.* 15(4), 891-904.
- Manasfi, T., Lebaron, K., Verlande, M., Dron, J., Demelas, C., Vassalo, L., Revenko, G., Quivet, E. and Boudenne, J.-L., 2019, Occurrence and speciation of chlorination byproducts in marine waters and sediments of a semi-enclosed bay exposed to industrial chlorinated effluents. *Int. J. Hyg. Environ. Health* 222(1), 1-8.
- Mansilha, C.R., Coelho, C.A., Heitor, A.M., Amado, J., Martins, J.P. and Gameiro, P., 2009, Bathing waters: New directive, new standards, new quality approach. *Mar. Pollut. Bull.* 58(10), 1562-1565.
- Mirti, A.V. and Davies, S., 2005, Drinking Water Quality in the Pacific Island Countries: Situation Analysis and Needs Assessment, Applied Geoscience and Technology Division, Secretariat of the Pacific Community: Suva, Fiji Islands.
- Ng, T.L., 2015, Cost comparison of seawater for toilet flushing and wastewater recycling. *Water Policy* 17(1), 83-97.
- Padhi, R.K., Subramanian, S., Mohanty, A.K., Bramha, N., Prasad, M.V.R. and Satpathy, K.K., 2012, Trihalomethanes in the Cooling Discharge of a Power Plant on Chlorination of Intake Seawater. *Environmental Engineering Research* 17(S1), S57-S62.
- Pan, Y. and Zhang, X., 2013, Four Groups of New Aromatic Halogenated Disinfection Byproducts: Effect of Bromide Concentration on Their Formation and Speciation in Chlorinated Drinking Water. *Environ. Sci. Technol.* 47(3), 1265-1273.
- Penkett, S.A., Jones, B.M.R., Rycroft, M.J. and Simmons, D.A., 1985, An interhemispheric comparison of the concentrations of bromine compounds in the atmosphere. *Nature* 318(6046), 550-553.
- Polman, H.J.G., 2018, DBP study in the outlet area of a power station situated in Rotterdam harbor 2016-2017. Memorandum by H2O Biofouling Solutions B.V., H2O BFS.
- Qiang, Z., Zhang, H., Dong, H., Adams, C., Luan, G. and Wang, L., 2015, Formation of disinfection byproducts in a recirculating mariculture system: emerging concerns. *Environ Sci Process Impacts* 17(2), 471-477.
- Quack, B. and Wallace, D.W.R., 2003, Air-sea flux of bromoform: Controls, rates, and implications. *Global Biogeochemical Cycles* 17(1).
- Quivet, E., Höhener, P., Temime-Roussel, B., Dron, J., revenko, G., Verlande, M., Lebaron, K., Demelas, C., Vassalo, L., and Boudenne, J.L., 2022, Underestimation of anthropogenic bromoform released into the environment? *Environ. Sci. Technol.* 56(3), 1522-1533.
- Rajagopal, S., 2012, Chlorination and Biofouling Control in Industrial Cooling Water Systems, in: Operational and Environmental Consequences of Large Industrial Cooling Water Systems. Rajagopal, S., Jenner, H.A. and Venugopalan, V.P. (eds), pp. 163-182, Springer, New York.
- Richardson, S.D. and Ternes, T.A., 2018, Water Analysis: Emerging Contaminants and Current Issues. *Analytical chemistry* 90(1), 398-428.
- Richardson, S.D., Thruston Jr., A.D., Caughtran, T.V., Chen, P.H., Collette, T.W., Floyd, T.L., Schenck, K.M., Lykins Jr., B.W., Sun, G.-R. and Majetich, G., 1999, Identification of new drinking water disinfection byproducts formed in the presence of bromide. *Environ. Sci. Technol.* 33, 3378-3383.
- Rook, J.J., 1974, Formation of haloforms during chlorination of natural waters. *Water Treatment and Examination* 23, 234-243.
- Rook, J.J., Gras, A.A., van der Heijden, B.G. and de Wee, J., 1978, Bromide oxidation and organic substitution in water treatment. *Journal of Environmental Science and Health, Part A* 13, 91-115.
- Ruiz, G.M., Fofonoff, P.W., Carlton, J.T., Wonham, M.J. and Hines, A.H., 2000, Invasion of Coastal Marine Communities in North America: Apparent Patterns, Processes, and Biases. *Annu. Rev. Ecol. Syst.* 31(1), 481-531.
- Saiz-Lopez, A. and von Glasow, R., 2012, Reactive halogen chemistry in the troposphere. *Chem Soc Rev* 41(19), 6448-6472.
- Sedlak, D.L. and von Gunten, U., 2011, Chemistry. The chlorine dilemma. *Science* 331(6013), 42-43.
- Sgroi, M., Vagliasindi, F.G.A., Snyder, S.A. and Roccaro, P., 2018, N-Nitrosodimethylamine (NDMA) and its precursors in water and wastewater: A review on formation and removal. *Chemosphere* 191, 685-703.

- Shah, A.D., Liu, Z.-Q., Salhi, E., Hofer, T., Werschkun, B. and von Gunten, U., 2015a, Formation of disinfection by-products during ballast water treatment with ozone, chlorine, and peracetic acid: influence of water quality parameters. *Environmental Science: Water Research & Technology* 1(4), 465-480.
- Shah, A.D., Liu, Z.Q., Salhi, E., Hofer, T. and von Gunten, U., 2015b, Peracetic acid oxidation of saline waters in the absence and presence of H<sub>2</sub>O<sub>2</sub>: secondary oxidant and disinfection byproduct formation. *Environ. Sci. Technol.* 49(3), 1698-1705.
- Sim, W.J., Lee, S.H., Lee, I.S., Choi, S.D. and Oh, J.E., 2009, Distribution and formation of chlorophenols and bromophenols in marine and riverine environments. *Chemosphere* 77(4), 552-558.
- Sun, Y.X., Wu, Q.Y., Hu, H.Y. and Tian, J., 2009, Effect of bromide on the formation of disinfection by-products during wastewater chlorination. *Water Res.* 43(9), 2391-2398.
- Tang, S.L., Yue, D.P.T. and Ku, D.C.C., 2007, *Engineering and Costs of Dual Water Supply Systems*, IWA Publishing.
- Taylor, C.J., 2006, The effects of biological fouling control at coastal and estuarine power stations. *Mar. Pollut. Bull.* 53(1-4), 30-48.
- Tegtmeier, S., Atlas, E., Quack, B., Ziska, F. and Krüger, K., 2020, Variability and past long-term changes of brominated very short-lived substances at the tropical tropopause. *Atmospheric Chemistry and Physics* 20(11), 7103-7123.
- von Gunten, U., 2018, Oxidation Processes in Water Treatment: Are We on Track? *Environ. Sci. Technol.* 52(9), 5062-5075.
- von Sonntag, C. and von Gunten, U., 2012, *Chemistry of ozone in water and wastewater treatment. From basic principles to applications*, IWA, London.
- Wang, S., Kinnison, D., Montzka, S.A., Apel, E.C., Hornbrook, R.S., Hills, A.J., Blake, D.R., Barletta, B., Meinardi, S., Sweeney, C., Moore, F., Long, M., Saiz-Lopez, A., Fernandez, R.P., Tilmes, S., Emmons, L.K. and Lamarque, J.F., 2019, Ocean Biogeochemistry Control on the Marine Emissions of Brominated Very Short-Lived Ozone-Depleting Substances: A Machine-Learning Approach. *Journal of Geophysical Research: Atmospheres* 124(22), 12319-12339.
- Werschkun, B., Sommer, Y. and Banerji, S., 2012, Disinfection by-products in ballast water treatment: An evaluation of regulatory data. *Water Research* 46(16), 4884-4901.
- WHO, 2011, *Guide to Ship Sanitation*, 3rd Edition, WHO Press, Geneva, Switzerland.
- WHO, 2017, *Guidelines for Drinking Water Quality*, Fourth Edition., World Health Organization, Geneva.
- WMO, 2018, *Scientific assessment of ozone depletion: 2018, global ozone Research and monitoring project – Report No. 58*, Geneva.
- Yang, J.S., 2001, Bromoform in the effluents of a nuclear power plant: a potential tracer of coastal water masses. *Hydrobiologia* 464(1/3), 99-105.
- Yang, L., Chang, W.S. and Lo Huang, M.N., 2000, Natural disinfection of wastewater in marine outfall fields. *Water Res.* 34(3), 743-750.
- Yang, X., Shang, C. and Huang, J.C., 2005, DBP formation in breakpoint chlorination of wastewater. *Water Res.* 39(19), 4755-4767.
- Yokouchi, Y., Hasebe, F., Fujiwara, M., Takashima, H., Shiotani, M., Nishi, N., Kanaya, Y., Hashimoto, S., Fraser, P., Toom-Saunty, D., Mukai, H. and Nojiri, Y., 2005, Correlations and emission ratios among bromoform, dibromochloromethane, and dibromomethane in the atmosphere. *Journal of Geophysical Research* 110(D23).

**Supporting information:**

**Estimate on annual discharge of cooling water from coastal thermal power stations**

In 2016, approximately 25,000 TWh of electricity were produced worldwide (IEA 2018) with the annual global thermal electricity production relying on cooling systems for heat dissipation amounts to 18,900 TWh (16,300 TWh by fossil fuel, 2 600 TWh by nuclear power). Maas et al. (2020) identified that one fourth of the power plant capacities are located at the coast. Assuming an equal distribution between fossil fuel and nuclear power production between coastal and inland production and an average heating of water ( $\Delta T$ ) by 12.5°C, an annual discharge of  $4.7 \times 10^{11} \text{ m}^3$  is estimated (Table S1).

**Table S1: Overview on global cooling water use in electricity production**

	Production [TWh]		Estimated discharge of cooling water in the sea at different water heating temperatures ( $\text{m}^3$ )		
	Global	Coastal power plants	$\Delta T = 10 \text{ }^\circ\text{C}$	$\Delta T = 12,5 \text{ }^\circ\text{C}$	$\Delta T = 15^\circ\text{C}$
Fossil Fuel	16,300	4 080	$4.51 \times 10^{11}$	$3.76 \times 10^{11}$	$3.01 \times 10^{11}$
Nuclear	2 600	650	$1.18 \times 10^{11}$	$9.47 \times 10^{10}$	$7.82 \times 10^{10}$
Total	18,900	4 730	$5.69 \times 10^{11}$	$4.70 \times 10^{11}$	$3.79 \times 10^{11}$