

The 3D Slicer RVXLiverSegmentation plug-in for interactive liver anatomy reconstruction from medical images

Jonas Lamy, Thibault Pelletier, Guillaume Lienemann, Benoît Magnin, Bertrand Kerautret, Nicolas Passat, Julien Finet, Antoine Vacavant

▶ To cite this version:

Jonas Lamy, Thibault Pelletier, Guillaume Lienemann, Benoît Magnin, Bertrand Kerautret, et al.. The 3D Slicer RVXLiverSegmentation plug-in for interactive liver anatomy reconstruction from medical images. Journal of Open Source Software, 2022, 7 (73), pp.3920. 10.21105/joss.03920. hal-03649993

HAL Id: hal-03649993 https://hal.science/hal-03649993v1

Submitted on 3 May 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License



- The 3D Slicer RVXLiverSegmentation plug-in for
- interactive liver anatomy reconstruction from medical
- images
- ⁴ Jonas Lamy^{*1}, Thibault Pelletier^{†2}, Guillaume Lienemann^{‡3}, Benoît
- ⁵ Magnin³, Bertrand Kerautret¹, Nicolas Passat⁴, Julien Finet², and

6 Antoine Vacavant³¶

- 1 Université Lyon 2, LIRIS (UMR 5205) Lyon, France 2 Kitware SAS, Villeurbanne, France 3
- Université Clermont Auvergne, CNRS, SIGMA Clermont, Institut Pascal, F-63000, Clermont-Ferrand,
- $_{9}$ France 4 Université de Reims Champagne Ardenne, CReSTIC, EA 3804, 51100 Reims, France \P

O Corresponding author

DOI: 10.xxxxx/draft

Software

- Review C^{*}
- Repository 🗗
- Archive C

Editor: Kevin M. Moerman C Reviewers:

- @lassoan
- @deepakri201

Submitted: 05 October 2021 Published: unpublished

License

Authors of papers retain copyright and release the work 23 under a Creative Commons Attribution 4.0 International License (CC BY 4.0). 25

¹¹ Summary

12

13

15

16

17

18

19

20

21

22

RVXLiverSegmentation is a 3D Slicer (Kikinis et al., 2014, 2022) plug-in aiming at speedingup the annotation of liver anatomy from medical images (CT -Computerized Tomographyscans or MRI -Magnetic Resonance Imaging- for instance). This organ has particular anatomy and physiology; within its parenchymal volume, the liver receives blood from the portal vein and hepatic artery (the former one being the most visible in medical images), and delivers filtered blood through the hepatic veins, toward inferior vena cava. The blood vessels subdivide into the liver as fine vascular tree structures, which makes the segmentation difficult, especially in the case of MRI. To facilitate this task, our plug-in is decomposed into modules dedicated to the segmentation of the liver volume, inner vessels and possible tumors. RVXLiverSegmentation can be downloaded from (Pelletier et al., 2022) or installed from the 3D Slicer software as an official module.

Statement of need

Annotation plays a key role in clinical practice and in the creation of reference datasets that 24 are useful to evaluate medical image processing algorithms and to train machine learning 25 based architectures (Park et al., 2020). Since softwares embedded into acquisition machines 26 are not always accurate for this task, researchers and engineers have developed more and 27 more interactive annotation and segmentation tools (Wang et al., 2021). But, despite these 28 developments, annotated datasets are still missing for many clinical applications. The creation 20 of the RVXLiverSegmentation plug-in has been motivated by the dramatic absence of a public 30 dataset providing hepatic MRI data together with their ground-truth segmentations of liver 31 anatomy. By creating our own dataset, we have developed a plug-in specifically dedicated to 32 this task, that can be used publicly by any user for the construction of new datasets related to 33 liver pathologies. Moreover, our plug-in has numerous clinical applications, such as the hepatic 34 volumetry, which is becoming increasingly important in view of the growing number of chronic 35 hepatopathies requiring transplants or hepatectomies (Lim et al., 2014). 36

^{*}co-first author [†]co-first author [‡]co-first author



³⁷ Overview of RVXLiverSegmentation

- ³⁸ For research purpose needing annotation of liver anatomy from medical images, the RVXLiver
- ³⁹ Segmentation provides 7 main tabs:
 - loading and managing medical imaging data;
- liver segmentation;

40

42

43

46

59

60

- annotation of portal veins and segmentation;
- editing portal veins segmentation;
- annotation of inferior vena cava and segmentation;
- editing inferior vena cava segmentation;
 - tumor segmentation.

Once the medical image data is loaded into the 3D Slicer interface, the liver can be segmented 47 with the associated tab, either by using interactive tools (such as region growing approaches) 48 or by an automatic deep learning based algorithm (for CT scans only), as exposed in Figure 1. 49 Then, the reconstructions of hepatic vessels (portal vein and inferior vena cava) are based on 50 tree structures interactively built by the user, who places the nodes of important branches and 51 bifurcations (with specific anatomical nomenclature) into the scene of the medical image to 52 be processed. After this step, a VMTK (Vascular Modeling Tool Kit) (Antiga et al., 2008) 53 module segments the vessels by using those graphs as initialization patterns (see Figure 2); 54

- also, the user can verify and edit this segmentation. The last tab allows the user to segment
- ⁵⁶ interactively possible tumoral tissues with dedicated tools.
- 57 This tab also permits to export the complete scene, comprising:
- segmentation label maps (liver, inferior vena cava, portal vein, tumors);
 - portal vein and inferior vena cava intersection positions (fiducial CSV and adjacency matrix);
- the complete scene as a MRB file.



Figure 1: Liver segmentation tab.





Figure 2: Tab for portal vein annotation and segmentation.

⁶² Preliminary results obtained with the plug-in

- A first version of the RVXLiverSegmentation has been employed for segmenting livers from
- ⁶⁴ dynamic-contrast enhanced MRI data in order to test and evaluate a combined registration-
- ⁶⁵ segmentation algorithm, described in (Debroux et al., 2020). We have also compared the time
- $_{\rm 66}$ $\,$ of segmentations obtained by RVXLiverSegmentation and by the embedded image processing
- ⁶⁷ tool General Electric AW solution (Server 3.2). Our first results (Lamy et al., 2020) have
- ⁶⁸ shown a significant speed-up in the segmentation of liver volume and inner vessels. The ⁶⁹ following averaged times were measured with a first cohort of 6 "healthy" patients (*i.e.* not
- ⁶⁹ following averaged times were measured with a first cohort of 6 "healthy" patients (*i.e.* ⁷⁰ suffering from any hepatic disease) and 4 patients with liver cancer and cirrhosis.
- ¹ suffering non-any hepatic disease/ and 4 patients with liver cancer and ent

Healthy patients	RVXLiverSegmentation	General Electric AW
Liver	3 ± 2 mins	10 ± 5 mins
Vessels	5 ± 3 mins	30 ± 10 mins

Cirrhotic patients	RVXLiverSegmentation	General Electric AW
Liver Vessels	4 ± 2 mins 7 ± 4 mins	15 ± 10 mins 35 ± 15 mins

71 Future works

We first would like to integrate advanced deep learning models for liver and hepatic vessels 72 segmentation (Affane et al., 2021) into our RVXLiverSegmentation plug-in, in order to provide 73 automatic reconstructions that can be then edited by the user with the other tools proposed in 74 the plug-in and in 3D Slicer. Another important work concerns the VMTK module, which 75 needs more adaptations for MRI processing. As an example, the Frangi filter is employed as 76 a pre-processing step (as a vascular enhancement algorithm), while other approaches could 77 be opted instead (Lamy et al., 2021). Finally, a more complete evaluation protocol will be 78 conducted with our plug-in, compared to commercial solutions, by taking into account larger 79

⁸⁰ patient cohorts.



Acknowledgements

- ⁸² This work was funded by the French Agence Nationale de la Recherche (grant ANR-18-CE45-
- 83 0018, project R-Vessel-X, http://tgi.ip.uca.fr/r-vessel-x).

References

97

- Affane, A., Kucharski, A., Chapuis, P., Freydier, S., Lebre, M.-A., Vacavant, A., & Fabijańska,
 A. (2021). Segmentation of liver anatomy by combining 3-D U-Net approaches. *MDPI*
- ⁸⁷ Journal of Applied Sciences, 11(11:4895). https://doi.org/10.3390/app11114895

Antiga, L., Piccinelli, M., Botti, L., Ene-Iordache, B., Remuzzi, A., & Steinman, D. A. (2008). An image-based modeling framework for patient-specific computational hemodynamics.

⁹⁰ *MBEC*, 46, 1097–1112. https://doi.org/10.1007/s11517-008-0420-1

- ⁹¹ Debroux, N., Lienemann, G., Magnin, B., Guyader, C. L., & Vacavant, A. (2020). A
- ⁹² time-dependent joint segmentation and registration model: Applications to longitudinal
- registration of hepatic DCE-MRI sequences. *IEEE IPTA 2020.* https://doi.org/10.1109/
 ipta50016.2020.9286658
- ⁹⁵ Kikinis, R., Pieper, S. D., & Fillion-Robin, J. P. (2022). *3D Slicer*. https://www.slicer.org
- ⁹⁶ Kikinis, R., Pieper, S. D., & Vosburgh, K. (2014). 3D Slicer: A platform for subject-specific
 - image analysis, visualization, and clinical support. In F. A. Jolesz (Ed.), Intraoperative
- Imaging Image-Guided Therapy (Vol. 3(19), pp. 277–289). https://doi.org/10.1007/ 978-1-4614-7657-3_19
- Lamy, J., Merveille, O., Kerautret, B., Passat, N., & Vacavant, A. (2021). Vesselness filters: A survey with benchmarks applied to liver imaging. *IEEE ICPR 2020*. https: //doi.org/10.1109/icpr48806.2021.9412362
- Lamy, J., Pelletier, T., Lienemann, G., Magnin, B., Kerautret, B., Passat, N., Finet, J., &
 Vacavant, A. (2020). Preliminary results with a new annotation tool for liver volume and
 inner vessels from DCE-MRI data. VPH 2020.
- Lim, M. C., Tan, C. H., Cai, J., Zheng, J., & Kow, A. W. (2014). CT volumetry of the liver: Where does it stand in clinical practice? *Clinical Radiology*, 69(9), 887–895.
 https://doi.org/10.1016/j.crad.2013.12.021

Park, S., Chu, L. C., Fishman, E. K., Yuille, A. L., Vogelstein, B., Kinzler, K. W., Horton, K.
 M., Hruban, R. H., Zinreich, E. S., Fouladi, D. F., Shayesteh, S., Graves, J., & Kawamoto,
 S. (2020). Annotated normal CT data of the abdomen for deep learning: Challenges and strategies for implementation. *Diagnostic and Interventional Imaging*, *101*(1), 35–44.
 https://doi.org/10.1016/j.diii.2019.05.008

- Pelletier, T., Finet, J., & Vacavant, A. (2022). RVesselX slicer liver anatomy an notation plugin. In *GitHub repository*. GitHub. https://github.com/R-Vessel-X/
 SlicerRVXLiverSegmentation
- Wang, S., Li, C., Wang, R., Liu, Z., Wang, M., Tan, H., Wu, Y., Liu, X., Sun, H., Yang, R.,
 Liu, X., Chen, J., Zhou, H., Ben Ayed, I., & Zheng, H. (2021). Annotation-efficient deep
 learning for automatic medical image segmentation. *Nature Communications*, *12*(5915).
- 120 https://doi.org/10.1038/s41467-021-26216-9