



**HAL**  
open science

## Retrieving river discharge from SWOT-like data time-series

Pierre-André Garambois, Hélène Roux, Jérôme Monnier

► **To cite this version:**

Pierre-André Garambois, Hélène Roux, Jérôme Monnier. Retrieving river discharge from SWOT-like data time-series: a sample of rivers types. European Geosciences Union (EGU) General Assembly, 2015, Apr 2015, Vienna, Austria. pp.1. hal-03662167

**HAL Id: hal-03662167**

**<https://hal.science/hal-03662167>**

Submitted on 9 May 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



## Retrieving river discharge from SWOT-like data time-series : a sample of rivers types

Pierre-André Garambois (1), H  l  ne Roux (2), and J  r  me Monnier (3)

(1) INSA, Strasbourg, France, (2) IMFT, Toulouse, France, (3) INSA, Toulouse, France

The future Surface Water and Ocean Topography (SWOT) mission would provide new cartographic measurements of ocean surface and inland water surfaces dynamics, and especially river height, width and slope. The highlight of SWOT will be its almost global coverage and temporal revisits on the order of 1 to 4 times per 22 - days repeat cycle [1]. The estimation of hydraulic parameters from water surface observations is still an open question. Several methods have recently been proposed for retrieving river discharge from SWOT data ([2, 3, 4]). The method introduced by [2] and used in the present study is based on Manning equation. The first step consists in retrieving an equivalent bathymetry profile for a river given one in situ depth measurement and SWOT like data of the water surface, that is to say water elevation, free surface slope and width. From this equivalent bathymetry, the second step consists in solving mass and Manning equation in the least square sense. Nevertheless, for cases where no in situ measurement of water depth is available, it is still possible to solve a system formed by mass and Manning equations in the least square sense (or with other methods such as Bayesian ones, see e.g. [3]). The approach is tested with synthetic data generated from hydraulic models for several river reaches around the world (cf. [5]). We show that a good a priori knowledge of bathymetry and roughness is required for such methods. The identifiability of the roughness geometry couple is also investigated for different space time sampling and hydraulic regimes. Indeed, the knowledge of effective hydraulic representation and limitations might be a cornerstone in identifications of hydraulic or hydrologic variables through data assimilation chains.

### References

- [1] E. Rodriguez, "SWOT science requirements document," JPL document, JPL, 2012.
- [2] P. A. Garambois and J. Monnier, "Inference of river properties from remotely sensed observations of water surface," (minor revisions) *Advances in Water Resources*, 2014.
- [3] M. Durand, J. Neal, E. Rodriguez, K. M. Andreadis, L. C. Smith, and Y. Yoon, "Estimating reach-averaged discharge for the river severn from measurements of river water surface elevation and slope," *Journal of Hydrology*, vol. -, no. 0, pp. -, 2014.
- [4] C. J. Gleason, L. C. Smith, and J. Lee, "Retrieval of river discharge solely from satellite imagery and atmany-stations hydraulic geometry: Sensitivity to river form and optimization parameters," *Water Resources Research*, pp. n/a-n/a, 2014.
- [5] M. Durand, L. Smith, C. Gleason, D. Bjerklie, P.-A. Garambois, and H. Roux, "Assessing swot discharge algorithms performance across a range of river types," in *AGU fall meeting*, H51S-02, 2014.