



**HAL**  
open science

## Study of the behavior of bi-axially loaded composite laminates

Damien Busca, Marina Fazzini, Bernard Lorrain, Sébastien Mistou, Moussa Karama

► **To cite this version:**

Damien Busca, Marina Fazzini, Bernard Lorrain, Sébastien Mistou, Moussa Karama. Study of the behavior of bi-axially loaded composite laminates. 5th International Symposium on Aircraft Materials - ACMA 2014, Apr 2014, Marrakech, Morocco. pp.1-2. hal-03667151

**HAL Id: hal-03667151**

**<https://hal.science/hal-03667151v1>**

Submitted on 13 May 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



## Open Archive Toulouse Archive Ouverte (OATAO)

OATAO is an open access repository that collects the work of Toulouse researchers and makes it freely available over the web where possible.

This is an author-deposited version published in: <http://oatao.univ-toulouse.fr/>  
Eprints ID: 11860

**To cite this version:**

Busca, Damien and Fazzini, Marina and Lorrain, Bernard and Mistou, Sébastien and Karama, Moussa *Study of the behavior of bi-axially loaded composite laminates*. (2014) In: 5th International Symposium on Aircraft Materials - ACMA 2014, 23 April 2014 - 26 April 2014 (Marrakech, Morocco).

Any correspondence concerning this service should be sent to the repository administrator:  
[staff-oatao@inp-toulouse.fr](mailto:staff-oatao@inp-toulouse.fr)

## Study of the behavior of bi-axially loaded composite laminates

D. Busca<sup>1</sup>, M. Fazzini<sup>1</sup>, B. Lorrain<sup>1</sup>, S. Mistou<sup>1,2</sup>, M. Karama<sup>1</sup>

*1 : UNIVERSITE DE TOULOUSE, INP,*

Ecole Nationale d'Ingénieurs de Tarbes, Laboratoire Génie de Production, 47 avenue  
d'Azereix, BP 1629 65016 TARBES CEDEX, FRANCE

2 : Nimatech Etudes, Parc Industriel de la Haute Bigorre, 1 Avenue des victimes du 11  
juin 1944, 65200 BAGNERES DE BIGORRE, France

[damien.busca@enit.fr](mailto:damien.busca@enit.fr), [marina.fazzini@enit.fr](mailto:marina.fazzini@enit.fr), [bernard.lorrain@enit.fr](mailto:bernard.lorrain@enit.fr),  
[sebastien.mistou@nimatech.fr](mailto:sebastien.mistou@nimatech.fr), [moussa.karama@enit.fr](mailto:moussa.karama@enit.fr), [marie.laetitia.pastor@iut-tarbes.fr](mailto:marie.laetitia.pastor@iut-tarbes.fr)

**Keywords:** *Composites, bi-axial, thermography, Digital Image Correlation*

Composite materials are increasingly used in the industry. Combining light weight and high resistance, they represent a good alternative to metals for weight saving in structures, such as airplanes. The behavior of those materials is intensively studied by researchers all over the world. Since a structure is usually submitted to complex loading, the study of the bi-axial behavior of those materials is a key issue to the understanding of damage progression of in service composite structures. Very few experiments have been done on bi-axial loading. The particular shape of the specimen and the absence of standard specimen make the task complex and the study remains open.

A specific cruciform specimen has been designed to respond to some criteria to allow performing reliable testing, based on already existing geometries [1,2]. The design has been made using a finite element model. The design criteria are:

- Stresses focused in the central area of the specimen
- Fracture in the central area
- Homogeneity of stresses in the central area

The specimen is then manufactured using the liquid resin infusion process, with a specific mold and a specific strategy to match with all the requirements. The material tested is a woven balanced carbon fabric with an epoxy resin. The specimen has a reduced section in the central area.

Damage characterization of materials is a complex procedure which needs to know a lot of data to be performed correctly. Digital image correlation (DIC) is an optical full field measurement method which is increasingly used [3,4]. When strain gages allow an accurate measurement of the strains on a small surface, DIC allows the measurement of the displacements all over the surface of a specimen. The accuracy of the system used is 5  $\mu\text{m}$ . It is also possible to calculate the strains all over the surface.

Damage is also characterized by a local increase of the temperature of the material, due to energy release caused by fracture of the matrix or the fibers. These increases are detectable by infrared thermography, which is also a full field optical measuring method.

Combining those two monitoring systems, a specific monitoring setup has been designed, to get the most information during a bi-axial static tensile test. Two cameras are set on the opposite sides of the specimen to perform DIC and have access to the displacement fields on both sides of the specimen. A thermic camera is also used to get the temperature evolution on the surface of the specimen until complete fracture. Finally, a high-speed camera is used to get successive pictures during the fracture of the specimen at a rate of 3000 images per second to study accurately the fracture kinematic. The specimen is tested on a bi-axial tensile machine. The test consists in a bi-axial tension with the same load on both arms. The load is applied continuously until complete fracture of the specimen.

Finally, X-ray tomography is performed on the broken specimen to determine the fracture profile. X-ray tomography is an efficient way to perform non-destructive control by obtaining a 3 dimensional picture of the specimen, including the inside. It is then possible to detect delamination, as well as fibers and matrix cracks.

All the data obtained are correlated to attempt to identify the damage mechanisms of those materials under bi-axial loading. A finite element approach is then attempted with a progressive damage model to match with the experience.

## References

- [1] A. Escárpita, H. Elizalde, R. Ramirez, E. Ledezma. S. Pinho. (2010) Modified cruciform specimen for bi-axial testing of fibre reinforced composites. *40° congreso de investigacion y desarrollo Mexico*, 232-232
- [2] A. Smits, D. Van Hemelrijck, T. P. Philippidis, A. Cardon, (2006) Design of a cruciform specimen for biaxial testing of fiber reinforced composite laminates. *Composites science and technology*, 66, 964-975
- [3] R. Brault, T. Djilali, M. Fazzini. S. Mistou. (2010) Bi-axial fatigue analysis by stereo-correlation measurement. *EPJ Web of Conferences* 6, 16005
- [4] E. Lamkanfi, W. Van Paepegem, A. Makris. D. Van Hemelrijck. J. Degrieck. C. Ramault (2010). Strain distribution in cruciform specimens subjected to biaxial loading conditions - Part 1 - Two-dimensional versus 3-dimensional finite element model. *Polymer testing*, 29, 7-13