

Investigation of shipborne GNSS ZTD retrieval processing parameters by simulation

A. Panetier P. Bosser A. Khenchaf

Lab-STICC UMR 6285 CNRS, ENSTA Bretagne, France

CONTACT: aurelie.panetier@ensta-bretagne.org



May 23, 2022

OUTLINE

- Context and objectives
- Method
- Results
- Further investigation
- Conclusion



Context and objectives

CONTEXT

- Precise positionning at sea is a current key issue, especially for hydrography, meteorology and climate studies [Boniface et al., 2012, Bosser et al., 2021, Männel et al., 2021].
- Results from previous study [Panetier et al., 2021]: best agreement between ship-borne and ground antennas tropospheric delays with a RMS error of 3.4 mm on ZTD.
- Impact of filtering parameters as cut-off angle, random walk on ZTD and weighting function on elevation, with an increased RMS up to +94% on ZTD.

OBJECTIVES

- Process the French Oceanographic Fleet GNSS data.
- What parameter values use for the processing?
→ Testing on simulations.



Method

1 - Simulation of a ship-borne GNSS antenna **phase observable**
 [Elosegui et al., 1995, Teunissen and Montenbruck, 2017]:

$$\delta\phi_{LC, \text{iono free}} = \delta\text{clock} + \delta\text{height} \times \sin el + \frac{\delta ztd}{\sin el} + \epsilon + mp \quad (1)$$

el elevation of the satellite,

δztd troposphere variations based on latitude [Hadas et al., 2020],

ϵ measurement noise,

mp multipath effect

[King and Watson, 2010].

2 - Kalman filter estimation of parameters over 200 simulations:

- Estimates (**kinematic**): 3D position, clock, troposphere.
- Parameters:
 - **cut-off angle** (co),
 - **elevation weighting** (WG),
 - **ZTD random walk** (RW).

3 - Choice of best filter parameterization:

- compare estimates to simulation,
- mean **RMS**, **correlation** terms,
- focus on **ZTD** and **height** results.




Results

Reference simulation: **Multi-GNSS, 30s time resolution, 45° latitude.**

Best modelling: **CO 3°, WG SQRTSIN, RW 5 mm. $h^{-0.5}$.**

→ RMS errors: **δZTD 1.3mm, $\delta height$ 9.4mm, with a correlation of 45%.**



Further investigation

Reference	Test	RMS	
		Height	ZTD
→ CO 3°, WG SQRTSIN, RW 5 mm.h ^{-0.5}		9.4 mm	1.3 mm
Multi-GNSS	GPS	+61%	+46%
30s	300s	+13%	+38%
perfectly corrected PCV	no correction	+46%	+77%
	azimuthal mean correction	+4%	+8%
	false North correction	+6%	+15%
mid-latitude	Equator - 10 mm.h ^{-0.5}	+31%	+46% ¹
	Pole - 2 mm.h ^{-0.5}	+10%	-15% ²

¹+23% with 10 mm.h^{-0.5} instead of 5 mm.h^{-0.5}

²-31% with 3 mm.h^{-0.5} instead of 5 mm.h^{-0.5}



Conclusion

SUMMARY

- Simulations have been conducted to **assess the impact of filter modeling** in ship-borne GNSS processing.
- **RMS on ZTD goes from 1.3 mm to 3.6 mm** depending on the configuration used.
- Best configuration is **3° of cut-off angle, 5 mm.h^{-0.5} of random walk** on ZTD and **SQRTSIN weighting** function on elevation.

OUTLOOK

- Apply the highlighted configuration to process the French Oceanographic Fleet GNSS data since 2015.

CONTACT: aurelie.panetier@ensta-bretagne.org



Bibliographic references



Boniface, K., C., C., Chery, J., Ducrocq, V., Rocken, C., Doerflinger, E., and Collard, P. (2012). Potential of shipborne GPS atmospheric delay data for prediction of mediterranean intense weather events. *Atmospheric Science Letters*, 13:250–256.



Bosser, P., Bock, O., Flamant, C., Bony, S., and Speich, S. (2021). Integrated water vapour content retrievals from ship-borne gnss receivers during eurec⁴a. *Earth System Science Data*, 13(4):1499–1517.



Elosegui, P., Davis, J. L., Jaldehag, R. T. K., Johansson, J. M., Niell, A. E., and Shapiro, I. I. (1995). Geodesy using the Global Positionning System : The effects of signal scattering on estimates of site position. *Journal of Geophysical Research*, 100:9921–9934.



Hadas, T., Hobiger, T., and Hordyniec, P. (2020). Considering different recent advancements in GNSS on real-time zenith troposphere estimates. *GPS Solutions*, 24(99).



King, M. A. and Watson, C. S. (2010). Long gps coordinate time series: Multipath and geometry effects. *Journal of Geophysical Research: Solid Earth*, 115(B4).



Männel, B., Zus, F., Dick, G., Glaser, S., Semmling, M., Balidakis, K., Wickert, J., Maturilli, M., Dahlke, S., and Schuh, H. (2021). GNSS-based water vapor estimation and validation during the MOSAiC expedition. *Atmos. Meas. Tech.*, 14:5127–5138.



Panetier, A., Bosser, P., and Khenchaf, A. (2021). Sensitivity of ship-borne GNSS troposphere retrieval to processing parameters. Scientific Assembly of the International Association of Geodesy. Poster.



Teunissen, P. J. G. and Montenbruck, O. (2017). *Springer Handbook of Global Navigation Satellite Systems*. Springer.

