

Discrete elastic parameters for lattice model with embedded discontinuities and application in concrete fracture

Jadran Čarija, Mijo Nikolić, Eduard Marenić

▶ To cite this version:

Jadran Čarija, Mijo Nikolić, Eduard Marenić. Discrete elastic parameters for lattice model with embedded discontinuities and application in concrete fracture. The 8th European Congress on Computational Methods in Applied Sciences and Engineering, ECCOMAS Congress 2022, Jun 2022, Oslo, Norway. hal-03689512

HAL Id: hal-03689512 https://hal.science/hal-03689512v1

Submitted on 14 Jun2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

DISCRETE ELASTIC PARAMETERS FOR LATTICE MODEL WITH EMBEDDED DISCONTINUITIES AND APPLICATION IN CONCRETE FRACTURE

Jadran Čarija¹, Mijo Nikolić¹, Eduard Marenić²

 ¹ University of Split, Faculty of Civil Engineering, Architecture and Geodesy, Croatia, E-mail: jadran.carija@gradst.hr
¹ University of Split, Faculty of Civil Engineering, Architecture and Geodesy, Croatia, E-mail: mijo.nikolic@gradst.hr
² Institut Clement Ader (ICA), Université de Toulouse, CNRS-INSA-UPS-ISAE-Mines Albi, Toulouse, France
E-mail: marenic@ insatoulouse.fr

Key Words: lattice model, elastic uniformity, fracture, concrete

This work presents a lattice fracture model [1-4] with a choice of parameters that lead to correct elastic continuum response. This choice of elastic parameters is important for post peak softening behaviour of the model, where correct stiffness of the model influence fracture propagation. The procedure for the computation of geometric parameters in a lattice fracture model of this type can match the global stiffness correctly [5] and it is applicable in heterogeneous materials under quasi-static regime. Such model can represent fracture and failure mechanisms in concrete and reinforced concrete structures. We show the procedure for choosing the correct elastic parameters which is based on Voronoi domain discretization of points randomly positioned in the domain. Lattice elements are zero-size elements that can match the global stiffness, but it can also be elastically homogeneous for various Poisson coefficients. Numerical examples show the capabilities of the model for simulation of the prepeak and post-peak behaviour of fracturing in concrete.

Acknowledgements

This work has been supported through the project 'Parameter estimation framework for fracture propagation problems under extreme mechanical loads' (UIP-2020-02-6693), funded by the Croatian Science Foundation

REFERENCES

- [1] M. Nikolić, E. Karavelić, A. Ibrahimbegovic, and P. Miščević, Lattice element models and their peculiarities. *Archives of Computational Methods in Engineering*, Vol. 25, pp. 753-784, 2018.
- [2] A. Ibrahimbegovic, Nonlinear solid mechanics: theoretical formulations and finite element solution methods, Springer Science & Business Media 2009.
- [3] J. Čarija, M. Nikolić, A. Ibrahimbegovic and Ž. Nikolić, Discrete softening-damage model for fracture process representation with embedded strong discontinuities, *Engineering Fracture Mechanics*, Vol. 236, pp. 107211, 2020.
- [4] E Karavelić, M Nikolić, A Ibrahimbegovic and A Kurtović, Concrete meso-scale model with full set of 3D failure modes with random distribution of aggregate and cement phase. Part I: Formulation and numerical implementation, *Computer Methods in Applied Mechanics and Engineering*, Vol. 344, pp. 1051-1072, 2019.
- [5] J. Čarija, M. Nikolić and Ž. Nikolić, A Voronoi Based Discrete Numerical Approach for Modelling Reinforcement in Concrete Structures. *International Journal for Engineering Modelling*, Vol. 34 (2), pp. 77-98, 2021.