



HAL
open science

Comparison of Maximum Transmission Efficiency and Magnetic Flux Leakage for Different Coupling Coils in Inductive Power Transfer Systems

Yao Pei, Mohamed Bensetti, Yann Le Bihan, Lionel Pichon, Karim Kadem

► **To cite this version:**

Yao Pei, Mohamed Bensetti, Yann Le Bihan, Lionel Pichon, Karim Kadem. Comparison of Maximum Transmission Efficiency and Magnetic Flux Leakage for Different Coupling Coils in Inductive Power Transfer Systems. The 7th Conference on Inductics (University-Industry), May 2022, Constantine, Algeria. ⟨hal-03695332⟩

HAL Id: hal-03695332

<https://hal.science/hal-03695332v1>

Submitted on 14 Jun 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



HAL Authorization

Comparison of Maximum Transmission Efficiency and Magnetic Flux Leakage for Different Coupling Coils in Inductive Power Transfer Systems

Yao PEI, Mohamed BENSETTI, Yann LE BIHAN and
Lionel PICHON

*Université Paris-Saclay, CentraleSupélec, CNRS, Laboratoire
de Génie Electrique et Electronique de Paris, 91192,
Gif-sur-Yvette, France;*

*Sorbonne Université, CNRS, Laboratoire de Génie Electrique
et Electronique de Paris, 75252, Paris, France*

{yao.pei & mohamed.bensetti & yann.lebihan &
lionel.pichon}@centralesupelec.fr

Karim KADEM

*Institut VEDECOM, 23 bis Allée des Marronniers, 78000
Versailles, France*

kadem.karim@hotmail.fr

Abstract – Nowadays, inductive power transfer technology is widely considered for the charging of electric vehicles due to environmental pollution. The most important part of this system is how to design coupling coils with high efficiency and low magnetic flux leakage. The present work aims at comparing the maximum transmission efficiency and the magnetic flux leakage for different coupling coils in an inductive power transfer system. Here, four typical shaped coils (circle, square, double D and bipolar) are studied and compared in the simulation and the experimental aspect. The transmission efficiency and magnetic field distribution are relevant to different shaped coils as well as the variation of the misalignment between the coils.

Index Terms - Inductive power transfer, Maximum transmission efficiency, Electromagnetic compatibility

I. INTRODUCTION

Inductive power transfer (IPT) has recently received increasing attention for electric vehicles due to a growing concern for the air pollution produced by conventional powered cars. Nowadays, electric vehicles (EVs) are equipped with large batteries that must be efficiently and rapidly recharged. These batteries can be charged via IPT technology to increase comfort and electrical safety in the charging process. So it is necessary to consider the transfer efficiency and the magnetic field leakage for an IPT system.

In order to design an effective IPT system, some reviews summarize and discuss different structures and shapes of the coils [1]. In [2], a simulation study was carried out to explore the variation of the coupling coefficient for different air-cored coil configurations under different air gaps and coil misalignments. However, it does not study the magnetic flux leakage around the coils for electromagnetic safety. Reference [3] provided several criteria such as the maximum transfer efficiency and the magnetic flux leakage to study the effect of coil shapes, but the coils are air-cored. Reference [4] only compared coupling coefficient of differently shaped coils with ferrite plates under different misalignments. In a word, the literature does not consider the maximum transfer efficiency

and the magnetic flux leakage for different coupling coils with ferrite plate at the same time.

In this paper, the main aim is to study the maximum transmission efficiency and magnetic flux leakage for differently shaped coils with ferrite plate. Four differently shaped coils (including circular coils, square coils, bipolar (BP) coils, and double D (DD) coils) have been proposed in small scales simulations and experiments to save computational time and the cost of the coupling systems. Moreover, different coil configurations are analyzed on the maximum transmission efficiency according to the effect of the misalignment between the transmitter and the receiver, and the magnetic flux leakage near the coupling systems.

II. INDUCTIVE POWER TRANSFER SYSTEM

The block diagram of an inductive power transfer system for electric vehicles is provided in Fig.1.




Fig. 1 Block diagram of IPT systems.

The IPT system consists of several converters and resonant compensation networks for the transmitter side and the receiver side. The electrical network provides the voltage to the transmitter through the converters. The magnetic field produced by the transmitter induces an alternating field in the receiver. The AC power is then rectified at the receiver side in order to charge the battery. Compensation networks are added to the transmitter and the receiver to create the resonant case and reduce additional losses.

The specifications of an IPT system include the air gap between the transmitter and the receiver, maximum allowed size and a specific shape for the transmitter and the receiver.

Typical coil shapes for the transmitter and the receiver in IPT systems include circular, square, BP and DD. However, a realization of real-scale coils of different coupling coils consumes a lot of time and is costly, especially considering the price of the materials used (wire and ferrite). To save time and cost, the coils here are not considered in real sizes but miniaturized on a scale of 1:10 [4]. The circular coils, square coils, DD coils and BP coils with ferrite plates in small-scale sizes are shown in Fig.2. The current inside the transmitter is the same for different coupling coils. The coils are made of Litz wires with six turns distributed in 2 layers. The width of the coil is 3.6 mm and the thickness is 2.4 mm. The thickness of the ferrite is 2 mm and its relative permeability is 2500. The air gap between the transmitter and the receiver is 15 mm.




Fig. 2 Small scales of the coils.

III. ANALYSIS OF DIFFERENT COUPLING COILS

A. Electrical parameters

The equation to calculate the maximum transmission efficiency η_{\max} can be simplified as below when the product of the coupling coefficient k and the inductor quality factor Q is higher than 2, and the coils are identical for the transmitter and the receiver [5]:

$$\eta_{\max} = \frac{(kQ)^2}{(1 + \sqrt{1 + (kQ)^2})^2} \approx 1 - \frac{2}{kQ} = 1 - \frac{2\sqrt{R_1 R_2}}{w_0 M} = 1 - \frac{\rho}{\pi f_0 S M} \quad (1)$$

Where $k = \frac{M}{\sqrt{L_1 L_2}}$, l is the length of the conducting wires for

different coupling coils, S is the cross-sectional area of the conducting wires, ρ is the resistivity of the wires made of copper, the frequency f_0 is equal to 85 kHz and M is the mutual inductance between the coils.

Fig.3 shows the variation of the maximum transmission efficiency with the misalignment along the X/Y axis (defined in Fig.2) leads to the same result. When they are all in the aligned positions, the value from the circular coupling coils is the maximum among these coupling coils. With the misalignment increasing, the square coupling coils have a better tolerance compared to other coupling coils.

B. Magnetic flux leakage around the coupling coils

To evaluate the magnetic flux leakage near the coupling systems, the observation part is to be above the receiver with a ferrite plate 32 mm, as shown in Fig.4 (a). The distribution of the magnetic flux leakage is hereby reported in Fig.4 (b) when the current amplitude inside the primary coil is 0.21A and they are aligned.




Fig. 3 Impact of misalignment on maximum transmission efficiency for different coupling coils.




Fig. 4 Measurement of magnetic field distribution for different coupling coils.

IV. CONCLUSION

In this work, how to choose the shape of the coupling coils depends on a trade-off among the transmission efficiency, the tolerance to the misalignment and the magnetic flux leakage. Square coupling coils are chosen for the further study due to the tolerance to the misalignment, but for the real scale of coils, an electromagnetic shielding needs to be considered for the human safety.

REFERENCES

- [1] J.-M. Clairand, P. Guerra-Terán, X. Serrano-Guerrero, M. González-Rodríguez, and G. Escrivá-Escrivá, "Electric Vehicles for Public Transportation in Power Systems: A Review of Methodologies," *Energies*, vol. 12, no. 16, p. 3114, Aug. 2019.
- [2] Y. Yang, J. Cui, and X. Cui, "Design and Analysis of Magnetic Coils for Optimizing the Coupling Coefficient in an Electric Vehicle Wireless Power Transfer System," *Energies*, vol. 13, no. 16, pp. 1–15, 2020.
- [3] K. Knaisch and P. Gratzfeld, "Comparison of magnetic couplers for inductive electric vehicle charging using accurate numerical simulation and statistical methods," in 2015 5th International Electric Drives Production Conference (EDPC), Sep. 2015, pp. 1–10.
- [4] K. Kadem, Y. Le Bihan, M. Bensetti, É. Laboure, A. Diet, and M. Debbou, "Reduction of the shielding effect on the coupling factor of an EV WPT system," in 2019 IEEE PELS Workshop on Emerging Technologies: Wireless Power Transfer, Jun. 2019, pp. 21–24.
- [5] Y. Pei, Y. Le Bihan, M. Bensetti, and L. Pichon, "Comparison of Coupling Coils for Static Inductive Power-Transfer Systems Taking into Account Sources of Uncertainty," *Sustainability*, vol. 13, no. 11, p. 6324, Jan. 2021, doi: 10.3390/su13116324.