



**HAL**  
open science

## Model-driven deployment of Digital Twins for Smart Environments - The HUMAN at home projecT case study

Alireza Asvadi, Gaëlic Bechu, Antoine Beugnard, Caroline G. L. Cao, Christophe Lohr, Panagiotis Papadakis, Quentin Perez, Christelle Urtado, Sylvain Vauttier

### ► To cite this version:

Alireza Asvadi, Gaëlic Bechu, Antoine Beugnard, Caroline G. L. Cao, Christophe Lohr, et al.. Model-driven deployment of Digital Twins for Smart Environments - The HUMAN at home projecT case study. Journées nationales du GDR GPL 2022, Jun 2022, Vannes, France. , 13, 2022, Actes des journées du GDR GPL 2022. hal-03701748

**HAL Id: hal-03701748**

**<https://hal.science/hal-03701748>**

Submitted on 22 Jun 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Model-driven deployment of Digital Twins for Smart Environments

## The HUman at home project case study

### Motivation and Goals

HUT is a multidisciplinary project that aims at studying the impact of smart environments on well-being.

Its main equipment is an observatory apartment that collects data generated by daily life activities of voluntary occupants thanks to a large variety of sensors (e.g. temperature, hygrometry, CO2, light, presence, doors, electric and water consumptions).




The observatory apartment of HUT

**How to use these datasets for studying the integration of AI components in smart environments?**

**How to continue these experiments after the end of the HUT project?**

The concept of Digital Twin (DT), as studied for Industry 4.0, is a potential solution. DT is now more precisely defined as the combined IoT and software parts of a cyber-physical system that provides virtual real-time representations of its physical parts [1].



Conceptual definition of a DT [1]


However, more concrete and operational models are still to be designed, for instance to manage the deployment of DTs [2].

Our proposed metamodel is a first step towards a model-driven approach for DT deployment. It is derived from our previous work on ADLs [3, 4].

### Modeling the Deployment of DTs


DT deployment encompasses many dimensions:

- ▶ variable configurations, adapting architectures to environment,
- ▶ hierarchical composite architectures, mixing various types of software / hardware components / resources,
- ▶ deployment processes, defining ordered tasks for installing, executing, configuring or instantiating the architectures and their supporting environments.



Excerpt of our deployment metamodel

### Metamodel Validation



Deployment model for a BedPressure Sensor DT for the HUT case study

On the HUT case study, the validation of our metamodel is twofold:

- ▶ modeling of CPS architectures including DTs of sensors and AI,
- ▶ fully implemented and executable deployments of the modeled elements as Ansible scripts.

Another case study is also currently run for extended / cross validation, implying the DT of a Cobot for pick and place tasks.

### Future Work

- ▶ Refine and extend the metamodel with architectural and design patterns for DTs,
- ▶ Design and implement DSLs, transformations and formal semantics for full-fledged MDE,
- ▶ Study composition and evolution mechanisms to support reuse in DT deployment definitions.

### Authors

Alireza ASVADI<sup>2</sup>  
Gaëlic BECHU<sup>2</sup>  
Antoine BEUGNARD<sup>2</sup>  
Caroline CAO<sup>2</sup>  
Christophe LOHR<sup>2</sup>  
Panagiotis PAPADAKIS<sup>2</sup>  
Quentin PEREZ<sup>1</sup>  
Christelle URTADO<sup>1</sup>  
Sylvain VAUTTIER<sup>1</sup>

<sup>1</sup>EuroMov Digital Health in Motion, Univ Montpellier, IMT Mines Ales, Ales, France  
<sup>2</sup>Lab-STICC, UMR CNRS 6285, IMT Atlantique, Brest, France

### References

[1] N. Julien and E. Martin. How to characterize a Digital Twin: A Usage-Driven Classification. 17th IFAC Symposium on Information Control Problems in Manufacturing, 2021, pp.894-899.

[2] Fei Tao, Meng Zhang, and Andrew Yeh Chris Nee. Digital twin driven smart manufacturing. Academic Press, 2019.

[3] Abderrahman Mokni, Christelle Urtado, Sylvain Vauttier, Marianne Huchard, Zhang Huaxi Yulin. A formal approach for managing component-based architecture evolution. Science of Computer Programming, Elsevier, 2016, 127, pp.24-49.

[4] Paul Perrotin, Nicolas Belloir, Salah Sadou, David Hairion, Antoine Beugnard. HoS-ML: Socio-Technical System ADL Dedicated to Human Vulnerability Identification. 26th International Conference on Engineering of Complex Computer Systems, Mar 2022, Hiroshima, Japan.

### Acknowledgments

This research has been conducted as part of GT VOCA of the Human at home project (HUT), funded by FEDER and Occitanie Region. It is also part of the TwinCoBot project, funded by Carnot Mines.

