

Wake the Concept Lattice in You!

Marianne Huchard
Montpellier University, LIRMM, France



Keynote Talk

19th International Conference on Information Processing and
Management of Uncertainty in Knowledge-Based Systems
July 11-15, 2022 – Milan, Italy

Introduction

Roots

FCA toolbox

Complex data

FCA in KD

Conclusion

Agenda

Introduction

Roots

FCA toolbox

Complex data

FCA in KD

Conclusion

RESTRUCTURING LATTICE THEORY:
AN APPROACH BASED ON HIERARCHIES OF CONCEPTS


Rudolf Wille
Fachbereich Mathematik
Technische Hochschule Darmstadt
6100 Darmstadt
Federal Republic of Germany

ABSTRACT

Lattice theory today reflects the general status of current mathematics: there is a rich production of theoretical concepts, results, and developments, many of which are reached by elaborate mental gymnastics; on the other hand, the connections of the theory to its surroundings are getting weaker and weaker, with the result that the theory and even many of its parts become more isolated. Restructuring lattice theory is an attempt to reinvigorate connections with our general culture by interpreting the theory as concretely as possible, and in this way to promote better communication between lattice theorists and potential users of lattice theory.

The approach reported here goes back to the origin of the lattice concept in nineteenth-century attempts to formalize logic, where a fundamental step was the reduction of a concept to its "extent". We propose to make the reduction less abstract by retaining in some measure the "intent" of a concept. This can be done by starting with a fixed *context* which is defined as a triple $\langle G, M, I \rangle$ where G is a set of *objects*, M is a set of *attributes*, and I is a binary relation between G and M indicating by gIm that the object g has the attribute m . There is a natural Galois connection between G and M defined by $A' = \{m \in M \mid gIm \text{ for all } g \in A\}$ for $A \subseteq G$ and $B' = \{g \in G \mid gIm \text{ for all } m \in B\}$ for $B \subseteq M$. Now, a *concept* of the context $\langle G, M, I \rangle$ is introduced as a pair (A, B) with $A \subseteq G$, $B \subseteq M$, $A' = B$, and $B' = A$, where A is called the *extent* and B the *intent* of the concept (A, B) . The *hierarchy of concepts* given by the relation subconcept-superconcept is captured by the definition $(A_1, B_1) \leq (A_2, B_2) \Leftrightarrow A_1 \subseteq A_2$ ($\Leftrightarrow B_1 \supseteq B_2$) for concepts (A_1, B_1) and (A_2, B_2) of $\langle G, M, I \rangle$. Let $L(G, M, I)$ be the


445




Dissemination 1982-2022

- Conceptualization, philosophical developments
- Data analysis, data mining, clustering
- Knowledge representation (ontology construction)
- Classification, indexation (information retrieval)
- Unsupervised learning
- Supervised learning (adding classes in description)
- Tools and applications

Dissemination 1982-2022




Credits Uta Priss <https://upriss.github.io/fca/fca.html>



ICCS




ICFCA



CLA



FCA4AI




S21. FORMAL CONCEPT ANALYSIS AND UNCERTAINTY

Organizers: **Pablo Cordero**, **Domingo López-Rodríguez**, and **Ángel Mora**

Crossing FCA path

Partial orders




$CLOS(2) = LOOPS(2) = \mathcal{L}_{LOOPS}^*(2) = (2\ 3\ 6\ 7\ 8)$
 $CLOS(4) = LOOPS(4) = \mathcal{L}_{LOOPS}^*(4) = (4\ 5\ 6\ 8)$
 $CLOS(1) = LOOPS(1) = (1\ 2\ 3\ 7\ 4\ 5\ 6\ 8)$
 $\mathcal{L}_{LOOPS}^*(1) = (1\ 2\ 3\ 4\ 5\ 6\ 7\ 8)$

*Multiple inheritance
conflict resolution*

OOPSLA 1994

Concept lattices




*Class hierarchy compact
factorization*


OOPSLA 1996

An 'engineering view' on FCA

Algorithms, relational extension (RCA)




Environmental data applications



Software engineering applications

	boolean add(Object)	boolean isEmpty()	Object peek()	Object poll()	Object get(int i)
StepSeq					
PriorityQueue	x	x	x	x	
ArrayDeque	x	x	x	x	
ArrayList	x	x			x
LinkedList	x	x	x	x	x

(a) Formal Context
classes X signatures of public methods



(b) Concept lattice / AOC-poset (compact)
maximal factorization, exact specialization

Agenda

Introduction

Roots

FCA toolbox

Complex data

FCA in KD

Conclusion

Formal Concept Analysis

Formal concepts are “a natural feature of information representation which is as fundamental to hierarchies and object/attribute structures as set theory or relational algebra are for relational databases”.



Uta Priss. 40th anniv. vol. of Annual Review of Inf. Sc. and Tech., 2006

Simple but powerful **basics**

- Formal Context
- Concept Lattice
- Galois connection

Formal Context

Triple (O, A, R) , where O is a finite set of objects, A is a finite set of attributes and $R \subseteq O \times A$ is a **binary relation**.
 $(o, a) \in R$ means that **object o owns attribute a** .

	<i>flies</i>	<i>nocturnal</i>	<i>feathered</i>	<i>migratory</i>	<i>red-bill</i>	<i>elytra</i>	<i>sea-habitat</i>	<i>wood-habitat</i>	<i>six-legged</i>	<i>eats-fish</i>	<i>water-habitat</i>
ladybird	x					x			x		
bat	x	x									
ostrich			x								
greater-flamingo	x		x	x			x			x	x
silver-gull	x		x		x		x			x	x
little-tern	x		x	x			x			x	x
great-auk	x		x				x			x	x
wood-pecker	x		x					x			
giant-otter										x	x
arctic-tern	x		x	x	x		x			x	x

Characteristic maps of $R \subseteq O \times A$

Map f associates an **object set** with the **shared attributes**.

$$f : P(O) \rightarrow P(A) \quad X \mapsto f(X) = \{y \in A \mid \forall x \in X, (x, y) \in R\}$$

	flies	nocturnal	feathered	migratory	red-bill	elytra	sea-habitat	wood-habitat	six-legged	eats-fish	water-habitat
ladybird	x					x			x		
bat	x	x									
ostrich			x								
greater-flamingo	x		x	x			x			x	x
silver-gull	x		x		x		x			x	x
little-tern	x		x	x			x			x	x
great-auk	x		x				x			x	x
wood-pecker	x		x					x			
giant-otter										x	x
arctic-tern	x		x	x	x		x			x	x

In [Ganter and Wille, 1999], f is denoted by the polymorphic symbol \hat{f} . We will use both notations depending the situations

Characteristic maps of $R \subseteq O \times A$

Map g associates an attribute set with the objects sharing them

$$g : P(A) \rightarrow P(O) \quad Y \mapsto g(Y) = \{x \in O \mid \forall y \in Y, (x, y) \in R\}$$

	<i>flies</i>	<i>nocturnal</i>	<i>feathered</i>	<i>migratory</i>	<i>red-bill</i>	<i>elytra</i>	<i>sea-habitat</i>	<i>wood-habitat</i>	<i>six-legged</i>	<i>eats-fish</i>	<i>water-habitat</i>
ladybird	x					x			x		
bat	x	x									
ostrich			x								
greater-flamingo	x		x	x			x			x	x
silver-gull	x		x		x		x			x	x
little-tern	x		x	x			x			x	x
great-auk	x		x				x			x	x
wood-pecker	x		x					x			
giant-otter										x	x
arctic-tern	x		x	x	x		x			x	x

In [Ganter and Wille, 1999], g is denoted by the polymorphic symbol $'$. We will use both notations depending the situations

Formal Concept

Pair $C=(E, I)$ such that $f(E) = I$ (or equivalently $E = g(I)$)

E is the concept *extent*; I is the concept *intent*.

	<i>flies</i>	<i>nocturnal</i>	<i>feathered</i>	<i>migratory</i>	<i>red-bill</i>	<i>elytra</i>	<i>sea-habitat</i>	<i>wood-habitat</i>	<i>six-legged</i>	<i>eats-fish</i>	<i>water-habitat</i>
ladybird	×					×			×		
bat	×	×									
ostrich			×								
greater-flamingo	×		×	×			×			×	×
silver-gull	×		×		×		×			×	×
little-tern	×		×	×			×			×	×
great-auk	×		×				×			×	×
wood-pecker	×		×					×			
giant-otter										×	×
arctic-tern	×		×	×	×		×			×	×

Concept ordering

Concepts can be ordered through the following partial order \leq_s :

$(E_1, I_1) \leq_s (E_2, I_2) \Leftrightarrow E_1 \subseteq E_2$, or equivalently $I_2 \subseteq I_1$

(E_1, I_1) sub-concept of (E_2, I_2) ; (E_2, I_2) super-concept of (E_1, I_1)

$C_{\text{great-}auk}$:

$X_{10} =$

$\{\text{great-}auk, \text{silver-gull}, \text{greater-flamingo}, \text{little-}tern, \text{arctic-}tern\}$

$Y_{10} = \{\text{sea-habitat}, \text{eats-fish}, \text{water-habitat}, \text{feathered}, \text{flies}\}$

$C_{\text{silver-gull}}$:


$X_8 = \{\text{silver-gull}, \text{arctic-}tern\}$

$Y_8 = \{\text{sea-habitat}, \text{eats-fish}, \text{water-habitat}, \text{feathered}, \text{flies}, \text{red-bill}\}$


$C_{\text{silver-gull}} \leq_s C_{\text{great-}auk}$, as $X_8 \subseteq X_{10}$ (and $Y_{10} \subseteq Y_8$).

Concept lattice $\mathcal{L}_K = (\mathcal{C}_K, \leq_s)$

Set \mathcal{C}_K of all concepts of $K = (O, A, R)$, provided with \leq_s



Assembly: through a Galois connection



Generalization: Galois connection


(f, g) associated with a $R \subseteq O \times A$ is a Galois connection between $(2^O, \subseteq)$ and $(2^A, \subseteq)$

Galois connection

For posets (X, \leq_X) and (Y, \leq_Y) , and $f : X \rightarrow Y$ et $g : Y \rightarrow X$

The pair (f, g) is a Galois connection if:

$\forall x \in X$ and $\forall y \in Y$, $x \leq_X g(y) \Leftrightarrow y \leq_Y f(x)$.



poset: partially ordered set

Generalization: Galois connection

If (f, g) is a Galois connection between (X, \leq_X) and (Y, \leq_Y)
 $h_X = g \circ f$ et $h_Y = f \circ g$ are **closure operators**:

op closure operator on a poset (P, \leq_P)

- isotone: $X \leq_P Y \Rightarrow op(X) \leq_P op(Y)$
- extensive: $X \leq_P op(X)$
- idempotent: $op(op(X)) = op(X)$

X is a **closed set** iff $op(X) = X$

$X = \{\textit{great-auk}, \textit{silver-gull}\}$

$f(X) = \{\textit{sea-habitat}, \textit{eats-fish}, \textit{water-habitat}, \textit{feathered}, \textit{flies}\}$

$g(f(X)) = \{\textit{great-auk}, \textit{silver-gull}, \textit{greater-flamingo}, \textit{little-tern}, \textit{arctic-tern}\}$

$f(g(f(X))) = \{\textit{sea-habitat}, \textit{eats-fish}, \textit{water-habitat}, \textit{feathered}, \textit{flies}\}$

$g(f(g(f(X)))) = \{\textit{great-auk}, \textit{silver-gull}, \textit{greater-flamingo}, \textit{little-tern}, \textit{arctic-tern}\}$

Inspiring references




- **Concept lattices**
(Rudolf Wille, 1982, Bernhard Ganter & Rudolf Wille, 1999)
- **Lattice theory, Galois connections, Galois lattices**
(Marc Barbut & Bernard Monjardet, 1970; Georges David Birkhoff, 1940; Øystein Ore, 1944)
- **Galois connection, subgroups/subfields**
(Evariste Galois, ~ 1830)

Sum up


Any Galois connection between finite lattices (X, \leq_X) and (Y, \leq_Y) induces a Galois lattice (i.e. theory is not restricted to tabular data)

	x			
	x		x	
		x	x	
		x	x	x

Duality between: Objects/attributes ; lattices (X, \leq_X) and (Y, \leq_Y)



Genericity: Any lattice can be labelled to be a Galois lattice of some binary relation



Agenda

Introduction

Roots


FCA toolbox

Complex data

FCA in KD

Conclusion

Conceptual structures: Concept lattice




Worst case:

$$\# \text{concepts} < 2^{\min(|A|, |O|)}$$

Reached with the lattice of all subsets of E where $E = O$ if $|O| = \min(|A|, |O|)$ (otherwise, $E = A$)

Conceptual structures: AOC poset




Sub-order of
introducer concepts

Worst case
complexity: $\#concepts$
 $< |A| + |O|$

Reached when
 $|A| = |O|$ and
every attribute is
shared by several
distinct objects
(ex. bipartite
crown graph)

Conceptual structures: Iceberg



Concepts with
frequent intent
or
frequent extent

Here:
concepts with
frequent extent
($\geq 50\%$)

Implication rules $Prem \implies Conc$ of $K = (O, A, R)$

Pair $(Prem, Conc) \subseteq A \times A$ s.t. $g(Prem) \subseteq g(Conc)$

all the *objects* that own the *attributes* of Prem (premise) also own the *attributes* of Conc (conclusion)

$elytra \implies six\text{-legged}$

$feathered \wedge eats - fish \wedge water - habitat \implies flies \wedge sea - habitat$

Implication rules

Criteria for an implication set

- **Sound**: any implication of the set holds
- **Complete**: any other implication can be obtained from the set
- **Basis**: sound and complete
- **Minimal cardinality**
- **Direct**: any attribute closed set can be obtained in one iteration
- **No redundancy** between rules and inside rules

Implication rules

Diverse approaches

- Minimal non-redundant set of binary implications
- Basis of Duquennes-Guigues [Guigues, 1986] (For a systematic study, see [Bertet&Monjardet, 2010])
- Left-minimal direct basis of implications [Cordero 2013]
- Basis of proper premises [Reppe, 2008; Ryssel, 2014]
- and others ...

Duquenne-Guigues Basis of Implications (DGBI)

Cardinality minimal set of non redundant implications

$\langle 0 \rangle$ *flies, feathered, sea-habitat, wood-habitat, eats-fish, water-habitat* \Rightarrow
nocturnal, migratory, red-bill, elytra, six-legged

$\langle 0 \rangle$ *flies, feathered, elytra, six-legged* \Rightarrow *nocturnal, migratory, red-bill, sea-habitat, wood-habitat, eats-fish, water-habitat*

$\langle 0 \rangle$ *flies, nocturnal, elytra, six-legged* \Rightarrow *feathered, migratory, red-bill, sea-habitat, wood-habitat, eats-fish, water-habitat*

$\langle 0 \rangle$ *flies, nocturnal, feathered* \Rightarrow *migratory, red-bill, elytra, sea-habitat, wood-habitat, six-legged, eats-fish, water-habitat*

$\langle 1 \rangle$ *six-legged* \Rightarrow *flies, elytra*

$\langle 1 \rangle$ *wood-habitat* \Rightarrow *flies, feathered*

$\langle 1 \rangle$ *elytra* \Rightarrow *flies, six-legged*

$\langle 1 \rangle$ *nocturnal* \Rightarrow *flies*

$\langle 2 \rangle$ *red-bill* \Rightarrow *flies, feathered, sea-habitat, eats-fish, water-habitat*

$\langle 3 \rangle$ *migratory* \Rightarrow *flies, feathered, sea-habitat, eats-fish, water-habitat*

$\langle 5 \rangle$ *sea-habitat* \Rightarrow *flies, feathered, eats-fish, water-habitat*


$\langle 5 \rangle$ *feathered, eats-fish, water-habitat* \Rightarrow *flies, sea-habitat*

$\langle 5 \rangle$ *flies, eats-fish, water-habitat* \Rightarrow *feathered, sea-habitat*

$\langle 6 \rangle$ *water-habitat* \Rightarrow *eats-fish*

$\langle 6 \rangle$ *eats-fish* \Rightarrow *water-habitat*


Logical Constraints: Binary implication



Concept 5 subconcept of Concept 9

elytra \implies flies

Logical Constraints: Co-occurrence (equivalence)




elytra and six-legged both introduced in Concept 5

elytra \Leftrightarrow six-legged

eats-fish and water-habitat both introduced in Concept 8

eats-fish \Leftrightarrow water-habitat


Logical Constraints: Mutual exclusion



Intersection of C1, C2, C3 extents is empty

$$\neg(\text{red-bill} \wedge \text{migratory} \wedge \text{elytra})$$

Logical Constraints: Or




Extent of C1 is covered by extents of C2, C3, C4 and C5
(possibly non disjoint)

$$\text{Extent}(C1) = \text{Extent}(C2) \cup \text{Extent}(C3) \cup \text{Extent}(C4) \cup \text{Extent}(C5)$$

living-being \implies

urban-habitat \vee *wood-habitat* \vee *field-habitat* \vee *sea-habitat*

Logical Constraints: Xor



Extents of C2, C3 form a partition of C1 Extent



$Extent(C1) = Extent(C2) \cup Extent(C3)$ and

$Extent(C2) \cap Extent(C3) = \emptyset$

$living-being \implies warm-blooded \oplus cold-blooded$

Sum up

	flies	nocturnal	feathered	migratory	red-bill	elytra	six-legged	wood-habitat	six-legged	eats-fish	water-habitat
ladybird	x										
bat	x	x									
ostrich			x								
greater-flamingo	x		x	x			x			x	x
silver-gull	x		x		x		x			x	x
little-tern	x		x	x			x			x	x
great-awk	x		x				x			x	x
wood-pecker	x		x					x			
giant-otter										x	x
arctic-tern	x		x	x	x			x		x	x



<0> flies,feathered,sea-habitat,wood-habitat,eats-fish,water-habitat => nocturnal,migratory,red-bill,elytra,six-legged

(...)

<0> flies,nocturnal,elytra,six-legged => feathered,migratory,red-bill,sea-habitat,wood-habitat,eats-fish,water-habitat

(...)

<1> nocturnal => flies\\

(...)

<5> flies,eats-fish,water-habitat => feathered,sea-habitat\\(...)

The magic triangle

Agenda

Introduction

Roots

FCA toolbox

Complex data

FCA in KD

Conclusion

FCA for various data types

- **Multi-valued attributes** : integers, double, terms, structures, symbolic objects, etc. (Ganter et Wille, Diday, Polaillon, ...)
- **Fuzzy** (Belohlavek et al., Cabrera, Cordero, Enciso, Mora, Lòpez-Ròdriguez, Ojeda-Aciego et al., Cornejo, Medina et al., Yahia et al., Dubois, Prade ...)
- **Value taxonomies** (Godin et al., Carpineto et Romano, ...)
- **Logical description** (Chaudron et al., Ferré et al., ...)
- **Graphs** (Ganter and Kuznetsov, Liquière, Prediger et Wille, Kötters et al., Graph-FCA Ferré et al....)
- **Multi-relational, RCA** (Priss, Rouane et al., ...); **RCA+Fuzzy** (Boffa et al.)
- **Polyadic** (Sacarea, Tronca et al.)
- **Sequences** (Boukhetta, Demko, Bertet et al., Buzmakov et al.)
- **Temporal** data (Wolff et al., Nica, Braud, Dolques, Le Ber et al., Boukhetta, Demko, Bertet et al.)
- **Pattern Structures** (Ganter et al., Kuznetsov et al., Napoli et al., Buzmakov et al.)

Scaling: Multi-valued attributes

<i>rent</i>	begin	end
flat1	2000	2002
flat2	2000	2005
flat3	2010	2019
flat4	2020	

year	≥ 2000	≥ 2010	≥ 2020
2000	x		
2010	x	x	
2020	x	x	x



year	$[2000,2010]$	$[2005,2010]$	$[2000,2005]$	$[2000,2020]$
2002	x		x	x
2005	x	x	x	x
2019				x

<i>rent</i>	begin			end			
	≥ 2000	≥ 2010	≥ 2020	$[2000,2010]$	$[2005,2010]$	$[2000,2005]$	$[2000,2020]$
flat1	x			x		x	x
flat2	x			x	x	x	x
flat3	x	x					x
flat4	x		x				

[Ganter & Wille, 1999; Kaytoue et al, 2011] - Credits example P. Keip



Triadic concept analysis

FCA



2D concept
(rectangle)

TCA



3D concept
(cuboid)

Pattern Structures

Pattern structures, Ganter and Kuznetsov 2001

In the following framework:


- a set of objects G
- a set of descriptions (D, \sqcap) which is a semilattice
- a partial order on D : $a \sqsubseteq b$ iff $a \sqcap b = a$ (a is subsumed by b)
- a map $\delta : G \rightarrow D$

A Galois connection (f, g) can be defined:

- $\forall A \subseteq G, f(A) = \sqcap_{g \in A} \delta(g)$
- $\forall d \in D, g(d) = \{g \in G \mid d \sqsubseteq \delta(g)\}$


Ex.1 Interval Pattern Structures [Kaytoue et al., 2011]

<i>rent</i>	begin	end	$[a, b] \cap [c, d]$
flat1	[2000,2000]	[2002,2002]	=
flat2	[2000,2000]	[2005,2005]	
flat3	[2010,2010]	[2019,2019]	$[\min(a, c), \max(b, d)]$







Ex.2 Graph Pattern Structures [Ganter&Kuznetsov, 2001]

G1



G2



$G1 \sqcap G2$

Relational Concept Analysis (RCA)

[Huchard et al., 2007, Rouane Hacène et al. 2013]




Principles

- Extends the purpose of FCA for taking into account object categories and links between objects
- Main principles:
 - a relational model based on the entity-relationship model (with binary relationships)
 - integrate relations in formal contexts between objects as *relational* attributes
 - various operators (quantifiers) inspired by description logics
 - iterative and tunable process
- RCA provides a set of interconnected lattices
- Produced structures can be written in DLs









Relational Context Family (RCF)

A RCF \mathcal{F} is a pair (K, R) with:

- K is a set of object-attribute contexts $K_i = (O_i, A_i, I_i)$
- R is a set of object-object contexts $R_j = (O_k, O_l, I_j)$
 - (O_k, O_l) are the object sets of formal contexts $(K_k, K_l) \in K^2$
 - $I_j \subseteq O_k \times O_l$
 - K_k is the *source/domain context*
 - K_l is the *target/range context*
 - we may have $K_k = K_l$



Drone types (Object-Attribute context)

Drone	Gimbal	GPS	GLONASS	Avoidance	Headless	Altitude Hold	FT I 10	FT ge 10	FT ge 20
Syma X4S Assault 					×		×		
Syma X8G 					×		×		
Parrot Bebop 		×				×		×	
DJI Ryze Tello 						×		×	
Hubsan X4 H502S 		×			×	×		×	
Aosenma CG035 GPS FPV 	×	×			×	×		×	
DJI Mavic Air 	×	×	×	×	×	×			×
Yuneec Typhoon H Pro 	×	×	×	×	×	×			×



Drone fleets (Object-Attribute context)

DroneFleet	mission:agri	mission:rescue	mission:Audiovisual	archi:centralized	archi:distributed	guidance:human	guidance:ML	control:leaderFollower	control:behaviorBased
agriDF0	×			×		×		×	
agriDF1	×				×	×		×	
rescueDF2		×			×	×	×		×
rescueDF3		×			×	×	×		×
audiovisualDF4			×		×	×			×

Contains (Object-Object Context)


		Syma X4S Assault	Syma X8G	Parrot Bebop	DJI Ryze Tello	Hubsan X4 H502S	Aosenma CG035 GPS FPV	DJI Mavic Air	Yuneec Typhoon H Pro
contains									
agriDF0	x								
agriDF1	x	x						x	x
rescueDF2								x	
rescueDF3									x
audiovisualDF4			x	x	x			x	x

⇒ rescueDF2 and rescueDF3 do not share drone types

Relational attributes

rescueDF2 and rescueDF3 do not share concrete drone types
but they share the fact that all their drones with GLONASS, GPS, FT
 ≥ 20 , etc.

Relational attribute: $\exists \forall \text{contains}(\text{Concept_Drone_14})$




Drone fleets (Extended Object-Attribute context)

DroneFleet	mission:agri	mission:rescue	mission:Audiovisual	archi:centralized	archi:distributed	guidance:human	guidance:ML	control:leaderFollower	control:behaviorBased		$\exists \forall \text{contains}(\text{Concept_Drone_14})$	
agriDF0	×			×		×		×				
agriDF1	×				×	×		×				
rescueDF2		×			×	×	×		×		×	
rescueDF3		×			×	×	×		×		×	
audiovisualDF4			×		×	×			×			






Relational attributes

rescueDF2 and rescueDF3 do not share concrete drone types
but they share the fact that all their drones with GLONASS, GPS, FT
 ≥ 20 , etc.


Relational attribute: $\exists \forall \text{contains}(\text{Concept_Drone_14})$




Quantifiers




AOC-posets of drone fleets and drones



AOC-posets of drone fleets and drones (excerpt)



RCA in the general case



An iterative process

- Complex model with paths and cycles of any length
- Objects groups (concepts) are propagated along the paths and the cycles, step after step
- The process stops when no new concept appears

Agenda

Introduction

Roots

FCA toolbox

Complex data

FCA in KD

Conclusion

FCA in Knowledge Discovery

- **Knowledge structuring**: ontologies, data models in KR/DB/SE
Stumme, Maedche, Cimiano, Hotho, Sertkaya, Valtchev, ...
- **Information retrieval, Exploratory KD**: conceptual navigation, visualization, Decision Tree - like structure, Efficient index structure Ferré, Carpineto, Romano, Eklund, ...
- **Data mining, Data analysis**: Pattern mining, implication/association rules, functional dependencies, interestingness measures Valtchev et al., Missaoui et al., Bertet et al., Cordero et al., Valverde-Albacete et al. Baixeries et al. ...
- **Knowledge elicitation**: Concept discovery, concept definition, attribute exploration Ganter, Obidekov, Alam, Buzmakov, Codocedo, Napoli, ...
- **Recommendation systems** Ignatov, Kuznetsov, Codocedo, Napoli, ...
- **Querying** with answers classification Messai, Napoli, Azmeh et al., ...

Part of them in: Jonas Poelmans, Sergei O. Kuznetsov, Dmitry I. Ignatov, Guido Dedene: Formal Concept Analysis in knowledge processing: A survey on models and techniques. Expert Syst. Appl. 40(16): 6601-6623 (2013) + significant new work since

Applications (A few domains)

- Environment, biology, chemistry, health
- Linguistics, Text understanding
- Software engineering
- Communities, social network

Part of them in: Jonas Poelmans, Dmitry I. Ignatov, Sergei O. Kuznetsov, Guido Dedene: Formal concept analysis in knowledge processing: A survey on applications. Expert Syst. Appl. 40(16): 6538-6560 (2013) + significant new work since

Tools (A few examples)

More than 50 web applications, downloadable software or plugins at Uta Priss webpage <https://upriss.github.io/fca/fcasoftware.html>

- **Algorithms**: Conexp family, ToscanaJ, fcaR, GALACTIC
- Specializations: **RCA** software (Galicja, RCAexplore, FCA4J), **Fuzzy** (fcaR), **polyadic** (FCA Tools Bundle)
- IR and **Search/Query** engines: Credo family, Search Sleuth family, Camelis, Sparklis family
- **Visualization+navigation**: Latviz, RV-xplorer, ConceptCloud, RCAviz

Workshop Applications and Tools of Formal Concept Analysis@ICFCA2019
Workshop ETAFCA@CLA2022

Focus on Software Engineering

- Mostly well formatted and complete data: conceptual models, specifications, source code, traces, call graphs, git actions...
- Software engineers are proficient to understand and exploit the results

A large range of applications, e.g.

- Migration from procedural to object-oriented paradigm
- Class model / Class hierarchies refactoring from artefact description or artefact usage
- Organization of repositories of software artefacts: classes, components, web services
- Extraction of model transformation patterns
- Feature models synthesis in software product lines

Focus on class model refactoring: Motivation

Class models, ontologies


- Capturing and representing domain knowledge
- Highlight is-a relationships as the skeleton of the representation
- Encourage reuse and abstraction

Normal form model with RCA

- No redundancy
- All abstractions and specialization relationships are included
- Most compact structure


Seminal paper (FCA version): Godin & Mili, 1993

Focus on class model refactoring: Initial Model




inspired by Pesticides Models, A. Miralles, IRSTEA

Focus on class model refactoring: Identified defaults




- `measuringDate` `codeQuality` repeated in **Rainfall** and **Wind** (missing *measure* abstraction)
- **RainGauge** et **Anemometer** are connected via `measuredXXX` (missing *Device* abstraction)
- repeated behavior in `print` methods (M/C = print `measuringDate` / `codeQuality`).


Focus on class model refactoring: Lattices



Focus on class model refactoring: Lattices excerpt



Focus on class model refactoring: Final Model



Focus on class model refactoring: references

- Design: PhDs theses of C. Roume (2004), A. Rouane Hacène (2006), J.-R. Falleri (2009), A. Osman Guédi (2013)
- Implementation and practice: France Télécom (M. Dao, 2004), IRSTEA (A. Miralles, 2012-...)
- Cousin methods: OODB schema refactoring (Lakhal et al., Missikov & Scholl, Rundensteiner), Ontology learning and refactoring (Rouane Hacène, Napoli, Valtchev et al.)

Focus on software product lines

Software Product Lines

A paradigm to discipline the construction of families of similar software (e.g. e-commerce, travel reservation), reduce the cost, increase quality and personalization


Main challenge

Capturing, representing and exploiting variability to be able to derive almost automatically software variants

Focus on software product lines: Feature Model

Feature Model


One of the most used variability models



Credits J. Galasso-Carbonnel

Focus on software product lines: FCA variability model


All FM with the same configuration set can be mapped or extracted from the concept lattice [Galasso-Carbonnel et al.]



Credits A. Waffo Kouhoué, Y. Bonavero

Focus on software product lines: FCA completeness

FCA is more powerful than FM: it allows to express any propositional logic formula [Galasso-Carbonnel et al.]



Credits J. Galasso-Carbonnel

Focus on software product lines:

Applications

- Feature Model refactoring or synthesis (from a set of existing configurations)
- Feature Model operations: union, intersection
- Configuration recommendation

Evaluations


- SPLOT repository (<http://www.splot-research.org/>)
- Product comparison matrix (e.g. wikipedia)
- Visual accessibility options in operating systems

Focus on Agroecology: Knomana

- Find alternative solutions to chemical pesticides and antibiotics



- +45000 plant usage description
- +35 attributes
- +700 scientific papers



- Data exploration with RCAVIZ rcaviz.lirmm.fr/
- Implication Rules computed for FCA and RCA with www.lirmm.fr/fca4j/

Focus on Agroecology: Knomana

Data exploration with RCAVIZ rcaviz.lirmm.fr/

Aspergillus parasiticus attack in Benin


Context: **Pest** ▾

Objects			Attributes			Concepts
<input type="button" value="Select all"/>	<input type="text" value=""/>	<input type="button" value="AND"/>	<input type="button" value="Select all"/>	<input type="text" value=""/>	<input type="button" value="AND"/>	<input type="radio"/> 12
<input type="button" value="Unselect all"/>	Selected *****	<input type="button" value="OR"/>	<input type="button" value="Unselect all"/>	Selected *****	<input type="button" value="OR"/>	<input type="radio"/> 13
<input type="checkbox"/> aspergillusFlavus	<input type="checkbox"/> aspergillusOchrace...		<input type="checkbox"/> aspergillus	<input type="checkbox"/> attacksPeanuts		<input checked="" type="radio"/> 27
<input checked="" type="checkbox"/> aspergillusParasiti...	<input type="checkbox"/> aspergillusTamaritii		<input type="checkbox"/> ∃ isFoundIn: 17	<input type="checkbox"/> ∃ isFoundIn: 20		
			<input type="checkbox"/> ∃ isFoundIn: 26	<input type="checkbox"/> attacksCheese		

Credit example: A. Ouzerdine - RCAVIZ joint work with E. Muller, P. Martin, A. Sallaberry, P. Poncelet


Focus on Agroecology: Knomana

Aspergillus parasiticus concept is highlighted; we follow relational attribute to Concept 10 (controlling plant)




Focus on Agroecology: Knomana

Which is ... *Aspilia Africana*




Focus on Agroecology: Knomana

Unfortunately, it can be found in Nigeria (not in Benin) - Concept 23




Focus on Agroecology: Knomana

Can we find in Benin an alternative to *Aspilia Africana*? We come back to Concept 10.




Focus on Agroecology: Knomana

To find a cousin plant, we go up to Concept 21




Focus on Agroecology: Knomana

Then down to Concept 25, where we find *Chromolaena odorata*



Focus on Agroecology: Knomana


Which fortunately, can be found in Benin (Concept 26)



Focus on Agroecology: Knomana

Chromolaena odorata controls Aspergillus ochraceus, which has the same genus as Aspergillus parasiticus.

This hypothesis that can be delivered to experts: i.e. conduct experiments for using Chromolaena odorata against Aspergillus parasiticus



Focus on Agroecology: Knomana



Challenges

- Incomplete and imprecise data (e.g. indications like spp)
- Potential mistakes (needed cleaning)
- FCA/RCA tools still hardly used by domain experts (a data scientist is needed)

Agenda

Introduction

Roots

FCA toolbox



Complex data

FCA in KD


Conclusion

FCA: a Swiss knife for Knowledge Discovery

	fly	water-habitat	feathered	ingestary	red-bill	fly	sea-habitat	wood-habitat	six-legged	insectal	eat-fish	water-habitat
hybrid	x											
bat	x											
ostrich		x									x	x
grunter			x									
flamingo				x								
albatross		x					x				x	x
little-tern			x		x						x	x
great-auk				x							x	x
wood-pecker		x						x				
great-otter											x	x
arctic-tern		x									x	x



six-legged => flies,elytra
 red-bill => flies,feathered,sea-habitat,eats-fish,water-habitat
 feathered,eats-fish,water-habitat => flies,sea-habitat
 eats-fish => water-habitat



Credits: J. Galasso-Carbonnel




Credits: J. Galasso-Carbonnel

What's next?

- **Theory**: e.g. connecting the different FCA trends, connecting FCA to other KD approaches
- **Algorithms**: e.g. local/incremental, parallel
- **Methodology**: e.g. User interaction, Detecting and correcting anomalies, Classifying rules, Generalizing from applications
- Address **Complex data / Big data** challenges
- Using FCA/RCA as **data complexity measuring** framework
- **Hybrid IA/KD** systems; Explainable AI
- Integration in **data science workflows** (e.g. in Orange or Scikit-learn with subsymbolic ML, in Jupyter Notebooks)

Thank you!



Smart **FCA**

Partly supported by the ANR SmartFCA project
Grant ANR-21-CE23-0023 of the French National Research Agency



Many thanks to many collaborators, and ...
Special credits to Amedeo Napoli for sharing ideas and references