



N-hexane abatement using a non-thermal plasma

P Trad, N. Blin-Simiand, M. Fleury, F. Gérardin, M. Heninger, P. Jeanney, S. Pasquier

► To cite this version:

P Trad, N. Blin-Simiand, M. Fleury, F. Gérardin, M. Heninger, et al.. N-hexane abatement using a non-thermal plasma. The XXV Europhysics Conference on the Atomic and Molecular Physics of Ionized Gases (ESCAPEIG), Jul 2022, Paris, France. hal-03761003

HAL Id: hal-03761003

<https://hal.science/hal-03761003v1>

Submitted on 25 Aug 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

N-hexane abatement using a non-thermal plasma

P. Trad^{1,2}, N. Blin-Simiand¹, M. Fleury¹, F. Gerardin², M. Heninger³, P. Jeanney¹, S. Pasquier¹

¹LPGP, CNRS, bat. 210 Univ. Paris-Saclay, 91405 Orsay Cedex, France

²INRS, CS 60027 54519 Cedex, Rue du Morvan, 54500 Vandœuvre-lès-Nancy, France


³ICP, CNRS, bat. 350 Univ. Paris-Saclay, 91405 Orsay Cedex, France

perla.trad@universite-paris-saclay.fr

Abstract: This work is part of a collaborative research project to evaluate the relevance of combining an oxidation technique to a complementary process for the treatment of VOCs in air. VOCs are volatile organic molecules that are among the main atmospheric pollutants. They have several uses in different industry sectors, in particular as solvents, but they have harmful effects on health and the environment. Conventional VOC treatment methods (adsorption, oxidation...) are not always sufficient. The use of non-thermal plasmas can be a solution. The present study is done with the purpose of evaluating and understanding the effect of a dielectric barrier discharge (DBD) on a heavy hydrocarbon in terms of removal efficiency in dry air as well as by-product formation, in view of further coupling to a complementary process. The chosen molecule, n-hexane, C₆H₁₄, is a VOC found in different types of industries, its treatment is likely to generate numerous by-products. This aim of this study is to understand the physicochemical processes involved in the abatement of n-hexane in air by non thermal plasma,

EXPERIMENTAL SET-UP

DBD reactor:




- Detectors at the reactor outlet:
- Real-time ozone (UV 254 nm) and CO₂ (IR)
- Detection et quantification of n-hexane, H₂, CO, formaldehyde using gas-phase chromatography (Micro-GC Fusion).
- Detection of remaining by-products (ppb) using high-resolution mass spectrometry.

Reactor volume = 3.9 cm³

Flow rate : Q = [0.5, 1] L/min



Electrical Parameters :




- Frequencies : f = [500, 1000, 1500] Hz.
- Energy E_{pulse} (J) deposited in the plasma per pulse: $E_{pulse} = \int I(t)*V(t)dt$
- Specific energy density(J/L): SED = E*f/Q

Mesures effectuées avec un oscilloscope LeCroy 204MXi-A (0.5 L/min, 500 Hz)

RESULTS AND DISCUSSION


Ozone production:

Effect of n-hexane on ozone production (500 Hz, 150 J/L, 500 mL/min)




- Ozone production: [2,3]
 $O_2 + e \rightarrow O(^3P) + O(^3P) + e$
 $O_2 + e \rightarrow O(^1D) + O(^3P) + e$
 $O(^1D) + M \rightarrow O(^3P) + M$
 $O_2 + O(^3P) + M \rightarrow O_3 + M$
- Ozone destruction: [2,3]
 $O_3 + NO \rightarrow NO_2 + O_2$
 $O_3 + O_2(\Delta) \rightarrow O_2 + O_2 + O(^3P)$
 $O(^3P) + O_3 \rightarrow O_2 + O_2$
 $O(^3D) + O_3 \rightarrow O_2 + O_2(\Delta)$

Thermal effect in an air discharge (1000 Hz, 660 J/L, 500 mL/min)




In the presence of C₆H₁₄ in the gas stream, in addition to the previous reactions, an atomic oxygen O or a hydroxyl radical HO° can break a C-H bond on the n-hexane molecule.



O and especially OH are also involved in other reactions with by-products.

This explains the lower ozone detection when n-hexane is introduced into the discharge.

There are three possibilities for initiation reactions with breaking on : C₁(C₆), C₂(C₅) or C₃(C₄) in n-hexane molecule




N-hexane abatement:

- Results were obtained at the exit of the reactor using the micro -GC Fusion (black points) and the BTrap (hollow points).
- Exponential decay:


$$[COV] = [COV]_0 \exp(-SED/\beta)$$

- [COV]₀: inlet concentration of n-hexane
- β : characteristic energy
- n-hexane : [5-500] ppm

Q = 0.5 L/min and f = 500 Hz



Q = 1 L/min and f = 500 Hz



Complete conversion:
• at 930 J/L (5 ppm)
• at 1350 J/L (11 ppm)

References :

- [1] Hyun-Ha Kim. Nonthermal Plasma Processing for Air-Pollution Control : A Historical Review, Current Issues, and Future Prospects. *Plasma Processes and Polymers*, 1(2) :91–110, 2004
- [2] Blin-Simiand, N., Jorand, F., Magne, L. et al. Plasma Reactivity and Plasma-Surface Interactions During Treatment of Toluene by a Dielectric Barrier Discharge. *Plasma Chem Plasma Process* 28, 429–466, 2008
- [3] Pasquier, S. et al. Real-time analysis of toluene removal in dry air by a dielectric barrier discharge using proton transfer reaction mass spectrometry. *Journal of Physics D: Applied Physics* 51(42), 2018
- [4] Kuiwen Zhang, et al. An experimental and kinetic modeling study of n-hexane oxidation, *Combustion and Flame*, 162(11) :4194-4207, 2015


Effect of total gas flow rate:

Residual C₆H₁₄ measured at the reactor exit as a function of the SED for an inlet concentration of 50 ppm of C₆H₁₄ at 500 Hz and 0.5 L/min and 1 L/min.

In our case: no critical influence of the gas flow rate on the abatement of C₆H₁₄

Removal efficiency:

$$\text{Efficiency } \chi = \frac{[COV]_0 - [COV]}{[COV]_0} * 100$$




- Results obtained at the exit of the reactor using the BTrap, and the Micro-GC Fusion.
- SED = 250 J/L, f = 500 Hz.
- Applied voltage 25 kV, Q = 0,5 L/min


The less polluted the air stream, the easier is the treatment

By-product formation:

By-products detected using the Btrap (210 J/L, 500 Hz, 0.5 L/min).



Evolution of the main by-products in the discharge in air with and without n-hexane (100 ppm) (210 J/L, 500 Hz, 0.5 L/min)



Main by-products:
formaldehyde, acetaldehyde, propanal, carbon dioxide

Detection of by-products that aren't issued from the oxidation of n-hexane:
H₂ (13 ppm for 500 ppm of n-hexane) and HCN.