

## Influence of biaxial stress on magnetostriction experiments and modelling

Olivier Hubert, Z. Maazaz, Julien Taurines, Raphael Crepinge, Frenk van den

Berg, Carola Celada-Casero

### ▶ To cite this version:

Olivier Hubert, Z. Maazaz, Julien Taurines, Raphael Crepinge, Frenk van den Berg, et al.. Influence of biaxial stress on magnetostriction - experiments and modelling. 25th Soft Magnetic Materials - SMM25, May 2022, Grenoble, France. hal-03773040

## HAL Id: hal-03773040 https://hal.science/hal-03773040

Submitted on 8 Sep 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Influence of biaxial stress on magnetostriction – experiments and modelling

O. Hubert<sup>a</sup>, Z. Maazaz<sup>a</sup>, J. Taurines<sup>a</sup>, R. Crepinge<sup>a</sup>, F. van den Berg<sup>b</sup>, C. Celada-Casero<sup>b</sup>

<sup>a</sup>LMT (Univ. Paris Saclay, ENS-Paris-Saclay, CNRS) 91190 Gif-Sur-Yvette, France <sup>b</sup>Tata Steel, PO-Box 10.000, 1970CA IJmuiden, The Netherlands.

The study takes place in the context of in-line non-destructive testing of steels and the development of magnetomechanical models that it requires. New magnetic and magnetostrictive measurements of a steel submitted to biaxial mechanical loading are presented. They allow validation of the proposed models.

Keywords: biaxial stress, magnetostriction, multiscale modelling

#### 1. Introduction

In the last few years, a growing interest of the car industry for the use of Advanced High Strength Steel (AHSS) products has been observed, especially considering the weight saving solutions they lead to. Their excellent mechanical behaviour comes from the very complex microstructure they exhibit, achieved thanks to precise thermomechanical treatments. They are on other hand highly sensitive to small variations in the forming process. *On-line* non-destructive magnetic monitoring techniques are consequently relevant to evaluate the quality fluctuations.

#### 2. objectives

On-line monitoring faces different issues. One of them concerns the multiaxial mechanical stress to which the laminations are submitted, that may have a strong effect on the magnetic behaviour [1] and may lead to erroneous estimations of the microstructure quality. Developing multiaxial multiaxial experiments and magnetomechanical models for inverse identification is therefore relevant. Previous works have addressed magnetic behaviour change due to multiaxial stress, including dualphase steel [2,3,4]. In this communication, some new results showing the effect of a biaxial stress on the magnetostrictive behaviour are presented.

#### 3. Measurement and modelling

A flat carbon Steel (thickness ~3mm) is considered in this study. Its post hot-rolled state ensures isotropic global magnetic and mechanical behaviours. 1D samples consist of 200mm long and 12mm wide strips cut by electroerosion machining. 2D samples are cross-shape specimen designed to promote homogeneous stress and magnetic field in the central area. Samples have been instrumented with longitudinal and transverse strain gauges, pick-up coil for 1D samples and H-coil and needle-B for the 2D samples. Magnetic and magnetostrictive measurements are performed under quasistatic and anhysteretic conditions

\* Corresponding author: olivier.hubert@ens-paris-saclay.fr

and for a large range of stress levels. Among other results, it is shown that the magnetostriction amplitude isovalues seem to follow a rule different from the susceptibility isovalues (fig.1). Results are compared step by step to the output of a multiscale model taking account the crystallographic texture and phases volume fraction [1-5]. Measurement and modelling are found to be in agreement. These comparisons give some keys for a future inverse identification procedure.



Figure 1 : magnetic susceptibility  $\chi$  and magnetostriction amplitude parameter  $\alpha$  as function biaxial stress state ( $\sigma$ 1,  $\sigma$ 2) for magnetic field applied along direction 1.

#### Acknowledgement

This project has received funding from the Research Fund for Coal and Steel under the grant agreement N° 847296.

#### References

[1] Daniel L. Hubert O., Bernard L., Multiscale Modeling of Magnetic Materials, Reference Module in Materials Science and Materials Engineering, Elsevier, 2020,

[2] Hubert O., Przedglad Elektrotecniczny R83, 4 (2007) 70-77.

[3] Hubert O., Daniel L., Journal of Magn. and Magn. Mater.,

323, 20, (2011) 1766-1781

[4] Hubert O., Mballa-Mballa F. S., He S. and Depeyre S., IEEE Transactions on Magnetics, vol. 52, 5 (2016) 1-4

[5] Hubert O, Journal of Magn. and Magn. Mater., 491, (2019), 165564