

Sewage sludge thermochemical treatment with MgCl2: Preparation conditions impact on trace metal elements vaporization and phosphorus recovery

Basile Galey, Boram Kim, Denise Blanc, Gaëlle Ducom, Elodie André, Vincent Chatain, Norbert Rousset, Nathalie Dumont, Joel Zürcher, Rémy

Gourdon, et al.

▶ To cite this version:

Basile Galey, Boram Kim, Denise Blanc, Gaëlle Ducom, Elodie André, et al.. Sewage sludge thermochemical treatment with MgCl2: Preparation conditions impact on trace metal elements vaporization and phosphorus recovery. Sustainable Chemistry and Pharmacy, 2022, 27, pp.100652. 10.1016/j.scp.2022.100652 . hal-03776323

HAL Id: hal-03776323 https://hal.science/hal-03776323v1

Submitted on 22 Jul 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

1	Sewage sludge thermochemical treatment with MgCl ₂ : preparation conditions impact
2	on trace metal elements vaporization and phosphorus recovery
3	Basile Galey ¹ , Boram Kim ¹ , Denise Blanc ¹ , Gaelle Ducom ¹ , Vincent Chatain ¹ , Elodie André ² ,
4	Norbert Rousset ³ , Nathalie Dumont ¹ , Joel Zurcher ⁴ , Rémy Gourdon ¹ , Christophe Guyot ² , Mathieu
5	Gautier ^{1,*}
6	* Corresponding author: mathieu.gautier@insa-lyon.fr
7	¹ Univ Lyon, INSA Lyon, DEEP, EA7429, 69621 Villeurbanne, France
8	² Holcim Innovation Center, 38291 Saint-Quentin Fallavier, France
9	³ Geocycle, 38291 Saint-Quentin Fallavier, France
10	⁴ Holcim, Zürich 8500, Switzerland
11	Abstract

Phosphorus (P) plays an essential role in crops growth. Due to the overexploitation of non-renewable 12 13 phosphate rock deposits and their uneven distribution worldwide, P has turned into a strategic 14 resource for the modern agricultural system. Finding sustainable ways to secure P for fertilizer 15 applications has become critical. Sewage sludge (SS) is a waste material containing P in high amounts. 16 Among several options, SS thermochemical treatment with Cl-donors addition such as MgCl₂, CaCl₂ or 17 NaCl allows to separate P from inorganics pollutants such as trace metal elements (TME). The 18 additives goal is to help fix and form bioavailable P species in solid residues while promoting TME 19 vaporization through the gas phase via chlorination mechanisms. This paper studies the impact of 20 MgCl₂ addition on TME vaporization and P speciation during SS direct calcination treatment at 1000 °C for 4 hours. Four different preparation methods for the "SS + MgCl₂" mixtures were compared, 21 22 with a variation of either the SS (raw or crushed) or the MgCl₂ form (powder or solution). The 23 samples were characterized by ED-XRF, FTIR, XRD, TGA/DSC and the P speciation was obtained 24 thanks to Williams-Saunders method. The use of 0.06 g MgCl₂ / g SS as a Cl-donor divides the TME 25 contents in the solid residues by a factor of more than 10 for Zn and Pb, about 2 for As and Ni but 26 less than 1.25 for Cu. Concerning P, Ca associated P species (mostly Mg₃Ca₃(PO₄)₄) are formed with 27 MgCl₂ addition. The results showed that the impact of different preparation methods on the 28 obtained solid residues characteristics is limited.

29 Key words

30 Phosphorus recovery, Trace metal elements, Sewage sludge, Thermochemical treatment,

31 Vaporization, Chlorination

32 1. Introduction

Phosphorus (P) is a vital non-substitutable element for life and food production (Ruttenberg, 2003). It 33 34 is also a strategic resource as the modern agricultural system has become highly dependent on 35 massive application in the fields of industrial P-based fertilizers. These fertilizers are however mostly produced by exploiting non-renewable phosphate rock (PR) deposits (Cordell et al., 2009; Cordell and 36 37 White, 2011). Even if the scientific community is split about whether or not the reserve depletion will 38 occur within 50 or 300 years, there is a general consensus on (i) the uneven distribution of PR 39 deposits around the world, (ii) the remaining PR decreasing quality and (iii) the increasing extraction 40 processing and shipping costs (Daneshgar et al., 2018). Consequently, finding alternative ways with 41 circular economy approach to secure P for fertilizer applications has become one of the major 42 challenges for the next decades.

43 Among several options, P recovery from sewage sludge (SS) has gathered the interest of many 44 scientists (Raheem et al., 2018). Indeed, SS is the waste material containing the second greatest 45 amounts of P after bone meal and has the main advantage of being abundantly produced worldwide. 46 However, due to trace metal elements (TME) and the presence of microbiologic and organic 47 pollutants, SS is most of the time incinerated for energy production and not further valued as a 48 secondary P resource (Schnell et al., 2020). Indeed, in such thermochemical processes, the TME (Cr, 49 Ni, Cu, Pb, Zn, etc.) are concentrated with P in the solid residues. European legislation will thus 50 evolve. In 2026 in Switzerland, it will be mandatory to recover at least 80% of the P contained in SS 51 before final disposal. Germany, France and the EU may follow before 2030 (in 2029 or 2032 for 52 Germany, depending on the plant size). Simple SS incineration processes will therefore no longer be 53 possible. Finding a way to recover both P and energy during SS thermochemical treatment is 54 therefore highly desirable (Gao et al., 2020).

55 Alternative SS thermochemical treatments with additives may be a solution. The idea is to treat 56 SS with chemical additives to produce energy and P-rich solid residues that may be directly used as 57 fertilizers or soil conditioners (Meng et al., 2019). Cl-based compounds such as MgCl₂, CaCl₂, PVC, 58 NaCl and KCl are the most frequently used (Adam et al., 2009; Vogel et al., 2013). The role of these 59 additives is to help fix P under bioavailable forms in solid residues (interaction with Mg, Ca, Na, K, 60 etc.) while promoting TME (As, Cd, Cr, Cu, Hg, Ni, Pb and Zn) vaporization through the gas phase 61 (chlorination mechanisms). Current existing thermochemical treatments with Cl-donors can be 62 performed either in one (Xia et al., 2020) or two steps (Vogel et al., 2013). In the two step processes, 63 SS are first incinerated (leading to energy production and waste volume reduction), then the 64 obtained ashes are further thermochemically treated with additives for P recovery (Nowak et al., 65 2010). The two step processes have been extensively studied during the last decades due to existing 66 widespread SS incinerators (Adam et al., 2007; Herzel et al., 2016; Jeon and Kim, 2018; Kuboňová et 67 al., 2013; Li et al., 2015; Nowak et al., 2012; Schnell et al., 2020; Vogel et al., 2016; Vogel and Adam, 68 2011; Yu et al., 2016). In single step SS thermochemical processes, the sludge is directly treated with 69 additives either by incineration, pyrolysis or gasification, with the dual purpose of recovering energy 70 and P. Despite advantages of single industrial installation, only few studies focus on the single step SS 71 thermochemical treatments with Cl-based compounds (Liu et al., 2015; Saleh Bairq et al., 2018; Xia et 72 al., 2020; Yang et al., 2019). Galey et al. recently wrote a review article on the topic (Galey et al., 73 2022).

74 Magnesium chloride (MgCl₂) has been extensively studied in the literature due to a high 75 efficiency for TME removal (indirect chlorination pathway) combined with a high solubility of the P 76 species formed during treatment (interaction Mg-P) (Adam et al., 2009, 2007; Jeon and Kim, 2018; Li et al., 2015; Nowak et al., 2012, 2010; Xia et al., 2020; Yu et al., 2016, p. 2). Most of the time, MgCl₂ is used in powder hexahydrate form (MgCl₂.6H₂O) and mixed with SS (or SS ashes) before thermochemical treatment (Nowak et al., 2012, 2010; Xia et al., 2020; Yu et al., 2016). The Cl-donor can also be solubilized in water before being added to the SS (Adam et al., 2009, 2007). The preparation method for the "MgCl₂ + SS" mixtures is however only poorly detailed in most papers. Furthermore, to our knowledge, no work compared different preparation methods impact on trace metal elements vaporization and phosphorus recovery from sewage sludge yet.

84 The present study therefore aims to present and compare different preparation methods for one-85 step SS thermochemical treatments with MgCl₂. Five different SS-based mixtures were thus prepared 86 by varying either the form of SS (raw or crushed) or the form of MgCl₂ (powder or in solution with 87 water). They were treated in a tubular furnace at 1000 °C with air excess and with a 4 h residence 88 time. The objectives were to highlight the role of MgCl₂ addition and to evaluate the influence of the 89 particle size of the SS and of the water content during the incineration process with chloride addition 90 notably regarding the TME removal and the phosphorus distribution in ashes. The obtained ashes 91 were characterized by XRD to identify the principal crystalline forms and by ED-XRF to determine the 92 inorganics contents. Additional thermogravimetry analyses coupled with differential scanning 93 calorimetry and Fourier-transform infrared spectroscopy analyses were also performed. A special 94 focus was also done on phosphorus, which was fractioned into four operationally defined fractions: 95 organic, inorganic, Ca associated and non Ca associated, thanks to Williams-Saunders method (Kim et 96 al., 2015).

97 **2. Materials and methods**

98 2.1. Materials

All the thermochemical experiments were carried out with a SS from a Swiss wastewater treatment plant, using Fe salts to precipitate phosphates from wastewater. The sludge was dehydrated (using a centrifugation process), dried to reach a water content of around 6 wt% and stored in a freezer up to treatment. In the following, this sludge is referred to as raw SS "**r-SS**". Commercial hexahydrate magnesium chloride (pure MgCl₂.6H₂O, powder form, Chimie Plus Laboratory) salt was used as additive.

105 2.2. Samples preparations

Five different SS-based mixtures were prepared. For some samples, a ball mill from Retsch was used to perform a grinding at 30 RPM during 5 min with a zirconium ball. When MgCl₂ was added to SS, it is important to note that, irrespective of the preparation method, the amount of MgCl₂ added was always 0.06 g MgCl₂ / g SS (i.e. 44.7 g Cl/kg SS).

- The first prepared mixture is called "m-SS". It is the reference sample and corresponds to raw
 SS milled during 5 min as detailed above.
- Raw SS was also co-milled with 0.06 g MgCl₂ / g SS of MgCl₂ under MgCl₂.6H₂O powder form.
 It is the most classic preparation method. This sample is denoted as "m-(SS+MgCl₂.6H₂O)".
- For the third preparation method, SS was first milled and then mixed with MgCl₂ in solution
 concentrated at 32 wt%. In this mixture, the water amount involved is of 17 wt% and not
 enough to moisturize all SS. This mixture is called "m-SS + MgCl₂.32%".
- 1174. For the fourth mixture, SS was also first milled and then mixed with MgCl2 in solution118concentrated at 12 wt%. In this mixture, the water content is of 35 wt% and allows to

119 moisturize all SS. This sample is denoted as "**m-SS + MgCl₂.12%**". Along with the third 120 mixture, it may allow to study water impact on MgCl₂ dispersion in SS during preparation.

5. Finally, raw SS was used (without milling) and directly mixed with MgCl₂ in solution concentrated at 12 wt%. This mixture is called "r-SS + MgCl₂.12%". The water content is also of 35 wt%. With this sample, the goal is to investigate the impact of not milling the SS prior to thermochemical treatment.

125 *2.3. Thermochemical treatment*

After preparation, the 5 mixtures were thermochemically treated in a horizontal tube furnace from 126 127 Thermolyne, under the same operating conditions. Four ceramic crucibles were used (for each 128 mixture, in order to obtain enough ashes for sample characterization), filled with 20 g of samples (5 g 129 in each crucible) and placed in the furnace. The treatment temperature was set to 1000 °C with a 130 residence time of 4 h. Considering the heating time of 1 h and the cooling time of 2 h, each treatment lasts 7 h, of which 4 h at 1000 °C. Air was used in high excess as treatment gas. The 131 132 obtained solid residues (ashes) were collected and milled 30 s at 30 RPM to ease subsequent 133 analyses. Hereafter, ash from the calcination of m-SS is referred to as "m-SS ash", ash from the 134 calcination of m-(SS+MgCl₂.6H₂O)" is referred to as "m-(SS+MgCl₂.6H₂O) ash", etc.

135 2.4. Samples characterization

The characterizations were performed either on the mixtures before thermochemical treatment or
on the obtained solid residues (ashes). The produced gases during treatment were unfortunately not
monitored.

Energy Dispersive X-ray Fluorescence (ED-XRF) with Xepos (AMETEK, FX EDXRF model XEPOS V HE) method was used to determine the inorganics contents (majors and minors) in the different samples. ED-XRF was also used to determine the TME and the total P contents in the solid residues obtained after the calcination experiments.

A thermogravimetric analyser coupled with a differential scanning calorimeter (TG-DSC, Mettler Toledo TGA 2) was used to study the mixtures decomposition. The mass of the samples was approximately 20 mg. The decomposition experiments were performed under 50 ml/min air, from 30 to 1000 °C, with a heating rate of 10 °C/min and in an Al_2O_4 crucible. A second heating ramp under the same conditions was performed after the first one, in order to see if the decomposition is complete.

Fourier Transform InfraRed spectroscopy (FTIR, Perkin Elmer Spectrum One FTIR spectrometer) experiments were performed on the raw SS and the produced ashes, with the Attenuated Total Reflectance method (ATR). X-ray diffraction experiments (XRD, Bruker D8 Advance instrument equipped with a copper anticathode) were also performed to determine the different crystalline forms in the produced ashes.

Finally, P was fractioned in organic, inorganic, Ca associated and non Ca associated, and the various liquid extracts were quantified by inductively coupled plasma with atomic emission spectroscopy (ICP-AES, Ultima 2 Horiba Jobin Yvon SAS) thanks to Williams-Saunders method, as described elsewhere by Kim et al. (Kim et al., 2015).

158 3. Results and discussion

159 3.1. Samples characterization

The composition (majors and TME contents) of the sewage sludge used in this work is given in **Table 1**, as obtained by ED-XRF. The SS is Fe rich, which is in good agreement with the fact that Fe salts were used to precipitate phosphates during the wastewater treatment process. Phosphorus content is 2.8 wt%. The other majors contents are in the typical range of SS in Europe (Ronda et al., 2019). Concerning the trace metal elements, the sludge is mostly rich in Cu and Zn (content of 399 and 855 mg/kg respectively) while only 80, 36, 35, 13, 1 and 1 mg/kg of Cr, Pb, Ni, As, Cd and Hg were detected by ED-XRF respectively (**Table 1**).

Table 1 – r-SS composition: majors (wt%) and TME (mg/kg), as obtained by ED-XRF										
Majors	Si	Al	Fe	Ca	Mg	K	S	Р		
wt%	2.7 ± 0.3	2.5 ± 0.2	5.4 ± 0.5	3.2 ± 0.3	0.5 ± 0.1	0.2 ± 0.1	2.1 ± 0.5	2.8 ± 0.3		
TME	As	Cd	Cr	Cu	Hg	Ni	Pb	Zn		
mg/kg	13 ± 3	1 ± 1	80 ± 37	399 ± 30	1 ± 1	35 ± 4	36 ± 6	855 ± 50		

167

168



Figure 1 – Thermochemical decomposition of the reference system "m-SS" heated under air from 30 to 1000 °C (10 °C/min):
 (a) mass loss (TGA) and derivative (DTG) (b) heat flow as a function of the temperature.

Fig. 1 presents the thermal analyses performed on the reference system (m-SS), allowing to 171 172 study its decomposition pathway. As visible in the thermogravimetric analyses of Fig. 1 (a), the decomposition of the sludge starts as early as 40 °C with a first mass loss of approximately 10 wt% up 173 to 190 °C. It is likely to correspond to the vaporization of water present in the sludge. Above 200 °C 174 175 (with 2 DTG maxima at 280 and 445 °C), the organic carbon species are decomposed, as confirmed by 176 the two exothermic peaks visible in the DSC experiment of Fig. 1 (b). At the end of the thermal treatment, a plateau is visible from 600 to 1000 °C with no more significant decomposition. 177 According to the performed TG-DSC experiment, the volatile content in the sewage sludge is 62 w%, 178 179 with 10 wt% of water. No thermal decomposition is visible during the second heating ramp as visible 180 in Fig. S1.





Figure 2 – Thermochemical decomposition of a mixture of SS and MgCl₂.6H₂O in powder form "m-(SS+MgCl₂.6H₂O)" heated under air from 30 to 1000 °C (10 °C/min): (a) mass loss and derivative (b) heat flow as a function of the temperature.

184 When $MgCl_2$ is added to the SS, few differences can be noticed. Fig. 2 presents the thermal analyses performed on the mixture m-(SS+MgCl₂.6H₂O). 0.06 g MgCl₂ / g SS of MgCl₂ was thus added 185 to the SS before grinding, under MgCl₂.6H₂O powder form. The thermogravimetric analysis of Fig. 2 186 (a) shows three mass losses with DTG maxima at 87, 284 and 420 °C. The first one corresponds to 187 water evaporation and is slightly higher than for m-SS (14 against 10 wt%) due to the presence of 188 189 water in the MgCl₂.6H₂O used to prepare the mixture. The two other mass losses correspond to the 190 organic carbon species decomposition (as confirmed in Fig. 2 (b) by the two exothermic peaks). In 191 comparison with the thermal decomposition of m-SS in Fig. 1, the second exothermal peak observed 192 for m-(SS+MgCl₂.6H₂O) mixture is thinner and happens at a lower temperature (444 against 471 °C). 193 As visible in Fig. S2 (thermal decomposition of the MgCl₂.6H₂O powder used for the experiments), 194 when MgCl₂ is heated up to 1000 °C, HCl gas is likely to be produced from 400 to 800 °C (as also reported in (Yu et al., 2016)). HCl presence and interaction with the SS may therefore explain the 195 difference of the peak shape between Fig. 1 (b) and 2 (b). At 1000 °C, about 65 wt% of the mixture is 196 197 decomposed, with 14 wt% of water. No further thermal decomposition is visible during the second 198 heating ramp, Fig. S1. Vogel et al. investigated the treatment of sewage sludge ashes with MgCl₂ by 199 thermogravimetry (Vogel et al., 2011a). Without organic matter, they observed a nearly constant 200 mass loss in the range 400–1000 °C, which is consistent with these results.



201



Figure 3 – FTIR experiments performed on the raw SS and on the obtained ashes after the calcination experiments for the five prepared mixtures.

Fig. 3 presents the FTIR experiments performed on the raw SS and on the ashes obtained after the calcination treatment at 1000 °C for the five mixtures. First, it is important to note that the absorption bands corresponding to water at 3269 cm⁻¹ and to carbon species present at 1562, 1539, 1417 and 875 cm⁻¹ in the raw SS are not present anymore in the ashes after the calcination 208 treatment, mainly due to water vaporization and organic matter degradation. The mixture 209 decomposition is therefore complete under the chosen operating conditions (1000 °C – 4 h residence time – air). The IR bands between 900 and 1200 cm⁻¹ visible in the ashes samples result from several 210 211 contributions which overlap. These wavelengths are characteristic of Si-O-Si vibrations and therefore to quartz and silica based minerals (Vogel et al., 2011a). In the range 1000-1100 cm⁻¹ some 212 213 P-O stretching bands characteristic of Mg/Ca-P compounds can also be observed (Kim et al., 2013; 214 Vogel et al., 2011b). The high content in iron in raw sludge would also suggest the presence of P–O 215 stretching bands associated to small amount of iron phosphate (Palacios et al., 2012). No significant differences are visible between the 5 ashes except the presence of an IR bound at 1065 cm⁻¹ for the 4 216 217 mixtures containing MgCl₂, which may be attributed to P-O bound stretching of Mg-P compounds 218 (Vogel et al., 2011b).



219

Figure 4 – X-ray diffraction patterns of the obtained ashes after the calcination experiments for the five prepared mixtures.

222 XRD experiments were also performed on the produced ashes after calcination experiments. 223 The obtained results are presented in Fig. 4. Classical inorganic compounds are detected in the 5 224 solid residues, corresponding to SiO₂, Fe₂O₃ and Ca-Al-Si species. No significant differences 225 concerning these species are visible between the samples. Interestingly, for the P based species: $Ca_9Al(PO_4)_7$ is detected in all mixtures while $Mg_3Ca_3(PO_4)_4$ is only present in the samples containing 226 227 MgCl₂. It means that MgCl₂ addition prior to thermochemical treatment leads to the formation of 228 Mg-Ca-P species when treated at high temperature, as also observed in other works (Adam et al., 229 2009; Vogel et al., 2013; Yang et al., 2019).

230 3.2. TME removal

The primary goal of sewage sludge thermochemical treatment with Cl-based additives is to promote TME vaporization in order to obtain TME-free solid residues (for further use as fertilizer). The European regulation focuses on 8 TME: arsenic, cadmium, chromium, copper, lead, mercury, nickel and zinc. Their contents in the solid residues obtained after the calcination of the 5 prepared mixtures were therefore measured thanks to ED-XRF. The results are presented in Fig. 5.



Figure 5 – TME contents in the obtained ashes after the calcination experiments for the five prepared mixtures as obtained
 by ED-XRF.

236

First, it is interesting to compare the ashes obtained from the sample without $MgCl_2$ (m-SS ash) with the ashes from the mixtures containing 0.06 g $MgCl_2$ / g SS of $MgCl_2$ (the four other samples):

241 It appears that the contents of Zn and Pb in the ashes are greatly decreased thanks to $MgCl_2$ 242 addition (from 3011 to less than 350 mg/kg for Zn and from 59 to less than 1 mg/kg for Pb, Fig. 5). Cl 243 addition therefore promotes Zn and Pb removal thanks to ZnCl₂ (boiling point of 732 °C) and PbCl₂ (boiling point of 950 °C) volatile compounds formation, as reported elsewhere (Fraissler et al., 2009; 244 245 Galey et al., 2022; Liu et al., 2015; Xia et al., 2020). According to (Galey et al., 2022), the chosen 246 calcination conditions (combustion under air, at 1000 °C, 4 h residence time and with MgCl₂ as 247 chlorine donor) are the best to promote both Zn and Pb removal through the gas phase. It probably 248 explain the low contents observed in the ashes after calcination.

Cadmium is a volatile compound which was initially present in low amounts in the SS (1 mg/kg, see **Table 1**) and was observed in amounts lower than 1 mg/kg in the obtained ashes after the calcination experiments, Fig. 5. Because of these very low amounts, the influence of MgCl₂ on Cd vaporization properties in these experiments are complicated to discuss.

Arsenic removal seems to be enhanced by MgCl₂ addition, with a decrease of the contents in the 253 254 ashes from 39 mg/kg without MgCl₂ to around 25 mg/kg in the 4 "MgCl₂ + SS" mixtures. It is difficult 255 to conclude if the vaporization is due to chlorination mechanisms and/or by a remobilization of the 256 element due to the acidic condition created by $MgCl_2$ addition. However, according to the data 257 compiled by (Galey et al., 2022), arsenic hardly interacts with Cl during thermochemical treatment of 258 SS. The authors also reported that arsenic mostly interacts with the major inorganic elements initially 259 present in SS to form As-based stable compounds such as Ca₃(AsO₄)₂, KAsO₂ and AlAsO₄. The 260 decomposition temperatures of these species are above 1000 °C. It may explain why arsenic in not 261 completely vaporized during the calcination experiments.

262 Copper vaporization properties seem to be only slightly enhanced in presence of MgCl₂ (1274 mg/kg of Cu in m-SS ashes against around 1050 mg/kg in the ashes treated with MgCl₂). If higher 263 264 removal rates are often reported in literature for copper when SS are treated with MgCl₂ (Adam et al., 2009; Xia et al., 2020), some authors also highlighted lower Cu removal rate (Galey et al., 2022; 265 266 Jeon and Kim, 2018; Nowak et al., 2012). A competition between Cl⁻ and other anions may occur and 267 limit Cu-Cl interaction. For example the high sulphur content in the used SS (2.1 wt%, Table 1) could 268 lead to the formation of CuS, which is a stable compound under the chosen operating conditions, 269 limiting Cu-Cl interaction and therefore Cu vaporization as CuCl, CuCl₂ or (CuCl)₃ (Galey et al., 2022). The amount of Cl addition, the limiting interaction of gas phase with solid and the residence time were also factors which were identified as limiting for Cu removal (Galey et al., 2022).

The observed mercury contents in the ashes are surprisingly high (between 29 and 22 mg/kg), especially regarding the initial content in the SS of only 1 mg/kg and the high volatility of the element (Cheng et al., 2019; Sun et al., 2020). The observed contents are therefore likely to be due to an external contamination, probably coming from the furnace used to perform the calcination treatments. This element was therefore not further studied.

277 No significant changes in the chromium contents are visible for the five ashes, meaning that 278 MgCl₂ has no impact on its vaporization under the chosen treatment conditions. It is in good 279 agreement with what is observed in literature, Cr being considered as a low volatile TME with low 280 interaction with Cl and whose removal is particularly challenging (Fraissler et al., 2009; Galey et al., 2022; Vogel and Adam, 2011).

282 The comparison between the 4 samples containing MgCl₂ (added with different preparation 283 methods) with each other shows no significant difference concerning the obtained TME contents in 284 the produced ashes except for nickel. Indeed, when MgCl₂.6H₂O in powder form is co-milled with dry 285 SS, the Ni content in the obtained solid residues after calcination is of 309 mg/kg, while when more 286 water is involved in the preparation process (use of MgCl₂ in solution), the obtained contents are 287 below 160 mg/kg. It means that the presence of water in the mixtures prior to treatment may 288 enhance nickel removal, probably by promoting HCl formation and interaction with Ni to form NiCl₂ 289 gas phase. To our knowledge, such Ni vaporization properties were however not observed elsewhere 290 in literature.



291 *3.3. P recovery*

292

Figure 6 – Phosphorus speciation in the raw SS (no calcination) and on the ashes after the calcination experiments for the
 five prepared mixtures, as obtained by Williams-Saunders method.

The second goal of sewage sludge thermochemical treatment with Cl-based additives is to help form P species that are bioavailable, in order to use the obtained ashes directly as fertilizers. A special focus on the behaviour of phosphorus during treatment was therefore done. Fig. 6 presents the speciation of P in the raw SS and in the ashes obtained after the calcination experiments for the five prepared mixtures. "Organic P" corresponds to phosphorus associated with organic compounds, "non-Ca associated P" to P associated with oxides and hydroxides of Al, Fe and Mn and "Ca associated P".

302 In the raw SS, phosphorus is mostly under non-Ca associated forms, Fig. 6. It is in good 303 agreement with the fact that Fe salts were used to precipitate phosphates during the wastewater 304 treatment process and the observed high Fe content in the sludge (5.4 wt%, Table 1). Organic P is 305 also detected in the raw sludge as well as Ca associated P. The P in the ashes obtained after the 306 calcination treatment without MgCl₂ involved (m-SS ash) is mostly under Ca associated forms (mostly 307 Ca₉Al(PO₄)₇, as detected by XRD in Fig. 4) but with significant amounts of non-Ca associated P as well. 308 When $0.06 \text{ g MgCl}_2 / \text{g SS of MgCl}_2$ is added to the mixtures prior to calcination, the P in the obtained 309 ashes is almost 100% under Ca associated forms. MgCl₂ addition therefore allows to convert non-Ca 310 associated P into Ca associated P, with the predominant crystalline form being Mg₃Ca₃(PO₄)₄ as 311 detected by XRD in Fig. 4. Mg-Ca-P species formation thanks to MgCl₂ addition is also widely 312 observed in literature (Adam et al., 2009; Galey et al., 2022; Vogel et al., 2013; Yang et al., 2019). 313 Interestingly, these Mg-Ca-P species are considered highly bioavailable, notably in acidic soils (Vogel 314 et al., 2018), and therefore particularly interesting for further use of the ashes as recycling fertilizers.

Concerning the 4 different preparation methods for MgCl₂ addition to SS, no significant differences are visible for the P speciation (Fig. 6), as well as for the P crystalline forms in XRD (Fig. 4) and the total P contents (Fig. 6). It means that the preparation method has a negligible impact on the P forms in the obtained solid residues.

319 4. Conclusion

This study investigated the effect of MgCl₂ addition and the addition method on TME vaporization during sewage sludge direct thermochemical treatment at 1000 °C for 4 hours and the forms of P species in the solid residues. The use of 0.06 g MgCl₂ / g SS MgCl₂ as a Cl-donor (44.7 g Cl/kg SS) divides the TME contents in the solid residues by a factor of more than 10 for Zn and Pb, about 2 for As and Ni (when water is involved during preparation) but less than 1.25 for Cu (due to the high S content in the SS). No Cr removal was observed while Cd was vaporized even without MgCl₂ addition.

326 Concerning phosphorus, the obtained speciation and XRD analyses show the formation of Ca 327 associated P forms in the solid residues obtained after SS calcination with MgCl₂, mostly under the 328 Mg₃Ca₃(PO₄)₄ form. SS direct thermochemical treatment at high temperature (1000 °C) with MgCl₂ is 329 therefore particularly interesting to form bioavailable P species (notably in acidic soils) for further use 330 of the ashes as recycling fertilizers.

331 Concerning the 4 different preparation methods for the "SS + MgCl₂" mixtures explored in this work, no significant differences were observed between the produced ashes for the P speciation and 332 333 forms and for the TME removal rates, except for nickel. Indeed, lower Ni contents in the solid residues were observed when water is involved in the "SS + MgCl₂" mixtures preparation method, 334 meaning that the presence of water promotes Ni-Cl interaction. The comparison of the different 335 preparation methods allows to conclude that the co-milling of the SS and MgCl₂ is not required to 336 337 obtain a good interaction between the SS and MgCl₂, at least under the studied conditions. The 338 simple mixing of SS (dewatered form thanks to a centrifugation process for example) with MgCl₂ in solution (the preparation method noted "r-SS + MgCl₂.12%") thus allows to obtain solid residues with
 similar TME contents (even lower for Ni) and P forms.

341 **Conflicts of interest**

342 There are no conflicts to declare.

- 343 References
- 344Adam, C., Kley, G., Simon, F.-G., 2007. Thermal Treatment of Municipal Sewage Sludge Aiming at345MarketableP-Fertilisers.Mater.Trans.48,3056–3061.346https://doi.org/10.2320/matertrans.MK200707
- Adam, C., Peplinski, B., Michaelis, M., Kley, G., Simon, F.-G., 2009. Thermochemical treatment of
 sewage sludge ashes for phosphorus recovery. Waste Manag. 29, 1122–1128.
 https://doi.org/10.1016/j.wasman.2008.09.011
- Cheng, L., Wang, L., Geng, Y., Wang, N., Mao, Y., Cai, Y., 2019. Occurrence, speciation and fate of
 mercury in the sewage sludge of China. Ecotoxicol. Environ. Saf. 186, 109787.
 https://doi.org/10.1016/j.ecoenv.2019.109787
- Cordell, D., Drangert, J.-O., White, S., 2009. The story of phosphorus: Global food security and food
 for thought. Glob. Environ. Change, Traditional Peoples and Climate Change 19, 292–305.
 https://doi.org/10.1016/j.gloenvcha.2008.10.009
- 356Cordell, D., White, S., 2011. Peak Phosphorus: Clarifying the Key Issues of a Vigorous Debate about357Long-TermPhosphorusSecurity.Sustainability3,2027–2049.358https://doi.org/10.3390/su3102027
- Daneshgar, S., Callegari, A., Capodaglio, A.G., Vaccari, D., 2018. The Potential Phosphorus Crisis:
 Resource Conservation and Possible Escape Technologies: A Review. Resources 7, 37.
 https://doi.org/10.3390/resources7020037
- Fraissler, G., Jöller, M., Mattenberger, H., Brunner, T., Obernberger, I., 2009. Thermodynamic
 equilibrium calculations concerning the removal of heavy metals from sewage sludge ash by
 chlorination. Chem. Eng. Process. Process Intensif. 48, 152–164.
 https://doi.org/10.1016/j.cep.2008.03.009
- Galey, B., Gautier, M., Kim, B., Blanc, D., Chatain, V., Ducom, G., Dumont, N., Gourdon, R., 2022.
 Trace metal elements vaporization and phosphorus recovery during sewage sludge
 thermochemical treatment A review. J. Hazard. Mater. 424, 127360.
 https://doi.org/10.1016/j.jhazmat.2021.127360
- Gao, N., Kamran, K., Quan, C., Williams, P.T., 2020. Thermochemical conversion of sewage sludge: A
 critical review. Prog. Energy Combust. Sci. 79, 100843.
 https://doi.org/10.1016/j.pecs.2020.100843
- Herzel, H., Krüger, O., Hermann, L., Adam, C., 2016. Sewage sludge ash A promising secondary
 phosphorus source for fertilizer production. Sci. Total Environ., Special Issue on Sustainable
 Phosphorus Taking stock: Phosphorus supply from natural and anthropogenic pools in the
 21st Century 542, 1136–1143. https://doi.org/10.1016/j.scitotenv.2015.08.059
- Jeon, S., Kim, D.-J., 2018. Enhanced phosphorus bioavailability and heavy metal removal from sewage
 sludge ash through thermochemical treatment with chlorine donors. J. Ind. Eng. Chem. 58,
 216–221. https://doi.org/10.1016/j.jiec.2017.09.028
- Kim, B., Gautier, M., Michel, P., Gourdon, R., 2013. Physical–chemical characterization of sludge and
 granular materials from a vertical flow constructed wetland for municipal wastewater
 treatment. Water Sci. Technol. 68, 2257–2263. https://doi.org/10.2166/wst.2013.485
- Kim, B., Gautier, M., Rivard, C., Sanglar, C., Michel, P., Gourdon, R., 2015. Effect of Aging on
 Phosphorus Speciation in Surface Deposit of a Vertical Flow Constructed Wetland. Environ.
 Sci. Technol. 49, 4903–4910. https://doi.org/10.1021/es506164v

- Kuboňová, L., Langová, Š., Nowak, B., Winter, F., 2013. Thermal and hydrometallurgical recovery
 methods of heavy metals from municipal solid waste fly ash. Waste Manag. 33, 2322–2327.
 https://doi.org/10.1016/j.wasman.2013.05.022
- Li, R., Zhao, W., Li, Y., Wang, W., Zhu, X., 2015. Heavy metal removal and speciation transformation
 through the calcination treatment of phosphorus-enriched sewage sludge ash. J. Hazard.
 Mater. 283, 423–431. https://doi.org/10.1016/j.jhazmat.2014.09.052
- Liu, J., Fu, J., Ning, X., Sun, S., Wang, Y., Xie, W., Huang, S., Zhong, S., 2015. An experimental and
 thermodynamic equilibrium investigation of the Pb, Zn, Cr, Cu, Mn and Ni partitioning during
 sewage sludge incineration. J. Environ. Sci. 35, 43–54.
 https://doi.org/10.1016/j.jes.2015.01.027
- Meng, X., Huang, Q., Xu, J., Gao, H., Yan, J., 2019. A review of phosphorus recovery from different
 thermal treatment products of sewage sludge. Waste Dispos. Sustain. Energy 1, 99–115.
 https://doi.org/10.1007/s42768-019-00007-x
- Nowak, B., Frías Rocha, S., Aschenbrenner, P., Rechberger, H., Winter, F., 2012. Heavy metal removal
 from MSW fly ash by means of chlorination and thermal treatment: Influence of the chloride
 type. Chem. Eng. J. 179, 178–185. https://doi.org/10.1016/j.cej.2011.10.077
- Nowak, B., Pessl, A., Aschenbrenner, P., Szentannai, P., Mattenberger, H., Rechberger, H., Hermann,
 L., Winter, F., 2010. Heavy metal removal from municipal solid waste fly ash by chlorination
 and thermal treatment. J. Hazard. Mater. 179, 323–331.
 https://doi.org/10.1016/j.jhazmat.2010.03.008
- Palacios, E., Leret, P., Fernández, J.F., De Aza, A.H., Rodríguez, M.A., 2012. Synthesis of amorphous
 acid iron phosphate nanoparticles. J. Nanoparticle Res. 14, 1131.
 https://doi.org/10.1007/s11051-012-1131-y
- Raheem, A., Sikarwar, V.S., He, J., Dastyar, W., Dionysiou, D.D., Wang, W., Zhao, M., 2018.
 Opportunities and challenges in sustainable treatment and resource reuse of sewage sludge:
 A review. Chem. Eng. J. 337, 616–641. https://doi.org/10.1016/j.cej.2017.12.149
- Ronda, A., Gomez-Barea, A., Haro, P., de Almeida, V.F., Salinero, J., 2019. Elements partitioning
 during thermal conversion of sewage sludge. Fuel Process. Technol. 186, 156–166.
 https://doi.org/10.1016/j.fuproc.2019.01.001
- Ruttenberg, K.C., 2003. 8.13 The Global Phosphorus Cycle, in: Holland, H.D., Turekian, K.K. (Eds.),
 Treatise on Geochemistry. Pergamon, Oxford, pp. 585–643. https://doi.org/10.1016/B0-08043751-6/08153-6
- Saleh Bairq, Z.A., Li, R., Li, Y., Gao, H., Sema, T., Teng, W., Kumar, S., Liang, Z., 2018. New
 advancement perspectives of chloride additives on enhanced heavy metals removal and
 phosphorus fixation during thermal processing of sewage sludge. J. Clean. Prod. 188, 185–
 194. https://doi.org/10.1016/j.jclepro.2018.03.276
- Schnell, M., Horst, T., Quicker, P., 2020. Thermal treatment of sewage sludge in Germany: A review. J.
 Environ. Manage. 263, 110367. https://doi.org/10.1016/j.jenvman.2020.110367
- Sun, Y., Chen, G., Yan, B., Cheng, Z., Ma, W., 2020. Behaviour of mercury during Co-incineration of
 sewage sludge and municipal solid waste. J. Clean. Prod. 253, 119969.
 https://doi.org/10.1016/j.jclepro.2020.119969
- Vogel, C., Adam, C., 2011. Heavy Metal Removal from Sewage Sludge Ash by Thermochemical
 Treatment with Gaseous Hydrochloric acid. Environ. Sci. Technol. 45, 7445–7450.
 https://doi.org/10.1021/es2007319
- Vogel, C., Adam, C., Unger, M., 2011a. Heavy metal removal from sewage sludge ash analyzed by
 thermogravimetry. J. Therm. Anal. Calorim. 103, 243–248. https://doi.org/10.1007/s10973010-0966-7
- Vogel, C., Exner, R.M., Adam, C., 2013. Heavy Metal Removal from Sewage Sludge Ash by
 Thermochemical Treatment with Polyvinylchloride. Environ. Sci. Technol. 47, 563–567.
 https://doi.org/10.1021/es300610e

- Vogel, C., Kohl, A., Adams, C., 2011b. Spectroscopic Investigation in the Mid- and Far-Infrared
 Regions of Phosphorus Fertilizers Derived from Thermochemically Treated Sewage Sludge
 Ash. Appl. Spectrosc. 65, 265–271. https://doi.org/10.1366/10-06168
- Vogel, C., Krüger, O., Adam, C., 2016. Thermochemical treatment of sewage sludge ash with sodium
 additives under reducing conditions analyzed by thermogravimetry. J. Therm. Anal. Calorim.
 123, 1045–1051. https://doi.org/10.1007/s10973-015-5016-z
- Vogel, C., Rivard, C., Wilken, V., Muskolus, A., Adam, C., 2018. Performance of secondary P-fertilizers
 in pot experiments analyzed by phosphorus X-ray absorption near-edge structure (XANES)
 spectroscopy. Ambio 47, 62–72. https://doi.org/10.1007/s13280-017-0973-z
- Xia, Y., Tang, Y., Shih, K., Li, B., 2020. Enhanced phosphorus availability and heavy metal removal by
 chlorination during sewage sludge pyrolysis. J. Hazard. Mater. 382, 121110.
 https://doi.org/10.1016/j.jhazmat.2019.121110
- Yang, F., Chen, J., Yang, M., Wang, X., Sun, Y., Xu, Y., Qian, G., 2019. Phosphorus recovery from
 sewage sludge via incineration with chlorine-based additives. Waste Manag. 95, 644–651.
 https://doi.org/10.1016/j.wasman.2019.06.029
- Yu, J., Sun, L., Ma, C., Qiao, Y., Xiang, J., Hu, S., Yao, H., 2016. Mechanism on heavy metals
 vaporization from municipal solid waste fly ash by MgCl2²6H2O. Waste Manag. 49, 124–130.
 https://doi.org/10.1016/j.wasman.2015.12.015

454

