

# Mise en œuvre de composites thermoplastiques. *Méthodologie de caractérisation de la déconsolidation et de l'adhésion.*

Arthur Levy arthur.levy@univ-nantes.fr

IN Nantes ✔ Université



June 2022





2006 : Ingénieur Centrale Nantes, matériaux et procédés 2010 : PhD , Ecole Centrale - GeM, Nantes

> 2011 - 12 : Post-doctorate, University of Delaware

Montréal

Delaware

2012 - 14 : Research assistant McGill, Montreal

2014 - 19 : Assistant Professor, LTEN -Polytech, Nantes

Algérie Jl2>

Paris

France

Kingdr

Nantes

Madrid

Casablanca

### Outline

- Nantes, France,
  - Nantes Université / Polytech
  - Laboratoire de Thermique et Energie de Nantes
  - Procédé polymères et composites
- Composite manufacturing
  - Deconsolidation
  - Adhesion



# Nantes



### Nantes (600 000 inhab.)



### A Composite hub in France







### Nantes Université

### Created in 2022.



Second biggest university in France by number of students. The largest University and second most important centre for research in the West of France.



## Nantes Université

- 43,000 students, including 5,000 international students (License - Master – Doctorate)
- 7,800 members of staff including:
  - 4,600 support staff and technicians
  - 3,257 lecturers, lecturer-researchers
- 20 faculties, schools or institutes
- 1,500 (approximately) PhD students
- 42 research structures



### **Engineering Curriculum**



### **Polytech Network**



### THE NETWORK OF FRENCH GRADUATE SCHOOLS OF ENGINEERING

- **15** public graduate engineering faculties
- an alliance with **4** partners schools
- 12 different scientific fields
- 17 500 students
- 90 000 alumni
- 100 partner universities around the world
- 2 000 Masters and Ph.D students





### **Polytech' Nantes**



7 engineering specialities





+ joint degree ETS

#### Laboratoire de Thermique et Energie de Nantes (LTEN)



#### Laboratoire de Thermique et Energie de Nantes (LTEN)







### **Composite team**



Steven Le Corre



Jean-Luc Bailleul



Vincent Sobotka



Elissa El Rassy



Nicolas Boyard





14

### **LTEN** expertise







# Composite manufacturing processes



### **Composite use in aeronautical industry**



### **Today's challenges**

### Increase part complexity



Pylone MATCH project



Boeing assembly line

- Intricate / thick parts
- Large parts
- Assembly

### Cheap / sustainable



www.sabca.be



- Fast and efficient cycles
- Out-of-autoclave
- Defect free

TP composites / robust forming processes

### **TPC** manufacturing processes



### Motivation

# **Industrial goal**: control and optimize forming/assembling processes.

Scientific aim : develop predictive tools (simulation).





# Modelling and characterization of the leading phenomena during :

I – Deconsolidation

II - Adhesion





# I - Deconsolidation





### Luc Amedewovo, Arthur Levy, Steven Le Corre, Laurent Orgeas, Basile de Parscau









### **Industrial context**

# GF / PEI resistance welding



GF/PEI resistance welding

[Shi et al. 16]

I'=

### Thermo stamping



Need for prediction and control

### State of the art hypothesis





## Scientific approach





Development of a characterization bench under processing conditions

## **Existing methods**

### Post-process)

Thickness measurement (caliper)

Density measurement

Microscopy

Infrared thermography

Ultrasounds

Micro-tomography

### On line measurements

ThermoMechanical Analysis (TMA) Optical measurement (image correlation)



# **CODEC** bench

[Amedewovo et al. 22]

### **CODEC** bench









### Validation



**I**<sup>I</sup>EN

 $\Rightarrow$  CODEC bench resolution : ±36 µm

# First results

### **Test procedure**

#### Material **CF/PEKK** (Toray Composites) 348 \* 348 mm\*2,90 mm 16 plis UD à 0° Consolidation • Oven (VbO) • Press 0.005 -0.00 perte de masse (%) -0.01 -0.015 -0.02 -0.025 -0.03

#### Pre-conditionning

- Drying 180°C / 72h
- Ambiant storage 5 months



### **Results press/oven**





## **Results press/oven**







# **Results dry/wet**





## **Results dry/wet**





### **Results dry/wet**



#### Non séché Vc=60°C/min



#### Séché Vc=10°C/min





### Conclusion

### Development of CODEC

Lab scale deconsolidation Representative of manufacturing conditions In situ continuous measurement

### First results on Carbon/PAEK

Effect of moisture Effect of residual stress





# Ongoing work

### In-situ observation in synchrotron (ESRF)



**L**EN



# II – Adhesion kinetics in thermoplastic composite manufacturing







Julien Avenet, Thomas Cender, Arthur Lepoivre, Jean-Luc Bailleul, Steven Le Corre, Arthur Levy



**L**EN





### Thermoplastic composite adhesion



Goal : predict mechanical property of interface
Under processing conditions (high temp., short times)

## Scientific approach





ETS -

# TACOMA welding bench



[Avenet et al, 20]

### **TACOMA** welding bench















Stopped homogeneous welding test

# Mechanical characterization



### **DCB test**



45

# **Kinetics identification**



[Avenet et al, 21]

## **Adhesion regimes**



**L**EN [Avenet et al 21]







#### [Avenet et al 20]

**L**EN

### **Correlation with rheological time**



I'EN

Preprocessing influences weldability



Temps de contact (s)







### Effect of pressure 2









Intimate contact is non-Newtonian

0,0

# Implementation



[Lepoivre, PhD, 2021]





[Lepoivre PhD, 21]



dt

Parametric study, processing window

### Conclusion

Novel welding bench

Procedure for adhesion kinetics identification

Healing can be implemented in simulation tools



# Perspectives





### **Sustainability**

### Material

End of life Recyclability Low tech / footprint

### Manufacturing

Energy efficiency Scraps Consummable





### Acknowledgments

Polytech Nantes, Martine Dubé and Pascal Hubert (for travel funding)

Steven Le Corre and the LTEN lab

Jerome Delmas, Nicolas Lefevre, Arnaud Arrivé, Julien Aubril

arthur.levy@univ-nantes.fr

