

β -chitosan-clay films: Characterization and antibacterial study using response surface methodology

Mohamed Hajjaji, Abdelhakim Alagui, Nicolas Joly, Patrick Martin

► To cite this version:

Mohamed Hajjaji, Abdelhakim Alagui, Nicolas Joly, Patrick Martin. β -chitosan-clay films: Characterization and antibacterial study using response surface methodology. Polymers from Renewable Resources, In press, 10.1177/20412479221128967. hal-03788046

HAL Id: hal-03788046 https://hal.science/hal-03788046

Submitted on 28 Sep 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés. ×

β-chitosan-clays films: Characterization and antibacterial study using response surface methodology

Journal:	Polymers from Renewable Resources
Manuscript ID	PRR-22-0014.R1
Manuscript Type:	Original Article
Date Submitted by the Author:	n/a
Complete List of Authors:	Hajjaji, Mohamed; Cadi Ayyad University Faculty of Sciences Semlalia, Chemistry; University of Cadi Ayyad Alagui, Abdelhakim; Cadi Ayyad University Faculty of Sciences Semlalia, Chemistry Joly, Nicolas; Artois University, Unité Transformations & Agroressources Martin, Patrick; Artois University, Unité Transformations & Agroressources
Keywords:	β -chitosan-clay films, structure, physical/mechanical properties, antibacterial activity, response surface methodology
Abstract:	Properties of the chitosan films can be improved by incorporating clay minerals. So, solvent-cast films of the β -chitosan containing stevensiterich or kaolinitic-illitic clays (up to 50 mass %) were characterized for their structural and mechanical properties. The effects of molecular weight (MW) and deacetylation degree (DD) of chitosan, and the clay/chitosan mass ratio on the inhibition growth of Escherichia coli and Staphylococcus aureus were studied using the response surface methodology (RSM). The films consisted of exfoliated/intercalated or flocculated composites, and the electrostatic bonds formed between the functional moieties of the chitosan and the clay particles active sites essentially influenced their mechanical strength. The results of the study using RSM showed that the optimal value of MW required for the inhibition of the bacteria varied according to the film used, and high antibacterial activity necessitated high DD (89-97%).



1		
3	1	β-chitosan-clays films: Characterization and antibacterial study
4 5	2	using response surface methodology
6 7	3	
8	4	Mohamed Hajjaji ¹ *, Abdelhakim Alagui ¹ , Nicolas Jolv ² , Patrick Martin ²
9 10	5	
11	6	¹ Laboratoire des Sciences des Matériaux et Optimisation des Procédés, Faculté des Sciences
12 13	7	Semlalia, Université Cadi Ayyad, B.P. 2390, Av. Pce My Abdellah, Marrakech 40001,
14	8	Morocco. ² Unité Transformations & Agroressources, UL P7510 , Univ. Artois, Univ. acalle, F. 62408
15 16	9 10	Béthune France
17	11	
18 19	12	Abstract
20 21	13	Properties of the chitosan films can be improved by incorporating clay minerals. So, solvent-
22	14	cast films of the β -chitosan containing stevensite-rich or kaolinitic-illitic clays (up to 50 mass
25 24	15	%) were characterized for their structural and mechanical properties. The effects of molecular
25 26	16	weight (MW) and deacetylation degree (DD) of chitosan, and the clay/chitosan mass ratio on
27 28	17	the inhibition growth of Escherichia coli and Staphylococcus aureus were studied using the
29 30	18	response surface methodology (RSM). The films consisted of exfoliated/intercalated or
31 32	19	flocculated composites, and the electrostatic bonds formed between the functional moieties of
33	20	the chitosan and the clay particles active sites essentially influenced their mechanical strength.
34 35	21	The results of the study using RSM showed that the optimal value of MW required for the
36 37	22	inhibition of the bacteria varied according to the film used, and high antibacterial activity
38 39	23	necessitated high DD (89-97%).
40	24	4
41 42	25	Keywords: β-chitosan-clay films, structure, physical/mechanical properties, antibacterial
43 44	26	activity, response surface methodology
45	27	
46 47	28	
48 49	29	
50 51	30	
52	31	
53 54	32	
55 56	33	
57 58	34	*0 1 1
59 60	35	Correspondence: hajjaji@uca.ma
00	36	

1. Introduction

Chitosan is a deacetylated derivative of the chitin, which is a constituent of shellfish and crustaceans exoskeletons, among others. It is a copolymer composed of β -(1-4)-2-amino-D-glucose and β -(1-4)-2-acetamido-D-glucose units. Three polymorphic forms (α , β and γ) of chitosan are identified. β -chitosan is more soluble and more reactive than α -chitosan,¹ which is the most abundant form. Chitosan is suitable for many practical uses²⁻⁶ because of its non-toxicity, biodegradability, film-forming character, and high density of positive charges associated with the protonated amino-groups. The chitosan exhibited a good antibacterial activity. Referring to some authors, the antibacterial activity of β -chitosan was higher than that of α -chitosan.¹

The inhibition processes depend on chitosan characteristics, mainly its deacetylation degree (DD) and molecular weight (MW), as well as on bacteria strain.⁷⁻⁹ It can be summarized that the higher the DD, the better the inhibition. This fact is linked to the abundance of protonated amino-groups, and to their ability to interact with the specific functional groups of cells membrane macromolecules.¹⁰ The studies dealing with the influence of MW on the inhibition of bacteria growth, such as Escherichia coli, showed different results.¹⁰ Disparate effects of MW on chitosan antibacterial properties were cited elsewhere.¹¹ According to Raoka et al.¹² the effect of MW on the antibacterial activity of chitosan is greater than that of DD.

⁵⁶ Clay minerals, especially those of the smectite group, can be delaminated. So, nano-⁵⁷ sized particles with high-aspect ratio are obtained. Compared to kaolinite and illite, smectite ⁵⁸ minerals have high cation exchange capacity (CEC) and surface area.¹³ Owing to these ⁵⁹ characteristics and to their anionic character, these clay minerals are suitable materials for ⁶⁰ medical and cosmetic purposes.¹⁴

To improve mechanical and barrier properties of chitosan films for drug carrying and food packaging uses, the chitosan was mixed with limited amounts (up to about 5 wt%) of montmorillonite.¹⁵⁻¹⁷ The addition of the montmorillonite (di-octahedral clay mineral of the smectite group) to chitosan resulted in the formation of nanocomposites with efficient bactericidal effects.^{16, 18, 19} So far, no attention has been paid to the study of antibacterial activity of β-chitosan films containing stevensite or kaolinitic-illitic clays. Stevensite is a tri-octahedral swelling clay mineral, which belongs to the smectite group such as montmorillonite. So, chitosan association with limited amount of stevensite should result in intercalated and/or exfoliated nanocomposites formation. The lack of studies related to bacterial inhibition by chitosan-stevensite films could be due to stevensite scarcity. Kaolinite

and illite are non-expandable natural clay minerals,¹³ and chitosan intercalation in the interlayer spaces of their pristine structures could not occur. Thereby, chitosan association with kaolinite or illite should lead to tactoids formation. In such a condition, kaolinite as well as illite behaves like conventional fillers. To obtain chitosan-kaolinite nanocomposites films, some authors prepared exfoliated kaolinite by mechano-chemical treatment.²⁰

The use of β-chitosan-montmorillonite films as bactericidal materials has been ignored in spite of the potential reactivity of β -chitosan, which consists of parallel chains with weak intermolecular bonds.²¹ For the same amount of montmorillonite (up to 5 mass%), β chitosan-based films showed higher tensile strength and Young's modulus than those of α chitosan-based films, and both films manifested similar water solubility.²²

The influences of chitosan characteristic (DD and MW) and clay/chitosan ratio changes on the inhibition of pathogenic bacteria growth have not been investigated, probably because of the numerous experiences required. This drawback could be overcome by using the response surface methodology.²³

In this study, the structure of solvent-casted films composed of β -chitosan and stevensite-rich clay (RH) or kaolinitic-illitic clay (BN2) was examined. Moreover, the changes of the physical/mechanical properties of films according to clay additions were followed. In addition, the growth inhibition of the most prevalent bacteria (Escherichia coli and Staphylococcus aureus) according to chitosan DD, chitosan MW, and clay/chitosan ratio was assessed using the RSM. R

2. Materials and Methods

2.1. β-chitosan

The β -chitosan was prepared from the chitin, extracted from the pens of local squid. For this purpose, finely ground squid pens were demineralized with HCl solution (0.55 N) and deproteinized with heated NaOH solution (80 °C, 0.33 N). The pens powder/solution ratio was 1:10 (w/v). To prepare chitosan, chitin was deacetylated for 24 h using NaOH solution (40 mass%) and standard reflux setup.²⁴ The X-ray diffraction pattern of the prepared chitosan is shown in Fig.1. Taking into consideration the latter trace, and using the Scherrer's equation and the crystallinity index determination method given in Focher et al.,25 the chitosan crystallinity index and apparent crystal size were found to be 77 and 2.1 nm, respectively. Referring to the thermal curve shown in Fig. 2, the chitosan was thermally stable up to about 266°C.

104 The molecular weight (MW) of the chitosan was calculated using the Mark-Houwink 105 equation.²⁶

$$[\eta] = K(MW)^a \qquad (1)$$

¹⁰⁷ η is the intrinsic viscosity, K and a are determined constants. The deacetylation degree (DD) ¹⁰⁸ of the chitosan was determined by potentiometric titration following the experimental ¹⁰⁹ procedure in Tolaimate et al.²⁴, and using the following equation.²⁷

$$DD = \frac{1}{m + 42(V_2 - V_1)N}$$

 $203(V_2 - V_1)N$

 V_1 and V_2 are the volumes of NaOH solution at the first and the second neutralization points.

¹¹² N is the strength of the alkali solution used. m is the weight of the chitosan sample.

114 2.2. Clays

Clays, referenced as RH and BN2, were taken from clay pits located at Jbel Rhassoul (Midelt province, Morocco) and Tetouan-Hoceima province (Morocco), respectively. They consisted of stevensite and an assemblage of kaolinite and illite, respectively. Quartz and carbonates were the main ancillary minerals found. The chemical compositions of RH and BN2 are given in Table 1, and their cation exchange capacities, determined by the cobaltihexamine chloride method²⁸ were 0.8 and 0.3 meq/g, respectively. The decarbonation of clays was done with a buffer acetic acid/Na-acetate solution (pH = 4.74). The carbonate-free clays (particles size $< 80 \,\mu\text{m}$) were sodium-saturated,²⁴ and oven dried at 105 °C.

124 2.3. Chitosan-clay films

Chitosan-clay films (clay/chitosan mass ratio $\leq 100\%$) were prepared with the solvent casting technique.³⁰ For this purpose, sample (≤ 1 g) of the sodium-saturated clay was dispersed in 5 mL of acetic acid (1% v/v) solution, and stirred for 24 h. On the other hand, a portion of chitosan (1 g) was introduced in 100 mL of an acetic acid solution (1 %v/v), and stirred for 2 h. The limpid solution of chitosan was mixed with the clay dispersion, and the mixture was homogenized for 24 h. 25 mL of the mixture was poured in a Petri dish and kept at 30°C for 48 h, so to evaporate water. The film formed was retrieved and soaked with a solution of NaOH (0.5 M) for 12 h, rinsed with distilled water, and dried at 25 °C. The thickness of the films was of about 10 µm.

136 2.4. Physical/mechanical properties of the film

The mass loss of films was determined by weighing disks (~3 cm diameter) before and after immersion in 50 mL of distilled water stirred at 350 rpm for 24 h. The tensile strength and the elongation at break of films were measured on strips according to the ASTM D882,³¹ using an Instron universal machine operating with a crosshead speed of 50 mm/min. The measurements were done in triplicate.

2.5. Analysis techniques

Fourier-transform infrared (FT-IR) analyses were carried out on thin disks composed of 1mg sample and 99 mg KBr. The spectra were recorded with a Perkin Elmer 1725 spectrophotometer functioning in the range of 4000–400 cm⁻¹ at a resolution of 4 cm⁻¹. The Xray diffraction (XRD) analyses were performed on powder samples with a Philips X'Pert MPD diffractometer operating with a copper anode ($\lambda_{K\alpha} = 1.5418$ Å). The step size (°20) and the scan step time were set at 0.013 and 1 s, respectively.

2.6. Percentage inhibition of bacteria growth

To determine the percentage inhibition (PI) of bacteria growth, a bacteria suspension (considered as a blank suspension) was adjusted to 10^5 - 10^6 CFU/mL using sterile saline water (0.9% w/v). A film sample (9 cm²) was introduced in a tube containing 5 mL of nutrient broth, and autoclaved at 120 °C for 20 min. Then, the tube was inoculated with 0.5 mL of the bacteria suspension, and incubated at 37 °C for 24 h. The optical density (OD) of the incubated and the blank suspensions were measured by using an UV-visible spectrophotometer operating at 620 nm.³² These data were used to calculate PI:

- $PI(\%) = \frac{OD \text{ of the blank suspension} OD \text{ of the incubated suspension}}{OD \text{ of the blank suspension}} \times 100$ (2)

2.7. Effects of the chitosan characteristics and the clay/chitosan ratio on the growth inhibition of the bacteria

The weights of the effects of clay/chitosan mass ratio (R), DD and MW on the PI of bacteria were assessed using the RSM and adopting the following model:³³

$$Y = b_o + \sum_{i=1}^{3} b_i X_i + \sum_{i=1}^{3} b_{ii} X_{ii}^2 + \sum_{1 \le i < j}^{3} b_{ij} X_i X_j$$
(3)

Where Y = PI, and b_0 , b_i , b_{ii} and b_{ij} are constant. X_1 , X_2 and X_3 are the coded variables: $X_1 = (R-R_0)/\Delta R$, $X_2 = DD-(DD)_0/\Delta(DD)$ and $X_3 = MW-(MW)_0/\Delta(MW)$. Considering the factors domains investigated: $0 \le R \le 100\%$, $70 \le DD \le 100\%$, $50000 \le MW \le 400000$ g/mol, the factors values at the centers of these domains, and the variation steps were: $R_0 = 0.5$, $(DD)_0 = 85\%$, $(MW)_0 = 225000$ g/mol, and $\Delta R = 0.5$, $\Delta(DD) = 15\%$, $\Delta(MW) = 175000$ g/mol. The Doehlert design and the least-square regression method were adopted for the determination of the constants.^{34,35} The experiments planned according to the Doehlert design and the PI measured (Y₁, Y₂) are given in Table 2.

The validity of the polynomial models was assessed on the basis of the analysis of variance (ANOVA) and checked by the probability plot of residuals.

3. Results and discussion

179 3.1. Structural characterization of the chitosan-clay films

As can be deduced from the typical XRD patterns shown in Fig. 3A, the association of β -chitosan with BN2 clay did not have impact on the position of the basal reflexions of illite $(^{\circ}2\theta = 8.78)$ and kaolinite ($^{\circ}2\theta = 12.48$). So, the interlayer space of both clay minerals remained unchanged, and consequently intercalated composites did not occur in this case. So, tactoid structure took place.³⁶ Considering that the points of zero charge of chitosan and chitosan-clay films (Table 1) were somewhat similar, the surface charge densities of these materials were comparable. So, BN2 particles were layered with chitosan.

Referring to Fig. 3B, the basal X-ray reflexion of the stevensite ($^{\circ}2\theta = 6.02$) vanished as a result of the association of RH clay with β-chitosan. This fact was associated to stevensite delamination caused by excessive expansion of the interlayer due to the excessive insertion of chitosan chains. Such a phenomenon was also observed in the case of mixing montmorillonite (smectite clay mineral) with chitosan.³⁷ Stevensite particles, as was the case with BN2 particles, were coated with chitosan because the pHPZC of stevensite-containing films and chitosan were close (Table 1). However, in this case exfoliated/intercalated structure was formed.

¹⁹⁵ Considering the FT-IR analyses shown in Fig. 4A, the spectrum of the film (b) ¹⁹⁶ consisted of an additional band at 1566 cm⁻¹, which is associated to the protonated amino-¹⁹⁷ groups of chitosan. In addition, the band at 1417 cm⁻¹, which is attributed to the deformation ¹⁹⁸ of the CH₂ in the CH₂OH group of the chitosan, intensified. The bands related to the clay ¹⁹⁹ minerals bonds were not modified. These results allowed the deduction that the functional

groups (-NH₃⁺ and CH₂OH) of the chitosan were involved in its retention by clay particles
surfaces, which are negatively charged.

The comparative examination of FT-IR spectra given in Fig. 4B showed that the band at 1420 cm⁻¹associated to the CH₂ in the CH₂OH group of the chitosan was well distinguished on the spectrum of the film (b), whereas the remaining bands were not affected. So, it was believed that the primary hydroxyl group of chitosan developed hydrogen bonds with stevensite particles, known as anionic clay mineral. These bonds played a key role in the adsorption of the chitosan on the clay particles.

SEM examinations of chitosan-BN2 films showed clay aggregates such as seen in Fig. 5A (micrograph a) together with embedded particles (Fig. 5A, micrograph b). In addition, chitosan-rich zones were identified (Zone 1). These observations allowed the deduction that chitosan-BN2 films consisted of segregated domains and the inter-aggregates spaces were chitosan-rich zones. The SEM observations realized on chitosan-RH films revealed scarce clay aggregates (Fig. 5B, micrograph b), and chitosan-coated clay particles such as shown in Fig. 5B (micrograph b). The scarcity of clay aggregates was associated to the clay exfoliation and the formation of exfoliated/intercalated composites, as previously mentioned.

3.2. Physical/mechanical properties and thermal stability of the films

3.2.1. Films mass loss

The mass loss of films containing up to about 0.15 g of RH/g of chitosan was somewhat constant $(3.5 \pm 0.7 \text{ mass}\%)$ (Fig. 6, curve a). However, it increased almost linearly with the increase of clay content, and the increment was of 10.3xMc (Mc : mass of the clay added). Considering chitosan and clay characteristics (DD = 90%, CEC (cation exchange capacity) = 0.8 meq/g, the estimated amount of glucosamine unit per one gram of β -chitosan was of 5.56x10⁻³ mole, and the quantity of clay active sites was of 8x10⁻⁴ mol/g. Hence, the portion of chitosan bonded to RH particles (0.15 g) was not significant ($\sim 2\%$), and the clay particles were thick-coated with chitosan. In the clay-rich films, a portion of clay particles was scarcely coated with chitosan. So, in such a condition, the clay particles were easily lost.

The mass loss of chitosan-BN2 films, which consisted of up to 0.5 g BN2 per g chitosan, was almost constant (Fig. 6, curve b). However, it increased linearly in the case of clay-rich films. In this case, the mass loss per gram of clay was estimated to be 10.5.

Taking into consideration the DD of chitosan and the CEC of BN2 clay (0.3 meq/ g), together with the fact that the hydroxyls of chitosan were implicated in the association of film constituents, the fraction of chitosan involved in the binding process was estimated to be 10%

for the film containing 0.5 g BN2. Thus, a high amount of chitosan was stacked over the clay
particles, and flocculated composite formed.

In view of the above results, the abundance of flocculated composites in chitosan-clay films contributed to the reduction of clay particles loss.

3.2.2. Thermal stability of the films

The thermal curves of chitosan-BN2 and chitosan-RH films displayed endothermic peaks at 89 and 92°C, and exothermic effects at 277 and 280°C, respectively (Fig. 2). The endotherms were associated to the loss of physisorbed water. The exotherms were assigned to the chitosan decomposition. The relative thermal stability shown by clay-containing films could be associated to the clay characteristics (nanosized structure, high aspect ratio) and to their barrier effect.³⁸

3.2.3. Mechanical properties

Small additions of RH (< ~ 0.14 g/g chitosan, i.e. 12 mass%) to β -chitosan improved the Young's modulus as well as the tensile strength of films (Fig. 7A), but they led to the reduction of the elongation at break and the tensile energy absorption (Fig. 7B). Excessive additions (> 20 wt %) resulted in the decline of the films stiffness.

The tensile strength of the chitosan-BN2 films containing up to about 0.25 g clay /g chitosan increased with respect to that of the chitosan film (Fig. 8A), whereas the Young's modulus (Fig. 8A), the elongation at break and the tensile energy absorption (Fig. 8B) fluctuated. For clay-rich films, the mechanical properties declined for the reasons given below.

In overall, the mechanical properties of polymer-based composites are affected by the inherent characteristics of the components used, the amount and the distribution of fillers, the interfacial bonding as well as by the processing methods.³⁹ Considering chitosan-RH films, the improvement of films mechanical resistance was essentially due to the formation of hydrogen bonds between the chitosan and the delaminated clay particles. In fact, the formation of tough interfaces clay/chitosan facilitated the load transfer across the film, and consequently the stress was homogeneously distributed.⁴⁰ However, as the volume fraction of RH exceeded 1.6% (v/v), the clay addition had a detrimental effect on film mechanical resistance. It was believed that because of the swelling character of RH clay, the clay-rich films were the object of microcraks due to the drying shrinkage. The formation of such

defects together with the uneven distribution of the clay particles could be responsible for thedecline of mechanical strength.

For BN2-containing films, the presence of the aforementioned electrostatic forces seemed to play a main role in the improvement of mechanical resistance of films with clay fraction < 3.2% (v/v). Further clay additions resulted in a drop of mechanical strength, possibly because of the flocculation and/or the heterogeneous distribution of clay particles.

3.3. Kinetics of the growth inhibition of the bacteria

Referring to the kinetics curves given in Fig. 9A, PI of the *E. coli* growth by the films approximated 90 to 100% after 24 h. The kinetics of the inhibition of the bacteria growth followed the pseudo-first order equation:

$$(PI)_t = (PI)_e e^{-kt} \tag{4}$$

(PI)_t and (PI)_e are the instantaneous and the equilibrium percentages inhibition of the *E. coli* growth, respectively, k and t are the rate constant and time. The estimated values of k were of 3.12x10⁻⁵ s⁻¹ and 3.45x10⁻⁵ s⁻¹ for RH- and BN2- containing films, respectively. Based on the linear evolution of $PI = f(\sqrt{time})$ curves, the kinetics of the inhibition process was chiefly controlled by the diffusion process.⁴¹ which seemed to be affected by the closest environment of cells (boundary layer). The diffusion process likely represented the leakage of vital intracellular substances, as the interaction between the chitosan and the negatively charged phospholipid bilayer of the bacterium has a detrimental effect on membrane permeability.10,18,19

Taking into consideration the curves shown in Fig. 9B, the kinetics of the inhibition of the *S. aureus* growth by the RH-chitosan film was relatively slow, but for both films, the change of the PI versus time fitted better the following linear form of the pseudo-second kinetics equation:

$$\frac{t}{(PI)_t} = \frac{t}{(PI)_e} + \frac{1}{k_2(PI)_e^2}$$
(5)

 k_2 is the rate constant. (PI)_t, (PI)_e and t kept the same meaning. The values of k_2 were determined to be 3.17×10^{-2} and 5.88×10^{-2} /s.(%) for RH- and the BN2-based films, respectively.

In view of the above results, the kinetics of inhibition process was mainly dependent on the interaction between microorganisms and film constituents, mainly chitosan. Indeed, according to some authors,¹⁰ the lipoteichoic acid, which is a constituent of the cell wall of the 301 gram-positive bacteria, such as the *S. aureus*, can interact with chitosan, and results in the 302 disturbance of the cell membrane functions. The built up of chitosan around the cell wall 303 might impede the entrance of nutriments and the release of residue by the cell. Therefore, cell 304 metabolism was drastically altered. On the other hand, the PI of the *E. coli* was controlled by 305 diffusion, seemingly owing to the loss of the selective permeability of the cell membrane. 306 This fact was attributed to the interaction between the anionic groups of bacterial membrane 307 lipopolysaccharide and the protonated amino-groups of chitosan.¹⁰

3.4. Evaluation of the effects of the factors studied on the bacteria inhibition

The ANOVA results (Table 3) showed that the F-ratio was somewhat high and the statistical significance was smaller than 0.05, which is considered as the maximum limit to assert the validity of the proposed model.⁴² So, the variations of PI (Yi) of the bacteria by both films as a function of the coded variables related to R, DD and MW were adequately described by the following equations:

 Y_1 (Chitosan-RH/*E. coli*) = 45.3+5.0 X_1 +27.7 X_2 -21.2 X_3 +36.5 X_1X_2 -34.7 X_1X_3 -50.2 X_2X_3 316 -40.6 X_1^2 -25.8 X_2^2 -15.6 X_3^2 (6)

317 Y₂ (Chitosan-RH/*S. aureus*)= 43.8-1.0 X₁+28.4 X₂-21.3 X₃ +53.6 X₁X₂-22.5X₁X₃-61.0X₂X₃ -318 29.0X₁²-10.4X₂²-29.8X₃² (7)

319 Y₁ (Chitosan-BN2/*E. coli*) = 95.2-42.9X₁+27.6X₂+13.7 X₃ -35.7X₁X₂- 53.8X₁X₃+7.6X₂X₃ -320 45.5X₁²-66.8X₂²-62.2X₃² (8)

321 Y₂ (Chitosan-BN2/*S. aureus*) = 97.2-6.4X₁+39.2X₂+57.1X₃ -5.1X₁X₂-2.0X₁X₃-18.5X₂X₃ -322 9.8X₁² -65.0X₂²-54.2X₃² (9)

The validity of these models was also assessed by the probability plot of residuals.³⁵ The almost linear distribution of the residuals, shown in Fig. 10, supported the adequacy of these polynomial models.

The comparison of the algebraic values of the linear terms b_2X_2 (equations 6-9) pointed out that the increase of DD, which is correlated to the increase of the chitosan amino-groups amount, improved the inhibition growth of both strains of bacteria. This result was in conformity with the above discussion that is the amino-groups were the main functional moieties involved in the inhibition of the bacteria growth. Considering the linear terms of the equations 6 and 7, the weights of the studied factors effects on PI followed the order: DD > MW > R. Moreover, PI using chitosan-RH films decreased with the increase of MW. In contrast, it increased with the use of chitosan-BN2 films (equations 8 and 9). These results supported the disparate effects of MW on the bactericidal activity.¹⁰ Recalling the above

 equations, the weight of the effect of R on PI was relatively low, except in the case of the equation 8 where the increase of R resulted in the decline of PI.

Taking into consideration the $b_{ii}X_iX_i$ terms of the equations 6, 7 and 9, the most important influencing interaction was that occurring between DD and MW. This interaction was categorized as an antagonistic one because the simultaneous rise of DD and the decrease of MW or vice-versa should result in the increase of PI. A typical response surface representing the antagonistic effect of the interaction between DD and MW is shown in Fig. 11a. In the case of the equation 8, R and MW interacted antagonistically and their interaction had the prominent effect on PI. The response surface showing the variation of PI against R and MW is given in Fig. 11b.

The optimal operating factors for high inhibition of the bacteria growth, which were determined by using the desirability function approach, are given in Table 4. Based on these results, the films composed of chitosan with high DD should inhibit the growth of both bacteria strains, as previously documented. In addition, the films consisting of about 40 mass% RH of chitosan with low to moderate MW should be highly effective against the tested bacteria. In the case of the chitosan-BN2 films, the use of chitosan with high MW is one of the operating conditions for high inhibition of the bacteria growth.

Considering the PI = f(clay/chitosan) curves plotted on the basis of the equations 6-9 (Fig. 12), the antibacterial effect of the chitosan film was less important as compared to that of the chitosan-RH films, which consisted of exfoliated/intercalated composites. In contrast, it was almost equivalent or somewhat better than that of the chitosan-BN2 films, which were composed of tactoids.

4. Conclusions

Stevensite-containing chitosan films consisted of exfoliated/intercalated nanocomposites, and the association between the films components were presumably achieved through hydrogen bonding. Limited additions of RH (up to 0.14 g /g chitosan) improved films tensile strength and Young's modulus, but they had a negative impact on their elongation at break.

Chitosan films containing kaolinitic-illitic clay were essentially composed of flocculated composites. The amino-groups together with the hydroxyls of chitosan were involved in its association with the clay particles. The addition of BN2 clay (up to 0.25 g BN2/g chitosan) improved the mechanical strength of films. The results of the kinetics of the bacteria growth inhibition by the studied films allowed the deduction that the inhibition process depended on the bacterial strain. In the case of *E. coli*, the cell membrane seemed to be damaged due to its interaction with the protonated amino-groups of chitosan, and the vital substances flowed out. For *S. aureus*, the nutrients seemed to be impeded to get into the cells because of the stack of chitosan over their membranes.

The polynomial models obtained by using the RSM allowed the prediction of the effects of the factors studied and of their mutual interactions on PI. The rise of MW resulted in the decrease of the PI of *E. coli*, but it increased that of the *S. aureus*. The increase of DD yielded to the rise of PI, and the optimal value should be in the range of 89-97%. Based on the RSM results, the antibacterial activity of the chitosan film was a good as that of the tactoidrich films. However, it was less significant as compared to that of the films composed of exfoliated/interacted clay.

382 Acknowledgement

This work was supported by the CNRST (grant number PPR/26/2015).

References

- Van Hoa N, Vuong NTH, Minh NC, et al. Squid pen chitosan nanoparticles: small
 size and high antibacterial activity. *Polymer Bulletin* 2021; 78: 7313–7324.
- 2. Choi C, Nam JP and Nah JW. Application of chitosan and chitosan derivatives as
 biomaterials. *J Ind Eng Chem* 2016; *33*: 1–10.
- 391 3. Dutta PK, Dutta J and Tripathi VS. Chitin and chitosan: Chemistry, properties and
 392 applications. *J Sci Ind Res* 2004; 63: 20-31.
- Islam S, Rahman Bhuiyan MA and Islam MN. Chitin and chitosan: Structure,
 properties and applications in biomedical engineering. *J Polym Environ* 2017; 25:
 854–866.
- 396 5. Mahmoud MG, El Kady E and Asker, MS. Chitin, chitosan and glucan, properties and
 397 applications. *World J. Agri. Soil. Sci.* 2019; 3(1). DOI:
 398 10.33552/wjass.2019.03.000553.
 - https:/

1 2			
2 3 4 5	399 400	6.	Rinaudo M. Chitin and chitosan: properties and applications. <i>Prog Polym Sci</i> 2006; 31: 603–632.
6 7	401	7.	Walke S Srivastava G Nikalie M et al Physicochemical and functional
8	101		characterization of chiteson propored from chrisme shalls and investigation of its
9 10	402		characterization of chitosan prepared from shrimp shells and investigation of its
10	403		antibacterial, antioxidant and tetanus toxoid entrapment efficiency. Int J Pharm Sci
12	404		<i>Rev Res</i> 2014; 26(2): 215-225.
13 14	405	8.	Wang W, Xue C and Mao X. Chitosan: Structural modification, biological activity and
15 16	406		application. Int J Biol Macromol 2020; 164: 4532–4546.
17 18 10	407	9.	Confederat LG, Tuchilus CG, Dragan M, et al. Preparation and antimicrobial activity
20	408		of chitosan and its derivatives: A concise review, Molecules 2021; 26: 3694.
21	409	10.	Kong M. Chen XG. Xing K. et al. Antimicrobial properties of chitosan and mode of
22	410		action: A state of the art review. Int J Food Microbiol 2010; 144: 51–63.
24 25	411	11	Li I and Zhuang S. Antibacterial activity of chitosan and its derivatives and their
26	111		interaction machanism with bosteric: Current state and perspectives. Fur Dehm I
27 28	412		interaction mechanism with bacteria. Current state and perspectives. Eur Totym 5
29	413		2020; 138: 109984. DOI: 10.1016/j.eurpolymj.2020.109984.
30 31 22	414	12.	Rajoka MSR, Mehwish HM, Wu Y, et al. Chitin/chitosan derivatives and their
32 33	415		interactions with microorganisms: a comprehensive review and future perspectives.
34 35	416		Critical Reviews in Biotechnology 2020; 40(3): 365-379.
36 37	417	13.	Murray HH. Applied clay mineralogy-occurrences, processing and applications of
38	418		kaolins bentonites palvgorskite-sepiolite and common clays Development in clay
39 40	110		azionas 2. Elsevier 2007
40 41	419		science 2, Eisevier, 2007.
42	420	14.	Carretero MI and Lagaly G. Clays and health: An introduction. Appl Clay Sci 2007;
43 44	421		36: 1–3.
45	422	15.	De Azeredo HMC. Nanocomposites for food packaging applications. J Int Food Res
46 47	123		2009: 42: 1240–1253
48	423		
49 50	424	16.	Han Y-Su, Lee S-H, Choi KH, et al. Preparation and characterization of chitosan–clay
51	425		nanocomposites with antimicrobial activity. J Phys Chem Solids 2010; 71: 464-467.
52 53	426	17.	Qu B and Luo Y. A review on the preparation and characterization of chitosan-clay
54 55	427		nanocomposite films and coatings for food packaging applications. Carbohydrate
56	428		Polymer Technologies and Applications 2021; 2: 100102. DOI:
57	429		10 1016/i carpta 2021 100102
58 59	427		10.1010/J.output.2021.100102.
60			

Chandrasekaran M, Kim KD and Chun SC. Antibacterial activity of chitosan 18. nanoparticles: A Review. Processes 2020; 8: 1173. DOI:10.3390/pr8091173. 19. Kassem A, Ayoub GM and Malaeb, L. Antibacterial activity of chitosan nano-composites and carbon nanotubes: A review. Sci Total Environ 2019; 668: 566-576. 20. Neji AB, Jridi M, kchaou H, et al. Preparation, characterization, mechanical and barrier properties investigation of chitosan-kaolinite nanocomposites. *Polymer Testing* 2020; 84: 106380. DOI: 10.1016/j.polymertesting. 2020.106380. Kurita K, Tomita K, Tada T, et al. Squid chitin as a potential alternative chitin source: 21. Deacetylation behavior and characteristic properties. J Polym Sci Part A-1: Polym Chem 1993; 31: 485-491. Mourak A, Hajjaji M, Alagui A, et al. Effects of geomaterial-originated fillers on 22. microstructure and mechanical/physical properties of α - and β -chitosan-based films. Molecules 2021; 26: 7514. DOI: 10.3390/molecules26247514. Khalfaoui A, Hajjaji M, Kacim S, et al. Evaluation of the simultaneous effects of 23. firing cycle parameters on technological properties and ceramic suitability of a raw clay using the response surface methodology. J Am Ceram Soc 2006; 89 (5): 1563-1567. Tolaimate A, Desbrières J, Rhazi M, et al. A. Contribution to the preparation of chitins 24. and chitosans with controlled physicochemical properties. Polymer 2003; 44: 7939-7952. Focher B, Beltranme PL, Naggi A, et al. Alkaline N-deacetylation of chitin enhanced 25. by flash treatments. Reaction kinetics and structure modifications. Carbohydr Polym 1990; 12: 405-418. Maghami GG and Roberts GAF. Evaluation of the viscometric constants for chitosan. 26. Makromol. Chem. 1988; 189: 195-200. Gupta KC and Jabrail FH. Effects of degree of deacetylation and cross-linking on 27. physical characteristics, swelling and release behavior of chitosan microspheres. Carbohydrate Polymers 2006; 66: 43-54. Aran D, Maul A and Masfaraud J-F. A spectrophotometric measurement of soil cation 28. exchange capacity based on cobaltihexamine chloride absorbance. C. R. Geoscience 2008;340:865-871.

1			
3	461	29.	Lagaly G. Colloid clay science. In: Bergaya, F.; Theng, BKG.; and Legally, G.(eds)
4 5	462		Handbook of Clay Science-Developments in Clay Science. Elsevier, 2006, p.141.
6 7	463	30.	Tang ZG, Black RA, Curran JM, et al. Surface properties and biocompatibility of
8	464		solvent-cast poly[e-caprolactone] films. <i>Biomaterials</i> 2004; 25: 4741–4748.
9 10	465	31.	ASTM D882-18.Standard Test Method for Tensile Properties of Thin Plastic Sheeting;
11 12	466		ASTM International: West Conshohocken, PA, USA, 2018.
13 14	467	32.	Muloiwa M, Nyende-Byakika S and Dinka M. Comparison of unstructured kinetic
15	468		bacterial growth models. S Afr J Chem Eng 2020; 33: 141–150.
16 17	469	33.	El Hafid K, and Hajjaji M. Geopolymerization of glass- and silicate-containing heated
18 19	470		clay. Constr Build Mater 2018; 159: 598–609.
20	471	34.	Ferreira SLC, dos Santos WNL, Quintella CM, et al. Doehlert matrix: a chemometric
21 22	472		tool for analytical chemistry-review. <i>Talanta</i> 2004 ; 63 : 1061–1067.
23 24	473	35.	Mathieu D. Phan Tan Luu, R. Software NEMROD, Université d'Aix, Marseille III.
25	474		France 1980
26 27	475	36	Ou B and Luo Y A review on the preparation and characterization of chitosan-clay
28 29	476	50.	nanocomposite films and coatings for food nackaging applications <i>Carbohydrate</i>
30 31	177		Polymer Technologies and Applications 2021: 2: 100102
32	478	37	Darder M. Colilla M and Eduardo Ruiz-Hitzky F. Biopolymer-clay papocomposites
33 34	470	57.	based on chitosan intercalated in montmorillonite. <i>Chem Mater</i> 2003: 15: 3774–3780
35 36	47.7		bused on entrosan interculated in montholine. Chem Mater 2005, 15. 5774 5760.
37	480	38.	Leszczynska A, Njuguna J, Pielichowski K, et al. Polymer/montmorillonite
38 39	481		nanocomposites with improved thermal properties. Part II: Thermal stability of
40 41	482		montmorillonite nanocomposites based on different polymeric matrixes. Thermochim.
42	483		Acta 2007: 454 : 1–22.
43 44	484	39.	Tiong SC. Structural and mechanical properties of polymer nanocomposites. <i>Mater Sci</i>
45 46	485		<i>Eng R Rep</i> 2006; 53: 73–197.
47	486	40.	Rhim JW, Hong SI, Park HM, et al. Preparation and characterization of chitosan-based
48 49	487		nanocomposite films with antimicrobial activity. J Agric Food Chem 2006: 54: 5814-
50 51	488		5822.
52	100	4.1	
55 54	489	41.	Ismadji S, Edi Soetaredjo F and Aning Ayucitra A. Clay materials for environmental
55 56	490		remediation. Springer, 2015, p.113.
57 58			
59			

42. Myers RH, Montgomery DC and Anderson-Cook CM. Response surface methodology: process and product optimization using designed experiments, 4th Edition Joh.

for per peries



Figure 1. X-ray diffraction trace of the prepared chitosan.



Figure 2. Thermal curves of the prepared chitosan, BN2- chitosan (a) and RH-chitosan (b) films. (clay/chitosan mass ratio: 0.25/1).



Figure 3. XRD patterns of the clays (**a**, **a**'), the sodium-loaded clay fractions (**b**, **b**') and the chitosan-clay films (**c**, **c**'). (**A**) and (**B**) are associated to BN2 and RH, respectively. I: illite, K: kaolinite, Q: quartz, C: calcite, D: dolomite, St: stevensite, G: gypsum. (clay/chitosan mass ratio: 1/1).



Figure 4. F1-IR spectra of the clay fractions (**a**, **a**'), the chitosan-clay films (**b**, **b**'), and the β - chitosan (**c**, **c**'). (**A**) and (**B**) are related to BN2 and RH, respectively. CM: clay minerals, Chit: chitosan, W: water, Q: quartz, S: silicates, St: stevensite. (clay/chitosan mass ration: 1/1)



Figure 5. SEM micrographs of chitosan-BN2 (A) and chitosan-RH (B) films, and EDS spectra of different areas. Zone 1 (A) and zones 2 (B) are chitosan-rich domains. Zone 2 (A) and zone 1 (B) are clay-rich areas.



Figure 6. Variation of the mass loss of films vs. the clay content. (a) chitosan-RH film,(b) chitosan-BN2 film.



Figure 7. Variation of the mechanical properties of the chitosan-RH films as a function of the clay content. **A**: Young's modulus and tensile strength; **B**: Elongation at beak and tensile energy absorption.



Figure 8. Evolution of the mechanical properties of the chitosan-BN2 films versus the clay content. **A**: Young's modulus and tensile strength; **B**: Elongation at beak and tensile energy absorption.



Figure 9. Kinetics curves associated to the inhibition growth of *E. coli* (**A**) and *S. aureus* (**B**) by the chitosan-RH (**a**) and the chitosan-BN2 (**b**) films.





Figure 10. Probability plots of residuals related to the models used.



Figure 11. Variations of the percentage of inhibition of *E. coli* (Y₁ (Chitosan-RH), Y₁ (Chitosan-BN2)) against the factors studied. (**a**): clay/chitosan mass ratio (R) = 0.5; (**b**): deacetylation degree (DD) = 85%.



Figure 12. Variation of the percentage inhibition of the bacteria growth by the prepared films versus clay/chitosan mass ratio. DD = 85%, MW = 225000 g/mol.

Perez.

Table 1. Chemical compositions (mass%) of the raw clays used, and pH_{PZC} of the basicmaterials and the studied chitosan-clay films.

		С	hemical com	positions				
	SiO ₂	Al ₂ O ₃	Fe ₂ O ₃	MgO	CaO	K ₂ O	SO ₃	
BN2	48.1	16.5	7.3	4.5	19.4	2.8	1.4	
RH	58.1	4.8	2.3	22.6	6.6	1.1	4.5	
			pH _{PZC}	2				
Chi	tosan	BN2		RH	Chit	osan-clay f	ĩlms	
6	5.0	9.1		8.0		6.6 ± 0.3		

Table 2. Experimental design matrix and the measured percentage inhibition (Y_i) of the bacteria (*E. coli* and *S. aureus*) by the films prepared.

				Chitosa	n-RH film	Chitosan-BN2 film		
Run	X ₁	X ₂	X ₃	Y ₁ (%)	Y ₂ (%)	Y ₁ (%)	Y ₂ (%)	
				E. coli	S. aureus	E. coli	S. aureus	
1	1.0000	0.0000	0.0000	0.00	0.00	0.00	75.36	
2	-1.0000	0.0000	0.0000	9.48	29.60	99.31	99.43	
3	0.5000	0.8660	0.0000	62.93	80.17	96.54	87.68	
4	-0.5000	-0.8660	0.0000	0.29	23.85	0.00	0.00	
5	0.5000	-0.8660	0.0000	0.00	0.00	0.00	0.00	
6	-0.5000	0.8660	0.0000	0.00	11.21	98.39	96.56	
7	0.5000	0.2887	0.8165	0.00	0.00	0.00	94.56	
8	-0.5000	-0.2887	-0.8165	3.74	0.00	22.81	0.00	
9	0.5000	-0.2887	-0.8165	19.83	5.75	35.71	6.02	
10	0.0000	0.5774	-0.8165	100.00	98.56	12.90	0.00	
11	-0.5000	0.2887	0.8165	19.54	0.00	95.62	94.84	
12	0.0000	-0.5774	0.8165	0.00	0.00	42.86	96.28	
13	0.0000	0.0000	0.0000	44.64	44.64	94.47	99.14	
14	0.0000	0.0000	0.0000	43.40	41.95	95.39	95.42	
15	0.0000	0.0000	0.0000	45.48	42.82	95.39	97.99	
16	0.0000	0.0000	0.0000	46.07	43.87	95.62	97.13	
17	0.0000	0.0000	0.0000	46.98	45.98	95.16	96.56	

Significance

< 0.01

< 0.01

< 0.01

< 0.01

		Sources of	Sum of	Degrees of	Mean	F-rati
		variation	squares	freedom	square	
	Y ₁	Regression	11555.4	9	1283.9	4.4
film		Residues	2046.3	7	292.3	
RH		Total	13601.7	16		
an-	Y ₂	Regression	12544.9	9	1393.9	5.1
nitos		Residues	1919.1	7	274.1	
G		Total	14464.0	16		
	Y ₁	Regression	27542.2	9	3060.2	11.9
N2 film		Residues	1793.1	7	256.2	
		Total	29335.3	16		
an-B	Y ₂	Regression	28572.5	9	3174.7	8.9
iitos		Residues	2499.4	7	357.1	
C		Total	31071.9	16		

alidity of the models

Table 4. Optimal operating factors for total inhibition of the bacteria growth determined by using the desirability function approach.

	X ₁	R	X ₂	DD (%)	X ₃	MW (g/mol)
Y ₁ (Chitosan-RH/ <i>E. coli</i>)	0.3554	0.68	0.6404	95	-0.6808	105557
Y ₂ (Chitosan-RH/S. aureus)	0.4572	0.73	0.7726	97	-0.4405	147917
Y ₁ (Chitosan-BN2/ <i>E. coli</i>)	-0.4861	0.26	0.6962	95	0.5282	317430
Y ₂ (Chitosan-BN2/S. aureus)	0.6617	0.83	0.2956	89	0.6890	354370