



HAL
open science

Electrical diagnostics for Dielectric Barrier Discharges

Clémence Tyl, Antoine Belinger, Simon Dap, Nicolas Naudé

► **To cite this version:**

Clémence Tyl, Antoine Belinger, Simon Dap, Nicolas Naudé. Electrical diagnostics for Dielectric Barrier Discharges: From integrated measurements to spatially resolved measurements. Benefits for plasma processes at atmospheric pressure?. Plathinium 2021 (Plasma Thin Film International Union Meeting), Sep 2021, Virtual, France. hal-03799295

HAL Id: hal-03799295

<https://hal.science/hal-03799295>

Submitted on 5 Oct 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Electrical diagnostics for Dielectric Barrier Discharges: from integrated measurements to spatially resolved measurements. Benefits for plasma processes at atmospheric pressure?

Clémence Tyl, Antoine Belinger, Simon Dap, Nicolas Naudé

LAPLACE, Université de Toulouse, CNRS, INPT, UPS, 31062 Toulouse, France

Abstract:

Dielectric Barrier Discharges (DBDs) can be used in many processes as thin-film coating, sterilization, treatment of gases, aerodynamic flow control, and lighting devices [1]. Depending on the gas, electrical operation parameters and discharge geometry, the plasma operates in the classical filamentary mode or in a homogeneous regime [2]. Electrical measurements are a more convenient than optical measurements to characterize the discharge regime and to study the discharge behavior. However, and because of the dielectric presence, it is not possible to directly measure the electrical parameters of the discharge. Usually, the electrical parameters are calculated from the measured quantities under usage of an electrical equivalent circuit [4]. The key parameter for this approach is the determination of the discharge area, which is usually considered to be equal to the electrode surface as long as the discharge is homogeneous. However, even if the plasma seems to cover the electrodes uniformly, its electrical properties (current density, breakdown voltage, duration of discharge, ...) are not exactly the same at any time and at any point of the surface. For example, when a gas flow is injected from one side of the planar DBD arrangement, the species densities are not the same along the gas flow because of the kinetic processes and chemical reactions in the discharge [4]. Thus, the discharge current and the gas voltage are not uniform along the spatial DBD dimensions. Therefore, determination of discharge current and gas voltage from macroscopic parameters of the DBD is often inaccurate.

In order to have a more accurate characterization of the discharge behavior, a measurement of the local current density is required. To get a 2D mapping of the discharge electrical parameters, the ground electrode is prepared as a segmented electrode with 64 equally spaced square segments. The high voltage electrode still remained full. This electrode is a $3 \times 3 \text{ cm}^2$ square, while each square of the segmented electrode has a 3.44 mm side length, a distance of $350 \mu\text{m}$ spaced each segments. A prototype, using a ground electrode divided into 64 identical squares and a data acquisition system has been developed [5]. This system can be used to study the spatial electrical behavior of a DBD. It has been successfully validated on planar DBD by the comparison with short exposure time photos taken by a camera from above the discharge cell [5]. It has been used to study the diffuse discharge (APTD) and shows the effect of a gas flow on the local electrical behavior of the discharge. In the case of diffuse DBDs with sinusoidal voltages at frequencies from 1 to 20 kHz, the temporal and spatial resolutions are high enough to characterize the behavior of the discharge with sufficient spatial information.

This electrode arrangement and measuring systems allows a 2D mapping of the discharge electrical parameters (discharge current, power dissipated, gas voltage, etc.) of Townsend but also for Glow discharges, hybrid or patterned regimes. Concerning the plasma processes for surface coatings, this system can be used to monitor the evolution of the local discharge power which defines the local deposition rate. If we use this segmented electrode as the high voltage electrode with adequate power supply, we could reconfigure the electrode and the power transfer to the discharge. Then this system could be used to realized patterns. All of this opens up new directions which will be discussed during the presentation.

References:

1. U. Kogelschatz, *Plasma Chem Plasma P* 23 (1), 1-46 (2003).
2. R. Brandenburg, *Plasma Sources Science and Technology* 26 (5), 053001 (2017).
3. A. V. Pipa, J. Koskulics, R. Brandenburg and T. Hoder, *Rev Sci Instrum* 83 (11), 115112 (2012).
4. C. Tyl, X. Lin, M. C. Bouzidi, S. Dap, H. Caquineau, P. Segur, N. Gherardi and N. Naudé, *J Phys D Appl Phys* 51 (35) (2018).
5. C. Tyl, S. Martin, C. Combettes, G. Brillat, V. Bley, A. Belinger, S. Dap, R. Brandenburg, N. Naudé, *Rev Sci Instrum* 92 (5), 053552 (2021).