



HAL
open science

Ultrafast laser writing stabilized by nonlinear absorption

Pol Sopenña, Mario García-Lechuga, Andong Wang, David Grojo

► **To cite this version:**

Pol Sopenña, Mario García-Lechuga, Andong Wang, David Grojo. Ultrafast laser writing stabilized by nonlinear absorption. The 23rd International Symposium on Laser Precision Microfabrication – LPM2022, 2022, Dresde, Germany. hal-03817206

HAL Id: hal-03817206

<https://hal.science/hal-03817206>

Submitted on 17 Oct 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Ultrafast laser writing stabilized by nonlinear absorption

Pol Sopeña^{*1}, *Mario García-Lechuga*², *Andong Wang*¹, *David Grojo*¹

1-Aix-Marseille Université, CNRS, LP3, UMR7341, 13009 Marseille, France

2- Laser Processing Group, Instituto de Óptica, IO-CSIC, 28006 Madrid, Spain

**pol.sopena-martinez@univ-amu.fr*

The concept of nonlinear resolution exploited in optical microscopy does not directly translate in ultrafast material processing since the size of the produced modifications is primarily defined by an incoming fluence threshold independently on nonlinear energy deposition [1]. This leads to feature geometries corresponding to the beam contour at this threshold condition. Such description holds for processes like ablation or structural modification. Accordingly, high-resolution patterns can be achieved when working with very tightly focused beams at peak fluence close to these conditions. However, supported by a noise model and ablation experiments we described how the process becomes increasingly unreliable due to pulse-to-pulse energy fluctuations as we approach the fluence threshold. This quantifies the inherent contradiction between precision and reproducibility in such a configuration [2].

Varying the level of laser energy fluctuations in our experiment, we demonstrate in this work the validity of the noise model to describe the production of amorphous spots on crystalline Si with single femtosecond pulses. In this way, we can precisely assess the precision limits imposed by the laser stability performance. To surpass this limit there are several methods to reduce pulse-to-pulse energy fluctuations. These include dynamically controlled Pockels cells [3] or Kerr interactions [4]. Alternatively, we propose a more straightforward passive extra-cavity approach based on high-order nonlinear absorption of the beam through transparent materials [5]. We show this simple configuration can be accounted in the model and results in a reduction of the feature size fluctuations through energy stabilization.

In this regard, we first study the stabilization response of several materials (including ZnSe, Si, or sapphire) to our femtosecond laser source (1030nm, <200fs). The best compromise between absorption and stabilization is found for a ZnS crystal, proving a reduction of laser fluctuations of 1/5. Then, using an incoming laser fluctuation of 2% (SD, Gaussian noise), we demonstrate an enhanced feature repeatability and writing performance at near-threshold conditions that are unachievable without stabilization [6]. In particular, the method allows reliable writing at energies just 1% above the threshold. The feature size obtained with large beams at these conditions is one tenth of the beam spot, which should directly translate in stable features of around 10 nm with tightly focused beams. In this regard, the implementation of our simple scheme holds potential for contributions in the most demanding precision manufacturing applications. These today remain addressed by extreme UV lithography and/or focused ion beam and likely represent the next challenge of ultrafast laser processing.

Acknowledgement: This work is funded by H2020 European Research Council (724480).

[1] M. García-Lechuga, O. Utéza, N. Sanner and D. Grojo, Evidencing the nonlinearity independence of resolution in femtosecond laser ablation, *Opt. Lett.* 45, 952, (2020).

[2] M. Garcia-Lechuga, G. Gebrayel El Reaidy, H. Ning, P. Delaporte and D. Grojo, Assessing the limits of determinism and precision in ultrafast laser ablation, *Appl. Phys. Lett.* 117, 171604, (2020).

[3] T. Oksenhendler, F. Legrand, M. Perdrix, O. Gobert and D. Kaplan, Femtosecond laser pulse energy self-stabilization, *Appl. Phys. B* 79, 933, (2004).

[4] S. Matsuo, L. Yan, J. Si, T. Tomita and S. Hashimoto, Reduction of pulse-to-pulse fluctuation in laser pulse energy using the optical Kerr effect, *Opt. Lett.* 37, 1646, (2012).

[5] R. H. Pantell and J. Warszawski, Laser power stabilization by means of nonlinear absorption, *Appl. Phys. Lett.* 11, 213, (1967).

[6] P. Sopeña, M. García-Lechuga, A. Wang and D. Grojo, Ultrafast laser stabilization by nonlinear absorption for enhanced-precision material processing, *Opt. Lett.* 47, 993-996 (2022).