

The effect of speech degradation on the ability to track and predict turn structure in conversation

Céline Hidalgo, Isaïh Mohamed, Christelle Zielinski, Daniele Schön

▶ To cite this version:

Céline Hidalgo, Isaïh Mohamed, Christelle Zielinski, Daniele Schön. The effect of speech degradation on the ability to track and predict turn structure in conversation. Cortex, 2022, 151, pp.105-115. 10.1016/j.cortex.2022.01.020 . hal-03823231

HAL Id: hal-03823231 https://hal.science/hal-03823231v1

Submitted on 20 Oct 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

- 1 Title: The effect of speech degradation on the ability to track and predict turn structure in
- 2 conversation
- 3 Céline Hidalgo¹, Isaïh Mohamed¹, Christelle Zielinski², Daniele Schön¹
- 4 ¹ Aix Marseille Univ, Inserm, INS, Inst Neurosci Syst, Marseille, France
- ² Aix-Marseille Univ, Institute of Language, Communication and the Brain, France
- 6 **Corresponding author**: Céline Hidalgo, celine.hidalgo@univ-amu.fr
- 7 Professional Address: Institut de Neurosciences des Systèmes, Faculté de Médecine, bd Jean
 8 Moulin, 13005 Marseille, France
- 9 Telephone: 04 91 32 41 02
- 10

11 Abstract

12 Conversation represents a considerable amount of the daily language usage and plays an 13 important role in language acquisition. In conversation, listeners simultaneously process 14 their interlocutor's turn and prepare their own next turn. As such the turn-taking dynamics 15 heavily relies on prediction. In other words, listeners avail prior knowledge to constrain both 16 speech perception and production. Here we explored the relation between prediction and 17 comprehension while watching two interlocutors having a conversation. We capitalize on 18 gaze switch as a proxy of predictive behaviour to class dialogue turns as more or less well 19 predicted and explore how this affects dialogue comprehension. Moreover, we study the 20 extent to which speech degradation, by increasing the global uncertainty of the context, 21 affects the relation between predictions, brain correlates of prediction errors (N400) and global comprehension. Results show that 1) listeners direct gaze to the current speaker, in particular in challenging conditions, 2) gaze behaviour possibly affects the semantic processing of the upcoming turn (N400), 3) participants with a more efficient gaze predictive behaviour better solve semantic uncertainties at the turn onset, in particular in the most challenging listening condition. Our findings contribute to a better understanding of the relation between predictions, neural predictions errors and speech comprehension under challenging conditions.

29 Keywords: conversation, ERPs, eye-tracking, prediction, turn-taking.

30

31 Author contributions: Conceptualization C.H. and D.S.; Data curation C.H., C.Z. and I.M.;

32 Formal Analysis C.H.; Funding acquisition D.S.; Project administration C.H.; Supervision D.S.;

33 Visualization C.H, C.Z. and I.M; Writing – original draft C.H., I.M., C.Z. and D.S.

34

35 Author Note: In accordance with the Peer Reviewers' Openness Initiative

36 (https://opennessinitiative.org, Morey, Chambers, Etchells, Harris, Hoekstra, Lakens, et al.,

37 2016), all materials and scripts associated with this manuscript are available on

38 https://osf.io/7dc6y/

39 Introduction

40 Speech perception is not the result of a real-time decoding of audio-visual information. It is a 41 dynamic process of an anticipatory nature building on 1) the use of the linguistic and extra-42 linguistic context to generate hypotheses about the upcoming signal, i.e. we make 43 predictions about what we are likely to hear and 2) a comparison of our predictions against 44 what is actually perceived. Thus, when we listen to a conversation between two people, we 45 anticipate, for example, the words that the speakers will produce according to the linguistic 46 context that precedes their utterances. The more we know about this context, the fewer 47 prediction errors we make and the faster and more accurate our understanding of their 48 conversation. According to predictive coding theory (Clark, 2013), predictions would indeed 49 be a default brain mode of operation for processing sensory information (Friston, 2005). To optimize speech perception, the brain would pre-activate representations of the expected 50 51 speech input (Molinaro et al., 2016) at a phonological, lexical, semantic or even syntactic 52 level (Pickering & Gambi, 2018). With increasingly accurate predictions, the brain would only 53 need to compute the difference between sensory input and prediction, thereby decreasing 54 the cost of perceptual processing and speeding up the understanding of the spoken 55 message. A well-known fact in the comprehension literature is that the amount of 56 contextual information, i.e. the increase in the precision of prediction, positively influences 57 the speed of word recognition (Tyler & Wessels, 1983). This has been thoroughly studied 58 using event-related potentials, by observing changes in the amplitude of a negative 59 component. Indeed, words with low cloze probability engender a prediction error that is 60 visible in an increase of the N400 amplitude. By contrast the N400 amplitude is reduced 61 when perceiving speech in highly predictive contexts (see for a review Kutas & Federmeier 62 2011). However, until now, no study had shown a direct link between contextual predictions

63 and the integration of these predictions in the semantic comprehension process in a conversational context. This is due to the fact that, while prediction errors engender 64 65 observable brain responses (e.g., N400 or Mismtach Negativity), this is not the case of predictions. Recently, Grisoni and colleagues (Grisoni et al., 2021) described an 66 electrophysiological index of predictions called the "Semantic Prediction Potential", and 67 68 showed, by measuring the N400 brain response during the perception of more or less contextually constrained sentences, the direct effect of predictions (SPP) on the processing 69 70 of prediction errors (N400).

71 Another possibility to infer the ongoing predictions is to use behavioural measures. In the 72 case of language, several studies have used for instance eye movements during reading 73 (Rayner, 1978; Staub, 2015). Similarly, in speech perception, some authors relied on the 74 implicit anticipatory gaze behaviour when listening to different people having a conversation 75 (Casillas & Frank, 2017; Keitel et al., 2013). More precisely, listeners anticipate the end of the 76 turn of the current speaker and switch gaze to the following speaker, before the actual onset 77 of the new turn. This predictive behaviour is particularly important considering that the 78 silence separating speech turns of conversing speakers only lasts a few hundred milliseconds 79 (Levinson, 2016; Stivers et al., 2009). In considering turn-taking in conversation, predictions 80 build on several linguistic cues such as prosody (Roberts et al., 2015), lexical-semantic cues 81 (De Ruiter et al., 2006), syntactic structures (Selting, 1996) or pragmatic cues (Beňuš et al., 82 2011). When listening to a dialogue (as a third person), a similar behaviour possibly takes 83 place via the generation of internal models, allowing a listener to anticipate in a precise 84 temporal window the speakers' turn-taking.

85 The aim of the current study is to explore the links between predictions at the turn level, measured by gaze switch, and both local and global semantic processing when listening to a 86 dialogue, as indexed by N400 to turn onset and comprehension score, respectively. 87 88 Importantly we are interested in studying how these relations evolve when adding 89 uncertainty to the context by degrading the input signal. Indeed, degrading the acoustic signal or adding noise or competing speakers, adds uncertainty and challenges speech 90 91 comprehension (Mattys et al., 2012; Peelle, 2018). To this aim, we asked participants to 92 watch videos of two people having a conversation manipulating different levels of speech 93 degradation. We measured eye movements to estimate predictive gaze behaviour and used 94 this measure to class turns as well predicted (early gaze switch) or poorly predicted (late 95 gaze switch). We also measured EEG and used the N400 as a marker of prediction error at the turn onset and studied the extent to which this response is influenced by gaze 96 97 behaviour. Finally, all participants responded to several open questions at the end of each 98 dialogue, allowing estimating a global comprehension measure. Most importantly, we 99 explored the relation between these different variables as a function of speech degradation 100 and increasing uncertainty. We hypothesized that poorly predicted turns (late gaze switch) 101 would engender a larger N400 response compared to well anticipated turns (early gaze 102 switch). Importantly, this effect may change as a function of speech degradation and should 103 be reduced at high speech degradation levels when uncertainty is highest. We also 104 hypothesized that, if predictions are fully implicit and based on the understanding of the 105 dialogue, then gaze switches should behave similarly to comprehension score and decrease 106 from normal to moderately degraded and even more for highly degraded speech.

107

108 Materials and Methods

109 We report how we determined our sample size, all data exclusions, all inclusion/exclusion

110 criteria, whether inclusion/exclusion criteria were established prior to data analysis, all

- 111 manipulations, and all measures in the study. No part of the study procedures or analyses
- 112 was preregistered prior to the research being conducted.
- 113

114 **Participants**

115 Forty-eight participants (27 females) were tested after being informed of the procedure of 116 the study, which was approved by the Sud Méditerranée Ethics Committee (ID RCB: 2015-117 A01490-49). In absence of a known effect size, the sample size was chosen as rather large 118 with respect to N400 studies (Šoškić et al., 2021). Inclusion and exclusion criteria: 119 Participants were between 18 and 62 years old (mean = 32, SD = 6 years). They were native French speakers. The had normal or corrected to normal vision and normal hearing. years); 120 121 they had no history of speech disorder or neurological disease based on self-report. Prior the 122 experiment, the hearing thresholds were controlled using a 5dB-step custom screening 123 hearing test made in Python 3.7.9 (Expyriment version 0.10.0). Data from nine participants were excluded because of noisy EEG recordings (high impedances or excessive 124 125 eye/movement artifacts) or track loss for long temporal windows in the eye-tracking dataset, 126 resulting in 39 participants in the final dataset.

127 Stimuli


We presented 6 audiovisual stimuli of ~4.5 minutes each, showing a man and a woman having a conversation. The themes of the conversations differed and were joyful to maintain attention during the whole duration of the dialogue. Dialogues contained on average 59 turns (min = 46; max = 66; see details in table 1). Turns lasted on average 3.75s (SD = 2.75)
and global speech rate was approximately 5Hz. 60% of these turns were
questions/responses adjacency pairs (min = 56 %; max = 66%) in order to elicit predictive
behaviours as suggested in Casillas & Frank, 2017 (Casillas & Frank, 2017). We used Final Cut
Pro X to set the gap duration at speakers' turn to 500ms in order to have homogeneous turn
conditions, allow anticipatory gaze behaviour (cf. Foulsham et al. 2010; Casillas and Frank
2017) and obtain equivalent EEG baseline for turn onset analyses.

138 For the clarity of the evoked potentials, each turn onset began with a plosive consonant 139 (although we avoided bilabial to avoid visual cues preceding the plosion). In the stimuli 140 recording session, all dialogues were written and displayed on a desk in front of the speakers 141 during video shooting. Dialogues were all read by the same male and female speaker and 142 videos were recorded in an anechoic room. To avoid body movement when reading the 143 dialogues, the speakers sat on a chair and their head was maintained still by a hard hat fixed 144 to the chair. Each speaker wore sunglasses to hide eye movements and a wig to hide the 145 hard hat (Figure 1A left). Furthermore, in order to discard spurious visual cues, the non-146 speaking speaker was "frozen" via video editing whenever a head or lip movement occurred 147 before the turn. This happened in approximately ~20% of the turns. In order to avoid sharp jumps in the images of the upcoming speaker such freezing took advantage of fading and 148 149 morphing technics (mMorphCut plug-in ; FINAL CUT pro X).

150 In other words, turns could not be anticipated on the basis of visual information of the next 151 speaker right before the turn. Thus, anticipatory gaze behaviour cannot be interpreted in 152 response to visual cues but as auditory predictive behaviour only. We also created 12 open 153 questions for each dialogue (e.g. "why was Tom walking in the wood?") (see table 2 for more

examples for one dialogue). These questions were recorded using an auditory only format,by a female speaker different from the one in the dialogues.

156 Speech recordings of the six dialogues were degraded using a noise vocoding approach 157 (Shannon et al. 1995; custom Matlab script). This allows to parametrically vary the spectral 158 detail, with increasing numbers of channels associated with increasing perceptual clarity 159 (Figure 1A right). The procedure allowed creating a highly degraded condition in which we 160 kept only frequency bands from 120Hz to 237Hz, 405Hz to 538Hz and 919Hz to 1028Hz (i.e. 161 3 frequency bands left with 5 ERB scales) and a moderately degraded condition in which we 162 removed all frequency bands except from 120Hz to 237Hz, from 674Hz to 805Hz, from 163 2025Hz to 2112Hz and 5208Hz to 5236Hz (so 4 frequency bands left with 8 ERB scales). The 164 overall RMS amplitude of the audio files was adjusted to be the same across all dialogues in 165 the three conditions (normal, moderately degraded, highly degraded). We also run a pilot 166 test to ensure that comprehension varied as a function of speech degradation and that, in 167 the most challenging condition, participants could still understand part of the conversation. 168 More precisely, 6 native French participants listened to audio excerpts of the dialogues and 169 repeated all words they could recognize. The excerpts were degraded in a parametric 170 manner in the number of channels, the bandwidth and the low frequency cut-off. The 171 parameters were chosen in such a way to yield a condition of moderate difficulty (comprehension level between 30 and 50%) and another condition of great difficulty 172 173 (comprehension level between 10 and 30%).



175

176 Figure 1. Schematic illustration of the task and analyses. A. On the left, snapshot of the video illustrating the 177 fixation points of the participant and the gaze switch. On the right, the three different speech conditions with 178 normal, moderately degraded and highly degraded speech (using a vocoding approach). B. Schematic 179 illustration of the turns in the dialogue, the controlled gap between turns (500ms) and the gaze switch window 180 of analysis. C. On the left, gaze behaviour of a single participant showing the gaze switch for every turn of a 181 single dialogue in the normal speech condition with respect to turn onset (zero). On the right, the gaze switch 182 distribution for a single participant in the three different degradation conditions. A median split is used to class 183 turns as being more or less well anticipated.

184 **Procedure**

185 Participants were equipped with a 64 preamplified Ag–AgCl electrodes (International 10/10 186 system site, BrainAmp system). The ground electrode was placed at AFz, the reference 187 electrode at FCz, and the EEG signal sampling rate recording was 1000 Hz. Participants were 188 comfortably seated in a Faraday sound-proof booth in front of a computer screen (24") with 189 a resolution of 1920 x 1080px and a refresh rate of 100Hz), at a distance of approximately 70 190 cm. A Gazepoint GP3 eye-tracker (sampling rate: 60 Hz; accuracy: 0.5-1° of visual angle) was 191 installed at the bottom of the screen on a tripod to record the participant's gaze positions. 192 OpenSesame software (Mathôt et al., 2012) installed on a Dell laptop (Precision T1700) 193 launched the eye-tracker recording through the PyGaze package (Dalmaijer et al., 2014) and 194 the audio-visual stimulation. The videos were displayed on full screen resolution, and the 195 sound was delivered through a 2040 YAMAHA amplifier and two NS 1020 Studio YAMAHA 196 loudspeakers located on both sides of the screen. Before each video presentation, the 197 participant's eyes were calibrated using the PyGaze's standard 12-points calibration 198 procedure.

199 The experimenter asked participants to attentively follow the dialogues and informed them 200 that, after each dialogue, they should answer 12 questions on the dialogue content. These 201 questions allowed us to ascertain participants' attention and assess the level of 202 comprehension. Each participant saw 2 dialogues in each of the three experimental 203 conditions (normal speech, moderately degraded speech, highly degraded speech). The level 204 of degradation of each dialogue and the order of the dialogues were counterbalanced across 205 participants (each dialogue was presented at a different degradation level - normal, 206 moderately degraded, highly degraded - to different participants).

207

208 Stimuli, eye-tracking and EEG data synchronization

209 A custom-made sync box based on an Arduino micro-controller ensured the synchronization 210 between the EEG data and the acoustic stimulation that was embedded in the video file. The 211 stereo sound goes from the stimulation PC to the sync box (audio cable). There, the stereo is 212 split and the first channel containing the speech signals of the dialogues goes directly to the 213 loudspeakers. The second channel signal goes through the micro-controller. This channel 214 contains an audio trigger indicating the beginning and the end of each dialogue. The Arduino 215 detects the audio trigger and sends an adapted signal to the EEG system. To ensure a precise 216 synchronization of the eye-tracking on the acoustic stimulation and the EEG data, we used 217 saccadic movements. More precisely, saccades can be easily detected in the eye-tracking 218 data, but they are also clearly visible in the EEG signal, especially using Independant 219 Component Analysis decomposition (Makeig et al., 1996). Thus, for each dialogue, we 220 detected gaze switch for every turn in both the eye-tracking and EEG data (see 221 supplementary material 1). Then, we computed for each subject and dialogue the median 222 delay between the two signals across all turns and used it to temporally realign the eye-223 tracking to EEG (median delay across participants = 23ms; median sd across participants = 224 12ms). This procedure ensured a good time-alignment of the three types of data (video, eye-225 tracking and EEG).

226 Data Analysis

227 Eye-tracking

In this study we used the gaze switch from one speaker to the other as a proxy of anticipatory behaviour with respect to the upcoming turn onset (see Figure 1A left and B). However, in contrast with previous studies (Casillas & Frank, 2017) that were mostly interested in anticipatory gaze shift, we were also interested in somewhat late gaze shifts.

We assumed that adult participants need approximately 200ms to plan an eye movement (Kamide et al., 2003). Thus, we considered a temporal window around the turn allowing to keep both anticipatory and non-anticipatory gaze switch, resulting in a -1/+1s window around the turn onset (Figure 1B). Note, nonetheless that, as expected, most shifts occurred in the inter-turn gap, that is before the turn onset (Foulsham et al., 2010; Keitel et al. 2013; Casillas and Frank 2017, see Figure 2B).

Moreover, we also applied three supplementary criteria to filter spurious gaze switches. First, gaze before and after the switch should fall within an area of interest (AOIs), defined as stationary rectangle surrounding each face (see Figure 1A left). Second, gaze switch should be preceded by at least 100ms fixation on the current speaker. Third, it should be followed by at least 150ms fixation to the next speaker. Concerning the possible back and forth gaze behaviour preceding turn (4.5% in our data), we kept only the first gaze switch.

In short, we computed a gaze switch latency, that is relative to the upcoming turn onset time. A positive indicates thus a gaze switch following the turn onset, while a negative value indicates a gaze switch before the turn onset (Figure 1C left). Then, we used a median split to class turns as early or late, separately for each subject and condition (Figure 1C right).

248 EEG

Signal processing was done using EEGLAB (Delorme & Makeig, 2004) and custom scripts written in MATLAB. We high-pass filtered (0.5Hz) continuous data and rejected major artifacts (> 300 μ V). For every participant, we systematically used Independent Component Analysis to remove eye blinks and saccadic movements and, when needed, muscular activity. We then low-pass filtered (45Hz) and segmented continuous data into epochs of 900ms starting at 100ms prior to turn onset. We zero-mean normalized epochs to the baseline ([–

255 100, 0]ms) and re-referenced to the algebraic average of all electrodes. Finally, we averaged
256 epochs according to the three conditions, also separating epochs according to the latency of
257 the gaze shift corresponding to each turn (early or late, see above).

258 Statistical analysis

259 We computed all statistical analysis using R (Team, 2021) and the Ime4 package (Bates et al., 260 2015). We evaluated participants' comprehension scores (1 point attributed to each good answer; range 0 - 12) as a function of speech degradation by fitting linear models on the 261 262 mean of correct responses for each condition (2 dialogues by condition) and each subject. 263 Similarly, we modelled the mean of gaze switch latencies for each dialogue as a function of 264 speech degradation by fitting linear model on latency data. We then used a general linear 265 model (glm) in modelling the time spent gazing at the current speaker (ratio of the total 266 fixation time). All theses models were tested against the null model before being 267 interpreted. We computed a linear mixed model with interaction to explain comprehension 268 score according to gaze switch latencies and speech degradation, with subject as random 269 effect (comprehension \sim gaze switch latency * speech degradation + 1|subject). This model 270 was compared 1) to the null model, 2) to the model with only gaze switch latencies as 271 predictor and 3) to the additive model (gaze switch latencies and speech degradation as 272 independent predictors). Statistical significance of the fixed effects was assessed by model 273 comparison using the Akaike Information Criterion, thus arbitrating between complexity and 274 explanatory power of the models. Normality and homoscedasticity of the residuals of all the 275 models were systematically visually inspected. Reported p values are Satterthwhaite 276 approximations obtained with the ImerTest package (Kuznetsova et al., 2017).

277 The statistical significance of the differences between conditions for the ERP data was evaluated by a cluster-based random permutation approach for the full set of 64 electrodes 278 279 (2-tailed test with 500 permutations over the whole time range of the ERP epoch, i.e. 280 between -100 and 800ms). This statistical approach handles the multiple-comparisons 281 problem. More precisely, the approach controls for the Type-1 error rate in multiple testing 282 across channels and time points by identifying clusters of significant differences between 283 conditions in the time and space dimensions (Maris & Oostenveld, 2007). Finally, in order to assess the relation between gaze switch and ERPs, we used simple linear models with the 284 amplitude difference between late and early trials in the N400 window explained as a 285 286 function of the interaction between gaze switch latencies and speech degradation (N400 287 effect ~ gaze switch latency * speech degradation). As for the other analyses, this model was 288 compared to the additive model.

289


290 Results

As expected, the comprehension score decreases as a function of increasing speech degradation (β = -2.551, SE = 0.22, t = -11.55, p < 0.001, Figure 2A). Compared to the normal condition, both the highly degraded and degraded speech conditions altered the comprehension score (β = -1.23, SE = 0.42, t = -2.929 p = 0.004; β = -5.102, SE = 0.42, t = -12.145, p < 0.001, respectively).

296 It is important to note that participants' score are well above zero and this is also the case in 297 the highly degraded condition (range: 1-10, median 5.5). Considering that the score is based 298 on response to open questions, it is extremely unlikely that a single correct answer is given by chance. As such, these results show that participants of the current experiment can partlyunderstand the dialogues even in the most difficult condition of speech perception.

301 When turning to eye-movements, participants gaze data are available on average for 87% of 302 the total duration of the dialogues (range: [82-90]). The loss of data is possibly due to a gaze 303 off the screen and/or to a temporary loss of the eye from the tracker. From these available 304 data, it appears that participants gazed at the current speaker most of the time during video 305 playback (93%; range: [87-97]). Compared to the normal condition, time spent on current 306 speaker is greater in the degraded (β = 0.580, SE = 0.073, t = 7.881, p < 0.001) and highly 307 degraded conditions (β = 0.616, SE = 0.074, t = 8.317, p < 0.001). Importantly, not only 308 participants gazed most of the time at the current speaker, but when considering gaze 309 switch towards the current speaker, these took place most often in a -1/+1sec window 310 around the turn onset (mean 80 %, range: [0.56-0.96]), the rest being gaze switches far away 311 from the turn or missing data.

Figure 2



312

Figure 2. Behavioural results and correlations. A. Effect of speech degradation level on comprehension. Dots represent the average comprehension score for each participant in each condition. B. Effect of speech degradation level on gaze switch latency. Latency at zero milliseconds corresponds to the onset of the turn. Dots represent the average latency for each participant in each condition. C. Scatter plots and linear regression between comprehension scores and gaze switch latency in the three different conditions. D. Scatter plots and linear regression between N400 effect size (late minus early, in the <u>300-550ms</u> latency window) and gaze switch latency in the three different conditions.

320 Normalizing by time unit this gives a number of gaze switch per second of 0.47 during the 321 turn window and 0.08 during the rest of the dialogue (that is switches from one AOI to the

322 other that were performed outside the -1/+1s window around the turn, see supplementary 323 material 2). Overall, these results clearly show that gaze and gaze switches are not randomly 324 distributed across the dialogues. On the contrary, gaze behaviour to current speakers 325 demonstrates that participants are tracking turns during the videos, as previously reported 326 (Casillas & Frank, 2017). When moving to gaze switch latencies, one can see that these are 327 influenced by speech degradation ($\beta = \frac{43.382}{5.382}$, SE = 9.52, t = 4.553, p < 0.001, see Figure 2B). 328 This is due to longer latencies to turns with highly degraded speech compared to normal and 329 degraded speech (always p < 0.001) while there are no latency differences between 330 degraded and normal conditions (p > 0.1). Moreover, latencies globally move from negative 331 values in the normal condition to positive values in the highly degraded condition. Because 332 latencies are estimated with respect to turn onset, this means that while in the normal 333 condition participants realize the gaze switch before the turn, switches mostly take place 334 after the turn onset in the highly degraded condition.

335 When looking at the relation between comprehension scores and gaze latency, this changes 336 as a function of speech degradation ($\beta = -5.740$, SE = 0.001, t = -3.936, p < 0.001). More 337 precisely, in the highly degraded condition shorter gaze switch latencies to turn onsets are 338 associated to good comprehension scores (β = - 0.008, SE = 0.003, t = -2.989, p < 0.01). This 339 effect was not significant in the moderately degraded nor in normal conditions (p > 0.5, 340 Figure 2C). This model with gaze switch latencies and speech degradation as interaction 341 factors was the best compared to the additive model (AIC = 1038.5 and 1043.6 respectively ; 342 p < 0.01 and p < 0.001).

The classification of turns on the basis of the latency of gaze switches (late vs early) shows a clear negative component for turns with late switches evolving between 350 and 700ms 345 post-stimulus onset over a fronto-central region (Figure 3B). This effect is visible in the three 346 different levels of speech degradation (p < 0.05, FDR corrected). However, this effect seems 347 to differ across the three levels of speech degradation (Figure 3A) insofar as the clusters 348 start at different latencies. Because it is not appropriate to make an inferential claim on the 349 time extension of the cluster (Sassenhagen et al., 2019), we run a further analysis using a 350 jackknife approach in five subsequent 50ms latency windows from 150 to 400ms. This 351 approach is considered appropriate to make inferences on the latency of an ERP effect 352 (Miller et al., 1998). Results show that differences between early and late turns are 353 significant starting 200ms post turn onset in the normal condition, 150ms in the moderately 354 degraded condition and 300ms in the highly degraded condition (p < 0.05, FDR corrected).

Finally, when looking at the relation between the ERP effect (late vs early gaze switches) in the 300-550ms window and the global gaze switch latency of participants, we find a significant interaction between gaze switch latencies and speech degradation levels (F = 7.135, p = 0.001). More precisely, one can notice, that, in the highly degraded condition, participants with overall shorter gaze switch latencies to turn onsets show a larger effect (β = 0.007, SE = 0.001, t = 3.753, p < 0.001). A similar but not significant trend is also visible in the moderately degraded ($\beta = 0.003$, SE = 0.001, t = 1.912, p = 0.058) but not in the normal 362 conditions (β = 0.000, SE = 0.001, t = 0.204, p = 0.838, Figure 2D).




Figure 3

363

Figure 3. A. event-related potentials (ERPs) in a fronto-central region of interest time-locked to the turn onset
for early and late gaze switch latencies. Shaded areas indicate the standard error of the mean. The black line
below the ERPs indicates the FDR corrected significant difference between early and late conditions. B.
Cluster-based statistical analyses on all electrodes showing the main effect of gaze behaviour (early vs late).
The topography illustrates the difference between late and early turns across all levels of degradation. The red

369 dots represent electrodes with significant differences (cluster corrected).

370 Discussion

In the present experiment, participants watched a series of videos showing two interlocutors
having a conversation. We parametrically degraded speech and measured eye-movements,
EEG and dialogue comprehension to gather a deeper understanding of the mechanisms
underlying speech comprehension under challenging conditions. We build on the fact that

375 participants switch gaze at the current speaker and use this measure as a proxy of prediction 376 to class dialogue turns as more or less well predicted and study ERPs accordingly. Results 377 show that 1) Participants switch gaze towards the current speaker in a limited temporal 378 window around the turn. 2) Speech degradation reduces the anticipatory gaze behaviour. 3) 379 Globally, participants with a low comprehension score tend to have a later gaze behaviour 380 when speech is strongly degraded. 4) ERPs to turn onsets vary as a function of the latency of 381 the gaze switch. 5) Finally, participants with overall shorter switch gaze latencies show a 382 better comprehension score and a stronger anticipatory effect in their neural responses; this 383 relation between behavioural and neural variables is significant only in the most challenging 384 (degraded) condition. We discuss these findings with respect to the relation between 385 predictions, neural predictions errors and speech comprehension under challenging 386 conditions. Of course, these findings are limited by the constraints inherent to the present 387 experiment, wherein predictions are possible purposely on the basis of auditory cues only 388 because we controlled all extralinguistic visual cues (e.g. lip preparatory movement) that 389 undoubtedly play an important role in conversation.

390 Our study replicates previous findings (Casillas & Frank, 2017; Foulsham et al., 2010; Keitel et 391 al., 2013), showing that gaze switch takes place in a precise temporal window centered 392 before turn onset. Considering the short period between turns and the time needed to 393 prepare and realize a saccade, gaze switch, in this context, can be interpreted as anticipatory 394 behaviour (Keitel & Daum, 2015). The new result, in this respect, is that gaze switch 395 behaviour is affected by the more or less challenging speech comprehension, here obtained 396 by spectrally degrading speech signal. The reduction of anticipatory gaze behaviour in 397 presence of stronger speech degradation seems to indicate that increasing the cost of 398 speech processing has a detrimental effect on the prediction of the upcoming turn. This is in

line with results on hearing-impaired individuals showing a delay (greater effort) in
 processing sentences with more or less contextual cues, compared to normal-hearing (Winn,
 2016).

402 Importantly, our results show a relation between comprehension score and turn anticipatory 403 behaviour, under challenging conditions. This result is not trivial. Indeed, the comprehension 404 score reflects the global understanding of the whole dialogues, because it corresponds to 405 questions that were asked at the end of each dialogue. By contrast, gaze switch and EEG 406 dynamics reflect anticipatory behaviour at precise temporal windows surrounding 407 conversational turns. This means, that, under challenging conditions, participants that are 408 able to understand can take advantage of an anticipatory gaze behaviour. Alternatively, 409 participants with an anticipatory gaze behaviour are better able to understand. While the 410 present design does not allow for a causal interpretation between gaze behaviour and global 411 understanding of the dialogues, we will see that ERP results play here a very important role. 412 However, before discussing this point one has to interpret the ERP components, in particular 413 the negative component peaking around 400ms.

414 First, one may raise the possibility that residual gaze-related artefact may still be present in 415 the EEG, even following ICA procedures (see methods). However, 1) the systematic 416 difference in latency between late and early switches was on average 480ms, while we do 417 not observe such a delay in ERPs to early and late turns; 2) while highly degraded speech 418 induces overall later gaze switches, the N400 peak in this condition has the same latency as 419 in the other conditions (in Figure 3A the N400 peak is always 400ms). Thus, overall, one can consider that differences in ERPs are due to cognitive processes and not to residual 420 421 physiological artefacts due to eye movements.

422 The first and most likely interpretation of the larger negativity to both degraded turns and 423 late turns is in terms of an N400 like component. Indeed, the amplitude of the N400 is 424 strongly affected by expectations: the more a target word is unexpected within a sentence 425 context, the larger the N400 amplitude (Kutas & Federmeier, 2011; Kutas & Hillyard, 1984). 426 While the N400 topography we report is more anterior compared to the classic centro-427 parietal distribution, this may be due to the audiovisual modality (Kelly et al., 2004) or to the 428 presence of complex scenes (Kutas & Federmeier, 2011) inducing a topography more frontal 429 than for written words. Importantly, the N400 has been proposed to be a proxy of prediction 430 errors (Bornkessel-Schlesewsky & Schlesewsky, 2019; Rabovsky & McRae, 2014), that play a 431 key role within the predictive coding framework (Friston, 2010; Schultz & Dickinson, 2000).

432 As stated above, in order to assess the relevance of predictive coding theories with respect 433 to speech comprehension, it is necessary to have access to both prediction and prediction 434 error indicators. Our results, as well as previous studies, seem quite clear in showing that 435 gaze switch behaviour can be considered as a proxy of predictions. Previous research using 436 an electrophysiological marker of prediction (the semantic prediction potential, SPP) showed 437 that smaller SPP amplitude (weak predictions) result in a large N400 (Grisoni et al., 2021). 438 Similarly, our results show that turns preceded by a late gaze switch, indicating poor 439 predictions, give rise to a larger N400 like complex compared to turns preceded by an early 440 gaze switch. An interesting advantage of the current design is that the target words (here 441 turn onsets) do not need to differ in content or in context in order to engender a N400. This 442 is different for instance, from previous studies manipulating the semantic and temporal turn 443 relation to induce an N400 effect (Bögels et al., 2015). In other words, in the current study, 444 the word and the context eliciting or not the N400 are strictly identical and we take

445 advantage of the natural variability in the accuracy of participants' predictions across turns.

446 The interpretation in terms of N400 also fits quite well with the literature on weaker 447 expectancies under degraded speech. Previous work showed that adverse listening 448 conditions narrow the expectancies about the upcoming speech. This is visible in a reduced 449 N400 effect in response to incongruent or less likely words under acoustic degradation 450 (Aydelott et al., 2006; Obleser & Kotz, 2011; Strauß et al., 2013). The present findings show a 451 somewhat similar result, with an N400 effect that is significant in a later latency window in 452 the most challenging condition (strong speech degradation) compared to the two other 453 conditions. While the typical N400 effect concerns the amplitude of the negative wave, 454 several works reported later N400 latencies in context presenting more difficult semantic 455 access (Deacon et al., 1995; Moreno & Kutas, 2005). Interestingly, the temporal window 456 analysis shows that traces to early and late turns diverge first in the degraded condition, 457 then in the normal and last in the highly degraded conditions. It thus seems as if the 458 advantage of an early gaze switch was integrated faster in moderately challenging conditions. There, the benefit of an anticipatory gaze behaviour and temporally precise 459 460 (local) predictions may be maximal compared to the two other conditions wherein 461 uncertainty may either be too low (normal speech) or too high (highly degraded speech). 462 However, while the N400 latency is earliest in the degraded condition (Figure 3A), the N400 463 amplitude best correlates with turn anticipatory behaviour in the highly degraded condition (Figure 2D). In considering this inconsistency one should keep in mind that 1) the N400 464 465 effect, in terms of amplitude, is also significant in the highly degraded condition; 2) while the 466 correlation between N400 amplitude and average gaze behaviour does not reach the significance threshold (p = .06), the trend of the correlation is similar across the two 467

468 degraded conditions.

469 Importantly, Figure 2C and 2D clearly show that there is a similar relation between gaze 470 behaviour and the semantic access of dialogues. Differently from global comprehension 471 score, the N400 amplitude does not reflect a global understanding of the conversation, but it 472 is a rather local measure, as it is the case with gaze switch behaviour. Moreover, the two 473 measures are serially ordered in time, with gaze switch taking place earlier ~400ms before 474 the N400 peak. Thus, one can hypothesize that participants with an overall early gaze switch, by having a better prediction of the turn, have an easier lexical-semantic integration of the 475 word starting the turn in the conversational context. This relation between gaze and both 476 477 local (N400 effect) and global (comprehension scores) understanding is only shown under 478 challenging conditions, wherein indeed participants can benefit of a predictive behaviour to 479 improve their understanding of the dialogues.

480 It seems appropriate here to evoke an alternative (although not necessarily the most likely) 481 interpretation of the negative component in terms of a phonological mismatch negativity 482 (pMMN). Several studies have addressed the timing of audio-visual integration. For instance, 483 in McGurk illusion, the temporal window allowing modality fusion and allusion ranges 484 between 30ms and 170ms of asynchrony (van Wassenhove et al., 2007). When looking at 485 the electrophysiological response to the incongruent audio-visual stimulation, several 486 authors report a pMMN (Colin et al., 2002; Eskelund et al., 2015; Stekelenburg & Vroomen, 487 2012). The latency of this response is later than the classic MMN and is described 488 approximately 500ms after the voice onset (Proverbio et al., 2018). In our study, the 489 classification of turns as being accompanied by late or early gaze switch implies that the 490 audio-visual relation of the stimuli differs in the two classes. For early gaze switch, the gaze 491 is well anticipated and thus the audio-visual information is perceived simultaneously. By 492 contrast, in turns with a late gaze switch, often occurring after the voice onset, the

audiovisual integration has a higher level of uncertainty. In other words, if a gaze switch
takes place later than a turn onset, there may be an audiovisual mismatch because the
participant is looking at the previous speaker while listening to the upcoming speaker's
voice. In this context, looking at the closed lips of the previous speaker and hearing the word
pronounced by the following speaker, may engender a phonological audiovisual MMN.

498 We would like to end the discussion with a consideration on the implicit and explicit role of 499 predictions. It is known that the influences of the visual system on auditory perception can 500 be so strong as to override under certain conditions the original input of the auditory system 501 (Mcgurk & Macdonald, 1976). More commonly, viewing the lips provides relevant 502 complementary information and can augment and improve auditory capabilities (Calvert et 503 al., 1997; Drijvers & Özyürek, 2017; Grant & Seitz, 2000; Sumby & Pollack, 1954). In this 504 context, it is interesting to note that, compared to the normal condition, the moderately 505 degraded condition yields a poorer comprehension but similar gaze switch latencies and an 506 earlier N400 effect. These preserved latencies, in a context of poorer comprehension that 507 should rather induce poorer predictions, may be mediated by an active compensatory 508 strategy, explicitly making greater use of visual cues to improve predictive processes 509 (Sohoglu & Davis, 2016). Such a compensatory strategy may not hold when speech is highly 510 degraded, yielding to slower gaze switches due to a poor understanding of the semantic and 511 syntactic context. The respective role of implicit and explicit predictions and their link to 512 conversation strategies (Hadley et al., 2021) will require further work addressing this specific 513 question. Another interesting aspect that will require further work is the inter-relation between local predictions (gaze), local semantic processing (N400) and global 514 515 comprehension (here assessed via specific questions on the dialogues). While on one side gaze switches temporally precede auditory and semantic processing of the upcoming turn, 516

- 517 this anticipatory behaviour can only build on the global comprehension of the dialogue, that,
- 518 in turn, depends on the integration of local semantic processing.

To conclude, this study confirms that gaze switch can be used as a proxy of predictions in a conversational context. It shows that these predictions are related to the lexico-semantic processing of the turn start, as estimated by a neural marker of prediction error. It also shows that predictions are less accurate in more challenging listening conditions, but that they are also most useful in that specific context to make sense of the upcoming turn and, more generally, are a good indicator of global dialogue comprehension.

525 Acknowledgements

526 We would like to thank Laura Leone, Romane Pradels and Benjamin Morillon for their 527 participation in the design of the dialogues and the production of videos.

- 528 Funding sources: Work supported by APA foundation (RD-2016-9), ANR-16-CONV-0002
- 529 (ILCB) and the Excellence Initiative of Aix-Marseille University (A*MIDEX).

530

531 References

- 532 Aydelott, J., Dick, F., & Mills, D. L. (2006). Effects of acoustic distortion and semantic context
- 533 on event-related potentials to spoken words. *Psychophysiology*, *43*(5), 454–464.
- 534 https://doi.org/10.1111/j.1469-8986.2006.00448.x
- 535 Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting Linear Mixed-Effects Models
- 536 Using {Ime4}. *Journal of Statistical Software*, *67*(1), 1–48.
- 537 https://doi.org/10.18637/jss.v067.i01

- 538 Beňuš, Š., Gravano, A., & Hirschberg, J. (2011). Pragmatic aspects of temporal
- accommodation in turn-taking. *Journal of Pragmatics*, *43*(12), 3001–3027.
- 540 https://doi.org/10.1016/j.pragma.2011.05.011
- 541 Bögels, S., Kendrick, K. H., & Levinson, S. C. (2015). Never say no . . . How the brain interprets
- the pregnant pause in conversation. *PLoS ONE*, *10*(12).
- 543 https://doi.org/10.1371/journal.pone.0145474
- 544 Bornkessel-Schlesewsky, I., & Schlesewsky, M. (2019). Toward a neurobiologically plausible
- 545 model of language-related, negative event-related potentials. *Frontiers in Psychology*,
- 546 *10*(FEB), 298. https://doi.org/10.3389/fpsyg.2019.00298
- 547 Calvert, G. A., Bullmore, E. T., Brammer, M. J., Campbell, R., Williams, S. C. R., McGuire, P. K.,
- 548 Woodruff, P. W. R., Iversen, S. D., & David, A. S. (1997). Activation of auditory cortex
- 549 during silent lipreading. *Science*, *276*(5312), 593–596.
- 550 https://doi.org/10.1126/science.276.5312.593
- 551 Casillas, M., & Frank, M. C. (2017). The development of children's ability to track and predict
- 552 turn structure in conversation. *Journal of Memory and Language*, *92*, 234–253.
- 553 https://doi.org/10.1016/j.jml.2016.06.013
- 554 Clark, A. (2013). Whatever next? Predictive brains, situated agents, and the future of
- 555 cognitive science. *Behavioral and Brain Sciences*, *36*(3), 181–204.
- 556 https://doi.org/10.1017/S0140525X12000477
- 557 Colin, C., Radeau, M., Soquet, A., Demolin, D., Colin, F., & Deltenre, P. (2002). Mismatch
- 558 negativity evoked by the McGurk-MacDonald effect: A phonetic representation within
- short-term memory. *Clinical Neurophysiology*, *113*(4), 495–506.

560 https://doi.org/10.1016/S1388-2457(02)00024-X

- 561 Dalmaijer, E. S., Mathôt, S., & Van der Stigchel, S. (2014). PyGaze: an open-source, cross-
- 562 platform toolbox for minimal-effort programming of eyetracking experiments. *Behavior*
- 563 *Research Methods*, *46*(4), 913–921. https://doi.org/10.3758/s13428-013-0422-2
- 564 De Ruiter, J., Mitterer, H., & Enfield, N. J. (2006). Projecting the end of a speaker's turn: a
- 565 cognitive cornerstone of conversation. *Language*, *82*, 515–535.
- 566 http://dx.doi.org/10.1353/lan.2006.0130
- 567 Deacon, D., Mehta, A., Tinsley, C., & Nousak, J. M. (1995). Variation in the latencies and
- amplitudes of N400 and NA as a function of semantic priming. *Psychophysiology*, *32*(6),
 569 560–570.
- 570 http://search.ebscohost.com/login.aspx?direct=true&db=s3h&AN=11064097&lang=fr&
 571 site=ehost-live
- 572 Delorme, A., & Makeig, S. (2004). EEGLAB: an open source toolbox for analysis of single-trial
- 573 EEG dynamics. *Journal of Neuroscience Methods*, *13*, 9–21.
- 574 <u>https://doi.org/http://dx.doi.org/10.1016/j.jneumeth.2003.10.009</u>
- 575 Drijvers, L., & Özyürek, A. (2017). Visual context enhanced: The joint contribution of iconic
- 576 gestures and visible speech to degraded speech comprehension. Journal of Speech,
- 577 *Language, and Hearing Research, 60*(1), 212–222. https://doi.org/10.1044/2016_JSLHR-
- 578 H-16-0101
- 579 Eskelund, K., MacDonald, E. N., & Andersen, T. S. (2015). Face configuration affects speech
- 580 perception: Evidence from a McGurk mismatch negativity study. *Neuropsychologia*, 66,
- 581 48–54. https://doi.org/10.1016/j.neuropsychologia.2014.10.021

- 582 Foulsham, T., Cheng, J. T., Tracy, J. L., Henrich, J., & Kingstone, A. (2010). Gaze allocation in a
- 583 dynamic situation: Effects of social status and speaking. Cognition, 117(3), 319–331.
- 584 https://doi.org/10.1016/j.cognition.2010.09.003
- 585 Friston, K. (2005). A theory of cortical responses. *Philosophical Transactions of the Royal*
- 586 *Society B: Biological Sciences, 360*(1456), 815–836.
- 587 https://doi.org/10.1098/rstb.2005.1622
- 588 Friston, K. (2010). The free-energy principle: A unified brain theory? Nature Reviews
- 589 *Neuroscience*, *11*(2), 127–138. https://doi.org/10.1038/nrn2787
- 590 Grant, K. W., & Seitz, P.-F. (2000). The use of visible speech cues for improving auditory
- 591 detection of spoken sentences. The Journal of the Acoustical Society of America, 108(3),
- 592 1197. https://doi.org/10.1121/1.1288668
- 593 Grisoni, L., Tomasello, R., & Pulvermüller, F. (2021). Correlated Brain Indexes of Semantic
- 594 Prediction and Prediction Error: Brain Localization and Category Specificity. *Cerebral*
- 595 *Cortex*, *31*(3), 1553–1568. https://doi.org/10.1093/cercor/bhaa308
- 596 Hadley, L. V., Whitmer, W. M., Brimijoin, W. O., & Naylor, G. (2021). Conversation in small
- 597 groups: Speaking and listening strategies depend on the complexities of the
- 598 environment and group. Psychonomic Bulletin & Review, 28(2), 632-640.
- 599 Hirvenkari, L., Ruusuvuori, J., Saarinen, V.-M., Kivioja, M., Peräkylä, A., & Hari, R. (2013).
- 600 Influence of Turn-Taking in a Two-Person Conversation on the Gaze of a Viewer. PLoS
- 601 ONE, 8(8), e71569. https://doi.org/10.1371/journal.pone.0071569
- 602 Kamide, Y., Altmann, G. T. M., & Haywood, S. L. (2003). The time-course of prediction in
- 603 incremental sentence processing: Evidence from anticipatory eye movements. Journal

604 of Memory and Language, 49(1), 133–156. https://doi.org/10.1016/S0749-

- 605 596X(03)00023-8
- 606 Keitel, A., & Daum, M. M. (2015). The use of intonation for turn anticipation in observed
- 607 conversations without visual signals as source of information. *Frontiers in Psychology*,
- 608 6(February), 108. https://doi.org/10.3389/fpsyg.2015.00108
- 609 Keitel, A., Prinz, W., Friederici, A. D., Hofsten, C. von, & Daum, M. M. (2013). Perception of
- 610 conversations: The importance of semantics and intonation in children's development.
- 611 Journal of Experimental Child Psychology, 116(2), 264–277.
- 612 https://doi.org/10.1016/j.jecp.2013.06.005
- 613 Kutas, M., & Federmeier, K. D. (2011). Thirty years and counting: Finding meaning in the
- 614 N400 component of the event-related brain potential (ERP). Annual Review of
- 615 *Psychology*, *62*, 621–647. https://doi.org/10.1146/annurev.psych.093008.131123
- 616 Kutas, M., & Hillyard, S. A. (1984). Brain potentials during reading reflect word expectancy
- 617 and semantic association. *Nature*, *307*(5947), 161–163.
- 618 Kuznetsova, A., Brockhoff, P. B., & Christensen, R. H. B. (2017). ImerTest Package: Tests in
- 619 Linear Mixed Effects Models. *Journal of Statistical Software*, 82(13), 1–26.
- 620 https://doi.org/10.18637/jss.v082.i13
- 621 Levinson, S. C. (2016). Turn-taking in Human Communication Origins and Implications for
- 622 Language Processing. *Trends in Cognitive Sciences*, 20(1), 6–14.
- 623 https://doi.org/10.1016/j.tics.2015.10.010
- Makeig, S., Bell, A. J., Jung, T.-P., & Sejnowski, T. J. (1996). Independent component analysis
- 625 of electroencephalographic data. Advances in Neural Information Processing Systems,

626 145–151.

- 627 Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and MEG-data.
- 628 Journal of Neuroscience Methods, 164(1), 177–190.
- 629 https://doi.org/10.1016/j.jneumeth.2007.03.024
- 630 Mathôt, S., Schreij, D., & Theeuwes, J. (2012). OpenSesame: An open-source, graphical
- 631 experiment builder for the social sciences. *Behavior Research Methods*, 44(2), 314–324.
- 632 https://doi.org/10.3758/s13428-011-0168-7
- Mattys, S. L., Davis, M. H., Bradlow, A. R., & Scott, S. K. (2012). Speech recognition in adverse
- 634 conditions: A review. *Language and Cognitive Processes*, *27*(7–8), 953–978.
- 635 https://doi.org/10.1080/01690965.2012.705006
- 636 Mcgurk, H., & Macdonald, J. (1976). Hearing lips and seeing voices. *Nature*, *264*(5588), 746–
 637 748. https://doi.org/10.1038/264746a0
- 638 Miller, J., Patterson, T. U. I., & Ulrich, R. (1998). Jackknife-based method for measuring LRP
- onset latency differences. Psychophysiology, 35(1), 99-115.
- 640 Molinaro, N., Monsalve, I. F., & Lizarazu, M. (2016). Is there a common oscillatory brain
- 641 mechanism for producing and predicting language? *Language, Cognition and*
- 642 *Neuroscience*, *31*(1), 145–158. https://doi.org/10.1080/23273798.2015.1077978
- 643 Moreno, E. M., & Kutas, M. (2005). Processing semantic anomalies in two languages: An
- 644 electrophysiological exploration in both languages of Spanish-English bilinguals.
- 645 *Cognitive Brain Research*, *22*(2), 205–220.
- 646 https://doi.org/10.1016/j.cogbrainres.2004.08.010

- 647 Obleser, J., & Kotz, S. A. (2011). Multiple brain signatures of integration in the
- 648 comprehension of degraded speech. *NeuroImage*, *55*(2), 713–723.
- 649 https://doi.org/10.1016/j.neuroimage.2010.12.020
- 650 Peelle, J. E. (2018). Listening effort: How the cognitive consequences of acoustic challenge
- are reflected in brain and behavior. *Ear and Hearing*, *39*(2), 204–214.
- 652 https://doi.org/10.1097/AUD.00000000000494
- 653 Pickering, M. J., & Gambi, C. (2018). Predicting while comprehending language: A theory and

654 review. *Psychological Bulletin*, 144(10), 1002–1044.

- 655 https://doi.org/10.1037/bul0000158
- 656 Proverbio, A. M., Raso, G., & Zani, A. (2018). Electrophysiological Indexes of Incongruent
- 657 Audiovisual Phonemic Processing: Unraveling the McGurk Effect. *Neuroscience*, 385,

658 215–226. https://doi.org/10.1016/j.neuroscience.2018.06.021

- 659 Rabovsky, M., & McRae, K. (2014). Simulating the N400 ERP component as semantic network
- 660 error: Insights from a feature-based connectionist attractor model of word meaning.
- 661 *Cognition*, *132*(1), 68–89. https://doi.org/10.1016/j.cognition.2014.03.010
- 662 Rayner, K. (1978). Eye movements in reading and information processing. Psychological

663 Bulletin, 85(3), 618–660. https://doi.org/10.1037/0033-2909.85.3.618

- Roberts, S. G., Torreira, F., & Levinson, S. C. (2015). The effects of processing and sequence
- 665 organization on the timing of turn taking: a corpus study. Frontiers in Psychology, 6,
- 666 509. https://doi.org/10.3389/fpsyg.2015.00509
- 667 https://doi.org/10.1093/cercor/bhl024

- Sassenhagen, J., & Draschkow, D. (2019). Cluster-based permutation tests of MEG/EEG data
 do not establish significance of effect latency or location. Psychophysiology, 56(6),
 e13335.
- 671 Schultz, W., & Dickinson, A. (2000). Neuronal coding of prediction errors. Annual Review of
- 672 *Neuroscience*, 23, 473–500. https://doi.org/10.1146/annurev.neuro.23.1.473
- 673 Selting, M. (1996). On the interplay of syntax and prosody in the constitution of turn-
- 674 constructional units and turns in conversation. *Pragmatics. Quarterly Publication of the*
- 675 International Pragmatics Association (IPrA), 6(3), 371–388.
- 676 https://doi.org/10.1075/prag.6.3.06sel
- 677 Shannon, R. V, Zeng, F. G., Kamath, V., Wygonski, J., & Ekelid, M. (1995). Speech recognition
- 678 with primarily temporal cues. *Science*, *270*(5234), 303–304.
- 679 https://doi.org/10.1126/science.270.5234.303
- 680 Sohoglu, E., & Davis, M. H. (2016). Perceptual learning of degraded speech by minimizing
- 681 prediction error. Proceedings of the National Academy of Sciences of the United States
- 682 of America, 113(12), E1747–E1756. https://doi.org/10.1073/pnas.1523266113
- 683 Šoškić, A., Jovanović, V., Styles, S. J., Kappenman, E. S., & Ković, V. (2021). How to do better
- 684 N400 studies: reproducibility, consistency and adherence to research standards in the
 685 existing literature. *Neuropsychology Review*, 1-24.
- 686 Staub, A. (2015). The Effect of Lexical Predictability on Eye Movements in Reading: Critical
- 687 Review and Theoretical Interpretation. Language and Linguistics Compass, 9(8), 311–
- 688 327. https://doi.org/10.1111/lnc3.12151
- 689 Stekelenburg, J. J., & Vroomen, J. (2012). Electrophysiological correlates of predictive coding

- 690 of auditory location in the perception of natural audiovisual events. *Frontiers in*
- 691 *Integrative Neuroscience, 6*(MAY 2012), 1–7. https://doi.org/10.3389/fnint.2012.00026
- 692 Stivers, T., Enfield, N. J., Brown, P., Englert, C., Hayashi, M., Heinemann, T., Hoymann, G.,
- Rossano, F., de Ruiter, J. P., Yoon, K.-E., & Levinson, S. C. (2009). Universals and cultural
- 694 variation in turn-taking in conversation. *Proceedings of the National Academy of*
- 695 Sciences of the United States of America, 106(26), 10587–10592.
- 696 https://doi.org/10.1073/pnas.0903616106
- 697 Strauß, A., Kotz, S. A., & Obleser, J. (2013). Narrowed expectancies under degraded speech:
- 698 Revisiting the N400. *Journal of Cognitive Neuroscience*, 25(8), 1383–1395.
- 699 https://doi.org/10.1162/jocn_a_00389
- 700 Sumby, W. H., & Pollack, I. (1954). Visual Contribution to Speech Intelligibility in Noise.
- 701 Journal of the Acoustical Society of America, 26(2), 212–215.
- 702 https://doi.org/10.1121/1.1907309
- Team, R. C. (2021). R: A language and environment for statistical computing. Vienna: R
- 704 *Project, 2017*.
- Tyler, L. K., & Wessels, J. (1983). Quantifying contextual contributions to word-recognition
 processes. *Perception & Psychophysics*, *34*(5), 409-420
- van Wassenhove, V., Grant, K. W., & Poeppel, D. (2007). Temporal window of integration in
- auditory-visual speech perception. *Neuropsychologia*, 45(3), 598–607.
- 709 https://doi.org/10.1016/j.neuropsychologia.2006.01.001
- 710 Winn, M. (2016). Rapid Release From Listening Effort Resulting From Semantic Context, and
- 711 Effects of Spectral Degradation and Cochlear Implants. *Trends in Hearing*, 20, 1–17.

713 Supplementary material

	Dialogue's longth		Number of
Dialogue's number	Dialogue's length (seconds)	Number of turns	questions/response
			pairs
1	269	60	40
2	247	46	26
3	185	62	36
4	258	60	38
5	253	66	40
6	248	62	36

714

715 Table 1. Dialogues's details.

Est-ce que Damien veut attraper une bête avec sa cage ?		
Does Damien want to catch an animal with his cage?		
Cette cage est faite pour qui ?		
Who is this cage for?		
Comment Damien arrive à rentrer dans sa cage ?		
How does Damien get into his cage?		
Dans quoi peut rentrer le génie d'Aladin ?		
What can Aladdin's genie fit into?		

Pourquoi Damien veut se cacher dans une cage ?

Why does Damien want to hide in a cage?

Comment se déplace l'étrange fée ?

How does the strange fairy move?

Qui porte un grand chapeau ?

Who is wearing a big hat?

Pourquoi la sorcière veut attraper Damien ?

Why does the witch want to catch Damien?

Camille va chercher qui pour aider Damien à se débarrasser de la méchante sorcière ?

Who will Camille look for to help Damien get rid of the wicked witch?

Dans cette histoire, où habite Harry Potter ?

In this story, where does Harry Potter live?

Pourquoi Camille pense qu'une bête s'est échappée ?


Why does Camille think an animal has escaped?

Est-ce que Harry Potter aime les vilaines sorcières ?


Does Harry Potter like bad witches?

717

718 Table 2. Exemple of questions for one dialogue.



Supplementary material 1. Example of eye-tracking and EEG synchronization for one dialogue. A. Overlapping of ICA-EEG data and Eye-tracking data. B. Zoom in for one trial (one turn); latency at zero milliseconds corresponds to the onset of this turn. C. Dashed red line represents the mean of delays between Eye-tracking and EEG data for the same subject in the same dialogue as in A.



Supplementary material 2. Number of gaze switch per second in and out of the turn window.