

Topology optimization of periodic beam lattices using Cosserat elasticity

Gergely Molnár, Nawfal Blal

▶ To cite this version:

Gergely Molnár, Nawfal Blal. Topology optimization of periodic beam lattices using Cosserat elasticity. Computers & Structures, 2023, 281, pp.107037. 10.1016/j.compstruc.2023.107037. hal-03831937

HAL Id: hal-03831937 https://hal.science/hal-03831937

Submitted on 27 Oct 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Topology optimization of periodic beam lattices using Cosserat elasticity

Gergely Molnár^{a,*}, Nawfal Blal^a

^aUniv Lyon, CNRS, INSA Lyon, LaMCoS, UMR5259, 69621 Villeurbanne, France

Abstract

This paper presents a novel method based on the Cosserat theory to optimize the topology of slender metamaterials. First, we compared the optimal topology of discrete Euler-Bernoulli beam lattices with counterparts obtained using the homogenized Cosserat theory. We investigated the effect of material and numerical parameters on the optimization results and the global stiffness. Finally, the paper highlights the importance of second-order models for slender lattice structures through different macroscopic geometries. For the first time, we presented an excellent quantitative agreement between continuum Cosserat and discrete beam results. We demonstrated that the Cosserat theory is necessary and sufficient to optimize slender, lightweight designs with lattice-based microstructures. Furthermore, the results showed that the locally allowed volume fraction was the most critical limiting parameter when maximizing global stiffness. Finally, we found that the reinforced honeycomb lattice is the stiffest microstructure for a given mass among the investigated forms.

Keywords: Cosserat elasticity, Topology optimization, Lattice structures, Gradient elasticity, Metamaterial

1. Introduction

Historically, when creating structures with large spans (e.g., bridges, roofs, or towers), lattice and truss elements were used to reduce the total mass and increase the global stiffness. However, early in history, structural engineers realized that by increasing the space between bent components, the added tensile and compression forces would increase the bending inertia quadratically with the distance (Huygens–Steiner theorem). As a consequence, the additional bending momentum would magnify not only the stiffness but also the global stability of the structures. This way, structures can span considerable distances that are not accessible to solid forms.

A similar phenomenon is seen in nature. A structural hierarchy is found when observing the microstructure of diverse load-bearing components. Examples range from cork [16], through many Diatom species [30], honeycombs [44] and the trabecular bone [35, 50]. In all cases, smaller beam-like elements form an intricate network based on the characteristic loads.

¹² In recent years, with the advancements in additive manufacturing, metamaterials with custom-made microstructures ¹³ have been prepared [6]. In addition to an increased stiffness, this small-scale procedure makes the load-bearing elements ¹⁴ stronger. Moreover, as the material approaches its microscopic length scale, the manufacturing defects' size and effect are ¹⁵ reduced. As a result, macroscopically brittle materials might behave in a ductile manner [73, 7] thereby giving rise not ¹⁶ only to a lightweight and stiff material but also a resistant one.

17 Thanks to the advanced manufacturing processes, developing new products with specific optimized properties is possible by modifying their shape or topology. Topology optimization provides a suitable mathematical framework to optimize 18 the material distribution, *i.e.*, the spatial distribution of the material in a design domain. After defining a cost function 19 to be minimized, the sensitivity analysis provides an updating scheme for the design variables. The cost function can 20 be defined for various quantities of interest (compliance, maximal stress, target shape, displacements, etc.). Topology 21 optimization problems can be considered constrained as Partial Differential Equation (PDE) design problems, requiring a 22 combination of optimization solvers and numerical discretization schemes to solve the PDEs physical equations (mainly 23 the finite element method). Two types of optimization solvers can be used: (i) meta-heuristic approaches needing only a 24 back run call of different cost function computations [19] and (ii) gradient-based solvers where the derivative of the cost 25 function is required. Gradient-based topology optimization is usually based on the adjoint state method. 26

*Corresponding author

Email address: gergely.molnar@insa-lyon.fr (Gergely Molnár)

The literature cites several approaches for topology optimization. Density-based techniques pioneered by the standard 27 Solid Isotropic Material with Penalization (SIMP) method [9, 11] have proven their efficiency in structural topology 28 design for a broad range of applications. SIMP considers density variables defined at each element of the finite element 29 discretization as the optimized topology's design parameters (design variables). The main idea is to consider the elastic 30 behavior at each element designated by a power law introducing a density variable that has a value between 0 (no material) 31 and 1 (material) and a power law parameter (larger than 1) aiming to penalize intermediate densities. Consequently, when 32 the penalization parameter is adequately chosen, the spatial material distribution leads to an optimized structure with 33 only two material types: void regions (elements with no stiffness) and solid regions (elements whose stiffnesses equal the 34 bulk behavior). Empirically, the penalization parameters are taken to be greater than 3. However, the works of Bendsøe 35 and Sigmund [10] propose a rigorous methodology for their calibration. 36

One other important issue when using such approaches is the checkerboard pathology. It is due to the apparition of neighboring elements with alternating void and solid materials. This problem can be addressed with the use of filter solutions. Usually, one can employ density filters to impose limitations on the density variation by a fixed length scale in the stiffness distribution. Another option is to introduce sensitivity filtering so that the design sensitivity is maintained in a fixed neighborhood. Filtering techniques are efficient for limiting mesh-dependency in density-based topology optimization solvers [12].

The other class of topology optimization is based on the level-set function as a parametrization of the design domain topology [56, 47]. The level-set function represents the boundaries between void and solid phases, and the spatial evolution of the void-solid interfaces is usually governed by a shape derivative [59] or a topological derivative [29] to find the gradient direction toward the optimized topology. In recent years, numerous investigations have been proposed for level-set-based topology optimization approaches [4, 3, 67, 45].

Thanks to the recent advent of manufacturing technologies, the design of advanced materials, incorporating small scales 48 with complex topologies, has become possible. However, simulations for structural optimization describing the finest scales 49 are computationally expensive. Therefore, multi-scale topology optimization techniques have emerged as a macro-to-micro 50 optimization technique with noteworthy performances. The optimized structure results from the macro topology design 51 as the optimized representation of ascribed microstructures (which can be spatially varying). Such two-scale optimization 52 bridges the underlying scales with less expansive effort while capturing relevant microstructural effects. However, the 53 optimization process considers the microstructure effect exclusively by its effective (homogenized) behavior. Various 54 previous studies have investigated the potential macro-micro design optimization [37, 31, 28, 71, 65, 26, 55, 70, 63, 42]], 55 and most of the corresponding papers are based on scale separation assumptions and periodic homogenization theory. 56 In order to accelerate multi-scale processes, approaches merging data-driven techniques have recently been developed to 57 58 accelerate multi-scale topology optimization solvers [21, 66, 33, 72, 20].

The main explorations deal with the framework of the Cauchy theory, and the methods are thus suitable for large-scale transitions but limited to exhibiting the microstructure size effects. Moreover, such first-order frameworks fail when the scale separation assumption does not prevail (*e.g.*, when topology cells are kinematically coupled as in some compliant mechanisms). Enriched kinematic homogenization schemes are needed to efficiently design architected materials and capture local microstructural effects, mutual interactions, non-localities, or instabilities.

One of the first higher-order theories was proposed by the Cosserat brothers [18]. They enriched the simple Cauchy model with an independent rotation field gradient. This way, the model had three displacement and three rotational degrees of freedom (in 2D: two displacements DoFs and one rotation DoF). This theory was the first to define couple stresses and to render the Cauchy stress tensor non-symmetric. Since its first introduction, Toupin [62] formulated the energy density function using the classic displacement and rotation gradient terms. Finally, Mindlin [43] gave the linearized mathematical theory, serving as the basis of the variational solution.

Since its first introduction, the Cosserat theory has been used in numerous fields such as granular materials [39], masonry structures [1], composites [34], or even human bone [36, 46]. However, most importantly, it was shown that Cosserat elasticity efficiently captures the effect of the intrinsic length scale in cellular structures [53]. The constitutive equations of the model can be written in several forms ranging from a single added constant to Hooke's law [2] to the entirely redefined stiffness matrix [69]. However, one of the main disadvantages of the Cosserat theory is that is has too many material parameters.

Bottom-up homogenization methods are usually applied to determine the elastic Cosserat constants of lattice structures. Two main approaches exist: (i) the micro-scale is represented by an inhomogeneous Cauchy continuum [25, 22, 24, 23], and (ii) the lattices are modeled with either Euler-Bernoulli [48, 54, 49] or Timoshenko–Ehrenfest beams [40]. The important difference is that in the latter case, the rotational degrees of freedom are already present at the microscale. On the other hand, with beam theory, the solid volume fraction cannot be represented. This paper focuses on analytical results obtained ⁸¹ using the asymptotic method on Euler-Bernoulli beams [48, 54], and the limitations of the model are discussed.

In recent years, various studies have been devoted to obtaining the optimal topology with a characteristic length scale by using the Cosserat theory. Most works have focused on fictitious materials with only a few elastic constants. Parameter studies have been conducted to investigate the effect of the intrinsic length [27, 52, 41, 5, 38], the fundamental eigenfrequencies [13, 60, 61], the Cosserat shear modulus [17], and even 3D non-centrosymmetricity [64]. A majority of the investigations were based on the use of the SIMP and the level set methods to obtain the results.

Among the various models proposed in the literature, second gradient elasticity (such as a Cosserat medium) and micromorphic [68, 51] computational homogenization methods seem to be adequate tools to be integrated into topology optimization simulations. Indeed, encouraging recent results for bottom-up multiscale modeling of microstructural materials with enriched kinematics revive their use in design optimization. However, this topic remains an open research field [14].

Most studies focusing on the topology optimization of the Cosserat medium use fictitious material parameters, whereas papers presenting the optimization of lattice structures calculate only the Cauchy coefficients [66]. A comparative analysis using real microstructures and a homogenized second-order continuum has yet to be performed.

In the present paper, we present an new method to optimize the topology of slender lattice structures with small local volume fractions. We compare the optimal topology of discrete Euler-Bernoulli beam lattices to topologies obtained using the Cosserat theory. The local stiffness is calculated based on real geometrical properties, such as the beam height or the slenderness. We finally highlight the importance of the enriched model in the optimization of lattice structures and present optimal microstructures for a variety of macroscopic mechanical problems.

The paper is structured as follows. First, section 2 introduces the basic concept of topology optimization, after which section 3 lays out the different mechanical descriptions. Subsequently section 4 discusses the effect of both numerical and lattice parameters on the optimal topology. This is followed by a discussion on the optimal microstructure in section 5. Finally, section 6 concludes the paper.

¹⁰⁴ 2. Topology optimization

Topology optimization is a design method in which the material is distributed inhomogeneously in the design domain to maximize a specific property. We chose to use the algorithm published by Sigmund [58] and replaced the arbitrary design variable with the height of the beams. Among its advantages, the modified algorithm is easy to implement, robust, and converges rapidly. Despite that Bendsøe and Sigmund [10] showed that, for the SIMP method, the cubic penalty function is physically permissible, we decided to use the constitutive analytic relations. Based on the Bernoulli beam theory, the Cosserat stiffness constants used in this paper were deduced from asymptotic approaches [48, 54]. In addition, constraints on the maximum height and volume ratios are discussed in section 3.

The overall aim of the topology optimization procedure is to keep the compliance of the model at a minimum by minimizing the potential energy as a function of the local design variables:

$$\mathbf{h} = \operatorname{Arg\,inf}_{\mathbf{h}} \left\{ c\left(\mathbf{h}\right) = \frac{1}{2} \mathbf{U}^{T} \mathbf{K} \mathbf{U} = \frac{1}{2} \sum_{e=1}^{N} \mathbf{u}_{e}^{T} \mathbf{k}_{e} \left(h_{e}\right) \mathbf{u}_{e} \right\}.$$
(1)

¹¹⁴ This was done by respecting the equilibrium constraint:

$$\mathbf{KU} = \mathbf{F},\tag{2}$$

and the volume constraint:

$$\frac{V\left(\mathbf{h}\right)}{V_{0}} = f,\tag{3}$$

with a lower and an upper limit on the design variables (beam heights):

$$0 < \mathbf{h}_{\min} \le \mathbf{h}_e \le \mathbf{h}_{\max}.$$
(4)

In eq. (1), c is the total potential energy, **U** and \mathbf{u}_{e} are the vectors of the global and elementary degrees of freedom (translation, rotation), **K** and \mathbf{k}_{e} are the global end elementary stiffness matrices, N is the number of finite elements in the design domain, and **h** is the vector containing the elementary design variables (h_{e}). In our case, this is the height of the beam cross sections. In this paper, we assume rectangular beam sections with a unitary thickness in the out-of-plane



Figure 1: Basic structure of the topology optimization algorithm.

(z) direction. In the equilibrium equation (2), \mathbf{F} is the global force vector, V is the total volume of the model, V_0 is the volume of the design domain and f is called the relative density or prescribed volume fraction.

The optimization problem is formulated based on the algorithm proposed by Sigmund [58]. Apart from that work, the penalty exponent was replaced by the exact stiffness as a function of the beam height (the design variable); as in lattice structures, this variable comes with a physical meaning. The optimality criteria method [8] with a sensitivity filter [57] was utilized to update the design variables for a given equilibrium problem.

As shown in Fig. 1, we kept the original structure of Ref. [58]. However, we replaced each block with our own features. As the paper discusses different mechanical descriptions (Cauchy, Cosserat, Euler-Bernoulli beam) for the same mechanical problem, these blocks varied accordingly.

First, the finite element model was generated, after which the first equilibrium was obtained. The analytic solutions were applied to calculate the stiffness, energy, and sensitivity functions. For the Cosserat medium, the results of references [48] and [54] were utilized. Finally, the filter was applied directly to the array containing the sensitivity functions, as initially done by Sigmund [58] where rmin was the effective filter distance. Next, the design variables were updated iteratively to satisfy the volume constraint. Finally, the convergence was verified: if the maximum change in the design variable was smaller than $(h_{max} - h_{min})/1000$, the algorithm was stopped. Otherwise, a new equilibrium was determined with the new design variable distribution.

137 3. Mechanical description

This section briefly summarizes the basic mechanical descriptions used in the paper. All simulations assumed a static equilibrium, wherefore, each model was governed by a set of equations describing equilibrium, the kinetic constraints, and the material model.

141 3.1. Cauchy continuum

In continuum mechanics, probably one of the most frequently used assumptions is proposed by Cauchy [15]. The equilibrium of the differential object is depicted in Fig. 2(a) and can be described with the following set of equations:



Figure 2: Equilibrium and admissible deformations of the elementary volume of the (a) Cauchy, (b) Euler-Bernoulli beam, and (c) Cosserat theories.

$$\nabla \boldsymbol{\sigma} + \mathbf{b} = \mathbf{0} \quad \text{in} \quad \Omega, \boldsymbol{\sigma} \cdot \mathbf{n} = \mathbf{\bar{t}} \quad \text{on} \quad \Gamma_N, \mathbf{u} = \mathbf{\bar{u}} \quad \text{on} \quad \Gamma_D,$$
(5)

where σ is the stress tensor, and **b** represents body forces (in our case zero). The second and third rows describe respectively Neumann and Dirichlet boundary conditions. The bar symbol represents external forces ($\bar{\mathbf{t}}$), and prescribed displacements ($\bar{\mathbf{u}}$).

¹⁴⁷ The material is considered to be linear elastic:

$$\boldsymbol{\sigma} = \mathbf{C}\boldsymbol{\varepsilon},\tag{6}$$

where **C** is the stiffness matrix, and ε the strain tensor. Due to the local equilibrium ($\sigma_{xy} = \sigma_{yx} = \tau_{xy}$) the Voight notation can be used, thus simplifying the stress tensor to a vector with 3 components in 2D: $\boldsymbol{\sigma} = \begin{bmatrix} \sigma_x & \sigma_y & \tau_{xy} \end{bmatrix}^T$. Consequently, **C** becomes a 3 × 3 matrix. The strain tensor is also simplified to the three elementary deformations shown in Fig.2(a). Assuming small deformations, the displacement-strain relationship can be expressed as:

$$\varepsilon_x = \frac{\partial u_x}{\partial x}, \varepsilon_y = \frac{\partial u_y}{\partial y}, \gamma_{xy} = \frac{\partial u_x}{\partial y} + \frac{\partial u_y}{\partial x}.$$
(7)

To solve the mechanical problem, the following energy is minimized with respect to the degrees of freedom by following the kinematically admissible set given in eq. $(5)_3$. In this first case, the displacements are obtained by solving the following minimization problem:

$$\mathbf{u} = \operatorname{Arg\,inf}_{\mathbf{u}} \left\{ \int_{\Omega} \frac{1}{2} \boldsymbol{\varepsilon}^{T} \mathbf{C} \boldsymbol{\varepsilon} - \mathbf{b} \cdot \mathbf{u} d\Omega - \int_{\Gamma} \mathbf{\bar{t}} \cdot \mathbf{u} d\Gamma \right\}.$$
(8)

155 3.2. Euler-Bernoulli model

To model slender beam structures, the Euler-Bernoulli beam theory provides the most approachable framework. The classical beam theory is adapted to describe the behavior of elongated load-bearing elements with one side significantly larger than the others. The three primary assumptions that have to be made are that (i) the plane sections remain plane, (ii) the plane sections are perpendicular to the neutral axis, and (iii) the deformed beam angles are small. Thus, the equilibrium shown in Fig. 2(b) can be described by the following equations:

$$\frac{d^2M}{dt^2} + p_n = 0,
\frac{dN}{dt} + p_t = 0.$$
(9)

Here, M and N represent the bending moment and the normal force, and p_n and p_t are distributed loads perpendicular and parallel to the neutral axis. These equations are completed with Neumann and Dirichlet boundary conditions similar to that of eq. (5)_{2,3}. The Euler-Bernoulli beam theory neglects the effect of shear deformation, and as a result, it is adapted to describe the response of slender beams. The linear elastic response can be obtained by:

$$\begin{aligned} M &= EI\kappa_t, \\ N &= EA\varepsilon_t, \end{aligned} \tag{10}$$

where κ_t and ε_t are the two types of deformations present beams can be subjected to: (i) curvature/bending and (ii) elongation/compression. E is Young's modulus, I is the bending moment of inertia around axis z, and A is the area of the cross-section.

¹⁶⁸ To obtain the relationship between the degrees of freedom and the deformations, the following assumptions are used:

$$\kappa_t = \frac{\partial \phi}{\partial t} = \frac{\partial^2 u_n}{\partial t^2}, \quad \varepsilon_t = \frac{\partial u_t}{\partial t}, \tag{11}$$

where ϕ is the rotation, u_n is the perpendicular displacement, and u_t is the parallel displacement in relation to the neutral axis.

To obtain equilibrium, the following energy functional is minimized by following the kinematically admissible set:

$$(\mathbf{u},\phi) = \operatorname{Arg\,inf}_{\mathbf{u},\phi} \left\{ \int_{L} \frac{1}{2} \left(\varepsilon_{t}^{2} E A + \kappa_{t}^{2} E I \right) dL - \mathbf{p} \cdot \mathbf{u} dL - \mathbf{\bar{t}} \cdot \mathbf{u} - \bar{M} \cdot \phi \right\}.$$
(12)

The bar symbol represents external forces $(\bar{\mathbf{t}})$, and moments (M).

173 3.3. Cosserat continuum

The classical description of continuum mechanics is ill-suited to characterize the response of materials with an inhomogeneous microstructure, *i.e.*, a characteristic microscopic length scale. However, the mechanical behavior of architected materials (*e.g.*, lattice structures) is often determined by their specific micro-scale configurations. Therefore, the Cosserat theory (or micropolar elasticity) incorporates rotational degrees of freedom (ϕ) into the mechanical description.

The Cauchy model is completed with an additional set of equations describing momentum equilibrium as shown in Fig. 2(c):

$ abla \sigma + \mathbf{b} = 0$	in	$\Omega,$	
$ abla \mu + \sigma \hat{\epsilon} = 0$	in	$\Omega,$	
$oldsymbol{\sigma} \cdot \mathbf{n} = \overline{\mathbf{t}}$	on	$\Gamma_N,$	(13)
$\boldsymbol{\mu} \cdot \mathbf{n} = \bar{M}$	on	$\Gamma_N,$	(13)
$\mathbf{u} = \mathbf{\bar{u}}$	on	Γ_D ,	
$\phi = \bar{\phi}$	on	$\Gamma_D.$	

In this equation, $\boldsymbol{\sigma}$ is now a non-symmetric $(\sigma_{xy} \neq \sigma_{yx})$ force-stress tensor, $\boldsymbol{\mu}$ is the moment or couple-stress tensor, and $\hat{\boldsymbol{\epsilon}}$ is the Levi-Civita symbol. The bar symbol represents external forces $(\bar{\mathbf{t}})$, moments (\bar{M}) , prescribed displacements $(\bar{\mathbf{u}})$, and rotations $(\bar{\phi})$.

The literature [24] recounts various ways to define linear elastic behavior. In this paper, we chose to correlate the complete stress tensor to the deformation components using the following model:

$$\begin{bmatrix} \sigma_{x} \\ \sigma_{y} \\ \tau_{xy} = \frac{\sigma_{xy} + \sigma_{yx}}{2} \\ \vartheta_{xy} = \frac{\sigma_{xy} - \sigma_{yx}}{2} \\ \mu_{x} \\ \mu_{y} \end{bmatrix} = \begin{bmatrix} [\mathbf{C}]_{3\times3} & \mathbf{0} & \mathbf{0} \\ \mathbf{0} & G_{c} & \mathbf{0} \\ \mathbf{0} & \mathbf{0} & [\mathbf{D}]_{2\times2} \end{bmatrix} \begin{bmatrix} \varepsilon_{x} \\ \varepsilon_{y} \\ \gamma_{xy} \\ \omega_{xy} \\ \kappa_{x} \\ \kappa_{y} \end{bmatrix}.$$
(14)



Figure 3: Optimized topology of a cantilever: (a) geometry (L = 100, H = 50), (b) optimal topology using the Cauchy and the beam model for f = 0.12 ($r_{\min} = 1$).

As a result, the first three elements of the stress vector correspond to the Cauchy stress components, the fourth element provides the difference between σ_{xy} and σ_{yx} , finally, the last components are the couple stresses.

The corresponding deformations are depicted in Fig. 2(c), with the missing kinematic constraints described by the following:

$$\omega_{xy} = \frac{\partial u_x}{\partial y} - \frac{\partial u_y}{\partial x} - 2\phi, \quad \kappa_x = \frac{\partial \phi_x}{\partial x}, \quad \kappa_y = \frac{\partial \phi_y}{\partial y}.$$
(15)

¹⁸⁹ The equilibrium is then obtained by minimizing the following functional equations:

$$(\mathbf{u},\phi) = \operatorname{Arg}\inf_{\mathbf{u},\phi} \left\{ \int_{\Omega} \frac{1}{2} \left[\boldsymbol{\varepsilon}^{T} \mathbf{C} \boldsymbol{\varepsilon} + \omega_{xy}^{2} G_{c} + \boldsymbol{\kappa}^{T} \mathbf{D} \boldsymbol{\kappa} \right] - \mathbf{b} \cdot \mathbf{u} d\Omega - \int_{\Gamma} \overline{\mathbf{t}} \cdot \mathbf{u} + \bar{m} \cdot \phi d\Gamma \right\}.$$
(16)

¹⁹⁰ By incorporating rotational degrees of freedom into the continuum description, the Cosserat theory proposes an ¹⁹¹ analogous description to the discrete beam model with a significantly lower computational cost.

¹⁹² 4. Numerical examples

Fig. 3(a) depicts the geometry of the optimization problem. In this section, a cantilever geometry of length (L) 100 and height (H) 50 was chosen. The concentrated force (F) applied at the end was 10^{-3} unless otherwise specified. This paper presents the model and the results in dimensionless quantities. Young's modulus was set to 1. Both translational and rotational degrees of freedom were constrained on the nodes on the left side.

For a beam structure, the volume constraint defined in eq. (3) can be expressed by summing up all the individual elements and dividing the sum by the overall area of the design domain:

$$f = \frac{V\left(\mathbf{h}\right)}{V_0} = \frac{\sum\limits_{e=1}^{N} h_e l_e}{LH},\tag{17}$$

where V_0 is the total volume of the design domain, l_e represents the individual length of the beams, and h_e is their height. There are N beams in the structure. In this case, h_e , The design variable has a geometrical significance wherefore its bounds can be defined as:

$$0 < h_{\min} \le h_e \le h_{\max},\tag{18}$$

with h_{\min} as a lower bound responsible for numerical stability ($h_{\min} = h_{\max}/5000$), and h_{\max} as an upper bound:

$$h_{\max} \le \frac{V_0}{\sum\limits_{i=1}^N l_i}.$$
(19)

Lattice type	l_x	l_y	$\sum l_e$	$V_{\rm RVE}$	$h\left(f_{ m RVE} ight)$	$f_{\mathrm{RVE}}\left(h ight)$	$f_{\rm RVE} \left(l_e / h = 5 \right)$
Rectangular	l_m	l_m	$2l_m$	l_m^2	$\frac{l_m f_{\rm RVE}}{2}$	$\frac{2h}{l_m}$	0.4
Honeycomb	$\sqrt{3}l_m$	$3l_m$	$6l_m$	$3\sqrt{3}l_m^2$	$\frac{\sqrt{3}}{2}l_m f_{\rm RVE}$	$\frac{2h}{\sqrt{3}l_m}$	$\frac{2}{5\sqrt{3}} = 0.23$
Reinforced honeycomb	$\sqrt{3}l_m$	$3l_m$	$l_m \left(6 + 6\sqrt{3}\right)$	$3\sqrt{3}l_m^2$	$\frac{\sqrt{3}l_m f_{\rm RVE}}{2+2\sqrt{3}}$	$\frac{h}{l_m} \frac{2+2\sqrt{3}}{\sqrt{3}}$	$\frac{2+2\sqrt{3}}{5\sqrt{3}} = 0.63$

Table 1: Lattice geometries and correlation between volume ratio and beam height.

Lattice type	C_{11}, C_{22}	C_{12}, C_{21}	C_{33}	G_c	D_{11}, D_{22}
Rectangular	$\frac{ht}{l_m}E$	0	$\frac{th^3}{2l_m^3}E$	$\frac{th^3}{2l_m^3}E$	$\frac{th^3}{12l_m}E$

Table 2: Cosserat constants for the rectangular beam lattice.

The characteristic quantities, upper bounds, and the correlation between local volume fraction and beam height are summarized in Table 1.

When using h_{max} , the RVE should be considered solid ($f_{\text{RVE}} = 1$). This limit is unsuitable for beam theory, and consequently, in the following examples, h_{max} is set to $l_e/5$, at which value the Euler-Bernoulli beam theory still gives a fairly precise outcome (the difference to the Timoshenko–Ehrenfest theory is 3.06%).

Part (b) of Fig. 3 shows the optimization results of a rectangular lattice modeled using the Cauchy continuum (with SIMP) and Euler-Bernoulli beams. When employing the Cauchy description, the design variable was penalized using a cubic function, and the maximum value of the design variable was limited to 0.4, which corresponds to the volume ratio of the rectangular grid RVE when $h_e = l_m/5$. It can be clearly seen that Cauchy's description with the SIMP technique is unable to correctly determine the optimal topology.

In the present paper, we discuss three microstructures: square, hexagonal, and reinforced honeycomb lattices. The reason for this is that the analytic Cosserat stiffness components for these structures are available in the literature [48, 54]. Tables 2 and 3 summarize each constant of the matrices \mathbf{C} , \mathbf{D} and the component G_c . The remaining components of the matrices were zero.

The aim of section 4 is to prove that the Cosserat medium is necessary and sufficient to optimize the topology of light and slender beam lattices. Therefore, each material and numerical parameter was tested using the Euler-Bernoulli beam and the Cosserat theory, after which the optimal topology and the final displacement (u_y^F) measured at the concentrated force F were compared. It should be noted, that the objective function (potential energy) was equal to $c = F u_y^F/2$, and

Lattice type	K_s	G_s	G_c	D_{11}, D_{22}
Ť!	$\frac{\sqrt{3}}{6}\frac{Eth}{l_m}$	$rac{Eth^3}{\sqrt{3}l_m(l_m^2+h^2)}$	$\frac{Eth^3}{2\sqrt{3}l_m^3}$	$\frac{Eth^3}{12\sqrt{3}l_m}$
Honeycomb				
	$\frac{3+\sqrt{3}}{6}\frac{Eth}{l_m}$	$\frac{\frac{t^2h^6}{3} + \frac{4}{3}(\sqrt{3}+1)t^2h^4l_m^2 + l_m^4t^4h^4}{4l_m^3(l_m^2th + th^3)}E$	$\frac{3+\sqrt{3}}{6\sqrt{3}}\frac{Eth^3}{l_m^3}$	$\frac{1+\sqrt{3}}{12\sqrt{3}}\frac{Eth^3}{l_m}$
Reinforced honeycomb				

Table 3: Cosserat constants for honeycomb and reinforced honeycomb beam lattices. $C_{11} = C_{22} = K_s + G_s, C_{12} = C_{21} = K_s - G_s, C_{33} = G_s.$



Figure 4: Topology and deflection results on a rectangular grid as a function of local and global volume fractions.

the potential energy was thus not an independent measure of optimality.

222 4.1. Square lattice

The homogenized stiffness of a rectangular grid lattice is orthotropic. The two principal orientations are parallel to the 223 two main beam directions. Due to the lack of normal interaction, $C_{12} = 0$, which means that extension in one direction 224 causes no contraction in the other. This property signifies that the homogenized material's Poisson's ratio is zero ($\nu = 0$). 225 The rectangular beam lattice was used to demonstrate the effect of the volume fractions on the optimal topology. We 226 distinguish between local f_{RVE} and global f values, where f_{RVE} represents the allowed maximum local volume fraction, 227 while f is the global volume fraction defined in eq. (17). These two quantities are independent, with $f \leq f_{\text{RVE}}$, and f_{RVE} 228 is mostly controlled by prescribing a lower beam height in the model based on the correlation shown in Table 1. Due to 229 the difference in local geometry, various lattice structures have different $f_{\rm RVE}$ for the same l_e/h_e ratio. 230

The beam model was constructed from 300×150 RVEs. The beam segments were unified, which resulted in 90 450 beam finite elements with $l_m = 1/3$. The load was applied on a node situated on the bottom line furthest to the right. The Cosserat model was divided into 300×150 4-node quadrilateral elements. We used 45000 elements to capture similar topology details as in the beam model. The advantage of the Cosserat model is that l_m reduces to a material parameter, and the element size does not affect it. The material and the boundary conditions can be found in the main part of Section 4. A filter of $r_{\min} = 1$ was used in both cases.

The first two rows of Fig. 4(a) and (b) show the optimal topology for two global volume fractions obtained using a beam model (left) and the Cosserat continuum (right). The third row portrays the change if thicker beams are allowed. The results displayed in the two columns are almost identical. However, they differed significantly from the outcome obtained using the Cauchy continuum and the SIMP technique shown in Fig. 3(b).

Similar to the topologies, the displacement results were also in good correspondence. Fig. 4(c) shows the effect of the 241 local slenderness. The maximum difference between the deflection values was 2.16%, which was within the precision of 242 the built models. Furthermore, we observed a tendency to favor thicker beams. When $f_{\rm RVE}$ increased, the maximum 243 deflection decreased. Without a global stability analysis, the optimal topology favors thinner elements with higher local 244 volume fractions. When $h_{\rm max}$ was reduced, the size of the global elements grew, raising the moment of inertia but lowering 245 the leverage-resulting in a less rigid structure. This effect was demonstrated but not discussed by Watts [66], where the 246 optimal topology was fairly independent of the chosen structure, and local maxima gave mostly solid parts (with $f_{\text{RVE}} = 1$). 247 Of course, this solution defeats the purpose of creating an architected material. 248

Finally, Fig. 4(d) presents a plot of the deflection results as a function of the global volume fraction with $h_{\text{max}} = l_m/5$ ($f_{\text{RVE}} = 0.4$). The results were fitted perfectly using a hyperbolic function. Moreover, the maximum difference was 3.8%,



Figure 5: Topology and deflection results on a honeycomb structure as a function of the filter width.

which demonstrated how well the Cosserat theory reproduced the mechanical response of these periodic beam structures.

252 4.2. Honeycomb lattice

In contrast, the homogenization of honeycomb lattices gives an isotropic response with a Poison's ratio depending on the slenderness varying between 0.3-0.5 (for $l_e/h_e = 5$, it is 0.46). Therefore, as shown in Fig. 5, the optimal topologies are much closer to the results produced by SIMP. This section thus describes the use of the honeycomb structure to demonstrate the effect of the filter width (r min on the topology and the maximum deflection at the concentrated force as a measure of optimality.

The beam model was constructed from 300×87 RVEs. The beam segments were unified, which resulted in 156 387 beam finite elements with $l_m = 0.192$. The load was applied on a node situated on the bottom line furthest to the right. The Cosserat model was divided into 300×150 4-node quadrilateral elements (45000 elements), similarly to the rectangular case. The material and the boundary conditions can be found in the main part of Section 4. The filter width was varied through the analysis.

Fig. 5(a) and (b) show the results obtained using Euler-Bernoulli beams and the Cosserat continuum, respectively. An agreement was observed, highlighting the Cosserat theory's versatile potential. When the filtering was switched off, the two theories started to deviate, as shown in Fig. 5(d). However, it is our opinion that these results bear little practical importance.

Finally, we plotted the maximum deflection in Fig. 5(c). Introducing the filter reduced the optimality and the overall stiffness of the structure. By increasing the filter width, the displacement increased linearly. However, when $r_m in$ was smaller than the shortest distance between the beam elements, the filter could no longer complete its task, and the results started to fluctuate. Until that point, the maximum difference between the two methods was 1.51%.

271 4.3. Reinforced honeycomb lattice

Our third example focuses on the effect of the characteristic micro length scale on the reinforced honeycomb network. In this case, the classic hexagonal structure was fortified with a triangular grid. While the hexagonal structure was mostly a bending-dominated lattice, triangular cells provided normal rigidity. The homogenized Cauchy stiffness was isotropic with a Poisson's ratio varying between 0.3-0.34 (for $l_e/h_e = 5$, it is 0.325).

Different beam structures were created to test the effect of the micro-length. However, only whole RVEs were used to create the beam models. Due to the irrational size of the RVE, not many configurations had precisely the same size. Therefore, the following sample sizes were considered: 142×41 , 239×69 , 284×82 , 336 and 426×123 , which corresponded to $l_m = 0.4, 0.24, 0.2, 0.17$ and 0.14, respectively.



Figure 6: Topology and deflection results on a reinforced honeycomb structure as a function of l_m . The results for the concentrated force are shown with solid symbols, whereas for the empty ones, the load was distributed on a unit length.

The advantage of the Cosserat model is that there is no need to change the mesh for a different l_m value, as it is only a material parameter. However, both models were tested with a mesh following the change of l_m and one independent constant of 300×150 elements.

The finite element mesh was generated from 4 node quadrilateral elements. The material and the Dirichlet boundary conditions can be found in the main part of Section 4. A filter of $r_{\min} = 1$ was used in both cases.

After initial testing, the results showed that the concentrated force and the changing mesh had more significant effects on the deflection than l_m . Therefore, a model was developed to distribute the loading on a unit length. Practically, the force was divided and applied on the beam and the continuum model as shown in Fig. 6.

Fig. 6(a) and (b) show that neither l_m nor the Neumann boundary affected the optimal topology. Both the beam and Cosserat models gave a solid-like outer shell (with f_{RVE}) and a less filled interior. Fig. 6(c) displays the deflection results as a function of l_m . Its effect was found to be much smaller than the increased deflection originating from the singularity. When the load was distributed, a small increase in rigidity was observed in favor of larger motifs.

²⁹² 5. Discussion

In Section 4 we demonstrated that the Cosserat description was sufficient not only qualitatively but also quantitatively to describe the mechanical behavior of beam lattice structures. Moreover, the response as well as the optimal topologies was found to be in agreement.

Here, we take a step back to understand the critical components of the Cosserat description, ultimately investigating different structures (design domains) with varying L/H ratios to identify an "ideal" microstructure.

Fig. 7 shows the optimization problem introduced in Section 4. The elementary grid is a rectangular lattice with 300×150 RVEs, and the global volume fraction was set to f = 0.12 with an $r_{\min} = 1$ filter width. The results were compared with those of the beam model shown Fig. 3(b).

Fig. 7(a) presents, the optimal topology using the SIMP method with a $\nu = 0$ material and a cubic penalty. In this 301 first case, no limit was applied to the local volume ratio ($f_{\rm RVE} = 1$), and as a result, the final topology differed significantly 302 from the results obtained as compared to the beam lattice. Furthermore, the deflection was much smaller because of the 303 higher local volume ratio. As a result, the SIMP method with an isotropic material was inadequate to model slender 304 lattice structures. In part (b) the maximum stiffness was calculated with $f_{\rm RVE} = 0.4$ based on Tables 1 and 2. To scale 305 between empty and solid states, a cubic penalty was applied. This modification was the first step when the form started 306 to resemble the results obtained with the beam model. The global form was recovered, however, the details remained 307 dissimilar. Part (c) portrays the results when the penalty was omitted, and the stiffness was calculated based on 2. The 308 details started to emerge, however, the deflection values overestimated the beam results ($u_y^F = 2.5$) by 7.2%. Finally, part (d) presents the optimal topology obtained using the Cosserat theory. The details were fully recovered with a 1.2% 309 310 difference in the deflation value. 311

The introduction of the rotational degree of freedom and the Cosserat theory clearly helped recover the finer details and the precise mechanical response of the underlying beam structures. Compared to the classical continuum, the finite



Figure 7: Different approximations of the rectangular grid with the global volume ratio of f = 0.12: (a) isotropic Cauchy model with a maximum of $f_{\text{RVE}} = 1$ and a cubic penalty; (b) Cauchy model with a maximum of $f_{\text{RVE}} = 0.4$ and a cubic penalty; (c) Cauchy model with a maximum of $f_{\text{RVE}} = 0.4$ and a cubic penalty; (c) Cauchy model with a maximum of $f_{\text{RVE}} = 0.4$ based on the beam heights; (d) full Cosserat description. The rigidity was calculated based on Tables 2 and 3. The maximum displacement for the reference beam model at the concentrated load was $u_y^F = -2.50$ (see topology result in Fig. 3).



Figure 8: Maximum displacement as a function of the design space's aspect ratio for a global volume ratio of f = 0.075 and $l_m = 1/3$: (a) with $f_{RVE} = 0.23$ for all lattice geometries; (b) with their maximum volume ratios by respecting $l_e/h_e \ge 5$.

element implementation of the theory was not much more complicated. The only difficulty lies in determining the Cosserat
constants for arbitrary beam structures. However, this can be done using various homogenization methods [25, 32, 40].
The Cosserat optimization code used in this paper is included in Supplementary Materials.

The aspect ratio of the design space was varied to compare the three lattice structures. We were interested in 317 determining whether an optimal microstructure could be found as a function of the geometry. According to Fig. 4(c), 318 the locally allowed maximum volume fraction had a significant effect on the deflection results. Therefore, in Fig. 8(a) we 319 first compared results using the same local filling ratio, $f_{\rm RVE} = 0.23$. Interestingly, there was a competition between the 320 honeycomb and the rectangular grid. However, the reinforced honeycomb was consistently more rigid. When the local 321 volume fraction of the rectangular grid was increased to 0.4, it became superior to the honeycomb, even in the initial 322 interval. The results obtained using the Cosserat theory repeatedly corresponded well to the beam models. It could thus 323 be stated that, depending on the design problem, the optimal RVE can be appropriately chosen using Cosserat elasticity. 324

325 6. Conclusion

This paper presents a topology optimization algorithm based on the Cosserat theory. The continuum results were compared and verified using Euler-Bernoulli beam models, and the stiffness of the enriched medium was determined from analytic calculations.

We observed an excellent quantitative correspondence between continuum Cosserat and discrete beam results. We showed that the Cosserat theory was necessary and sufficient to optimize slender, lightweight designs with beam microstructures and that the maximum local volume ratio (thus the maximum beam height) significantly affected the optimal deflection values. The effect of the filter width and the local length scale were also tested.

The addition of the rotational degree of freedom allowed us to capture the equivalent behavior of the beam theory. The advantage of the Cosserat model is that l_m reduces to a material parameter wherefore, the element size does not affect the microstructure. Consequently, the calculations can be significantly accelerated compared to beam models.
 While the finite element implementation of the Cosserat theory is relatively simple, the stiffness components are available analytically only for a few periodic microstructures. Consequently, developing and publishing a universal homogenization algorithm is crucial in order to establish a database with various lattice structures used in practice. Furthermore, the algorithm should be employed to optimize the beam heights and, for example, the microscopic length scale.

340 **References**

- [1] Addessi, D., Sacco, E., Paolone, A., 2010. Cosserat model for periodic masonry deduced by nonlinear homogenization.
 European Journal of Mechanics A/Solids 29, 724–737. doi:10.1016/j.euromechsol.2010.03.001.
- [2] Aifantis, E.C., 1984. On the microstructural origin of certain inelastic models. Journal of Engineering Materials and
 Technology 106, 326–330. doi:10.1115/1.3225725.
- [3] Allaire, G., De Gournay, F., Jouve, F., Toader, A.M., 2005. Structural optimization using topological and shape
 sensitivity via a level set method. Control and cybernetics 34, 59.
- [4] Allaire, G., Jouve, F., Toader, A.M., 2004. Structural optimization using sensitivity analysis and a level-set method.
 Journal of computational physics 194, 363–393. doi:10.1016/j.jcp.2003.09.032.
- [5] Arimitsu, Y., Karasu, K., Wu, Z., Sogabe, Y., 2011. Optimal topologies in structural design of micropolar materials.
 Procedia Engineering 10, 1633–1638. doi:10.1016/j.proeng.2011.04.273.
- [6] Askari, M., Hutchins, D.A., Thomas, P.J., Astolfi, L., Watson, R.L., Abdi, M., Ricci, M., Laureti, S., Nie, L., Freear,
 S., Wildman, R., Tuck, C., Clarke, M., Woods, E., Clare, A.T., 2020. Additive manufacturing of metamaterials: A
 review. Additive Manufacturing 36, 101562. doi:10.1016/j.addma.2020.101562.
- [7] Bauer, J., Schroer, A., Schwaiger, R., Kraft, O., 2016. Approaching theoretical strength in glassy carbon nanolattices.
 Nature materials 15, 438–443. doi:10.1038/nmat4561.
- [8] Bendsøe, M.P., 1995. Optimization of structural topology, shape, and material. volume 414. Springer. doi:10.1007/978-3-662-03115-5.
- [9] Bendsøe, M.P., Kikuchi, N., 1988. Generating optimal topologies in structural design using a homogenization method.
 Computer methods in applied mechanics and engineering 71, 197–224. doi:10.1016/0045-7825(88)90086-2.
- [10] Bendsøe, M.P., Sigmund, O., 1999. Material interpolation schemes in topology optimization. Archive of applied
 mechanics 69, 635–654. doi:10.1007/s004190050248.
- [11] Bendsøe, M.P., Sigmund, O., 2003. Topology Optimization: Theory, Methods and Applications. Springer.
 doi:10.1007/978-3-662-05086-6.
- [12] Bourdin, B., 2001. Filters in topology optimization. International Journal for Numerical Methods in Engineering 50,
 2143-2158. doi:10.1002/nme.116.
- [13] Bruggi, M., Taliercio, A., 2012. Maximization of the fundamental eigenfrequency of micropolar solids through topology
 optimization. Structural and Multidisciplinary Optimization 46, 549–560. doi:10.1007/s00158-012-0779-3.
- [14] Calisti, V., Lebée, A., Novotny, A., Sokolowski, J., 2021. Sensitivity of the second order homogenized elasticity tensor
 to topological microstructural change. Journal of Elasticity 144, 141–167. doi:10.1007/s10659-021-09836-6.
- [15] Cauchy, A.L., 1823. Recherches sur l'équilibre et le mouvement intérieur des corps solides ou fluides, élastiques ou non élastiques. Bulletin de la Société Philomatique, 9–13.doi:10.1017/CBO9780511702518.038.
- [16] Chen, B., Yuan, Q., Luo, J., Fan, J.H., 2010. Fibre reinforced cellular microstructure of cork wood. Plastics, Rubber
 and Composites 39, 86–90. doi:10.1179/174328910X12608851832650.
- ³⁷⁴ [17] Chen, L., Wan, J., Chu, X., Liu, H., 2021. Parameterized level set method for structural topology optimization based ³⁷⁵ on the cosserat elasticity. Acta Mechanica Sinica 37, 620–630. doi:10.1007/s10409-020-01045-z.

- ³⁷⁶ [18] Cosserat, E., Cosserat, F., 1909. Théorie des corps déformables. Librairie Scientifique A. Hermann et Fils.
 ³⁷⁷ doi:10.1038/081067a0.
- ³⁷⁸ [19] Di Cesare, N., Domaszewski, M., 2019. A new hybrid topology optimization method based on i-pr-pso and eso. appli-³⁷⁹ cation to continuum structural mechanics. Computers Structures 212, 311–326. doi:10.1016/j.compstruc.2018.11.006.
- [20] Djourachkovitch, T., Blal, N., Hamila, N., Gravouil, A., 2021. Multiscale topology optimization of 3d structures: A micro-architectured materials database assisted strategy. Computers and Structures 255, 106574.
 doi:10.1016/j.compstruc.2021.106574.
- Ferrer, A., Cante, J.C., Hernández, J., Oliver, J., 2018. Two-scale topology optimization in computational ma terial design: An integrated approach. International journal for numerical methods in engineering 114, 232–254.
 doi:10.1002/nme.5742.
- [22] Forest, S., 1998. Mechanics of generalized continua: construction by homogenizaton. Le Journal de Physique IV 8,
 39–48. doi:10.1051/jp4:1998405.
- Forest, S., 2002. Homogenization methods and mechanics of generalized continua-Part 2. Theoretical and applied
 mechanics, 113-144doi:10.2298/TAM0229113F.
- Forest, S., Pradel, F., Sab, K., 2001. Asymptotic analysis of heterogeneous cosserat media. International Journal of
 Solids and Structures 38, 4585–4608. doi:10.1016/S0020-7683(00)00295-X.
- ³⁹² [25] Forest, S., Sab, K., 1998. Cosserat overall modeling of heterogeneous materials. Mechanics research communications
 ³⁹³ 25, 449–454. doi:10.1016/S0093-6413(98)00059-7.
- [26] Gaynor, A.T., Meisel, N.A., Williams, C.B., Guest, J.K., 2014. Multiple-material topology optimization of compliant
 mechanisms created via polyjet three-dimensional printing. Journal of Manufacturing Science and Engineering 136.
 doi:10.1115/1.4028439.
- ³⁹⁷ [27] Gei, M., Rovati, M., Veber, D., 2006. Effect of internal length scale on optimal topologies for cosserat continua,
 ³⁹⁸ in: Bendsøe, M.P., Olhoff, N., Sigmund, O. (Eds.), IUTAM Symposium on Topological Design Optimization of
 ³⁹⁹ Structures, Machines and Materials, Springer Netherlands. pp. 157–166. doi:10.1007/1-4020-4752-5_16.
- [28] Groen, J.P., Sigmund, O., 2018. Homogenization-based topology optimization for high-resolution manufacturable
 microstructures. International Journal for Numerical Methods in Engineering 113, 1148–1163. doi:10.1002/nme.5575.
- [29] Jackowska-Strumillo, L., Sokolowski, J., Zochowski, A., 1999. The topological derivative method in shape optimiza tion, in: Proceedings of the 38th IEEE Conference on Decision and Control (Cat. No.99CH36304), pp. 674–679 vol.1.
 doi:10.1109/CDC.1999.832864.
- [30] Jang, D., Meza, L.R., Greer, F., Greer, J.R., 2013. Fabrication and deformation of three-dimensional hollow ceramic nanostructures. Nature materials 12, 893–898. doi:10.1038/nmat3738.
- Kato, J., Yachi, D., Kyoya, T., Terada, K., 2018. Micro-macro concurrent topology optimization for nonlinear solids
 with a decoupling multiscale analysis. International Journal for Numerical Methods in Engineering 113, 1189–1213.
 doi:10.1002/nme.5571.
- [32] Kouznetsova, V., Geers, M.G.D., Brekelmans, W.A.M., 2002. Multi-scale constitutive modelling of heterogeneous materials with a gradient-enhanced computational homogenization scheme. International journal for numerical methods in engineering 54, 1235–1260. doi:10.1002/nme.541.
- [33] Kumar, S., Tan, S., Zheng, L., Kochmann, D., 2020. Inverse-designed spinodoid metamaterials. npj Computational
 Materials 6, 73. doi:10.1038/s41524-020-0341-6.
- [34] Lakes, R., 1991. Experimental Micro Mechanics Methods for Conventional and Negative Poisson's Ratio Cellular
 Solids as Cosserat Continua. Journal of Engineering Materials and Technology 113, 148–155. doi:10.1115/1.2903371.
- ⁴¹⁷ [35] Lakes, R., 1993. Materials with structural hierarchy. Nature 361, 511–515. doi:10.1038/361511a0.
- ⁴¹⁸ [36] Lakes, R., Saha, S., 1979. Cement line motion in bone. Science 204, 501–503. doi:10.1126/science.432653.

- [37] Li, H., Luo, Z., Gao, L., Qin, Q., 2018. Topology optimization for concurrent design of structures with multi patch microstructures by level sets. Computer Methods in Applied Mechanics and Engineering 331, 536–561.
 doi:10.1016/j.cma.2017.11.033.
- [38] Li, L., Khandelwal, K., 2015. Topology optimization of structures with length-scale effects using elasticity with
 microstructure theory. Computers & Structures 157, 165–177. doi:10.1016/j.compstruc.2015.05.026.
- ⁴²⁴ [39] Li, X., Liu, Q., Zhang, J., 2010. A micro-macro homogenization approach for discrete particle assembly ⁴²⁵ cosserat continuum modeling of granular materials. International Journal of Solids and Structures 47, 291–303.
 ⁴²⁶ doi:10.1016/j.ijsolstr.2009.09.033.
- [40] Liebenstein, S., Zaiser, M., 2018. Determining cosserat constants of 2D cellular solids from beam models. Materials
 Theory 2, 1–20. doi:10.1186/s41313-017-0009-x.
- [41] Liu, S., Su, W., 2010. Topology optimization of couple-stress material structures. Structural and Multidisciplinary
 Optimization 40, 319–327. doi:10.1007/s00158-009-0367-3.
- [42] Lu, Y., Wang, Y., 2022. Structural optimization of metamaterials based on periodic surface modeling. Computer
 Methods in Applied Mechanics and Engineering 395, 115057. doi:10.1016/j.cma.2022.115057.
- [43] Mindlin, R.D., 1963. Microstructure in linear elasticity. Technical Report. Columbia Univ New York Dept of Civil
 Engineering and Engineering Mechanics. doi:10.1007/BF00248490.
- [44] Mousanezhad, D., Babaee, S., Ebrahimi, H., Ghosh, R., Hamouda, A.S., Bertoldi, K., Vaziri, A., 2015. Hierarchical
 honeycomb auxetic metamaterials. Scientific reports 5, 1–8. doi:10.1038/srep18306.
- ⁴³⁷ [45] Otomori, M., Yamada, T., Izui, K., Nishiwaki, S., 2015. Matlab code for a level set-based topology optimiza ⁴³⁸ tion method using a reaction diffusion equation. Structural and Multidisciplinary Optimization 51, 1159–1172.
 ⁴³⁹ doi:10.1007/s00158-014-1190-z.
- [46] Park, H.C., Lakes, R.S., 1986. Cosserat micromechanics of human bone: strain redistribution by a hydration sensitive
 constituent. Journal of biomechanics 19, 385–397. doi:10.1016/0021-9290(86)90015-1.
- [47] Peng, D., Merriman, B., Osher, S., Zhao, H., Kang, M., 1999. A pde-based fast local level set method. Journal of
 computational physics 155, 410–438. doi:10.1006/jcph.1999.6345.
- [48] Pradel, F., Sab, K., 1998. Cosserat modelling of elastic periodic lattice structures. Comptes Rendus de l'Académie
 des Sciences-Series IIB-Mechanics-Physics-Astronomy 326, 699-704. doi:10.1016/S1251-8069(98)80002-X.
- [49] Reis, F.D., Ganghoffer, J.F., 2012. Construction of micropolar continua from the asymptotic homogenization of beam
 lattices. Computers & Structures 112, 354–363. doi:10.1016/j.compstruc.2012.08.006.
- ⁴⁴⁸ [50] Ritchie, R.O., 2011. The conflicts between strength and toughness. Nature Materials 10, 817—-822. ⁴⁴⁹ doi:10.1038/nmat3115.
- [51] Rokoš, O., Ameen, M.M., Peerlings, R.H.J., Geers, M.G.D., 2019. Micromorphic computational homogenization for
 mechanical metamaterials with patterning fluctuation fields. Journal of the Mechanics and Physics of Solids 123,
 119–137. doi:10.1016/j.jmps.2018.08.019.
- [52] Rovati, M., Veber, D., 2007. Optimal topologies for micropolar solids. Structural and Multidisciplinary Optimization
 33, 47–59. doi:10.1007/s00158-006-0031-0.
- ⁴⁵⁵ [53] Rueger, Z., Lakes, R.S., 2016. Experimental cosserat elasticity in open-cell polymer foam. Philosophical Magazine
 ⁴⁵⁶ 96, 93–111. doi:10.1080/14786435.2015.1125541.
- ⁴⁵⁷ [54] Sab, K., Pradel, F., 2009. Homogenisation of periodic cosserat media. International journal of computer applications
 ⁴⁵⁸ in technology 34, 60. doi:10.1504/IJCAT.2009.022703.
- [55] Sanders, E.D., Aguiló, M.A., Paulino, G.H., 2018. Multi-material continuum topology optimization with arbi trary volume and mass constraints. Computer Methods in Applied Mechanics and Engineering 340, 798–823.
 doi:10.1016/j.cma.2018.01.032.

- ⁴⁶² [56] Sethian, J.A., 1996. Level set methods, evolving interfaces in geometry, fluid mechanics computer vision, and
 ⁴⁶³ materials sciences, isbn-13: 978-0521572026. Cambridge Monographs on Applied and Computational Mathematics,
 ⁴⁶⁴ 3.
- ⁴⁶⁵ [57] Sigmund, O., 1997. On the design of compliant mechanisms using topology optimization. Journal of Structural
 ⁴⁶⁶ Mechanics 25, 493–524. doi:10.1080/08905459708945415.
- ⁴⁶⁷ [58] Sigmund, O., 2001. A 99 line topology optimization code written in matlab. Structural and multidisciplinary
 ⁴⁶⁸ optimization 21, 120–127. doi:10.1007/s001580050176.
- ⁴⁶⁹ [59] Sokolowski, J., Zolesio, J.P., 1992. Introduction to shape optimization, in: Introduction to Shape Optimization.
 ⁴⁷⁰ Springer, pp. 5–12. doi:10.1007/978-3-642-58106-9.
- ⁴⁷¹ [60] Su, W., Liu, S., 2016. Topology design for maximization of fundamental frequency of couple-stress continuum.
 ⁴⁷² Structural and Multidisciplinary Optimization 53, 395–408. doi:10.1007/s00158-015-1316-y.
- ⁴⁷³ [61] Su, W., Liu, S., 2020. Size-dependent microstructure design for maximal fundamental frequencies of structures.
 ⁴⁷⁴ Structural and Multidisciplinary Optimization 62, 543–557. doi:10.1007/s00158-020-02510-w.
- ⁴⁷⁵ [62] Toupin, R., 1962. Elastic materials with couple-stresses. Archive for rational mechanics and analysis 11, 385–414. doi:10.1007/BF00253945.
- ⁴⁷⁷ [63] Tozoni, D., Dumas, J., Jlanh, Z., Panetta, J., Panozzo, D., Zorin, D., 2020. A low-parametric rhombic microstructure ⁴⁷⁸ family for irregular lattices. ACM Transactions on Graphics (TOG) 39(4), 101. doi:10.1145/3386569.3392451.
- ⁴⁷⁹ [64] Veber, D., Taliercio, A., 2012. Topology optimization of three-dimensional non-centrosymmetric micropolar bodies.
 ⁴⁸⁰ Structural and Multidisciplinary Optimization 45, 575–587. doi:10.1007/s00158-011-0707-y.
- ⁴⁸¹ [65] Wang, L., Cai, Y., Liu, D., 2018. Multiscale reliability-based topology optimization methodology for truss-like
 ⁴⁸² microstructures with unknown-but-bounded uncertainties. Computer Methods in Applied Mechanics and Engineering
 ⁴⁸³ 339, 358–388. doi:10.1016/j.cma.2018.05.003.
- [66] Watts, S., Arrighi, W., Kudo, J., Tortorelli, D.A., White, D.A., 2019. Simple, accurate surrogate models of the elastic
 response of three-dimensional open truss micro-architectures with applications to multiscale topology design. Struct
 Multidisc Optim 60, 1887–1920. doi:10.1007/s00158-019-02297-5.
- ⁴⁸⁷ [67] Yamada, T., Izui, K., Nishiwaki, S., Takezawa, A., 2010. A topology optimization method based on the level set
 ⁴⁸⁸ method incorporating a fictitious interface energy. Computer Methods in Applied Mechanics and Engineering 199,
 ⁴⁸⁹ 2876–2891. doi:10.1016/j.cma.2010.05.013.
- ⁴⁹⁰ [68] Yvonnet, J., Auffray, N., Monchiet, V., 2020. Computational second-order homogenization of materials with
 ⁴⁹¹ effective anisotropic strain-gradient behavior. International Journal of Solids and Structures 191-192, 434–448.
 ⁴⁹² doi:10.1016/j.ijsolstr.2020.01.006.
- [69] Zhang, H.W., Wang, H., Chen, B.S., Xie, Z.Q., 2008. Analysis of Cosserat materials with Voronoi cell finite element
 method and parametric variational principle. Computer methods in applied mechanics and engineering 197, 741–755.
 doi:10.1016/j.cma.2007.09.003.
- [70] Zhang, X.S., Paulino, G.H., Ramos Jr, A.S., 2018. Multimaterial topology optimization with multiple volume con straints: Combining the zpr update with a ground-structure algorithm to select a single material per overlapping set.
 International Journal for Numerical Methods in Engineering 114, 1053–1073. doi:10.1002/nme.5736.
- [71] Zheng, J., Luo, Z., Li, H., Jiang, C., 2018. Robust topology optimization for cellular composites with hybrid uncertainties. International Journal for Numerical Methods in Engineering 115, 695–713. doi:10.1002/nme.5821.
- [72] Zheng, L., Kumar, S., Kochmann, D., 2021. Data-driven topology optimization of spinodoid metamaterials
 with seamlessly tunable anisotropy. Computer Methods in Applied Mechanics and Engineering 383, 113894.
 doi:10.1016/j.cma.2021.113894.
- [73] Zheng, X., Smith, W., Jackson, J., Moran, B., Cui, H., Chen, D., Ye, J., Fang, N., Rodriguez, N., Weisgraber, T.,
 Spadaccini, C.M., 2016. Multiscale metallic metamaterials. Nature materials 15, 1100–1106. doi:10.1038/nmat4694.