

Numerical simulation of submarine landslides and generated tsunamis: application to the on-going Mayotte seismo-volcanic crisis

Pablo Poulain, Anne Le Friant, Rodrigo Pedreros, Anne Mangeney, Andrea Filippini, Gilles Grandjean, Anne Lemoine, Enrique Fernández-Nieto, Manuel Castro Díaz, Marc Peruzzetto

▶ To cite this version:

Pablo Poulain, Anne Le Friant, Rodrigo Pedreros, Anne Mangeney, Andrea Filippini, et al.. Numerical simulation of submarine landslides and generated tsunamis: application to the on-going Mayotte seismo-volcanic crisis. Comptes Rendus. Géoscience, 2022, 354 (S2), pp.1-30. 10.5802/crgeos.138 . hal-03839253

HAL Id: hal-03839253 https://hal.science/hal-03839253

Submitted on 4 Nov 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Numerical simulation of submarine landslides and generated tsunamis:

2 Application to the on-going Mayotte seismo-volcanic crisis

- 3
 4
 5 Poulain P.^{1,2}, Le Friant A.¹, Pedreros R.², Mangeney A.¹, Filippini A. G.², Grandjean G.², Lemoine
 6 A.², Fernandez-Nieto E.³, Castro Diaz, M⁴, Peruzzetto, M.².
 7
 8 ¹ Institut de Physique du Globe de Paris, Université Paris Cité
 9 ² BRGM
 10 ³ Departamento de Matematica Aplicada, Universidad de Sevilla
 11 ⁴ Departamento de Analisis Matematico, Universidad de Malaga
- 12
- 13

14 Corresponding Author

- 15 Poulain Pablo
- 16 Tel.: +33645524981
- 17 E-mail: poulain@ipgp.fr
- 18

19 Résumé (150 mots max)

- 20 Since May 2018, Mayotte Island has been experiencing seismo-volcanic activity that could trigger submarine
- 21 landslides and, in turn, tsunamis. To address these hazards, we use the HYSEA numerical model to simulate
- 22 granular flow dynamics and the Boussinesq FUNWAVE-TVD numerical model to simulate wave propagation
- and subsequent inundations. We investigate 8 landslide scenarios (volumes from 11.25×10^6 m³ to 800×10^6 m³).
- 24 The scenario posing the greatest threat involves destabilizations on the eastern side of Mayotte's lagoon at
- shallow depth and can generate sea-surface deformations of up to 2 m. We show that the barrier reef surrounding
- 26 Mayotte plays a prominent role in controlling water-wave propagation and in protecting the island. The tsunami
- travel time to the coast is very short (a few minutes) and the tsunami is not necessarily preceded by a sea
- 28 withdrawal. Our simulation results provide a key to establishing hazard maps and evacuation plans and
- 29 improving early-warning systems.
- 30

31 Key Words:

- 32 Mayotte, seismo-volcanic crisis, submarine landslide, debris-avalanches, tsunamis, numerical modeling,
- 33 coastal flooding hazard.
- 34

1. Introduction 35

36

37 The Comoros archipelago is composed of four volcanic islands (Grande Comore, Mohéli, Ajouan and 38 Mayotte) with volcanic activity recorded from the Miocene to the Holocene (Debeuf, 2004). Since May 2018, 39 the island of Mayotte has been undergoing intense seismic activity related to the birth of a large new submarine volcano 50 km offshore Petite Terre, with a volume estimated to be around 5 km³ (Feuillet et al., 2021). The 40 epicenters of the seismic swarms are located between 5 and 15 km east of Petite Terre for the proximal swarm 41 42 (Figure 1) and from 25 km to 50 km east of Petite Terre for the distal swarm (Lemoine et al., 2020a; Saurel et 43 al., 2022). Perturbations in the water column associated with plumes likely linked to magmatic activity were 44 reported in the new volcano area and in the vicinity of the seismic swarm closest to Petite Terre (Feuillet et al., 45 2021, Scalabrin et al., 2021). Although variations in the frequency of earthquakes and their distribution have been observed since the start of the eruption in early July 2018 (Cesca et al., 2020; Lemoine et al., 2020a; 46 Mercury et al., 2020; Saurel et al., 2022), continuous seismicity persists that could generate earthquakes of 47 48 magnitudes close to Mw4, or even greater, that would be widely felt by the population. Since May 10, 2018, 2054 earthquakes with magnitudes greater than 3.5 have been recorded, including 36 with recorded magnitudes 49 50 greater than 5 (REVOSIMA bulletin no.33, August 2021). This strong seismic activity is located near the island 51 of Mayotte and mainly east of Petite Terre where steep submarine slopes are observed (Figure 1). The intense 52 seismo-volcanic crisis that has affected Mayotte since 2018, the location of earthquakes near the steep slopes 53 surrounding the island and the construction of a new volcanic structure (Feuillet et al., 2021) may trigger 54 submarine instabilities offshore Mayotte (and in particular to the east). The triggering of tsunamigenic submarine landslides by intense seismic activity has already been documented, for instance in 2018 in Palu Bay (Sulawesi, 55 56 Indonesia) after a Mw 7.8 earthquake (Liu et al., 2020). However, recent studies show that low amplitude (M < 3) 57 but cumulative seismicity may also trigger landslides (Bontemps et al., 2020). Gravitational instabilities could 58 occur on steep submarine slopes offshore Mayotte but also on the new submarine volcano 50 km offshore Petite 59 Terre: such instabilities are not new on volcano edifices (e.g. Lebas et al., 2018; Le Friant et al., 2015; Le Friant 60 et al., 2019; Lipman et al., 1988; Moore et al., 1989; Paris et al., 2020; Sassa et al., 2016; Watt et al., 2014). For instance, the collapse of the Anak Krakatau volcano in Indonesia in 2018 (93 Mm³, Gouhier and Paris 2019) 61 62 triggered a tsunami that hit the coast of the Sunda Strait with waves of up to 80 m (Grilli et al., 2019; Paris et 63 al., 2020). Stromboli is also a tsunamigenic volcano that triggered five tsunamis from 1916 to 1954 (Maramai et al., 2005) and one in 2002 (Tinti et al., 2006). Another example is the Soufrière volcano on Montserrat Island 64 65 (Lesser Antilles), where a 200 Mm³ dome collapse generated a tsunami in 2003, with waves of up to 2 m 66 (Pelinovsky et al., 2004). Potential instabilities and resulting tsunamis of the submarine volcano Kick-'em-Jenny 67 (Grenada, Lesser Antilles) have also been studied by Dondin et al. (2016). 68

69 As discussed by Roger (2019), landslide-generated tsunamis could have a significant impact on 70 Mayotte's population and infrastructure. This impact can be quantified through hazard assessment. One of the 71 main difficulties for hazard assessment is to identify the most probable landslide scenarios. Lemoine et al. 72 (2020b) estimated the impact of 32 potential scenarios of submarine landslides on the slopes of Mayotte or on 73 the new volcano. They then identified the scenarios that would be the most impactful for Mayotte. As a first 74 attempt to assess tsunami hazards in Mayotte for national and local authorities in charge of risk mitigation, the 75 deformation of the sea surface generated by each of the potential submarine landslides was calculated with the TOPICS software (Tsunami Open and Progressive Initial Condition System; Watts et al., 2003), based on simple 76 77 empirical relations for the landslide description (Le Roy et al., 2015; Poisson and Pedreros., 2010 and Di Risio 78 et al., 2011 for a review of such empirical relations). These relations represented the landslide motion as a rigid 79 block moving along a constant slope. The displacement of the free surface of the water is modeled through 80 empirical relationships that relate the geometric and physical characteristics of the landslide to the initial 81 amplitude and wavelength of the generated tsunamis. However, beyond simple empirical relations or block 82 models (Gylfadóttir et al., 2017), more realistic models describing the landslide exist (see for example the large 83 number of models already used to simulate the 2018 Anak Krakatau landslide-generated tsunami listed in Grilli 84 et al. (2021)). They may be used for hazard assessment as done for example by Giachetti et al. (2012) and 85 Heinrich et al. (1998) who simulated tsunami waves generated by potential landslides on Anak Krakatau and 86 Montserrat, respectively. A few years after these studies, landslides on these two volcanoes actually occurred. 87 The generated tsunamis had characteristics (e.g. height and impacted areas) with orders of magnitude that were 88 similar to the characteristics of the previously simulated tsunamis. As a result, despite the high uncertainty in 89 such simulations (Lovholt et al., 2020) related to the potential scenario (location, volume, shape), the rheological 90 laws describing these complex natural materials, and the model approximations, such numerical codes provide 91 a unique tool to build hazard maps that are as physics based as possible. Full 3D models (e.g. Abadie et al., 2012; 92 Rauter et al., 2022 and references in Romano, 2020 and Grilli et al., 2021) or a combination of 3D and 2D models

93 (Grilli et al., 2019; Loyholt et al., 2008) have been developed. As such models have huge computational costs. 94 a significant number of shallow depth-averaged numerical models of tsunamis generated by landslides have also 95 been developed over the past decades and applied to natural events (e.g. Abadie et al., 2010; Giachetti et al. 96 2012; Gittings., 1992; Heinrich et al., 2001a; Heinrich et al., 2001b; Kelfoun et al., 2010; Mangeney et al., 2000; 97 Paris et al., 2019, 2020). For tsunami wave simulation, most of the models applied at the field scale solve shallow 98 (i.e. hydrostatic pressure) depth-averaged equations for a two-layer flow made of a layer of granular material 99 moving beneath a water layer (Fine et al., 2003; Fine et al., 2005; Fernández-Nieto et al., 2008; Giachetti et al., 100 2011; Jiang and LeBlond, 1992; Majd and Sanders, 2014; Yavari-Ramshe and Ataie-Ashtiani, 2015 and references within). For the water wave propagation part, more advanced depth-averaged models, based on 101 102 Boussinesq-type equations (non-hydrostatic pressure) that are weakly dispersive (e.g. Kirby et al., 2013; Popinet, 103 2015; Zhou et al., 2011) are available. In particular, these non-hydrostatic models are necessary at least to 104 accurately simulate tsunami wavelengths of about the same order of magnitude as the water depth (Gylfadóttir 105 et al., 2017; Kirbi et al., 2022 for a benchmark; Yavari-Ramshe and Ataie-Ashtiani, 2016). 106

107 Submarine landslides are known to generate waves with wavelengths of around a few kilometers 108 (Papadopoulos and Kortekaas 2003). In the seismo-volcanic context of Mayotte, the potential areas of 109 instabilities are close to the island (as shown by the presence of confirmed past submarine instabilities on the 110 slope and foot of the island (Thinon et al., 2021)). In these conditions, the water wave wavelengths could be 111 about the same order of magnitude as the water depth (wavelengths from 1000 m to 5000 m (Lemoine et al., 112 2020b). Consequently, to investigate the impact of tsunamis generated by submarine landslides, we need to use 113 models that take into account the landslide dynamics but that also solve Boussinesq-type equations for the 114 tsunami propagation. These models do not yet include an accurate description of the source (for instance 115 accounting for correct topography effects (Delgado-Sánchez et al., 2020; Ma et al., 2015)) together with a precise 116 simulation of the wave propagation. For instance, in his analysis of landslide-generated tsunamis in Mayotte 117 with the GEOWAVE software, Roger (2019) first simulated the submarine landslide and then used the 118 corresponding deformation as a source term for the tsunami simulation with the FUNWAVE model (Shi et al., 119 2012). This strategy presents two drawbacks: (i) the landslide and the wave generation are not simulated in a 120 single simulation and (ii) the shallow-water assumption inherent to FUNWAVE is not valid at the beginning of 121 the simulation. To overcome this issue, we propose here a framework for coupling two near-field and far-field 122 numerical models as done for example by Grilli et al. (2019), each model being efficient to describe a specific 123 part of the physical processes involved. We thus combine the HYSEA model (Macías et al., 2017), used to 124 describe the submarine avalanche and initiate the waves, with the widely used Boussinesq FUNWAVE- TVD 125 model (Abadie et al., 2020; Grilli et al., 2019; Le Roy S., 2017; Rohmer et al., 2017; Shi et al., 2012), used to propagate the wave and compute the flooding on the Mayotte coast. To implement this approach, we: i/ analyze 126 127 morphological data offshore Mayotte to define scenarios of potential submarine landslides by reconstructing 128 precise topography, ii/process numerical simulation of the submarine landslide including a detailed description 129 of the sources and of the granular flow, iii/ simulate the wave generated by the landslide, its propagation, and 130 the coast inundation and discuss the pertinence of the combination of models.

131

133

142

132 **2. Submarine landslide scenarios**

134 The two islands of Mayotte (Petite Terre and Grande Terre) are surrounded by a well-developed shallow 135 submarine shelf (defining the lagoon) extending offshore from 0.5 km east of Petite Terre to 17 km at certain 136 locations around Grande Terre (Figure 1). The shelf-to-slope transition occurs at depths of 30 to 100 m. It 137 corresponds to a significant topography slope break, from shallow slopes on the shelf (<9°) to flanks with 138 maximum slopes of 25° to 60° locally. The slopes then decline away from the shelf-break, towards the more 139 subdued topography of the surrounding area. In deeper water, many gullies and canyons (up to 150 meters depth) 140 form tributaries of large valleys. These canyons and discontinuities are present all around the island and may 141 control the circulation of sediments.

143 In their exploratory study, Lemoine et al. (2020b) considered 62 scenarios around Mayotte that could 144 generate tsunamis (32 instability scenarios located in Figure A.1, 19 earthquake scenarios and 11 caldera collapse 145 scenarios) and a sensitivity study was carried out on the density of collapsed material and tides. They concluded 146 that the most impactful scenarios were associated with gravitational instabilities located on the slopes close to 147 the reef and at the foot of the slope to the east of Petite Terre (see Figure A1). Repeated earthquakes located 148 between 5 and 15 km from the coast east of Petite Terre could weaken the sedimentary pile and trigger 149 tsunamigenic gravitational instabilities. The results of Lemoine et al. (2020b), combined with the location of the 150 seismo-volcanic crisis, led us to focus our attention on the eastern coast of Mayotte. We performed a

morphological analysis of the submarine slopes east of Mayotte using new bathymetric data collected in 2019 151 (MAYOBS 1 cruise in 2019, Feuillet et al., 2021) but we also considered scenarios on the western part of 152 Mayotte that were considered by Lemoine et al. (2020b). The extent, the depth, and the geometry of collapse 153 154 structures were constrained by a geomorphological analysis of bathymetric surveys. The collapse structure was 155 then constructed by digging into the present submarine slope within the defined extent. Sensitivity tests on the 156 volumes and associated geometries of the collapsing mass are presented in section 6.1, showing that they strongly influence wave generation. We thus consider 8 scenarios with different volumes and depths for 157 158 numerical simulations to get an idea of the magnitude of the potential generated tsunami. The list of scenarios 159 is not exhaustive and other scenarios could be considered in the future. We summarize the characteristics of the 160 collapse scenarios in Table 1 (with reference to the scenarios used in Lemoine et al., 2020b) and in Figures 1 161 and 2.

- The volumes of the landslide scenarios vary from 11.25×10^6 m³ to 800×10^6 m³. Six scenarios involve 163 at shallow depths: Piton 100, Piton 200, North Slope and South Slope to the east of Petite Terre and West Slope 164 and West Canyon to the west of Grande Terre. Two scenarios are also considered at greater depths: the 3 Lobes 165 scenario involves the morphological lobes close to the seismic swarm at middle depth and the New Volcano 166 scenario involves the new submarine volcano at 3300 m depth. The Piton 200 scenario is located at the shelf to 167 168 slope transition close to Petite Terre (2.5 km) at depths between 50 and 600 m below sea level. It probably involves a volcanic morphology (one volcano or a complex of volcanic cones) and a volume of 200×10⁶ m³ 169 170 (Figures 2a). The Piton 100 scenario is similar to that of Piton 200 but with a shallower profile and a volume of 100×10⁶ m³. The 3 Lobes scenario is constrained by morphological discontinuities and gullies east of Petite Terre 171 at depths between 850 and 1350 m below sea level and involves a volume of $800 \times 10^6 \text{ m}^3$ (Figure 2b). The South 172 173 Slope (Figure 2c) and North Slope (Figure 2d) scenarios are located on the steep slopes at the shelf break at depths between 400 and 1000 m and 50 and 250 m respectively and involve volumes of 290×10⁶ m³ and 174 11.25×10^6 m³. The West Slope (Figure 2e) and West Canyon (Figure 2f) are both located to the west of Grande 175 Terre at depths between 30 m and 300 m and involve volumes of 19×10^6 m³ and 69×10^6 m³. The New Volcano 176 scenario involves the western part of the volcano (that will flow towards the west). It is located at depths between 177 2600 and 3150 m and involves a volume of 260×10^6 m³ (Figure 2g). 178
- 179

162

180 **3. Numerical models and coupling**

181

185 186

Let us briefly describe the two numerical models, HySEA and FUNWAVE-TVD, that will be used to simulate
 landslide dynamics and wave generation, and wave propagation, respectively, as well as the strategy adopted to
 couple these models.

3.1 HYSEA

187 The two-layer hydrostatic HySEA code is a 2D extension of the model proposed by Fernandez-Nieto 188 et al. (2008), but using Cartesian coordinates. It describes submarine avalanches and the water motion on top of 189 them. As in most landslide-generated tsunami models, the fluid and the granular mass are assumed to be 190 incompressible and homogeneous. This means that the landslide is considered as an effective media described 191 by an empirical rheological law, as discussed below. Therefore, the natural complexity of the phenomena is not 192 fully taken into account. For instance, we do not take into account material heterogeneity, segregation and 193 fragmentation processes, bed erosion and incorporation of air and/or water, or density variations that can be 194 caused by the expansion or contraction of the material and their impact on pore fluid pressure (see Delannay et 195 al. 2017 for a review of processes). HySEA was developed by the EDANYA group (Asunción-Hernández et al., 196 2012; Asuncion et al., 2013; Castro Diaz et al., 2005; Castro Diaz et al., 2006; Castro Diaz et al., 2008a; Castro 197 Diaz et al., 2008b; Macias et al., 2015) and has been successfully used to simulate tsunamis generated by 198 landslides (Kirby et al., 2022 (for a benchmarking exercise); Macias et al., 2021; Esposti Ongaro et al., 2021). 199 From the depth-averaged equations, six unknowns are solved by the model, (h_1, u_{1x}, u_{1y}) and (h_2, u_{2x}, u_{2y}) , representing the vertical height and horizontal velocity of the fluid (index 1) and granular layer (index 2), 200 201 respectively, averaged in the vertical direction. The HySEA code is based on an efficient hybrid finite-volume-202 finite-difference numerical scheme on GPU architectures (Macias et al., 2020). The equations are solved 203 numerically using a relaxation method, as described in Escalante et al. (2019).

The appropriate rheology for subaerial and submarine landslides is still an open issue. Indeed, the high mobility of these gravitational flows (Lucas et al., 2014) and their complex deposit shape (Kelfoun et al., 2008) have only been reproduced by empirical laws with no clear physical origin. The empirical laws used in submarine 207 landslide simulations include the simple Coulomb friction law (Brunet et al., 2017), the Voellmy rheology 208 (Salmanidou et al., 2018), a retarding stress (Giachetti et al., 2012), the viscous law (Grilli et al., 2021), the 209 friction-weakening law (Lucas et al., 2014), and the $\mu(I)$ rheology (Brunet et al., 2017), the latter being derived from lab-scale experiments on granular flows. The $\mu(I)$ rheology, resulting in the Pouliquen and Forterre (2002) 210 211 flow law in depth-averaged models, includes the dependence of the friction coefficient on the velocity and 212 thickness of the flow. Note that the thickness dependency behavior is gualitatively similar to that of the retarding 213 stress. Following Brunet et al. (2017), we use this law here with empirical parameters. Indeed, as in most 214 landslide simulations, the parameters of the laws have no physical meaning but result from empirical fits 215 obtained to reproduce past events. The frictional rheology and in particular $\mu(I)$ made it possible to reproduce 216 the main characteristics of landslide dynamics and deposits (Brunet et al., 2017; Le Friant et al., 2003; Lucas et 217 al., 2014; Moretti et al., 2015).

218 In depth-averaged models with frictional rheologies, the empirical friction coefficient $\mu = \tan(\delta)$, with δ 219 the constant or flow-dependent friction angle, can be seen as a representation of the mean dissipation during the 220 flow (Mangeney et al., 2007a; Pouliquen et al., 1999; Pouliquen and Forterre, 2002). Pouliquen and Forterre 221 (2002) developed a friction law for the whole range of possible thicknesses and Froude numbers (Fr) even 222 though the experimental data only concerned steady and uniform flows. Depending on the value of the Froude 223 number, the flow is assumed to be in a dynamic, intermediate or static regime and the friction coefficient can be 224 written in each regime as a function of four parameters: L, which is a characteristic length of the grain diameter, 225 and $\mu_1 = \tan(\delta_1), \mu_2 = \tan(\delta_2)$ and $\mu_3 = \tan(\delta_3)$, which are the tangents of the critical angles, δ_1, δ_2 and δ_3 . 226 The angle δ_3 corresponds to the asymptote of the curve $\theta_{start}(h)$, representing the slope angle at which a layer 227 of thickness h is mobilized. Two other empirical parameters β and γ appear in the rheological law describing (i) 228 the critical Froude number above which the flow is assumed to be in the dynamic regime $(Fr>\beta)$ and (ii) the 229 transition between the static and dynamic regime (γ) , respectively. Several studies have shown that this law well 230 reproduces laboratory experiments on granular flows such as erosion/deposition waves (Edwards and Gray., 231 2014; Edwards et al., 2017; Edwards et al., 2019; Mangeney et al., 2007b; Russell et al., 2019) or self-channeling 232 flows and levee formation (Maneney et al., 2007a; Rocha et al., 2019). It has also made it possible to produce 233 conclusive results for submarine landslides in the Antilles (Brunet et al., 2017; Le Friant et al., 2003). More 234 precisely, a detailed comparison of the simulated and observed deposit of a submarine avalanche showed that 235 the simulation with the $\mu(I)$ rheology better reproduces observations than the simple Coulomb friction law (Brunet et al., 2017). Following these studies and in order to only have one free empirical parameter (μ_1), we 236 assume that $\delta_2 - \delta_1 = 10^\circ$ and $\delta_3 - \delta_1 = 2^\circ$ are constants, their values corresponding to those measured at the 237 lab-scale, and we fix L=1 m. We also fix the parameters $\beta=0.136$ and $\gamma=10^{-3}$ as in Pouliquen and Forterre (2002) 238 and Mangeney et al. (2007a). Note that the value of γ has been shown to poorly affect the results in these studies. 239 Finally, the value of μ_1 is first based on the volume-dependent friction law of Lucas et al. (2014), $\mu_1 = \tan(\delta_1) =$ 240 $V^{-0.0774}$, empirically defined to fit the deposit of a series of almost dry landslides of different volumes V. We 241 242 then subtract approximately 6° from δ_1 as was done empirically in Peruzzetto et al. (2019) and Moretti et al. 243 (2015) to roughly account for water effect. Table 1 summarizes the angles used for each scenario. The effect of the friction between the landslide layer and the water layer $m_{\rm f}$ is small in our case as discussed in section 6.1 244 245 (Macias et al., 2021).

In our simulations, as in most landslide simulations in the literature (Yavari-Ramshe and AtaieAshtiani., 2016), the initial mass is instantaneously released from rest at the initial instant, without considering
the transition phase from a coherent mass to a granular flow.

3.2 FUNWAVE-TVD

249 250

251

252 The FUNWAVE-TVD code, widely used in the literature (e.g. Grilli et al., 2019), employs an enhanced 253 version of the fully non-linear Boussinesq equations derived by Wei et al. (1995). Chen (2006) improved the 254 original equations of Wei et al. (1995) in order to include the vertical vorticity, which is well suited to describe 255 wave-induced currents (Chen et al., 2003). They also incorporated the adaptive vertical reference level of 256 Kennedy et al. (2001) to improve the non-linear representation of the model. The FUNWAVE-TVD code solves 257 either fully non-linear equations in a Cartesian framework (Shi et al., 2012) or a weakly non-linear spherical coordinate formulation with Coriolis effects (Kirby et al., 2013) to take into account Earth curvature. It uses a 258 259 TVD shock-capturing algorithm with a hybrid finite-volume and finite-difference scheme. Following the 260 approach of Tonelli and Petti (2009), wave breaking is detected when the ratio between wave height and water 261 depth exceeds 0.8. The subsequent coastal inundation is simulated by cancelling off dispersive terms, hence solving the non-linear shallow-water equations. The third order strong stability preserving (SSP) Runge-Kutta 262 263 scheme is adopted for time stepping.

The code is fully parallelized using the Message Passing Interface (MPI) protocol and efficient algorithms, ensuring a substantial acceleration of the computations with the number of cores. For operational uses, FUNWAVE-TVD has received many convenient features, such as the use of nested grids to refine the simulations in the interest areas or the use of heterogeneous Manning coefficients to characterize bottom friction.

268 269 270

281

3.3 Coupling between Hysea and Funwave-TVD

271 Coupling two numerical codes is a complex task because they are generally developed using different 272 numerical schemes, computing libraries and language versioning. This is the case with Hysea and Funwave-273 TVD. To prevent any intrusive coupling option that could produce errors and numerical instabilities, we choose 274 to run each of them sequentially, so that after simulating the initiation of the landslide and the associated waves 275 with HYSEA, and at a time t_c (coupling time), HYSEA results are passed on as initial conditions for FUNWAVE-TVD. This choice ensures that all parameters (wave velocities and free-surface elevation) are 276 correctly transmitted from one numerical environment to the other. In order to explain our choice of $t_{c_{2}}$ we 277 represent, for the Piton 200 scenario, the free-surface elevation computed by HYSEA along the main propagation 278 279 line, from 0 to 90s, roughly the time when the waves have vanished (Figure 3). We can identify in Figure 3 280 various times:

- early times when the first wave is emerging and is not yet formed;
- 282 the time t_{c1} when the landslide has moved enough to generate a completely shaped wave at the sea 283 surface located directly above. At this time, around 22s, the wave amplitude has completely returned 284 to zero (orange color) after negative (blue color) then positive (yellow colors) values;
- 285 the time t_{c2} , around 35s, when the wave has reached a maximum of amplitude (dark blue color) at the 286 free surface in the surroundings of the source area. At t_{c2} , the initial first wave has grown and it can be 287 considered to be completely formed because of the level of energy transmitted by the granular flow; 288 - Later times where secondary waves are propagating.

To define t_c for each scenario, we consider i) situations where the sliding mass has transmitted a sufficient level of energy to the free surface to generate a complete wave and ii) minimal errors introduced by the HySEA hydrostatic approximation when simulating wave propagation. In order to be sure to form a maximal amplitude wave (and so being conservative enough in terms of final impacts) while minimizing non-hydrostatic effects during propagation, we decided to fix t_c at the value of t_{c2} . Table 1 summarizes the coupling times chosen for each scenario.

296 **4. Model setup**

297

295

The numerical simulations of landslide and sea-surface deformation were carried out under the following conditions:

- wave propagation was simulated in mean high water springs (+ 1.92 m at Dzaoudzi to the Mayotte vertical datum IGN1950 following the RAM 2017), which, in most cases, reduces the protective effect of the reef (Thran et al., 2021), compared to the other reference tide levels (e.g. mean high water neaps or mean tide level with values of 1.02 and 0.35 m/IGN1950 respectively),
- a global island subsidence of 0.15 m linked to the deflation phenomenon that has been observed since
 summer 2018 (Cesca et al., 2020; Lemoine et al., 2020a; Feuillet et al., 2021), without taking into
 account the west-east differential visible in GNS measurements,
- 307 two DTM (Digital Terrain Model) with spatial resolutions of 50 m and 10 m were used. They are the 308 same as those in Lemoine et al. 2020b. They are based on: Gebco 2014 (https://www.gebco.net), 309 HOMONIM SHOM DTM (100 m resolution, https://data.shom.fr), MAYOBS 1 (Feuillet et al., 2021, 310 30 m resolution), bathymetric surveys of SHOM (25 m resolution, https://data.shom.fr), and litto3D 311 (lidar data at 1 m resolution, https://data.shom.fr). The 50 m DTM is used for the landslide and wave 312 propagation simulation, and the 10 m DTM for the inundation. The mesh resolution remains constant 313 throughout the domain. It is either 50 m when performing the large-scale simulation for the propagation 314 of the waves and 10 m when performing the inundation simulation. The extent of the 10 m mesh grid 315 is however smaller than that of the 50 m mesh grid to limit simulation time and focus on specific areas.
- in FUNWAVE-TVD, one-way nested grids are used to simulate inundation together with wave propagation. The 10 m DTM receives as boundary conditions the free-surface elevation and flow velocities from the simulation on the 50 m DTM. Absorbing layers are used as boundary conditions for the wave propagation simulation on the 50 m DTM.
- in FUNWAVE-TVD, the spatial changes in the bottom friction (related to land use) are taken into account by the model using Manning's roughness coefficients, *n* (see details in Lemoine et al., 2020b).
 Typical values of *n* are determined from the literature (see e.g. Bunya et al., 2010) and vary for example

between $0.02 \text{ s/m}^{1/3}$ for the deep ocean and $0.14 \text{ s/m}^{1/3}$ for the mangrove forest. Note that *n* is constant in HySEA (see sensitivity test in Figure of section 6.1).

325 in FUNWAVE-TVD: the wave breaking approach of Tonelli and Petti (2009) is activated and the simulations at 10 m resolution are conducted with a one-way nested grids (DTM at 10 m receives as 326 327 boundary conditions the free-surface elevation and flow velocities from the simulation at 50 m 328 resolution). For the boundary conditions of the model at 50 m resolution, we consider absorbing layers. 329 For the eight scenarios, the landslides and the tsunamis (generation, propagation and inundation phases) 330 were first simulated with a 50 m mesh grid surrounding the whole island of dimensions 151.2 km by 110.4 km (part of it is represented in Figure 4). The results are presented with maps of the extension of landslide deposits 331 332 (Figure 2h-n) and maps of maximum sea-surface elevation due to the tsunami including Grande Terre and Petite 333 Terre (Figure 4 a-h). In this paper, the term sea-surface elevation refers to the deformation in sea level caused 334 by the generated tsunami and not an absolute elevation value. For the most impactful tsunamis, the one-way 335 nested grid approach was used for a realistic simulation of the flooding (10 m resolution) in terms of extension, 336 water depth (sea-surface elevation - bottom elevation) and currents. For these simulations, we focus on strategic 337 areas provided by the local authorities: a) Dzaouzi, b) Airport, c) North-east Petite Terre, d) Mamoudzou, e) 338 Vicinity of Koungou (Figure 1).

The simulations performed with FUNWAVE-TVD were run on a cluster composed of 4 to 8 nodes, each with 24 CPU processing cores. Simulations on the 50 m DEM take between 15 and 36 hours. Simulations on the 10 m DEM last between 28 and 50 hours.

343 **5. Results**

344345346

342

5.1 Landslide simulation at low resolution (50 m)

347 We first simulate the submarine landslides and tsunamis with HYSEA. For the Piton 200 scenario, the 348 velocity of the front of the avalanche varies from 53 m/s at 40 seconds to 25 m/s at 150 seconds. Considering 349 the steep slope and the volume of the slide, these velocities values seem to be around what can be found in the 350 literature, even if 53 m/s is at the upper limit for submarine slides. Indeed, the velocity for the landslide of the 351 1741 Oshima-Oshima tsunami was estimated to be around 100 m/s (Satake., 2001), which is similar to the velocities of the subaerial flank collapse of Mount St Helens (70 m/s Voight et al., 1983). Other studies show 352 353 lower slide velocity values such as Ward and Day (2003) who estimated an average velocity of 40 m/s for Ritter 354 Island (supposedly, the front is faster). In our simulation, the landslide stops at 260 s, extending over an area of 28 km² with a maximum thickness of 52 m (Figure 2h). We simulated the landslide deposits for all 8 scenarios 355 (Figure 2h-n). The deposit extension varies from 12 km² to 36 km² and the maximum deposit thicknesses vary 356 357 from 30 m to 90 m. The runout distance (distance between scar highest point and deposit front) varies from 2.3 358 km to 9.2 km. As expected, higher friction angles induce smaller runouts and deposit areas (see section 6.1). The 359 topography strongly controls the dynamics and emplacement of the landslide (Figure 2h-n) as found for instance 360 by Peruzzetto et al. (2019, 2021) and Fischer et al. (2012).

361 362 363

5.2 Tsunami propagation simulations at low resolution (50 m)

The sea-surface elevation at low resolution (50 m) for the 8 landslide scenarios (Figure 4) is simulated with FUNWAVE-TVD:

372 - Piton 100 ($V = 100 \times 10^6 \text{ m}^3$): The Piton 100 scenario is located at the same place as the Piton 200 373 scenario but only half of the volume is involved. Figure 4b shows sea-surface elevations at the coasts of 374 maximum 10 m northeast of Petite Terre (uninhabited area) and 1.2 m northeast of Grande Terre (inhabited 375 area). Off the airport, the maximum sea surface recorded is 2.3 m while it is 1.2 m northeast of Grande Terre 376 and 0.4 m at the N4 road. Note that reducing the volume of the landslide by two does not decrease the sea-377 surface elevation by the same factor (Figure 4b). Off the coast of Grande Terre, where the sea-surface elevation 378 was between 1 m and 3 m in the Piton 200 scenario, the maximum difference between the 100 and 200 scenarios 379 is about 0.5 m. In the area close to the source of the landslide (northeast of Petite Terre) these differences are

- greater than 1 m or even 3 m locally where sea-surface elevations calculated for Piton 200 were between 5 mand 10 m.
- $\begin{array}{ll} 382 & -3 \ Lobes \ (V=800 \times 10^6 \ m^3): \ \text{This scenario mobilizes the largest volume and is located at a greater depth.} \\ 383 & \text{This scenario therefore has less impact than other scenarios on the Mayotte coasts (Figure 4c). Only the eastern coast of Petite Terre appears to be impacted with water elevations up to almost 2 m reached in the uninhabited areas northeast of Petite Terre. For Grande Terre, the elevations at the coasts are about 1 m (near Majicavo Koropa) and 1.3 m locally near Mamoudzou (Figure 4c). \end{array}$
- $New Volcano (V=260 \times 10^6 m^3):$ This scenario investigates a landslide on the flank of the new volcano located 50 km east of Mayotte at more than 3000 m below sea level (Figure 4d). Although the volume is high (260×10⁶ m³), the sea-surface elevation off the coasts of Mayotte is low. We observe that the maximum seasurface elevation reaches 0.7 m very locally on the east coast of Petite Terre. Offshore Mamoudzou, the maximum elevation of the sea surface is 1 m locally but most of the values are less than 0.2 m (around 0.15 m). The maximum sea-surface elevations calculated offshore Dzaoudzi and the airport are 0.8 m and 0.5 m respectively (Figure 4d).
- 394 North Slope $(V=11,25\times10^6 \text{ m}^3)$: This landslide scenario is located at a shallow depth and close to the 395 reef, however it has little impact on the coasts of Mayotte with sea-surface elevations about 0.2 m offshore 396 Koungou and Dzaoudzi, with local maximums at 0.7 m and 0.9 m respectively (Figure 4e).
- $\begin{array}{ll} 397 & South \ Slope \ (V=290\times10^6 \ m^3): \ This \ scenario \ investigates \ a \ landslide \ located \ south \ of \ Petite \ Terre. \ It \ has \ a \ strong \ impact \ on \ the \ east \ southeast \ coasts \ of \ Grande \ Terre \ and \ mainly \ on \ the \ east \ coast \ of \ Petite \ Terre. \ It \ has \ a \ strong \ impact \ on \ the \ east \ southeast \ coasts \ of \ Grande \ Terre \ and \ mainly \ on \ the \ east \ coast \ of \ Petite \ Terre. \ It \ has \ a \ strong \ impact \ on \ the \ east \ southeast \ coasts \ of \ Grande \ Terre \ and \ mainly \ on \ the \ east \ coast \ of \ Petite \ Terre. \ It \ has \ a \ strong \ impact \ of \ the \ east \ coast \ of \ Petite \ Terre. \ It \ southeast \ coast \ of \ Petite \ Terre. \ It \ a \ southeast \ coast \ of \ Petite \ Terre. \ It \ a \ southeast \ of \ Petite \ Terre. \ It \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ of \ Petite \ Terre. \ a \ southeast \ a \ southea$
- 402 West Canyon ($V=69 \times 10^6 \text{ m}^3$): This scenario is located offshore the western coast of Grande Terre. It 403 has a fairly limited impact off the west coast of Mayotte and has little or no impact off the east coast. The 404 maximum sea-surface elevation reaches up to 4 m locally (Figure 4g). In the Sada and Sohoa region, the 405 maximum sea-surface elevation reaches 2.4 and 2.8 m respectively. Offshore the Chembényoumba and the 406 Acoua area, the maximum sea-surface elevations are 2.2 m and 2.1 m respectively.
- 407 West Slope $(V=19\times10^6 m^3)$: This scenario located offshore the west coast of Grande Terre has a limited 408 impact off the west coast of Grande Terre and no impact off the east coast. The maximum sea-surface elevations 409 reach up to 3 m locally (Figure 4h). Offshore the Sada and Sohoa region, the maximum sea-surface elevation 410 reaches 1.2 and 2 m respectively. Offshore Chembényoumba and Acoua, the maximum sea-surface elevations 411 are 1.3 m and 2 m respectively.

Table 2 summarizes the tsunami travel time at different strategic zones defined in Figure 1 for all the scenarios. We describe here the time series of the sea-surface elevation for three of the most impactful cases identified on the low-resolution simulations (50 m), Piton 200 (Figure 5), South Slope and West Canyon (Figures A.2, A.3). Digital gauges have been chosen close to specific strategic sites in order to capture the evolution of the free-surface (see locations on insert in Figure 1).

- 418 *Piton 200* $(V=200 \times 10^6 \text{ m}^3)$: 1 minute after the start of the simulation, the first waves reach the east coast 419 of Petite Terre (Figure 5a-d). The airport area is reached by waves in 3'55". At 6', the first waves propagate in 420 the lagoon towards the northeast of Grande Terre and Dzaoudzi. The waves reach the coasts of Grande Terre at 421 8'25" for the south of the east coast and 10' 35'' for the northeast coast. Mamoudzou is only hit by the waves at 422 11'15". At 20', the waves have not yet reached the west coast of Grande Terre; they are just starting to propagate 423 in this part of the lagoon. Note that the tsunami is not necessarily preceded by a withdrawal of the sea and that 424 the first wave does not always have the highest elevation as seen on the pink plot (Figure 5d).
- 425 South Slope $(V=290 \times 10^6 \text{ m}^3)$: 2' after the start of the wave propagation, the first waves reach the east 426 coast of Petite Terre (Figure A-2a-d). The airport area is reached by waves in 5'30", but the interior of the lagoon 427 remains protected. Still at 5'30", the first waves propagate in the lagoon towards the southeast of Grande Terre 428 and Dzaoudzi. The waves reach Dzaoudzi at 11'20", then continue to propagate in the lagoon and reach 429 Mamoudzou in 13'50". 15' after the beginning of the propagation of the waves, the northeast coast of Grande 430 Terre is reached by the waves.
- 431 West Canyon ($V=69 \times 10^6 \text{ m}^3$): 7'10" after the start of the landslide, the first waves reach the west coast 432 of Grande Terre starting with the Acoua region, then the Chembeyoumba area at 9' (Figures A-3a-d). The waves 433 then propagate in the Lagoon towards the southwest of Grande Terre. The Sada region is reached by the waves 434 at 10'50" before the waves propagate in Bouéni bay and reach Chirongui at 20'10". Finally, the southwest coast 435 of Mayotte is reached at 20'40" with the Kani-Kéli region.
- 436 437

5.3 Coastal flooding simulations and hazard mapping at high resolution (10 m)

To get precise results near the coast of Mayotte, high resolution simulations (10 m) were performed at the local scale for the Piton 200 and South Slope scenarios as they are the most impactful (Figure 4) in the area of the current seismo-volcanic activity. We described here the results for Piton 200 ($V=200 \times 10^6 \text{ m}^3$) which is the most impactful scenario. The results were post-processed to obtain the maximum water depth (Figure 6) and maximum flow velocities (Figure 7). Results for the South Slope scenario are shown in Figures A-4 and A-5.

Figure 6a shows that the N4 road leading from Labatoir to Dzaoudzi is partially submerged with water depth varying from 10 cm to 1.5 m. The airport area is also subject to partial flooding with water depths of up to 35 cm on the runway and 1.50 m near the runway (Figure 6b). At Mamoudzou, maximum water depths of 1.50 m are reached (Figure 6c) north of the large Mamoudzou market. In the Koungou region, maximum water depths of 2.60 m are reached on the first buildings (such as in Majicavo Koropa, Figure 6d) and up to 1.90 m at a distance of 50 m from the shore. In the northern part of Petite Terre (Figure 6e), water depths of 6 m are reached in an uninhabited area and 8 m near Moya beach.

Figure 7 shows that the maximum velocities are reached on the eastern side of Petite Terre and can exceed 3 m/s close to the airport (Figure 7b) and Moya beach (Figure 7d). These values are lower in the lagoon, where the depth is greater, and do not exceed 0.75 m/s (e.g. 7a). Finally, significant velocities of 1 to 3 m/s can be observed again near the coastline and on land in some bays such as Mamoutzou (Figure 7c) and Koungou (Figure 7d) as well as on the west coast of Petite Terre (Figures 7a and 7b).

456

438

457 6. Summary and discussion

458 459

460

6.1 Sensitivity analysis

461 As discussed above, significant uncertainties are associated with these landslide and tsunami 462 simulations (Lovholt et al., 2020). We test here the effect of the main assumptions and parameters involved in 463 the models: the landslide volume, the friction law and parameters involved, the Manning coefficient, and the 464 hydrostatic approximation. When the friction coefficient μ_1 of the friction law increases to reach typical values used for dry avalanches of similar volumes ($\delta_1 = 13^\circ$, $\delta_2 = 23^\circ$ and $\delta_3 = 15^\circ$) compared to our so-called 465 reference case (Pouliquen friction law, $\delta_1 = 7^\circ$, $\delta_2 = 17^\circ$ and $\delta_3 = 9^\circ$, L = 1 m, $n = 0.025 m^{-1/3}$, $m_f = 0.$ 466 467 0, Hydrostatic version of HySEA), the landslide runout is much smaller (Figure 10a) and the maximum generated waves are about two meters smaller at gauge 2 (Figure 10c). Decreasing the typical diameter of the 468 granular material involved (L=0.1 m instead L=1 m) in the $\mu(I)$ rheology does not change the maximum 469 470 amplitude but slightly changes the wave shape after the first wave arrival. When L=0.1 m, the simulated water 471 wave becomes closer to the simulation using the Coulomb friction law with $\delta = 7^{\circ}$. Indeed, in the $\mu(I)$ rheology, 472 when L gets smaller, μ tends to μ_1 . The difference between the landslide deposits simulated with the $\mu(I)$ 473 rheology and the Coulomb friction laws is however significant (Figure 10a). The friction between the landslide 474 layer and the water layer m_f and the Manning coefficient n poorly affect the generated wave for typical values of m_t between 0 and 10⁻⁴ m⁻¹ and Manning *n* between 0 and 0.05 (e.g. Macias et al., 2021; Gonzalez-Vida et al., 475 476 2019) (Figure 10b,c), at least during the first tens of seconds before the coupling time t_c . The strongest effect is 477 related to the hydrostatic assumption. Indeed, in the particular case of Mayotte, the non-hydrostatic simulations 478 give very different results with a more rounded and longer-period wave with a maximum amplitude of the same 479 order of magnitude (a few meters), but more than two times smaller than the hydrostatic simulation at gauge 2. 480 The picked waves obtained with the hydrostatic assumption are typical of such approximation (see e.g. Figure 481 3b of Giachetti et al. (2012) or Figures 9 and 10 of Gylfadóttir et al. (2017)). Finally, the maximum wave 482 amplitude increases as the landslide volume increases (Figure A.6) and the waveform changes.

483 484

485

6.2 Numerical models and coupling approach

486 We used here the depth-averaged hydrostatic version of HYSEA (i.e. with one layer for the avalanche 487 and another layer for the water column, as opposed to the multilayer HySEA model where the water column is 488 divided into several layers) The depth-averaged hydrostatic version of HYSEA has been already applied to real 489 landslides and tsunamis (Macias et al., 2017; Macias et al., 2020). The accuracy of hazard maps related to 490 landslide-generated tsunamis would be significantly improved by more advanced models accounting for non-491 hydrostatic effects in the landslide (Garres-Diaz et al., 2021) and water wave propagation, different coordinate 492 systems for the landslide and avalanche (Delagdo-Sanchez et al., 2020), in-depth variations (Garres-Diaz et al., 493 2021), and grain-fluid interactions (Bouchut et al., 2016). However, some of these models are not yet applicable 494 for field-scale simulations or require more parameters that are not easy to calibrate, which could lead to 495 significant uncertainties.

496 In order to preserve the numerical stability of each code (HYSEA and FUNWAVE-TVD) when 497 coupling them and to be the least intrusive possible, the coupling consisted in considering the wave parameters 498 (velocities and free-surface elevation) computed by HYSEA at a certain time as initial conditions of 499 FUNWAVE. This protocol needs to evaluate the coupling time (t_c) so that it reflects the best continuity between the two codes. Thus, the choice of t_c is important because it affects the simulated impact of the scenarios. Taken 500 501 too early, the landslide will not yet have fully formed the water wave and the impact will be reduced. Taken too 502 late, the wave will have started to spread with hydrostatic conditions and the impact may be overestimated. This 503 time also depends on the characteristics of the landslide (depth, thickness, volume, slope, etc.) and its interaction 504 with the topography. Starting the FUNWAVE-TVD simulation later increases the impacted area and the 505 elevations of water at the coasts. For example, in the Piton 200 scenario, if we start the FUNWAVE-TVD 13s 506 before t_{c2} , the maximum water elevation is reduced by 3.1 m at the airport and by 0.8 m in Dzaoudi. Thus, using a slightly longer coupling time is a way to obtain envelope scenarios satisfying precautionary principles in terms 507 508 of hazard assessment, as done in this work. 509

510 511

6.3 Tsunami generation, wave propagation and inundation by combining the scenarios

512 Figure 8 displays the maximum sea-surface elevation obtained by combining the results of numerical 513 simulations from all the eight scenarios simulated for a 50 m mesh grid. The most penalizing scenarios can 514 locally generate elevations of the water level greater than 1 m, in particular along the eastern coast of Petite 515 Terre where they can reach several meters locally for the most impactful scenarios. The scenarios considered 516 here are associated with rather maximizing assumptions. The most impactful sources are linked to sliding masses 517 of large volume and occurring at shallow depths, i.e. close to the reef and along the slope east of Petite Terre. A 518 good example is the Piton 200 scenario (Figure 4a) that mainly participates in defining the map of the maximum 519 elevations of the water body (Figure 8) for the east part of Petite Terre. Other considered scenarios have a limited 520 impact, with elevations of the water level less than 30 cm at the coast of the lagoon and the reef. This point is particularly illustrated by the impact of the 3 lobe scenarios (huge volume at middle depth) and the South-Slope 521 522 and North-Slope scenarios (small volume at shallow depth) (Figure 4). This also concerns the collapses of the 523 new volcanic edifice, corresponding to one of the most significant cases in terms of destabilized volume. 524 However, the movements transmitted to the water are so deep that the impact at the free surface is strongly 525 attenuated and the impact along the coasts is low.

526 The impact on the coast of simulated potential tsunamis is heterogeneous and depends not only on the 527 considered scenarios but also on the coastal areas as is generally the case. Globally, modeled impacts of tsunamis 528 along the coast of Mayotte can be considered as moderate, except for some maximizing scenarios along the 529 eastern side of the island. This side of the island is the most exposed since we considered potential landslides in 530 this area, associated with the ongoing seismo-volcanic activity. However, the reef plays an essential protective 531 role since it can dissipate much of the energy of tsunamis coming westward, as it does for cyclonic waves 532 (Kunkel at al., 2006, De la Torre et al., 2008). The east coast of Petite Terre is much more exposed because of 533 the lack of a reef. Elsewhere, coastal morphologies characterized by steep slopes associated with the presence of mangroves also mitigate the impact of submersion due to dissipation processes. Given the orders of magnitude 534 535 of the modeled events, it is essential to take into account the tides and the subsidence linked to regional deflation 536 (phenomenon of emptying of the magmatic chamber (Cesca et al., 2020, Lemoine et al., 2020a, Feuillet et al., 537 2021)). In our study, unfavorable assumptions (full spring tide and homogeneous subsidence of 15 cm) have 538 been considered during the modeling of tsunamis in order to conserve the logic of the "worst credible risky 539 case".

540 More locally, in addition to the exposure to the phenomenon, the level of risk depends on the presence 541 of buildings, roads or particular infrastructures such as the airport or administrative centers and their vulnerability. The most exposed areas (in terms of wave height) are not associated with a high level of risk as 542 543 they are located along the eastern coast of Petite Terre that is almost uninhabited (beaches surrounded by relief 544 and cliffs). Higher resolution simulations (10 m resolution) were carried out for some of the most impactful 545 scenarios such as Piton 200 and South Slope in order to model the potential flooding. To engage operational 546 communication with local authorities, we were encouraged to map a simplified parameter representing the 547 intensity of flooding along the coasts. Because it has been computed by integrating all the most impactful 548 scenarios, it reflects the intensity, from low to very high, on a specific area, as defined by the French coastal risk 549 prevention plan guide (MEDDE, 2014) (Table 3). The resulting mapping is thus obtained by combining the 550 water depths and flow velocities simulated for the most impactful scenarios, and for simplification, it has been 551 associated with the notion of hazard (or pseudo-hazard), even if it is not feasible or realistic to associate a 552 probability with the considered simulated scenarios. However, the performed simulations show that inundations 553 located on Petite Terre, and in particular at the airport and Dzaoudzi, lead to a high pseudo-hazard level. On 554 Grande Terre, specific local conditions (mangrove, steep slopes) mitigate the impact of inundation. Figure 9

exhibits such high to very high pseudo-hazard levels along the entire coastline studied, impacting in particular some coastal urbanized sectors (e.g. Figure 9d) and coastal infrastructures (Figure 9a,b). In addition, tsunami arrival times for these scenarios are around a few minutes (Figure 9), which is relatively short to set up an early warning system.

559 560

561 7. Conclusion

562

563 Since May 2018, Mayotte Island has experienced intense seismic activity linked to the on-going seismo-564 volcanic crisis. This could weaken the submarine slopes of Mayotte and trigger submarine landslides associated 565 with tsunamis. To address the hazards associated with such events, we have combined two complementary numerical models (the HYSEA and the Boussinesq FUNWAVE- TVD models) to numerically simulate eight 566 567 potential submarine landslides and the associated generation and propagation of waves. Our results show that, 568 for the most penalizing scenarios, the generated elevations of the water level are generally around 1 m, except 569 in Petite Terre where they can reach very locally more than 15 m in an uninhabited area. Indeed, the most 570 impactful sources are linked to sliding masses of large volumes and occurring at shallow depths, i.e. close to the 571 reef and along the slope east of Petite Terre, as represented by the Piton 200 scenario. Other considered scenarios 572 have a limited impact, with less than 30 cm elevations of the sea level at the coast of the lagoon and the reef. 573 The impact on the coast is therefore non-uniform and depends on the side of the island. Globally, the eastern 574 side of the island is the most exposed since it faces the location of landslides potentially generated by the seismo-575 volcanic activity. Fortunately, at this location, the reef plays a key protective role by dissipating much of the 576 energy of tsunamis coming westward. Preserving the reef is therefore crucial to maintain this natural protection.

577 Our simulations show that, for some of the most impactful scenarios, such as Piton 200 and South Slope, 578 inundations located on Petite Terre, and in particular at the airport and Dzaoudzi (up to 1.5 m), can lead locally 579 to a very high hazard level. On Grande Terre, specific local conditions (mangrove, steep slopes) mitigate the 580 impact of any inundation. Note that preserving the mangroves is also crucial to reduce flooding.

581 Our study opens the way to the development and use of complex numerical models to simulate both 582 landslides and wave propagation processes (e.g. Rauter et al., 2022; Yavari-Ramshe and Ataie-Ashtiani, 2016 583 for a review), instead of simple empirical laws for the landslides (Lemoine et al., 2020b). This should improve 584 hazard and risk assessment strategies in contexts similar to Mayotte, i.e. in active seismo-volcanic contexts near 585 the coast. To understand the results presented in this study, it is essential to be aware of the uncertainties linked 586 to the scenario definition, model approximations, empirical rheological laws, and the simplification of natural 587 complexity (see section 6.1 and Figure A.6). Each of these parameters affect the tsunami wave, but the non-588 hydrostatic effects dominate in such a context and should thus be accounted for in the future. Furthermore, we 589 have not taken into account the heterogeneity of the material involved, grain/fluid interactions, and the transition 590 phase from an initially coherent mass to a granular flow. However, the purpose of these simulations is to give 591 the order of magnitude of waves, for a set of realistic submarine landslide scenarios, using state-of-the-art 592 models. Thus, our results confirm the potential of advanced numerical models to build precise hazard maps 593 suitable for use in land-use planning or the design of evacuation plans (Leone et al., 2021).

594 This approach could however be improved in different aspects. More precise scenarios could be 595 determined using new geological data from future marine surveys and drillings in the targeted areas. From the 596 modeling point of view, the simulation accuracy could be significantly improved by developing more advanced 597 numerical models for landslide and tsunami waves accounting for non-hydrostatic effects, different coordinate 598 systems for the landslide and the tsunami, grain-fluid interactions in the granular mass, and multilayer 599 approaches for the landslide and tsunami wave. Another key improvement would be to account for uncertainties 600 and develop probabilistic approaches in the simulated hazard maps (Loyholt et al., 2020), based notably on series 601 of simulations using for example statistical emulation (e.g. Salmanidou et al., 2019).

602

603 Acknowledgements

604 We thank staff scientists and crew for the data provided by MAYOBS 1 cruise that was funded by the CNRS-605 INSU TELLUS MAYOTTE program (SISMAYOTTE project). This study was supported by the Réseau de Surveillance Volcanologique et Sismologique de Mayotte (REVOSIMA). Since June 2019, all activities on 606 Mayotte are funded by le Ministère de l'Enseignement Supérieur, de la Recherche et de l'Innovation (MESRI), 607 le Ministère de la Transition Ecologique (MTE), le Ministère des Outremers (MOM), le Ministère de l'Intérieur 608 609 (MI), and le Ministère des Armées with the support of the DIRMOM (Direction Interministérielle aux Risques Majeurs en Outremer) and the MAPPPROM (Mission d'appui aux politiques publiques pour la prévention des 610 risques majeurs en Outremer) throughout the REVOSIMA. The work was also funded by the contract ERC-CG-611 2013-PE10-617472 SLIDEQUAKES along with the Spanish Government and FEDER through the Research 612

- 613 Project MTM2015-70490- C2-2-R. This study contributes to the IdEx Université de Paris ANR contract
- 614 ANR-18-IDEX-0001.

615 References

- Abadie, S., Morichon, D., Grilli, S.T., Glockner, S., 2010. Numerical simulation of waves generated by
 landslides using a multiple-fluid Navier–Stokes model. Coastal Engineering, 57, 779-794.
- Abadie, S. M., Harris, J. C., Grilli, S. T., Fabre, R., 2012. Numerical modeling of tsunami waves generated by
 the flank collapse of the Cumbre Vieja Volcano (La Palma, Canary Islands): Tsunami source and near field
 effects, J. Geophys. Res., 117, C05030, doi:10.1029/2011JC007646.
- Abadie, S., Paris, A., Ata, R., Le Roy, S., Arnaud, G., Poupardin, A., Clous, L., Heinrich, P., Harris, J.C.,
 Pedreros, R., Krien, Y., 2020. La Palma landslide tsunami: computation of the tsunami source with a calibrated
 multi-fluid Navier–Stokes model and wave impact assessment with propagation models of different
- 624 types. Natural Hazards and Earth System Sciences, 20, 3019-3038.
- Asunción-Hernández, M.D., Parés-Madroñal, C.M., Díaz-del-Río-Español, V., Castro-Díaz, M.J., MacíasSánchez, J., Vázquez, J.T., Fernández-Salas, L.M., Bárcenas-Gascón, P., González-Vida, J.M., Morales-deLuna, T., 2012. Deslizamientos submarinos y tsunamis en el Mar de Alborán. Un ejemplo de modelización
 numérica. Ed : Instituto Espanol de Oceanographia. DOI:10.13140/RG.2.1.2122.3845.
- Asunción, M.D., Castro, M.J., Fernández-Nieto, E.D., Mantas, J.M., Ortega Acosta, S., González-Vida, J.M.,
 2013. Efficient GPU implementation of a two waves TVD-WAF method for the two-dimensional one layer
 shallow water system on structured meshes. Computers Fluids, 80, 441-452.
- Bontemps, N., Lacroix, P., Larose, E., Jara, J., Taipe, E., 2020. Rain and small earthquakes maintain a slowmoving landslide in a persistent critical state. Nature Communication 11 (780), 1-10.
- Bouchut, F., Fernández-Nieto, E.D., Mangeney, A., Narbona-Reina, G., 2016. A two-phase two-layer model for
 fluidized granular flows with dilatancy effects. Journal of Fluid Mechanics, 801, 166 221.
- Brunet, M., Moretti, L., Le Friant, A., Mangeney, A., Fernández Nieto, E.D., Bouchut, F., 2017. Numerical
 simulation of the 30–45 ka debris avalanche flow of Montagne Pelée volcano, Martinique: from volcano flank
 collapse to submarine emplacement. Natural Hazards, 87, 1189-1222.
- Bunya, S., Dietrich, J.C., Westerink, J.J., Ebersole, B.A., Smith, J.M., Atkinson, J.H., Jensen, R.E., Resio, D.T.,
 Luettich, R.A., Dawson, C.N., Cardone, V.J., Cox, A.T., Powell, M.D., Westerink, H.J., Roberts, H.J., 2010.
 A High-Resolution Coupled Riverine Flow, Tide, Wind, Wind Wave, and Storm Surge Model for Southern
 Louisiana and Mississippi. Part I: Model Development and Validation. Monthly Weather Review, 138, 2, 345-
- 643 377.
- Castro Díaz, M.J., Ferreiro, A.M., García-Rodríguez, J.A., González-Vida, J.M., Macias, J., Parés, C., Vázquez Cendón, M.E., 2005. The numerical treatment of wet/dry fronts in shallow flows: application to one-layer and
 two-layer systems. Math. Comput. Model., 42, 3-4, 419-439.
- Castro Díaz, M.J., Gallardo, J.M., Parés, C., 2006. High order finite volume schemes based on reconstruction of
 states for solving hyperbolic systems with nonconservative products. Applications to shallow-water
 systems. Math. Comput., 75, 1103-1134.
- Castro Díaz, M.J., López, J.A., Madroñal, C.P., 2008a. Finite Volume Simulation of the Geostrophic Adjustment
 in a Rotating Shallow-Water System. SIAM J. Sci. Comput., 31, 444-477.
- Castro Díaz, M.J., Rebollo, T.C., Fernández-Nieto, E.D., Vida, J.M., Parés, C., 2008b. Well-balanced finite
 volume schemes for 2D non-homogeneous hyperbolic systems. Application to the dam-break of
 Aznalcóllar. Computer Methods in Applied Mechanics and Engineering, 197, 3932-3950.
- Cesca, S., Letort, J., Razafindrakoto, H.N., Heimann, S., Rivalta, E., Isken, M.P., Nikkhoo, M., Passarelli, L.,
 Petersen, G.M., Cotton, F., & Dahm, T., 2020. Drainage of a deep magma reservoir near Mayotte inferred
 from seismicity and deformation. Nature Geoscience, 13, 87-93.
- Chen, Q., 2006. Fully Nonlinear Boussinesq-Type Equations for Waves and Currents over Porous Beds. Journal
 of Engineering Mechanics-asce, 132, 2, 220-230.
- Chen, Q., Kirby, J.T., Dalrymple, R.A., Shi, F., Thornton, E.B., 2003. Boussinesq modeling of longshore
 currents. Journal of Geophysical Research, 108, n° C11, 3362.
- De la Torre, Y., Lecacheux, S., Pedreros, R., Balouin, Y., 2008. Modélisation de la houle cyclonique dans le
 lagon de Mayotte. Xèmes Journées Nationales Génie Côtier Génie Civil, Sophia Antipolis,
 10.5150 /jngcgc.2008.031-D.
- Debeuf, D., 2004. Etude de l'évolution volcano-structurale et magmatique de Mayotte, Archipel des Comores,
 océan Indien: approches structurales, pétrographique, géochimique et géochronologique, PhD, La Réunion
 University, 277p.
- Delannay, R., Valance, A., Mangeney, A., Roche, O., Richard, P., 2017. Granular and particle-laden flows: from
 laboratory experiments to field observations. Journal of Physics D, 50, 40.
- Delgado-Sánchez, J.M., Bouchut, F., Fernández-Nieto, E.D., Mangeney, A., Narbona-Reina, G., 2020. A twolayer shallow flow model with two axes of integration, well-balanced discretization and application to
 submarine avalanches. J. Comput. Phys., 406, 109186.
- Di Risio, M., De Girolamo, P., Beltrami, G., 2011. Forecasting landslide generatedtsunamis: a review, The
 Tsunami Threat -Research and Technology, Nils-Axel Marner (Ed.).
- Dondin, F. J.-Y., Heap, M. J., Robertson, R. E. A., Dorville, J.-F. M., & Carey, S., 2016. Flank instability
 assessment at Kick-'em-Jenny submarine volcano (Grenada, Lesser Antilles): A multidisciplinary approach
 using experiments and modeling. Bulletin of Volcanology, 79(1), 5. https://doi.org/10.1007/s00445-016-10908.
- Edwards, A.N., Gray, J.M., 2014. Erosion–deposition waves in shallow granular free-surface flows. Journal of
 Fluid Mechanics, 762, 35 67.

- 681 Edwards, A.N., Viroulet, S., Kokelaar, B.P., Gray, J.M., 2017. Formation of levees, troughs and elevated 682 channels by avalanches on erodible slopes. Journal of Fluid Mechanics, 823, 278 - 315.
- Edwards, A.N., Russell, A.S., Johnson, C.G., Gray, J.M., 2019. Frictional hysteresis and particle deposition in
 granular free-surface flows. Journal of Fluid Mechanics, 875, 1058 1095.
- Escalante, C., Dumbser, M., Castro. M.J., 2019. An efficient hyperbolic relaxation system for dispersive non hydrostatic water waves and its solution with high order discontinuous Galerkin schemes. Journal of
 Computational Physics (394)385–416.
- Esposti Ongaro, T., de'Michieli Vitturi, M., Cerminara, M., Fornaciai, A., Nannipieri, L., Favalli, M., Calusi, B.,
 Macías, J., Castro, M.J., Ortega, S., González-Vida, J.M., Escalante, C., 2021. Modeling tsunamis generated
 by submarine landslides at Strom- boli volcano (Aeolian Islands, Italy): a numerical benchmark study.
 Frontiers in Earth Science 9, 274.
- Fernández-Nieto, E.D., Bouchut, F., Bresch, D., Díaz, M.J., Mangeney, A., 2008. A new Savage-Hutter type
 model for submarine avalanches and generated tsunami. J. Comput. Phys., 227, 7720-7754.
- Feuillet, N., Jorry, S.J., Crawford, W.C., Deplus, C., Thinon, I., Jacques, E., Saurel, J., Lemoine, A., Paquet, F.,
 Satriano, C., Aiken, C., Foix, O., Kowalski, P., Laurent, A., Rinnert, E., Cathalot, C., Donval, J.P., Guyader,
 V., Gaillot, A., Scalabrin, C., Moreira, M., Peltier, A., Beauducel, F., Grandin, R., Ballu, V., Daniel, R.,
 Pelleau, P., Gomez, J., Besançon, S., Géli, L., Bernard, P., Bachélery, P., Fouquet, Y., Bertil, D., Lemarchand,
 A., & Van der Woerd, J., 2021. Birth of a large volcanic edifice offshore Mayotte via lithosphere-scale dyke
 intrusion. Nature Geoscience, 14, 787 795.
- Fine, I.V., Rabinovichb, A.B., Bornholdt, B.D., Thomsonb, R.E., Kulikovb, E.A., 2005. The Grand Banks
 landslide-generated tsunami of November 18, 1929: preliminary analysis and numerical modeling. Marine
 Geology MAR GEOLOGY. 215. 10.1016/j.margeo.2004.11.007.
- Fine, I.V., Rabinovich, A.B., Thomson, R.E., Kulikov, E.A., 2003. Numerical Modeling of Tsunami Generation
 by Submarine and Subaerial Landslides. DOI:10.1007/978-94-010-0205-9_9.
- Fischer, J.-T., Kowalski, J., Pudasaini, S.P., 2012. Topographic curvature effects in applied avalanche modeling,
 Cold Regions Science and Technology, 74-75, 21–30, doi: 10.1016/j.coldregions.2012.01.005.
- Garres-Díaz, J., Fernández-Nieto, E.D., Mangeney, A., Luna, T.M., 2021. A weakly non-hydrostatic shallow
 model for dry granular flows. J. Sci. Comput., 86(2), 25.
- Giachetti T., Paris R., Kelfoun K., Pérez-Torrado F. J., 2011. Numerical modelling of the tsunami triggered by
 the Güimar debris avalanche, Tenerife (Canary Islands): comparison with field-based data: Marine Geology,
 v. 284, p. 189-202. DOI:10.1016/j.margeo.2011.03.018.
- Giachetti, T., Paris, R., Kelfoun K., Ontowirjo, B., 2012. Tsunami hazard related to a flank collapse of Anak
 Krakatau Volcano, Sunda Strait, Indonesia, Geological Society, London, Special Publications, 361, 79-90.
- Gittings, M. L., 1992. SAIC's adaptive grid Eulerian hydrocode. In Defense nuclear agency numerical methods
 symposium (pp. 28-30).
- González-Vida, J.M., Macías, J., Castro, M. J., Sánchez-Linares, C., de la Asunción, M., Ortega-Acosta, S. and
 Arcas, D., 2019. The Lituya Bay landslide-generated mega-tsunami –numerical simulation and sensitivity
 analysis, 2019, Nat. Hazards Earth Syst. Sci., 19, 369–388.
- Gouhier, M. and Paris, R., 2019. SO2 and tephra emissions during the December 22, 2018 Anak Krakatau
 eruption", Volcanica, 2(2), pp. 91–103. doi: 10.30909/vol.02.02.91103
- Grilli, S., Tappin, D., Carey, S., Watt, S., Ward, S., Grilli, A., Engwell, S., Zhang, C., Kirby, J., Schambach, L.,
 Muin, M., 2019. Modelling of the tsunami from the December 22, 2018 lateral collapse of Anak Krakatau
 volcano in the Sunda Straits, Indonesia. Scientific Reports. 9. DOI:10.1038/s41598-019-48327-6.
- Grilli, S.T., C. Zhang, J.T. Kirby, A.R. Grilli, D.R. Tappin, S.F.L. Watt, J.E. Hunt, A. Novellino, S. Engwell,
 M.E.M. Nurshal, M. Abdurrachman, M. Cassidy, A.L. Madden-Nadeau, S. Day, 2021.Modeling of the Dec.
 22nd 2018 Anak Krakatau volcano lateral collapse and tsunami based on recent field surveys: Comparison
 with observed tsunami impact, Marine Geology, 440, 106566.
- Gylfadóttir, S., Kim, J., Helgason, J. K., Brynjólfsson, S., Hoskuldsson, A., Jóhannesson, T., Harbitz, C.,
 Løvholt, F., 2017. The 2014 Lake Askja rockslide-induced tsunami: Optimization of numerical tsunami model
 using observed data. Journal of Geophysical Research: Oceans. 122. DOI:10.1002/2016JC012496.
- Heinrich, Ph., Mangeney, A., Guilbourg, S., Roche, R., Boudon, G., Cheminée, J. L., 1998. Numerical simulation of a potential landslide-generated tsunami in Monserrat, GEOPHYS. RES. LETT., 25(19), 3697-3700.
- Heinrich, P., Piatanesi, A., Hébert, H., 2001a. Numerical modelling of tsunami generation and propagation from
 submarine slumps: the 1998 Papua New Guinea event. Geophysical Journal International, 145, 97-111.
- Heinrich, P., Boudon, G., Komorowski, J., Sparks, R.S., Herd, R.A., Voight, B., 2001b. Numerical simulation
 of the December 1997 Debris Avalanche in Montserrat, Lesser Antilles. Geophysical Research Letters, 28,
 2529-2532.
- Jiang, L., Leblond, P.H., 1992. The coupling of a submarine slide and the surface waves which it generates. Journal of Geophysical Research, 97, 12731-12744.
- Kelfoun, K., Druitt, T., van Wyk de Vries, B., Guilbaud, M.-N., 2008. Topographic reflection of the Socompa debris avalanche, Chile. Bulletin of Volcanology. 70. 1169-1187. 10.1007/s00445-008-0201
- Kelfoun K., Giachetti T., Labazuy P., 2010. Landslide–generated tsunamis at Réunion Island. Journal of
 Geophysical Research, Earth Surface, 115, F04012. DOI:10.1029/2009JF001381.
- Kennedy, A.B., Kirby, J.T., Chen, Q., Dalrymple, R.A., 2001. Boussinesq-type equations with improved nonlinear performance. Wave Motion, 33, 225-243.

- Kirby, J. T., Shi, F., Tehranirad, B., Harris, J. C., and Grilli, S. T, 2013. Dispersive tsunami waves in the ocean:
 Model equations and sensitivity to dispersion and Coriolis effects, Ocean Modell., 62, 39–55.
- Kirby, J., Grilli, S., Horrillo, J., Liu, P., Nicolsky, D., Abadie, S., Ataie-Ashtiani, B., Castro, M., Clous, L.,
 Escalante Sánchez, C., Fine, I., González-Vida, J., Løvholt, F., Lynett, P., Ma, G., Macías, J., Ortega, S., Shi,
 F., Yavari, S., Zhang, C., 2022. Validation and inter-comparison of models for landslide tsunami generation.
 Ocean Modelling. 170. 101943. DOI:10.1016/j.ocemod.2021.101943.
- Kunkel, C.M., Hallberg, R., Oppenheimer, M., 2006. Coral reefs reduce tsunami impact in model simulations. Geophysical Research Letters, 33. DOI:10.1029/2006GL027892.
- Le Friant, A.L., Heinrich, P., Deplus, C., Boudon, G., 2003. Numerical simulation of the last flank- collapse
 event of Montagne Pelée, Martinique, Lesser Antilles. Geophysical Research Letters, Volume 30, 2, p.1034.
 DOI:10.1029/2002GL015903
- Le Friant, A., Ishizuka, O., Boudon, G., Palmer, M.R., Talling, P., Villemant, B., Adachi, T., Aljahdali, M.,
 Breitkreuz, C., Brunet, M., Caron, B., Coussens, M., Deplus, C., Endo, D., Feuillet, N., Fraas, A.J., Fujinawa,
 A., Hart, M. B., Hatfield, R.G., Hornbach, M., Jutzeler, M., Kataoka, K. S., Komorowski, J-C., Lebas, E.,
 Lafuerza, S., Maeno, F., Manga, M., Martínez-Colón, M., McCanta, M., Morgan, S., Saito, T., Slagle, A.,
- Sparks, S., Stinton, A., Stroncik, N., Subramanyam, K. S.V., Tamura, Y., Trofimovs, J., Voight, B., Wall Palmer, D., Wang, F., Watt, S.F.L. 2015. Submarine record of volcanic island construction and collapse in the
- Fainler, D., Wang, F., Watt, S.F.L. 2015. Submarine record of volcanic island construction and conspscent the
 Lesser Antilles arc: First scientific drilling of submarine volcanic island landslides by IODP Expedition 340.
 Geochem., Geophys., Geosyst, 16, 2, 420-442.
- Le Friant, A., Lebas E., Brunet, M., Lafuerza, S., Hornbach, M., Coussens, M, Watt, S.F.L., Cassidy, M.J.,
 Talling, P.J. and IODP 340 Expedition scientists (2019). Submarine landslides around volcanic islands: A
 review of what can be learned from the Lesser Antilles Arc. AGU Book "Submarine landslides: subaqueous
 mass transport deposits from outcrops to seismic profiles" edited by K. Ogata, A. Festa, G.A.
 Pini. <u>https://doi.org/10.1002/9781119500513.ch17</u>
- Le Roy, S., Pedreros, R., Monfort, D., Terrier, M., 2015. Simulations numériques de tsunamis sur la côte méditerrannéenne Française: le cas d'Antibes. La Houille Blanche. Vol 101, 6, DOI:10.1051/lhb/20150063.
- Le Roy, S.A., Legendre, Y., 2017. Détermination de la submersion marine liée aux tsunamis en Martinique.
 Rapport final BRGM/RP-66547-FR p 177p.
- Lebas, E., Lebas, E., Friant, A.L., Deplus, C., Voogd, B.D., 2018. Understanding the Evolution of an Oceanic
 Intraplate Volcano From Seismic Reflection Data: A New Model for La Réunion, Indian Ocean. Journal of
 Geophysical Research, 123, 1035-1059.
- Lemoine, A., Briole, P., Bertil, D., Roullé, A., Foumelis, M., Thinon, I., Raucoules, D., de Michele, M., Valty,
 P., Hoste Colomer, R., 2020a. The 2018–2019 seismo-volcanic crisis east of Mayotte, Comoros islands:
 seismicity and ground deformation markers of an exceptional submarine eruption. Geophysical Journal
 International, 223, 22-44.
- Lemoine, A., Pedreros, R., Filippini, A., 2020b, Scénarios d'impact de tsunamis pour Mayotte. BRGM/RP 69869-FR.
- Leone F., Gherardi M., Péroche M., Idaroussi F., Lagahé E., 2021. Planifier les évacuations préventives face au risque de tsunami à Mayotte. Rapport intermédiaire du projet EVACTSU Mayotte pour le compte de la DIRMOM. https://arcg.is/1be4iC0.
- Liu, P. L.-F., Higuera, P., Husrin, S., Prasetya, G. S., Prihantono, J., Diastomo, H., Pryambodo, D. G., &
 Susmoro, H., 2020. Coastal landslides in Palu Bay during 2018 Sulawesi earthquake and tsunami. Landslides.
 https://doi.org/10.1007/s10346-020-01417-3.
- Lipman, P.W., Normark, W.R., Moore, J.G., Wilson, J.B., Gutmacher, C.E., 1988. The Giant Submarine Alika
 Debris Slide, Mauna Loa, Hawaii. Journal of Geophysical Research, 93, 4279-4299.
- Løvholt, F., Pedersen, G., Gisler, G., 2008. Oceanic propagation of a potential tsunami off La Palma Island.
 Journal of Geophysical Research. 113. DOI:10.1029/2007JC004603.
- Løvholt, F., Glimsdal, S., Harbitz, C., 2020. On the landslide tsunami uncertainty and hazard. Landslides. 17.
 DOI:10.1007/s10346-020-01429-z.
- Lucas, A., Mangeney, A., Ampuero, J.P., 2014. Frictional velocity-weakening in landslides on Earth and on
 other planetary bodies. Nature communications, 5, 3417. DOI: 10.1038/ncomms4417.
- Ma, G., Kirby, J.T., Hsu, T., Shi, F., 2015. A two-layer granular landslide model for tsunami wave generation:
 Theory and computation. Ocean Modelling, 93, 40-55.
- Macías, J., Vazquez, J.T., Fernández-Salas, L.M., González-Vida, J.M., Bárcenas, P., Castro, M.J., Díaz-delRío, V., Alonso, B., 2015. The Al-Borani submarine landslide and associated tsunami. A modelling
 approach. Marine Geology, 361, 79-95.
- Macías, J., Escalante Sánchez, C., Castro, M., González Vida, J., Ortega, S., 2017. HySEA model. NTHMP
 Landslide Benchmarking Results. 10.13140/RG.2.2.27081.60002.
- Macías, J., Castro, M.J., Ortega, S., González-Vida, J.M., 2020a. Performance assessment of Tsunami-HySEA
 model for NTHMP tsunami currents benchmarking. Field cases. Ocean Modelling, 152, 101645.
- Macías, J., Escalante, C., Castro, M., J., 2021., Multilayer-HySEA model validation for landslide-generated
 tsunamis Part 2: Granular slides, Nat. Hazards Earth Syst. Sci., 21, 791–805.
- Majd, M., Sanders, B.F., 2014. The LHLLC scheme for Two-Layer and Two-Phase transcritical flows over a
 mobile bed with avalanching, wetting and drying. Advances in Water Resources, 67, 16-31.
- 811 Mangeney, A., Heinrich, P., Roche, R., Boudon, G., Cheminée, J.L., 2000. Modeling of debris avalanche and
- generated water waves: Application to real and potential events in Montserrat. Physics and Chemistry of The
 Earth Part A-solid Earth and Geodesy, 25, 741-745.

- 814 Mangeney, A., Bouchut, F., Thomas, N., Vilotte, J., Bristeau, M., 2007a. Numerical modeling of self-815 channeling granular flows and of their levee- channel deposits. Journal of Geophysical Research: Earth
- 816 Surface. 112. F02017. DOI:10.1029/2006JF000469.
- Mangeney, A., Tsimring, L.S., Volfson, D., Aranson, I.S., Bouchut, F., 2007b. Avalanche mobility induced by
 the presence of an erodible bed and associated entrainment. Geophysical Research Letters, 34. 22401.
 DOI:10.1029/2007GL031348.
- Maramai, A., Graziani, L., Tinti, S., 2005. Tsunamis in the Aeolian Islands (southern Italy): A review. Marine
 Geology. 215. 11–21. 10.1016/j.margeo.2004.03.018.
- Mercury, N., Lemoine, A., Bertil, D., Vanderwoerd, J., Doubre, C., & Hoste-Colomer, R. (2020, December).
 The 2018-2020 seismo-volcanic crisis, east of Mayotte, Comoros islands: in-depth study of poorly
 instrumented first months of crisis. In *AGU Fall Meeting Abstracts* (Vol. 2020, pp. V040-0007).
- MEDDE, 2014. Guide Méthodologique, Plan de Prévention des Risques Littoraux, 05-2014, 169 p.
- Moore, J.G., Clague, D.A., Holcomb, R.T., Lipman, P.W., Normark, W.R., Torresan, M.E., 1989. Prodigious
 submarine landslides on the Hawaiian Ridge. Journal of Geophysical Research, Vol. 94, Pages 17,465 17,484.
- Moretti, L., Allstadt, K.E., Mangeney, A., Capdeville, Y., Stutzmann, É., Bouchut, F., 2015. Numerical
 modeling of the Mount Meager landslide constrained by its force history derived from seismic data. Journal of
 Geophysical Research, 120, 2579-2599.
- 831 Papadopoulos, G.and Kortekaas, S. (2003). Characteristics of Landslide Generated Tsunamis from
- Observational Data. Submarine mass movements and their consequences, 19, 367-374. 10.1007/978-94-0100093-2_40.
- Paris, A., Okal, E.A., Guerin, C., Heinrich, P., Schindelé, F., Hébert, H., 2019. Numerical Modeling of the June
 17, 2017 Landslide and Tsunami Events in Karrat Fjord, West Greenland. Pure and Applied Geophysics, 176.
 DOI:10.1007/s00024-019-02123-5.
- Paris, A., Heinrich, P., Paris, R., Abadie, S., 2020. The December 22, 2018 Anak Krakatau, Indonesia, Landslide
 and Tsunami: Preliminary Modeling Results. Pure and Applied Geophysics. 177. DOI:10.1007/s00024-01902394-y.
- Pelinovsky, E.N., Zahibo, N., Dunkley, P., Edmonds, M., Herd, P., Talipove, T., Kozelkov, A., Nikolkina, I.,
 2004. Tsunami generated by the volcano eruption on July 12-13, 2003 at Montserrat, Lesser Antilles: Science
 of Tsunami Hazards, v. 22, p. 44.
- Peruzzetto, M., Komorowski, J., Le Friant, A., Rosas-Carbajal, M., Mangeney, A., Legendre, Y. 2019. Modeling
 of partial dome collapse of La Soufrière of Guadeloupe volcano: implications for hazard assessment and
 monitoring. Scientific Reports, 9. DOI: 10.1038/s41598-019-49507-0.
- Peruzzetto, M., Mangeney, A., Bouchut, F., Grandjean, G., Levy, C., Thiery, Y., Lucas, A., 2021. Topography
 curvature effects in thin-layer models for gravity-driven flows without bed erosion. Journal of Geophysical
 Research: Earth Surface, 126, e2020JF005657.
- Poisson, B., & Pedreros, R., 2010. Numerical modelling of historical landslide-generated tsunamis in the French
 Lesser Antilles. Natural Hazards and Earth System Sciences, 10, 1281-1292.
- Popinet, S., 2015. A quadtree-adaptive multigrid solver for the Serre-Green-Naghdi equations. J. Comput. Phys.,
 302, 336-358.
- Pouliquen, O., 1999. Scaling laws in granular flows down rough inclined planes. Physics of Fluids, 11, 542-548.
- Pouliquen, O., Forterre, Y., 2002. Friction law for dense granular flows: application to the motion of a mass
 down a rough inclined plane. Journal of Fluid Mechanics, 453, 133 151.
- Rauter, M., Viroulet, S., Gylfadottir, S., Fellin, W., Løvholt, F., 2022. Granular porous landslide tsunami
 modelling the 2014 Lake Askja flank collapse. Nature Communications. 13. 10.1038/s41467-022-28296-7.
- Rocha, F.M., Johnson, C.G., Gray, J.M., 2019. Self-channelisation and levee formation in monodisperse granular
 flows. Journal of Fluid Mechanics, 876, 591 641.
- Roger, J., 2019. Potential tsunami hazard related to the seismic activity East of Mayotte Island, Comoros
 Archipelago. Science of Tsunami Hazards: Journal of Tsunami Society International, 38 (3), p. 118-131. ISSN 8755-6839.
- Rohmer, J., Rousseau, M., Lemoine, A., Pedreros, R., Lambert, J., Benki, A., 2017. Source characterisation by
 mixing long-running tsunami wave numerical simulations and historical observations within a metamodel aided ABC setting. Stochastic Environmental Research and Risk Assessment, 32, 967-984.
- Romano, A., 2020. Physical and Numerical Modeling of Landslide-Generated Tsunamis: A Review.
 10.5772/intechopen.93878.
- Russell, A.S., Johnson, C.G., Edwards, A.N., Viroulet, S., Rocha, F.M., Gray, J.M., 2019. Retrogressive failure
 of a static granular layer on an inclined plane. Journal of Fluid Mechanics, 869, 313 340.
- Salmanidou, D.M., Georgiopoulou, A., Guillas, S., and Dias, F., 2018. Rheological considerations for the
 modelling of submarine sliding at Rockall Bank, NE Atlantic Ocean, Physics of Fluids 30, 030705.
- Salmanidou, D., Heidarzadeh, M., Guillas, S., 2019. Probabilistic Landslide-Generated Tsunamis in the Indus
 Canyon, NW Indian Ocean, Using Statistical Emulation. Pure and Applied Geophysics. 176. 1-16.
 DOI:10.1007/s00024-019-02187-3.
- Sassa, K., Dang, K., Yanagisawa, H., He, B., 2016. A new landslide-induced tsunami simulation model and its
 application to the 1792 Unzen-Mayuyama landslide-and-tsunami disaster. Landslides. 13.
 DOI:10.1007/s10346-016-0691-9.
- 878 Satake, K. (2001). Tsunami modeling from submarine landslides. ITS Proc 6(6-4):665–674
- Saurel, J.-M., Jacques, E., Aiken, C., Lemoine, A., Retailleau, L., Lavayssière, A., Foix, O., Dofal, A., Laurent,
- A., Mercury, N., Crawford, W., Lemarchand, A., Daniel, R., Pelleau, P., Bès de Berc, M., Roullé, A., Broucke,

- 881 C., Colombain, A. Besançon, S., Guyavarch, P., Kowalski, P., Roudaut, M., Battaglia, J., Bodihar, S., Bouin,
- 882 M.-P., Canjamale, K., Desfete, N., Doubre, C., Dretzen, R., Ferrazzini, V., Fontaine, F., Géli, L., Griot, C.,
- Grunberg, M., Guzel, E. C., Hoste Colomer, R., Lambotte, S., Léger, F., Vergne, J., Satriano, C., Tronel, F.,
- Van der Woerd, J., Feuillet, N., Fouquet, Y., Stéphan, J., Rinnert, E., Thinon, I., 2022. Mayotte seismic crisis:
 building knowledge in near real-time by combining land and ocean-bottom seismometers, first results, *Geophysical Journal International*, 228(2), 1281–1293.
- Scalabrin, C., Feuillet, N., Fouquet, Y., Thinon, I., Jorry, S., Gaillot, A., Guérin, C., Komorowski, J.-C., Rinnert,
 E. & Cathalot, C. (2021, December). Acoustic Plumes of the 2019 Mayotte Submarine Volcanic Eruption. In *AGU Fall Meeting 2021*. AGU.
- Shi, F., Kirby, J.T., Harris, J.C., Geiman, J.D., Grilli, S.T., 2012. A high-order adaptive time-stepping TVD
 solver for Boussinesq modeling of breaking waves and coastal inundation. Ocean Modelling, 43, 36-51.
- Thinon, I., Lemoine, A., Leroy, S., Berthod, C., Bernard, J., et al.. 2021. Discovery of recent volcanic and
 tectonic provinces along the Comoros archipelago (North Mozambique Channel) Preliminary results of the
 SISMAORE oceanographic cruise (ANR-COYOTES project). RST 27e édition de la Réunion des Sciences
 de la Terre, Lyon, France. hal-03375817v2
- Thran, M.C., Brune, S., Webster, J.M., Dominey-Howes, D., Harris, D., 2021. Examining the impact of the
 Great Barrier Reef on tsunami propagation using numerical simulations. Natural Hazards, 108, 347 388.
- Tinti, S., G. Pagnoni, and F. Zaniboni (2006), The landslides and tsunamis of the 30th of December 2002 in
 Stromboli analysed through numerical simulations. Bull. Volcanol., 68, 462–479
- Tonelli, M., Petti, M., 2009. Hybrid finite volume finite difference scheme for 2DH improved Boussinesq
 equations. Coastal Engineering, 56, 609-620.
- Voight, B., Janda, R.J., Glicken, H., Douglass, P.M. (1983). Nature and mechanics of the Mount St Helens
 rockslide-avalanche of 18 May 1980. *Géotechnique*, 33:243-273.
- Ward, S.N., Day, S., 2003. Ritter Island Volcano lateral collapse and the tsunami of 1888. *Geophysical Journal International* 154, 891–902.
- Watt, S.F., Talling, P.J., Hunt, J.E., 2014. New Insights into the Emplacement Dynamics of Volcanic Island
 Landslides. Oceanography, 27(2), 46-57.
- Watts, P., Grilli, S.T., Kirby, J.T., Fryer, G.J., & Tappin, D.R., 2003. Landslide tsunami case studies using a
 Boussinesq model and a fully nonlinear tsunami generation model. Natural Hazards and Earth System
 Sciences, 3, 391-402.
- Wei, G., Kirby, J.T., Grilli, S.T., Subramanya, R., 1995. A fully nonlinear Boussinesq model for surface waves.
 Part 1. Highly nonlinear unsteady waves. Journal of Fluid Mechanics, 294, 71-92.
- Yavari-Ramshe, S., Ataie-Ashtiani, B., 2015. A rigorous finite volume model to simulate subaerial and
 submarine landslide-generated waves. Landslides, 14, 203-221.
- Yavari-Ramshe, S., Ataie-Ashtiani, B., 2016. Numerical modeling of subaerial and submarine landslide generated tsunami waves—recent advances and future challenges. Landslides, 13, 1325-1368.
- Zhou, H., Moore, C.W., Wei, Y., Titov, V.V., 2011. A nested-grid Boussinesq-type approach to modelling
 dispersive propagation and runup of landslide-generated tsunamis. Natural Hazards and Earth System
- 919 Sciences, 11, 2677-2697.

Figure 1: Bathymetry from Lemoine et al. (2020b) based on: Gebco 2014 (https://www.gebco.net), HOMONIM
SHOM DTM (100 m resolution, https://data.shom.fr), MAYOBS 1 (Feuillet et al., 2021, 30 m resolution),
bathymetric surveys of SHOM (25 m resolution, https://data.shom.fr), litto3D (lidar data at 1 m resolution,
<u>https://data.shom.fr)</u>. The main seismic swarm related to the on-going volcano seismic crisis is indicated as well
as the new volcano. The scenarios of potential submarine instabilities are indicated in red. The location of the
gauge EB is indicated. The insert (corresponding to the black rectangle in the main map) defines five strategic
areas that will be discussed and shows the locations of the gauges voK, EM, ND, SD, WA, EA, NEPT.

Figure 2: Left column (a-g): location of scenarios of instabilities on bathymetry and associated cross-sections
(the black curve represents the bathymetry before sliding and the red and orange curves represent the bathymetry
after sliding) (a) Piton 200 (red) & Piton 100 (orange), (b) 3 Lobes, (c) South Slope, (d) North Slope, (e) West
Slope, (f) West Canyon, (g) New Volcano; Right column (h-n): thickness of the deposits calculated using Hysea
for seven scenarios: (h) Piton 200, (i) 3 Lobes, (j) South Slope, (k) North Slope, (l) West Slope, (m) West
Canyon, (n) New Volcano

Figure 3: Evolution in time of the sea-surface elevation along a longitudinal plane collinear to the sliding
direction. Srcp: location of the initial movement; tc1: time at which the wave is entirely formed at the free
surface; tc2: time at which the maximum of energy is transmitted to the free surface.

Figure 4: Maximum sea-surface elevation (MSSE) in meters calculated for the eight scenarios (resolution: 50 m): a) Piton 200, b) Piton 100, c) 3 Lobes, d) New Volcano, e) North Slope, f) South Slope, g) West Canyon and h) West Slope. The volumes of the landslides and the coupling times used are indicated for each scenario.
The bold black line is the Histolitt coastline from SHOM.

Figure 5: a) Piton 200 scenario (resolution: 50 m): wave propagation from 1 minute to 20 minutes after the landslide. The color scale represents the elevation of the calculated sea surface at a given time. The green dots on the maps indicate the locations of the gauges. b-d) Evolution of the elevation of the sea surface at different gauges (NEPT, EA, ND, SD, WA, voK, EM, EB). The locations of the gauges are indicated in Figure 1 and Figure 5a.

Figure 6: Maximum water depths (MWD) with 10 m resolution for the Piton 200 scenario. The color scale
represents the value of MWD calculated for each point: (a) Dzaoudzi and route N4, (b) Airport and Pamandzi,
(c) Mamoudzou, (d) northeast coast of Petite Terre, and (e) Koungou. The bold black line is the Histolitt coastline
from SHOM.

Figure 7: Maximum water velocities in m/s with 10 m resolution for the Piton 200 scenario. The color scale
represents the value of the maximum water velocity calculated for each point: (a) Dzaoudzi and route N4, (b)
Airport and Pamandzi, (c) Mamoudzou, (d) northeast coast of Petite Terre, and (e) Koungou. The bold black
line is the Histolitt coastline from SHOM.

Figure 8: Map of the maximum sea-surface elevation (values in m) combining the results of the eight simulated
scenarios (resolution: 50 m). The bold black line is the Histolitt coastline from SHOM.

963 Figure 9: Hazard value and time of travel of the tsunami from the combined results of the most impactful 964 scenarios (Piton 200 and South Slope) with a 10 m resolution. The color scale represents the value of the hazard 965 calculated for each point: (a) Dzaoudzi and route N4, (b) Airport and Pamandzi, (c) Mamoudzou, (d) northeast 966 coast of Petite Terre, and (e) Koungou. The bold black line is the Histolitt coastline from SHOM. The colored 967 lines and dashed lines represent the travel times of the tsunami in minutes.

Figure 10: Sensitivity tests performed on the Piton 200 scenario with varying Manning coefficient *n*, friction angles δ_i , water landslide friction m_f , value of the typical grain diameter *L*, and version of HySEA (parameters can be found in table 4). (a) deposit extension for each sensitivity test and locations of the gauges, (b) sea-surface elevation at gauge 1, (c) sea-surface elevation at gauge 2. The reference simulation is the thick black curve.

Table 1: Characteristics of the eight scenarios (volume, bathymetry) and parameters (friction angles and coupling time) used for the numerical simulations.

Table 2: Times of arrival of the first tsunami wave at the gauges placed around Mayotte for each simulated
scenario (locations of the gauges in Figure 1).

Table 3: Parameters used to represent the intensity of the flooding, as defined in the French coastal risk
 prevention plan guide (MEDDE, 2014).

Table 4: Parameters involved in the sensitivity tests performed by varying the landslide volume V, the friction law and associated friction angles δ_i , the Manning coefficient n, the typical grain diameter L in the Pouliquen $(\mu(I))$ flow law, friction between the avalanche and water layer m_f , and version of the model (hydro and nonhydro).

















Figure 7









Figure 10

10	09
100	J9

Type of source	Name of the scenario	Volume (10 ⁶ m ³)	Bathymetry shallower/deeper (m)	Pouliquen friction angle (°)		Coupling Time (s)	Scenario with comparable volume and placement (Lemoine et al. 2020b)	
				δ_1	δ_2	δ_3		
Active Volcano	New Volcano	260	-2600/-3150	6	16	8	26	Sce_47
Bottom of the slope	3 Lobes	800	-850/-1350	6	16	8	28	Sce_35
East reef	Piton 200	200	-50/-600	7	17	9	35	Sce_48
	Piton 100	100	-50/-500	7	17	9	30	Sce_36
	North Slope	11.25	-50/-250	10	20	12	28	Sce_53
Bottom of East reef	South Slope	290	-400/-1000	6	16	8	30	Sce_42
West reef	West Canyon 69 -30/-300		-30/-300	8	18	10	20	Sce_40
	West Slope	19	-30/-300	9	19	11	23	Sce_39

1010 Table 1

Scenario	Airport	Dzaoudzi	Koungou	Mamoudzou	Bandrélé
Piton 200	3'55"	8'35''	11'35"	8'25''	8'35"
Piton 100	2'50"	9'30"	12'30"	11'30"	10'30"
3 Lobes	3'48"	12'28"	13'48"	14'08"	6'08"
New Volcano	6'46"	14'56"	17'46"	18'16"	11'26"
North Slope	rth Slope 4'28"		9'28"	12'28"	15'28"
South Slope	South Slope 5'30"		15'30"	13'50"	7'10"
Scenario	Acoua	Chembényoumba	Sada	Chirongui	Kani-Kéli
West Canyon	7'10"	9'	10'50"	20'10"	20'40"
West Slope	est Slope 6'13"		10'43"	19'03"	20'53"
Table2					

1011 T

1012

Water height (m)	Submersion dynamics: velocities						
	0m/s < V < 0.2m/s	$0.2m/s \leq V < 0.5m/s$	Fast: $V \ge 0.5 m/s$				
H < 0.5m	Low	Medium	High				
$0.5m \le H \le 1$	Medium	Medium	High				
$H \ge 1m$	High	High	Very High				
Table 3							

1013

1014

N° of the simulation	Name	Volume (10 ⁶ m ³)	Friction law	Friction angle (°)			<i>L</i> in m Pouliquen law	$\frac{\text{Manning}}{n \text{ (m}^{-1/3} \text{ s)}}$	Water- landslide friction m_f (m ⁻¹)	Version of HySEA
				δ_1	δ2	δ3				
1	Reference	200	Pouliquen	7	17	9	1	0.025	0	Hydro
2	Poul_13_23_15	200	Pouliquen	13	23	15	1	0.025	0	Hydro
3	$m_{f} 10^{-5}$	200	Pouliquen	7	17	9	1	0.025	0.00001	Hydro
4	$m_{f} _{10^{-4}}$	200	Pouliquen	7	17	9	1	0.025	0.0001	Hydro
5	<i>n</i> _0	200	Pouliquen	7	17	9	1	0	0	Hydro
6	<i>n</i> _0.05	200	Pouliquen	7	17	9	1	0.05	0	Hydro
7	Coul_13	200	Coulomb	13				0.025	0	Hydro
8	Coul_7	200	Coulomb	7				0.025	0	Hydro
9	L_0.1	200	Pouliquen	7	17	9	0.1	0.025	0	Hydro
10	NonHydro	200	Pouliquen	7	17	9	1	0.025	0	Non Hydro
11	V_100.10 ⁶	100	Pouliquen	7	17	9	1	0.025	0	Hydro
12	$V_{50.10^6}$	50	Pouliquen	8	18	10	1	0.025	0	Hydro

1015 Table 4

1018 Supplementary Material

1017

1021Figure A.1: Locations of landslide scenarios from Lemoine et al., 2020b (red dots) and from this study (blue1022stars).

Figure A.2: a) South Slope scenario (resolution: 50 m): wave propagation from 30 seconds to 15 minutes after the landslide. The color scale represents the elevation of the calculated sea surface at a given time. The green dots on the maps correspond to the emplacement of the gauges. b-d) Evolution of the elevation of the sea surface at different gauges (NEPT, EA, ND, SD, WA, voK, EM, EB). The locations of the gauges are indicated in Figure 1 and figure A-2a.

Figure A.3: a) West Canyon scenario (resolution: 50 m): wave propagation from less than 20 seconds to 20 minutes after the landslide. The color scale represents the elevation of the calculated sea surface at a given time. The green dots on the maps indicate the locations of the gauges. b-d) Evolution of the elevation of the sea surface at different gauges (Ac, Che, Sa, Chi, KaK). The locations of the gauges are indicated in Figure 1 and Figure A-3a.

1035

Figure A.4: Maximum water depths (MWD) with 10 m resolution for the South Slope scenario. The color
scale represents the value of MWD calculated for each point: (a) Dzaoudzi and route N4, (b) Airport and
Pamandzi, (c) Mamoudzou, (d) northeast coast of Petite Terre, and (e) Koungou. The bold black line is the
Histolitt coastline from SHOM.

Figure A.5: Maximum water velocities in m/s with 10 m resolution for the South Slope scenario. The color
scale represents the value of the maximum water velocity calculated for each point: (a) Dzaoudzi and route
N4, (b) Airport and Pamandzi, (c) Mamoudzou, (d) northeast coast of Petite Terre, and (e) Koungou. The bold
black line is the Histolitt coastline from SHOM.

1045

Figure A.6: Sensitivity tests performed on the Piton scenario with varying volume (parameters can be found in table A1). (a) deposit extension for each sensitivity test and locations of the gauges, (b) sea-surface elevation at gauge 1, (c) sea-surface elevation at gauge 2. The reference simulation is in the thick black curve



1050 Figure A1:











Figure A5

