



HAL
open science

High repetition rate laser-induced printing of biopolymers: time-resolved study of multiple jet dynamics

Lucas Duvert, Adrien Casanova, Jérôme Robin-Ducellier, Frédérique Magdinier, Anne Patricia Alloncle

► To cite this version:

Lucas Duvert, Adrien Casanova, Jérôme Robin-Ducellier, Frédérique Magdinier, Anne Patricia Alloncle. High repetition rate laser-induced printing of biopolymers: time-resolved study of multiple jet dynamics. E-MRS spring Meeting, Symposium Q, May 2022, virtual conference, France. hal-03842335

HAL Id: hal-03842335

<https://hal.science/hal-03842335>

Submitted on 18 Jan 2023


HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Motivation

- Development of pluripotent induced stem cells
- Creation of *in vitro* biological models
- Creation of complex cell arrangements with bioprinting
- Use of Laser Induced Forward Transfer (LIFT) for precise cell deposition

Regenerative medicine
 Pharmaceutical testing
 Pathology studies



Advantages of LIFT

- Nozzleless system
- Large range of fluid viscosity
- High printing resolution
- High spatial resolution

Objective of the study :

From High velocity → High mechanical stress
 To Slow velocity → Reduced mechanical stress

Increased cell viability and recovery

Single jet dynamic

Jet height as a function of gel thickness

(Time normalized to maximum reached) Alginate 3% + Glycerol 10% 277mJ/cm²

Layer thickness → Maximum jet height

Evolution of the jet height as a function of time after the laser impact

Alginate 2% + Glycérol 10%

Pulse energy → Maximum jet height

Evolution of the jet height as a function of time after the laser impact

Alginate 3% + Glycerol 10% 277mJ/cm²

Viscosity → Reproducibility Stability

From high-speed impact to a soft deposition While keeping a very high spatial resolution

Characterisation of the ejection dynamic

Why is real time visualisation important ?

Characteristics of jets depending on:

- Viscosity of the bioink
- Energy of the laser pulses
- Thickness of the gel layer deposited on the donor

Jet height depending on time

Maximum height reach by the jet

Set up for capturing the dynamics

- Camera coupled with nanosecond flash
- Pictures with high temporal resolution
- Artificial reconstruction of one dynamic with series of individual delayed jet pictures

Multi-jets dynamics

Spacing dependence

Distance between each laser shot

Time dependence

- Viscosity → Modify dynamic duration
- Laser energy → Modify dynamic duration

Enough delay for single jet mechanism

Compromise: Fast printing → Larger spacing → More printing possibilities

Conclusion

Deposition of hydrogel lines containing cells

- Process optimization
- Next: characterization survival with optimal velocity