

Representing Diet in a Tree-Based Format for Interactive and Exploratory Assessment of Dietary Intake Data

Nicole Litwin, Kalen Cantrell, Aurelie Cotillard, Muriel Derrien, Abigail Johnson, Rob Knight, Franck Lejzerowicz, Daniel Mcdonald, Brent Nowinski, Se Jin Song, et al.

▶ To cite this version:

Nicole Litwin, Kalen Cantrell, Aurelie Cotillard, Muriel Derrien, Abigail Johnson, et al.. Representing Diet in a Tree-Based Format for Interactive and Exploratory Assessment of Dietary Intake Data. Current Developments in Nutrition, 2022, 6 (Supplement_1), pp.774-774. 10.1093/cdn/nzac063.016. hal-03842852

HAL Id: hal-03842852 https://hal.science/hal-03842852v1

Submitted on 24 Sep 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Representing Diet in a Tree-Based Format for Interactive and Exploratory Assessment of Dietary Intake Data

Nicole Litwin,¹ Kalen Cantrell,¹ Aurelie Cotillard,² Muriel Derrien,² Abigail Johnson,³ Rob Knight,¹ Franck Lejzerowicz,¹ Daniel McDonald,⁴ Brent Nowinski,¹ Se Jin Song,¹ Julien Tap,² and Patrick Veiga²

¹Center for Microbiome Innovation, University of California, San Diego; ²Danone Nutricia Research; ³University of Minnesota; and ⁴University of California San Diego

Objectives: We assessed the utility of representing dietary intake data in hierarchical tree structures that consider relationships among foods.

Methods: Dietary intake was collected from 1909 adults (≥18 years) using a food frequency questionnaire (FFQ; VioScreen) from the American Gut Project. FFQ food items were formatted into hierarchical tree structures based on 1) USDA's Food Nutrient and Database for Dietary Studies (FNDDS) classifications, 2) nutrient content, and 3) molecular compound information detected via mass spectrometry to capture the non-nutrient composition of foods. Next, we compared how well representing dissimilarities (or distances)

between individuals based on their diet corresponded with indices such as the Healthy Eating Index (HEI-2015), when those distances are calculated using tree-based versus non-tree-based metrics. We performed an Adonis test (PERMANOVA) to measure the amount of variation explained (R²) in these diet-based distances by HEI-2015.

Results: We observed that dietary ordinations generated using tree-based relationships between foods have better agreement with HEI than ordinations generated without considering relatedness between foods. The variation explained by HEI-2015 increased by 35% when using the FNDDS tree compared to using a non-tree based quantitative metric (Bray-Curtis (not tree-based) $R^2 = 0.02931$ vs. Weighted UniFrac (tree-based) $R^2 = 0.03969$), by >20% when using the nutrient tree (vs. Weighted UniFrac $R^2 = 0.03627$), and only marginally (6%) when using the molecular compound tree (vs. Weighted UniFrac $R^2 = 0.03116$).

Conclusions: We show that tree-based measurements of dietary similarity lead to better agreement with diet indices (e.g., HEI) than when relationships among foods are not considered. We also show that representing dietary intake in a tree-like structure can offer interactive visualizations of data that can be used to inform hypotheses regarding dietary characteristics.

Funding Sources: Danone Nutricia Research.