This paper is part of a special issue on Education in Acoustics.

NoiseCapture smartphone application as pedagogical support for education and public awareness

Gwenaël Guillaume,¹ Pierre Aumond,² Erwan Bocher,³ Arnaud Can,² David Écotière,¹ Nicolas Fortin,² Cédric Foy,¹ Benoit Gauvreau,² Gwendall Petit,³ and Judicaël Picaut²

¹ UMRAE, CEREMA, Université Gustave Eiffel, IFSTTAR, F-67035 Strasbourg,

France^a

² UMRAE, Université Gustave Eiffel, IFSTTAR, CEREMA, F-44344 Bouguenais,

France

FUNKAE, Universite Gustave Eiffel, IFSTTAR, CEREMA, F-44344 Bouguenais,

³CNRS, Lab-STICC (UMR 6285), 56017 Vannes, France

(Dated: 8 April 2022)

Teaching science subjects such as acoustics to the youth or general public audiences can be facilitated by illustrating physical phenomena or scientific issues through fun experiences. A few years ago, our team developed a smartphone application named NoiseCapture with the aim of offering to anyone the opportunity to measure their sound environment and to share their geolocated measurements with the community in order to build a collective noise map. Since, the NoiseCapture team members experimented numerous interventions in schools or scientific events for the general public based on the app for explaining not only societal and environmental issues related to noise but also for teaching acoustic notions and for addressing technical and scientific topics associated with sound measurement. The paper describes some of them implemented in particular in school context through training courses given to middle school and university students, as well as teachers of secondary school, that focused on basic knowledge in buildings and environmental acoustics, on the practice of acoustic measurement and on noise mapping. Some examples of interventions with the general public are also presented that were mostly integrated into scientific events.

10

11

12

13

14

15

16

^agwenael.guillaume@cerema.fr

17 I. INTRODUCTION

The hardware and software developments of smartphones over the last decade and their wide distribution in the population have motivated several participatory projects related to 19 the acoustic measurement by smartphones with the objective of proposing an alternative 20 approach to simulation-based noise mapping (D'Hondt et al., 2013; Maisonneuve et al.; Picaut et al., 2019; Zuo et al., 2016) or more precisely offering additional information on the perception of soundscapes (Li et al., 2018; Radicchi et al., 2018). The Directive 2002/49/EC thus afford the possibility of producing noise maps from measurements, which was not possible until now due to the large number of measurement points required. Despite the lower quality of the acoustic measurements compared to those of dedicated professional equipment, these research works have shown the relevance of such an approach (Aumond et al., 2017; Ventura et al., 2017) which also allows users to have feedback on their own sound environment and contribute to a civic and scientific approach. The NoiseCapture project was thus initially implemented in the context of the environmental noise assessment within the meaning of Directive 2002/49/EC with the aim of building a collaborative noise map from measurements by any user of geolocalized noise indicators by offering them in return information about their own sound environment (Picaut et al., 2019). The NoiseCapture application was diverted from this latter as a support of education to secondary-school pupils, high school and university students, and teachers, but also for the wider public of citizens. The NoiseCapture application is part of a more global project, called Noise-Planet (Noise-Planet.org), which proposes tools combining acoustics and geographic information

- science approaches for environmental noise assessment. The Noise-Planet project is led by
 the Environmental Acoustics Research Unit (UMRAE¹) and the Laboratory of Sciences and
 Techniques of Information, Communication and Knowledge (Lab-STICC²), associated with
 other partners from the academic world and professional acoustic community.
- Such use of mobile devices equipped with sound measurement applications with the aim of 42 introducing some basis on acoustics was already undertaken and published by some authors. Kawahara et al. (2019) experimented an innovative approach to broach sound perception with primary school pupils by inviting them to collect sounds thanks to a tablet computer and to discuss together their perception of these sounds through a quiz based on recognition of the origin of the recorded sounds. Satoh et al. (2016) and Sakagami et al. (2013; 2019a; 2019b) used smart mobile devices to teach about environmental and architectural acoustics. In their work, the authors compared A-weighted sound levels measured by a few applications installed on different iOS devices and a Class 1 sound level meter, before investing university students in the creation of sound maps based on measurements carried out with the smartphone application. Elejalde-García and Macho-Stadler (2019) also experimented to employ a smartphone application to learn concepts concerning indoor acoustics to high school and undergraduate students. They highlight that acoustic education may be a valuable way to prevent from noisy individual behaviours and thus to improve the acoustic comfort in the classroom since the pupils themselves seem to be the main noise source in primary school classroom according to Dockrell and Shield (2004). The use of mobile devices applications for educational activities concerning indoor acoustics to pupils of primary and secondary schools is also discussed by Sakagami et al. (2019b). The authors conclude their

paper by mentioning that smartphones applications, "Hush City or Noise Capture, will be in demand for educational purposes" in order to integrate perceptual information. Indeed, the two latter applications provide a useful participatory sensing framework dedicated to two complementary objectives: the Hush City application is mainly devoted to identify and evaluate quiet areas in cities (Radicchi, 2019) while, as already explained above, the Noise-Capture application aims at building a participatory noise map. Both applications rest upon a methodology that combines a citizen sensing approach and a feedback to the community, which allows to involve the users in the assessment of their sound environment as well as to raise them awareness of the importance to preserve quiet areas and to make quieter cities (Suarez and Arenas, 2018).

The present paper precisely details the use of the NoiseCapture application with various groups of participants from school children to teachers and the general public. The
educational interventions were implemented in the form of specific events of collaborative
production of noise maps (NoiseCapture Party) with the objective of raising awareness of
the problematic of noise environments, or by using the NoiseCapture application as a pocket
sound level meter for various problems of acoustic measurement. The first section describes
the measurement and data extraction processes. Then, the second section presents the use
of these data in different contexts in school, teacher training and general public contexts.
Finally, the third section discusses the teaching opportunities related to the use of Noise-

80 II. NOISECAPTURE MEASUREMENTS AND COLLECTED DATA EXTRAC-

A. NoiseCapture measurement and calibration

TION

82

A measurement with the NoiseCapture application takes place in three steps. The first 83 step consists in starting the simultaneous measurement of acoustic indicators (such as the one-second third octave band equivalent sound levels $(L_{Aeq,1s})$ and GPS location, during 85 which the real-time evolution of sound sound level is displayed in the form of a classical spectrum or spectrogram, or else as a map of measurements. The second step, that begins when the measurement is stopped, allows the user to provide optional information such as 88 a short description of the sound environment, tags describing the measurement conditions, pleasantness and sound sources present, or eventually a party code if the measurement falls within the framework of a NoiseCapture Party event³. The third and last step allows to view and explore the measurements through different noise indicators (e.g. equivalent sound levels, spectrum, percentile values) or overlaid on the community map. A help menu in the application also gives various information on the use of the application as well as basic notions in acoustics to carry out and interpret the measurements.

Like most measurement devices, the NoiseCapture application must be calibrated, according to the selected smartphone, in order to produce expected results. In the NoiseCapture application, it is necessary to define a specific gain to correct the acoustic measurement that can be obtained by using a manual or automatic calibration protocol, and is stored in the Settings of the application. Two manual calibration procedure are available which

consist either in correcting the sound level obtained by the application by comparison with a simultaneous measurement with a professional sonometer, or in using an acoustic calibrator if an external microphone is connected to the smartphone. Alternatively, NoiseCapture also proposes two automatic calibration procedures based on a comparison either with an already calibrated smartphone used as a reference through a communication protocol between the reference smartphone and the smartphones to be calibrated by using the internal generation of pink noise or on the basis of background noise, or with expected noise levels provided by a numerical model by performing vehicle passage noise measurements close to a few road sections with constant speed driving conditions (Aumond et al., 2020).

B. Data reading and extraction

110

Data collected from NoiseCapture can be exploited in different ways. The most common 111 need for users is to visualize measurements in the application. The data can be directly read 112 in the NoiseCapture application during or at the end of the measurement or a posteriori 113 in the measurement history. This latter alternative also allows to extract data from the 114 NoiseCapture application by selecting the expected measurements in the list and exporting 115 them in a .zip file that will contain three files: the metadata of the measurement (i.e. the 116 date and time of the measurement, the device manufacturer, the mean equivalent sound 117 level or the gain of calibration), a descriptive text with information about the exported data 118 and the measurement track with information on the geolocation accuracy or else the third 119 octave band sound pressure levels.

The NoiseCapture application allows the user to share its measurements by uploading 121 them to the NoiseCapture remote server in order to be used for producing noise maps, but 122 also to be shared again with the community. All the data uploaded by users to the database 123 fully respects the privacy of users as no personal data is collected, a unique identifier being 124 only created at the installation of the application and provided with user data which allows 125 to associate different measurements to the same application installation. The data from the remote server can be used in four different ways. Firstly, raw data shared by contributors 127 can be uploaded in the form of .geojson files, this approach being mainly address to the 128 scientific community⁵. Secondly, pre-processed daily data are also available from the web 129 page https://data.noise-planet.org/noisecapture/ as .geojson files distributed un-130 der open license (ODbL, see for more details) and organized as .zip files by country (Bocher 131 et al., 2017). Each archive contains three files by administrative region that correspond to 132 data collected along a track (file .tracks.geojson), post-processed data aggregated in 133 hexagons of 15 m radius (file .areas.geojson) and one-second measurement points data 134 (file .points.geojson). Thirdly, a 3-years extraction of the NoiseCapture database is also 135 freely available for download and use, according to the OdBL license, as a relational Post-GIS database (Picaut et al., 2021a,b). Finally, the data processed by means of the OnoMap 137 Spatial Data Infrastructure (SDI), that is also based on free and open source tools compliant 138 with OGC standards (Bocher et al., 2016), are also available in the form of Web Map Service (WMS) layers with the L_{A50} and L_{Aeq} levels inside the hexagonal cells (noisecapture_area 140 and noisecapture_area_laeg respectively), as well as all the measurement point locations provided by the entire community (noisecapture_leaflet_point) or within the framework
of a NoiseCapture Party (noisecapture_points_party).

44 III. USE OF NOISECAPTURE FOR PEDAGOGICAL EVENTS

The ease-of-use of the NoiseCapture application allows to address a diverse audience that includes both youths and adults. Its use as a pedagogical material was investigated through some interventions in different contexts from school environment to the general public as well as teacher training.

A. In school environment

149

153

NoiseCapture can allow to improve the student investment in pedagogical activities by offering a playful way for both teaching basis on acoustics and doing prevention concerning the health and environmental risks associated with noise.

1. "Immersion Science" event (secondary/high school)

One of the first interventions in school environment based on NoiseCapture took place
within the framework of the "Immersion Science" (IMS) event. This annual operation jointly
carried out since 2011 by the region of Brittany (France), the academy of Rennes in charge
of education in the region and the French National Centre for Scientific Research (CNRS),
aims at immersing high school students into the world of Science to foster their course guidance toward scientific disciplines. Renewed each year in the nautical centre of the Île-Tudy

peninsula (France), students attend during a week around twenty workshops and confer-160 ences that are held by researchers who showcase their scientific activities. The proposed 161 interventions involving NoiseCapture were undertaken in 2018 and 2019, and consisted in a short presentation of acoustics basics and research activities related to environmental noise 163 assessment followed by a NoiseCapture party with the students accompanied by their teach-164 ers. The measurement workshop lasted for about two hours and was established by dividing the covered area into 5 sub-zones, each of these latter being allocated to one or more student 166 pairs equipped with Android smartphones with the pre-installed NoiseCapture application. 167 Smartphones were first calibrated by using the automated process based on an already cali-168 brated smartphone as mentioned in Sec. II A (figure 1), then student pairs roamed their areas 169 while performing measurements for around one hour. The 2018 and 2019 sessions gathered 170 13 and 23 contributors respectively, who shared 45 itinerant measurements the first year 171 and 192 the second year for respective total durations of 4h38mn and 4h48mn. The maps 172 generated from those two sessions are given at Figure 1. One can note the windy conditions 173 that significantly impacted the first session measurements (i.e. higher sound levels). An 174 online map that aggregates the two-year sessions and participant tracks is available here: 175 http://noise-planet.org/map_noisecapture/index.html#17/47.84239/-4.16735/. 176

2. "Research Passport in Pays de la Loire" event (secondary/high school)

177

A second intervention was carried out in 2018 and 2019 as part of the operation named "Research Passport in Pays de la Loire" led by the Regional Educational Pact of the Pays de la Loire Region (France) and supported by the educational academy of Nantes. This opera-




FIG. 1. (color online) NoiseCapture parties organized within the framework of the Immersion Science events: (top) calibration of the smartphones, sound maps produced in (bottom left) 2018 and (bottom right) 2019.

tion was addressed to young high school students and aimed at allowing them to discover the research community and laboratories in the region through meetings with researchers or a 182 visit of a laboratory. Students enhanced their analytical skills related to scientific and techni-183 cal topics and have the opportunity to convey their learning by elaborating a communication 184 support on a specific issue proposed by the researchers. The project ongoing throughout the 185 school year allowed numerous exchanges with scientists with a visit of their laboratory and school's interventions of researchers. A day of restitution was finally organized at the end of 187 the school year during which classes or ally presented their project in a lecture hall, as well 188 as in the form of workshops and demonstrations. This project undertaken by the college 189 students of the high school of the City of Bouaye (France) in partnership with researchers 190 of the UMRAE over the period from October 2018 until May 2019 (2 hours per week) dealt 191 with the issue of "calibrating sonometric applications for smartphones for the in situ mea-192 surement of sound environments" what is of major concern as it raises numerous scientific 193 and technical issues concerning, for example, the methodology or metrology (Celestina et al., 194 2018; Garg et al., 2019; Guillaume et al., 2016). In addition, the concepts discussed in class-195 room and in workshops with the college students fit in well with the curriculum taught in 196 1st year of "Laboratory Science and Technology". Each stage of the project led to inter-197 esting and fruitful discussions from the implementation of the experimental protocol and 198 the formation of student groups for in situ measurements through a NoiseCapture Party to the processing and analysis of the collected data (figure 2). A technical report was finally 200 written by students that explains both the Research Passport operation and the scientific 201 results of the project⁶. Besides, during the project, the students had the opportunity to visit



FIG. 2. (color online) Experimental campaign carried out within the framework of the Research Passport operation: (left) location of measurement points, (top right) resulting map and (bottom right) comparison of smartphone measurements with sonometer results.

the UMRAE outstanding facilities such as the semi-anechoic room. It is interesting to note
that it was through this intervention that the idea of developing an alternative calibration
method came about, which then led to a specific research work and the publication of the
article by Aumond et al. (2020), who are UMRAE researchers involved with the students.

3. 'A week outside the classroom" event (University student)

207

A third intervention was undertaken under the program "A week outside the classroom"
proposed to first-year students in their curriculum at the Faculty of Geography of the University of Nantes. The operation aims at allowing students to develop their knowledge and skill on a field and an object of study, to gain more independence and to comprehend ge-

ographer work. The 2019 and 2020 sessions focused on the investigation of the soundscapes 212 of the city of Nantes (France) and gathered around 120 students each year divided into 213 groups of five who could attend half-day workshops allowing them to get more familiar with acoustic notions from both physical and perceptive points of view, to grasp the concepts 215 behind the approaches of the participatory measurement and perceptual data collection, and 216 to orally report as a team their work at the conclusion of the week. In this way, physical and subjective data were collected by groups of students for 20 listening points per group, which 218 approximately represents 650 listening points for the two years (figure 3). The listening 219 points were chosen as being representative of various sound environments over the pedes-220 trian and road network and consisted in practice in 3-minute measurements of the L_{Aeq} and 221 L_{A90} indicators at the same time as one to five students completed a perceptual question-222 naire on the sound environment. Both physical and subjective collected data were finally 223 compared and discussed by the students in addition to a geospatial analysis of the sound 224 data aggregated during the NoiseCapture Party which was presented in the closing day of 225 the week, what enabled to highlight the collective benefit of the collaborative approach. 226

4. Noise health and learning awareness school project (middle school)

227

These last three interventions fit well within the scope of application planned for NoiseCapture, namely proposing a participatory and freely accessible tool dedicated to any user
for outdoor acoustic measurements. Indeed, the GPS position is required to be able to relate sound measurements with geographical locations, what can not be reached yet indoor.
The following operation overcame this issue by implementing an adapted protocol to allow




FIG. 3. (color online) Listening points investigated within the framework of the program "A week outside the classroom": (left) amount of data at listening points; (right) sample of the measurement results.

the creation of noise maps indoor. This latter was undertaken in 2018 at the Gutenberg 233 technical middle school (Illkirch-Graffenstaden, France) as part of a project of awareness 234 concerning noise-related risks on health and learning. The training courses of the establish-235 ment on digital systems, multimedia visual communication, graphic and printed productions 236 were involved in the project, which was structured around four components: the collection 237 of general information concerning noise, the study of the noise sources in the school, the 238 information on health and learning effects of noise, and the implementation of an awareness 239 campaign and actions in the school. The project started with the creation and analysis of an online questionnaire directed at the students and teachers what enables to gather their 241 perception of noise in school and more specifically to locate the major "noise black-spots" 242 among which the printing facilities workplace was highlighted. The intervention proposed by the UMRAE team took place in two stages: a short lecture on some generalities in acoustics

from basic physical phenomena and indicators to the noise measurement and its effects on health and learning, and a collaborative experimental campaign aiming at establishing a 246 noise map of the workshop of printing facilities from a series of measurements performed by the students with their personal smartphones. Before this operation, students prepared 248 markings on the floor, which was facilitated by the presence of floor tiles, in such a way 249 as to create a grid of one-meter apart measurement points, each assigned of an index that consists of a letter representing one Cartesian direction and a number for the other direction 251 on a horizontal plane (figure 4). The collective measurement campaign was preceded by the 252 calibration of all smartphones by using the manual process of the NoiseCapture application 253 with a professional sonometer (see section IIA). Then, the measurement campaign was car-254 ried out and organized by grouping schoolchildren by pair with one smartphone and a sheet 255 of paper on which they reported the collected data at each point. Each pair of schoolchildren 256 divided up alternately the roles: one performed the measurement above a marking, while 257 the other wrote up the equivalent sound pressure level $L_{Aeq,10s}$ into a table with the related 258 marking index. The pairs of schoolchildren went all over the workspace until its full coverage 259 by the entire class. This operation was carried out twice under two distinct conditions of 260 printing machine load: an extreme situation for which all machines were operating and an 261 ordinary working case for which only few printing facilities were running (figure 4). 262

In addition to these actions, schoolchildren also created awareness-raising materials in the
form of videos, leaflets and posters. The general school project entitled "Noise and us" ("Le
bruit et nous" in french) was submitted to compete in the "CGénial" competition organised
every year by the Foundation "CGénial" and the french Ministry of National Education




FIG. 4. (color online) Grid of measurement points implemented (left) over the printing facilities workshop (right) with related indexing (the origin index appears in red online).

through the program "Sciences at School". This scientific contest aims at promoting sciences and is addressed to secondary-school and College students who have to carry out an innovative project through a multidisciplinary team approach combining different scientific subjects such as life and earth sciences, technology, physics, chemistry or mathematics. The project was selected for the final of the "CGénial" competition based on a written report of tasks undertaken as part of the project. The event took place at the "Cité de l'Espace" in Toulouse on 25 May 2018 during which a trio of schoolchildren accompanied by their teacher received the "CGénial" diploma.




FIG. 5. Noise maps of the printing facilities workspace for (left) the extreme case for which all printing machines in operation and (right) in current use.

5. Pedagogical toolkit for teachers

275

Following the last successful event, a pedagogical toolkit (available here https://

www.umrae.fr/en/productions/software-apps-and-computing-methods/ and named

"CARTO_ACOUSTIQUE_INTERIEURE") was implemented to allow any teacher to manage similar actions with students. It consists of a slideshow concerning basics in acoustic

focusing both on the health and societal impacts of noise and the good practices for acoustic

measurement, and of a software with a graphical user interface. The software allows to

build the grid of indexed points based on a spreadsheet file that contains the coordinates of

the room corners with a user-adjustable resolution and to build the noise map in the form



FIG. 6. (color online) Graphical user interface (in french) of the pedagogical toolkit to build a noise map from indoor measurements over a grid of points.

of coloured measurement dots, interpolated data and isosurfaces as interactive .html files (figure 6).

This educational kit was tested in a similar project undertaken in collaboration with a classroom of cabinet-making students of the Duguesclin Arts High School ("Lycée des métiers d'art Duguesclin"), on the initiative of their physics-chemistry teacher. The short lecture was provided by a non-acoustician member of the Noise-Planet team. The mea-

- surement campaign focused on a woodworking workshop (figure 7, left) that includes fifteen
 wood-working machines and a ventilation system. As previously, students were organised in
 pairs who achieved equivalent sound levels measurements of 5-second duration owing to the
 stationarity of the noise sources and the practical session consisted in three stages:
- first, students materialized the 437 measurement points using stretched ropes with falling ropes tied every 1 m (figure 7, right), what took about 4 hours;
- then, the student's smartphones were calibrated thanks to the automated process
 based on an already calibrated smartphone;
- finally, three series of measurement were carried out in around one hour and a half with
 alternatively only the ventilation system in operation (figure 8, top), wood-working
 machines switched on (figure 8, center) and machines chopping wood (figure 8, bottom).
- Student pairs rewrote their measurements into spreadsheet files that allow to build the three noise maps presented at figure 8.

B. Teacher training context

The "Houses for science" ("Maison pour la science" in french⁸ is a project launched in 2012 at the initiative of the Academy of Sciences with the financial support of the program "Investments for the future" (Investissements d'Avenir in french) that aims at proposing professional development courses to teachers from the primary to secondary levels. The "Houses for science" network includes eleven "Houses for Science" under the coordination of





FIG. 7. (color online) Pictures (left) of the woodworking workspace and (right) of the marking method.

the Foundation "La main à la pâte" (what can be translated into "Get involved"). Teachers
can thus subscribe to training programs addressing different scientific and technical topics
in order to help advancing their education practices through an interdisciplinary approach
of inquiry-based learning.

The UMRAE team proposed a training module that was part of a program entitled "On my signal, sound at will!" ("À mon signal, son à volonté!" in french) in which physical aspects concerning indoor and outdoor acoustic phenomena were addressed both in the form of short lectures and practical implementations. The module was divided into two sessions that focused alternately on building and environmental acoustics (the last one is not detailed in this paper).

Concerning building acoustics, the notions of stationary phenomena and modal sound fields in rooms as well as wall acoustic absorption and transmission were approached with




FIG. 8. (color online) Noise maps of the woodworking workspace for the three series of measurement: (top) with only the ventilation system in operation, (center) woodworking machines in no load operation and (bottom) chopping wood.

practical examples by using room scale models and therefore adapting the frequency range of the experiment.

324

The following well-known acoustic phenomena were then highlighted: stationary phenom-

ena in rooms, acoustic absorption by walls and acoustic transmission through walls. The 325 presence of eigenmodes in rooms was demonstrated by emitting a sine wave successively 326 adjusted to some eigenfrequencies of the scale model with the help of a smartphone sound 327 generator positioned in a room corner, and by simultaneously measuring the sound pressure 328 level at different places of the room scale model with the NoiseCapture application as a sound level meter. The longitudinal and transverse modes of the room were observed as the 330 sound level is reinforced and reduced in the regions of the nodes and antinodes respectively. 331 Then, acoustic absorption by walls was highlighted by, first, measuring the sound level in 332 the scale model without absorbent material and, then, successively repeating the experiment 333 with one, two, three or four absorbent layers on the surrounding walls. This experimentation 334 enables to estimate the acoustic gain provided by the addition of absorbent systems. Finally, 335 the acoustic transmission phenomena, and more particularly the mass-frequency law related to the acoustic insulation to airborne, was studied by inserting a wall into the scale model in 337 such a way as to create two rooms. The first experiment consisted in repeating twice a mea-338 surement at a single frequency and in varying the density of the separating wall successively by introducing a balsa slab then a plasterboard, what enables to highlight the improvement 340 in acoustic insulation when increasing the wall density. The second experiment, for a given 341 wall, aimed at illustrating the increase of the acoustic insulation when the frequency of the 342 signal increases. This experimentation was performed using a smartphone as a sound source generator positioned in one of the rooms, while another smartphone alternately measured with NoiseCapture the sound level $L_{\rm E}$ in the emission room and $L_{\rm R}$ in the reception one, then estimating the acoustic transmission loss through the panel ${\rm TL}=L_{\rm E}-L_{\rm R}$.

Lastly, the effect of a doubling up of the wall with a second panel was analyzed in comparison to a single panel of equivalent density. This latter experiment allowed to illustrate
the mass-spring-mass system principle and to demonstrate the gain in sound insulation with
the double partition wall. For this experimentation, a similar protocol as the previous one
with two smartphones (an emitter and a receiver) was implemented.

C. In a general public context

352

The NoiseCapture application stand for attractive and interactive tools that enable to 353 organize participatory workshops and to bring people together around the environmental noise issue. An event was organized by the agglomeration of Bastia (Corsica, France -355 60,000 inhabitants) that illustrates the benefit of using these media to involve people in an 356 urban development project. The city desired to implement a public awareness approach in collaboration with its city dwellers before the implementation of noise reduction actions. 358 A NoiseCapture Party was set up within the framework of this project in October 2018 350 with some members of the NoiseCapture team. This event was organized with high school students and the general public, in two stages: a first intervention in the afternoon that 361 involved two classrooms of 9^{th} grade students (i.e. approximately 40 students) accompanied by four teachers, and a meeting time, in the late afternoon, opened to the public. In 363 both cases, a presentation was made by the NoiseCapture team members who addressed

the noise pollution issues and the general approach behind the NoiseCapture ecosystem. Then, the team helped participants to calibrate their smartphones and finally accompanied 366 them in using the smartphone application and contributing to the party by carrying out measurements in good conditions. Besides, a two-week extension was set up to allow the 368 participants to keep contributing to the noise map after the event. In total, 19 contributors 369 uploaded 16 hours and 37 minutes of measurements (507 measures) with more than 50,000 points over these two weeks, as illustrated at figure 99. A restitution in the form of closing 371 plenary brought together the participants, local elected representatives and journalists, that 372 was subsequently used as a means of public communication and awareness raising to the 373 inhabitants and was the subject of various press articles. 374

Following the same example, numerous other NoiseCapture Parties were implemented as for example within the framework of the "Festival of Science" in 2018 in Nantes¹⁰ and Strasbourg¹¹. Since 2017, half of the 26 NoiseCapture Parties co-organized by the members of the team in 4 countries (France, Spain, Italy, Ecuador) dealt with education. Some of these parties are repeated each year as the teachers who co-organized the event have incorporated it in their education program (e.g. Immersion Science, Universidade da Coruña, ...), with rich exchanges with the NoiseCapture team.

382 IV. DISCUSSION

Android devices are nowadays very widespread in the general public, which makes it possible to have a large number of people, whether young or adult, equipped with an acoustic sensor and thus facilitate the setting up of experiments. Their use as training materials allows




FIG. 9. (color online) Noise map produced (left) on the city of Bastia and (right) downtown zoom with measurement tracks.

different concepts to be addressed with high school pupils or students, and more generally with the general public.

In an educational context as in most of the interventions presented above, its integration
into training activities offers a good opportunity to tackle technical issues concerning the
accuracy and reliability of such acoustic sensors in comparison with professional systems.
Questions relating to measurement uncertainties or even sound signal processing can thus be
addressed to awaken participants' critical sense concerning the results of their measurements,

and more generally on acoustic performance and noise pollution information that they may encounter in their daily life.

During all the events, an essential step may be the calibration of the smartphones, which 395 allows participants to understand the difference between a smartphone and a reference device, by observing the bias between the different devices. One of the messages to be passed 397 on to the public is therefore to keep a critical mind on both the measurement and calibra-398 tion protocols. However, the lack of smartphone calibration, for example in the absence 399 of specific hardware or when the smartphone is difficult to calibrate, should not be a barrier. The lack of calibration does not necessarily matter when it comes to raising awareness 401 about noise pollution. Furthermore, in some interventions such as those presented in this 402 article, the interest of certain measurements is based on the measurement of the difference between measured sound levels, which is normally independent of the calibration (unless the 404 smartphone measures over sound level ranges for which it is not the most suitable). 405

In addition, the NoiseCapture application offers different display options for measurement 406 results and various acoustic indicators. Numerous basic concepts in acoustics can thus be 407 approached on the basis of the application from the notions of the decibel or sound frequency, 408 to the concepts of equivalent sound pressure level over a time period or acoustic emergence. 400 Practicing measurement with such application makes it easier to learn these concepts because participants can interact with the application to better understand the information provided. 411 Moreover, such interventions allow to expose the health, societal and environmental impacts 412 of noise. The bringing together of participants and acoustics professionals around a noise 413 measurement activity also makes it possible to open up discussion on practices and activities that have an impact on individual exposure, and to carry out educational and preventive
work on good practices to avoid hearing trauma linked to exposure to excessive noise levels.
Finally, this collective activity can open the discussion towards an awareness of the noise
annoyance for others that certain activities can cause, and thus contribute socially to better
living together.

In this respect, now that the pedagogical capacities for raising awareness about noise issues through the use of the application have been demonstrated through experience, the question arises as to how users can grasp it in the longer term. In an open format where anyone can download it, it becomes possible for local authorities to initiate projects in which groups of inhabitants are invited to download and use the application. The objective would be then to make them becoming aware of the issue of urban noise, and be part of the proposal and decision processes regarding noise. The interest is then to know to what extent this empowerment operates. These subjects are addressed in the work in progress (Can et al., 2022).

429 V. CONCLUSION

The NoiseCapture app and its ecosystem offer an interesting and attractive material to
teach basics in acoustics, and more generally noise issue, both to youth and adult audiences.

As outlined in this paper, the NoiseCapture team has experimented various contexts of
pedagogical interventions whether in school environment or else as part of scientific events,
on the own initiative of team members or at the request of teachers or public authorities.

All these interventions made it possible to approach numerous basic concepts in general

acoustics as well as in more specific disciplines such as building, environmental acoustics or else psychoacoustics. These educational initiatives are fully in line with the open-science approach at the heart of the NoiseCapture project (codes, data, publications, etc.) since they greatly promote the dissemination of knowledge and public awareness.

Acknowledgement

440

The authors would like to thank all the teachers, educational institutions, public institutions and French regions mentioned in this article for their support in organizing these events. The authors would also like to thank all the pupils and students who, through their motivation and commitment, have also participated in the success of these operations.

```
<sup>1</sup>UMRAE website: https://www.umrae.fr/en/.
    <sup>2</sup>Lab-STICC website: https://labsticc.fr/en.
    <sup>3</sup>The concept of NoiseCapture Party aims at regrouping a set of participants simultaneously in order to pro-
    duce a participatory noise map over a delimited area (http://noise-planet.org/noisecapture_party.
448
    html).
449
    <sup>4</sup>The automatic procedure with a reference smartphone makes it possible to calibrate several devices simul-
    taneously.
451
    <sup>5</sup>A tutorial is proposed on the Noise-Planet website to exploit a huge amount of data thanks to Python or
    R scripts (see https://noise-planet.org/noisecapture_exploit_data.html#raw_files).
453
    ^6https://www.bruit.fr/entreprises/mesure-environnementales-au-smartphone-travaux-de-recherche-des-lycee
454
    <sup>7</sup> "CGénial" stands for "c'est génial" in french, which can be translated as "it's great".
    8https://www.maisons-pour-la-science.org/en
456
    ^9The online map is available here: https://noise-planet.org/map_noisecapture/noisecapture_party.
457
    html#16/42.7010/9.4515/AGGLOBASTIA2018.
   <sup>10</sup>Online map: https://noise-planet.org/map_noisecapture/noisecapture_party.html#11/47.2251/
     -1.5850/FDSNTS2018
460
   <sup>11</sup>Online map: https://noise-planet.org/map_noisecapture/noisecapture_party.html#16/48.5845/
    7.7620/FDSSTRAS2018
462
463
    Aumond, P., Can, A., G. R., Fortin, N., and Suárez, E. (2020). "Method for in situ acoustic cal-
464
      ibration of smartphone-based sound measurement applications," Applied Acoustics 166, 107337,
465
      http://www.sciencedirect.com/science/article/pii/S0003682X1931196X, doi: 10.1016/
466
```

j.apacoust.2020.107337.

- Aumond, P., Lavandier, C., Ribeiro, C., Boix, E. G., Kambona, K., D'Hondt, E., and Delaitre,
- 469 P. (2017). "A study of the accuracy of mobile technology for measuring urban noise pollution
- in large scale participatory sensing campaigns," Applied Acoustics 117, 219–226, https://www.
- sciencedirect.com/science/article/pii/S0003682X16302055, doi: https://doi.org/10.
- 472 1016/j.apacoust.2016.07.011.
- Bocher, E., Petit, G., Fortin, N., Picaut, J., Guillaume, G., and Palominos, S. (2016). "Onom@p
- : a spatial data infrastructure dedicated to noise monitoring based on volunteers measure-
- ments," PeerJ Preprints 4, https://peerj.com/preprints/2273v2/#, doi: 10.7287/peerj.
- preprints.2273v2.
- Bocher, E., Petit, G., Picaut, J., Fortin, N., and Guillaume, G. (2017). "Collaborative noise
- data collected from smartphones," Data in Brief 14, 498-503, http://www.sciencedirect.
- com/science/article/pii/S2352340917303414, doi: 10.1016/j.dib.2017.07.039.
- 480 Can, A., Audubert, P., Aumond, P., Guiu, C., Lorino, T., and Rossa, E. (2022). "Sound environ-
- ments and citizen action: what place for the participatory tool? The case of the city of Rezé
- using NoiseCapture," in *Proceedings of Internoise 2022*, Glasgow.
- 483 Celestina, M., Hrovat, J., and Kardous, C. A. (2018). "Smartphone-based sound level mea-
- surement apps: Evaluation of compliance with international sound level meter standards,"
- Applied Acoustics 139, 119-128, http://www.sciencedirect.com/science/article/pii/
- s0003682X17309945, doi: 10.1016/j.apacoust.2018.04.011.
- 487 Directive 2002/49/EC (2002). "Directive of the European parliament and of the council of 25 June
- 2002 relating to the assessment and management of environmental noise" http://ec.europa.
- eu/environment/noise/directive.htm.

- Dockrell, J. E., and Shield, B. (2004). "Children's perceptions of their acoustic environment at
- school and at home," The Journal of the Acoustical Society of America 115(6), 2964–2973, doi:
- 492 10.1121/1.1652610.
- ⁴⁹³ D'Hondt, E., Stevens, M., and Jacobs, A. (2013). "Participatory noise mapping works! An eval-
- uation of participatory sensing as an alternative to standard techniques for environmental mon-
- itoring," Pervasive and Mobile Computing 9(5), 681-694, https://www.sciencedirect.com/
- science/article/pii/S1574119212001137, doi: https://doi.org/10.1016/j.pmcj.2012.
- 497 09.002 special issue on Pervasive Urban Applications.
- Elejalde-García, M. J., and Macho-Stadler, E. (2019). "Using a smartphone to investigate class-
- room acoustics," Journal of Physics: Conference Series 1287, doi: 10.1088/1742-6596/1287/
- 500 1/012023.
- Garg, S., Lim, K. M., and Lee, H. P. (2019). "An averaging method for accurately calibrating
- smartphone microphones for environmental noise measurement," Applied Acoustics 143, 222–
- 503 228, https://www.sciencedirect.com/science/article/pii/S0003682X18304468, doi: 10.
- 1016/j.apacoust.2018.08.013.
- 505 Guillaume, G., Can, A., Petit, G., Fortin, N., Palominos, S., Gauvreau, B., Bocher,
- 506 E., and Picaut, J. (2016). "Noise mapping based on participative measurements,"
- Noise Mapping 3(1), 140-156, http://www.degruyter.com/view/j/noise.2016.3.issue-1/
- noise-2016-0011/noise-2016-0011.xml?format=INT, doi: 10.1515/noise-2016-0011.
- Kawahara, K., Suzuki, S., Toyomasu, M., and Toyota, S. (2019). "Development of a Teaching
- Material on "Life and Sounds" for Primary School Home Economics: An Activity Program on
- Making Sound Quizzes Using Tablet Devices," Bulletin of Fukuoka University of Education 68,

- 1-6, http://hdl.handle.net/10780/2161 (In Japanese).
- Li, C., Liu, Y., and Haklay, M. (2018). "Participatory soundscape sensing," Landscape
- and Urban Planning 173, 64-69, https://www.sciencedirect.com/science/article/pii/
- 515 S0169204618300446, doi: https://doi.org/10.1016/j.landurbplan.2018.02.002.
- 516 Maisonneuve, N., Stevens, M., and Ochab, B. "participatory noise pollution monitoring using
- mobile phones,".
- Picaut, J., Boumchich, A., Bocher, E., Fortin, N., Petit, G., and Aumond, P. (2021a). "A
- 519 Smartphone-Based Crowd-Sourced Database for Environmental Noise Assessment," Interna-
- tional Journal of Environmental Research and Public Health 18(15), 7777, https://www.mdpi.
- com/1660-4601/18/15/7777, doi: 10.3390/ijerph18157777 number: 15 Publisher: Multidisci-
- plinary Digital Publishing Institute.
- Picaut, J., Fortin, N., Bocher, E., and Petit, G. (2021b). "NoiseCapture data extraction from Au-
- gust 29, 2017 until August 28, 2020 (3 years)" https://research-data.ifsttar.fr/dataset.
- xhtml?persistentId=doi:10.25578/J5DG3W, doi: 10.25578/J5DG3W.
- Picaut, J., Fortin, N., Bocher, E., Petit, G., Aumond, P., and Guillaume, G. (2019). "An open-
- science crowdsourcing approach for producing community noise maps using smartphones," Build-
- ing and Environment 148, 20 33, http://www.sciencedirect.com/science/article/pii/
- 529 S0360132318306747, doi: 10.1016/j.buildenv.2018.10.049.
- Radicchi, A. (2019). "Soundwalking with children for a quieter and healthier city," Cities & Health
- 3(1-2), 78–84, doi: 10.1080/23748834.2019.1578455.
- Radicchi, A., Henckel, D., and Memmel, M. (2018). "Citizens as smart, active sensors for a quiet
- and just city, the case of the "open source soundscapes" approach to identify, assess and plan

- "everyday quiet areas" in cities," Noise Mapping 5(1), 1-20, https://www.degruyter.com/
- view/journals/noise/5/1/article-p1.xml.
- Sakagami, K., Satoh, F., and Omoto, A. (2013). "A case study of introductory teaching method for
- architectural/environmental acoustics using a smartphone," Acoustical Science and Technology
- 34(3), 209–211, doi: 10.1250/ast.34.209.
- 539 Sakagami, K., Satoh, F., and Omoto, A. (2019a). "Revisiting Acoustics Education Using Mo-
- bile Devices to Learn Urban Acoustic Environments: Recent Issues on Current Devices and
- 541 Applications," Urban Science **3**(4), https://www.mdpi.com/2413-8851/3/3/73, doi: 10.3390/
- 542 urbansci3030073.
- 543 Sakagami, K., Satoh, F., and Omoto, A. (2019b). "Use of Mobile Devices with Multifunctional
- 544 Sound Level Measurement Applications: Some Experiences for Urban Acoustics Education in
- Primary and Secondary Schools," Urban Science 3(111), https://www.mdpi.com/2413-8851/
- 3/4/111, doi: 10.3390/urbansci3040111.
- Satoh, F., Sakagami, K., and Omoto, A. (2016). "Application of a smartphone for introductory
- teaching of sound environment: Validation of the precision of the devices and examples of stu-
- dents' work," Acoustical Science and Technology 37(4), doi: 10.1250/ast.37.165.
- 550 Suarez, E., and Arenas, J. (2018). "Educational app for traffic noise mapping," INTER-
- NOISE and NOISE-CON Congress and Conference Proceedings 258(4), 3930–3939, https:
- //www.ingentaconnect.com/content/ince/incecp/2018/00000258/00000004/art00102.
- Ventura, R., Mallet, V., Issarny, V., Raverdy, P., and Rebhi, F. (2017). "Evaluation and calibration
- of mobile phones for noise monitoring application," The Journal of the Acoustical Society of
- America **142**(5), 3084-3093, https://asa.scitation.org/doi/abs/10.1121/1.5009448, doi:

```
10.1121/1.5009448.
```

⁵⁵⁷ Zuo, J., Xia, H., Liu, S., and Qiao, Y. (2016). "Mapping Urban Environmental Noise Using

558 Smartphones," Sensors **16**(10), https://www.mdpi.com/1424-8220/16/10/1692, doi: 10.3390/

s16101692.