

Simulated destructive release from antibubble microcapsules

Nicole Anderton, Craig Stuart Carlson, Michiel Postema

▶ To cite this version:

Nicole Anderton, Craig Stuart Carlson, Michiel Postema. Simulated destructive release from antibubble microcapsules. MET Research Day, Nov 2022, Tampere, Finland. hal-03849806

HAL Id: hal-03849806 https://hal.science/hal-03849806

Submitted on 12 Nov 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



JOHANNESBURG

Simulated destructive release from antibubble microcapsules

N Anderton, CS Carlson, M Postema

Antibubbles are small gas bubbles comprising one or multiple liquid or solid cores, typically surrounded by stabilising shells. Acoustically active microscopic antibubbles have been proposed for use as theranostic agents. For clinical applications such as ultrasound-guided drug delivery and flash-echo, it is relevant to know the fragmentation threshold of antibubbles and the influence of the stabilising shells thereon. For antibubbles with an infinitesimal frictionless elastic shell of constant surface tension, we simulated ultrasound-assisted fragmentation by computing radial pulsation as a function of time using an adapted Rayleigh-Plesset equation, and converting the solutions to time-variant kinetic energy of the shell and time-variant surface energy deficit. By repetition over a range of pressure amplitudes, fragmentation thresholds were found for antibubbles of varying size, core volume, shell stiffness, and driving frequency. As backscattering increases with scatterer size, and as drug delivery would require vehicles just small enough to pass through capillaries with a relatively large payload, we chose to present typical results for antibubbles of resting diameter 6µm with a 90% incompressible core. At a driving frequency of 13MHz, the fragmentation threshold was found to correspond to mechanical indices less than 0.4, irrespective of shell stiffness. This mechanical index is not considered unsafe in diagnosis. That means that antibubbles acting as drug-carrying vehicles could release their payload under diagnostic conditions.





Schematic representation of an endoskeletal antibubble.



Antibubble before (a) and after (b) sonication and resulting fragmentation.

Methods



Fundamental pulsation

$R\ddot{R} + \frac{3}{2}\dot{R}^2 = \frac{1}{\rho} \left[\left(p_0 - p_v + \frac{2\sigma R_0}{R_0^2 - R_c^2} \right) \left(\frac{R_0^3 - R_c^3}{R^3 - R_c^3} \right)^{\gamma} \right]$ $+p_{\rm v}-\frac{2\sigma R}{R^2-R_c^2}-2\chi\left(\frac{1}{R_0}-\frac{1}{R}\right)$ $-\frac{4\eta\dot{R}}{R}-\delta\omega\rho R\dot{R}-p_0-p(t)\right] ,$

where

p(t) – time-dependent acoustic driving function 1.00 atm – ambient pressure 2.33kPa - vapour pressure R – instantaneous radius R_0 – initial radius variable – equivalent core radius variable - ratio of specific hears 1.4

- damping coefficient 0
- liquid viscosity
- liquid density D
- surface tension
- shell stiffness

Radius and instantaneous energies as a function of time simulated for an antibubble of initial radius $R_0 = 3 \mu m$ with a 90% core radius and shell stiffness $\chi = 7.6 \text{ Nm}^{-1}$ driven with a 0.6-MI pulse of centre frequency 1MHz (a, c) and 13MHz (b, d). Instantaneous kinetic energies are indicated by blue lines and surface energy deficits by red lines. The purple arrow indicates the point of fragmentation.

Fragmentation threshold in MI as a function of shell stiffness χ , simulated for a 3-µm radius antibubble with a 90% core radius, subjected to a pulse of centre frequency 1MHz (red) and 13MHz (blue).

Fragmentation threshold in MI as a function of driving frequency, simulated for a 3-µm radius antibubble with a 90% core radius and a 7.6-Nm⁻¹ shell stiffness.

angular driving frequency

variable

variable

1.00mPas

998 kg m⁻³

Instantaneous kinetic energy

 $E_{\rm k} \approx 2\pi\rho R^3 \dot{R}^2$

Surface energy deficit

 $\Delta E_{\rm s} \approx 4\pi R^2 \sigma$

Conclusions

Shell stiffness only influences antibubble fragmentation at lower driving frequencies.

At 13-MHz, stiff-shell-encapsulated antibubbles fragment at amplitudes not considered diagnostically unsafe.

Shell-stabilised, drug-loaded antibubbles could be forced to release their contents using diagnostic ultrasound.

Author statement

Research funding: This work was supported by the National Research Foundation of South Africa, Grant Number 340026. Conflict of interest: Authors state no conflict of interest. Informed consent: Authors state that informed consent is not applicable. Ethical approval: Authors state that no ethical approval was required for this research as no human or animal samples or data were used.

Image: Nicole.Anderton@tuni.fi