

# Can lateral mobility be restored along a highly domesticated low-energy gravel-bed river?

Thomas Dépret, Nathalie Thommeret, Hervé Piégay, Emmanuèle Gautier

# ▶ To cite this version:

Thomas Dépret, Nathalie Thommeret, Hervé Piégay, Emmanuèle Gautier. Can lateral mobility be restored along a highly domesticated low-energy gravel-bed river?. Journal of Environmental Management, 2023, 325, pp.116485. 10.1016/j.jenvman.2022.116485 . hal-03853525

# HAL Id: hal-03853525 https://hal.science/hal-03853525

Submitted on 23 Feb 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1	Can lateral mobility be restored along a highly domesticated
2	low-energy gravel-bed river?
3	
4	Thomas Dépret <sup>a</sup> *, Nathalie Thommeret <sup>b</sup> , Hervé Piégay <sup>c</sup> , Emmanuèle Gautier <sup>d</sup>
5	
6	<sup>a</sup> Laboratoire de Géographie Physique, CNRS UMR8591, 2 rue Henri Dunant, 94320 Thiais,
7	France
8	<sup>b</sup> Laboratoire Géomatique et Foncier, CNAM-ESGT, 1 Boulevard Pythagore, 72000 Le Mans,
9	France
10	<sup>c</sup> Université de Lyon, CNRS, UMR 5600 - Environnement-Ville-Société, Site ENS de Lyon,
11	15 Parvis René Descartes, Lyon 69342, France
12	<sup>d</sup> Université Paris 1 Panthéon-Sorbonne, Laboratoire de Géographie Physique, CNRS
13	UMR8591, 2 rue Henri Dunant, 94320 Thiais, France
14	
15	
16	* Corresponding author
17	
18	
19	Abstract
20	Fluvial engineering works such as weirs, rip-rap, groynes, and dykes have constrained for
21	decades and more the lateral mobility of rivers, one of the key drivers of aquatic and riparian
22	diversity. Preserving or restoring a sufficient space for river mobility has therefore become a
23	major river management focus. Because the success and relevance of management actions are
24	conditioned by the level of energy and sediment supply of rivers, such actions are generally
25	considered unsuitable for low-energy rivers. However, some low-energy rivers have

numerous ancient engineering works along their length, especially bank protections, 26 27 suggesting a potential capacity for bed migration. In this context, it is essential to determine to what extent planform dynamics is disturbed, and if lateral mobility can be restored. Herein, a 28 29 case study was done on a 146 km stretch of the low-energy meandering gravel-bed Cher 30 River (France). The goal of the study was to estimate the remnant shifting capacity, identify 31 the factors controlling the location and intensity of lateral erosion, determine the potential for 32 preserving and restoring lateral mobility, and examine management measures that could be 33 implemented to this end. For that, field surveys, analysis of existing databases, aerial 34 photographs, and laser imaging detection and ranging digital elevation model (LiDAR DEM) 35 data were combined. The study revealed a strong longitudinal fragmentation of the river, with most of it laterally constrained due to the presence of anthropogenic structures such as bank 36 37 protections, former gravel pits in the alluvial plain, bridges, and weirs. The river is now 38 composed of a string of constrained and unconstrained reaches, and the space available for 39 river shifting has been dramatically reduced. Due to these fluvial engineering works and 40 anthropogenic legacies, the potential for lateral movement of the riverbed, and, therefore, 41 diversification of riparian and aquatic habitats, is limited. Furthermore, lateral mobility could 42 be preserved or restored only for very short sections of the river. It is therefore highly unlikely 43 that good ecological status could be achieved on the entire river corridor through removal of 44 bank protections. Nevertheless, a possible solution could be combining bank protection 45 removals with a series of gravel augmentations close to each other.

46

## 47 Keywords

48 Lowland river; Erodible corridor; Anthropogenic constraints; Stream restoration; Meander
49 migration; Ecological status

51

# 52 Highlights

53	•	Potential for lateral mobility on a low-energy gravel bed river is estimated
54	٠	A strong decease in the shifting capacity due to anthropogenic constraints is found
55	•	A short cumulative length of river along which the lateral mobility is still possible
56	•	Good ecological status is not achievable on the entire river corridor even with rip-rap
57		removal
58		

59

# 60 1. Introduction

61 Due to their widespread presence on Earth, their tremendous attraction for human societies, 62 and because their morphology reflects changes occurring from basin to reach scale, rivers are 63 among the landscape units most influenced by anthropogenic constraints. In response to these 64 constraints, river forms and processes have been heavily altered, causing homogenization of 65 their aquatic and riparian habitats, degradation of their ecological quality, and 66 impoverishment of the social and ecosystem services they provide (Basak et al., 2021; 67 Borgwardt et al., 2019; Culhane et al., 2019; Dudgeon, 2019; Dudgeon et al., 2006; Ekka et al., 2020; Elosegi et al., 2010; Florsheim et al., 2008; Vörösmarty et al., 2010). Increasing 68 69 awareness of this damage has led to attempts to mitigate the negative effects of these 70 alterations, and an era of river repair has begun (Downs and Gregory, 2004; Fryirs and 71 Brierley, 2016). Indeed, many countries have enacted legal frameworks aimed at protecting or 72 improving the ecological status of rivers. One of the most striking examples is the Water 73 Framework Directive (WFD), adopted in 2000 by the European Union, that commits member states to achieve good ecological status of rivers, and to implement restoration measures to
achieve this status (European Parliament and Council, 2000; Grizzeti et al., 2017).

From the Neolithic to the Middle-ages, anthropogenic constraints were mainly, if not 76 77 exclusively, indirect, consisting of the modification of land cover in watersheds and floodplains, thereby affecting water and sediment fluxes and connectivity from hillslopes to 78 79 rivers (Brown et al., 2018; Hoffmann, 2015; Hoffmann et al., 2010; Notebaert and 80 Verstraeten, 2010). Over the last millennium, local constraints, most involving direct 81 modification of river channels and acting at segment or reach scales, have strengthened, first with the development of weirs connected to mills from the 11<sup>th</sup> century, followed by the 82 channelization and/or rectification of river courses from the 19<sup>th</sup> century, then the exponential 83 84 installation of large dams and massive gravel mining areas in riverbeds and floodplains from the mid-20<sup>th</sup> century (Brown et al., 2018; Downs and Piegay, 2019; Lehner et al., 2011; Maas 85 86 et al., 2021; Overeem et al., 2013; Rinaldi et al., 2005; Surian, 2021; Wohl, 2020). These 87 local constraints have resulted in a dramatic loss of lateral mobility of rivers (Dépret et al., 88 2017; Fremier et al., 2014; Friedman et al., 1998; Reid and Church, 2015), even though lateral 89 mobility is one of the main drivers of aquatic and riparian habitat diversity (Choné and Biron, 90 2016; Florsheim et al., 2008; Stanford et al., 2005; Tockner et al., 2010; Williams et al., 2020). For altered rivers, achieving good ecological status may be impossible without 91 92 restoration of a sufficient space to allow rivers to move laterally.

93 Restoration of space for lateral movement is grounded on process-based principles through 94 which rivers are believed to be able to self-restore, namely to recover fluvial landforms and 95 functions, with minimal anthropogenic intervention (Beechie et al., 2010; Ciotti et al., 2021; 96 Fryirs and Brierley, 2021). Self-restoration actions promote longitudinal and cross-wise 97 topographic as well as grain size heterogeneity, which increases the diversity of habitats, 98 particularly aquatic habitats (Gaeuman, 2012; Yarnell et al., 2006; Hauer et al., 2018;

99 Staenzel et al., 2020). Moreover, shifting riverscape mosaic processes guaranteed by the 100 lateral mobility of rivers allow rejuvenation of riparian succession associated with pulse disturbance (e.g., Diaz-Redondo et al., 2018; Gonzalez del Tanago et al., 2021; Hauer et al., 101 102 2016; Stanford et al., 2005; Tockner et al., 2010). These approaches are especially relevant 103 when natural lateral constraints and socio-economical issues (SEIs) in the floodplain are rare, 104 and when river energy and bedload are high (Kondolf, 2011). Nonetheless, these approaches 105 also could be appropriate for low-energy rivers, providing that the bed material is mobile and 106 alluvial material is sufficiently erodible to allow such rivers to be inherently behaviourally 107 sensitive (Fryirs, 2017).

108 At the reach scale, river mobility often is determined through reconstruction of 109 planimetric trajectory evolution (Khan and Fryirs, 2020; Piégay et al., 2005; Reid and 110 Brierley, 2015). For low-energy rivers, such methods can be unsuitable where lateral 111 anthropogenic constraints occur that may block channel movement, causing channel 112 responsiveness to be underestimated. Bank protection on such rivers often are not archived, 113 and they may be difficult to determine in the field unless a careful survey of the bed is carried 114 out at low flow (Dépret et al., 2017). Disentangling the natural and anthropogenic drivers 115 responsible for the weak planform shifting of low-energy rivers may, therefore, be 116 challenging. Such disentangling is yet crucial because it influences river responsiveness 117 appraisal and the design of preservation or restoration strategies, acting on forms or processes, 118 and depending on the trade-off between the timescale needed for recovery and the timescale 119 desired by managers. Determining to what extent lateral mobility can be restored along highly 120 domesticated low-energy gravel-bed rivers requires first examining if lateral processes are 121 still active, and if so to what extent, and whether there is enough space for river shifting.

122 To answer these questions, a case study was done on a 146 km stretch of the Cher 123 River (France), for which the long-term anthropogenic influence on planform displacements

124 as well as the potential for self-restoration of lateral dynamics have been demonstrated on 125 several short discrete reaches (8-12 km) (Dépret et al., 2015, 2017, 2021; Vayssière et al., 126 2016, 2020). The aims of this study were to estimate the remnant shifting capacity, to identify 127 the factors controlling the location and intensity of lateral erosion, to determine the potential for preservation and restoration of lateral mobility, and to examine the management measures 128 129 that could be implemented to this end. Therefore, a methodological framework was developed 130 combining (1) thorough field surveys and preexisting databases to identify the constraints on 131 lateral mobility and the current SEIs in the floodplain; (2) geographic information systems 132 (GIS) analysis aimed at reconstructing the planimetric evolutionary trajectory of the river 133 from aerial photographs, to quantify the available space for river shifting with and without 134 lateral constraints and/or SEIs, and to compute some of the main factors assumed to control 135 retreat rates (specific stream power, curvature, lateral constraints, availability of the coarse 136 bed-material load); and (3) statistical analysis to determine how these factors influence the 137 occurrence and intensity of lateral erosion.

138

139

# 140 **2.** Characteristics of the study reach

141 After leaving its source at 713 m above sea level, the Cher River mainly flows through gorges 142 across steep slopes or in deep valleys with a very narrow floodplain (upstream Cher in Figure 143 1). The upstream section of the river is located at the northwest end of the low-altitude 144 mountainous Massif Central, which mainly consists of crystalline and metamorphic rocks 145 (Larue, 1981, 2011). After 63 km, the Cher alluvial plain begins (Alluvial Cher in Figure 1) 146 and the river becomes single thread with a meandering pattern developed over recent 147 millennia (Vayssière et al., 2020). After first occupying the Tertiary graben of Montluçon, 148 which continues for 45 km to the confluence with the Aumance River (Larue, 1981, 2011;

149 Simon-Coincon et al., 2000), the river then crosses the sedimentary domain of the Parisian Basin, where it joins the Loire River at 38 m asl. The study reach extends over 146 km, 150 151 between Montluçon at the beginning of the Alluvial Cher, and Vierzon at the junction with 152 the Yèvre River, one of the main tributaries of the Cher River (Figure 1). With a surface 153 median sediment diameter (D<sub>50</sub>) of around 15–45 mm and a mean specific stream power of 20 W  $\,m^{\text{-}2}$  (calculated from the width of the active channel formed by flow channels and 154 155 unvegetated bars) for a discharge not exceeded 99% of the time (close to bankfull discharge), 156 it is a low-energy river with coarse gravel (Dépret, 2014; Dépret et al., 2015).

The alluvial infill is organized into two or three main stratigraphic levels. The base of the infill is composed of sand, gravel, and pebble, while the upper part consists of overflow deposits of clay, silt and sand (Dépret, 2014; Lablanche et al., 1994; Manivit et al., 1994; Larue, 1994; Turland et al., 1989c). A predominantly sandy layer is frequently interspersed between these two levels. Because of this composite structure and the coarse nature of the material, the banks are highly erodible (Dépret et al., 2015, 2017). Moreover, bed mobility occurs over several days per year (Dépret et al., 2015, 2017).

164 The rainfall-evaporation regime of the Cher is essentially influenced by western flows. 165 High water occurs in winter, generally in February, and low water occurs in summer, 166 typically in August. On the upstream part of the middle course of the river, the hydrological 167 regime, in particular for low flow, is partly artificialized since the construction of the 168 Rochebut Dam at the beginning of the 20<sup>th</sup> century. Along the 146 km stretch studied, along 169 with the Aumance River, the Cher River receives contributions from one major tributary 170 (Figure 1).



Figure 1 - Location of the study reach. A: The Cher River watershed within French territory.
B: The study reach in the Cher River watershed. C: Diagram of the course of the Cher River and its alluvial plain.

176

172

177

# 178 **3. Materials and methods**

```
179
```

# 3.1 Reconstruction of bank retreat rates and length since the mid-20<sup>th</sup> century

180 The bank retreat rates and length of the river were reconstructed from aerial 181 orthophotographs from the Institut Géographique National (IGN; National Geographic 182 Institute) dated 1950s and 2016 using ArcGIS 10.6 (Table 1). For the 1950s, photographs were dated 1954, 1959, and 1960, and they are subsequently referred to using the 1959 datealone, for which the majority of the active channel was digitized.

Quantification and characterization of bank retreat rates and length were based on the identification and digitization of the active channel at each date. Between the two successive dates, all areas occupied by perennial vegetation (islands and alluvial plain) at date t and active channel at date t+1 were considered eroded.

189

190 Table 1 – Date, scale, resolution (m) and rectification error (m) of aerial photographs used in

191 reconstruction of bank retreat rates and length of the Cher River since the mid-20th century.

Date	Scale	Resolution	Rectification error
1954–1960	1/25000-1/27000	0.5	3.3
2016		0.2	3.2

192

193

194 Two main types of errors are inherent with the method used to generate the data 195 (Gaeuman et al., 2003). The first corresponds to the rectification error (E1). The errors 196 reported by the IGN for the 1959 and 2016 images are 2 m and 1 m, respectively. These errors 197 are equal to the root mean squared error, which "summarizes the continuous deviations 198 encountered over the ground surface (rather than at a few specific points)" (IGN, 2016). The 199 second type of error corresponds to the active channel digitizing error (E2). It corresponds to 200 the maximum uncertainty in locating the active channel boundary under overhanging forest. 201 Obtained by iterative digitizing of its outline (Gurnell et al., 1994), it is equal to plus or minus 202 3 m for 1959 and 2016. Since these two errors are independent of each other, the total error,

203 equal to 3.3 m for 1959 and 3.2 m for 2016 (Table 1), was obtained by calculating the square

root of the sum of the square of these errors (Taylor, 1997): *Totalerror* =  $\sqrt{E1^2 + E2^2}$ .

205 Once total error was determined, eroded areas were delineated. For each date, a buffer 206 zone with a width equal to twice the value of the total error was created along each of the 207 banks. The buffer zones of the active channel at two successive dates were then merged, 208 denoting the spatial extent within which any change was considered unproven. Finally, any 209 eroded polygon that was entirely within this merged buffer zone was excluded from the 210 analysis. Conversely, when polygons exceeded the merged buffer zone, the change was 211 considered proven and these polygons were retained. From these final eroded polygons the 212 normalised retreat rates were computed at 50 m spaced cross-sections positioned 213 perpendicular to the centerline of the active channel (ratio of retreat rate to the active channel 214 width at the initial date expressed per year) (Roux et al., 2015). The normalised retreat rates 215 were calculated for both banks combined and for concave banks alone. As there were no 216 major changes in the river course, the longitudinal position of the cross-sections in 1959 and 217 2016 was determined from an origin located at the level of the Glacerie footbridge, in 218 Montluçon. In addition, a certain number of river sections where gravel mining has led to an 219 artificial widening of the bed were excluded from the analysis. Next, from the 50 m spaced 220 cross-sections, the percentage of river length affected by lateral erosion was quantified every 221 km. Finally, the longitudinal pattern of retreat rates and of the percentage of river length 222 affected by lateral erosion were examined.

223

# 3.2 Evaluation of lateral constraints and space potentially available for channel shifting

Natural and anthropogenic structures, both present and from 1959, that directly constrain thepotential lateral mobility of the river were characterized at each of the 50 m equidistant cross-

228 sections previously described. For natural constraints, digitized 1:50,000 scale geological 229 maps from the Bureau de Recherches Géologiques et Minières (BRGM; French Geological 230 Survey) were used (Debrand-Passard et al., 1977a, 1978; Lablanche, 1984, 1994; Manivit and 231 Debrand-Passard, 1994; Obert et al., 1997; Turland et al., 1989a, 1989b). The maximum 232 space available for channel shifting in absence of anthropogenic constraints was assigned to 233 the location of the present and recent alluvium (fy/fz). Any cross-section with at least one 234 bank abutting hillslope, alluvial or colluvial fan, or terrace was considered laterally 235 constrained (Fryirs et al., 2016). Because of the relative spatial uncertainty of the boundaries 236 between the alluvium and the hillslopes, fans or terraces, it was considered that abutting 237 occurred when the distance between the river and the natural constraints is less than 50 m. 238 The same approach was applied for concave banks only.

Four types of anthropogenic constraints were distinguished: bank protection, bridges, weirs, and gravel pits installed in the alluvial plain. If gravel pits could have been classified as a SEI, their presence also is a direct constraint on lateral mobility to the extent that lateral displacement of the river would be completely blocked for decades in the case of capture by a pit. For this reason, they were classified as a constraint to lateral mobility rather than as a SEI.

244 Bank protection works were identified and their positions surveyed by GPS in the field 245 during the 2018 summer low flow. Bank protection works in 2018 located on sections of 246 river not eroded between 1959 and 2016 were considered to be present in 1959. Bridges and 247 weirs were identified and located from 1959 and 2016 aerial photographs and from the 248 Référentiel des Obstacles à l'Ecoulement (Repository of obstacles to flow, ROE; 249 https://www.sandre.eaufrance.fr/atlas/srv/fre/catalog.search#/map). On cross-sections located 250 within 50 m of bridges and weirs, the river was considered constrained. Finally, gravel pits 251 currently present in the alluvial plain were digitized by Cossalter (2011) from 2005 aerial 252 photographs. This digitization was updated in the present work using 2016 aerial photographs.

Similarly, 1959 gravel pit locations were digitized from 1959 aerial photographs. Any crosssections located within 50 m of a gravel pit were considered constrained.

255 Moreover, all current SEIs encountered in the floodplain, except those related to 256 agricultural lands, also were integrated into the GIS analysis. Taking SEIs into consideration 257 allows determination of the space potentially available for river shifting in the absence of 258 lateral constraints, specifically in the case of restoration of lateral mobility. For each cross-259 section, the distance to the nearest SEI was measured, but SEIs were not prioritized. The raw 260 data used were from the IGN Topo database. The GIS layers including important buildings, 261 industrial buildings, cemeteries, sports grounds, water reservoirs, pylons, pipes of any kind, 262 electricity lines, electrical substations, marshalling areas, stations, railroads, and the Berry 263 Canal were used without modification. For the 'undifferentiated buildings' layer, polygons 264 representing buildings judged non-essential were excluded (shelters, huts, etc.). Finally, the 265 'primary road' layer was kept unchanged, whereas the 'secondary road' layer was selected 266 since roads and paths not accessing one of the objects listed above were excluded.

267 The extent of lateral constraints and/or SEIs in the floodplain was considered in two 268 distinct but complementary ways. First, the percentage of river length affected by the different 269 types of constraints and/or SEIs were quantified. We considered that a SEI is present along 270 the river when it is located <50 m from the closest bank. The percentage of river length 271 laterally constrained was calculated every km. In a second step, the space potentially available 272 for channel shifting was measured at each 50 m spaced cross-section after taking into account 273 the different types of constraints and/or SEIs. Here, all SEIs present in the floodplain were 274 considered. The constrained length and the space potentially available for channel shifting 275 were determined by considering both banks or just concave banks. Concave banks were the 276 focus because this is where most of lateral erosion occurs. Thus, in a relatively short timescale 277 (years to decades), and from the perspective of improving the ecological status of the river by

restoration of lateral erosion, the available floodplain space adjacent to this concave side is of
direct interest for river managers. Finally, visual examination and Hubert's segmentation
(Hubert et al., 1989; Hubert, 2000) were applied to determine the longitudinal pattern of (1)
the percentage of river length affected by the different types of constraints and/or SEIs, and
(2) the space potentially available for channel shifting.

- 283
- 284

# **3.3 Factors controlling lateral erosion**

285 Bank retreat rates for the 1959–2016 period were related at different spatial scales to four of 286 the main potential controlling factors reported in the literature: specific stream power 287 (calculated for a discharge not exceeded 99% of the time) (e.g., Richard et al., 2005), 288 curvature (e.g., Furbish, 1988; Sylvester et al., 2019), lateral constraints (Dépret et al., 2017), 289 and the density of bars and alluvial riffles, used as an indicator of the coarse material 290 available for bedload, the availability of a sufficiently large load of mobile coarse sediment 291 being an indispensable condition for the self-maintenance of lateral mobility (e.g., Donovan et 292 al., 2021). The assumed trends are an increase in retreat rates and in the occurrence of lateral 293 erosion with an increase in each of these four factors.

First, the presence of any spatial correspondence between the longitudinal pattern of retreat rates or the percentage of river length affected by lateral erosion on one hand, and the longitudinal pattern of specific stream power, curvature, lateral constraints, and the density of bars and alluvial riffles on the other hand was evaluated.

Second, at the scale of unconstrained cross-sections, the extent to which specific stream power and curvature at the initial date differed between cross-sections with erosion and cross-sections without erosion was examined. Then, for cross-sections subjected to erosion only, correlations between retreat rates and specific stream power or local curvature were calculated. In a second step, a Chi-square test was performed to determine the influenceof lateral constraints present in 1959 on the manifestation of lateral erosion.

Specific stream power was obtained using the formula:  $\rho_w gQS/w$ , where  $\rho_w$  is the 304 density of water (1000 kg m<sup>-3</sup>), g is the gravitational acceleration (9.81 m s<sup>-2</sup>), Q is the 305 discharge  $(m^3 s^{-1})$ , S is the bed slope  $(m m^{-1})$ , and w is the active channel width (m). The 306 specific stream power was determined for each 50 m equidistant cross-section using the low-307 308 water line slope from the laser imaging detection and ranging digital elevation model (LiDAR 309 DEM) data of the Cher Valley (2011) and the 1959 active channel width. A discharge with 310 the same non-exceedance frequency (not exceeded 99% of the time) was used upstream and 311 downstream of the confluence with the Aumance River in order to make the two sub-reaches comparable. It was equivalent to 90 m<sup>3</sup> s<sup>-1</sup> for the upstream sub-reach (Montluçon reference 312 gauging station) and 190 m<sup>3</sup> s<sup>-1</sup> for the downstream sub-reach (Saint-Amand-Montrond 313 314 reference gauging station), values similar to the bankfull discharge on each of the sub-reaches (85  $\text{m}^3 \text{s}^{-1}$  upstream and 178–245  $\text{m}^3 \text{s}^{-1}$  downstream) (Dépret, 2014). 315

Curvature was calculated locally at each cross-section. This corresponds to the angle (in radians per m) between the centerline segment connecting the upstream cross-section and the cross-section in question on the one hand, and the centerline segment connecting the cross-section in question and the downstream cross-section on the other. The curvature was then normalized against the width of the active channel to make comparable the sub-reaches upstream and downstream of the Aumance junction (rad m<sup>-1</sup> m<sup>-1</sup>). Lateral constraints in 1959 were identified as described in Section 3.2.

Bars, alluvial riffles, and rocky riffles were identified and their positions surveyed by global positioning system (GPS) in the field during the 2018 summer low flow. During this same campaign, the presence of bedrock in the bed (other than in the form of rocky riffles) also was systematically surveyed. Thereby the length of the sections along which bedrock is outcropping and the distance between the sections in question were acquired. However, these sections are somewhat heterogeneous, since they include both sections of the river along which the alluvium has been completely evacuated and sections where the bedrock outcrops are laterally and/or longitudinally more or less discontinuous. Due to the different widths of the river upstream and downstream of the confluence with the Aumance, the distance between two successive units or the length of the bedrock sections was normalized against the width of the river.

334

335

# **3.5 Preservation and restoration of lateral mobility**

336 Herein, identification of river sections for which measures to preserve or to restore lateral 337 mobility could be undertaken is done. The main objective was to propose a synthetic image of 338 each of these sections that could be used by managers as a decision-making tool. The sections 339 likely to be most suitable for restoration of lateral mobility are those equipped with bank 340 protection, the only type of constraint that can be removed. The approach utilized included 341 three stages. First, sections presenting a priori a minor interest in terms of preservation or 342 restoration of lateral mobility were excluded (see paragraph below for detailed explanation). 343 Next, based on the remaining sections to be preserved, the intensity of retreat rates can be 344 explained from the values for tested controlling factors in 1959 using logistic regression 345 models. Finally, the generated models were applied using the values of controlling factors in 346 2016 to predict retreat rates for the sections to be preserved or restored. The various criteria 347 taken into account in this analysis were incorporated at an elementary level at the scale of 348 cross-sections spaced 50 m apart. The values finally retained at the scale of the considered 349 sections correspond to the mean or median of values informing the cross-sections encountered 350 on each section.

351 For preservation, sections with at least one of the following criteria were excluded: maximum retreat rate in concave bank <0.017 m m<sup>-1</sup> y<sup>-1</sup>, length <100 m, space potentially 352 available for channel shifting in concave bank  $\leq 100$  m, specific power in 2016 for a discharge 353 not exceeded 99% of the time  $\leq 13$  W m<sup>-2</sup>. The use of a threshold value for retreat rates allows 354 355 the exclusion of sections without erosion between 1959 and 2016. This criterion appears to be 356 essential because a section without erosion in recent decades is unlikely to present lateral erosive activity in the future. The chosen threshold of 0.017 m m<sup>-1</sup> year<sup>-1</sup> corresponds to the 357 358 value for which the performance of the logistic regression model used to explain and predict 359 retreat rates at the section scale was optimized. In addition, this threshold allows the focus to 360 be exclusively on the most historically active reaches. The section length and the space 361 potentially available for channel shifting criteria were set so that the manifestation of lateral 362 erosion could ensure a sustained and long-lasting injection of coarse sediments into the active 363 channel. The selected length of 100 m corresponds to the median of the length of the eroded 364 sections between 1959 and 2016. The minimum envelope of 100 m retained for the space 365 potentially available for channel shifting makes it possible to ensure maintenance of erosion 366 over several decades without having to intervene to protect SEIs currently relatively far from 367 the bed. This value of 100 m corresponds to the most important bank retreat measured 368 between 1959 and 2016 along the study reach. The space potentially available for channel 369 shifting retained is equal to the median of the values on the concave side at the level of the cross-sections present at each river section. Finally, the value of 13 W  $m^{-2}$  was chosen based 370 371 on monitoring of eroded banks between 2009 and 2013 at two sites located upstream and downstream (kilometric point (kp) 26.45-37.1 and kp 61.4-69.9) of the confluence with the 372 Aumance (Dépret, 2014). The value of 13 W m<sup>-2</sup> corresponds to the lowest specific stream 373 power for a discharge not exceeded 99% of the time at these different monitoring sites. 374

375 Once sections meeting at least one of these criteria were excluded, a logistic regression 376 model adapted to beta-type distributions (values taken by individuals of the dependent 377 variable between 0 and 1) was applied. For this, the GAMLSS package of R (Rigby and 378 Stasinopoulos, 2005) was used. Two regression models were constructed to explain the mean 379 and maximum concave bank retreat rates between 1959 and 2016 along the sections to be 380 preserved. The two independent variables ultimately selected were the maximum specific 381 power in 1959 for a discharge not exceeded 99% of the time and the mean local curvature in 382 1959. The generated models then were applied to predict retreat rates from the maximum 383 specific stream power in 2016 and the mean local curvature in 2016.

384 For restoration of lateral mobility, the considered sections include river sections with 385 concave bank protection extending from contiguous upstream and/or downstream river 386 sections without bank protection. As a result, there is a partial overlap between some sections 387 to be preserved and some sections that may be restored. The same exclusion criteria as 388 presented for the sections to be preserved were applied, with the exception of the criterion 389 relating to erosion. Two other criteria also were added: a very small amount of bank 390 protection (proportion of river length  $\leq 20\%$  of the length of the sections or a length of bank 391 protection equal to 50 m, which corresponds to the minimum length of the protection since 392 the latter were informed on the scale of the cross-sections), and the presence of SEIs 393 immediately downstream of the sections equipped with bank protection. Logistic regression 394 models then were used to predict the mean and maximum erosion rates along each of the 395 sections identified as suitable for restoration.

396

397

**4. Results** 

399

# 4.1 Characteristics of planimetric erosion between 1959 and 2016

Mean and median bank retreat reached 0.0107 and 0.0067 m m<sup>-1</sup> year<sup>-1</sup>, respectively, when both banks were considered, and 0.012 and 0.0075 m m<sup>-1</sup> year<sup>-1</sup> when only concave banks were taken into account (Figure 2). The retreat rates showed a main break at kp 70.15 when both banks were considered and kp 69.8 when only concave banks were taken into account (Figure 3A). Downstream of these points, retreat rates were on average 4.1 and 2.7 times lower for both banks and concave banks, respectively. A less sharp break also occurred at kp 406 44.6. The reach upstream of this point had the highest retreat rates.

407

408



409

410 Figure 2 – Examples of active channel displacements from 1959 to 2016, and some of the
411 main current constraints of bed mobility. The reaches are numbered in ascending order from
412 upstream to downstream (with their location indicated between subfigures of reaches 1 and 2).
413

414 Between 1959 and 2016, bank erosion occurred on at least one bank along 380 415 discrete sections (comprising 40% of the river length). The 380 eroded sections have a mean-

416	median length of 130–100 m. The longitudinal pattern shows a main break at kp 71, very
417	close to the main break identified for the retreat rates (Figure 3B). Downstream of this point,
418	the percentage of eroded river length per km is 1.6-1.9 (mean-median) and 2.3-2.9 times
419	lower than upstream, when considering all banks or only concave banks, respectively.



Figure 3 – Longitudinal pattern of (A) planimetric retreat rates between 1959 and 2016, (B)
percentage of eroded river length and cumulative percentage of eroded river length between
1959 and 2016, (C) 2016 specific stream power for a discharge not exceeded 99% of the time,
(D) 2016 local curvature, (E) cumulative length of lateral constraints in 1959 and (F) bars,
alluvial riffles and rocky riffles in 2018.

- 426
- 427

#### 4.2 Bed confinement and space potentially available for channel shifting

In this section, the extent to which engineering works, the legacy of human activities, and SEIs identified in the valley bottom contribute to the current lateral confinement of the Cher is examined (see examples in Figure 2). The initial focus is on the river length affected by these constraints, then the focus shifts to the space potentially available for channel shifting.

- 432
- 433

# 4.2.1 Description and quantification of laterally constrained river length

434 The Cher River is a partially confined river based on criteria established by Fryirs et al. 435 (2016); 19.2% of its length is within 50 m of a terrace, alluvial or colluvial fan, or hillslope 436 (Figure 4A). Its mobility is, therefore, naturally constrained in many locations. If we add to 437 these natural constraints all the anthropogenic physical obstacles, the channel cannot shift 438 over 56% of its length (Figure 4A and Figure 5). Engineering works or legacy of human 439 activities are, therefore, responsible for a 2.9-fold increase in the length of the river along 440 which lateral erosion is now impeded. If we add to these 'primary' anthropogenic constraints 441 all of the SEIs identified in the alluvial plain <50 m from the banks, the length laterally 442 constrained reaches 63% (Figure 4A). Bank protection accounts for the largest proportion of 443 the constraints on lateral mobility, since they occupy 35.1% of the river length on either bank 444 (Figure 4A), followed by gravel pits at 10.9%. If only concave banks are considered, the 445 length along which the river cannot move laterally rises to 46.9% (compared with 15.6% for natural constraints alone) after all constraints are taken into account, and to 53.1% when SEIs
are added (Figure 4A). Bank protection occupies 29% of the total length, and gravel pits
account for another 6.1%.

449

450



Figure 4 – Boxplots of the current percentage of river length laterally constrained as a function of types of lateral constraints (A), current maximum space available for channel shifting as a function of types of lateral constraints (B), and current length of constrained and unconstrained reaches as a function of types of lateral constraints (C).

457 Despite important local variability, the longitudinal pattern of the different types of 458 constraints tends to be stable (Figure 5). For gravel pits, four main sections are nevertheless 459 visually identifiable (Figure 5). However, Hubert's segmentation (Hubert et al., 1989; Hubert, 460 2000) indicates only the upstream section (Figure 5). Although bank protection is present 461 along the entire length of the river, Hubert's segmentation highlights a long central reach that 462 is more densely equipped, extending from kp 21 to 76 (Figure 5). The reduced presence of 463 bank protection in the first 21 km of the study reach could be because a significant proportion 464 of the river length of this section had its course and banks artificially modified during gravel 465 mining. With the exception of two short peaks at the upstream and downstream ends of the 466 study reach, SEIs are distributed in a relatively regular and stable manner (Figure 5). The 467 constraints or constraints plus SEIs show a similar pattern, with maximum values for the first 468 16 km, a short section with very few constraints and/or SEIs (kp 17–20), then stability for the 469 rest of the length (Figure 5).

470



472

473 Figure 5 – Current longitudinal pattern of the percentage of river length laterally constrained
474 as a function of constraint types. Segmented data were obtained by applying the Hubert
475 method (Hubert et al., 1989; Hubert, 2000).

476

This foregoing reduction in river length along which bed migration is prevented is automatically accompanied by an increase in the longitudinal fragmentation of the bed (Figure 4C). The number of laterally unconstrained reaches is 99 when only natural constraints are considered, whereas it is 282 when all constraints are included. As a result, the 481 distance between two consecutive sections abutting against constraints decreases sharply;
482 1190–800 m (mean-median) with only natural constraints considered, compared with
483 227–150 m after incorporating anthropogenic constraints and 201–100 when SEIs are added
484 (Figure 4C). The length of laterally constrained sections varied much less; 285–200 m with
485 natural constraints, 290–200 m with all constraints and 330–200 m after incorporating all
486 SEIs (Figure 4C).

For concave banks alone, the number of sections without natural lateral constraints is 103 and 304 once anthropogenic constraints are incorporated (Figure 4C). The distance between two consecutive constrained reaches is 1195–850 m with natural constraints alone, 255–150 m once all constraints are incorporated, and 220–150 m with additional consideration of SEIs (Figure 4C). The length of constrained reaches is 220–200 m with natural constraints, 224–150 m with all constraints, and 249–150 m after addition of SEIs (Figure 4C).

494

#### 495

# 4.2.2 Space potentially available for channel shifting

The alluvial plain width (i.e,. the maximum space potentially available for channel shifting) is 707–678 m (mean-median; Figure 4B), and slightly lower upstream of the confluence with the Aumance River. However, the confinement index (ratio between the width of the alluvial plain and the width of the active channel) is higher in this upstream reach (18.3–17.6 vs. 14.3–13.7).

If all anthropogenic physical obstacles (bank protection, bridges, weirs, gravel pits) are added to the natural lateral constraints, the space potentially available for channel shifting decreases to 489–455 m (Figure 4B). This is equivalent to a reduction of 31–33%. After taking into account both constraints and SEIs, the space potentially available for channel shifting is only 330–267 m (i.e., a reduction of 53–61%; Figure 4B).

If we focus only on concave banks, the contraction of the maximum space potentially available for channel shifting is even larger. The maximum envelope shrinks from 281–221 m (mean-median) to 168–61 m when anthropogenic constraints are taken into account (i.e., a reduction of 41–73%; Figure 4B). After incorporating SEIs, the maximum space potentially available for channel shifting is then only 111–43 m, equivalent to a reduction of 61–81% (Figure 4B).

Regardless of the type of anthropogenic constraints considered, the longitudinal pattern of space potentially available for channel shifting remains relatively stable despite significant local variations (Figure 6). Moreover, the integration of anthropogenic constraints tends to homogenize this longitudinal variability.



517

Figure 6 – Current longitudinal pattern of the space potentially available for channel shifting
as a function of the types of constraints. For the sake of readability, data have been
'smoothed' using Hubert's segmentation method (Hubert et al., 1989; Hubert, 2000).

521

# 522

# 4.3 Factors controlling the intensity and location of lateral erosion

523 The longitudinal pattern of the specific stream power shows local variations that can 524 be high, but no overall tendency to decrease or increase (Mann-Kendall test, p > 0.1; Figure 525 3C). One of the main causes of these variations is the existence of many weirs, which results 526 in a strong reduction of specific stream power in their reservoirs, and an even more marked 527 increase immediately downstream. The decrease in erosive activity observed from about kp 528 70 during the 1959–2016 period (Figure 3A, B) is, therefore, not the result of an associated decrease in specific stream power. Regarding curvature, a main break is visible at kp 39.6, 529 530 just downstream of the junction with the Aumance River, with a two-fold diminution of 531 curvature values (Mann-Whitney test, p < 0.05; Figure 3D). This could explain the second 532 highest decrease in retreat rates, reported from kp 44.6. For lateral constraints in 1959, a 533 twofold decrease is observed downstream of the main break, located at kp 24.45 (Figure 3E). 534 On both sides of this point, lateral constraints are quite regularly distributed. There is 535 nevertheless an important uncertainty regarding the density of lateral constraints in 1959 536 along this upstream reach; most of this reach has been artificially redesigned due to gravel 537 mining in the 1970's, and it is not known to what extent bank protection was present before. 538 The reduced presence of bank protection in the first 24 km of the study reach could thereby 539 result from a significant proportion of the river length in this section having its course and banks artificially modified during gravel mining. In any case, there is no spatial 540 541 correspondence between the longitudinal patterns of erosive activity during the 1959–2016 542 period and of lateral constraints in 1959 (or even in 2016, see Figure 5).

The 2018 longitudinal pattern of bars, alluvial riffles, rocky riffles, and bedrock sections indicates two main reaches (Figure 3F); in the upstream reach, bars and alluvial riffles are frequent, while rocky riffles and bedrock sections are rare, and this trend is reversed in the downstream reach. For bars and alluvial riffles, the main break, located at kp 72.8 and 72.7, respectively, is slightly downstream of the break in erosive activity (kp 70). The mean spacing between bars and between alluvial riffles, therefore, increases from 6.3 to 23.8 bankfull widths for the former and from 10.6 to 36.8 bankfull widths for the latter (Mann-Whitney test, 550 p < 0.05; Figure 3F). In addition, for alluvial riffles, the upstream reach can be divided into 551 two sub-reaches with a limit located at kp 34.9, with a mean spacing of 8.9 bankfull widths upstream and 13.5 bankfull widths downstream (Mann-Whitney test, p < 0.05). For rocky 552 553 riffles, the break is located at kp 85.5 (Figure 3F). The mean spacing between rocky riffles 554 decreases significantly from upstream to downstream, from 110 to 13.8 bankfull widths 555 (Mann-Whitney test, p < 0.05). For bedrock sections, the limit is located at kp 84.5 (Figure 556 3F). Upstream, the mean length of bedrock sections and the distance between two consecutive 557 sections are 5.6 and 62 bankfull widths, respectively. Downstream, they are 9.6 and 23.4 558 bankfull widths.

559 Examined at the cross-section scale, the influence of specific stream power on the manifestation of erosion appears to be absent; in the absence of lateral constraints and when 560 both banks are considered, the mean specific stream power is 22.7 W  $m^{-2}$  and 22.3 W  $m^{-2}$  for 561 562 cross-sections with and without erosion, respectively (Mann-Whitney test, p = 0.83; Figure 7A). Focusing on concavities alone, the mean stream power is 22.8 W m<sup>-2</sup> and 21.7 W m<sup>-2</sup> 563 564 (Mann-Whitney test, p = 0.1; Figure 7A). Conversely, local curvature probably exerts a 565 significant influence since they are 1.8 times higher on cross-sections with erosion when both 566 banks are considered and 1.6 times higher when considering concave banks alone (Mann-567 Whitney test, p < 0.000001; Figure 7A). Finally, for cross-sections subjected to erosion, no 568 correlation was detected between the normalized retreat rate on the one hand, and the specific 569 stream power or the local curvature on the other hand (Figure 7B).



Figure 7 – Comparison of specific stream power for a discharge not exceeded 99% of the time
and of curvature between eroded and non-eroded unconstrained cross-sections (A). Relation
between the normalized annual retreat rate and the specific stream power for a discharge not
exceeded 99% of the time and the curvature of eroded cross-sections (B).

576

571

577 Lateral constraints play a major role in the expression of lateral erosion. Indeed, there 578 was a statistically significant difference in erosion between constrained and unconstrained 579 banks (Chi-square test, p < 0.00001; Table 2); 67% of cross-sections with erosion are located 580 where constraints are absent, while 60% of cross-sections without erosion are located where 581 constraints are present. Furthermore, 72% of cross-sections subjected to lateral constraints escape erosion, and the proportion drops to 46% for cross-sections not influenced by lateral constraints. If we consider only concave banks, the role of constraints appears even more significant since 83% of eroded cross-sections are located where constraints are absent and 90% of cross-sections subjected to lateral constraints escape erosion.

586

587 Table 2 – Presence-absence of lateral constraints and lateral erosion on cross-sections spaced

588 50 m apart. Statistical differences were determined using the Chi-square test.

	Lateral constraints	No lateral constraints	<i>p</i> -value
Right or left bank			
Erosion	260	524	<0,00001
No erosion	656	442	
Concave banks			
Erosion	79	717	<0,00001
No erosion	703	383	

589

590

591

# 4.5 Preservation and restoration of lateral mobility: priority elements

The developed logistic regression models provide a relatively good explanation of the concave bank retreat rates between 1959 and 2016 on sections prioritized for preservation of lateral mobility (Table 3 ; Figure 8). Just over 50% of the variance in retreat rates is explained by the maximum specific stream power and the mean local curvature along the sections, with both variables playing a significant role (Table 3). The equations for the prediction of the maximum (Eq.1) and the mean (Eq.2) retreat rates are:

598	Logit (Maximum annual normalized retreat rates) =
599	$-4.107 + 0.02562 \times$ maximum specific stream power + 3728 $\times$ mean curvature
600	(Eq.1)
601	
602	Logit (Mean annual normalized retreat rates) =
603	$-5.279 + 0.03772 \times$ maximum specific stream power + 4784 $\times$ mean curvature
604	(Eq.2)
605	
606	
607	Table 3 – Logistic (logit) regression coefficients explaining the maximum annual normalized
608	retreat rates (m m <sup>-1</sup> year <sup>-1</sup> ) and the mean annual normalized retreat rates (m m <sup>-1</sup> year <sup>-1</sup> ) as a
609	function of maximum specific stream power (W m <sup>-2</sup> ) and mean curvature (rad m <sup>-1</sup> m <sup>-1</sup> ) (R <sup>2</sup> =
610	Coefficient of determination).

	Coefficient	Standard error	t	<i>p</i> - value	Pseudo-R <sup>2</sup> (Cox and Snell)
Logit (Maximum annual normalized retreat rates)					
Interception	-4.107	0.1678	- 24.48	***	
1959 maximum specific stream power	0.02564	0.005298	4.84	***	0.53
1959 mean curvature	3728	1602	2.33	*	
Logit (Mean annual normalized retreat rates)					
Interception	-5.279	0.2499	- 21.13	***	
1959 maximum specific stream power	0.03772	0.007577	4.98	***	0.52

1959 mean curvature478423362.05

611

612 p-values \*\*\* = 0, \* = 0.01, . = 0.05.

613



614

Figure 8 – Relations between predicted and observed retreat rates for concave banks between
1959 and 2016 along unconstrained sections identified as a priority for preservation of lateral
mobility.

618

619 If the preservation and restoration sections have similar predicted retreat rate values, 620 they show a clear difference in the length and the space available for river shifting, with 621 preservation sections significantly having shorter length but larger space for river shifting 622 (Figure 9).



623

Figure 9– Length versus available space for river shifting on the concave side, and predicted
mean concave retreat rates along sections identified as a priority for preservation or
restoration of lateral mobility.

Twenty-four sections of the river are of particular interest in terms of preserving lateral mobility (Figure 10). They extend over a total length of 9.3 km (6.3% of the length of the study reach). Most are located upstream, between kp 15.9 and 69 (20 sections out of 24 and 84.3% of the total length of the sections), consistent with the decrease in erosive activity identified downstream of kp 70 (Figure 10).

633 After elimination of sections of less interest from the point of view of restoring river 634 lateral dynamics, 30 sections remain from the initial 112, extending over 69.2 km, 45.9% of 635 which have bank protection (Figure 10). These 30 sections represent a total length of 28.6 km, 636 or 19.7% of the length of the study reach, and bank protection occupies 11.3 km, namely 637 39.3% of the total length of the 30 sections. Compared with the conservation sections, the 638 restoration sections are more evenly distributed along the study area (Figure 10), but there is 639 also a high concentration of these restoration sections upstream; 12 of the 30 restoration 640 sections are located between kp 26.6 and 48.6, over 20 km (15.1% of the study reach length). 641 Moreover, these 12 sections represent 76.9% of the total length of the restoration sections.





642

Figure 10 – Localization and characteristics of sections identified as a priority for
preservation or restoration of lateral mobility. The predicted retreat rates were computed from
equations in Table 3, with 2016 values for specific stream power and curvature.

648

# 649 **5. Discussion**

650

# 5.1 Performance of logistic regression models

651 The logistic regression models developed for reaches of high interest for preserving or 652 restoring lateral mobility explain slightly more than 50% of the variance in the maximum or 653 mean lateral erosion between 1959 and 2016 (Pseudo-R<sup>2</sup> in Table 3). Other controlling factors 654 not considered here (maximum specific power in 1959 and mean curvature in 1959) should, 655 therefore, be considered. They were not included in the model due to insufficient data. The 656 first such controlling factor is heterogeneity of bank strength, driven by bank height and 657 morphology, the type of vegetation covering banks (e.g. Ielpi and Lapôtre, 2020; Horton et 658 al., 2017; Micheli and Kirchner, 2002; Micheli et al, 2004; Piégay et al., 2003), and the spatial 659 heterogeneity of the alluvial infill material (e.g., Bogoni et al., 2017; Constantine et al., 2009; 660 Fisk, 1944, 1947; Güneralp and Rhoads, 2011; Motta et al., 2012). The second controlling 661 factor is the spatial variability in the bedload supply, a major driver of lateral mobility in 662 meandering streams (Ahmed et al., 2019; Constantine et al., 2014; Donovan et al., 2021; 663 Dunne et al., 2010; Rollet and Piégay, 2013). The third controlling factor is the bed material D<sub>50</sub>, theoretically conversely correlated with bank retreat (Bledsoe and Watson, 2001; Richard 664 665 et al., 2005). The fourth controlling factor is the effect of lateral constraints on contiguous 666 river sections devoid of such constraints, where bank erosion can be inhibited/prevented or, 667 conversely, promoted. The fifth controlling factor is gravel mining in the riverbed that can 668 increase lateral erosion by destabilizing banks (Schumm et al., 1984; Simon, 1989; Simon and 669 Rinaldi, 2006; Watson et al., 2002), and the presence of undetected blocks of former bank 670 protection located in the riverbed that can conversely slow bank retreat (Dépret et al., 2017).

671 Compared with similar analyses that attempted to explain and/or predict lateral erosion 672 of meandering rivers computed from sequential aerial photographs through statistical 673 modelling at decadal or multi-decacal scales, the percentage of explained variance in the 674 current study can be considered more satisfactory. For example, in four reaches of the Rio 675 Grande River, U.S., Richard et al. (2005) obtained coefficients of determination (R<sup>2</sup>) between 676 0.43 and 0.93 explaining absolute migration rates with parameters representing flow energy used alone (either the mobility index of Bledsoe and Watson [2001], channel forming-677 678 discharge, total stream power, or specific stream power) or in combination with a planform 679 index. For 18 sites located in British Columbia and Alberta, Canada, Nandon and Hickin 680 (1986) explained 70% of the variance of the volume of laterally eroded sediment from the 681 outer banks using river size and grain size at the bank toe. In a regional analysis of migration 682 rates of single-thread rivers mainly located in the Rhône River basin, France, Alber and 683 Piégay (2017) explained 45% of the variability in migration rates using total stream power.

684 From a predictive and, thus, an operational point of view, one of the main drawbacks 685 of the proposed models is that they cannot take into account the role of future hydrological 686 variability, and, thus, the effects of ongoing climate change (Buffin-Bélanger et al., 2015). 687 Long-term predictive values of retreat rates estimated through the logistic regression models 688 could therefore be largely under- or overestimated depending on flood regime evolution. The 689 only study dealing with evolution of the flood regime in the Loire Basin according to different 690 climate change scenarios focused on maximum annual daily discharge with a 10-year return 691 period (Moatar et al., 2010a, 2010b). Because of a too high level of uncertainty, it is 692 impossible to predict future changes. Nevertheless, it is worth mentioning because lateral 693 erosion on the Cher River is mainly controlled by low-magnitude events (Dépret et al., 2015), 694 hence any changes in the occurrence frequency and/or duration of such common floods could 695 strongly affect lateral mobility.

696

697

#### 5.2 The issue of self-maintenance of river course migration

In this study, reaches with a significant shifting potential for preservation or 698 699 restoration were located and prioritized (Figure 10). However, self-maintenance of mobility 700 was not considered, even though it is a key influencer of the success of restoration operations 701 (Kondolf, 2011). Self-maintenance is mainly dependent on sufficient bedload mobility and 702 supply (Ahmed et al., 2019; Constantine et al., 2014; Donovan et al., 2021; Dunne et al., 703 2010). This supply, whether from upstream or from local reinjection resulting from bank 704 erosion, promotes point bar fattening, which then increases tractive forces toward the opposite 705 concave banks, ultimately sustaining lateral erosion processes (Dietrich and Smith, 1983, 706 1984; Dietrich et al., 1979; Legleiter et al., 2011). Local reinjection of coarse sediment 707 following bank erosion is considered a major driver of lateral instability (Braudrick et al., 708 2009). This material is indeed partly redistributed onto the immediate downstream point bar 709 (Pyrce and Ashmore, 2003a, 2003b, 2005), the development of which promotes lateral 710 erosion on the opposite bank as previously explained. This creates a negative feedback loop, 711 with bed migration maintained from near to far in the downstream direction. A reduction in 712 coarse alluvial stock should thus be associated with a weakening of lateral erosive dynamics.

713 It was found that the Cher River could be separated into two sub-reaches with very 714 distinct profiles in terms of the abundance of bars and alluvial riffles (Figure 3F). Whereas 715 upstream of kp 73, bars and alluvial riffles are very frequent, they become very scarce 716 downstream in favor of rocky riffles and bedrock reaches (Figure 3F). If we consider that this 717 dichotomy reflects a marked difference in available bed-material load, and, thus, in bedload, 718 and knowing that the specific stream power and curvature are not higher downstream (Figure 719 3C), it would be expected that the self-maintenance of the lateral erosion processes should be 720 much more limited along the downstream sub-reach. This hypothesis would be confirmed, on 721 the one hand, by retreat rates and the percentage of eroded river length from 1959 to 2016 that 722 were significantly higher upstream of about kp 70 (Figure 3A and Figure 3B), and on the

other hand, by the percentage of river length with lateral constraints that does not increase
downstream (Figure 3E). Following this reasoning, restoration of lateral mobility by
removing bank protection would be less suitable on the downstream sub-reach.

726 This assumed lack of bedload in the downstream sub-reach could be the result of excessive sediment mining in the riverbed from the 1960s to the 1980s (Dépret, 2014; Dépret 727 728 et al., 2021). However, these sediment extractions also were very significant in the upstream 729 sub-reach (Dépret, 2014). This explanation must, therefore, be at least partially rejected. The 730 lower availability of coarse sediment downstream could, thus, be due to inheritance, and be 731 explained by the decrease in the size and volume of coarse alluvium downstream. There is 732 evidence to support this postulation. First, the percentage of particles larger than 5 mm 733 (roughly the subsurface  $D_{50}$  (Dépret, 2014) in the alluvial infilling decreases significantly 734 from upstream to downstream. Above 40% between Montluçon and the Aumance junction 735 (from kp 0 to kp 37.1), it is ~25% at Saint-Amand-Montrond (kp 61.4), 15% at Châteauneuf-736 sur-Cher (kp 88.85), 10% at Saint-Florent-sur-Cher (kp 108.8), and 5% at Brinay (kp 136.4), 737 slightly upstream of Vierzon (Figure 1) (BRGM-CETE de Lyon, 1979; Debrand-Passard et 738 al., 1977b; Turland et al., 1989c). A report on the survey of potential sand and gravel deposits 739 in the alluvial infill in the Cher River valley from Saint-Amand-Montrond also mentions a 740 fining of gravel between Saint-Amand-Montrond and Vierzon (kp 61.4 and 145.7) (Bos and 741 Trautmann, 1970). A similar downstream trend would apply to the thickness of coarse 742 sediment. The findings of another study aimed at identifying deposits of exploitable 743 aggregates in the alluvial plain of the Cher (CETE of Rouen, 1972) provide information in 744 particular, on the average thickness of coarse alluvium between La Perche (kp 45.55) and 745 Saint-Florent-sur-Cher (kp 108.8). Referred to as 'gravelly sands', their thickness would be 746 4.2 m between kp 45.55 and 55, 4.1 m between kp 55 and 69, 3.6 m between kp 69 and 87, 747 and 2.3 m between kp 87 and 105.2. These data tend to confirm the existence of a relatively

10.748 limited coarse alluvial stock in the downstream sub-reach. For this reason, riverbed mining 1749 could have had a greater impact here than in the upstream sub-reach. More broadly, this 1750 reduced stock of coarse sediment limits the reinjection of coarse sediments into the riverbed 1751 following bank erosion, with a consequent limited capacity for self-maintenance of lateral bed 1752 instability compared to the upstream sub-reach.

On the Cher River, the mechanisms for self-maintenance of bed migration dynamics also are most likely partially impeded due to livestock access to the riverbed. Along the study area, most of the proximal alluvial plain surface is devoted to sheep or cattle grazing. This has the effect of inhibiting or even preventing the development of vegetation on convex bars. Yet, such vegetation encroachment processes promote concave bank erosion (Bywater-Reyes et al., 2018; Zen and Perona, 2020). Thus, free access of livestock to the river likely diminishes lateral mobility of the Cher River.

Finally, regarding the removal of bank protections, one of the main uncertainties regarding the morphological evolution of sections relies on the sustainability of erosive activity. Such management actions would imply bed widening, and thus a likely decrease in specific stream power that could in turn lead to a decrease in the potential for lateral erosion.

- 764
- 765

# 5.3 Lateral constraints, sediment connectivity and lateral mobility

The mean and median length of constrained and unconstrained concave bank reaches were calculated to be 224–150 m and 255–150 m, respectively, hence decadal-scale bedload displacement velocities would be between 30 and 300 m per decade (Dépret et al., 2021). This means that coarse sediment connectivity between successive unconstrained reaches would likely be very limited, if not absent, at the decadal or even multi-decadal scale. This also implies that at this timescale, sediment reinjected into the bed by lateral erosion in a given unconstrained reach would not be deposited along the unconstrained reach immediately downstream, and, would, therefore contribute little or nothing to the downstream maintenance of lateral dynamics. Furthermore, whereas lateral constraints, particularly bank protection, obviously prevent lateral erosion on reaches along which they are present, they would also indirectly limit the intensity of lateral erosion on reaches along which they are absent by reducing the sediment supply.

- 778
- 779

#### 5.4 Prospects for improving the ecological status of the Cher River

780 Along the study reach, the ecological status of the river according to the WFD 781 reference is considered poor upstream of the confluence with the Aumance River and 782 moderate downstream (https://qualite-riviere.lesagencesdeleau.fr/; Figure 1). However, the 783 WFD requires that good ecological status be reached. In the context of general coarse 784 sediment starvation in rivers, resulting in damaged ecological functioning, river restoration 785 strategies aimed at increasing the coarse sediment supply either by gravel augmentation or 786 trough re-establishing space for channel shifting are becoming more popular (e.g., Arnaud et 787 al., 2017; Bravard et al., 1999; Biron et al., 2014; Gaeuman, 2012; Kondolf, 2011; 788 Rheinheimer and Yarnell, 2017; Rinaldi et al., 2011, Staenzel et al., 2020; Williams et al., 789 2020). Such actions promote longitudinal and cross-wise topographic as well as grain size 790 heterogeneity, both of which increase the diversity of habitat, particularly aquatic habitat 791 (Gaeuman, 2012; Yarnell et al., 2006; Hauer et al., 2018; Staenzel et al., 2020). Moreover, 792 shifting riverscape mosaic processes caused by lateral mobility of rivers facilitates riparian 793 succession associated with pulse disturbance (e.g., Diaz-Redondo et al., 2018; Gonzalez del 794 Tanago et al., 2021; Hauer et al., 2016; Stanford et al., 2005; Tockner et al., 2010).

795 If it is assumed that the unsatisfactory ecological status of the Cher River is at least 796 partly the result of the strong direct anthropogenic constraints exerted on the lateral mobility 797 of the river, no improvement in ecological status is likely to be achieved without restoration 798 of this mobility. However, it has been revealed that such restoration only concerns a relatively 799 limited number of sections (Figure 10). Furthermore, the low bedload velocity (Section 5.3) 800 indicates that most of the coarse sediment reinjected in the riverbed by lateral erosion would 801 remain at a decadal scale in close proximity to the eroded banks. This implies that only a local 802 increase in the heterogeneity of aquatic and riparian habitat could be achieved through such 803 injections. The effects of management actions aimed at restoring lateral mobility would, thus, 804 be spatially limited. Therefore, questions remain to what extent such local diversification 805 could impact the biodiversity of constrained sections located upstream and downstream of 806 restored sections. With this in mind, there appears to be little possibility of achieving good 807 ecological status along the entire length of the river through removal of bank protection. 808 Furthermore, uncertainty remains on the timescale needed for the morphological effects of the 809 removal of protections to be felt. Because the erosive process is relatively slow it could take 810 several years, or even longer, before these actions achieve the desired effect. Such a time-811 scale does not comply with the needs of managers to obtain ecological improvements in the 812 short term. Due to these spatial and temporal limitations, it might be more productive to 813 implement a combination of rip-rap removal with a series of gravel augmentations close to 814 each other.

815

5.5 Applicability and reproducibility of the method for meandering gravel-bed rivers
The main principles guiding our methodological approach involve some key elements
of previous work through which are identified and delineated the alluvial plain, the historical
trajectory of the river course, the zone potentially prone to lateral erosion in the near future
(upcoming decades), as well as SEIs in order to preserve an erodible corridor in the alluvial
plain (e.g., Malavoi et al., 1998; Piégay et al., 1997, 2005; Biron et al., 2014). However, our
methodological framework differs from these previous studies; in addition to enabling the

823 detection of river sections along which bank erosion, and thus an erodible corridor, could be 824 preserved, it also focuses on whether and where lateral mobility could be restored. The 825 different steps of the method, replicable regardless of the energy of meandering gravel-bed 826 rivers, are (1) assessment of bed mobility over recent decades; (2) identification of the lateral constraints (natural and anthropogenic) to lateral mobility and SEIs in the floodplain; (3) 827 828 quantification and location of their effects on the available space for river shifting; (4) 829 determination of the relationship (through regression) between retreat rates and their 830 controlling factors along river sections without constraints; (5) delimitation of sections where 831 lateral constraints could be removed; (6) application of the regression developed in step 4 to 832 reaches identified in step 5; (7) prioritisation of preservation and restoration sections 833 according to a combination of criteria defined in accordance with river managers (i.e., 834 predicted retreat rates, length of river sections, and width of the remaining space for river 835 shifting).

836 This approach, when applied alongside information on bedload transport and 837 availability, could facilitate defining the most suitable and sustainable restoration actions in 838 terms of sediment budgeting and sediment exchanges between the river and its floodplain. 839 Along any river corridor, three management options are available and can be combined 840 depending on the intensity of constraints and SEIs, and the potential of the river for lateral 841 mobility: removal of constraints, gravel augmentation, and combining these two. While all 842 three options are suitable in the case of sediment starvation, and thus enable the enhancement 843 of aquatic habitats (e.g., Chardon et al., 2021; Mörtl and De Cesare, 2021), removal of lateral 844 constraints is the only measure that simultaneously promotes the improvement of riparian 845 habitats (e.g., Larsen et al., 2006). For this reason, removal of lateral constraints is thus a 846 relevant management action regardless the existence of any sediment deficit. More broadly, 847 such removal is also directly related to other issues since it can promote, for instance, a local and downstream reduction in flood hazard by increasing water storage in the floodplain during high-flow periods (Arnaud-Fassetta et al., 2009; Benito and Vázquez-Tarrío, 2022). Finally, the robustness of our approach could be enhanced by integrating into the erodible corridor different flooding zones as proposed by Biron et al. (2014) in their definition of freedom space, since the ecological integrity of rivers is also governed by maintenance of the surface and subsurface hydrological connectivity between riverbed and floodplain (Amoros and Bornette, 2002).

855

# 856 **6. Conclusions**

857 The results of the current study allowed the very strong fragmentation of the Cher 858 River to be highlighted and quantified. Most of the river is laterally constrained due to the 859 presence of anthropogenic structures such as bank protection, former gravel pits in the alluvial 860 plain, bridges, and weirs. Today, the Cher River is composed of a string of constrained and 861 unconstrained reaches, and its available space for channel shifting has been strongly reduced. Because of the fluvial engineering works and anthropogenic legacies, most of the potential for 862 863 lateral movement of the riverbed, and, therefore, diversification of the riparian and aquatic 864 habitat, has been lost. Due 1) to the very low proportion of the river length with lateral 865 mobility that could be preserved or restored, such restoration can only be done by removal of 866 bank protection where possible, 2) to the very likely local effects of restoration of the lateral 867 mobility, and assuming that the unsatisfactory ecological status of the Cher River is at least 868 partly the result of the strong, direct anthropogenic constraints exerted on the lateral mobility 869 of the river, the probability that a good ecological status can be achieved along the entire river 870 length by removal of bank protection is very low. For these different reasons, implementation 871 of rip-rap removal combined with a series of gravel augmentations close to each other could 872 help toward achieving good ecological status along the entire length of the Cher River.

873 This research has expanded the understanding of how the morpho-sedimentary 874 functioning of a low-energy, gravel-bed river can be impaired by current and past direct 875 anthropogenic constraints, and how to determine the river's recovery potential. However, 876 characterizing the factors controlling the diversity of biotopes and biocenoses through the 877 hydrosedimentary dynamics of such rivers remains challenging. On these rivers, and unlike 878 high-energy rivers, morphogenic processes occur at a relatively reduced intensity and at 879 moderate velocities. For this reason, the effects of direct anthropogenic constraints on the 880 degree of habitat heterogeneity and biodiversity may be much less pronounced than for high-881 energy rivers. Conversely, the morpho-sedimentary response time of the system to the 882 removal of these constraints could be relatively long. The links between alteration of 883 hydrosedimentary dynamics and biotope degradation, therefore, require further clarification.

884

885

# 886 Acknowledgements

The current research was done within the framework of the *Plan Loire Grandeur Nature*. It was funded by the European Regional Development Fund *Bassin de la Loire* and the *Agence de l'Eau Loire-Bretagne*. The authors thank Dominique Dépret and Bruno Dépret for their invaluable help in the field survey, and Lise Vaudor for her assistance with logistic regression. Finally, the authors are very grateful to the editor and the two reviewers for their very helpful comments that greatly improved the overall quality of the paper.

893

894

# 895 **References**

Ahmed, J., Constantine, J.A., Dunne, T., 2019. The role of sediment supply in the adjustment
of channel sinuosity across the Amazon Basin. Geology 47 (9), 807–810.

898	Alber, A., Piégay, H., 2017. Characterizing and modelling river channel migration rates at a
899	regional scale: Case study of south-east France. J. Environ. Manage. 202 (2), 479-493.
900	Amoros, C., Bornette, G., 2002. Connectivity and biocomplexity in waterbodies of riverine
901	floodplains. Freshwater Biology 47, 761–776.
002	Arnoud F. Diágov H. Báol D. Collory P. Voudor I. Pollot A. J. 2017 Monitoring
902	Amadu, F., Flegay, M., Beal, D., Cohery, F., Vaudor, L., Kohet, A.J., 2017. Moliholing
903	gravel augmentation in a large regulated river and implications for process-based
904	restoration. Earth Surf. Process. Landf. 42 (13), 2147-2166.
905	Arnaud-Fassetta, G., Astrade, L., Bardou, E., Corbonnois, J., Delahaye, D., Fort, M., Gautier,
906	E., Jacob, N., Peiry, J.L., Piégay, H., Penven, M.J., 2009. Fluvial geomorphology and
907	flood-risk management. Géomorphologie : relief, processus, environnement 15 (2), 109-
908	128.
909	

- Baudrick, C.A., Dietrich, W.E., Leverich, G.T., Sklar, L.S., 2009. Experimental evidence for
  the conditions necessary to sustain meandering in coarse-bedded rivers. Proc. Natl.
  Acad. Sci. U.S.A. 106 (40), 16936–16941.
- Basak, S.M., Hossain, M.S., Tusznio, J., Grodzińska-Jurczak, M., 2021. Social benefits of
  river restoration from ecosystem services perspective: A systematic review. Environ. Sci.
  Policy 124, 90–100.
- Beechie, T.J., Sear, D.A., Olden, J.D., Pess, G.R., Buffington, J.M., Moir, H., Roni, P.,
  Pollock, M.M., 2010. Process-based Principles for Restoring River Ecosystems.
  BioScience 60 (3), 209–222.
- Benito, G., Vázquez-Tarrío, D., 2022. Hazardous Processes: Flooding. In Shroder, J.F.,
  James, A., Harden, C.P., and Clague, J.J., (Eds.), Treatise on Geomorphology,
  Anthropogenic Geomorphology, Edition 2, Chapter 9.30. Academic PressEditors, pp.
  715–743.

923	Biron, P.M., Buffin-Bélanger, T., Larocque, M., Choné, G., Cloutier, C.A., Ouellet, M.A.,
924	Demers, S., Olsen, T., Desjarlais, C., Eyquem, J., 2014. Freedom Space for Rivers: A
925	Sustainable Management Approach to Enhance River Resilience. Environ. Manage. 54,
926	1056–1073.

- Bledsoe, B.P., Watson, C.C., 2001. Logistic regression of channel pattern thresholds:
  meandering, braiding and incising. Geomorphology 38, 281–300.
- Bogoni, M., Putti, M., Lanzoni, S., 2017. Modeling meander morphodynamics over selfformed heterogeneous floodplains. Water Resour. Res. 53 (6), 5137–5157.
- 931 Borgwardt, F., Robinson, L., Trauner, D., Teixeira, H., Nogueira, A.J.A., Lillebø, A.I., Piet,
- 932 G., Kuemmerlen, M., O'Higgins, T., McDonald, H., Arevalo-Torres, J., Barbosa, A.L.,
- 933 Iglesias-Campo, A., Hein, T., Culhane, F., 2019. Exploring variability in environmental
- 934 impact risk from human activities across aquatic ecosystems. Sci. Total Environ. 660,935 611–621.
- Bos, P., Trautman, F., 1970. Etude des gisements potentiels de sables et graviers de la vallée
  du Cher de Saint-Amand-Montrond (Cher) au confluent avec la Loire. BRGM.
- Bravard, J.P., Landon, N., Peiry, J.L., Piégay, H., 1999. Principles of engineering
  geomorphology for managing channel erosion and bedload transport, examples from
  French rivers. Geomorphology 31, 291–311.
- 941 BRGM CETE de Lyon, 1979. Synthèse et interaction des ressources en granulats et eaux
  942 souterraines dans la vallée du Cher et sur la zone granitique de Montluçon.
- 943 Brown, A.G., Lespez, L., Sear, D.A., Macaire, J.J., Houbend, P., Klimek, K., Brazier, R.E.,
- 944 Van Oost, K., Pears, B., 2018. Natural vs anthropogenic streams in Europe: History,
- 945 ecology and implications for restoration, river-rewilding and riverine ecosystem services.
- 946 Earth Sci. Rev. 180, 185–205.

947	Buffin-Bélanger, T., Biron, P.M., Larocque, M., Demers, S., Olsen, T., Choné, G., Ouellet,
948	M.A., Cloutier, C.A., Desjarlais, C., Eyqueme, J., 2015. Freedom space for rivers: An
949	economically viable river management concept in a changing climate. Geomorphology
950	251, 137–148.

- Bywater-Reyes, S., Diehl, R.M., Wilcox, A.C., 2018. The influence of a vegetated bar on
  channel-bend flow dynamics. Earth Surf. Dyn. 6, 487–503.
- 953 CETE de Rouen, 1972. Recherches de matériaux dans la vallée du Cher. Note technique.
- Chardon, V., Schmitt, L., Arnaud, F., Piégay, H., Clutier, A., 2021. Efficiency and
  sustainability of gravel augmentation to restore large regulated rivers: Insights from three
  experiments on the Rhine River (France/Germany). Geomorphology, 107639.
- 957 Choné, G., Biron, P.M., 2016. Assessing the Relationship Between River Mobility and
  958 Habitat. 32 (4), River Res. Appl. 528–539.
- Ciotti, D.C., Mckee, J., Pope, K.L., Kondolf, G.M., Pollock, M.M., 2021. Design Criteria for
  Process-Based Restoration of Fluvial Systems. BioScience 71 (8), 831–845.
- 961 Constantine, C.R., Dunne, T., Hanson, G.J., 2009. Examining the physical meaning of the
  962 bank erosion coefficient used in meander migration modeling. Geomorphology 106,
  963 242–252.
- 964 Constantine, J.A., Dunne, T., Ahmed, J., Legleiter, C., Lazarus, E.D., 2014. Sediment supply
  965 as a driver of river meandering and floodplain evolution in the Amazon Basin. Nature
  966 Geoscience 7, 899–903.
- 967 Cossalter, F., 2011. Des carrières alluviales aux captures dans la vallée du Cher. Analyses
  968 spatiales et méthodes de mesures des impacts hydrologiques et sédimentaires. Master 2
  969 thesis in Geography, Paris 1 Panthéon-Sorbonne University.
- 970 Cox, D.R., Snell, E.J., 1989. Analysis of Binary Data. Second Edition. Chapman & Hall.

- 971 Culhane, F., Teixeira. H., Nogueira, A.J.A., Borgwardt, F., Trauner, D., Lillebø, A., Piet, G.,
- 972 Kuemmerlen, M., McDonald, H., O'Higgins, T., Barbosa, A.L., van der Wal, J.T.,
- 973 Iglesias-Campos, A., Arevalo-Torres, J., Barbière, J., Robinson, L.A., 2019. Risk to the
- 974 supply of ecosystem services across aquatic ecosystems. Sci. Total Environ. 652, 1396–
  975 1408.
- 976 Debrand-Passard, S., Lablanche, G., Flamand, D., Soulas, J.P., 1977a. Carte géol. France
  977 (1/50000), feuille Bourges (519). Orléans : BRGM.
- 978 Debrand-Passard, S., Lablanche, G., Flamand, D., Soulas, J.P., 1977b. Notice explicative,
  979 Carte géol. France (1/50000), feuille Bourges (519). Orléans : BRGM.
- Debrand-Passard, S., Lablanche, G., Medioni, R., Flamand, D., Audebourg, B., Petitfils, B.,
  Martin, B., 1978. Carte géol. France (1/50000), feuille Vatan (518). Orléans : BRGM.
- 982 Dépret, T., 2014. Fonctionnement morphodynamique actuel et historique des méandres du
  983 Cher. Ph. Thesis, Paris 1 Panthéon-Sorbonne University.
- Dépret, T., 2021. REASED. Réajustements morpho-sédimentaires du Cher aux contraintes
  anthropiques actuelles et passées. Résilience et perspectives de restauration. Rapport
  final & recommandations opérationnalles, 93 p.
- Dépret, T., Gautier, E., Hooke, J., Grancher, D., Virmoux, C., Brunstein, D., 2015.
  Hydrological controls on the morphogenesis of low-energy meanders (Cher River,
  France). J. Hydrol. 531, 877–891.
- Dépret, T., Gautier, E., Virmoux, C., Gob, F., Piégay, H., Mesmin, E., Doncheva, M.,
  Plaisant, B., Ghamgui, S., Clocet, O., Peyret, A., 2021. REASED Réajustements
  morpho-sédimentaires du Cher aux contraintes anthropiques actuelles et passées,
  Résilience et perspectives de restauration. Rapport final et recommandations
  opérationnelles. Rapport (95 pp.).Dépret, T., Gautier, E., Hooke, J., Grancher, D.,

- 995 Virmoux, C., Brunstein, D., 2017. Causes of planform stability of a low-energy
  996 meandering gravel-bed river (Cher River, France). Geomorphology 285, 58–81.
- Diaz-Redondo, M., Marchamalo, M., Egger, G., Magdaleno, F., 2018. Toward floodplain
  rejuvenation in the middle Ebro River (Spain): From history to action. Geomorphology
  317, 117–127.
- Dietrich W.E., Smith J.D., 1983. Influence of the Point Bar on Flow Through Curved
  Channels. Water Resour. Res. 19 (5), 1173–1192.
- 1002 Dietrich, W.E., Smith, J.D., 1984. Bed load transport in a river meander. Water Resour. Res.
  1003 20 (10), 1355–1380.
- Dietrich W.E., Smith J.D., Dunne T., 1979. Flow and sediment transport in a sand bedded
  meander. J. Geol. 87, 305–315.
- Donovan, M., Belmont, P., Sylvester, Z., 2021. Evaluating the relationship between meanderbend curvature, sediment supply, and migration rates. J. Geophys. Res. Earth. Surf., 126,
  e2020JF006058.
- 1009 Downs, P.W., Gregory, K.J., 2004. River Channel Management: Towards Sustainable1010 Catchment Hydrosystems. London: Arnold, 408 p.
- 1011 Downs, P.W., Piégay, H., 2019. Catchment-scale cumulative impact of human activities on
- 1012 river channels in the late Anthropocene: implications, limitations, prospect.1013 Geomorphology 338, 88–104.
- 1014 Dudgeon, D., 2019. Multiple threats imperil freshwater biodiversity in the Anthropocene.
  1015 Curr. Biol. 29 (19), R960–R967.
- 1016 Dudgeon, D., Arthington, A.H., Gessner M.O., Kawabata, Z.I., Knowler, D.J., Lévêque, C.,
- 1017 Naiman, R.J., Prieur-Richard, A.H., Soto, D., Stiassny, M.L.J., Sullivan, C.A., 2006.
- 1018 Freshwater biodiversity: importance, threats, status and conservation challenges. Biol.
- 1019 Rev. 81 (2), 163–182.

- Dunne, T., Constantine, J.A., Singer, M.B., 2010. The role of sediment transport and sediment
  supply in the evolution of river channel and floodplain complexity. Trans. Jpn.
  Geomorphol. Union 31 (2), 155–170.
- 1023 Ekka, A., Pande, S., Jiang, Y., van der Zaag, P., 2020. Anthropogenic Modifications and
  1024 River Ecosystem Services: A Landscape Perspective. Waters 12, 2706.
- Elosegi, A., Díez, J., Mutz, M., 2010. Effects of hydromorphological integrity on biodiversity
  and functioning of river ecosystems. Hydrobiologia 657, 199–215.
- European Parliament and Council, 2000. Directive 2000/60/EC establishing a framework for
  community action in the field of water policy. Official Journal of the European Union L
  327, 22.12.2000.
- Fisk, H.N., 1944. Geological investigation of the alluvial valley of the lower Mississippi
  River. U.S. Army Corps of Engineers, Mississippi River Commission, Vicksburg, 78 p.
- 1032 Fisk, H.N., 1947, Fine-grained alluvial deposits and their effect on Mississippi River activity:
- 1033 Vicksburg, Mississippi. U.S. Army Corps of Engineers, Mississippi River Commission,
  1034 Vicksburg, 82 p.
- Florsheim, J.L., Mount, J.F., Chin, A., 2008. Bank erosion as a desirable attribute of rivers.
  BioScience 58 (6), 519–529.
- Fremier, A.K., Girvetz, E.H., Greco, S.E., Larsen, E.W., 2014. Quantifying Process-Based
  Mitigation Strategies in Historical Context: Separating Multiple Cumulative Effects on
  River Meander Migration. PLoS One 9 (6), e99736.
- 1040 Friedman, J.M., Osterkamp, W.R., Scott, M.L., Auble, G.T., 1998. Downstream effects of
- 1041 dams on channel geometry and bottomland vegetation: regional patterns in the Great1042 Plains. Wetlands 18 (4), 619–633.
- 1043 Fryirs, K.A., 2017. River sensitivity: a lost foundation concept in fluvial geomorphology.
- 1044 Earth Surf. Process. Landf. 42 (1), 55–70.

- Fryirs, K.A., Brierley, G.J., 2016. Assessing the geomorphic recovery potential of rivers:
  forecasting future trajectories of adjustment for use in management. WIREs Water 3,
  727–748.
- Fryirs, K.A., Brierley, G.J., in press. How far have management practices come in 'working
  with the river'? Earth Surf. Process. Landf.
- 1050 Fryirs, K.A., Wheaton, J.M., Brierley, G.J., 2016. An approach for measuring confinement
- and assessing the influence of valley setting on river forms and processes. Earth Surf.
  Process. Landf. 41 (5), 701–710.
- Furbish, D.J., 1988. River-bend curvature and migration How are they related. Geology 16
  (8), 752–755.
- 1055 Gaeuman, D.A., 2012. Mitigating downstream effects of dams. In: Church, M., Biron, P.,
- 1056 Roy, A.G. (Eds.), Gravel-bed Rivers: Processes, Tools, Environments. John Wiley &
  1057 Sons, Chichester, pp. 182–189.
- Gaueman, D.A., Schmidt, J.C., Wilcock, P.R., 2003. Evaluation of in-channel gravel storage
  with morphology-based gravel budgets developed from planimetric data. J. Geophys.
  Res. 108 (F1), 6001.
- 1061 González del Tánago, M., Martínez-Fernández, V., Aguiar, F.C., Bertoldi, W., Dufour, S.,
- 1062 García de Jalón, D., Garófano-Gómez, V., Mandzukovski, D., Rodríguez-González,
- P.M., 2021. Improving river hydromorphological assessment through better integration
  of riparian vegetation: Scientific evidence and guidelines. J. Environ. Manage. 292,
  1065 112730.
- Grizzetti, B., Pistocchi, A., Liquete, C., Udias, A., Bouraoui, F., van de Bund, W., 2017.
  Human pressures and ecological status of European rivers. Scientific Reports 7, 205.
- Güneralp, I., Rhoades, B.L., 2011. Influence of floodplain erosional heterogeneity on
   planform complexity of meandering rivers. J. Geophys. Res. 38, L14401.

- 1070 Gurnell, A.M., Downward, S.R., Jones, R., 1994. Channel planform change on the River Dee
  1071 meanders, 1876–1992. River Res. Appl. 9 (4), 187–204.
- 1072 Hauer, C., Leitner, P., Unfer, G., Pulg, U., Habersack, H., Graf, W., 2018. The Role of
- 1073 Sediment and Sediment Dynamics in the Aquatic Environment. In: Schmutz, S.,
- 1074 Sendzimir, J. (Eds.), Riverine Ecosystem Management. Aquatic Ecology Series, vol 8.
- 1075 Springer, Cham, pp 151–169.
- Hauer, F.R., Locke, H., Dreitz, V.J., Hebblewhite, M., Lowe, W.H., Muhfield, C.C., Nelson,
  C.R., Proctor, M.F., Rood, S.B., 2016. Gravel-bed river floodplains are the ecological
- 1078 nexus of glaciated mountain landscapes. Science Advances 2 (6), e1600026.
- Hoffmann, T., 2015. Sediment residence time and connectivity in non-equilibrium and
  transient geomorphic systems. Earth Sci. Rev. 150, 609–627.
- Hoffmann, T., Thorndycraft, V.R., Brown, A.G., Coulthard, T.J., Damnati, B., Kale, V.S.,
  Middelkoop, H., Notebaert, B., Walling, D.E., 2010. Human impact on fluvial regimes
  and sediment flux during the Holocene: Review and future research agenda. Glob.
  Planet. Change 72, 87–98.
- 1085 Horton, A.J., Constantine, J.A., Hales, T.C., Goossens, B., Bruford, M.W., Lazarus, E.D.,
- 2017. Modification of river meandering by tropical deforestation. Geology 45 (6), 511–
  514.
- Hubert, P., 2000. The segmentation procedure as a tool for discrete modeling of
  hydrometeorological regimes. Stochastic Environmental Research and Risk Assessment
  14, 297–304.
- Hubert, P., Carbonnel, J.P., Chaouche, A., 1989. Segmentation des séries
  hydrométéorologiques application à des séries de précipitations et de débits de
  l'afrique de l'ouest. Journal of Hydrology 110, 349–367.

- 1094 Ielpi, A., Lapôtre, M.G.A., 2020. A tenfold slowdown in river meander migration driven by1095 plant life. Nature Geoscience 13, pages 82–86.
- 1096 IGN, 2016. BD Ortho version 2.0, Ortho HR version 1.0, Descriptif de contenu.
- 1097 Khan, S., Fryirs, K.A., 2020. An approach for assessing geomorphic river sensitivity across a
- 1098 catchment based on analysis of historical capacity for adjustment. Geomorphology 359,1099 107135.
- Kondolf, M.G., 2011. Setting Goals in River Restoration: When and Where Can the River
  "Heal Itself"? In: Bennett, S.J., Castro, J.M., Simon, A. (Eds.), Stream Restoration in
- Dynamic Fluvial Systems: Scientific Approaches, Analyses, and Tools. Geophysical
  Monograph 194, American Geophysical Union, pp. 29–43.
- 1104 Lablanche, G., 1984. Carte géol. France (1/50000), feuille Châteauneuf-sur-Cher (546),
  1105 BRGM, Orléans.
- Lablanche, G., 1994. Carte géol. France (1/50000), feuille Saint-Amand-Montrond (572),
  BRGM, Orléans.
- Lablanche, G., Marchand, D., Lefavarais-Raymond, A., Debrand-Passard, S., Gros, Y.,
  Debéglia, N., Maget, P., Lallier, D., 1994. Notice explicative, Carte géol. France
- 1110 (1/50000), feuille Saint-Amand-Montrond (572), BRGM, Orléans, 81 p.
- 1111 Larsen, E.W., Girvetz, E.H., Fremier, A.K., 2006. Assessing the Effects of Alternative
  1112 Setback Channel Constraint Scenarios Employing a River Meander Migration Model.
  1113 Environ. Manage. 37, 880–897.
- 1114 Larue, J.P., 1981. Les nappes alluviales de la vallée du Cher dans le bassin de Montluçon.
  1115 Norois 111, 345–360.
- 1116 Larue, J.P., 1994. L'évolution morphodynamique de la vallée du Cher dans la région de Saint-
- 1117 Amand-Montrond (Cher, France). Rev. Géomorphol. Dynam. 43 (3), 81–92.

- Larue, J.P., 2011. Longitudinal profiles and knickzones: the example of the rivers of the Cher
  basin in the northern French Massif Central. Proc. Geol. Assoc. 122, 125–142.
- 1120 Legleiter, C.J., Harrison, L.R., Dunne, T., 2011. Effect of point bar development on the local
- 1121 force balance governing flow in a simple, meandering gravel bed river. J. Geophys. Res.1122 116, F01005.
- 1123 Lehner, B., Reidy Liermann, C., Revenga, C., Vörösmarty, C., Fekete, B., Crouzet, P., Döll,
- 1124 P., Endejan, M., Frenken, K., Magome, J., Nilsson, C., Robertson, J.C., Rödel, R.,
- 1125 Sindorf, N., Wisser, D., 2011. High-resolution mapping of the world's reservoirs and
- dams for sustainable river-flow management. Front. Ecol. Environ. 9 (9), 494–502.
- Maaß, A.L., Schüttrumpf, H., Lehmkuhl, F., 2021. Human impact on fluvial systems in
  Europe with special regard to today's river restorations. Environ. Sci. Eur. 33, 119.
- Malavoi, J.R., Bravard, J.P., Piégay, H., Hérouin, E., Ramez, P., 1998. Détermination de
  l'espace de liberté des cours d'eau. Guide technique no. 2, SDAGE RMC.
- Manivit, J., Debrand-Passard, S., 1994. Carte géol. France (1/50000), feuille Vierzon (491),
  BRGM, Orléans.
- Manivit, J., Debrand-Passard, S., Gros, Y., Desprez, N., 1994. Notice explicative, Carte géol.
  France (1/50000), feuille Vierzon (491), BRGM, Orléans, 50 p.
- Micheli, E.R., Kirchner, J.W., 2002. Effects of wet meadow riparian vegetation on
  streambank erosion. 1. Remote sensing measurements of streambank migration
  erodibility. Earth Surf. Process. Landf. 27, 627–639.
- Micheli E.R., Kirchner J.W., Larsen E.W., 2004. Quantifying the effect of riparian forest
  versus agricultural vegetation on river meander migration rates, central Sacramento
  River, California, USA. River Res. Appl. 20, 537–548.
- 1141 Moatar, F., Ducharne, A., Thiéry, D., Bustillo, V., Sauquet, E., Vidal, J.P., 2010. La Loire à
- 1142 l'épreuve du changement climatique. Géosciences BRGM 12, 78–87.

- 1143 Moatar, F., Ducharne, A., Thiéry, D., Sauquet, E., Vidal, J.P., Bernard, A., Bustillo, V., 2010.
- 1144 Impact du Changement Climatique sur l'hydrosystème Loire : HYDROlogie, Régime
- 1145 thermique, QUALité des eaux. Action 1 : Evolution hydroclimatique de la Loire et de
- ses affluents sous changement climatique. Rapport final, 105 p.
- Mörtl, C., De Cesare, G., 2021. Sediment Augmentation for River Rehabilitation and
  Management—A Review. Land 10, 1309.
- Motta, D., Abad, J.D., Langendoen, E.J., Garcia, M.H., 2012. The effects of floodplain soil
  heterogeneity on meander planform shape. Water Resour. Res. 48, W09518.
- 1151 Nanson, G.C., Kickin, E.J., 1986. A statistical analysis of bank erosion and channel migration
  1152 in western Canada. Geol. Soc. Am. Bull. 97, 497–504
- 1153 Notebaert, B., Verstraeten, G., 2010. Sensitivity of West and Central European river systems
  1154 to environmental changes during the Holocene: A review. Earth Sci. Rev. 103, 163–182.
- Obert, D., Gély, J.P., Mathis, V., Normand, M., Trouillet, A., Freytet, P., 1997. Carte géol.
  France (1/50000), feuille Charenton-sur-Cher (573). Orléans : BRGM.
- Overeem, I., Kettner, A.J., Syvitski, J., 2013. Impacts of Humans on River Fluxes and
  Morphology. In Shroder, J.F., Wohl E., (Eds.), Treatise on Geomorphology, Fluvial
  Geomorphology, Edition 1, Chapter 9.40. Academic PressEditors, pp. 828–842.
- Piégay, H., Arnaud, D., Souchon, Y., 2003. Effets de la végétation riveraine sur la géométrie
  des lits fluviaux : études de cas dans le Massif central (France). Geomorphol. Relief,
- 1162 Process. Environ. 9 (2), 111–127.
- 1163 Piégay, H., Cuaz, M., Javelle, E., Mandier, P., 1997. Bank erosion management based on
- 1164 geomorphological, ecological and economic criteria on the Galaure River, France. River
- 1165 Res. Appl. 13 (5), 433–448.

- Piégay, H., Darby, S.E., Mosselman, E., Surian, N., 2005. A review of techniques available
  for delimiting the erodible river corridor: a sustainable approach to managing bank
  erosion. River Res. Appl. 21 (7), 773–789.
- Pyrce, R.S., Ashmore, P.E., 2003a. The relation between particle path length distributions and
  channel morphology in gravel-bed streams: A synthesis. Geomorphology 56, 167–187.
- 1171 Pyrce, R.S., Ashmore, P.E., 2003b. Particle path length distributions in meandering gravel-
- bed streams: Results from physical models. Earth Surf. Process. Landf. 28, 951–966.
- Pyrce, R.S., Ashmore, P.E., 2005. Bedload path length and point bar development in gravelbed river models. Sedimentology 52, 839–857.
- 1175 Reid, D., Church, M., 2015. Geomorphic and Ecological Consequences of Riprap Placement
  1176 in River Systems. J. Am. Water. Resour. Assoc. 51 (4), 1043–1059.
- 1177 Reid, H.E., Brierley, G.J., 2015. Assessing geomorphic sensitivity in relation to river capacity
  1178 for adjustment. Geomorphology 251, 108–121.
- 1179 Rheinheimer, D.E., Yarnell, S.M., 2017. Tools for sediment management in rivers. In: Horne,
- 1180 A.C., Webb, J.A., Stewardson, M.J., Richter, B., Acreman, M. (Eds.), Water for the
- Environment, from Policy and Science to Implementation and Management. Academic
  Press, pp. 237–263.
- 1183 Richard, G.A, Julien, P.Y., Baird, D.C., 2005. Statistical analysis of lateral migration of the
- 1184 Rio Grande, New Mexico. Geomorphology 71, 139–155.Rigby, R. A., Stasinopoulos,
- 1185 D.M., 2005. Generalized additive models for location, scale and shape (with discussion).
- 1186 Applied Statistics 54, 507–554.
- Rinaldi, M., Piégay, H., Surian, N., 2011. Geomorphological Approaches for River
  Management and Restoration in Italian and French Rivers. In: Bennett, S.J., Castro, J.M.,
  Simon, A. (Eds.), Stream Restoration in Dynamic Fluvial Systems: Scientific

- Approaches, Analyses, and Tools. Geophysical Monograph 194, American GeophysicalUnion, pp. 319–336.
- Rinaldi, M., Wyżga, B., Surian, N., 2005. Sediment mining in alluvial channels: physical
  effects and management perspectives. River Res. Appl. 21 (7), 805–828.
- 1194 Rollet, A.J., Piégay, H., 2013. De l'intérêt de la quantification pour la gestion des systèmes
- 1195 fluviaux : exemple de la basse vallée de l'Ain. Geomorphol. Relief, Process. Environ. 1,
  1196 63–78.
- Roux, C., Alber, A., Bertrand, M. Vaudor, L., Piégay, H., 2015. "FluvialCorridor": A new
  ArcGIS toolbox package for multiscale riverscape exploration. Geomorphology 242, 29–
  37.
- Schumm, S.A., Harvey, M.D., Watson, C.C., 1984. Incised channels: Morphology, dynamics,
  and control, Water Resources Publications, Littleton, Colorado, 200 p.
- Simon, A., 1989. A model of channel response in disturbed alluvial channels. Earth Surf.
  Process. Landf. 14, 11–26.
- Simon, A., Rinaldi, M., 2006. Disturbance, stream incision, and channel evolution: The roles
  of excess transport capacity and boundary materials in controlling channel response.
  Geomorphology 79, 361–383.
- Simon-Coinçon, R., Thiry, M., Quesnel, F., 2000. Paléopaysages et paléoenvironnements
  sidérolithiques du Nord du Massif central (France). C. R. Acad. Sci. Ser. IIA Earth
  Planet. Sci. 330, 693–700.
- Staenzel, C., Kondolf, M., Schmitt, L., Combroux, I., Barillier, A., Beisel, J.N., 2020.
  Restoring fluvial forms and processes by gravel augmentation or bank erosion below
- dams: A systematic review of ecological responses. Sci. Total Environ. 706, 135743.
- 1213 Stanford, J.A., Lorang, M.S., Hauer, F.R., 2005. The shifting habitat mosaic of river
- 1214 ecosystems. Verh. Int. Ver. Theor. Angew. Limnol. 29 (1), 123-136.

Surian, N., 2021. Fluvial Changes in the Anthropocene: A European Perspective. In: Elias,
S.A. (Eds.), Reference Module in Earth Systems and Environmental Sciences. Elsevier,

1217 Amsterdam.

- Sylvester, Z., Durkin, P., Covault, J.A., 2019. High curvatures drive river meandering.
  Geology 47, 263–266.
- Taylor, J., 1997. An Introduction to Error Analysis: The Study of Uncertainties in Physical
  Measurements. University Science Books, Sausalito, California.
- Tockner, K., Lorang, M.S., Stanford, J.A., 2010. River flood plains are model ecosystems to
  test general hydrogeomorphic and ecological concepts. River Res. Appl. 26, 76-86.
- Turland, M., Cojean, R., Brulhet, J., Morice, E., Grolier, J., Lacour, A., 1989a. Carte géol.
  France (1/50000), feuille Hérisson (596), BRGM, Orléans.
- 1226 Turland, M., Feys, R., Desthieux, F., Virlogeux, D., 1989b. Carte géol. France (1/50000),
  1227 feuille Montluçon (619), BRGM, Orléans.
- 1228 Turland, M., Hottin, A.M., Cojean, R., Ducreux, J.L., Debéglia, N., d'Arcy, D., Mathis, V.,
- 1229 Carroué, J.P., Piboule, M., 1989c. Notice explicative, Carte géol. France (1/50000),
  1230 feuille Hérisson (596), BRGM, Orléans, 118 p.
- 1231 Vayssière, A., Dépret, T., Castanet, C., Gautier, E., Virmoux, C., Carcaud, N., Garnier, A.,
  1232 Brunstein, D., Pinheiro, D., 2016. Etude des paléoméandres holocènes de la plaine
  1233 alluviale du Cher (site de Bigny, moyenne vallée du Cher). Geomorphol. Relief, Process.
  1234 Environ. 22 (2), 163–176.
- 1235 Vayssière, A., Castanet, C., Gautier, E., Virmoux, C., Dépret, T., Gandouin, E., Develle1236 Vicent, A.L., Mokadem, F., Saulnier-Copard, S., Sabatier, P., Carcaud N., 2020. Long1237 term readjustments of a sinuous river during the second half of the Holocene in
- 1238 northwestern Europe (Cher River, France). Geomorphology 370.

- Vörösmarty, C.J., McIntyre, P.B., Gessner, M.O., Dudgeon, D., Prusevich, A., Green, P.,
  Glidden, S., Bunn, S.E., Sullivan, C.A., Reidy Liermann, C., Davies, P.M., 2010. Global
- 1241 threats to human water security and river biodiversity. Nature 467, 555–561.
- Watson, C.C., Biedenharn, D.S., Bledsoe, B.P., 2002. Use of incised channel evolution
  models in understanding rehabilitation alternatives. J. Am. Water Resour. Assoc. 38 (1),
- 1244 151–160.
- Williams, R.D., Bangen, S., Gillies, E., Kramer, N., Moir, H., Wheaton, J., 2020. Let the river
  erode! Enabling lateral migration increases geomorphic unit diversity. Sci. Total
  Environ. 715, 136817.
- Wohl E., 2020. Rivers in the Anthropocene: The U.S. perspective. Geomorphology 366,1249 106600.
- Yarnell, S.M., Mount, J.F., Larsen, E.W., 2006. The influence of relative sediment supply on
  riverine habitat heterogeneity. Geomorphology 80, 310–324.
- 1252 Zen, S., Perona, P., 2020. Biomorphodynamics of river banks in vegetated channels with self-
- 1253 formed width. Adv. Water Resour. 135, 103488.