

Characterization and troubleshooting of cloud gaming applications on mobile networks

Joël Roman Ky, Bertrand Mathieu, Abdelkader Lahmadi, Raouf Boutaba

▶ To cite this version:

Joël Roman Ky, Bertrand Mathieu, Abdelkader Lahmadi, Raouf Boutaba. Characterization and troubleshooting of cloud gaming applications on mobile networks. Network Traffic Measurement and Analysis Conference (TMA 2022), Jun 2022, Enschede, Netherlands. hal-03878114

HAL Id: hal-03878114 https://hal.science/hal-03878114

Submitted on 29 Nov 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Characterization and troubleshooting of cloud gaming applications on mobile networks.



Network Traffic Measurement and Analysis Conference 2022, Enschede, The Netherlands.

Joël Ky^{1,2}, Bertrand Mathieu¹, Abdelkader Lahmadi² & Raouf Boutaba³ ¹Orange Innovation Lannion, ²University of Lorraine, ³University of Waterloo

joelroman.ky@orange.com


Motivation

Low-latency applications (cloud-gaming, cloud-robotics, metaverse...) have soared with the rapid evolution of Internet. Current network capacities (especially time-varying capacity networks like 4G/5G networks) struggle to ensure user QoE (Quality of Experience). There is therefore a need to collect, identify and analyze metrics specific to low-latency applications in network equipment (switches, base stations, UEs...) for efficient troubleshooting of user QoE degradation purposes.

Transmission Opportunities of 4G network

To conduct controlled experiments on time-varying capacity network, we use **Saturatr tool** [1]. This experiment allows, by saturating the network link, to capture different behaviors of 4G base stations for one UE. From those captures, the tool generates **transmission opportunities (txops)** files, one for uplink and one for downlink, which we can use to emulate time-varying network conditions.

In a given txops file, one line represents a time (in ms) when the base station can send a **MTU-sized packet**.



Txops Generation

We captured 06 different configurations, 05 static conditions and one on a highway at the steady speed of 110km/h, on Orange 4G network in France. These configurations lead to txops files that differ by the average throughput, the frequency and the importance of the txops.


| Conditions | Throughput (Mbps) | Location |
|------------|-------------------|------------|
| File 1 | 220 | Orange |
| File 2 | 160 | Orange |
| File 3 | 120 | Brélévenez |
| File 4 | 80 | Brélévenez |

40



File 6 (Highway) 45

File 5




Inter txops tir

Plemeur-Bodou

Usage of txops for cloud gaming

We use the txops files to conduct experiments on cloud gaming applications like Google Stadia, NVIDIA GeForceNow under different emulated 4G network conditions. For this purpose, we use the **LinkShell tool** from the framework **Mahimahi** [2].

We collect metrics from Google WebRTC API (client delay, network RTT, frame rate, bit-rate...) and traffic traces from Wireshark to analyze the cloud gaming applications behaviors under time-varying capacity networks.



The txops files data are available in **OpenData** at the following link: https://cloud-gaming-traces.lhs.loria. fr/cellular.html

0.80 는 0.75

0.70

0.65

0.55

References


- [1] Keith Winstein. Saturatr tool. https:// github.com/keithw/multisend.
- [2] Ravi Netravali. Mahimahi. https://github. com/ravinet/mahimahi.

Troubleshooting of cloud gaming applications

Machine learning and/or deep learning unsupervised learning approaches for anomaly detection are applied on the data collected, which are multivariate timeseries KPIs.

Those approaches learn to reconstruct the time-series from *normal* inputs. Then, they are applied on samples and those with high reconstruction errors are identified as **anomalous**.

Once anomalous samples are detected, their causes must be identified based on the input features in order to consider remedial measures.



Acknowledgements

This work is partially funded by the French National Research Agency (ANR) MOSAICO project, under grant No ANR-19-CE25-0012.