

#### POLYLACTIDE FILMS WITH INCREASED OPTICAL BARRIER PROPERTIES THROUGH THE USE OF BIXIN

Liana Stoll, Alessandro de Oliveira Rios, Sandra Domenek

#### ▶ To cite this version:

Liana Stoll, Alessandro de Oliveira Rios, Sandra Domenek. POLYLACTIDE FILMS WITH INCREASED OPTICAL BARRIER PROPERTIES THROUGH THE USE OF BIXIN. Biopol 2019, Jun 2019, Stockholm, Sweden. 2019. hal-03899480

HAL Id: hal-03899480

https://hal.science/hal-03899480

Submitted on 14 Dec 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Sweden. Stockholm, -19th, 0 BIOP

#### 1. Introduction

The use of carotenoids as yellow-red colorants for polymeric materials represents a sustainable way of obtaining colored packaging. The introduction of bixin, a carotenoid with coloring and antioxidant properties, could be used to increase the barrier properties of poly(lactide) (PLA) films, turning the biodegradable polymer more suitable to protect light- and oxygen-sensitive food products. The present study aimed to evaluate the influence of bixin on the optical and oxygen barrier properties of PLA films. The thermal properties of films were also evaluated.

#### 2. Materials and Methods

## Films production

Bixin was extracted from annatto seeds (Bixa orellana) with dichloromethane.



Bixin extracts were added to PLA solution (7%w/w in dichloromethane) in order to achieve different bixin concentrations (w/w):


- Solutions were poured into Teflon plates and dried at ambient temperature for 48h.
- Films were peeled and thermo-pressed (160 °C, 6 min) to remove the residual solvent.

## Films characterization

The optical barrier properties were measured by placing the films in quartz

-0.00%

-0.01%




test cells. Samples were scanned from 200 to 800 nm in a UV-Vis spectrophotometer.

Films oxygen permeability was determined in a GDP-C permeameter (25 °C). The permeability (P) was calculated by multiplying the measured oxygen transmission rate by the sample thickness (measured with a micrometer on 9 points). The diffusion (D) and sorption (S) coefficients were calculated with the help of the time-lag (t<sub>lag</sub>) method.

Films crystallinity degree (x) and glass transition temperature (T<sub>a</sub>) were analyzed using a Q100 DSC.

# 3. Results and Discussion

**Figure 1**. PLA films produced with different bixin concentrations (0 - 1%)



✓ The presence of bixin reduced the light transmission of PLA films (Figure 2): the higher the concentration of bixin, the higher the films' barrier to ultraviolet (200-300 nm) and visible light (300–800 nm). The conjugated double bonds in bixin molecular structure serve as chromophore moieties, being responsible for its light absorption capacity.

Figure 2. Light transmittance (%) from 200 to 800 nm through PLA films 80 70 60 Transmittance 50 40 30 20 10 -10200 300 400 600 700 800 500 Wavelenght (nm)

-0.05%

**Table 1** – Oxygen barrier and thermal properties of PLA films produced with bixin.

Bixin	P.10 <sup>18</sup>	$D.10^{12}$	S.10 <sup>6</sup>	Tg	X
(%)	[m <sup>3</sup> m m <sup>-2</sup> Pa <sup>-1</sup> s <sup>-1</sup> ]	$[m^2 s^{-1}]$	[m <sup>3</sup> m <sup>-3</sup> Pa <sup>-1</sup> ]	(°C)	(%)
0.00	3.31	3.3	1.0	$50.5 \pm 0.7$	$0.8 \pm 0.1$
0.01	4.14	3.5	1.2	$49.8 \pm 1.9$	$1.5 \pm 0.2$
0.05	3.04	2.8	1.1	$50.4 \pm 1.7$	$1.0 \pm 0.4$
0.10	3.59	3.2	1.1	$50.3 \pm 0.1$	$1.3 \pm 0.2$
1.00	3.32	2.9	1.2	$49.3 \pm 2.3$	$1.3 \pm 0.0$

✓ Bixin did not affect the oxygen solubility, diffusivity and permeability of the films, neither their thermal properties, given by Tg and crystallinity degree (x) (Table 1).

### 4. Conclusion

Bixin effectively increased the UV-Vis light barrier of PLA films, where the presence of 1% of the carotenoid resulted in films with nearly zero UV light transmittance. Although improvements on oxygen barrier properties are still required, the presence of bixin is expected to retard oxidation reactions in light sensitive food products.





<del>-</del>0.10%



www.ufrgs.br

INRA and AgroParisTech, Group "Interactions between Materials and Media in Contact", 1 avenue des Olympiades, 91300 Massy,