



HAL
open science

Fluorinated vesicle-clay composites for PFAs removal from water

Alfredo Gonzalez-Perez, Angel Macia

► **To cite this version:**

Alfredo Gonzalez-Perez, Angel Macia. Fluorinated vesicle-clay composites for PFAs removal from water. 2023. hal-03924494

HAL Id: hal-03924494

<https://hal.science/hal-03924494v1>

Preprint submitted on 5 Jan 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

Fluorinated vesicle-clay composites for PFAs removal from water

Alfredo Gonzalez-Perez^{1,2*} and Angel Macia³

¹ Biocomplexity and Biophysics, Niels Bohr Institute, University of Copenhagen, Blegdamsvej 172100 Copenhagen, Denmark

² Water Centre for Innovation (Campus Roslagen AB), Kaserngatan 11, 761 46 Norrtälje, Sweden

³ Arcadia AB, Ribevägen 22A, 217 46 Malmö, Sweden

* Email: alfredo.gonzalez@campusroslagen.se / gonzalez@nbi.ku.dk

Keywords: PFAs, Catanionic vesicles, clay, F-surfactants, water

Summary

The use of modified clays for environmental remediation is heavily investigated. Different organic compounds containing fluorine are contaminating the environment and damage human health as well can form complexes with other compounds [1]. Modified clays can be efficient for the removal of ionic and non-ionic contaminants [2]. New bioinspired materials are being developed continuously in order to answer the environmental challenges that nature suffer as a consequence of human activities [3], while water utilities keep optimizing processes and cost and using new technology developed elsewhere [4]. Micelle-clay composites have been used for environmental remediation and for the removal of organic pollutants from water [2,5]. The removal of fluorinated compounds from water and soil is difficult. Fluorocarbons can form self-assembled structures and membranes that are at the same time hydrophobic and lipophobic [6,7]. In this research we investigate the use of hybrid catanionic fluoro-hydrocarbon surfactants, known to form membranous vesicular structures to combine with clays to prepare fluoro-vesicles-clay composites for the removal of fluoro-compounds from water.

(a) Purpose or objectives and status of study or research hypothesis

We work to develop clay filters based on fluorinated catanionic vesicles for the removal of key PFAs pollutants from water. We use a modified method based on clay-based composites characterized at the Molecular-Scale Biophysics Research Infrastructure (MOSBRI) under the project (MOSBRI 2022-101). This project has received funding from the European Union's Horizon 2020 research and innovation program under grant agreement No 101004806. The lessons learned on that project are now used for our new approach for fluorinated-based filters. The protocol used here for the preparation the clay composite was analogous to the one reported in the MOSBRI 2022-101 project substituting the nanocellulose for the solution of hybrid fluoro-hydrocarbon catanionic vesicles.

(b) Key issue(s) or problem(s) addressed

Many Fluorine-based pollutants cannot be absorbed directly in clays without modification. The chemical nature or Fluorine based compounds made them difficult to remove, hence persistent in the environment. We developed modified clays using catanionic vesicles (that

contain fluorocarbon chains) for the removal of Fluorine-based pollutants from water. We aim to develop cost-effective filters easy to recycle ensuring sustainability.

(c) Methodology or approach used

The clay is being modified at different concentrations of a cationic surfactant able to form vesicles with semi-fluorinated counterparts that become integral part of the clay. The modified clay and removal efficiency is characterized by different techniques. The removal efficiency will be investigated at the university facilities from our collaborators in Copenhagen.

(d) Results and conclusions derived from the project

The modified clay is being characterized and experiments will be provided to confirm the optimal F-vesicle concentration and ratio of Fluorinated vs Hydrogenated counterpart to ensure a functional clay modification for the removal of PFAs. Complementary studies are being done using different techniques (FTIR and UV) to assess the removal efficiency of different samples under investigation as a prove of concept. Preliminary test show the adsorption of PFAs into the F-vesicle-clay composite.

(e) Policy implications of the project relevant to the selected conference theme, theory and/or practice

We aim to provide with a cost-effective filter that can be reused many times for the removal of small amounts PFAs to maintain clean water bodies. If regulation requires the removal of small amounts of PFAs we will be able to provide solutions at a cost-effective.)

Acknowledgments

We want to acknowledge the MOSBRI network for the project MOSBRI 2022-101, Interaction of bacteria with clay-nanocellulose composites for water disinfection. (This project has received funding from the European Union’s Horizon 2020 research and innovation programme under grant agreement No 101004806). (<https://www.mosbri.eu/>).

References

- [1] Kumar Jha, S. (2011) Fluoride in the environment and its metabolism in humans. *Rev Environ Contam Toxicol.* 211, 121-42.
- [2] Benitez, A.R. et al. (2022) Modified compositions of micelle-clay and liposome-clay composites for optimal removal from water of bacteria and hydrophobic neutral chemicals. *Applied Sciences* 12, 3044-.
- [3] Gonzalez-Perez A. and Persson, KM (2016) Bioinspired materials for water purification. *Materials* 9, 6 (2016) 447.
- [4] Gonzalez-Perez, A. et al. (2021) Optimizing NOM Removal: Impact of Calcium Chloride. *Sustainability* 13, 11 (2021) 6338
- [5] Gonzalez-Perez, A. and Macia, A. (2022) Water disinfection with micelle-clay composites. IWA 3rd International Conference on Disinfection and DBPs, Milan, 221-223
- [6] Gonzalez-Perez, A. et al. (2007) Isolated Fluid Polyhedral Vesicles. *Journal of the American Chemical Society* 129 (2007) 756-757
- [7] Rosholm, KR. et al. (2012) Characterization of Fluorinated Catansomes: A Promising Vector in Drug-Delivery. *Langmuir* 28, 2773-2781.