



**HAL**  
open science

# NL-Ridge: a novel statistical patch-based approach for image denoising

Sébastien Herbreteau, Charles Kervrann

► **To cite this version:**

Sébastien Herbreteau, Charles Kervrann. NL-Ridge: a novel statistical patch-based approach for image denoising. 2022 - 10th International Conference on Curves and Surfaces, SMAI-SIGMA, Jun 2022, Arcachon, France. pp.1-1. hal-03926478

**HAL Id: hal-03926478**

**<https://hal.science/hal-03926478v1>**

Submitted on 6 Jan 2023


**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

**Overview**

We propose a **unified view** to reconcile **state-of-the-art unsupervised non-local denoisers**. We derive **NL-Ridge algorithm** which leverages local linear combinations of noisy similar patches.

- ▷ We show that non-local denoisers are characterized by the **family of functions** ( $f_\Theta$ ) used to process groups of similar noisy image patches.
- ▷ The optimal parameters  $\Theta^*$  for each group are found by minimizing an approximation of the  $L_2$  **risk** via a two-step algorithm.
- ▷ NL-Ridge linearly combines noisy similar patches. Our closed-form aggregation weights are computed, in the second step, through **multivariate Ridge regressions**.
- ▷ NL-Ridge **outperforms** well established state-of-the-art unsupervised denoisers, including BM3D [1] and NL-Bayes [2], as well as recent unsupervised deep learning methods [5, 6, 7], while being simpler conceptually.

**General principle of non-local denoisers**

**BM3D** [1] assumes a locally sparse representation in a transform domain:

$$f_\Theta(Y) = P^\top (\Theta \odot (PYQ)) Q^\top,$$

$P$  and  $Q$  are orthogonal matrices.

**NL-Bayes** [2] was established in the Bayesian setting:

$$f_{\Theta, \beta}(Y) = \Theta Y + \beta u^\top,$$

$u$  denotes a  $m$ -dimensional vector with all entries equal to one.

**NL-Ridge** denoises each patch by linearly combining the most similar noisy patches:

$$f_\Theta(Y) = Y\Theta$$

**Parameter optimization**

The optimal parameters  $\Theta^*$  for the local denoiser  $f_\Theta$  are found by minimizing the  $L_2$  **risk**:

$$R_\Theta(X) = \mathbb{E} \|f_\Theta(Y) - X\|_F^2.$$

As  $\Theta^*$  requires the knowledge of  $X$  which is unknown, we use the following two-step algorithm:

- Step 1: Minimize **Stein's unbiased risk estimate** (SURE) [3] to approximate  $\Theta^*$ , reposition all the denoised patches and compute the  $\hat{I}_1$  image aggregating estimators at each pixel.
- Step 2:  $\Theta$  is improved via "**internal adaptation**" [4] with the pilot image  $\hat{I}_1$ .

**Step1: SURE****Proposition 1**

Let  $Y = X + W$  where  $Y, X, W \in \mathbb{R}^{n \times m}$  and  $W_{i,j} \sim \mathcal{N}(0, \sigma^2)$  are independent along each row. An **unbiased estimate of the risk**  $R_\Theta(X) = \mathbb{E} \|f_\Theta(Y) - X\|_F^2$  is **Stein's unbiased risk estimate (SURE)**:

$$\begin{aligned} \text{SURE}_\Theta(Y) &= -nm\sigma^2 + \|f_\Theta(Y) - Y\|_F^2 + 2\sigma^2 \text{div} f_\Theta(Y) \\ &= -nm\sigma^2 + \|Y\Theta - Y\|_F^2 + 2n\sigma^2 \text{tr}(\Theta) \end{aligned}$$

- ▷ Substituting this estimate for the risk  $R_\Theta(X)$  yields:

$$\arg \min_{\Theta} R_\Theta(X) \approx \arg \min_{\Theta} \text{SURE}_\Theta(Y) = \hat{\Theta}_1$$

$$\hat{\Theta}_1 = I_m - n\sigma^2(Y^\top Y)^{-1}$$

**Step 2: Internal adaptation****Proposition 2**

The **quadratic risk**  $R_\Theta(X)$  is:

$$\mathbb{E} \|f_\Theta(X + W) - X\|_F^2 = \|X\Theta - X\|_F^2 + n\sigma^2 \|\Theta\|_F^2$$

which is minimal for:

$$\Theta^* = (X^\top X + n\sigma^2 I_m)^{-1} X^\top X$$

(solution of the **multivariate Ridge regression**).

- ▷ Substituting  $\hat{X}_1$  for  $X$  in the risk expression yields:

$$\arg \min_{\Theta} R_\Theta(X) \approx \arg \min_{\Theta} R_\Theta(\hat{X}_1) = \hat{\Theta}_2$$

$$\hat{\Theta}_2 = (\hat{X}_1^\top \hat{X}_1 + n\sigma^2 I_m)^{-1} \hat{X}_1^\top \hat{X}_1$$


**Results**

Fig. 1: Denoising results after step 1 and 2 (left), number of estimates by pixel before aggregation (middle) and standard deviation (right).



Fig. 2: PSNR results on Barbara corrupted with Gaussian noise ( $\sigma = 20$ ).

	Methods	Set12	BSD68	Urban100
	Noisy	24.61 / 20.17 / 14.15	24.61 / 20.17 / 14.15	24.61 / 20.17 / 14.15
Unsupervised	BM3D	32.37 / 29.97 / 26.72	31.07 / 28.57 / 25.62	32.35 / 29.70 / 25.95
	NL-Bayes	32.25 / 29.88 / 26.45	31.16 / 28.70 / 25.58	31.96 / 29.34 / 25.56
	<b>NL-Ridge</b>	<b>32.46 / 30.00 / 26.73</b>	<b>31.20 / 28.67 / 25.67</b>	<b>32.53 / 29.90 / 26.29</b>
	DIP	30.12 / 27.54 / 24.67	28.83 / 26.59 / 24.13	- / - / -
	Noise2Self	31.01 / 28.64 / 25.30	29.46 / 27.72 / 24.77	- / - / -
Supervised	Self2Self	32.07 / 30.02 / 26.49	30.62 / 28.60 / 25.70	- / - / -
	DnCNN	32.86 / 30.44 / 27.18	31.73 / 29.23 / 26.23	32.68 / 29.97 / 26.28
	FFDnet	32.75 / 30.43 / 27.32	31.63 / 29.19 / 26.29	32.43 / 29.92 / 26.52
	LIDIA	32.85 / 30.41 / 27.19	31.62 / 29.11 / 26.17	32.80 / 30.12 / 26.51

Table 1: The average PSNR (dB) results of different methods on various datasets corrupted with Gaussian noise ( $\sigma = 15, 25$  and  $50$ ).

**References**

- [1] K. Dabov, A. Foi, V. Katkovnik, and K. Egiazarian, "Image denoising by sparse 3D transform-domain collaborative filtering," in *IEEE Transactions on Image Processing*, vol. 16, no. 8, pp. 2080–2095, 2007.
- [2] A. Buades, M. Lebrun, and J.-M. Morel, "A non-local bayesian image denoising algorithm," *SIAM Journal on Imaging Science*, vol. 6, no. 3, pp. 1665–1688, 2013.
- [3] C. Stein, "Estimation of the mean of a multivariate normal distribution," *Annals of Statistics*, vol. 9, no. 6, pp. 1135–1151, 1981.
- [4] G. Vaksman, M. Elad, and P. Milanfar, "LIDIA: Lightweight learned image denoising with instance adaptation," *Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, June 2020.
- [5] D. Ulyanov, A. Vedaldi, and V. Lempitsky, "Deep image prior," *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, p. 9446–9454, 2018.
- [6] J. Batson and L. Royer, "Noise2Self: Blind denoising by self-supervision," *Proceedings of the 36th International Conference on Machine Learning*, vol. 97, pp. 524–533, 2019.
- [7] Y. Quan, M. Chen, T. Pang, and H. Ji, "Self2self with dropout: Learning self-supervised denoising from single image," *CVPR*, 2020.
- [8] K. Zhang, W. Zuo, Y. Chen, D. Meng, and L. Zhang, "Beyond a gaussian denoiser: residual learning of deep CNN for image denoising," in *IEEE Transactions on Image Processing*, vol. 26, no. 7, pp. 3142–3155, 2017.