

# Accelerated sodium MRI using undersampled 3D SPARKLING at 7T

Renata Porciuncula Baptista, Mathieu Naudin, Chaithya Giliyar Radhakrishna, Guillaume Daval-Frérot, Franck Mauconduit, Alexa Haeger, Sandro Romanzetti, Marc Lapert, Philippe Ciuciu, Cécile Rabrait-Lerman, et al.

# ▶ To cite this version:

Renata Porciuncula Baptista, Mathieu Naudin, Chaithya Giliyar Radhakrishna, Guillaume Daval-Frérot, Franck Mauconduit, et al.. Accelerated sodium MRI using undersampled 3D SPARKLING at 7T. 2023. hal-03929787

# HAL Id: hal-03929787 https://hal.science/hal-03929787v1

Preprint submitted on 9 Jan 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# <sup>1</sup> Accelerated Sodium MRI using undersampled 3D SPARKLING

# <sub>2</sub> at 7T

- Renata Porciuncula Baptista<sup>1,\*</sup>, Mathieu Naudin<sup>2</sup>, Chaithya G R<sup>1,3</sup>, Guillaume
- <sup>4</sup> Daval-Frérot<sup>1,3,4</sup>, Franck Mauconduit<sup>1</sup>, Alexa Haeger<sup>5</sup>, Sandro Romanzetti<sup>5</sup>, Marc Lapert<sup>4</sup>,
- <sup>5</sup> Philippe Ciuciu<sup>1,3</sup>, Cécile Rabrait-Lerman<sup>1</sup>, Remy Guillevin<sup>2</sup>, Alexandre Vignaud<sup>1</sup>, Fawzi
- 6 Boumezbeur<sup>1</sup>
- <sup>7</sup> NeuroSpin, CEA, CNRS, BAOBAB, University Paris-Saclay, Gif-sur-Yvette, France
- 2 Lab Com I3M, Dactim team LMA CNRS 7348 CHU & University of Poitiers, France
- 3 University Paris-Saclay, CEA, Inria, MIND, Palaiseau, France
- 4 Siemens Healthcare SAS, Saint-Denis, F-93210, France
- 5 Department of Neurology, RWTH Aachen University, Aachen, Germany.
- \* Corresponding author:

13

14

Name Fawzi Boumezbeur

**Department** NeuroSpin

Institute CEA

Address Centre d'études de Saclay, Building 145,

F-91191, Gif-sur-Yvette

France

**E-mail** fawzi.boumezbeur@cea.fr

Manuscript word count: 3317 out of 5000

Abstract word count: 210 out of 250

# 5 Detailed Word Count (not to be included for submission)

43

```
File: main.tex
   Sum count: 3525
17
   Words in text: 3390
   Words in headers: 55
   Words outside text (captions, etc.): 0
   Number of headers: 22
   Number of floats/tables/figures: 0
   Number of math inlines: 50
   Number of math displayed: 8
   Subcounts:
     text+headers+captions (#headers/#floats/#inlines/#displayed)
26
     1+0+0 (0/0/0/0) Subsection
27
     209+1+0 (1/0/0/0) Abstract
28
     747+1+0 (1/0/7/0) Section: Introduction
29
     0+3+0 (1/0/0/0) Section: Material and methods
30
     265+2+0 (1/0/16/5) Subsection: SPARKLING trajectories
31
     160+2+0 (1/0/0/2) Subsection: TPI trajectories
32
     383+7+0 (3/0/12/0) Subsection: In vitro experiments
33
     212+6+0 (3/0/4/0) Subsection: In vivo experiments
34
     306+11+0 (4/0/7/1) Subsection: Data Processing
     0+1+0 (1/0/0/0) Section: Results
36
     50+6+0 (1/0/0/0) Subsection: Expected spatial resolution - Point spread functions
37
     85+3+0 (1/0/0/0) Subsection: In vivo \Na images
38
     238+6+0 (1/0/1/0) Subsection: In vitro validation of TSC quantification
39
     63+4+0 (1/0/2/0) Subsection: In vivo TSC maps
40
     570+1+0 (1/0/1/0) Section: Discussion
41
     101+1+0 (1/0/0/0) Section: Conclusions
42
```

44 Abstract

**Purpose**: To evaluate the benefits of SPARKLING, a stochastic k-space sampling approach over the deterministic sampling scheme TPI (Twisted Projection Imaging) in the context of accelerated cerebral <sup>23</sup>Na MRI and assessing its impact on tissue sodium concentration (TSC) estimation.

Methods: Guided by simulation results, in vitro and in vitro UTE <sup>23</sup>Na MRI datasets were acquired at a 4 mm isotropic resolution from healthy volunteers using both TPI or SPARKLING trajectories with different acceleration factors (AF) on a 7T MR scanner equipped with a 32 channels head coil. Following reconstruction using NUFFT or Proximal Optimized Gradient Method (POGM) algorithms with or without regularization, respectively, the resulting sodium images were compared in terms of effective resolution (FWHM of the PSF), SNR and overall quality. with an in vitro assement of the accuracy of the TSC was performed via external referencing using a 4-point calibration approach.

**Results**: In vivo cerebral sodium images acquired using SPARKLING with an acceleration factor of 32 (TA= 5 min 38 s) are similar to those obtained using TPI at AF=8 (TA= 22 min 34 s) with minimal impact on the accuracy of our TSC quantification.

Conclusion: In conditions compatible with clinical examination, undersampled SPARKLING <sup>23</sup>Na MRI can outperform the conventional TPI k-space sampling scheme allowing for shorter acquisition times.

**Keywords**: <sup>23</sup>Na, SPARKLING, UHF, human brain, TSC, compressed sensing

# Introduction

Cerebral sodium (<sup>23</sup>Na) magnetic resonance imaging (MRI) provides unique information about brain 65 tissue viability in vivo. Indeed, neurons rely on the energy-hungry sodium-potassium (Na<sup>+</sup>/K<sup>+</sup>-66 ATPase) pump to regulate their transmembrane Na<sup>+</sup> and K<sup>+</sup> concentration gradients, which in their turn define their resting membrane potential. In pathological conditions where the cell membranes are damaged or their energy synthesis capabilities are compromised, an increase in intracellular 69 sodium concentration is bound to occur, while extracellular sodium concentration stays constant. This leads to an increase in tissue sodium concentration (TSC), neuronal dysfunction, and ultimately 71 cell death (Mccarthy et al., 2015). 72 Therefore changes in TSC are considered potential early biomarkers for many neurodegenerative 73 diseases. Several studies confirmed the relevance of assessing tissue sodium concentration (TSC) in neurological disorders such as Alzheimer's (Haeger et al., 2021), Multiple Sclerosis (MS) (Zaaraoui 75 et al., 2012; Eisele et al., 2019), Huntington's, (Reetz et al., 2012) and others (Zaric et al., 2021). 76 However,  $^{23}$ Na-MRI faces several technical challenges, limiting its clinical use. This is mainly due 77 to the moderate sodium concentration in the human brain (about 40 mM in the brain parenchyma 78 and 140 mM in the cerebrospinal fluid (CSF)) and its low intrinsic nuclear magnetic resonance 79 (NMR) sensitivity compared to proton MRI. In the healthy brain, those differences can lead to up 5500 fold less Signal-To-Noise Ratio (SNR) (Ladd et al., 2018). Consequently, <sup>23</sup>Na images have 81 to be acquired at lower spatial resolutions and require long acquisition time (TA) compared to <sup>1</sup>H MRI.. 83 Another difficulty is the fast transverse relaxation times  $(T_2/T_2^*)$  of <sup>23</sup>Na NMR signal, which are typically less than 5 ms (Ridley et al., 2018). Consequently, ultra-short echo time (UTE) sequences 85 combined with deterministic non-Cartesian k-space trajectories have been preferred (Konstandin 86 and Nagel, 2014) by the <sup>23</sup>Na MRI community. Among the most commonly used non-Cartesian 87 k-space sampling schemes, we can cite radial, density-adapted three-dimensional radial projection 88 reconstruction pulse sequence (DA-3DPR) (Nagel et al., 2009), twisted projection imaging (TPI) 89 (Boada et al., 1997) or Fermat-looped orthogonally-encoded trajectories (FLORET) (Robison et al., 91 These standard non-Cartesian readouts are flexible, as they are analytically and geometrically 92 constrained, and, when combined with density-compensated reconstruction, can provide good image quality. However they can be sub-optimal in sampling the k-space, especially for k values at the

borders of k-space which can lead to fast degrading spatial resolutions when the k-space is undersampled (as demonstrated by their computed point spread function (PSF) (Konstandin and Nagel, 2014)). In recent years, compressed-sensing (CS) approaches have been proposed for proton MRI (Dale et al., 2004; Mir et al., 2004; Kumar Anand et al., 2008; Vasanawala et al., 2010) in order to to accelerate image acquisition while preserving image quality. 99 At first, proton MRI CS approaches took advantage (i) of the sparse characteristic of MRI signals, 100 (ii) incoherent sampling schemes, and (iii) nonlinear reconstruction with a sparsity promoting prior. 101 Currently, the concept of an incoherent sampling scheme is considered sub-optimal (Adcock et al., 102 2017) and newer CS techniques focus on (i) globally variable density sampling non-uniformally the 103 high and low spatial frequencies but managing (ii) a locally uniform coverage of k-space (Donoho, 2006). 105 Recently, Chen et al. reviewed the first attempts at applying CS to <sup>23</sup>Na MRI (Chen et al., 2021). 106 Some of those studies have evaluated the impact of acceleration on TSC, as TSC is the primary goal 107 of <sup>23</sup>Na MRI. Twelve out of seventeen studies used radial or DA-3DPR as a sampling scheme, and 108 only one used a version of TPI (Nagel et al., 2009). Yet the authors assumed the incoherence of those 109 density-adapted three-dimensional radial projection reconstruction pulse sequence (DA-3DPR) or 110 TPI trajectories. Indeed, the efficacy of CS approach relies on the fulfilment of an "incoherence" 111 criterion. This criterion states that the measurement basis and the sparse representation basis must 112 be uncorrelated so that the k-space undersampling artifacts add incoherently to the sparse signal 113 coefficients. While few studies have proposed optimized undersampling schemes for proton MRI by using a series of second-order cone optimization sub-problems, ideas from the missile guidance field 115 or other strategies (Kumar Anand et al., 2008; Mir et al., 2004; Dale et al., 2004), none of those 116 previously cited CS <sup>23</sup>Na MRI studies explored such solutions to optimize the incoherence of their undersampled density-adapted three-dimensional radial projection reconstruction pulse sequence 118 (DA-3DPR) or TPI trajectories. 119 Here, we propose to apply SPARKLING (Spreading Projection Algorithm for Rapid K-space 120 sampLING) (Lazarus et al., 2020; Chaithya et al., 2022) to accelerate <sup>23</sup>Na MRI acquisitions. 121 SPARKLING is inspired by CS approaches with a (i) global variable density sampling but (ii) 122 locally uniform coverage of k-space. Compared to more classical approaches, this approach is an 123 excellent candidate for shortening the TA while preserving image quality in <sup>23</sup>Na MRI.

The application of CS techniques to sodium imaging presents its specific challenges because the acceleration achievable using CS approaches depends on the image size and available SNR: for both,

124

125

126

the bigger it is, the better Lazarus et al. (2018). Unfortunately for  $^{23}$ Na MRI, both are limiting factors compared to  $^{1}$ H MRI.

In this study, for the first time, we aimed at demonstrating that we can accelerate in vivo  $^{23}$ Na acquisitions at 7T and perform valid TSC quantification using 3D SPARKLING. We compare our effort to current state-of-the-art TPI acquisitions with identical acquisitions parameters ( $T_{obs}$ , bandwidth (BW), flip angle, and repetition time (TR)). Our study design was divided in two parts (i) in vitro measurements to assess the impact of the different AF on TSC quantification, and (ii) in vivo experiments to analyze the resulting quality of our cerebral TSC maps acquired from healthy human volunteers.

# 136 Material and methods

# 137 SPARKLING trajectories

The SPARKLING algorithm (Lazarus, 2019) generates optimized k-space sampling patterns  $\mathbf{K}[i] = (k_{x,i}, k_{y,i}, k_{z,i})$ , where i represents a sample which comply to a target acquisition density. At the same time, SPARKLING respects MR hardware limitations such as maximum gradient amplitudes and slew rates. SPARKLING generally focuses on radially symmetric densities, which present the advantage of yielding results invariant to translation and rotation of the sample to the image. This target density is defined by two parameters: cutoff (C) and decay (D) (figure 1). They are defined as follows:

$$\pi_{C,D}(x) = \begin{cases} K & |x| < C \\ K\left(\frac{C}{|x|}\right)^D & |x| > C \end{cases}$$
 [1]

where K is a constant obtained through normalization:

$$K = \frac{1 - D}{2C(C^{D-1} - D)}$$

This algorithm has been extended to 3D and is described in detail elsewhere (Chaithya et al., 2022). 3D SPARKLING offers a locally uniform coverage of k-space, differently from TPI or radial strategies. The trajectory  $\hat{\mathbf{K}}$  is optimized as:

$$\hat{\mathbf{K}} = \arg\min_{\mathbf{K}} F_p(\mathbf{K}) = F_p^a(\mathbf{K}) - F_p^r(\mathbf{K})$$
 [2]

where  $F_p^a(\mathbf{K})$  is the attraction term enforcing the sampling pattern  $\mathbf{K}$  and  $F_p^r(\mathbf{K})$  is the repulsion 148 term which guarantees a good filling of the k-space. The repulsion term  $F_p^r(\mathbf{K})$  and  $F_p^a(\mathbf{K})$  are 149 defined as: 150

$$F_p^r(\mathbf{K}) = \frac{1}{2p^2} \sum ||\mathbf{K}[i] - \mathbf{K}[j]||_2$$
 [3a]

$$F_p^a(\mathbf{K}) = \frac{1}{p} \sum_{\omega} \int_{\omega} ||(x - \mathbf{K}[i])||_2 \rho(x) dx$$
 [3b]

Here, we adopted a variation of SPARKLING, called MORE SPARKLING, (Chaithya G R 151 et al., 2022) to define sets of center-out spokes for  $^{23}\mathrm{Na}$  imaging. In this variation, the  $F_p^r$  factor incorporates a temporal weighting that notably enforces spokes to homogeneously move away from 153 the center and is defined as: 154

$$F_p^r(\mathbf{K}) = \frac{1}{2v^2} \sum \exp^{|t_i - t_j|} ||\mathbf{K}[i] - \mathbf{K}[j]||_2$$
 [4a]

where  $t_i$  and  $t_j$  correspond to the times when the samples  $\mathbf{K}[i]$  and  $\mathbf{K}[j]$  are acquired. This is 155 important to reduce off-resonance artifacts and avoid signal loss due to averaging points at different 156 observation times, which is especially important for the fast relaxing sodium nuclei. 157

The calculation of  $F_p^r$  and  $F_p^a$  is made through a gradient descent algorithm (Chaithya et al., 2022). The code has been optimized for GPU computing, (Chaithya et al., 2022). Interested researchers are invited to contact the authors to obtain access to this package. 160

Twisted projection trajectories (TPI) were introduced in 1997 (Boada et al., 1997). At that time,

#### TPI trajectories

158

159

162

the state-of-the-art k-space sampling schemes for <sup>23</sup>Na MRI were based on radial trajectories. The 163 premise behind TPI is that improvements in the sampling efficiency of three dimensional projection 164 imaging can be attained by removing the non-uniform sample density that results from uniform 165 sampling in time along radial lines in k-space. 166 In three dimensions, the improvement in the efficiency is done through a twist in the trajectories 167 that preserves the sample density. In a thin spherical shell the number of trajectories will be constant 168 if the number of samples inside a thin spherical shell is proportional to the volume of the shell. This 169 can be describe through the equations:

$$\dot{k} = \frac{\alpha}{k^2} \tag{5}$$

and

$$\dot{k} + k^2(\dot{\theta} + \sin^2\theta \dot{\varphi}^2) = \gamma^2 G^2 \tag{6}$$

Examples of TPI and SPARKLING trajectories can been seen in figure 2. The algorithm to generate TPI trajectories was implemented in MATLAB along with others (radial and density adaptive radial) and they are available in a public repository (https://github.com/rpbaptista/Trajectories/).

For our in vitro acquisitions, a realistic human head phantom was used Jona et al. (2021). This

phantom is composed of two compartments (figure 3): the inner compartment was filled with a

## 174 In vitro experiments

#### 175 Test objects

176

solution of 40 mmol/L of NaCl and the outer compartment was filled with a NaCl solution at a 178 higher concentration of 100 mmol/L. This phantom with known design and concentrations was used 179 to assess the effect of the different acceleration strategies on TSC quantification. 180 For TSC calibration, four cylindrical 50mL tubes were filled with 2% agarose gels to obtain 181 shorter, more realistic relaxation times for <sup>23</sup>Na. Sodium (NaCl) concentrations for each tubes were: 182 51, 105, 155 and 209 mM. For each acquisition and reconstruction, the tubes were masked and the 183 signal intensity histograms were analyzed to estimate the reference signal value corresponding to 184 each known sodium concentrations by considering the  $N^{th}$  percentile of the signal distribution, the 185 precise value of this percentile (ranging from 50 to 70) was calibrated separately from full Nyquist 186 images to account for the different partial-volume effects and artifacts affecting the signal intensity 187 distributions in the reference tubes. 188

#### 189 Data acquisition

<sup>23</sup>Na MRI sequence parameters were those determined previously by Coste et al. (2019) to maximize SNR for *in vivo* <sup>23</sup>Na MRI: TE/TR=0.8/20 ms, FOV=296 mm isotropic, FA= 55°, gradient raster time = 10  $\mu$ s, dwell time = 2  $\mu$ s,  $T_obs$  = 12.48 ms,  $N_s$ =6240, 32 averages, oversampling factor (OS) was set to 5.

As a reference image, a 3D radial acquisition fulfilling the Nyquist criteria  $(N_s \ge 4\pi (k_{max}FOV)^2)$ 194 was performed. The acceleration factor (AF) was defined relatively to this full-Nyquist radial ac-195  $\frac{N_{s_{radialfullNyquist}}}{N_{s_{currentacquisition}}}$ quisition: 196 For TPI acquisitions, the radial fraction parameter was set at 0.3, it was optimal parameter 197 in the literature Romanzetti et al. (2014). For SPARKLING acquisitions, the cutoff and decay 198 parameters of the targeted density function were: C = 30% and D = 2 (Fig 2). Four different 199 acceleration factors (AF=(8,32,64,128), TA=(22'30",5'40",2'48",1'28")) were explored for both TPI 200 and SPARKLING sampling schemes. (Fig 2). 201 <sup>23</sup>Na images were acquired at two flip angles (VFA<sub>1</sub>=25°/VFA<sub>2</sub> = 50) to allow for TSC quan-202 tification according to our Variable Flip Angle (VFA) approach Coste et al. (2019). 203 The B<sub>1</sub><sup>+</sup> field map was measured with the TPI sequence using a double angle method (DAM) 204 (Stollberger and Wach;, 1995) approach with  $\alpha_1/\alpha_2=45/90$  at 8 mm isotropic and TE/TR=0.8/120 205

ms. The acquisition time was 1 min 36 seconds per scan. The B<sub>1</sub><sup>+</sup> map was used to improve the

## 208 In vivo experiments

robustness of the computed  $T_1$  and  $M_0$  maps.

#### 209 Participants

206

207

216

This study was approved by local and French national ethics committees (2019-A02689-48) informed consent was obtained from all participants. Five healthy volunteers were recruited. The participants were split in two groups: one cohort in which image quality was assessed (1M/1F) (35±5 years old) and a second cohort (2M/1F) (22 ± 6 years old) in which the accuracy of the TSC quantification was assessed.

#### 15 Data acquisition

equipped with a whole-body gradient coil ( $G_{max}=80 \mathrm{mT/m}$ , slew rate of  $200 \mathrm{mT/m/s}$ ) and a doubletune  $1 \mathrm{Tx}/1 \mathrm{Rx}$  birdcage coil for  $^1 \mathrm{H}$  and  $1 \mathrm{Tx}/32 \mathrm{Rx}$  helmet coil for  $^{23} \mathrm{Na}$  (Rapid Biomedical GmbH, Rimpar, Germany). In vivo acquisitions also included an  $T_1$ -weighted image (MPRAGE, TE/TR/TI = 1.85/1310/500ms,  $FA=6^\circ$ , 1 mm isotropic resolution, TA=3:46 min) for anatomical reference. An iterative secondorder  $B_0$  shimming procedure was performed and the optimal shimming parameters were used during

MRI data were acquired on a Terra 7T MRI scanner (Siemens Healthineers, Erlangen, Germany)

223 the sodium acquisitions.

Sequence parameters for our  $^{23}$ Na MRI and  $B_1^+$  field acquisitions were identical to our in vitro acquisitions.

For the three volunteers of the second cohort, and only for AF=32, 64 and 128 (due to the limited examination time), <sup>23</sup>Na images were acquired using the second flip angle of 25° to allow for TSC quantification Coste et al. (2019).

#### 229 Data Processing

#### 230 Image reconstruction

Density compensation (Pipe and Menon, 1999) was performed using Pysap-MRI (El Gueddari et al., 2020) in all the data. This package allows for the management of large 3D non-Cartesian multichannel datasets. The iterative method was the same for TPI and SPARKLING datasets.

As the density compensation function depends solely on the k-space trajectories, the comparison between TPI and SPARKLING acquisitions remains fair.

While iterative reconstruction methods are expected to be used for CS acquisitions since they typically yield nicer images, it would be difficult to discriminate between the benefits of the un-

dersampled trajectories and those of the iterative reconstruction. Consequently, we chose to reconstruct and evaluate our data using both an iterative reconstruction method using proximal
optimized gradient method (POGM) (Kim et al., 2021) and an non-iterative regridding method

using NUFFT(Fessler and Sutton, 2003).

Our non-linear iterative reconstruction can be described as follows:

$$\hat{\mathbf{z}} = \arg\min_{\mathbf{z}} \frac{1}{2} ||y - ||_2^2 + \lambda ||z||_1$$

For each iterative reconstruction, the regularization parameter ( $\lambda$ ) were selected visually in the  $10^{-7}$  to  $10^{-20}$  range (30 steps) to maximize image quality.  $\lambda$  was kept constant between volunteers for a given acceleration factor and a given trajectory.

#### 246 TSC Quantification

241

242

In this study, the variable flip angle (VFA) approach was used as described in Coste et al. (2019) to estimate  $M_0$  maps which were corrected for residual  $T_1$ -weighting from the combination of two sodium images acquired at two different FA. Those  $M_0$  images were also corrected for any  $B_1^+$ 

inhomogeneities by accounting for the effective flip angles as measured from the independently acquired  $B_1^+$  field map.

To obtain quantitative TSC maps, four 50mL tubes were used as external references of concentration. The quantification process consisted in automatically segmenting those tubes in the last 23Na images, extracting their signal intensity distribution and performing a four-point linear regression using the reference signal values corresponding to each tubes against their known sodium concentrations.

# 257 Evaluation of TSC quantification accuracy

The accuracy of the TSC quantification was evaluated based on in vitro <sup>23</sup>Na images of the anthropomorphic human head phantom with known sodium concentrations. Relative errors in the TSC quantification were calculated and compared between undersampled TPI and SPARKLING acquisitions.

# 262 Results

#### 263 Expected spatial resolution - Point spread functions

Table 1 summarizes the FWHM of the PSF computed for each set of SPARKLING and TPI spokes.

The effective spatial resolution was consistently higher for undersampled SPARKLING trajectories
compared to their TPI counterparts. Figure 4 shows the central slice of the log of the PSF for the
investigated TPI and SPARKLING trajectories.

# <sup>268</sup> In vivo <sup>23</sup>Na images

Figure 5 shows a gallery of axial <sup>23</sup>Na MRI obtained from our first two healthy volunteers. As expected from the comparison of the PSF, undersampled SPARKLING strategies seems to better preserve high spatial frequency details such as the cortex delineation for bigger accelerations factors compared to TPI. This is particularly clear when comparing the images acquired with SPARKLING with an AF=32 to the ones acquired with TPI and an AF=8.

Figure 6 shows the result of the reconstruction of our accelerated <sup>23</sup>Na MRI using the POGM algorithm.

# 276 In vitro validation of TSC quantification

For all our linear regressions performed across different accelerations factors for calibration,  $R^2$  values were systematically superior to 0.96, demonstrating the robustness of the 4-point calibration method (see figure S1 for illustration).

Tables 2 and 3 summarize the average sodium concentration in the inner compartment of our anthropomorphic phantom estimated from TSC maps acquired *in vitro* with the different undersampled strategies and reconstructed with NUFFT or POGM respectively.

One can notice that undersampled TPI acquisitions lead to slightly larger apparent sodium concentration and quantification errors compared to undersampled SPARKLING acquisitions. This is consistent with the broader PSF of undersampled TPI. Yet for both TPI and SPARKLING, the quantification remained quite accurate up to an acceleration factor of 32, the relative quantification error being at about 2.5% when NUFFT was used for the reconstruction.

When using the POGM iterative method, the resulting TSC maps exhibited systematically larger quantification errors than their NUFFT counterparts. Yet for AF=8 or even for AF=32 and SPARKLING, the quantification biais introduced by the regularization in POGM seemed to be manageable.

For both trajectories, the higher accelerations were extremely detrimental to the accuracy of the quantification and should not be considered as a viable option for quantitative <sup>23</sup>Na MRI. For instance, for AF=128, the resulting TSC maps displayed relative errors of about 85% for TPI and 67.5% for SPARKLING with the NUFFT reconstruction. These values would increase to 175% for TPI and 153% for SPARKLING when POGM is used.

# <sup>297</sup> In vivo TSC maps

Figure 7 shows the TSC maps acquired from three healthy volunteers using both TPI and SPARKLING trajectories with an acceleration factor of 32 (acquisition time = 5'40"). As already observed for our *in vitro* data, TSC values were found sensibly higher for TPI compared to SPARKLING, the average difference being  $2 \pm 3$  mM when using the NUFFT reconstruction whereas it was  $11 \pm 2$  mM when using the iterative POGM iterative reconstruction.

# 303 Discussion

333

In this study, we investigated for the first time the application of SPARKLING (precisely MORE-SPARKLING) Lazarus (2019); Chaithya G R et al. (2022), a stochastic k-space sampling strategy to accelerate the acquisition of quantitative <sup>23</sup>Na MRI of the human brain at 7T.

As a popular and efficient deterministic non-Cartesian k-space sampling scheme, undersampled TPI datasets Boada et al. (1997) were acquired systematically to serve as comparison points.

From those comparisons, one can conclude that in the right conditions (i.e. at 7T for a resolution of 4 mm isotropic, a 32 channel coil and 32 averages) undersampled SPARKLING acquisitions outperform TPI for the same AF both in terms of image quality and accuracy of the TSC quantification.

In particular, we observed that sodium images acquired using undersampled SPARKLING at AF=32 exhibited similar visual qualities than the ones acquired using undersampled TPI at AF=8. We also estimated that this level of acceleration (AF=32) using SPARKLING (with either NUFT or POGM reconstructions) led to acceptable quantification errors (2,5%) while the relative error for TPI and AF=32 was much larger (27%).

There are likely two reasons for these differences between undersampled TPI and SPARKLING 318 strategies. The first one should be the narrower PSF estimated for SPARKLING compared to TPI 319 for the same number of spokes (Table 1). It is of import to notice than these computed PSF did 320 not take into account the impact of  $B_0$  inhomogeneities across the brain, nor the influence of the 321 reconstruction algorithm used of CS reconstructions. Such evaluation is not trivial and was not 322 explored in this work. The second factor should be that deterministic trajectories such TPI are 323 less likely to satisfy the "incoherence criterion" compared to the stochastic SPARKLING approach, 324 especially in absence of some optimization of the undersampling of k-space. 325

Recent studies (Gnahm et al., 2014; Blunck et al., 2020) have explored CS techniques for 3 mm isotropic at 7T while using DA-3DPR. Here, we targeted a resolution of 4 mm isotropic, which is a good trade-off for clinical examination in terms of TA and image quality. The authorship should refrain from extrapolating these results to different spatial resolutions or nuclei as the performance of CS approaches depends strongly on the available SNR and image sizes. This means that deterministic k-space sampling strategies such as TPI remain of actuality in most scenarios, especially in absence of acceleration or for modest acceleration factors.

As the determination of scenarios of interest for SPARKLING is not trivial (Lazarus, 2019), a

simulation tool was developed to assess efficiently different scenarios in silico (Porciuncula Baptista et al., 2022).

In preliminary studies, we measured image quality via the structural similarity index measure (SSIM) compared to a Full-Nyquist radial reference. This approach was not kept because SSIM (Wang et al., 2015) is known to not be robust to blurring effects and PSF distortions, leading to misleading results, ie, high SSIM and low image quality.

One of the main limitation of SPARKLING as a k-space sampling strategy is its lack of flexibility. Indeed, compared to deterministic and parametric sampling schemes, the computation of
SPARKLING trajectories is quite intensive and the different trajectories must be determined offline or made available in a library. These constitute real hurdles for the future application of such
approach in a clinical research setting. Still we believe that improvements in image quality and
reduction in acquisition times while preserving the accuracy of the TSC quantification are worth
the continuing investment in developing and implementing ever faster optimization techniques and
reconstruction systems.

In the future, those promising results could be improved further by adding a priori anatomical constraints or using dictionary learning techniques (Behl et al., 2016).

# 350 Conclusions

For the first time, SPARKLING a novel k-space sampling strategy for CS MRI was applied successfully to accelerate the acquisition of <sup>23</sup>Na MRI at 7T in few healthy volunteers. We showed that in those favorable conditions, the acquisition of quantitative TSC maps could be accelerated by a factor 32 using SPARKLING with minimal loss of anatomical details or accuracy in the calibration process. Besides the application of those accelerated TSC maps to investigate abnormally high TSC values in brain pathologies, the relative rapidity of these <sup>23</sup>Na acquisitions could be of interest to revisit the sodium changes observed during neuronal activation as proposed by Bydder et al. (2019).

# Acknowledgments

This work received financial support from Leducq Foundation (large equipment ERPT program, NEUROVASC7T project). Chaithya G R was supported by the CEA NUMERICS program, which has received funding from the European Union's Horizon 2020 research and innovation program

under the Marie Sklodowska-Curie grant agreement No 800945. This work was granted access to the HPC resources of IDRIS under the allocation 2021-AD011011153 made by GENCI.

# References

- Adcock B, Hansen AC, Poon C, Roman B. 2017. Breaking the coherence barrier: A new theory for compressed sensing. Forum of Mathematics, Sigma 5. doi:10.1017/fms.2016.32. 1302.0561.
- Behl NG, Gnahm C, BacherT P, Ladd ME, Nagel AM. 2016. Three-dimensional dictionary-learning reconstruction of 23Na MRI data. Magnetic Resonance in Medicine 75:1605–1616. doi:10.1002/ mrm.25759.
- Blunck Y, Kolbe SC, Moffat BA, Ordidge RJ, Cleary JO, Johnston LA. 2020. Compressed sensing
  effects on quantitative analysis of undersampled human brain sodium MRI. Magnetic Resonance
  in Medicine 83:1025–1033. doi:10.1002/mrm.27993.
- Boada FE, Gillen JS, Shen GX, Chang SY, Thulborn KR. 1997. Fast three dimensional sodium imaging. Magnetic Resonance in Medicine 37:706–715. doi:10.1002/mrm.1910370512.
- Bydder M, Zaaraoui W, Ridley B, Soubrier M, Bertinetti M, Confort-Gouny S, Schad L, Guye M,
  Ranjeva JP. 2019. Dynamic 23Na MRI A non-invasive window on neuroglial-vascular mecha-
- nisms underlying brain function. NeuroImage 184:771–780. doi:10.1016/j.neuroimage.2018.09.071.
- Chaithya G, Weiss P, Daval-Frérot G, Massire A, Vignaud A, Ciuciu P. 2022. Optimizing full
  379 3d sparkling trajectories for high-resolution magnetic resonance imaging. IEEE Transactions on
  380 Medical Imaging:1–1doi:10.1109/TMI.2022.3157269.
- Chaithya G R, Guillaume Daval-Frérot, Aurélien Massire, Boris Mailhe, Mariappan Naddar, Alexandre Vignaud, Philippe Ciuciu. 2022. MORE-SPARKLING: Non-Cartesian trajectories with Minimized Off-Resonance Effects. In: Proceedings of the 30th International Society of Magnetic Resonance in Medicine.
- Chen Q, Shah NJ, Worthoff WA. 2021. Compressed Sensing in Sodium Magnetic Resonance Imaging:
  Techniques, Applications, and Future Prospects. Journal of Magnetic Resonance Imaging: 1–
  17doi:10.1002/jmri.28029.

- Coste A, Boumezbeur F, Vignaud A, Madelin G, Reetz K, Le Bihan D, Rabrait-Lerman C, Ro-
- manzetti S. 2019. Tissue sodium concentration and sodium T1 mapping of the human brain
- at 3 T using a Variable Flip Angle method. Magnetic Resonance Imaging 58:116–124. doi:
- 10.1016/j.mri.2019.01.015.
- Dale BM, Lewin JS, Duerk JL. 2004. Optimal design of space trajectories using a multi-objective
- genetic algorithm. Magnetic Resonance in Medicine 52:831–841. doi:10.1002/mrm.20233.
- Donoho DL. 2006. Compressed sensing. IEEE Transactions on Information Theory 52:1289–1306.
- doi:10.1109/TIT.2006.871582.
- Eisele P, Konstandin S, Szabo K, Ebert A, Roßmanith C, Paschke N, Kerschensteiner M, Platten
- M, Schoenberg SO, Schad LR, Gass A. 2019. Temporal evolution of acute multiple sclerosis
- lesions on serial sodium (23 Na) MRI. Multiple Sclerosis and Related Disorders 29:48–54. doi:
- 10.1016/j.msard.2019.01.027.
- 400 El Gueddari L, Gr C, Ramzi Z, Farrens S, Starck S, . 2020. PvSAP-MRI: a Python Package for
- MR Image Reconstruction. . . . Image Reconstruction :8.
- Fessler J, Sutton B. 2003. Nonuniform fast fourier transforms using min-max interpolation. IEEE
- 403 Transactions on Signal Processing 51:560–574. doi:10.1109/TSP.2002.807005.
- 404 Gnahm C, Bock M, Bachert P, Semmler W, Behl NG, Nagel AM. 2014. Iterative 3D projec-
- tion reconstruction of 23Na data with an 1H MRI constraint. Magnetic Resonance in Medicine
- 406 71:1720–1732. doi:10.1002/mrm.24827.
- 407 Haeger A, Bottlaender M, Lagarde J, Porciuncula Baptista R, Rabrait-Lerman C, Luecken V,
- Schulz JB, Vignaud A, Sarazin M, Reetz K, Romanzetti S, Boumezbeur F. 2021. What can 7T
- sodium MRI tell us about cellular energy depletion and neurotransmission in Alzheimer's disease?
- 410 Alzheimer's and Dementia 17:1843–1854. doi:10.1002/alz.12501.
- Jona G, FurmanHaran E, Schmidt R. 2021. Realistic head [U+2010] shaped phantom with
- brain [U+2010] mimicking metabolites for 7 T spectroscopy and spectroscopic imaging. NMR
- in Biomedicine 34. doi:10.1002/nbm.4421.
- 414 Kim SY, Song J, Yoon JH, Kim KN, Chung JY, Noh Y. 2021. Voxel-wise partial volume correction
- method for accurate estimation of tissue sodium concentration in 23Na-MRI at 7 T. NMR in
- Biomedicine 34:3–5. doi:10.1002/nbm.4448.

- 417 Konstandin S, Nagel AM. 2014. Measurement techniques for magnetic resonance imaging of fast
- relaxing nuclei. Magnetic Resonance Materials in Physics, Biology and Medicine 27:5–19. doi:
- 10.1007/s10334-013-0394-3.
- 420 Kumar Anand C, Thomas Curtis A, Kumar R. 2008. Durga: A heuristically-optimized data collec-
- tion strategy for volumetric magnetic resonance imaging. Engineering Optimization 40:117–136.
- doi:10.1080/03052150701641783.
- Ladd ME, Bachert P, Meyerspeer M, Moser E, Nagel AM, Norris DG, Schmitter S, Speck O, Straub
- S, Zaiss M. 2018. Pros and cons of ultra-high-field mri/mrs for human application. Progress in
- Nuclear Magnetic Resonance Spectroscopy 109:1–50. doi:https://doi.org/10.1016/j.pnmrs.2018.
- 426 06.001.
- 427 Lazarus C. 2019. Compressed Sensing in MRI: optimization-based design of k-space filling curves
- for accelerated MRI To cite this version: L'echantillonnage compressif en IRM: conception
- optimis ee trajectoires d'echantillonnage 'erer pour acc el l'IRM. [[Doctoral thesis]]: .
- 430 Lazarus C, Weiss P, El Gueddari L, Mauconduit F, Massire A, Ripart M, Vignaud A, Ciu-
- ciu P. 2020. 3D variable [U+2010] density SPARKLING trajectories for high [U+2010] resolution
- T2\*[U+2010] weighted magnetic resonance imaging. NMR in Biomedicine 33. doi:10.1002/nbm.
- 4349.
- 434 Lazarus C, Weiss P, Vignaud A, Ciuciu P. 2018. An empirical study of the maximum degree
- of undersampling in compressed sensing for T2\* -weighted MRI. Magnetic Resonance Imaging
- 53:112–122. doi:10.1016/j.mri.2018.07.006.
- 437 Mccarthy JV, Mccarthy JV, Cotter TG. 2015. Cell shrinkage and apoptosis: a role for potassium
- and sodium ion efflux Cell shrinkage and apoptosis: a role for potassium and sodium ion efflux.
- Cell Death and Differentiation (1997) i:756–770.
- 440 Mir R, Guesalaga A, Spiniak J, Guarini M, Irarrazaval P. 2004. Fast three-dimensionalk-space
- trajectory design using missile guidance ideas. Magnetic Resonance in Medicine 52:329–336.
- doi:10.1002/mrm.20163.
- Nagel AM, Laun FB, Weber MA, Matthies C, Semmler W, Schad LR. 2009. Sodium MRI using a
- density-adapted 3D radial acquisition technique. Magnetic Resonance in Medicine 62:1565–1573.
- doi:10.1002/mrm.22157.

- <sup>446</sup> Pipe JG, Menon P. 1999. Sampling density compensation in MRI: Rationale and an iterative numer-
- ical solution. Magnetic Resonance in Medicine 41:179–186. doi:10.1002/(SICI)1522-2594(199901)
- 41:1<179::AID-MRM25>3.0.CO;2-V.
- Porciuncula Baptista R, Vignaud A, Chaithya G R, Daval-Frérot G, Mauconduit F, Naudin M,
- Lapert M, Guillevan R, Ciuciu P, Lerman-Rabrait C, Boumezbeur F. 2022. Evaluation of 3D
- 451 SPARKLING for undersampled Sodium UTE MRI at ultra-high magnetic field. In: Proceedings
- of the 30th International Society of Magnetic Resonance in Medicine.
- Reetz K, Romanzetti S, Dogan I, Saß C, Werner CJ, Schiefer J, Schulz JB, Shah NJ. 2012. Increased
- brain tissue sodium concentration in Huntington's Disease A sodium imaging study at 4T.
- NeuroImage 63:517–524. doi:10.1016/j.neuroimage.2012.07.009.
- Ridley B, Nagel AM, Bydder M, Maarouf A, Stellmann JP, Gherib S, Verneuil J, Viout P, Guye
- M, Ranjeva JP, Zaaraoui W. 2018. Distribution of brain sodium long and short relaxation times
- and concentrations: a multi-echo ultra-high field 23Na MRI study. Scientific Reports 8:1–12.
- doi:10.1038/s41598-018-22711-0.
- Robison RK, Anderson AG, Pipe JG. 2017. Three-dimensional ultrashort echo-time imaging using
- a FLORET trajectory. Magnetic Resonance in Medicine 78:1038–1049. doi:10.1002/mrm.26500.
- Romanzetti S, Mirkes CC, Fiege DP, Celik A, Felder J, Shah NJ. 2014. Mapping tissue sodium
- concentration in the human brain: A comparison of MR sequences at 9.4 Tesla. NeuroImage
- 96:44-53. doi:10.1016/j.neuroimage.2014.03.079.
- 465 Stollberger R, Wach; P. 1995. Imaging of the active B1 field in vivo. Magnetic Resonance in
- Medicine:73-75doi:0740-3194/96.
- Vasanawala SS, Alley MT, Hargreaves Ba, Barth Ra, Pauly JM, Lustig M. 2010. Improved Pediatric
- MR Imaging with Compressed Sensing. Radiology 256:607–616. doi:10.1148/radiol.10091218.
- Wang H, Hristov D, Qin J, Tian L, Willmann, Jürgen K. 2015. Three-dimensional Dynamic
- 470 Contrast-enhanced US Imaging for Early Antiangiogenic. Radiology 277:424–434.
- Zaaraoui W, Konstandin S, Audoin B, Nagel AM, Rico A, Malikova I, Soulier E, Viout P, Confort-
- Gouny S, Cozzone PJ, Pelletier J, Schad LR, Ranjeva JP. 2012. Distribution of Brain Sodium
- Accumulation Correlates with Disability in Multiple Sclerosis: A cross-sectional 23Na MR Imag-
- ing Study. Radiology 264:859–867. doi:10.1148/radiol.12112680/-/DC1.

Zaric O, Juras V, Szomolanyi P, Schreiner M, Raudner M, Giraudo C, Trattnig S. 2021. Frontiers of
 sodium mri revisited: From cartilage to brain imaging. Journal of Magnetic Resonance Imaging
 54:58–75.

# Figures and Tables





Figure 1: Target density function for SPARKLING and its parameters

Example of target density function for SPARKLING  $Pi_{C,D}(x)$  illustrating the definition of both parameters: cutt-off (C) and decay (D).






Figure 2: **TPI** (left) and **SPARKLING** (right) k-space sampling schemes

Each spoke is colored in blue at its start and in yellow at its end. For both TPI and SPARKLING,  $T_{obs}$  was equal to 12.48 ms.




Figure 3: Anthropomorphic human head phantom. The inner and outer compartments were filled respectively with a 40 and 100 mmol/L NaCl solution. Courtesy of Thadee Delaree





Figure 4: Estimated Point-spread functions of each investigated undersampled SPARKLING and TPI k-space sampling strategy.

The PSF are plotted in log scale to better visualize the ripples surrounding the central lobe.



 $\label{eq:sparkling} \begin{tabular}{ll} Figure 5: Undersampled TPI and SPARKLING acquisitions reconstructed with NUFFT with density compensation. \end{tabular}$ 

Isotropic resolution of 4 mm. TE/TR=0.8/20 ms. Acquisitions times indicated next to each image.




Figure 6: Undersampled TPI and SPARKLING acquisitions reconstructed with POGM iterative algorithm with density compensation.

Isotropic resolution of 4 mm. TE/TR=0.8/20 ms. Acquisitions times indicated next to each image.




Figure 7: Comparison of the TSC maps obtained using undersampled TPI and SPARKLING acquisitions (AF=32) and POGM iterative reconstruction.

Isotropic resolution of 4 mm. TE/TR=0.8/20 ms. TA=11' 20 ".FA<sub>1</sub>/FA<sub>2</sub>=25/50.

Table 1: Full-width at half maximum (FWHM) for the Point-spread functions (PSF) estimated for each undersampling strategy.

Targeted spatial resolution (pixel size) is 4mm isotropic

	FWHM (in pixels in the three dimensions)					
	AF=8	AF=32	AF=64	AF=128		
TPI	(2.4, 2.4, 2.4)	(2.6,2.6,2.6)	(2.6, 2.6, 2.6)	(2.6,2.6,2.6)		
SPARKLING	(2.2, 2.2, 2.2)	(2.2,2.2,2.2)	(2.4, 2.4, 2.4)	(2.4,2.4,2.4)		

Table 2: Mean TSC estimated within the inner compartment of the anthropomorphic phantom using NUFFT and increasing AF.

mean  $\pm$  standard deviation, concentrations expressed in mM. Expected TSC is 40 mM.

AF Trajectory	8	32	64	128
TPI	$40 \pm 4$	$42\pm2$	$56 \pm 4$	$74 \pm 5$
SPARKLING	$42 \pm 3$	$41 \pm 2$	$55 \pm 3$	$67 \pm 4$

Table 3: Mean TSC estimated within the inner compartment of the anthropomorphic phantom using POGM and increasing AF.

mean  $\pm$  standard deviation, concentrations expressed in mM. . Expected TSC is 40 mM.

AF Trajectory	8	32	64	128
TPI	$42\pm2$	$51 \pm 3$	$70 \pm 5$	$110 \pm 7$
SPARKLING	$44 \pm 2$	$39 \pm 2$	$65 \pm 5$	$103 \pm 6$




Figure S1: Example of a 4-point calibration curve for one of the *in vitro* undersampled SPARKLING (AF=128) acquisition.

The linear regression ( $R^2$ =0.99) does not cross at (0,0) due to the background noise with a non-zero mean due to its Rician nature.