



HAL
open science

On learning node selection in a branch and bound algorithm

Zacharie Alès, Marc Etheve, Côme Bissuel, Olivier Juan, Safia Kedad-Sidhoum

► **To cite this version:**

Zacharie Alès, Marc Etheve, Côme Bissuel, Olivier Juan, Safia Kedad-Sidhoum. On learning node selection in a branch and bound algorithm. Conférence ROADEF 2021, Apr 2021, Mulhouse, France. hal-03940726

HAL Id: hal-03940726

<https://hal.science/hal-03940726v1>

Submitted on 16 Jan 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

On Learning Node Selection in a Branch and Bound Algorithm

Marc Etheve^{1,3} Zacharie Alès^{2,3} Côme Bissuel¹ Olivier Juan¹
Safia Kedad-Sidhoum³

¹ EDF R&D, France

`{marc.etheve, come.bissuel, olivier.juan}@edf.fr`

² ENSTA Paris, Institut Polytechnique de Paris, France

`zacharie.ales@ensta-paris.fr`

³ CNAM Paris, CEDRIC, France

`safia.kedad_sidhoum@cnam.fr`

Mots-clés : *Machine Learning, Mixed Integer Linear Programming, Branch and Bound, Node Selection Strategy*

1 Introduction

Over the past few years, the study of interactions between Combinatorial Optimization and Machine Learning has been a growing field of research. In particular, learning the heuristically made choices along a Branch and Bound algorithm has been targeted by the literature (see [1] for a survey). The majority of the approaches is dedicated to learning to imitate the behaviour of solver's heuristics (see for instance [2, 3, 4, 5, 6]), using imitation learning.

On the contrary, quite few address the task of discovering new policies, undoubtedly due to the difficulty of the challenge. [7] learns a cutting strategy amongst Gomory's cutting planes, In this preliminary work, we extend the methodology presented in [8] to the node selection strategy, using reinforcement learning to discover such strategy. An alternative approach, using supervised learning, is also proposed.

2 Framework

Our goal is to design a node selection policy in a Branch and Bound procedure. The considered instances should come from a same given Mixed Binary Linear Problem. As a consequence, they share the same structure, *i.e.* the same dimensions and null coefficients. The objective of the designed node selection policy is to build trees of minimal size on such instances.

As in [9], we focus on learning the selection of one of the two node's children, once the branching variable has been selected. To ensure the coherence of the proposed methods, we enforce the use of Depth-First Search (DFS) and solve instances to optimality.

3 Node selection using Supervised Learning

Let us make two hypotheses in this section :

H1 : the branching strategy is only dependent on the current branching state.

H2 : the optimal integer solution is unique.

When dealing with the node selection strategy in a simple B&B procedure, one can first acknowledge that, under H1, the node selection strategy has no impact on the tree size once the optimal solution of the instance has been found.

As a consequence, when the optimal integer solution is unique (H2), choosing at each node the

child leading to the optimal solution (if possible) will minimize the number of nodes processed to reach it, hence the size of the entire tree.

Our approach is then to predict, at each node, the optimal integer solution of the according sub-problem. Once the branching variable has been selected, we then visit first the child node corresponding to the predicted solution. A classifier is trained to predict the optimal integer solution (if any) at each node, the training data being drawn from the according node selection strategy.

4 Node selection using Reinforcement Learning

In addition to the hypotheses previously mentioned, a limit to the supervised approach is the absence of the notion of risk. As a classifier cannot predict perfectly the optimal node, it seems to be important to limit the occurrence of harmful errors.

Under DFS, the optimal choice presented above is equivalent to visiting first the child which will minimize the subtree size rooted in the current node. On the contrary, a harmful error would be choosing a child which leads to a large subtree.

Using Approximate Q-learning, we train an agent to design the node selection policy. The Q-value at current node is defined as a discounted version of the subtree size and the policy is given by the minimization of the predicted Q-value. Doing so, the agent can quantify the cost of a bad node selection and hence avoid making such choices.

5 Discussion

Both approaches have different advantages and drawbacks. On the one hand, supervised learning allows to avoid the sample complexity inherent to the reinforcement learning approach, as the targets are stationary. However, it may suffer from problem's symmetries and approximation errors. On the other hand, reinforcement learning quantifies the risk and handles symmetries, but at the price of a higher sample complexity.

Experiments are made on simple real-world problems provided by Electricité de France.

Références

- [1] Y. Bengio, A. Lodi, and A. Prouvost, "Machine learning for combinatorial optimization : a methodological tour d'horizon," *arXiv preprint arXiv :1811.06128*, 2018.
- [2] H. He, H. Daume III, and J. M. Eisner, "Learning to search in branch and bound algorithms," in *Advances in Neural Information Processing Systems 27* (Z. Ghahramani, M. Welling, C. Cortes, N. D. Lawrence, and K. Q. Weinberger, eds.), pp. 3293–3301, Curran Associates, Inc., 2014.
- [3] G. Zarpellon, J. Jo, A. Lodi, and Y. Bengio, "Parameterizing branch-and-bound search trees to learn branching policies," *arXiv preprint arXiv :2002.05120*, 2020.
- [4] E. B. Khalil, P. Le Bodic, L. Song, G. Nemhauser, and B. Dilkina, "Learning to branch in mixed integer programming," in *Thirtieth AAAI Conference on Artificial Intelligence*, 2016.
- [5] M.-F. Balcan, T. Dick, T. Sandholm, and E. Vitercik, "Learning to branch," *arXiv preprint arXiv :1803.10150*, 2018.
- [6] M. Gasse, D. Chételat, N. Ferroni, L. Charlin, and A. Lodi, "Exact combinatorial optimization with graph convolutional neural networks," *arXiv preprint arXiv :1906.01629*, 2019.
- [7] Y. Tang, S. Agrawal, and Y. Faenza, "Reinforcement learning for integer programming : Learning to cut," in *Proceedings of the 37th International Conference on Machine Learning*

(H. D. III and A. Singh, eds.), vol. 119 of *Proceedings of Machine Learning Research*, pp. 9367–9376, PMLR, 13–18 Jul 2020.

- [8] M. Etheve, Z. Alès, C. Bissuel, O. Juan, and S. Kedad-Sidhoum, “Reinforcement learning for variable selection in a branch and bound algorithm,” in *International Conference on Integration of Constraint Programming, Artificial Intelligence, and Operations Research*, pp. 176–185, Springer, 2020.
- [9] K. Yilmaz and N. Yorke-Smith, “Learning efficient search approximation in mixed integer branch and bound,” *arXiv preprint arXiv :2007.03948*, 2020.