

# Treating volumetric inequality constraint in a continuum media with a coupled X-FEM/Level-Set strategy

Nicolas Chevaugeon, Nicolas Moes, Nicolas Bonfils

### ▶ To cite this version:

Nicolas Chevaugeon, Nicolas Moes, Nicolas Bonfils. Treating volumetric inequality constraint in a continuum media with a coupled X-FEM/Level-Set strategy. Fifth International Conference on Advanced COmputational Methods in ENgineering (ACOMEN 2011), Nov 2011, Liège, Belgium. hal-03950857

## HAL Id: hal-03950857 https://hal.science/hal-03950857

Submitted on 22 Jan 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Treating volumetric inequality constraint in a continuum media with a coupled X-FEM/Level-Set strategy

N. Chevaugeon<sup>1</sup>, N. Moës<sup>1</sup> and N. Bonfils<sup>1</sup>

<sup>1</sup> Gem UMR6183, LUNAM Université, Ecole Centrale de Nantes e-mails: {*nicolas.chevaugeon, nicolas.moes, nicolas.bonfils*}@*ec-nantes.fr* 

Some mechanical problems involve inequality kinematic constraint. This study deals with an original approach to handle those difficult problems. The main issue is the treatment of the variational inequalities due to the fact that the constrained area is a priori unknown. After a brief statement of the constraint minimization problem studied here, we will describe an augmented lagrangian method classically used for contact problems, that we applied to our problem, using an Active Set algorithm [1]. However, we will show that in our particular case, this method offers a poor rate of convergence and the stability rely on hard to set parameters. Next, we will present our new approach. The strategy consists in turning the minimization problem under inequality constraint into a shape equilibrium one. The strategy proposed here is to replace the inequality constraint by an equality constraint over an unknown domain. Hence, we assimilate the media to a two elastic phases media. On one phase, no constraints are imposed and on the second one an equality constraint is imposed. Each phase has a mechanical behaviour that depends on the state of the constraint (active or inactive). With the help of the configurational mechanic and the notion of configurational force, the shape of the boundary between each phase is found iteratively. Numerically, the constraint zone is represented by a level-set [2] and the X-FEM [3] is used to properly enrich the displacement field on the interface. Several numerical tests will be shown to compare the two methods (figure 1). Finally some first results toward the extension of the method to contact problems will be described.



Figure 1: Application of the method on a simple case. From left to right, mechanical setting, mesh and constrained zone for both methods, evolution of the constrained zone during the iteration for two differents starting configuration using the new method.

#### References

- [1] H. Ben Dhia, I. Vautier, and Zarroug M. Problèmes de contact frottant en grandes transformations: du continu au discret. *Revue Européenne des Eléments Finis*, 9,1-3:243–261, 2000.
- [2] J. Sethian. Level Set Methods and Fast Marching Methods : Evolving Interfaces in Computational Geometry, Fluid Mechanics, Computer Vision, and Materials science. Cambridge University Press, 1999.
- [3] N. Moës, J. Dolbow, and T. Belytschko. A finite element method for crack growth without remeshing. *International Journal for Numerical Methods in Engineering*, 46:131–150, 1999.