



## A New Real-Time EEG Source Localization Method

Valentin Debenay, Grégory Turbelin, Jean-Pierre Issartel, Amine Chellali,  
Béatrice Alescio-Lautier, Marie-Hélène Ferrer

### ► To cite this version:

Valentin Debenay, Grégory Turbelin, Jean-Pierre Issartel, Amine Chellali, Béatrice Alescio-Lautier, et al.. A New Real-Time EEG Source Localization Method. Federation of European Neuroscience Societies (FENS 2022) forum, Jul 2022, Paris, France. 2022. hal-03955214

HAL Id: hal-03955214

<https://hal.science/hal-03955214>

Submitted on 25 Jan 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# A New Real-Time EEG Source Localization Method

Valentin Debenay<sup>1,2</sup>, Grégory Turbelin<sup>1</sup>, Jean-Pierre Issartel<sup>1</sup>, Amine Chellali<sup>2</sup>, Béatrice Alescio-Lautier<sup>3</sup>, Marie-Hélène Ferrer<sup>4</sup>

<sup>1</sup>Laboratoire de Mécanique et d'Énergétique d'Évry (LMEE, EA 3332), Évry, France. <sup>2</sup>Laboratoire d'Informatique, Bio-Informatique et Systèmes Complexes (IBISC, EA 4526), Évry, France. <sup>3</sup>Laboratoire de Neurosciences Cognitives (LNC, UMR 7291), Marseille, France.

<sup>4</sup>Institut de Recherche Biomédicale des Armées (IRBA), Brétigny-sur-Orge, France.

## I. CONTEXT

- Electroencephalography (EEG) is a widely used functional neuroimaging technique generally considered as having an excellent temporal resolution, but a poor spatial resolution.
- Scalp EEG can be input to the ill-posed source localization inverse problem for characterizing the electric currents in the brain generating them.




Fig. 1: The Renormalization method possible medical applications

## II. AIMS


- Improve the real-time interpretation of EEG signals for:
  - Neurophysiological & cognitive monitoring.
  - Development of brain-machine interfaces (BMI).
- Assess the complementarity between our source identification method and classical approaches (signal processing, AI, ...).
- Determine whether our approach brings valuable additional information for real-time feedback.

## REFERENCES

- Singh, S. K., Turbelin, G., & Issartel, J. P. (2019). Characterizing Variations in Concentration Data Measured from Unknown Releases. *Earth and Space Science*. Doi.org/10.1029/2019EA000669
- Grégory Turbelin. Contributions à la résolution du problème inverse d'estimation du terme source. Mécanique [physics]. Université d'Évry Val d'Essonne, 2019. (tel-02926234)
- Singh, S. K., Turbelin, G., Issartel, J.-P., Kumar, P., and Feiz, A. A. (2015). Reconstruction of an atmospheric tracer source in fusion field trials: Analysing resolution features, *J. Geophys. Res. Atmos.*, 120. Doi:10.1002/2015JD023099

## III. METHOD

- Our idea was to adapt an approach initially developed to solve a source term estimation problem for atmospheric dispersion of nuclear, radiological, biological or chemical (NRBC) substances, called "Renormalization".
- Using anatomically faithful high-resolution 3D head models, our approach can provide valuable insights for neurophysiological & cognitive monitoring:
- The "Renormalization" method uses the lead field theory to define the concept of "EEG visibility tensor".
- Workflow:
  - We compute the lead field matrix  $\mathbf{A}$  from a sensor point of view.
  - We generate the so-called "Visibility matrix"  $\mathbf{W}$ , corresponding to a tensor field, by a "3D renormalization" process.
  - To estimate the source  $\mathbf{s}$  at each time step, we simply apply the inverse operator  $\mathbf{G}$  to the measurement vector  $\boldsymbol{\mu}$ .



## IV. RESULTS




Fig. 2: Image 1 on the left: Visibility field (black = poorly seen areas, white = well seen areas). Image 2: EEG signal samples. Image 3: Source reconstruction (black = inactive areas, yellow = most active areas)

- The source estimation  $\hat{\mathbf{s}}$  enables:
  - Accurate real-time mapping of electrical brain activity.
  - Characterization (location, orientation, intensity) of single punctual or distributed sources.

## V. CONCLUSION

- We expect the "Renormalization" method not only to open new perspectives in the field of BMIs but also to contribute to a better understanding of the brain functions and improve the care of brain-injured patients:
  - Refined rehabilitation assessments by detecting brain activity changes correlated with cognitive disorders.
  - Better evaluation of post-TBI rehabilitation benefits.