

Two Polarization Comb Dynamics in VCSELs Subject to Optical Injection

Yaya Doumbia, Delphine Wolfersberger, Krassimir Panajotov, Marc

Sciamanna

► To cite this version:

Yaya Doumbia, Delphine Wolfersberger, Krassimir Panajotov, Marc Sciamanna. Two Polarization Comb Dynamics in VCSELs Subject to Optical Injection. Photonics, 2022, 9 (2), pp.115. 10.3390/photonics9020115 . hal-03982305

HAL Id: hal-03982305 https://hal.science/hal-03982305v1

Submitted on 10 Feb 2023 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

Two polarization comb dynamics in VCSELs subject to optical injection

Yaya DOUMBIA, Delphine WOLFERSBERGER, Krassimir PANAJOTOV and Marc SCIA-MANNA

February 10, 2023

The optical frequency comb technologies have received intense attention due to their numerous promising applications ranging from optical communications to optical comb spectroscopy. In this work, we experimentally demonstrate a new approach of broadband comb generation based on the polarization mode competition in single-mode VCSELs. More specifically, we analyze the nonlinear dynamics and polarization properties in VCSELs when subject of optical injection from a frequency comb. When varying injection parameters (injection strength and detuning frequency) and comb properties (comb spacing), we unveil several bifurcation sequences enabling the excitation of free-running depressed polarization mode. Interestingly, for some injection parameters, the polarization mode competition induces a single or a two polarization comb with controllable properties (repetition rate and power per line). We also show that the performance of the two polarization combs depends crucially on the injection current and on the injected comb spacing. We explain our experimental findings by utilizing the spin-flip VCSEL model (SFM) supplemented with terms for parallel optical injection of frequency comb. We provide a comparison between parallel and orthogonal optical injection in the VCSEL when varying the injection parameters, as for example dichroism linear dichroism ($\gamma_a = -0.1 \ ns^{-1}$ to $\gamma_a = -0.8 \ ns^{-1}$), injection current ($\mu = 2.29$ to $\mu = 5.29$), and spin-flip relaxation rate ($\gamma_s = 50 \ ns^{-1}$ to $\gamma_s = 2300 \ ns^{-1}$).

Keywords: Optical frequency comb; Polarization switching; Optical injection; Nonlinear dynamics; VCSEL.

The nonlinear dynamics of externally driven semiconductor laser have been extensively studied last decades [1-3]. The polarization dynamics in Vertical-Cavity Surface-Emitting Lasers (VCSELs) have particularly attracted much attention due to their compactness, low cost, low energy consumption and possibility of mass production. These properties have enabled several applications such as optical communications, sensing and computing [4]. The polarization properties of the VCSEL are directly linked to their cavity and active region geometrical properties. The cylindrical geometry of the VCSEL cavity combined with the symmetry of the gain in the plane of the quantum wells yields a weak polarization anisotropy giving rise to light emission of two linear orthogonally polarized fundamental modes. In addition, polarization mode instability including polarization switching (PS), polarization bistability and polarization mode hopping can be observed in the VCSELs between the two polarization modes [5–7]. Polarization switching has been firstly observed in the free-running operation when varying the injection current [8]. More recently, the optical injection have been demonstrated as a powerful tool to induce the PS in VCSELs [6,9,10]. Depending on the injected power and detuning frequency, the PS has been found to bifurcate to more complex dynamics including periodic dynamics, complex dynamics and chaos [6]. Interestingly, very recent study has shown that VCSEL output can exhibit complex chaotic dynamics even

CHAIRE PHOTONIOU

in free-running [11]. These rich nonlinear polarization dynamics in VCSELs have found several applications such as optical frequency comb generation [12].

Optical frequency combs have been in recent years the focus of intense scientific research from the fundamental viewpoint, as well as from the technological perspectives [13–15]. These works have unveiled several physical systems generating optical frequency combs such as modelocked lasers [14,16], electro-optic modulator, and optically pumped nonlinear microresonators [17]. The development of semiconductor laser based frequency combs has been widely motivated by their numerous properties such as low energy consumption, low size, and possibility of mass production and on-chip integration. The semiconductor lasers employed for optical comb generation by mode locking include multisection lasers, Vertical Extended-Cavity Surface-Emitting Lasers (VECSELs) [16, 18], quantum cascade lasers [19, 20] and quantum dot lasers [21, 22]. Unfortunately, the repetition rate of the combs based on these systems depend intrinsically of their cavity properties including cavity length and temperature inside the cavity. Frequency combs with large comb spacing have been proposed using the above systems but achieving a low and stable comb spacing remains a challenge because of the change in the cavity due to the temperature variation. For example, 6-mm-long devices, corresponds to a comb spacing of \approx 7.5 GHz [23] and requires an active stabilization

by acting on the cavity temperature for practical implementations such as dual comb spectroscopy. The comb generation system based on the electro-optic modulators has been adopted to overcome the limitations of the modelocked lasers-based frequency combs. The optical comb generation using electro-optic modulators is relatively simple because the comb is obtained by directly modulating the output of a single-frequency CW laser. The physical phenomena underlying these comb generation systems is linked to the electro-optic effect. The electro-optic modulator based-optical comb have shown several limitations including fluctuation in the amplitude of the comb lines and low bandwidth. Insertion of the electro-optic modulator inside an optical resonator and cascade electro-optic modulator have been adopted as alternative to improve the comb bandwidth and flatness. Recent works have controlled the comb properties by injecting a narrow comb into semiconductor lasers [24-27]. Optical injection of comb is used: first as a way to select and amplify a desired line in an optical frequency comb, but more recently as a technique to induce a rich nonlinear laser dynamics such as, relaxation oscillation frequency locking [24], harmonics frequency locking [24] and Devil's staircase resonance [25]. Yet to date, the full potential of this technique for broadband optical comb generation has only recently been addressed, with an in-depth analysis and mapping of nonlinear comb dynamics [26, 27]. In addition, in a very recent work, we have experimentally taken advantage of the polarization dynamics in a VCSEL to extend the comb bandwidth and improve the power per comb lines referred to as Carrier to noise ratio (CNR) [28]. It is shown that polarization switching induced by orthogonal optical injection plays a key role in the control of the comb properties (bandwidth and CNR) through generation of two combs with orthogonal polarization. This work was restricted to a single-mode VCSEL with birefringence of \sim 18 GHz and does not consider the full potential of the VCSEL parameters. The literature provides a lot of research on the optical injection dynamics in VCSEL with orthogonal polarized light [7, 10, 29-35]. The parallel (orthogonal) injection is injection of light with linear polarisation parallel (orthogonal) to the free-running VCSEL linear polarisation direction. Although parallel optical injection in VCSELs shows similarities to the optical injection in the conventional single-polarization edge-emitting laser, very interesting additional polarization dynamics have been reported recently [36-40]. Excitation of the polarization modes have been found to bifurcate to periodic, complex or chaotic dynamics with orthogonal polarization. The question of how parallel optical frequency comb injection in VCSELs induces additional nonlinear polarization dynamics is of great interest and has not been addressed so far.

In this paper, we analyze in details the nonlinear dynamics and polarization properties in VCSELs subject to optical frequency comb injection. More specifically, we provide an in-depth experimental and theoretical description of the bifurcation scenarios when the polarization of injection comb is parallel to that of the VCSELs. We show that a variation of the injection parameters together with the bias current allows enabling the excitation of the normally depressed polarization mode accompanied by the generation of two combs with orthogonal polarization directions. The appearance of the two polarization combs is directly linked to the evolution of the injection current. Indeed, for a fixed injection current, the comb generation performance is limited by the increase of the injected comb spacing, but the increase in the bias current allows overcoming this limitation. Experimental and numerical simulations highlight that the injection current is an addition parameter to control the comb properties. Beyond, the injection parameters used to tailor the comb properties in a VCSEL in our previous work [28], here, we take advantage of linear dichroism and birefringence to improve the comb properties in the VCSEL. We also contrast experimentally and theoretically the comb dynamics in the cases of parallel and orthogonal optical injection when varying the injection parameters, i.e. the comb spacing and injection strength and most importantly the injection current in the VCSEL. More specifically, we provide an in-depth bifurcation analysis of polarization comb dynamics when varying the VCSEL parameters. The bifurcation diagrams show that VCSEL parameters can be used to suppress the comb in the normally depressed polarization mode or to tailor the power in each polarization comb.

1 Experimental polarization dynamics

1.1 Experimental setup

Figure 1 (a) shows the experimental setup for parallel optical injection in a single-mode VCSEL. The tunable laser (TL) output is first amplified by an Erbium-Doped Fiber Amplifier (EDFA). The output of the EDFA is then sent to the RF port of the Mach-Zehnder Modulator (MZM), which is driven with an electrical signal modulation generated by an Arbitrary Waveform Generator (AWG) (Tektronix AWG 700002A). Three optical frequency lines are created at the output of the MZM. The polarization controller at the input of the MZM is used to align its polarization with the tunable laser. A fiber circulator is arranged to provide isolation for the comb injection in the VCSEL. The total power of the injected comb is controlled using a Variable Optical Attenuator (VOA). The VCSEL output is amplified before being sent to a 50/50 coupler to analyze the optical spectra and the corresponding time series separately. The optical spectra are analyzed with a high-resolution optical spectrum analyzer, BOSA 400, which allows monitoring optical spectra with a resolution of about a minimum of 0.1 pm (12 MHz) at the operating wavelength of 1550 nm. Figure 1 (b), (c), and (d) present the optical spectra of the injected comb for a fixed comb spacing of $\Omega = 1$ GHz, $\Omega = 2$ GHz, and $\Omega = 4$ GHz, respectively. The ratio



Figure 1: (a) Setup for frequency comb injection into a single-mode VCSEL. TL: Tunable Laser, EDFA: amplifier, P.C: Polarization Controller, AWG: Arbitrary Waveform Generator, MZM: Mach-Zehnder Modulator, VOA: Variable Optical Attenuator, OSA: Optical Spectrum Analyser, PD: photodiode, ESA: Electrical spectrum analyzer. (b), (c) and (d) correspond to the optical spectra of the injected comb for comb spacing of $\Omega = 1$ GHz, $\Omega = 2$ GHz and $\Omega = 4$ GHz, respectively. (d) shows the optical spectrum of the VCSEL in free running.

between the power of the central comb line and the side comb lines is around 12 dB. The VCSEL (Raycan) used is a single-mode device with a threshold current equal to I=3 mA. In free-running conditions, the dominant polarization mode (normally depressed polarization mode) emits along the X (Y) axis as shown in Fig. 1 (e). The ratio between the power of the linear polarization modes (X-PM and Y-PM) is around 43 dB. Figure 1 (e) is obtained for a bias current at I=6 mA, which corresponds to 2 times the threshold current. At that current, the total output power of the VCSEL has been measured to be $P_{inj} = 330 \,\mu\text{W}$. The dominant polarization mode (X-PM) emits at 1553.8 nm at I=6 mA. The difference in frequency between the linear polarization modes (VCSEL birefringence) is around 17.71 GHz at 23° C. The x-axes of the optical spectra will show the relative frequency with respect to the X-Polarization mode (X-PM), i.e. the zero value will correspond to the frequency position of the dominant X-Polarization mode (X-PM). In the following, the frequency detuning $\Delta \nu$ will be defined from the frequency of the central injected comb line to the frequency of dominant polarization mode of the VCSEL (X-PM) i.e., $\Delta \nu = \nu_0 - \nu_x$, where ν_0 and ν_x are the frequencies of the central injected comb line and the X-polarization mode of VCSEL (X-PM), respectively

1.2 Impact of the injected comb spacing

We first analyze the nonlinear polarization dynamics of a VCSEL under a narrow optical comb injection. To this end, we fix the bias current at I=6 mA and then scan the plane of injection parameters, namely the detuning frequency and injected power that leads to various polarization mode

competition. That bias current corresponds to a relaxation oscillation frequency of $\omega_{RO} = 4.2$ GHz. Figure 2 describes the sequence of bifurcations leading to the excitation of the normally depressed polarization mode (Y-PM) accompanied by unlocked time-periodic dynamics, which extends the injected comb to a much broader optical spectrum. Figure 2 is obtained for a small injected comb spacing, $\Omega = 1$ GHz and fixed detuning frequency $\Delta \nu = 1.6$ GHz when varying the injected power, P_{inj} . The VCSEL output shows stable free-running operation at a very low injected power [see Fig. 2 (a)]. A small increase in the injected power destabilizes the VCSEL output to modulated signal as a result of nonlinear wave-mixing in the dominant polarization mode (X-PM) [Fig. 2 (b)]. In agreement with our previous publications [26, 27], this nonlinear wave mixing takes place at the detuning frequency and a new frequency that depends on the injected comb spacing. The number of frequency lines involved in the nonlinear wave-mixing decreases with the injected power as shown in Fig. 2 (c). The VCSEL output is then an unstable comb with a high noise pedestal in X-PM at the injected comb repetition rate. By fine-tuning the injected power, instead of stabilizing the comb in a single polarization mode, a new bifurcation scenario leads to the excitation of the free-running normally depressed polarization mode of the VCSEL. Interestingly, this polarization mode competition induces in the VCSEL two optical frequency combs with orthogonal polarization directions as seen in Fig. 2 (d). The two polarization combs have comparable power and the same repetition rate as the injected one with 9 frequency lines in the X-PM comb and 8 in the Y-PM comb at -30 dB from the maximum. The strongest

comb line in the optical spectrum of Y-PM appears at the frequency position of the free-running Y-PM, i.e., its frequency position is ruled by the VCSEL linear birefringence. When we keep increasing the injected power, harmonic frequency comb dynamics takes place simultaneously in the two polarization combs as shown in Fig. 2 (e) and (f). The harmonic comb dynamics result in the reduction of the comb repetition rate. Sub-harmonic bifurcations are well studied, and understood phenomena that occur naturally in periodically forced oscillators [41]. Sub-harmonics dynamics have been expected to be a kind of frequency locking different from the Adler type in diode laser optically injected with optical comb [24,25]. They appear when the detuning frequency is close to the rational fraction of the injected comb spacing. When we increase the injected power, the harmonic polarization comb destabilizes to complex polarization dynamics in X-PM and Y-PM, Fig. 2 (g). It is worth noticing that the X-PM still shows some remarkable comb lines at the repetition rate of the injected comb. A further increase in the injected power leads to a progressive suppression of all the power in the depressed polarization mode Y-PM accompanied by the stabilization of the comb dynamics in the dominant polarization mode X-PM as seen in Fig. 2 (h) and (i). Such single-polarization comb has the same repetition rate as the injected one.

Figure 3 shows the polarization resolved optical spectra for the comb dynamics in Fig. 2 (d)-(f). Figure 3 confirms that the total VCSEL output comb shown in Fig. 2 (d)-(f) are formed by two combs with orthogonal polarization. In the optical spectrum of X-PM (Y-PM) we observed some comb lines at the frequency position of Y-PM (X-PM). This is due to the extension ratio of the polarization controllers.

We have shown in Fig. 2 the possibility of two orthogonal combs generation from polarization mode competition in a single-mode VCSEL. As discussed early in the introduction, the tunability of the optical frequency comb is a key property for many applications. To demonstrate the tuning capability, we show in Fig. 4 bifurcation scenarios giving rise to the two polarization comb dynamics for the same detuning $\Delta \nu = 1.6$ GHz when increasing the injected comb spacing to $\Omega = 2$ GHz. Like for $\Omega = 1$ GHz comb injection, the VCSEL output at low injected power shows the freerunning operation, which bifurcates to a nonlinear wavemixing due to a modulation involving the detuning and the injected comb spacing. In agreement again with Fig. 2, the wave-mixing leads to a two polarization combs generation. Most importantly, despite the comparable power of the two polarization combs, the numbers of lines in X-PM and Y-PM have significantly decreased compared to $\Omega = 1$ GHz comb injection case. Indeed, the number of frequency lines in each polarization mode has decreased to achieve 3 at -30 dB from the maximum. It is important to notice that the two polarization comb dynamics are observed in a very small area of injection parameters for $\Omega = 2$ GHz comb injection. We have checked through polarization resolved optical spectra that these total combs are formed by two micro-comb with orthogonal polarization in single-mode

VCSEL as shown in Fig. 5. A small increase in the injected power destabilizes the VCSEL to more complex dynamics in each polarization mode, as shown in Fig. 4 (d). We have checked that the size of the two polarization comb region shrinks when increasing the injected comb spacing until it disappears at $\Omega = 4$ GHz. Figure 6 shows how to overcome this limitation. Similar to $\Omega = 1$ GHz comb injection, the complex polarization dynamics bifurcates to the singlepolarization comb in X-PM. This polarized comb has an important noise pedestal, therefore, deteriorating the comb performances. Interestingly, we have also checked that the two polarization comb dynamics in the single-mode VC-SEL under parallel optical injection are not observed when the bias current is below I = 6mA. In contrast, when the polarization of the injected comb is orthogonal to that of the VCSEL, the two polarization comb dynamics is always observed, whatever is the bias current.

1.3 Influence of the injection current

We next increase the injected comb spacing to $\Omega = 4$ GHz and the bias current to I = 8 mA, which is 2.67 times the threshold current. Such bias currents have been used in VCSELs to observe various nonlinear dynamics in the presence of single-mode injection with parallel polarization [37, 39]. Compared to the I = 6 mA bias current injection where the nonlinear wave-mixing is accompanied by two polarization comb as a result of excitation of the normally depressed polarization mode, the VCSEL output bifurcates to selective amplification of the central injected lines in X-PM as shown in Fig. 6 (a)-(c). As seen in Fig. 6 (c) and (d), the selective amplification smoothly gives rise to a broad optical comb characterized by the appearance of new frequency lines. When we increase the injected power, the polarization mode competition leads to the extension of the polarized comb to a much broader optical spectrum as shown in Fig. 6 (e). We checked through polarization resolved-optical spectra in Fig. 7 that this overall comb corresponds to two combs based on the linear orthogonal polarization of the VCSEL. It is also possible to control the power in each polarization mode by fine-tuning the detuning. The two polarization combs and the polarized comb have the same repetition rate as the injected comb. By fine-tuning the injected power, the noise pedestal smoothly increases accompanied by harmonics comb line generation simultaneously in the two polarization combs as shown in Fig. 6 (e). The harmonics comb significantly increases the number of resulting output lines and gives rise to a new comb with a low repetition rate ($\Omega = 2$ GHz in Fig. 6 (e)). Most importantly, Fig. 6 (e) highlight a new possibility of broadband $\Omega = 2$ GHz comb generation using the same injection technique as in Fig. 4 (c) and (d). When we keep increasing the injected power, the harmonics comb destabilizes to complex dynamics with remarkable frequency comb lines mainly around the dominant polarization mode (X-PM) as seen in Fig. 6 (g). Interestingly, when further increasing the injected power, the VCSEL bifurcates again to



Figure 2: Bifurcation scenarios leading to the excitation of the depressed polarization mode. These optical spectra are obtained for detuning $\Delta \nu = 1.6$ GHz and injected comb spacing $\Omega = 1$ GHz when increasing the injected power, P_{inj} . (a) stable output at $P_{inj} = 3$ μ W, (b) and (c) wave mixing at $P_{inj} = 16 \mu$ W and $P_{inj} = 32 \mu$ W, respectively, (d) two polarization comb at $P_{inj} = 48 \mu$ W, (e) and (f) two polarization harmonics comb, at $P_{inj} = 80 \mu$ W and $P_{inj} = 96 \mu$ W, respectively, (g) two polarization complex dynamics at $P_{inj} = 128 \mu$ W, and (h) and (i) X-polarization comb at $P_{inj} = 144 \mu$ W, and $P_{inj} = 240 \mu$ W, respectively.

the new broadband comb encompassing the two polarization modes with a significant increase in the noise pedestal as shown in Fig. 6 (h) and (i). Like Fig. 6 (e), this overall comb is formed by two combs with the orthogonal polarization direction. The noise pedestal increases again with the injected power to deteriorate the comb performance, such as the CNR and the comb bandwidth. We have shown that the properties (bandwidth and CNR) of the two polarization combs induced by parallel optical injection are limited by increasing the injected comb spacing for fixed bias current. However, the increase of the bias current is therefore an alternative to improve the polarization combs properties.

1.4 Tailoring comb properties

Figure 8 provides further insight in the comb dynamics when varying the injection parameters, the injection cur-

rent in the VCSEL, and the polarization of the injected light. Figure 8 (a) and (b) analyze the comb properties for an injected comb spacing of $\Omega = 2$ GHz and fixed detuning, $\Delta \nu = 1.6$ GHz. For the measurement of comb bandwidth, we consider an output comb line when its amplitude lies above -30 dB from the maximum amplitude in the optical spectrum. When the spectrum total optical comb shows a big dip, the total comb bandwidth is estimated from the separate bandwidth of X-PM and Y-PM spectra. The polarization of the injected comb is parallel to that of the free-running VCSEL. When increasing the injected power, the comb bandwidth for I = 6 mA, and I = 8 mA current reaches a maximum of around $P_{inj} = 100 \ \mu W$ and $P_{inj} = 200 \ \mu\text{W}$, respectively as shown Fig. 8 (a). The decrease in the comb bandwidth is due to the bifurcation of the two polarization comb to a single polarization comb generation in X-PM as shown in Fig. 2 (i) and Fig. 4 (f). Figure 8 (b) shows that the best CNR is found for low injected



Figure 3: Polarization resolved-optical spectra corresponding to an example of two polarization comb dynamics similar to Fig. 2 (d)-(f) for detuning $\Delta \nu = 1.6$ GHz and injected power $P_{inj} = 20 \ \mu$ W. (a), (b) and (c) correspond to the optical spectra of Y-PM, X-PM and the superposition of Y-PM and X-PM, respectively.

power P_{inj} . The CNR decreases with the injected power due to the increase in the noise pedestal, which destabilizes the comb properties. Figure 8 (a) and (b) also show that the comb bandwidth and the CNR increase with the injection current for the same injected comb properties. We next highlight the impact of the polarization of the injected comb lines on the VCSEL output comb dynamics in Fig. 8 (c) and (d). In Fig. 8 (c) and (d), the blue and red correspond to the parallel and orthogonal optical injection cases, respectively. As discussed in [28], the two polarization comb dynamics are mainly observed when the VCSEL is injected between the two linear polarizations. But, for parallel optical injection, the two polarizations comb are observed only when the central injected comb lines are close to the dominant polarization mode of the VCSEL (detuning close to zero) at low injection current as shown in Fig. 8 (a) and (b). When the injection current is increased, the two comb dynamics are observed in a large portion of the plane of the injection parameters. Figure 8 (c) shows that the comb bandwidth increases with the injected power in the parallel and orthogonal optical injection case, which is in agreement with our previous publication [26–28]. Interestingly, the comb bandwidth for parallel optical injection is better than orthogonal optical injection at high injection current, as shown in Fig. 8 (c). When comparing Fig. 8 (a) to [28], we can observe that the comb bandwidth at low injection current is better for orthogonal than parallel optical injection. We also check that the optical comb performances do not change with the increase in the injection current. In the case of parallel optical injection, the improvement in the comb performance with the increase in the injection current is due to the polarization mode instability, i.e., the excitation of the depressed polarization mode in the VCSEL at a large injection current. The excitation of the free-running depressed polarization mode in the VCSEL has been recently analyzed in several studied [37, 39, 40]. In these works, the VCSEL was injected with a single frequency line master laser, and the injection current was higher than two times the threshold current of the VCSEL. The influence of the polarization of the injected comb is more impactful when we consider the CNR. Figure 8 (d)

shows the CNR of the comb dynamics induced by parallel (blue) and orthogonal (red) optical injection. We observe that for parallel optical injection, whatever is the injected comb spacing and the injection current, the best CNR is found at low injected power and then decreases due to the increase in the noise pedestal as shown in Fig. 6 (d)-(f). As shown in Fig. 8 (b) and (d), the best value of CNR are found at low injected for orthogonal and parallel optical injection, which is in agreement with [28].

2 Theoretical bifurcation analysis

In addition to the experimental results, theoretical studies have been performed to provide further insight into the polarization dynamics of comb injected VCSELs. We have used the Spin-Flip Model (SFM) [42], which is widely used to describe the polarization dynamics in free-running VC-SELs and supplemented it with additional term describing optical comb injection. The SFM parameters are chosen such that the dominant polarization mode (normally depressed polarization mode) of the VCSEL in free-running emits along the X-axis ((Y-axis). The model equations are given in equ. (1)-(4). In these equations, E_x and E_y are the two linearly polarized slowly varying components of the complex fields in the X and Y directions, respectively. D and n are the sum and the difference between the population inversions for the spin-up and spin-down radiation channels. μ , is the normalized current injection.

$$\frac{dE_x}{dt} = -(\kappa + \gamma_a)E_x - i(\kappa\alpha + \gamma_p)E_x + \kappa(1 + i\alpha)(DE_x + inE_y) + E_M \tag{1}$$
(1)
$$\frac{dE_y}{dt} = -(\kappa - \gamma_a)E_y - i(\kappa\alpha - \gamma_p)E_y + \kappa(1 + i\alpha)(DE_y - inE_x), \tag{2}$$
(2)
$$\frac{dD}{dt} = -\gamma[D(1 + |E_x|^2 + |E_y|^2) - \mu + in(E_yE_x^* - E_xE_y^*)], \tag{3}$$
(3)
$$\frac{dn}{dt} = -\gamma_s n - \gamma[n(|E_x|^2 + |E_y|^2) + iD(E_yE_x^* - E_xE_y^*)]. \tag{4}$$



Figure 4: Bifurcation scenarios leading to the excitation of the depressed polarization mode. These optical spectra are obtained for detuning $\Delta \nu = 1.6$ GHz and injected comb spacing $\Omega = 2$ GHz. (a) stable output at $P_{inj} = 3 \mu W$, (b) wave mixing at $P_{inj} = 16 \mu W$, (c) two polarizations comb at $P_{inj} = 48 \mu W$, (d) two polarization harmonics comb at $P_{inj} = 112 \mu W$, (e) two polarization complex dynamics at $P_{inj} = 208 \mu W$, and (f) X-polarization comb at $P_{inj} = 240 \mu W$.

The meaning of the remaining SFM parameters is the following: γ_p and γ_a , correspond to the linear birefringence and linear dichroism, respectively, γ_s is the spin-flip relaxation rate, γ is the decay rate of D, κ is the field decay rate, and α is the linewidth enhancement factor.

The complex electrical field of the injected comb is written as:

$$E_M = \kappa_{inj} \sum_j E_j(t) e^{i(2\pi\nu_j t + \varphi_j(t))}$$
(5)

with angular frequency ω_j and amplitude E_j corresponding to the j_{th} comb lines, and coupling coefficient κ_{inj} . We consider an optimal coupling between the VCSEL output and the injected comb, which correspond to $\kappa_{inj} = \kappa$. We consider a comb with three frequency lines and we simplify the calculations by supposing $\varphi_j = 0$, i.e., the phase of the individual injected comb lines is zero. The detuning frequency $\Delta \nu_j$ is the difference between ν_j and the intermediate frequency between those of the X and Y polarization, $\frac{2\pi\nu_x+2\pi\nu_y}{2}$, with $2\pi\nu_x = \alpha\gamma_a - \gamma_p$ and $2\pi\nu_y = \gamma_p - \alpha\gamma_a$, the frequency corresponding to the linear polarization mode X and Y, respectively.

The SFM parameters are taken as $\kappa = 33 \ ns^{-1}$, $\gamma_a = -0.1 \ ns^{-1}$, $\alpha = 2.8$, $\mu = 2.29$, $\gamma_p = 9 \ \text{GHz}$, $\gamma = 2.08 \ ns^{-1}$, $\gamma_s = 2100 \ ns^{-1}$. These numerical value are taken from [38]. In the following, we shall use κ_{inj} for injection strength, with $\kappa_{inj} = \frac{E_{inj}}{E_0}$, where E_{inj} and E_0 are the total amplitude of the injected field and the total amplitude of the VCSEL in free-running mode, respectively. The rate

equation (1-4) are numerically integrated using a fourthorder Runge-Kutta method. The numerical simulations are typically performed with a times series of 200 ns and a time step equal to 1.2 ps. The detuning frequency value is defined from the central injected comb line and is referred to as $\Delta \nu$. In this section, we model the experiment by considering that the difference between the amplitude of the central injected comb line and the side comb lines is 12 dB.

2.1 Y-PM comb dynamics

The experimental results have demonstrated the possibility of generating two combs with orthogonal polarization in a VCSEL subject to parallel optical injection. We have also shown that this polarization comb performance is limited by the increase in the injected comb spacing. In Fig. 9 we analyze the two polarization comb numerically through bifurcation diagrams. Figure 9 is obtained for fixed injected comb spacing $\Omega = 2$ GHz and detuning $\Delta \nu_x = -9$ GHz. These bifurcation diagrams are plotted by selecting the minima and the maxima of the polarization-resolved intensities, $I_{x,y} = |E_{x,y}|^2$ for each injection strength. In Fig. 9, the left and right panels correspond to the bifurcation diagrams of X-PM and Y-PM, respectively. Figure 9 (a_1) and (b_1) show the bifurcation diagrams for fixed linear dichroism $\gamma_a = -0.1 \ ns^{-1}$. When increasing the injection strength, the VCSEL output first shows a nonlinear wave-mixing involving the detuning and the injected comb spacing in X-PM. When we keep increasing the in-



Figure 5: Polarization resolved-optical spectra corresponding to an example of two polarization comb dynamics in Fig. 4 (c). (a), (b) and (c) are obtained for detuning $\Delta \nu = 1.6$ GHz and injected power $P_{inj} = 20 \ \mu$ W. (a), (b) and (c) correspond to the optical spectra of Y-PM, X-PM and the superposition of Y-PM and X-PM, respectively.

jection strength, the wave-mixing bifurcates to periodic dynamics corresponding to the optical frequency comb in the two linear orthogonal polarization modes. The two polarization comb region is referred to as "comb" in Fig. 9. The X-PM shows a larger number of lines than the Y-PM, but the number of lines in Y-PM can be controlled with the injection parameters. The two comb dynamics remain stable with a simultaneous increase in the number of lines over a large range of injection strengths. Interestingly, by fine-tuning the injection strength, the VCSEL output shows harmonic comb dynamics simultaneously in the two orthogonal combs at the boundary of the comb regions. A further increase of the injection strength leads to the complex dynamics in X-PM and Y-PM accompanied by abrupt suppression of all the power in Y-PM. Cascade comb dynamics leading to a very low comb repetition rate are observed in between the complex dynamics depending on the injection parameters. The complex polarization dynamics bifurcate to a single polarization comb in the dominant polarization mode (X-PM). We next vary the linear dichroism to highlight its impact on the two polarization comb dynamics. Interestingly, when decreasing the linear dichroism, the size of the two polarization comb region decreases as seen in Fig. 9 (a_2) , (a_3) , (b_2) , and (b_3) . The double horizontal arrows indicate how much the size of the combs regions decreases with the decrease of the linear dichroism. It is worth noticing that all the bifurcation sequences are similar to the case of $\gamma_a = -0.1 \ ns^{-1}$. When the linear dichroism reaches $\gamma_a = -0.8 \ ns^{-1}$, the two polarization comb disappear and the Y-PM is suppressed as shown in Fig. 9 (a_4) , (b_4) . Therefore, except for the disappearance of the comb lines in Y-PM, the bifurcation scenarios remain similar for X-PM. The bifurcation scenarios described in Fig. 9 are in a very good agreement with the experimental ones in Fig. 2 and Fig. 4.

Figure 10 shows an example comb and complex dynamics in the two polarization modes. Fig. 10 (a_1) and (b_1) show the optical spectra of comb dynamics in X-PM and Y-PM, respectively. We observe clearly in these spectra that the bandwidth of the frequency comb in the injected polarization mode (X-PM) is larger than the comb in the depressed polarization mode, Y-PM. As discussed early in the experimental section, these X-PM comb and Y-PM comb can combine to form a broad comb in the total output power of the VCSEL. Figure 10 (a_2) and (b_2) show an example of complex polarization dynamics. Depending on the injection parameters and injected comb properties, these complex polarization dynamics can simultaneously bifurcate to a two polarization harmonic combs or single-polarization comb.

Figure 9 has shown that the decrease in the linear dichroism leads to the complete suppression of the comb lines in the normally depressed polarization mode (Y-PM). In Fig. 11, we provide a further insight on comb generation, whatever is the linear dichroism. To this end, we keep all the parameters used to obtain Fig. 9 (a_4) , (b_4) , and then we vary the bias current. When the normalized bias current reaches 2.9 times the threshold, i.e., $\mu = 4.2$, the comb dynamics start to take place again in the two polarization modes as seen in Fig. 11 (a) and ((b). Most importantly, the bifurcation scenarios giving rise to the two polarization comb dynamics remain similar to the case of $\mu = 2.29$. When we increase the bias current to $\mu = 5.29$ in Fig. 11 (c) and (d), the bifurcation to the two polarization comb dynamics remain similar to the case of $\mu = 4.2$. Interestingly, unlike the case of $\mu = 4.2$, where the two polarization becomes abruptly chaotic, the VCSEL output bifurcates to cascade harmonic comb dynamics in the two polarization modes. The two polarization harmonics comb lead to the suppression of all the power in Y-PM and bifurcates, therefore, to the polarized comb generation in the X-PM. Interestingly, we checked that when the polarization of the injected comb is orthogonal to that of the VCSEL, the size of the two polarization combs area increases slightly when the linear dichroism, γ_a is decreased.

2.2 Influence of spin-flip relaxation rate

Further insight into the two polarization comb dynamics is given in Fig. 12, where the bifurcation diagrams are



Figure 6: Bifurcation scenarios leading to the excitation of the depressed polarization mode. These optical spectra are obtained for detuning $\Delta \nu = -0.9$ GHz and injected comb spacing $\Omega = 4$ GHz. (a) and (b) wave mixing at $P_{inj} = 3 \mu W$, and $P_{inj} = 32 \mu W$, respectively, (c) and (d) single polarization comb at $P_{inj} = 48 \mu W$ and $P_{inj} = 228 \mu W$, respectively, (e), (h) and (i) two polarizations comb at $P_{inj} = 304 \mu W$, $P_{inj} = 560 \mu W$ and $P_{inj} = 704 \mu W$, respectively, (f) two polarization harmonics comb at $P_{inj} = 376 \mu W$, (g) two polarization complex dynamics at $P_{inj} = 448 \mu W$.

shown for fixed $\Delta \nu_x = -9$ GHz when varying the injection strength together with the spin-flip relaxation rate γ_s . The blue and red colors in Fig. 12, correspond to the bifurcation diagrams of X-PM and Y-PM, respectively. When γ_s is small [Fig. 12 (a)], the two polarization modes are excited at very low injection strength. Most importantly, the comb lines start to progressively appear in each polarization mode as the injection strength increases. Interestingly, when we keep increasing the spin-flip relaxation rate γ_s , the VCSEL output first shows the complex dynamics in the dominant polarization mode, which bifurcates to the excitation of the depressed polarization mode accompanied by comb generation, as shown in Fig. 12 (b). The bifurcation sequence remains quite similar when further increasing the spin-flip relaxation rate. Still, the size of the complex dynamics region in X-PM increases leading, therefore, to the decrease in the size of the two combs region as seen in Fig. 12 (b), (c), and (d). The size of the comb regions remains fixed at a high value of γ_s as seen in Fig. 12 (c) and (d). Unlike the case of Fig. 12 (a) and (b), where the two polarization combs take place smoothly, the two comb appearance is abrupt when the spin-flip relaxation rate is

large in Fig. 12 (c) and (d). The two polarization comb dynamics bifurcates to a single polarization comb at large injection strength for each bifurcation diagram. It is worth noticing that cascade harmonics characterizes the bifurcation to the single polarization comb dynamics at low γ_s . In contrast, the two complex polarization dynamics lead to the single polarization comb at significant γ_s . Once the single polarization mode operation is achieved in the VCSEL, the bifurcation scenarios remain similar whatever is the value of the spin-flip relaxation rate. Beside the spin-flip relaxation rate, we have checked that the two polarization comb dynamics are observed in a wide range of SFM parameters including linear dichroism ($\gamma_a = -0.1 \ ns^{-1}$ to $\gamma_a = -0.8 \ ns^{-1}$), injection current ($\mu = 2.29$ to $\mu = 5.29$), linewidth enhancement factor ($\alpha = 1$ to $\alpha = 5$), and linear birefringence ($\gamma_p = 1$ GHz to several hundred of GHz).

3 Conclusion

We have shown experimentally and theoretically that VC-SEL can bifurcate to interesting polarization dynamics un-



Figure 7: Polarization resolved-optical spectra corresponding to an example of two polarization comb dynamics in Fig. 6 (e)-(i). (a), (b) and (c) are obtained for detuning $\Delta \nu = -0.9$ GHz and injected power $P_{inj} = 432.8 \ \mu$ W. (a), (b) and (c) correspond to the optical spectra of Y-PM, X-PM and the superposition of Y-PM and X-PM, respectively.



Figure 8: Control of comb properties using the injection parameters and polarization of the injected light. (a) and (b) are obtained for fixed detuning and comb spacing $\Delta \nu = 1.6$ GHz and $\Omega = 2$ GHz, respectively. (c) and (d) are obtained for fixed comb spacing $(\Omega = 4 \text{ GHz})$ and injection current I = 8 mA. The blue and red curve correspond to the parallel and orthogonal optical injection, respectively. The comb dynamics in parallel and orthogonal optical injection are obtained for fixed detuning $\Delta \nu = -0.9$ GHz and $\Delta \nu = -11.6$ GHz, respectively.

der optical frequency comb injection. Interestingly, we have demonstrated that when the polarization of the injected comb is parallel to that of the VCSEL, polarization mode competition can induce two combs in a single-mode VC-SEL. These combs are based on the two linear orthogonal polarizations in the VCSEL. We have also shown that these polarization combs are limited by the increase in the injected comb spacing, especially the normally depressed polarization mode, Y-PM. Our results have shown that the comb performance can be regained when increasing the bias current in the VCSEL. We have performed numerical simulations to highlight a strong agreement with experimental results through bifurcation diagrams. We have also numerically analyzed the influence of linear dichroism and the spin-flip relaxation rate on the two polarization comb



Figure 9: Bifurcation diagrams for fixed injected comb spacing $\Omega = 2$ GHz and detuning $\Delta \nu_x = -9$ GHz. The left and right panels correspond to X-polarization mode (X-PM) and Y-polarization mode (Y-PM). (a_1 , b_1), (a_2 , b_2), (a_3 , b_3) and (a_4 , b_4), are obtained for $\gamma_a = -0.1 \ ns^{-1}$, $\gamma_a = -0.2 \ ns^{-1}$, $\gamma_a = -0.6 \ ns^{-1}$, and $\gamma_a = -0.8 \ ns^{-1}$



Figure 10: Optical spectra for fixed $\Omega = 2$ GHz, $\Delta \nu_x = -9$ GHz, and $\gamma_a = -0.6 ns^{-1}$. The left (a) and right (b) panels correspond to X-PM and Y-PM, respectively. The top figures (a_1, b_1) are obtained for $\kappa = 0.525$ and the bottom figures (a_2, b_2) are obtained for $\kappa = 0.6$.

dynamics. Interestingly, the two polarization comb area becomes narrower when the linear dichroism decreases until it disappears at $\gamma_a = -0.8 \ ns^{-1}$. By contrast, the size of the region of two polarizations comb dynamics increases with the decrease of the linear dichroism when the VCSEL is under an orthogonal optical injection. The single or two polarization combs induced by parallel optical injection are not as efficient in term of bandwidth and CNR as the case of orthogonal comb injection investigated in [28] in term of the number of lines at low bias current. Furthermore, the two polarization combs are observed only if the bias current is significantly large, at least twice the threshold current for the VCSEL considered here. In the case of orthogonal optical injection, the single and two polarization combs dynamics show the same performance (bandwidth and CNR), whatever is the injection current.

Funding. Chaire Photonique: Ministère de l'Enseignement Supérieur, de la Recherche et de l'Innovation; Région Grand-Est; Département Moselle; European Regional Development Fund (ERDF); Airbus GDI Simulation; CentraleSupélec; Fondation Centrale-Supélec. Fondation Supélec; Metz Metropole, Fonds Wetenschappelijk Onderzoek (FWO) Vlaanderen Project No.G0E5819N.

References

- M. Sciamanna and K. A. Shore, "Physics and applications of laser diode chaos," *Nature photonics*, vol. 9, no. 3, pp. 151–162, 2015.
- [2] S. Wieczorek, B. Krauskopf, T. B. Simpson, and D. Lenstra, "The dynamical complexity of optically



Figure 11: Bifurcation diagrams for fixed injected comb spacing $\Omega = 2$ GHz and $\gamma_a = -0.8 n s^{-1}$. The left and right panels correspond to X-PM and Y-PM, respectively. (a) and (b) are obtained for $\mu = 4.2$ and (c) and (d) for $\mu = 5.29$.

injected semiconductor lasers," *Physics Reports*, vol. 416, no. 1-2, pp. 1–128, 2005.

- [3] F. Mogensen, H. Olesen, and G. Jacobsen, "Locking conditions and stability properties for a semiconductor laser with external light injection," *IEEE Journal* of Quantum Electronics, vol. 21, no. 7, pp. 784–793, 1985.
- [4] A. Larsson, "Advances in vcsels for communication and sensing," *IEEE Journal of Selected Topics in Quantum Electronics*, vol. 17, no. 6, pp. 1552–1567, 2011.
- [5] M. Sciamanna, K. Panajotov, H. Thienpont, I. Veretennicoff, P. Mégret, and M. Blondel, "Optical feedback induces polarization mode hopping in vertical-cavity surface-emitting lasers," *Optics letters*, vol. 28, no. 17, pp. 1543–1545, 2003.
- [6] M. Sciamanna and K. Panajotov, "Route to polarization switching induced by optical injection in verticalcavity surface-emitting lasers," *Physical Review A*, vol. 73, no. 2, p. 023811, 2006.
- [7] J. B. Altés, I. Gatare, K. Panajotov, H. Thienpont, and M. Sciamanna, "Mapping of the dynamics induced by orthogonal optical injection in vertical-cavity surfaceemitting lasers," *IEEE journal of quantum electronics*, vol. 42, no. 2, pp. 198–207, 2006.
- [8] K. D. Choquette, R. P. Schneider, K. L. Lear, and R. E. Leibenguth, "Gain-dependent polarization properties of vertical-cavity lasers," *IEEE Journal of Selected Topics in Quantum Electronics*, vol. 1, no. 2, pp. 661–666, 1995.
- [9] A. Hurtado, A. Quirce, A. Valle, L. Pesquera, and M. J. Adams, "Nonlinear dynamics induced by parallel



Figure 12: Bifurcation diagrams for fixed injected comb spacing $\Omega = 2$ GHz and detuning $\Delta \nu_x = -9$ GHz when varying γ_s . (a), (b), (c) and (d) are obtained for $\gamma_s = 50 \ ns^{-1}$, $\gamma_s = 200 \ ns^{-1}$, $\gamma_s = 1000 \ ns^{-1}$, and $\gamma_s = 2300 \ ns^{-1}$, respectively.

and orthogonal optical injection in 1550 nm verticalcavity surface-emitting lasers (vcsels)," *Optics express*, vol. 18, no. 9, pp. 9423–9428, 2010.

- [10] I. Gatare, J. Buesa, H. Thienpont, K. Panajotov, and M. Sciamanna, "Polarization switching bistability and dynamics in vertical-cavity surface-emitting laser under orthogonal optical injection," *Optical and quantum electronics*, vol. 38, no. 4, pp. 429–443, 2006.
- [11] M. Virte, K. Panajotov, H. Thienpont, and M. Sciamanna, "Deterministic polarization chaos from a laser diode," *Nature Photonics*, vol. 7, no. 1, pp. 60–65, 2013.
- [12] A. Quirce, C. de Dios, A. Valle, and P. Acedo, "Vcselbased optical frequency combs expansion induced by polarized optical injection," *IEEE Journal of Selected Topics in Quantum Electronics*, vol. 25, no. 6, pp. 1–9, 2018.
- [13] K. Minoshima and H. Matsumoto, "High-accuracy measurement of 240-m distance in an optical tunnel by use of a compact femtosecond laser," *Applied Optics*, vol. 39, no. 30, pp. 5512–5517, 2000.
- [14] S. M. Link, D. Maas, D. Waldburger, and U. Keller, "Dual-comb spectroscopy of water vapor with a freerunning semiconductor disk laser," *Science*, vol. 356, no. 6343, pp. 1164–1168, 2017.
- [15] P. Marin-Palomo, J. N. Kemal, M. Karpov, A. Kordts, J. Pfeifle, M. H. Pfeiffer, P. Trocha, S. Wolf, V. Brasch, M. H. Anderson *et al.*, "Microresonator-based solitons for massively parallel coherent optical communications," *Nature*, vol. 546, no. 7657, pp. 274–279, 2017.

- [16] L. Hargrove, R. L. Fork, and M. Pollack, "Locking of he-ne laser modes induced by synchronous intracavity modulation," *Applied Physics Letters*, vol. 5, no. 1, pp. 4–5, 1964.
- [17] P. Del'Haye, A. Schliesser, O. Arcizet, T. Wilken, R. Holzwarth, and T. J. Kippenberg, "Optical frequency comb generation from a monolithic microresonator," *Nature*, vol. 450, no. 7173, pp. 1214–1217, 2007.
- [18] B. W. Tilma, M. Mangold, C. A. Zaugg, S. M. Link, D. Waldburger, A. Klenner, A. S. Mayer, E. Gini, M. Golling, and U. Keller, "Recent advances in ultrafast semiconductor disk lasers," *Light: Science & Applications*, vol. 4, no. 7, pp. e310–e310, 2015.
- [19] A. Hugi, G. Villares, S. Blaser, H. Liu, and J. Faist, "Mid-infrared frequency comb based on a quantum cascade laser," *Nature*, vol. 492, no. 7428, pp. 229– 233, 2012.
- [20] C. Silvestri, L. L. Columbo, M. Brambilla, and M. Gioannini, "Coherent multi-mode dynamics in a quantum cascade laser: amplitude-and frequencymodulated optical frequency combs," *Optics Express*, vol. 28, no. 16, pp. 23 846–23 861, 2020.
- [21] C. Weber, L. L. Columbo, M. Gioannini, S. Breuer, and P. Bardella, "Threshold behavior of optical frequency comb self-generation in an inas/ingaas quantum dot laser," *Optics letters*, vol. 44, no. 14, pp. 3478–3481, 2019.
- [22] F. Grillot, J. Duan, B. Dong, and H. Huang, "Uncovering recent progress in nanostructured light-emitters for information and communication technologies," *Light: Science & Applications*, vol. 10, no. 1, pp. 1–17, 2021.
- [23] G. Villares, A. Hugi, S. Blaser, and J. Faist, "Dual-comb spectroscopy based on quantum-cascade-laser frequency combs," *Nature communications*, vol. 5, no. 1, pp. 1–9, 2014.
- [24] K. Shortiss, B. Lingnau, F. Dubois, B. Kelleher, and F. H. Peters, "Harmonic frequency locking and tuning of comb frequency spacing through optical injection," *Optics Express*, vol. 27, no. 25, pp. 36976–36989, 2019.
- [25] B. Lingnau, K. Shortiss, F. Dubois, F. H. Peters, and B. Kelleher, "Universal generation of devil's staircases near hopf bifurcations via modulated forcing of nonlinear systems," *Physical Review E*, vol. 102, no. 3, p. 030201, 2020.
- [26] Y. Doumbia, T. Malica, D. Wolfersberger, K. Panajotov, and M. Sciamanna, "Nonlinear dynamics of a laser diode with an injection of an optical frequency comb," *Optics Express*, vol. 28, no. 21, pp. 30379–30390, 2020.

- [27] —, "Optical injection dynamics of frequency combs," *Optics Letters*, vol. 45, no. 2, pp. 435–438, 2020.
- [28] Y. Doumbia, D. Wolfersberger, K. Panajotov, and M. Sciamanna, "Tailoring frequency combs through vcsel polarization dynamics," *Optics Express*, vol. 29, no. 21, pp. 33 976–33 991, 2021.
- [29] I. Gatare, M. Sciamanna, M. Nizette, and K. Panajotov, "Bifurcation to polarization switching and locking in vertical-cavity surface-emitting lasers with optical injection," *Physical Review A*, vol. 76, no. 3, p. 031803, 2007.
- [30] I. Gatare, M. Sciamanna, J. Buesa, H. Thienpont, and K. Panajotov, "Nonlinear dynamics accompanying polarization switching in vertical-cavity surfaceemitting lasers with orthogonal optical injection," *Applied Physics Letters*, vol. 88, no. 10, p. 101106, 2006.
- [31] A. Valle, I. Gatare, K. Panajotov, and M. Sciamanna, "Transverse mode switching and locking in verticalcavity surface-emitting lasers subject to orthogonal optical injection," *IEEE Journal of Quantum Electronics*, vol. 43, no. 4, pp. 322–333, 2007.
- [32] K. Panajotov, I. Gatare, A. Valle, H. Thienpont, and M. Sciamanna, "Polarization-and transverse-mode dynamics in optically injected and gain-switched vertical-cavity surface-emitting lasers," *IEEE journal* of quantum electronics, vol. 45, no. 11, pp. 1473–1481, 2009.
- [33] I. Gatare, K. Panajotov, and M. Sciamanna, "Frequency-induced polarization bistability in verticalcavity surface-emitting lasers with orthogonal optical injection," *Physical Review A*, vol. 75, no. 2, p. 023804, 2007.
- [34] M. Nizette, M. Sciamanna, I. Gatare, H. Thienpont, and K. Panajotov, "Dynamics of vertical-cavity surfaceemitting lasers with optical injection: a two-mode model approach," *JOSA B*, vol. 26, no. 8, pp. 1603– 1613, 2009.
- [35] M. Sciamanna and K. Panajotov, "Two-mode injection locking in vertical-cavity surface-emitting lasers," *Optics letters*, vol. 30, no. 21, pp. 2903–2905, 2005.
- [36] Y. Hong, P. S. Spencer, P. Rees, and K. A. Shore, "Optical injection dynamics of two-mode vertical cavity surface-emitting semiconductor lasers," *IEEE Journal of Quantum Electronics*, vol. 38, no. 3, pp. 274–278, 2002.
- [37] F. Denis-le Coarer, A. Quirce, Á. Valle, L. Pesquera, M. Sciamanna, H. Thienpont, and K. Panajotov, "Polarization dynamics induced by parallel optical injection in a single-mode vcsel," *Optics letters*, vol. 42, no. 11, pp. 2130–2133, 2017.

- [38] A. Quirce, P. Pérez, A. Popp, Á. Valle, L. Pesquera, Y. Hong, H. Thienpont, and K. Panajotov, "Polarization switching and injection locking in vertical-cavity surface-emitting lasers subject to parallel optical injection," *Optics letters*, vol. 41, no. 11, pp. 2664–2667, 2016.
- [39] A. Quirce, A. Popp, F. Denis-le Coarer, P. Pérez, Á. Valle, L. Pesquera, Y. Hong, H. Thienpont, K. Panajotov, and M. Sciamanna, "Analysis of the polarization of single-mode vertical-cavity surface-emitting lasers subject to parallel optical injection," *JOSA B*, vol. 34, no. 2, pp. 447–455, 2017.
- [40] F. Denis-le Coarer, A. Quirce, P. Pérez, A. Valle, L. Pesquera, M. Sciamanna, H. Thienpont, and K. Panajotov, "Injection locking and polarization switching bistability in a 1550 nm vcsel subject to parallel optical injection," *IEEE Journal of Selected Topics in Quantum Electronics*, vol. 23, no. 6, pp. 1–10, 2017.
- [41] J. Guckenheimer and P. Holmes, *Nonlinear oscillations, dynamical systems, and bifurcations of vector fields.* Springer Science & Business Media, 2013, vol. 42.
- [42] M. San Miguel, Q. Feng, and J. V. Moloney, "Lightpolarization dynamics in surface-emitting semiconductor lasers," *Physical Review A*, vol. 52, no. 2, p. 1728, 1995.