



HAL
open science

Effect of biaxial stretching of nanolayered poly(ethylene furanoate) (PEF) films on gas barrier properties

Alain Guinault, Sébastien Roland, Cyrille Sollogoub, Tiphaine Messin, Gilbert Anderer, Stefan Krawielitzki

► To cite this version:

Alain Guinault, Sébastien Roland, Cyrille Sollogoub, Tiphaine Messin, Gilbert Anderer, et al.. Effect of biaxial stretching of nanolayered poly(ethylene furanoate) (PEF) films on gas barrier properties. 36th International Conference of the polymer Processing Society 26-29 september 2021, Sep 2021, Montréal, Canada. 10.5281/zenodo.6401679 . hal-03992786

HAL Id: hal-03992786

<https://hal.science/hal-03992786>

Submitted on 16 Feb 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Effect of biaxial stretching of nanolayered poly(ethylene furanoate) (PEF) films on gas barrier properties

Food packaging films must be reinvented in order to meet the new ecological requirements and challenges. In particular, efforts have been directed to reduce the use of petrochemical polymers and to develop biobased and/or biodegradable polymers. Among those, Poly(ethylene furanoate) (PEF) is a new promising biopolymer with high gas barrier and good mechanical properties, but its high price limits currently its industrial applications. Its combination with another polymer is thus of great interest and film coextrusion could be a relevant processing method for PEF. Nanolayer coextrusion can create hundreds to thousands micro or nanolayers and has been shown to improve the gas barrier properties of some polymers due to various confinement effect [1,2].

In this study, a new grade of PEF, developed by AVA Biochem in the scope of the H2020 Mypack program, has been combined with PET using nanolayer coextrusion. Multilayered films with different PEF layer thicknesses (varying from the micrometer down to the nanometer scale) have been successfully processed. AFM observations have shown the continuity of the PEF layers with individual thicknesses as thin as 40 nm.

PEF was amorphous at the end of the coextrusion step and post-thermal annealing was necessary to get a crystallinity degree of 14%. Surprisingly, the gas barrier properties were not improved by the crystallization step.

While PEF alone is too brittle to withstand any deformation, it was possible to biaxially stretch amorphous PEF/PET multilayered films with draw ratio as high as 4,5 x 4,5. After a subsequent crystallization, an improvement of a factor 4, compared to the bulk PEF, has been obtained for the gas barrier properties.

Acknowledgement: the authors want to thank the European Commission for the funding of the H2020 Mypack Project.

[1] Wang, H., Keum, J. K., Hiltner, A., & Baer, E. (2009). Confined crystallization of PEO in nanolayered films impacting structure and oxygen permeability. *Macromolecules*, 42(18), 7055-7066.

[2] Messin, T., Marais, S., Follain, N., Guinault, A., Gaucher, V., Delpouve, N., Sollogoub, C. (2020), Biodegradable PLA/PBS multinanolayer membrane with enhanced barrier performances, *Journal of Membrane Science*, 598, 117777

Authors:

Alain Guinault, PIMM, Paris, France

Sébastien Roland, PIMM, Paris, France

Cyrille Sollogoub, PIMM, Paris, France

Tiphaine Messin, PIMM, Paris, France

Patrice Dole, CTCPA, Bourg en Bresse, France

Gilbert Anderer, AVA Biochem, Zug, Switzerland

Stefan Krawielitzki, AVA Biochem, Zug, Switzerland