

The formation mechanism of multilayer emulsions studied by isothermal titration calorimetry and dynamic light scattering

Wei Liao, Emilie Dumas, Abdelhamid Elaissari, Adem Gharsallaoui

► To cite this version:

Wei Liao, Emilie Dumas, Abdelhamid Elaissari, Adem Gharsallaoui. The formation mechanism of multilayer emulsions studied by isothermal titration calorimetry and dynamic light scattering. Food Hydrocolloids, 2023, 136 (Part A), pp.108275. 10.1016/j.foodhyd.2022.108275 . hal-03996443

HAL Id: hal-03996443 https://hal.science/hal-03996443

Submitted on 8 Nov 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1	A study of the formation mechanism of multilayer emulsions by
2	isothermal titration calorimetry and dynamic light scattering
3	
4	Wei Liao ¹ , Emilie Dumas ¹ , Abdelhamid Elaissari ² , Adem Gharsallaoui ¹ *
5	¹ Univ. Lyon, University Claude Bernard Lyon 1, CNRS, LAGEPP UMR 5007, 43 Bd
6	11 Novembre 1918, 69622 Villeurbanne, France
7	² Univ Lyon, University Claude Bernard Lyon 1, CNRS, ISA-UMR 5280, 69622
8	Villeurbanne, France
9	
10	*Corresponding author: <u>adem.gharsallaoui@univ-lyon1.fr</u>

11 Abstract

The formation of multilayered interfaces around oil droplets in oil-in-water (O/W) 12 systems has great advantages in delivering lipid-soluble active compounds. Until now, 13 few thermodynamic analyses have been performed on the preparation process of 14 multi-layer emulsions. In this study, isothermal titration calorimetry (ITC) and 15 dynamic light scattering (DLS) were used to investigate the binding properties and 16 physical properties of low methoxyl pectin (LMP) and sodium caseinate (CAS) based 17 18 multilayer emulsions during the formation process. ITC titration confirmed LMP does bind CAS-coated droplets through the electrostatic forces and it was a spontaneous 19 exothermic process ($\Delta G < 0$, $\Delta H < 0$). Furthermore, stable multilayer emulsions can 20 be only formulated by titrating the primary emulsion into LMP instead of 21 22 back-titrating. Finally, the effects of different mixing methods on the stability of multilayer emulsions were evaluated. The DLS results suggest that titration rather 23 than mixing directly can lead to more uniform and smaller-sized droplets, which can 24 be attributed to the fact that slow titration can effectively avoid droplet aggregation. 25

26

Keywords: Multilayer emulsions; Isothermal titration calorimetry; Dynamic light
scattering; Electrostatic interactions; Bridging flocculation

29 1. Introduction

Oil in water (O/W) emulsion systems, produced by homogenizing oil and 30 aqueous phases together in the presence of one or more emulsifiers, have been 31 extensively applied in foods such as soft drinks, milk, mayonnaise, and vinaigrette, 32 etc. (Guzey & McClements, 2006). Along with the food safety concerns, there is a 33 growing interest trend in the food field to replace commercial synthetic emulsifiers 34 with natural "label-friendly" ones (Dammak et al., 2020). In this regard, several food 35 36 protein-based emulsifiers, from different sources like milk, whey, eggs, legume, oilseed, and so on, have been extensively investigated as natural emulsifiers in recent 37 years due to their amphiphilic character, polymeric structure, and electrical charge 38 characteristics (Kim et al., 2020). Despite their favorable properties, protein-stabilized 39 emulsions have been reported to be highly sensitive to environmental stresses such as 40 pH, ionic strength, temperature, and oxygen (Bouyer et al., 2012). This instability of 41 protein-based emulsions under these conditions will limit their further application in 42 certain commercial products. In fact, the quality and stability of emulsions can be 43 44 improved by combining protein emulsifiers with other natural polymers to form multilayered interfaces (Surh et al., 2006). For example, protein-coated droplets are 45 either negatively or positively charged when the pH is below or above their isoelectric 46 point (pI) (Wang et al., 2019), and then they could attract the oppositely charged 47 polysaccharides present in the continuous phase, thereby forming a thicker layer at 48 O/W interface. Zhang et al. (2020) developed multilayer emulsions by addition of 49 camellia saponin (CS) into almond protein isolate (API) based primary emulsions at 50 pH 3. Compared with primary emulsions, droplets with multi-layered interfaces have 51 52 the ability to significantly inhibit lipid and protein oxidation during storage. Compare with emulsions with single-layer interfaces, emulsions with multilayered interfaces 53 were also found to have better stability against environmental stresses, such as pH 54 extremes, high ionic strengths, thermal processing, and freezing (Ogawa et al., 2003, 55 56 2004).

57 The basic mechanism for the preparation of multilayer interfaces is by adding 58 oppositely charged polymers to a "primary" emulsion prepared by conventional

homogenization techniques (Ogawa et al., 2003). As a result, a "secondary" emulsion 59 with a two-layer interface could be formulated due to electrostatic attraction. This 60 process can be repeated several times to produce three or more-layer emulsions with 61 desired functional properties. Previous studies (Guzey & McClements, 2006; 62 McClements, 2012) demonstrated that adsorption layers can be deposited around 63 droplets in two different ways: a one-step or two-step mixing procedure, depending 64 on the charge-pH properties of the used biopolymer. In the one-step mixing method, a 65 66 solution containing oppositely charged biopolymers is directly mixed with a primary emulsion containing charged droplets. This approach tends to promote the tendency of 67 droplets to flocculate or coalesce during the process, and the aggregation is generally 68 irreversible (Guzey & McClements, 2006; Surh et al., 2006). In the two-step method, 69 the solution containing the charged biopolymer is mixed with the primary emulsion at 70 a pH where there is no strong electrostatic attraction between them. The pH of the 71 mixture is then adjusted to a pH where the droplets and the unabsorbed polymer have 72 opposite charges, so that the polymer can be adsorbed to the droplet surface. This 73 74 method is usually preferred for the production of multilayered interfaces at laboratory scale, since the second layer of biopolymer is more uniformly distributed throughout 75 the aqueous phase prior to adsorption (Liu et al., 2022; Mundo et al., 2021; Shi et al., 76 2021). Nonetheless, the two-step approach has several drawbacks: (i) Irreversible 77 aggregation occurs when the pH is adjusted to pass the pI of the protein emulsifier; (ii) 78 not suitable for the preparation of emulsions with more than two layers; (iii) relatively 79 complex process is not suitable for industrial mass production. For this reason, the 80 one-step approach was selected in our study and further optimized to avoid droplet 81 82 aggregation for preparing stable multilayer emulsions.

To minimize droplet aggregation in the one step method, it is necessary to ensure that enough biopolymers for coatings is present in the system to surround the entire surface of the added oil droplets. Otherwise, bridging flocculation may occur, as one polyelectrolyte may adsorb to the surface of multiple droplets, causing them to link together (McClements, 2012). Even with sufficient free polyelectrolyte concentration in the aqueous phase, droplet aggregation cannot be completely avoided because particle-particle collisions are sometimes faster than the adsorption of biopolymers to the surface of the primary coating droplets. One strategy to avoid the droplet aggregation during the process of forming multilayer emulsions is to control the ratio of mixing by titrating primary emulsions into coating solutions (Zeeb et al., 2015). Therefore, the concentration and mixing methods of biopolymers must be carefully designed to avoid extensive droplet aggregation and massive free polyelectrolyte remaining in the aqueous phase after the coating step.

96 The saturation concentration for a mutilayer system has been mostly characterized by dynamic light scattering (DLS), which provides the saturation 97 condition by identifying the ζ-potential plateau (Okubo & Suda, 2003). In this study, 98 we used isothermal titration calorimetry (ITC) and conventional DLS to investigate 99 the interaction and thermodynamic characteristics between sodium caseinate (CAS) 100 stabilized emulsion and low methoxyl pectin (LMP) during the preparation of 101 multilayer emulsions. In the first part, the thermodynamic parameters and surface 102 charge during the formation (titration and back-titration) of the multilayer emulsion 103 104 were evaluated to understand the stabilization mechanism of the multilayer emulsion during the preparation. Meanwhile, the advantages of ITC and DLS in measuring the 105 system are described and compared. In the second part, the multilayer emulsions 106 prepared by titration and direct mixing methods were compared in terms of particle 107 size distribution, zeta potential (ζ-potential), creaming behavior, microstructure, and 108 fluorescence intensity. This research could provide more information for the rational 109 design of multilayer emulsions. 110

111

112 2. Materials and methods

113 **2.1. Materials**

The powder of CAS with 93.20% protein content (determined by the Kjeldahl method, N=6.38) was purchased from Fisher Scientific (UK). The powder of LMP (esterification degree from 22% to 28% and acetylation degree from 20% to 23%) with 81.21% carbohydrate content was obtained from Cargill (Baupte, France). A medium chain triacylglycerol oil (MCT) was purchased from Gattefossé (Saint-Priest,

France). Imidazole, acetic acid, sodium azide, sodium hydroxide, and hydrochloric
acid were purchased from Sigma-Aldrich Chimie (St Quentin Fallavier, France). The
water used in all preparations was deionized water.

122 **2.2. Sample preparation**

Imidazole-acetate buffer solutions (5 mM) containing 0.04 wt.% sodium azide (to avoid microbial growth, (Chang et al., 2016)) was prepared by dispersing weighed amounts of imidazole and acetic acid into deionized water. Biopolymer stock solutions were prepared by slowly dispersing 0.53 wt.% CAS and 0.50 wt.% LMP separately into 5 mM imidazole-acetate buffer and stirring overnight to ensure complete hydration. The pH of both stock solutions was then adjusted to 3.0 by adding HCl (1 M) 24 h prior their use.

130 **2.3.** Preparation of primary emulsions and multilayer emulsions

Oil-in-water coarse emulsions were prepared by mixing 5.0 g MCT oil and 95 g emulsifier aqueous solution (0.53 wt.% CAS stock solution at pH 3.0) by high-speed homogenization (IKA, Staufen, Germany) under 13,500 rpm for 5 minutes. The resultant pre-emulsions was then passed through a microfluidizer (Microfluidics LM20, Microfluidics Corp., Newton, MA, USA) 5 times at 5×10^7 Pa to obtain nanoemulsions (Liao et al., 2021). The obtained nanoemulsions (containing 0.5 wt.% CAS) were then adjusted to pH 3.0 and considered as "primary emulsions".

Multilayer emulsions were prepared by titrating the primary emulsions into LMP 138 stock solution (0.5 wt.%) at a rate of 2.5 mL/min by using an automated procedure 139 with the TitroLine 5000 (TitroLine 5000, Xylem Analytics GmbH, Weilheim in 140 Oberbayern, Germany). During the titration, the samples were kept under agitation 141 142 and different ratios of primary emulsion/LMP were collected for subsequent analysis. 143 To investigate the effect of LMP on the formulation of multilayer emulsions when the coating material was insufficient, back-titration was also performed on the same ratio 144 of CAS-based emulsion/LMP. Meanwhile, direct mixing was performed by slowly 145 pouring different volumes of primary emulsions in same ratios (w/w) into the LMP 146 147 stock solution under stirring to compare the effects of different mixing methods on the multilayer emulsions. 148

149 **2.4. Isothermal titration calorimetry (ITC)**

The energetics of the interactions between primary emulsions and LMP was 150 measured using an isothermal titration calorimeter (VP-ITC) from MicroCal (Malvern 151 Instruments, Northampton, MA) in a reaction cell volume of 1.4214 mL. LMP and 152 CAS-based emulsions were diluted to the desired concentration (0.05 or 0.50 wt.%) 153 with the same buffer (5 mM imidazole-acetate buffer, pH 3.0). All solutions were 154 degassed under stirring for 5-10 min before being loaded. The pH of each solution 155 156 was checked again before measuring to ensure the same values in the cell and in the syringe. The calorimetric cell was filled with LMP solution (0.5 wt.%) and the electric 157 injector was filled with CAS-based emulsion (0.05 wt.%), equilibrated at 25 °C. The 158 titration was performed by adding an initial 2 μ L injection and 28 consecutive 10 μ L 159 injections while continuously stirring the mixture at 307 rpm. Each injection lasted 20 160 s with a 200 s interval between consecutive injections. Back-titration was also 161 performed by placing the CAS-based emulsion (0.5 wt.%) into the cell and the LMP 162 solution (0.05 wt.%) into the syringe, separately. Controlled titrations were performed 163 164 by injecting the primary emulsion or LMP solution into imidazole-acetate buffer to obtain the heat of dilution, so corrected data were obtained by subtracting the heat of 165 dilution data from the raw data. Data analysis was carried out by Origin 7.0 software. 166 167 The Gibbs free energy is calculated by the equation $\Delta G = \Delta H - T\Delta S$. Measurements were performed in triplicate and results are reported as mean and standard deviation. 168

169 **2.5. Intrinsic fluorescence**

Intrinsic fluorescence intensity of multilayer emulsions with different ratios of 170 CAS-based emulsion/LMP was carried out at room temperature by a multimode 171 172 microplate reader equipped with a temperature-controlled 96-wells microplate (Thermo Scientific[™] Varioskan). The excitation wavelength was set at 280 nm and 173 the emission spectrum was recorded in the wavelength range of 298-550 nm with an 174 excitation and emission slit width of 5 nm. The multilayer emulsions formulated by 175 titration in different ratios was diluted with 5 mM imidazole acetate buffer (pH 3.0) to 176 177 a final concentration of 0.05 wt.% CAS. The diluted samples were then evenly transferred to 96-well plates for analysis, with 6 measurements per sample. The 178

179 fluorescence intensity of acetate-imidazole buffer and pure LMP solution were used180 as a blank and a control, separately.

181 **2.6. Zeta potential (**ζ potential)

The ζ potential was performed by electrophoretic mobility (Malvern Instruments, Worcestershire, UK) under room temperature. To avoid multiple scattering effects, each sample was diluted to a concentration of around 0.05 wt.% with the same buffer (5 mM imidazole-acetate buffer, pH 3). Diluted samples were transferred to disposable cells for electrophoretic mobility measurement. All measurements were performed three times and the ζ -potential values were calculated by the software as the average of three individual measurements.

189 2.7. Mean particle size

Mean particle size (nm), polydispersity index (PdI) and size distribution were determined by dynamic light scattering using a Zetasizer Nano-ZS90 (Malvern Instruments, Worcestershire, UK) under room temperature. To eliminate multiple scattering effects, each sample was diluted to a droplet concentration around 0.1 wt.% with corresponding pH buffers. After 90 s of equilibrium, each sample was analyzed three times.

196 **2.8. Microscopic image**

Before analysis, each sample should be gently stirred in glass tubes to ensure they 197 were homogeneous. A drop of the emulsion was placed on a microscope slide and 198 covered with a coverslip. The microstructure of samples was then visualized at room 199 200 temperature using an Evos bright-field microscope (EVOS M5000, 201 Thermo-Invitrogen, USA).

202 **2.9. Statistical analysis**

All experiments were carried out at least three times with freshly prepared samples. Data are reported as means \pm standard deviations.

205 **3. Results and discussions**

3.1. Formation mechanism of multilayer emulsions

207 **3.1.1. Zeta potential analysis**

The appropriate concentration of the biopolymer coating around the primary emulsion can usually be assessed by measuring the zeta potential (Okubo & Suda, 2003). It has been reported that the ζ -potential of colloidal systems varies with the continuous addition of adsorbable polymers, and the plateau of the ζ -potential as function of ratio is related to the surface saturation of the polymer coating (Chang et al., 2016).

Fig. 1 showed the ζ -potential of multilayer emulsions prepared by titration and 214 back-titration as function of CAS/LMP or LMP/CAS ratio. The ζ-potential of pure 215 LMP solution (Fig.1A) at pH 3.0 is negative (-17.0 mV) which is attributed to the 216 ionization of its carboxyl groups. When the ratio of CAS-based emulsion/LMP is 217 increased, the ζ-potential initially remain stable until the ratio reached 0.5, then 218 became increasingly less negative, with a point of zero charge in the ratio range 219 220 around 1.25 - 1.50, and finally reached a plateau for higher ratio (3.0) (ζ-potential close to that of primary emulsion). This is the fact that the primary emulsion exhibited 221 positive charge at pH 3.0 because the protonation of the basic side chain (NH_3^+) of the 222 casein molecule. As a result, LMP molecules can be adsorbed on the droplet surface 223 by electrostatic force, and then the overall negative charge of the system gradually 224 increases until there are not enough LMPs in the system to cover the newly dropped 225 droplet. As shown in Fig. 1B, the ζ -potential of the primary emulsion is positive 226 (+32.6 mV) and this value could be considered enough to ensure high intermolecular 227 repulsions (Lieberman et al., 2020). When the LMP concentration was increased, the 228 229 ζ -potential initially remains stable until the ratio reaches 0.3, then becomes increasingly less positive, with a point of zero charge in the ratio range around 0.6 -230 0.8, and finally reached a plateau at a ratio of 1.5 (Fig.1B). According to previous 231 reports (Chang et al., 2016; Liu et al., 2019), the plateau of ζ-potential indicates that 232 233 the lipid droplet surface is saturated with coating polysaccharides at this level. It should be mentioned that during the experiment, the titration of the primary emulsion 234

into the LMP solution resulted in a stable multilayer emulsion, while titration in the 235 opposite direction (LMP solution into the primary emulsion) showed obvious flocs 236 and these flocs did not disappear with the continuous addition of LMP (Data not 237 shown). Based on our results, the forward titration reached a plateau at a ratio 3.0 (Fig. 238 1A), which corresponds exactly to a ratio of 0.3 (Fig. 1B) for titration of the primary 239 emulsion into the LMP solution. After the ratio 0.3, the absolute value of the zeta 240 potential begins to decrease, indicating that the droplet saturation potentials 241 242 corresponding to the titrated and back-titrated samples are consistent. Therefore, this finding suggests that the zeta potential can represent the overall distribution of 243 particles in solution but cannot reflect whether the multilayer emulsion formulation is 244 stable during preparation (the occurrence of particle aggregation). 245

Meanwhile, to find the exact concentration of coating polymer at which the multilayer emulsions reach the plateau, a large number of samples in different ratios should be prepared to measure for ζ -potential measurements, which are considered very complex and time-consuming processes. In this regard, we employed ITC to measure thermodynamic parameters to gain a deeper understanding of the stoichiometry of layer-by-layer interactions and to analyze the energetics of multilayered interfaces processes.

253 **3.1.2. ITC analysis**

ITC have been widely used to investigate molecular interactions in biological 254 systems (Jafari et al., 2007; Wang et al., 2019), but there are few reports on the 255 interaction between droplets and molecules (Fotticchia et al., 2014). Hence, ITC was 256 used to obtain more information about the evolution of deposition around the primary 257 258 emulsion, such as the equilibrium adsorption constant, enthalpy of adsorption, and 259 adsorption stoichiometry. CAS-based emulsions and LMP solutions at pH 3.0 were chosen to perform ITC tests at 25 °C because CAS-coated droplets showed positive 260 charge and LMP molecules showed negative charges at pH 3.0 (Wang et al., 2019). In 261 this study, heat flow versus time curves (the upper of Fig. 2) were obtained by 262 263 gradually injecting 0.5 wt.% primary emulsion or 0.5 wt.% LMP solution into a reaction cell containing 0.05 g/L LMP solution or 0.05 wt.% primary emulsion at 264

265 25 °C. The enthalpy changes (the lower of Fig. 2) as function of mass ratio were
266 obtained by the software. The mass unit was used to replace the molecular unit in this
267 study, because both CAS and LMP are high molecular weight polymers.

The ITC measurements (Fig. 2A) showed that the titrating process was exothermic 268 with a stepwise change in the exothermic value for each injection. When the ratio of 269 primary emulsion/LMP is lower than 1.0, the values of heat released per injection are 270 very close, which indicates that the injected CAS-coated droplets have a more stable 271 272 interaction with the LMP molecules in the reaction cell at this stage. This phase also corresponds to that when the absolute value potential of zeta (Fig. 1A) gradually 273 approaching the "0" point from larger values (-17.0 mV to -8.42 mV), implying that 274 multiple emulsions may go from stable to relatively unstable from this point (Ratio 275 1.0). This was probably attributed to the fact that, at the initial stage, excess negative 276 LMP molecules in the cell can quickly adsorb on the surface of the positively charged 277 emulsion droplets due to electrostatic interactions. Our previous study (Wang et al., 278 2019) reported the interaction between CAS and LMP when used at the same contents 279 280 in this study. Interestingly, the heat released by the interaction between CAS and LMP decreases with regularity from the beginning. This difference may stem from 281 differences in binding between molecules and between molecules and droplets. The 282 CAS-encapsulated droplets prepared in this study have nanoscale diameters with an 283 average particle size of about 300 nm, so the CAS molecules adsorbed on the surface 284 of the oil droplets have a more ordered structure in the system than free casein 285 molecules in the aqueous phase. As a result, each casein-coated droplet entering the 286 cell has enough LMP molecules to cover the droplet surface through electrostatic 287 288 attraction rather than disordered droplet aggregation, thereby releasing a relatively stable heat per injection at the initial stage. For ITC measurements between CAS and 289 LMP solutions, complexes were formed during each injection and these complexes 290 were confirmed to be insoluble at pH 3.0 (Wang et al., 2019). Therefore, it can be 291 hypothesized that the casein molecules may rapidly form disordered network fibers 292 293 after entering the reaction cell, and the degree of network structure is more extensive, and the heat released is higher. When the ratio was above 1.0, the heat released per 294

injection stated to decrease regularly (Fig. 2A). This may be attributed to the gradual 295 depletion of LMP chains in the reaction cell. Above the ratio of 1.4, the enthalpy 296 becomes slightly positive and remains stable, indicating that none of the LMP 297 molecules in the cell can interact with the newly added droplet. However, the result of 298 zeta potential (Fig.1 A) showed that the plateau was obtained when the ratio of 299 CAS-based emulsion/LMP was around 3.0, which was not consist with ITC results. It 300 was reported that the ζ -potential is highly sensitive to the environmental conditions, 301 302 and slight differences in the ion concentration can affect measurements (Fotticchia et al., 2014). For instance, sample should be diluted before measurements the ζ -potential 303 and the dilution may also influence the authenticity of the system. Fotticchia et al. 304 (2014) showed similar results by titration chitosan or poly-l-lysine into egg lecithin 305 based emulsions and they demonstrated that ITC could provide more accurate 306 information than DLS. 307

Fig. 2A showed that the enthalpy change (Δ H) in the titration was -0.534.40 308 kcal/mg. The Gibbs free energy (ΔG) was also negative (-8.96 kcal/mg) by fitting the 309 310 curve of " one set of sites ", indicating that the interaction between the primary emulsion and LMP was a spontaneous reaction. Similar exothermic sequences were 311 also found in ovalbumin/chitosan (Xiong et al., 2016) and soy proteins/gum Arabic 312 (Dong et al., 2015). This result supports the generally accepted view that adsorption is 313 primarily driven by electrostatic interactions (Burgos-Díaz et al., 2016; Fotticchia et 314 al., 2014). Indeed, the interaction in the preparation of the multilayer emulsion is a 315 more complex interaction than just an electrostatic mechanism. It may also include 316 hydrophobic interactions, van-der-Waals forces, and hydrogen bonding. However, we 317 318 cannot say whether these forces are present, because ITC measures the sum of all events that occur in the reaction cell. Furthermore, comparing the ΔG value (-8.13) 319 kcal/mg) obtained from the interaction between CAS and LMP (Wang et al., 2019), it 320 was found that the absolute value of ΔG is higher in this study. This could be 321 attributed to the fact that the adsorbed casein (+32.6 mV) exhibited stronger surface 322 charge than free casein molecules (+20 mV) in the continuous phase at pH 3.0 (Wang 323 et al., 2018). 324

325 ITC measurements by titrating LMP solution into primary emulsions were also performed to understand the heat flow (Fig. 2B) in the presence of insufficient 326 polysaccharides. Instead of decreasing regularly, the heat released of each injection 327 increased in the initial phase and the maximum heating was obtained at ratio 0.3. 328 Several possibilities may explain this behavior: (i) insoluble flocs were clearly 329 observed by titration of LMP into the primary emulsion at the initial stage, and these 330 flocs did not disappear with the continuous addition of LMP (Data not shown). This 331 332 can be attributed to the bridging flocculation caused by negatively charged pectin molecules and positively charged droplets. The bridging flocculation process may be 333 accompanied by more complex reactions than electrostatic adsorption, such as some 334 endothermic effects (unfavorable conformational changes, hydrophobic interactions, 335 etc. (Bou-Abdallah & Terpstra, 2012)) and, (ii) when the pH of stock solution was 336 adjusted to 3.0 by HCl, some ions remained in the solution may inhibit binding 337 interactions (Xiong et al., 2017) due to the formation of an ionic screen that prevents 338 the interaction between the two biopolymers. Interestingly, the ratio 0.3 also 339 340 corresponds to the starting decrease of ζ -potential (Fig. 1B), suggesting that the overall droplet surface charge in this system changed. After this ratio, the heat 341 released after each injection started to decrease regularly and reaches the "0" point at 342 ratio 0.7. However, Fig. 1B showed that the ζ -potential reached a plateau until the 343 ratio 1.5, while ITC data indicated that there was no obvious heat changed at ratios 344 higher than 0.7. This finding suggested that the continued decreased in potential 345 caused by the addition of LMP is probably not accompanied by a significant thermal 346 347 change.

348 3.1.3. Schematic representation of the formation of multilayer emulsions by titration

Based on the above results, a schematic diagram was established to summarize the main events occurring as function of the ratio in the titration and back-titration systems (Fig. 3). For the primary emulsion titration by LMP solution, stable multilayer emulsions are successfully formed at the initial stage, which were stable to droplet flocculation. This is because each injection contains enough LMP chains to

completely cover oil droplets and gives them a negative surface charge, thereby 355 avoiding droplet aggregation due to electrostatic repulsion. Theoretically, as the LMP 356 in the system is gradually depleted, the injected droplets will interact with other 357 LMP-coated droplets, causing large droplets to aggregate. In general, bridging 358 flocculation tends to occur earlier (before the biopolymer in the continuous phase is 359 completely depleted), which are mainly depending on the mixing methods (mixing 360 (Liu et al., 2019) or titration (Zeeb et al., 2015)) and biopolymer properties (e.g., 361 362 charge density, molecular weight, and conformation (Gharsallaoui et al., 2010)). For back-titration, bridging flocculation occurs at the initial stage, as the injected 363 negatively charged LMP molecules will adsorb to the surface of multiple droplets and 364 link them together. Although negatively charged pectin continued to be added to the 365 system, making the surface of the entire system negatively charged (Fig. 1B), the 366 flocs that had produced did not disappear. This finding is consistent with some other 367 reports (Liu et al., 2019; Surh et al., 2006). Clusters of droplets held together by 368 protein bridges is generally not reversible, which can be disrupted only by strong 369 370 shear forces (e.g. a second-stage of homogenization) (Dickinson, 2019). For instance, F. Liu et al (2016) mixed primary emulsions and lactoferrin and then used a blender 371 and high pressure homogenizer to redisperse droplets to obtain stable multilayer 372 emulsions. However, Fotticchia et al. (2014) indicated that stable multilayer 373 emulsions can be prepared by titrating chitosan or poly-L-lysine into the primary 374 emulsion, although bridging flocculation occurs at the initial stage of titration. Tang et 375 al. (2021) successfully prepared multilayer emulsions by direct mixing relatively high 376 content of sodium alginate with chitosan based picking emulsions. These differences 377 378 may originate from the properties of different biopolymers (e.g., charge density, 379 molecular weight and conformation), the primary layer thickness of emulsion droplets, as well as solution conditions (e.g., pH, ionic strength, temperature, and stirring) 380 381 (Burgos-Díaz et al., 2016).

382 **3.1.4.** Analysis of fluoresence intensity

383 Several studies have reported (Acharya et al., 2013; Qiu et al., 2015) that CAS or 384 CAS-based droplets exhibited an obvious emission band around 330 nm when the extraction band was 280 nm due to the presence of tryptophan. For this reason, measurements of tryptophan fluorescence spectroscopy during the formation of CAS-LMP based multilayer emulsion were used to study CAS conformational changes, owing to the fact that the intrinsic fluorescence of tryptophan residues is highly sensitive to the polarity of microenvironments (Li et al., 2021).

Fig. 4A shows the fluorescence spectra of multilayer emulsions prepared by 390 titrating the primary emulsion into LMP solution with different ratios and all samples 391 392 maintained the same CAS content. All samples emulsion showed strong fluorescence emission upon excitation at 280 nm, with a peak near 330 nm. Interestingly, when the 393 ratio ≤ 0.6 , there was no obvious shift in the maximum emission wavelength of 394 LMP-CAS based emulsion; however, when the ratio was above 0.6, the wavelength 395 corresponding to the maximum showed a slight red shift compared to the primary 396 397 emulsion. It has been reported that the red or blue shift in the emission band of CAS was usually related to changes in the tryptophan environment (Li et al., 2019). 398 Therefore, no shift was observed at ratio ≤ 0.6 which suggest that binding of LMP and 399 400 CAS-coated droplets in this stage did not change the tryptophan environment.

The quenching of the fluorescence intensity has been reported as an indicator of 401 the interaction of the components in the solution (Wang et al., 2015). Therefore, the 402 adsorption force of LMP to the surface droplets of the primary emulsion can be 403 deduced from the test results. In this regard, the maximum fluorescence intensities of 404 these emulsions prepared by titration as a function of ratio are plotted in Fig. 4B. In 405 the ratio range of 0 to 0.6, titration-prepared samples showed similar maximum 406 fluorescence intensities; however, when the ratio is greater than 0.6, the maximum 407 408 intensity of samples decreases obviously with the increase of the ratio until it reaches 409 1.75. The decrease in entropy intensity indicates that some of the tryptophan residues of CAS adsorbed on the oil droplets were transferred from the polar surface to the 410 hydrophobic interior, which may be due to the interaction of tryptophan located in the 411 hydrophobic region of the protein with pectin through hydrophobic bonds. The 412 413 decrease in intensity suggests that some of the tryptophan residues of CAS adsorbed on the oil droplet are transferred from the polar surface to the hydrophobic interior, 414

415 which was probably attributed to the droplet aggregation. Similar behavior was reported for aggregation of soybean protein isolate/pectin complexes (Li et al., 2021). 416 This result also indicates that formation mechanism of multilayer emulsions by LMP 417 and CAS coated droplet is not only electrostatic but also accompanied by a certain 418 degree of hydrophobic interactions (especially when the droplets are extensively 419 aggregated), which was supported by the data of ITC results. At the same time, the 420 maximum fluorescence intensity of these samples increased as the ratio increased 421 422 from 1.75 to 2.5. This can be attributed to the presence of some individual CAS-coated droplets in the system due to the relatively high CAS-based 423 emulsion/LMP ratio. 424

3.2. Effect of titration or mixing on the properties of multilayer emulsions: analysis of droplet size and flocculation

It should be noted that many papers demonstrated the successful preparation of 427 multilayer emulsions by adding primary emulsions to other coating materials 428 (Burgos-Díaz et al., 2016; Liu et al., 2019; Shi et al., 2021). However, there are no 429 430 details on how to define "add". In fact, there are many ways of addition, such as slow/quick addition, titration or direct pouring, and these different ways of addition 431 seem to have a significant effect on droplet aggregation in the preparation of 432 multilayer emulsions. In this section, the direct mixing and titration under stirring 433 were used to prepare multilayer emulsions in different ratios of CAS-based 434 emulsion/LMP. Then, dynamic light scattering (DLS) (Fig. 5A-D), creaming index 435 (Fig. 6A), and optical microscopy (Fig.6 B) will be presented to evaluate the surface 436 charge, mean particle size and droplet aggregation of these emulsions. 437

Fig.5A exhibited the zeta potential of emulsions in both preparation methods. Interestingly, the multilayer emulsions in both methods showed similar trends in surface charge as a function of ratio, although distinct flocs were observed earlier in the emulsions prepared by direct mixing. This might be the limitation of microelectrophoresis mobility method: samples need to be highly diluted and this process may have changed the surface charge of the system (Hu et al., 2017; Salvia-Trujillo et al., 2013). For example, droplet aggregation in highly concentrated 445 emulsions may be partially redispersed to some extent after dilution and agitation. Primary emulsions exhibited nanoscale diameter (~300 nm, Fig. 5B) with relatively 446 lower polydispersity index (PdI) values (Fig. 5C). As the ratio increases, all emulsions 447 showed increased droplet size and PdI values, which can be attributed to the fact that 448 negatively charged LMP adsorbed on the surface of CAS-coated droplets or droplet 449 aggregates. A similar result was found in the study of chitosan/pectin-stabilized 450 multilayer emulsions (Liu et al., 2019). It is worth noting that the particle size and PdI 451 452 values of samples prepared by mixing method are higher than those prepared by titration one. Until the ratio reached 0.8, the titration-prepared multilayer emulsions 453 still exhibited nanoscale average droplet diameter (~600 nm) based on DLS analysis; 454 however, when the ratio was higher than 0.5, the size of sample prepared by mixing 455 was outside the measurement range of DLS. This was probably attributed the fact that 456 directly mixing provides more droplets in the same time than titration, and 457 consequently droplet-droplet collisions may occur more rapidly than polyelectrolyte 458 molecules adsorb to the droplet surfaces, thereby caused larger droplets (Guzey & 459 460 McClements, 2006). However, during the titration process, a small number of droplets added each time can be quickly encapsulated by the polyelectrolyte at a lower 461 concentration ratio. As a result, once the surface charge reached a certain value, there 462 will be a strong electrostatic repulsion between the surface and similarly charged 463 polyelectrolytes in the aqueous phase, which limits further adsorption of the 464 polyelectrolyte, thereby reducing the probability of droplet-droplet collision and 465 retarding the occurrence of particle aggregation. This result was also confirmed by the 466 droplet size distribution. The titration-prepared samples did not show distinct peaks in 467 468 the larger size range until ratio reached 0.5, while even with a ratio of only 0.1 (Fig. 469 5D), distinct peaks in the larger size range were detected in the sample formed by mixing (Fig. 5E). This result proved that droplet flocculation is readily to occur in the 470 mixing directly methods, indicating that different adding methods have a significant 471 472 effect on the droplet flocculation during the formulation of multilayer emulsions.

473 Fig. 6 A showed the visual appearance of multilayer emulsions prepared by
474 directly mixing and titration methods. As expected, those prepared by mixing showed

475 a cream layer when the ratio increased. Even at a ratio of 0.1, a phase separation can be observed where an opaque cream layer at the top and a strongly turbid 476 droplet-depleted layer at the bottom, which was consistent with result of particle size 477 (Fig. 5E). This behavior can be attributed to bridging flocculation promotion leading 478 to an increase in particle size, which facilitates gravitational separation (Grundy et al., 479 2018). However, when the ratio was increased to 0.5, there was a slight creaming at 480 the bottom of the emulsion prepared by mixing, which may be due to an increase in 481 482 viscosity (polymer entanglement or viscoelastic network formation) (Grundy et al., 2018). As a result, the increased viscosity restricts the upward movement of the 483 aggregated droplets. Notably, the multilayer emulsion prepared by titration showed 484 much better stable creaming stability than that prepared by mixing, since no obvious 485 phase separation occurred until the ratio reached 1.0. This could be attributed to 486 relatively low PdI value (Fig. 5C) in these emulsions. 487

For further analysis, the microstructure of the primary emulsion (control) and 488 several selected multilayer emulsions prepared by titration in different ratios (0.5:1; 489 490 0.8:1; 1:1; 1.5:1; 2:1) were observed by optic microscopy. These samples represent different states of droplets during the preparation of multilayer emulsions. Compared 491 to the primary emulsion, the multilayer emulsion also exhibits a very homogeneous 492 microstructure in the ratio ≤ 0.5 , which supports the results of the size measurements. 493 As the ratio increased, droplet aggregation was clearly observed at higher chitosan 494 concentrations, especially when the ratio was higher than 1.0. This is because there 495 are not enough LMP molecules in the system to coat the droplets, and then two or 496 more droplets share a polysaccharide chain to form aggregates. Remarkably, both 497 498 extensive droplet aggregation and significantly increased droplet size (Fig. 5B) 499 occurred around the ratio 1.0, which corresponds to the ratio where the heat released by titration (Fig. 2A) began to decrease. These findings suggest that ITC could 500 provide accurate information on when flocculation occurs, leading to optimal 501 conditions for the preparation of O/W multilayer emulsions. 502

503 4. Conclusion

504

This study tried to explain the mechanism of the formation of multilayer

emulsions by titrating primary emulsions into coating materials. According to the 505 obtained results, ITC measurements by titration of the primary emulsion into the 506 coating material allow the acquisition of thermodynamic characteristics of the studied 507 system, which are fast, accurate and informative compared to the information 508 obtained from zeta potential measurements. ITC titration confirmed that LMP does 509 bind CAS-coated droplets through the electrostatic forces and it was a spontaneous 510 exothermic process ($\Delta G < 0$, $\Delta H < 0$). The binding is also accompanied by 511 512 hydrophobic forces. Titration of the primary emulsion into the LMP solution resulted in a stable multilayer emulsion, while titration in the opposite direction showed 513 obvious flocs due to bridging flocculation. Meanwhile, more uniform and 514 smaller-sized droplets can be prepared by titrating the primary emulsion into LMP 515 solution rather than mixing them directly, which can be attributed to the fact that slow 516 addition can effectively avoid the aggregation of droplets. Based on emulsion stability 517 and microscopy observations, ITC appears to have the ability to define when 518 flocculation begins, thus providing optimal conditions for the preparation of O/W 519 520 multilayer emulsions. In this way, the remaining coating materials in the continuous phase of the prepared double-layer emulsion can be reduced, so as to further prepare 521 emulsions with three or four interfaces..., thus providing more possibilities for O/W 522 food emulsion products. 523

524 ACKNOWLEDGEMENTS

525 Wei Liao greatly thanks Chinese Scholarship Council for support.

526 CONFLICTS OF INTEREST

- 527 The author declares that there is no conflict of interest that could be perceived as
- 528 prejudicing the impartiality of the research reported.

529 **References**

- Acharya, D. P., Sanguansri, L., & Augustin, M. A. (2013). Binding of resveratrol with
 sodium caseinate in aqueous solutions. *Food Chemistry*, *141*(2), 1050–1054.
- Bou-Abdallah, F., & Terpstra, T. R. (2012). The thermodynamic and binding
 properties of the transferrins as studied by isothermal titration calorimetry. *Biochimica et Biophysica Acta (BBA)-General Subjects*, *1820*(3), 318–325.
- Bouyer, E., Mekhloufi, G., Rosilio, V., Grossiord, J.-L., & Agnely, F. (2012). Proteins,
 polysaccharides, and their complexes used as stabilizers for emulsions:
 Alternatives to synthetic surfactants in the pharmaceutical field? *International Journal of Pharmaceutics*, *436*(1), 359–378.
- Burgos-Díaz, C., Wandersleben, T., Marqués, A. M., & Rubilar, M. (2016). Multilayer
 emulsions stabilized by vegetable proteins and polysaccharides. *Current Opinion in Colloid & Interface Science*, 25, 51–57.
- Chang, P. G., Gupta, R., Timilsena, Y. P., & Adhikari, B. (2016). Optimisation of the
 complex coacervation between canola protein isolate and chitosan. *Journal of Food Engineering*, 191, 58–66.
- Chang, Y., Hu, Y., & McClements, D. J. (2016). Competitive adsorption and
 displacement of anionic polysaccharides (fucoidan and gum arabic) on the
 surface of protein-coated lipid droplets. *Food Hydrocolloids*, *52*, 820–826.
- Dammak, I., Sobral, P. J. do A., Aquino, A., Neves, M. A. das, & Conte- Junior, C. A.
 (2020). Nanoemulsions: Using emulsifiers from natural sources replacing
 synthetic ones—A review. *Comprehensive Reviews in Food Science and Food Safety*, 19(5), 2721–2746.
- 552 Dickinson, E. (2019). Strategies to control and inhibit the flocculation of 553 protein-stabilized oil-in-water emulsions. *Food Hydrocolloids*, *96*, 209–223.
- Dong, D., Li, X., Hua, Y., Chen, Y., Kong, X., Zhang, C., & Wang, Q. (2015). Mutual
 titration of soy proteins and gum arabic and the complexing behavior studied

- by isothermal titration calorimetry, turbidity and ternary phase boundaries. *Food Hydrocolloids*, 46, 28–36.
- Fotticchia, I., Fotticchia, T., Mattia, C. A., Netti, P. A., Vecchione, R., & Giancola, C.
 (2014). Thermodynamic Signature of Secondary Nano-emulsion Formation by
 Isothermal Titration Calorimetry. *Langmuir*, *30*(48), 14427–14433.
- Gharsallaoui, A., Saurel, R., Chambin, O., Cases, E., Voilley, A., & Cayot, P. (2010).
 Utilisation of pectin coating to enhance spray-dry stability of pea
 protein-stabilised oil-in-water emulsions. *Food Chemistry*, *122*(2), 447–454.
- Grundy, M. M. L., McClements, D. J., Ballance, S., & Wilde, P. J. (2018). Influence
 of oat components on lipid digestion using an in vitro model: Impact of
 viscosity and depletion flocculation mechanism. *Food Hydrocolloids*, *83*,
 253–264.
- Guzey, D., & McClements, D. J. (2006). Formation, stability and properties of
 multilayer emulsions for application in the food industry. *In Honor of Professor Nissim Garti's 60th Birthday*, 128–130, 227–248.
- Hu, Y.-T., Ting, Y., Hu, J.-Y., & Hsieh, S.-C. (2017). Techniques and methods to study
 functional characteristics of emulsion systems. *Dietary Natural Compounds*,
 25(1), 16–26.
- Jafari, S. M., He, Y., & Bhandari, B. (2007). Production of sub-micron emulsions by
 ultrasound and microfluidization techniques. *Journal of Food Engineering*,
 82(4), 478–488.
- Kim, W., Wang, Y., & Selomulya, C. (2020). Dairy and plant proteins as natural food
 emulsifiers. *Trends in Food Science & Technology*, *105*, 261–272.
- Li, F., Wang, H., & Mei, X. (2021). Preparation and characterization of
 phytosterol-loaded microcapsules based on the complex coacervation. *Journal of Food Engineering*, *311*, 110728.
- Li, X., Wu, G., Qi, X., Zhang, H., Wang, L., & Qian, H. (2019). Physicochemical

- properties of stable multilayer nanoemulsion prepared via the
 spontaneously-ordered adsorption of short and long chains. *Food Chemistry*,
 274, 620–628.
- Liao, W., Gharsallaoui, A., Dumas, E., Ghnimi, S., & Elaissari, A. (2021). Effect of
 carrier oil on the properties of sodium caseinate stabilized O/W nanoemulsions
 containing Trans-cinnamaldehyde. *LWT*, *146*, 111655.
- Lieberman, H., Rieger, M., & Banker, G. S. (2020). *Pharmaceutical dosage forms: Disperse systems*. CRC Press.
- Liu, C., Tan, Y., Xu, Y., McCleiments, D. J., & Wang, D. (2019). Formation,
 characterization, and application of chitosan/pectin-stabilized multilayer
 emulsions as astaxanthin delivery systems. *International Journal of Biological Macromolecules*, 140, 985–997.
- Liu, F., Wang, D., Sun, C., McClements, D. J., & Gao, Y. (2016). Utilization of
 interfacial engineering to improve physicochemical stability of β-carotene
 emulsions: Multilayer coatings formed using protein and protein–polyphenol
 conjugates. *Food Chemistry*, 205, 129–139.
- Liu, G., Hu, M., Du, X., Qi, B., Lu, K., Zhou, S., Xie, F., & Li, Y. (2022). Study on
 the interaction between succinylated soy protein isolate and chitosan and its
 utilization in the development of oil-in-water bilayer emulsions. *Food Hydrocolloids*, *124*, 107309.
- McClements, D. J. (2012). Advances in fabrication of emulsions with enhanced
 functionality using structural design principles. *Current Opinion in Colloid & Interface Science*, 17(5), 235–245.
- Mundo, J. L. M., Zhou, H., Tan, Y., Liu, J., & McClements, D. J. (2021). Enhancing
 emulsion functionality using multilayer technology: Coating lipid droplets
 with saponin-polypeptide-polysaccharide layers by electrostatic deposition. *Food Research International*, 140, 109864.

610	Ogawa, S., Decker, E. A., & McClements, D. J. (2003). Production and
611	characterization of O/W emulsions containing cationic droplets stabilized by
612	lecithin- chitosan membranes. Journal of Agricultural and Food Chemistry,
613	51(9), 2806–2812.

- Ogawa, S., Decker, E. A., & McClements, D. J. (2004). Production and
 characterization of o/w emulsions containing droplets stabilized by lecithin–
 chitosan– pectin mutilayered membranes. *Journal of Agricultural and Food Chemistry*, 52(11), 3595–3600.
- Okubo, T., & Suda, M. (2003). Multilayered adsorption of macrocations and
 macroanions on colloidal spheres as studied by dynamic light scattering
 measurements. *Colloid and Polymer Science*, 281(8), 782–787.
- Qiu, C., Zhao, M., Decker, E. A., & McClements, D. J. (2015). Influence of protein
 type on oxidation and digestibility of fish oil-in-water emulsions: Gliadin,
 caseinate, and whey protein. *Food Chemistry*, 175, 249–257.
- Salvia-Trujillo, L., Qian, C., Martín-Belloso, O., & McClements, D. J. (2013).
 Influence of particle size on lipid digestion and β-carotene bioaccessibility in
 emulsions and nanoemulsions. *Food Chemistry*, *141*(2), 1472–1480.
- Shi, F., Tian, X., McClements, D. J., Chang, Y., Shen, J., & Xue, C. (2021). Influence
 of molecular weight of an anionic marine polysaccharide (sulfated fucan) on
 the stability and digestibility of multilayer emulsions: Establishment of
 structure-function relationships. *Food Hydrocolloids*, *113*, 106418.
- Surh, J., Decker, E. A., & McClements, D. J. (2006). Influence of pH and pectin type
 on properties and stability of sodium-caseinate stabilized oil-in-water
 emulsions. *Food Hydrocolloids*, 20(5), 607–618.
- Tang, Y., Gao, C., Zhang, Y., & Tang, X. (2021). The microstructure and
 physiochemical stability of Pickering emulsions stabilized by chitosan
 particles coating with sodium alginate: Influence of the ratio between chitosan
 and sodium alginate. *International Journal of Biological Macromolecules*, 183,

- 1402–1409.
- Wang, J., Dumas, E., & Gharsallaoui, A. (2019). Low Methoxyl pectin / sodium
 caseinate complexing behavior studied by isothermal titration calorimetry. *Food Hydrocolloids*, 88, 163–169.
- Wang, J., Souihi, S., Amara, C. B., Dumas, E., & Gharsallaoui, A. (2018). Influence
 of low methoxyl pectin on the physicochemical properties of sodium
 caseinate- stabilized emulsions. *Journal of Food Process Engineering*, *41*(8),
 e12906.
- Wang, X., Liu, F., Liu, L., Wei, Z., Yuan, F., & Gao, Y. (2015). Physicochemical
 characterisation of β-carotene emulsion stabilised by covalent complexes of
 α-lactalbumin with (-)-epigallocatechin gallate or chlorogenic acid. *Food Chemistry*, 173, 564–568.
- Xiong, W., Ren, C., Jin, W., Tian, J., Wang, Y., Shah, B. R., Li, J., & Li, B. (2016).
 Ovalbumin-chitosan complex coacervation: Phase behavior, thermodynamic
 and rheological properties. *Food Hydrocolloids*, *61*, 895–902.
- Xiong, W., Ren, C., Tian, M., Yang, X., Li, J., & Li, B. (2017). Complex coacervation
 of ovalbumin-carboxymethylcellulose assessed by isothermal titration
 calorimeter and rheology: Effect of ionic strength and charge density of
 polysaccharide. *Food Hydrocolloids*, 73, 41–50.
- Zeeb, B., Lopez-Pena, C. L., Weiss, J., & McClements, D. J. (2015). Controlling lipid
 digestion using enzyme-induced crosslinking of biopolymer interfacial layers
 in multilayer emulsions. *Food Hydrocolloids*, 46, 125–133.
- Zhang, S., Tian, L., Yi, J., Zhu, Z., Decker, E. A., & McClements, D. J. (2020). Mixed
 plant-based emulsifiers inhibit the oxidation of proteins and lipids in walnut
 oil-in-water emulsions: Almond protein isolate-camellia saponin. *Food Hydrocolloids*, 109, 106136.



Fig. 1. ζ-potential of multilayer emulsions at pH 3.0 as a function of ratio: (A) titrating the
primary emulsion into LMP solution or (B) titrating LMP solution into the primary emulsion.



Fig. 2. ITC titration graphs (Upper) and enthalpy change (Lower) of (A) CAS-based
emulsion/LMP and (B) LMP/CAS-based emulsion at pH 3.0. The calorimetric cell and the syringe
were filled with 0.05 wt.% CAS-based emulsion and 0.5 wt.% LMP solution or 0.05 wt.% LMP
and 0.5 wt.% CAS-based emulsion.



673 Fig. 3. Schematic representation of the formation of multilayer emulsions by titration based on

674 CAS-coated emulsion and LMP at pH 3.0.



Fig. 4. (A) Fluorescence spectra and (B) maximum intensity of multilayer emulsions as a function
of ratio by titrating the primary emulsion into LMP solution. The excitation wavelength was set to
280 nm and the emission slit width was 5 nm.



- - -

(D)



Ratio (w/w, left to right): 0 - 0.1 - 0.25 - 0.5 - 0.8 - 1.0 - 1.25 - 1.5 - 2.0



Fig. 6. (A) Visual appearance of multilayer emulsions prepared by titration or mixing as function
of ratio and (B) Photomicrographs of multilayer emulsions prepared by titration. The scale bar is
20 μm in length.

(A)