

Error estimates for Gaussian beams at a fold caustic Olivier Lafitte, Olof Runborg

▶ To cite this version:

Olivier Lafitte, Olof Runborg. Error estimates for Gaussian beams at a fold caustic. Waves 2019, TU Wien, Aug 2019, Wien, Austria. hal-04004714

HAL Id: hal-04004714 https://hal.science/hal-04004714

Submitted on 25 Feb 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Error estimates for Gaussian beams at a fold caustic

<u>Olivier Lafitte^{1,*}</u>, Olof Runborg^{2,*}

 1 LAGA, Institut Galilée, Université Paris 13, Sorbonne Paris Cité, Université Paris 8

² Department of Mathematics, KTH, Stockholm, Sweden

*Email: olofr@kth.se

Abstract

Keywords: high frequency approximations, Gaussian beams, caustics

1 Introduction

We consider the particular case of a fold caustic in two dimensions generated by the index of refraction $n(x, y)^2 = 1 - x$. To be precise, we consider the out-going solution for the Helmholtz equation with a compactly supported source that concentrates on x = 0,

$$\Delta u + k^2 (1 - x)u = ik\delta(x)f(y),$$

where we take

$$f(y) = \frac{1}{\xi_0} A_0(y) e^{i\eta_0 y}, \qquad \xi_0 = \sqrt{1 - \eta_0^2}.$$

This represents an incoming plane wave in the direction θ with amplitude envelope $A_0(y)$, where $\eta_0 = \cos \theta$.

picture of solution

background on Gaussian beams and error estimates

2 Exact solution

We let $\hat{u}(x,\eta)$ be the k-scaled Fourier transform in y of the exact solution, i.e.

$$\hat{u}(x,\eta) = \sqrt{\frac{k}{2\pi}} \int e^{-i\eta ky} u(x,y) dy.$$

For x > 0 we can derive an exact expression written in terms of x, η and k using Airy functions,

$$\hat{u}(x,\eta) = \bar{\alpha} \frac{\operatorname{Ai}(k^{\frac{2}{3}}(x+\eta^2-1))}{\operatorname{Ai}(\alpha k^{\frac{2}{3}}(1-\eta^2))} \hat{u}_+(0,\eta). \quad (1)$$

In this expression, one notices that the denominator never vanish because all the roots of the Airv function are on the negative real axis.

what is α and \hat{u}_+ ?

3 Gaussian beam approximation

The approximation is made up of a superposition of Gaussian beams,

$$u_{GB}(x,y) = \sqrt{\frac{k}{2\pi}} \int v(x,y;z) dz.$$

where v is the Gaussian beam starting at y = z,

$$\begin{split} v(\boldsymbol{x}; z) &= \\ A(s; z) \exp\Bigl(ik\bigl[S(s; z) + (\boldsymbol{x} - \gamma(s; z)) \cdot \boldsymbol{p}(s; z) \\ &+ \frac{1}{2}(\boldsymbol{x} - \gamma(s; z))^T M(s; z)(\boldsymbol{x} - \gamma(s; z))\bigr]\Bigr), \end{split}$$

where $\boldsymbol{x} = (x, y)$. The beam parameters are the central ray position γ , the beam direction \boldsymbol{p} the shape M, the initial phase S and the amplitude A. They all satisfy known ODEs in s with initial data determined by z. In this particular case the ODEs can be solved exactly,

$$\begin{split} \gamma(s;z) &= (x(s;z), y(s;z) = (2s\xi_0 - s^2, \ z + 2s\eta_0) \\ \boldsymbol{p}(s;z) &= (\xi(s;z), \eta(s;z))) = (\xi_0 - s, \eta_0), \\ S(s;z) &= \eta_0 z + 2s - 2s^2\xi_0 + \frac{2}{3}s^3, \\ M(s;z) &= (I + 2sM_0)^{-1}M_0, \\ A(s;z) &= \frac{\tilde{A}_0(z)}{\sqrt{1 + 2si - s^2\beta}}. \end{split}$$

what is M_0 , β and $\tilde{A}_0(z)$?

For the evaluation of the beam we connect s to a particular y-coordinate by

$$s(y;z) = \frac{y-z}{2\eta_0}$$

Then we can derive the following expression for the k-scaled Fourier transform of u_{GB} ,

$$\hat{u}_{GB}(x,\eta) = 2\eta_0 \hat{\tilde{A}}_0(\eta - \eta_0) \sqrt{\frac{k}{2\pi}} e^{ik(-2\eta_0\xi_0(\eta - \eta_0) + 2\xi_0^3/3)}$$
(2)

$$\times \int \frac{e^{ik\phi(x,\theta,\eta - \eta_0)}}{\sqrt{1 + 2(\xi_0 + \theta)i - (\xi_0 + \theta)^2\beta}} d\theta,$$

where

$$\phi(x,\theta,\eta) = -\frac{1}{3}\theta^3 + \theta(\xi_0^2 - x - 2\eta_0\eta) + \frac{1}{2}m_{11}(\xi_0 + \theta)(x - \xi_0^2)$$

and m_{11} ?

4 Error estimate

We want to compute the max error at a fixed xand use the error in the k-scaled Fourier transform to estimate this,

$$\sup_{y} |u_{GB}(x,y) - u(x,y)| \le \sqrt{\frac{k}{2\pi}} \int |\hat{u}_{GB}(x,\eta) - \hat{u}(x,\eta)| dx$$

Away from the caustic where $0 \leq x < \xi_0^2$ we obtain the expected $O(k^{-1})$ error by using standard stationary phase estimates of the integral in the expression for \hat{u}_{GB} in (2) and asymptotic estimates for large arguments of Airy functions in the expression for \hat{u} . in (1).

The more interesting case is at the caustic where $x = \xi_0^2$. Then the asymptotic estimates above fail and a more precise analysis is needed. We use the Malgrange preparation theorem to change variables in (2). The critical values of the phase ϕ for η small are needed. Observing that $\partial_{\theta^3}^3(\xi_0^2, 0, 0) < 0$, let $\theta(x)$ solve (locally) $\partial_{\theta^2}^2(x, \theta(x), \eta) = 0$. One has $\theta(x) = (x - \xi_0^2)k(x)$, the (complex) critical points are $\theta_{\pm}(x, \eta) = \theta(x) \pm \delta_{\pm}\sqrt{\partial_{\theta}\phi}$ for $\Re \partial_{\theta} \phi > 0$, hence, for η small, two critical values arise:

$$\begin{aligned} \phi_{\pm}(x,\eta) &= \phi_0(x) \pm \frac{2}{3} (\tilde{\rho}(x,\eta))^{\frac{3}{2}}, \text{ with} \\ \tilde{\rho}(x,\eta) &= \partial_{\theta} \phi(x,\theta(x),\eta) r(x,\eta) \\ &= (\xi_0^2 - x + 2\eta\eta_0 + O((x - \xi_0^2)^2) r. \end{aligned}$$

Deduce then

$$\hat{u}_{GB}(x,\eta) = 2\eta_0 \hat{\tilde{A}}_0(\eta - \eta_0) \sqrt{2\pi} k^{\frac{1}{6}} \times$$
(3)

$$[\sigma_0 Ai + ik^{-\frac{3}{3}} \sigma_1 Ai'] (-k^{\frac{3}{2}} \tilde{\rho}(x,\eta)) \quad (4)$$

$$\times e^{ik(-2\eta_0 \xi_0(\eta-\eta_0) + 2\xi_0^3/3 + \phi_0(x,\eta))},$$

Comparing (3) and (1), using the principal term of $\tilde{\rho}$, $\phi_0, \sigma_0, \sigma_1$, the max error is of the order $O(k^{-5/6})$, which is demonstrated in numerical computations. Since the size of the solution itself grows as $O(k^{1/6})$ at the caustic, the relative error is then still $O(k^{-1})$.

References

 J. Ralston. Gaussian beams and the propagation of singularities. In *Studies in partial* differential equations, volume 23 of *MAA Stud. Math.*, pages 206–248. Math. Assoc. America, Washington, DC, 1982.

- [2] J.D. Benamou et al. A geometric optics based numerical method for high frequency
- based numerical method for high frequency + θ^2)²electromagnetic fields computations near a fold caustic I J. Comp. Appl. Math 156 (1): 93–125 (2003)
 - [3] H. Liu, O. Runborg, and N. M. Tanushev. Error estimates for Gaussian beam superpositions. *Math. Comp.*, 82:919–952, 2013.
 - [4] H. Liu, J. Ralston, O. Runborg, and N. M.
- dη. Tanushev. Gaussian beam method for the Helmholtz equation. SIAM J. Appl. Math., 74(3):771–793, 2014.
- [5] D. Ludwig Uniform expansion at the caustic Communications in Applied Mathematics, 19: 215–250, 1966
- [6] C. Zheng. Optimal error estimates for firstorder Gaussian beam approximations to the Schrödinger equation. SIAM J. Num. Anal., 52(6):2905–2930, 2014.
- [7] H. Liu, O. Runborg and N. Tanushev. Sobolev and max norm error estimates for Gaussian beam superpositions. *Commun. Math. Sci.*, 14(7):2037-2072, 2016.