



Acoustic responses of underwater superhydrophobic surfaces subjected to an intense pulse

Adrien Bussonnière, Qingxia Chad Liu, Peichun Amy Tsai

► To cite this version:

Adrien Bussonnière, Qingxia Chad Liu, Peichun Amy Tsai. Acoustic responses of underwater superhydrophobic surfaces subjected to an intense pulse. *Journal of Fluid Mechanics*, 2023, 956, pp.A32. 10.1017/jfm.2023.61 . hal-04009685

HAL Id: hal-04009685

<https://hal.science/hal-04009685>

Submitted on 1 Mar 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial - NoDerivatives 4.0 International License

Banner appropriate to article type will appear here in typeset article

Acoustic responses of underwater superhydrophobic surfaces subjected to an intense pulse

Adrien Bussonnière^{1,2,3}†, Qingxia Chad Liu² and Peichun Amy Tsai³‡

¹Laboratoire Matière et Systèmes Complexes, Université Paris Cité, UMR CNRS 7057, 75013 Paris, France

²Department of Chemical and Materials Engineering, University of Alberta, Edmonton, AB, T6G 1H9, Canada

³Department of Mechanical Engineering, University of Alberta, Edmonton, AB, T6G 1H9, Canada.

(Received xx; revised xx; accepted xx)

Underwater stability of an air layer trapped in a micro-structure, plastron, is critical in drag reduction application. Here we investigate the wetting state and plastron stability upon underwater superhydrophobic surfaces (SHS) under an intense acoustic drive. Flat surfaces and SHS are subjected to short acoustic pulses of different intensities. At low amplitude, the comparison between the results of various surfaces shows that plastron behaves like a water-air interface, whose presence can be detected from the phase of the reflected acoustic waves. At moderate intensity, a wetting transition towards a completely wetting state is observed and shown to be triggered by a sufficiently large acoustic radiation pressure. This wetting transition is well captured by a simplified model by balancing radiation pressure with the critical capillary pressure for the interface sliding. Cavitation clouds appear under strong excitation; their sizes and position greatly depend on the surface acoustic boundary condition. For a SHS in a Cassie-Baxter state (with an air layer), cavitation clouds appear at specific locations (from the solid surface) corresponding to the pressure anti-node of the transient standing wave generated by the reflection. This study unprecedentedly demonstrates the capability of acoustic waves to monitor and characterize plastron stability with low and moderate amplitudes, respectively.

Key words: acoustics, cavitation, contact lines, wetting and wicking

1. Introduction

Superhydrophobic surfaces (SHS) are bio-inspired surfaces composed of hydrophobic patterned micro/nano-structures (Quéré 2008). The combination of roughness and hydrophobicity makes such surfaces water-repellent, an attracting property for various applications (Quéré 2008). When immersed in water, SH surfaces can trap an air layer, also called plastron, inside the microstructure (Bobji *et al.* 2009), opening the avenue for drag reduction

† Email address for correspondence: adrien.bussonniere@cns.fr

‡ Email address for correspondence: peichun.amy.tsai@ualberta.ca

applications since such surfaces exhibit significant effective slipping lengths (Rothstein 2010). However, the stability of the air layer against pressure fluctuations, induced by potentially turbulent flow (Seo *et al.* 2018; Castagna *et al.* 2018) or against gas dissolution (Poetes *et al.* 2010), is a crucial problem in the development of such SH coatings. Indeed, the air layer can be pushed inside the microstructure, and the superhydrophobic state breaks down (Moulinet & Bartolo 2007; Reyssat *et al.* 2007), i.e., a wetting transition occurs from a (gas-trapping) Cassie-Baxter to a (completely wetting) Wenzel state, and the surface drag coefficient increases dramatically (Karatay *et al.* 2013). Although substantial efforts have been invested in developing robust SHS (Verho *et al.* 2012; Xiang *et al.* 2017), plastron stability still limits the useful applications of SHS.

To better understand superhydrophobic breakdown, the wetting transition has been extensively studied in quasi-static configurations, such as in evaporating droplet (McHale *et al.* 2005; Jung & Bhushan 2007; Tsai *et al.* 2010; Bussonnière *et al.* 2017), with surfactant additives (Shardt *et al.* 2019; Aldhaleai & Tsai 2022), under different drop volume (Yoshimitsu *et al.* 2002) and pressure (Lafuma & Quéré 2003), or in dynamic situations, e.g., drop impact (Bartolo *et al.* 2006) or under surface vibrations (Bormashenko *et al.* 2007). For immersed SHS, wetting transition was mainly studied under static pressure (Poetes *et al.* 2010; Lv *et al.* 2014). However, in the main application of underwater SHS (drag reduction), pressure fluctuates due to the flow, which can become turbulent (Seo *et al.* 2018).

Acoustic waves have the ability to impose precise pressure over an extensive frequency range. Moreover, sound waves strongly interact with bubbles (e.g., a plastron can be seen as an elongated bubble) in liquid. Therefore, an acoustic method can be a well-suited tool for submerged SHS characterisation. Promising plastron acoustic monitoring was obtained by using longitudinal waves coming from the solid, from beneath the surface, to probe the wetting state by monitoring the back-scattered waves (Saad *et al.* 2012; Dufour *et al.* 2013; Li *et al.* 2014). However, this method requires calibration or precise knowledge of the morphology of the SH coating. Furthermore, elastic acoustic waves are not in contact with the air-water interface and, therefore, prohibit direct interaction with the gas-liquid interface. In (Sudeepthi *et al.* 2020), drop wetting transitions were triggered by surface acoustic waves through indirect interaction, i.e., through drop oscillations. Other authors studied submerged SHS as potential acoustic meta-materials (Tong *et al.* 2020; Feng *et al.* 2019). However, the strong interaction between acoustic waves coming from the liquid phase and a SHS remains unexplored. Such an acoustic method is expected to be versatile since the technique uses only one portable transducer to excite and receive waves, similar to non-destructive testing. The acoustic technique would be hence well suited to characterize SHS in applications or in complex environments (e.g., underwater) whereby classical optical techniques, such as confocal microscopy (Papadopoulos *et al.* 2013) or light interference (Moulinet & Bartolo 2007) which require a microscope and transparent substrate, cannot be used.

In this paper, we propose to fill the gap by exploring experimentally the behavior of immersed superhydrophobic surfaces subjected to short acoustic pulses of varying intensity. Different SHS and flat surfaces are exposed to acoustic pulses using the experimental setup described in 2. At low acoustic amplitude, various surfaces show different acoustic boundary conditions described in Section 3.1. Cavitation behavior is characterized at high amplitude in Section 3.2. The wetting transition is observed at an intermediate intensity and discussed in Section 3.3.

2. Experimental setup

The experimental setup shown in Figure 1 consists of a High Intensity Focused Ultrasound (HIFU) transducer (Sonic Concepts H101, 1.1 MHz) which focuses short acoustic pulses onto




Figure 1: Schematic of the experimental setup. Short acoustic pulses are emitted by a High Intensity Focused Ultrasound transducer and focused upon the tested surface held by a glass coverslip. The dynamic is monitored from the side and from the bottom by two high speed cameras.

an immersed surface with a circular focal area of 3 mm in diameter. The acoustic excitation comprises 3 cycles of 1.1 MHz. To calibrate the pressure, we first map the acoustic field at a constant low amplitude using a needle hydrophone (Onda HNR-0500, bandwidth 0.25-10 MHz) mounted on 3D axis displacement stage and use the open source code solving nonlinear propagation (Khokhlov-Zabolotskaya-Kuznetsov equation) developed by Joshua Soneson (Soneson 2009; Maruvada *et al.* 2015) to fit the experimental results. The hydrophone is then kept at the focal point (for low amplitude) and at the secondary lobe (for high amplitude), and the amplitude is varied. Combining the acoustic mapping, pressure amplitude measurements, and the nonlinear simulation, we finally obtain the calibrated pressure field for a specific supply voltage of the acoustic drive (see Appendix A).

Four surfaces were used in this study to compare different behavior under acoustic excitation: glass, flat PDMS, and two PDMS SH surfaces. The SH and flat PDMS surfaces were first placed on a glass surface and then introduced at the focal point. The superhydrophobic surfaces consist of micro-scale cylindrical pillars of $5.5\ \mu\text{m}$ in diameter (D) and $5\ \mu\text{m}$ in height (H) organized in a square lattice. SHS 1 and 2 have a periodicity P of $14.1\ \mu\text{m}$ and $7.6\ \mu\text{m}$, respectively. Superhydrophobic surfaces were made by pouring liquid PDMS into a Si mold, vacuumed, cured, and finally peeled off as the samples. The PDMS surfaces were 3 mm thick. Once introduced at the focal point, surface dynamics is monitored by two high-speed cameras (Photron AX200 and AX100), while the HIFU transducer records the back scattering sound at low amplitude. A long range microscope is mounted on a camera to record from the side, while the second camera is used with a mirror to image the dynamic from the bottom (see Fig. 1).

3. Results and Discussion

3.1. Initial wetting state

The initial wetting state for the different surfaces is compared in Figure 2 using the bottom view and acoustic reflection at small amplitude. Glass, flat PDMS, and SH1 surfaces appear black from the bottom view, indicating that the light coming from the bottom is not reflected, and hence the solid surfaces are fully wet. The bottom view of the SH2 surface is much brighter, indicating that the bottom light is reflected by air-water interface, and thus an air layer is trapped inside the micro-structure. The stability of the Cassie-Baxter state has been predicted by Bico *et al.* (Bico *et al.* 2002) based on energy analysis. They show that an air




Figure 2: Comparison of the initial wetting state of the different solid surfaces submerged in water. The first row of images shows the bottom view by a high-speed camera, while the second row of data are the back-scattered sound detected by monitoring the voltage of the transducer. For comparison, the acoustic reflection from the glass surface solely (bottom left) is added in grey for the other surfaces.

layer will be stable if the contact angle of the constituting material on flat surface θ_f obeys:

$$\theta_f > \theta_c, \text{ with } \cos \theta_c = \frac{\Phi - 1}{R - \Phi}, \quad (3.1)$$

where $R = 1 + \pi DH/P^2$ is the roughness, and $\Phi = (\pi D^2)/(4P^2)$ is the solid fraction. Our SH1 (SH2) has a roughness $R = 1.43$ ($R = 2.5$) and a solid fraction of $\Phi = 0.12$ ($\Phi = 0.41$), leading to a critical contact angle $\theta_c = 134^\circ$ ($\theta_c = 106^\circ$). The water contact angle on flat PDMS is $\theta_f = 110 - 115^\circ$ (Mata *et al.* 2005). In agreement with the theoretical prediction, the θ_f -value for the flat PDMS is smaller than θ_c for the SH1 surface so water invades the microstructure. For the SH2 surface $\theta_f > \theta_c$, therefore, a stable air layer is trapped between the micropillars, as observed in the experiments.

The back-scattered sound of the different surfaces is then analyzed at a small amplitude. The HIFU transducer voltage averaged over ten pulses is shown in Figure 2. For all surfaces, echoes are detected at $85 \mu s$, corresponding to the time required for an acoustic wave to travel to the focal point and return to the transducer. The reflected pulse has the same shape as the incoming pulse for the glass surface. For the flat PDMS and the SHS 1, the back-scattered pulse is more complex and consists of a first small amplitude reflection followed by a second higher reflection similar to the glass case. More surprisingly, the back-scattered sound from the SHS 2 is only made of a strong pulse with a π -phase change, compared to the incoming pulse.

These observations can be explained using linear acoustics. The pressure reflection coefficient (r) of acoustic plane waves on an interface is given by $r_{i,j} = (Z_j - Z_i)/(Z_i + Z_j)$, with $Z_i = \rho_i c_i$ the acoustic impedance, ρ_i and c_i the density and sound velocity in the media i . The subscript i (j) represents the media supporting the incident (transmitted) pulse. The different interfaces present in our experiments have the following reflection coefficient: $r_{w,g} = 0.8$ for water/glass interface, $r_{w,p} = -0.18$ for water/PDMS, $r_{w,a} = -1$ for water/air and $r_{p,g} = 0.85$ for PDMS/glass (Xu *et al.* 2020). For the water-glass interface, $r_{w,g}$ is positive and close to 1, and the back-scattered pulse is expected to be of high amplitude without phase change as observed in Figure 2. The flat PDMS and SH1 surfaces are held by a glass plate, and the incoming pulse will first encounter the water/PDMS interface leading to a first weak reflection since $r_{w,p}$ is small. A non-negligible part of the pulse is transmitted to the PDMS and then reflected by the PDMS/glass interface, generating the second strong echo since $r_{p,g}$ is high.

Finally, the back-scattered sound coming from the SH2 surface is solely made of a strong

pulse with π -phase change, in agreement with a reflection on a water/air interface as $r_{w,a} = -1$. This confirms the presence of an air layer inside SH2 microstructure as optically observed, demonstrating that acoustics can be of great use to probe plastron stability. The absolute value of the reflection coefficient of the water/air interface is higher than the coefficient of water/glass ($|r_{w,a}| > |r_{w,g}|$). The amplitude of the back-scattered signal from SHS 2 should therefore be higher than the one from the glass surface, but the measured reflections are of similar amplitude (see Figure 2). This discrepancy might be ascribed to the fact that the SH2 interface is not a pure water/air interface but a mixture of water/air and PDMS pillars (41% of the surface is PDMS), which modifies the reflection coefficient.

3.2. Cavitation behavior

The solid surfaces were subjected to high-intensity pulses of different amplitudes to characterize their cavitation behavior. The cavitation is monitored by side-view images [see Figure 3 (b)-(c)] taken during the acoustic excitation when cavitation clouds are visible. The area of such cavitation cloud (A_{cav}) is measured and compared for the different surfaces under various excitation amplitudes in Figure 3 (a). Although the data are scattered, which is expected for cavitation experiments, it can be seen that only a few small cavitation bubbles appear on flat PDMS and on the SHS 1. In contrast, significant cavitation is observed on the glass surface and the SHS 2. The flat glass surface exhibits cavitation at low acoustic excitation, while cavitation cloud appears later for SHS 2.

The ability of surfaces or liquids to cavitate under relatively small pressure excitation, well above the spinodal pressure of water (~ -140 MPa) (Zheng *et al.* 1991), is determined by the presence of micro/nanobubbles trapped in surface defects or impurities, called cavitation nuclei (Harvey *et al.* 1944). Stabilisation of such nuclei on a surface requires a hydrophobic geometrical defect called crevice (Atchley & Prosperetti 1989; Bussonniere *et al.* 2020). When subjected to low enough negative pressure (i.e., cavitation threshold), such nuclei become mechanically unstable, and cavitation bubbles appear.

The different cavitation responses are therefore either due to a difference in nuclei population and/or in local negative pressure. The first nuclei source in the experiments comes from tap water, which contains many impurities and thus a large number of nuclei. However, the same water was used in all experiments, and hence these nuclei could not explain the cavitation differences observed. The second source of nuclei comes from the different solid surfaces. PDMS is naturally hydrophobic, which should favor nuclei trapping compared to hydrophilic glass. However, this soft material is expected to have little, if no, sharp defect (crack-like) due to its polymerization from a liquid form, which can explain that almost no cavitation on flat PDMS was detected (Figure 3). Similarly, SHS 1 in a Wenzel wetting state, although being micro-textured with cylindrical pillars, is not expected to have sharp crevices, which can explain the small cavitation activity observed. Glass, on the other hand, can have small cracks potentially leading to significant cavitation activity as observed on glass.

The other important factor for cavitation is the local negative pressure, which is greatly influenced by the acoustic boundary condition. The acoustic wave reflected by a surface with a factor of r interferes with the incident wave resulting in a local minimum pressure, which can greatly differ from the incident minimum pressure, $P_{\text{min}}^{\text{inc}}$. For example, at the interface between water and a surface j , the minimum pressure is $P_j^{\text{wall}} = (1 + r_{w,j}) P_{\text{min}}^{\text{inc}}$. The minimum pressure is therefore amplified on the glass surface ($P_{\text{glass}}^{\text{wall}} = 1.8 P_{\text{min}}^{\text{inc}}$), reduced on flat PDMS and SHS 1 ($P_{\text{pdms,shs1}}^{\text{wall}} = 0.8 P_{\text{min}}^{\text{inc}}$), or almost cancelled on SHS 2 ($P_{\text{shs2}}^{\text{wall}} \approx 0$). This simplified analysis is in agreement with the experiments where cavitation clouds appear on the surface for glass [Figure 3 (b)], whereas no cavitation is observed upon the surface of SHS 2 (Figure




Figure 3: (a) Area of the cavitation cloud (A_{cav} , captured from the side-view) as a function of the maximum incident acoustic intensity (I_{max}) for the different solid surfaces. Points in (a) represent the area of one experiment, while the solid lines represent the average values. (b)-(c) Side-view images of the cavitation cloud on glass surface [in (b)] and on the superhydrophobic surface 2 [in (c)] appearing for an incident maximum intensity of 3.9 kW/cm^2 .




Figure 4: (a) Incident waveform at the focal plan for different maximum incident intensity (I_{max}). The simulation results (solid lines) using the nonlinear acoustic code (Soneson 2009) are compared to the experimental measurements (cross points) at low intensity. (b) Evolution of the minimum and maximum incident pressure ($P_{min,max}^{inc}$) and of the minimum local pressure ($P_{min}^{position, surface}$) at specific position for a surface with the maximum incident intensity (I_{max}).

3 (c)). Note that the small bubbles in Figure 3 (b) top are actually on the surface, although appearing away from it due to the slight tilt between the camera and the surface.

Interference between the incident and reflected waves also occurs away from the surface. If a continuous excitation was used, a standing wave in the liquid would have been generated. However, here, we use short pulses with only 2 periods with a significant amplitude. Wave interference therefore only occurs in the surface vicinity, in a region of approximately one wavelength (λ). Local minima generated by the transient standing wave depend on the reflection coefficient sign. If $r > 0$, the pressure anti-nodes are located on the surface, at $\lambda/2$ and λ away for the surface. Differently, if $r < 0$ the minimum pressures are located at $\lambda/4$ and $3\lambda/4$ away from the surface. The above analysis may be consistent with the experimental data, which reveals that cavitation cloud appears at $\lambda/4$ and $3\lambda/4$ for the SHS2 experiments. However, with the analysis one would have expected appearance of cavitation at λ and $\lambda/2$ in the experiments with the glass surface and not only on the surface.

To understand this discrepancy for the glass surface, one needs to analyze the high acoustic intensity used in the experiments. Under such strong excitation, the acoustic propagation is nonlinear, and the acoustic waveform departs from a simple cosine function, as shown in Figure 4 (a). The solid lines represent the results from the nonlinear acoustic simulations. The simulation results are in good agreement with the experimental data (crosses) at low values of I_{max} . Note that the measurements at the focal point can only be performed at low

intensity to prevent deterioration of the hydrophone by cavitation. As detailed in the appendix A, the acoustic field at high intensity was calibrated by measuring the pressure at the second pressure lobe (after the focal region). As I_{\max} increases, the waveform become asymmetric, and the maximum incident pressure P_{\max}^{inc} increases faster than the absolute minimum pressure $|P_{\min}^{\text{inc}}|$, as shown in figure 4 (b).

Such asymmetry has important implications in the local minimum generated in the interference region. For $r > 0$, the local minimums located at λ , $\lambda/2$ and on the wall are equal to $P_j^{\lambda} = P_j^{\lambda/2} = P_j^{\text{wall}} = (1+r_{w,j}) P_{\min}^{\text{inc}}$. However, for $r < 0$, the reflected wave is inverted (with a phase change by π), and the local minimum pressures are $P_j^{3\lambda/4} = P_j^{\lambda/4} = P_{\min}^{\text{inc}} - r_{w,j} P_{\max}^{\text{inc}}$. Figure 4 (b) shows the minimum pressures generated by the combination of nonlinear acoustic and the reflection for the different surfaces. As the reflection from SHS2 at low intensity (Figure 2) has the same amplitude as the glass surface, we use $r_{w,\text{shs2}} = -0.8$ to better estimate the reflection. Due to the reflection of the strong maximum incident pressure, minimum pressures in SHS2 experiments reach the lowest level, which explains the biggest cavitation cloud observed. Cavitation with SHS2 appears at $I = 2.5 \text{ kW/cm}^2$, i.e., at $P_{\text{shs2}}^{\lambda/4} \approx -16 \text{ MPa}$, which corresponds to the threshold for cloud cavitation in water. Pressure in the glass experiment only reaches $P_{\text{glass}}^{\text{wall}} \approx -15 \text{ MPa}$ at the maximum intensity. This explains why no clouds are observed in water for the glass cases. Cavitation, in this case, occurs only on the glass interface due to the presence of surface nuclei. It should be noted that the nonlinear waveform reflected with a phase shift by π is unstable and will recover to a sine wave at the transducer, shown by Tanter *et al.* (2001).

3.3. Wetting transition

The stability of the superhydrophobic state is also studied by using the bottom camera and the acoustic reflection at a small amplitude. Figure 5 (a) shows the images from the bottom taken after the exposition of the SHS 2 to different intense acoustic pulses. Note that the surface is moved between each high impulsions experiment, so each trial is performed on a fresh area of the SHS. For intensities smaller than $\approx 0.1 \text{ kW/cm}^2$, the air layer remains unchanged, as shown by the brownish color. Starting at 0.25 kW/cm^2 , a change in color is observed, and clear interference color pattern appears at 0.59 W/cm^2 . These colors arise from the white light interference inside the air layer of the SHS and indicate that the air-layer thickness has been decreased at the focal region due to the acoustic pulse. For $I_{\max} > 1.1 \text{ kW/cm}^2$, a dark disk appears in the center surrounded by interference fringes. The radius of this disk increases with the acoustic intensity, and its evolution with I_{\max} is reported in Figure 5 (c).

This black disk might correspond to a local superhydrophobic breakdown (i.e., wetting transition) since SHS 1, which didn't trapped an air layer, appears black in Figure 2. To verify this, the acoustic reflection signals at low amplitude from the SHS 2 surface before (shown in dashed blue) and after (shown in red) an intense acoustic pulse of 2.5 kW/cm^2 are compared in Figure 5 (b). Before, the reflection corresponds to an air-water reflection as shown in Figure 2. The reflection after the high intensity pulse is drastically changed and is similar to the reflection of SHS 1 of Figure 2. This observation confirms that high intensity pulses trigger a local wetting transition, corresponding to the dark area where water penetrates inside the microstructure. It should be note that this transition occurs at amplitude smaller ($I_{\max} = 1.1 \text{ kW/cm}^2$) than the appearance of cavitation cloud ($I_{\max} = 2.5 \text{ kW/cm}^2$), ruling out a transition driven by cavitation.

The transition from a Cassie-Baxter to a Wenzel wetting state is usually understood by looking at the local force balance of the air-water interface in contact with the microstructure. A small pressure increase in the liquid phase is balanced by a capillary pressure arising from




Figure 5: (a) Bottom view of the SHS 2 after exposition of different high intensity acoustic pulses showing the apparition of interference fringes and a wetted region in black of radius (R_w). (b) Acoustic reflection of the SHS 2 of a small amplitude pulse before (blue) and after (red) the exposition of a high intensity pulse of $I_{\max} = 2.5 \text{ kW/cm}^2$. (c) Evolution of the wetted radius (R_w) observed experimentally as a function of the maximum acoustic intensity (I_{\max}). The solid and dashed lines correspond the wetted radius predicted by the sliding and touch-down models, respectively.

the bending of the interface between pillars (Qu  r   2008). At higher liquid pressure, the interface can either touch the bottom of the SHS (i.e., touch-down scenario) or slide on the pillar when the local contact angle on pillars reaches the advancing one (i.e., sliding scenario) (Moulinet & Bartolo 2007; Reyssat *et al.* 2007). These different scenarios are associated with two critical liquid pressures:

$$p_t^c \approx \frac{2\gamma H}{(\sqrt{2}P - D)^2}, \quad (3.2)$$

for the touch-down, with γ the air-water surface tension, and θ_a the advancing contact angle; for the sliding (Moulinet & Bartolo 2007):

$$p_s^c = \frac{2\Phi}{1 - \Phi} |\cos \theta_a| \frac{2\gamma}{D}. \quad (3.3)$$

Previously, we showed that the oscillating acoustic pressure at the SHS 2 interface almost vanishes due to the acoustic boundary condition, and thus the high oscillating acoustic pressure (at 1.1 MHz) cannot explain the wetting transition. Nonetheless, acoustic waves are known to apply radiation pressure on interfaces (Borgnis 1952) and are commonly used to trap objects in acoustofluidics (Bruus 2012). Such radiation forces arise from a change of media momentum induced by the acoustic scattering or reflection of an interface or an object (Westervelt 1957; Baresch *et al.* 2013). These radiation forces originate from the difference of the time-averaged acoustic energy density, i.e., radiation pressure, across the interface. It is a cumulative process, and these forces hence occur on a longer timescale than the fast-oscillating acoustic pressure. If we assume that the SHS 2 behaves as a pure water-air interface and an incident angle of 90° , the radiation pressure applied on the interface is given

278 by (Borgnis 1952):

$$279 \quad p_{\text{rad}}(r) = \frac{2I(r)}{c}, \quad (3.4)$$

280 with I the incident acoustic intensity, c sound speed in water, and r the radial coordinate on
 281 the surface centered on the focal axis. The acoustic intensity, and thus the radiation pressure,
 282 depends on r due to the HIFU geometry as shown in Figure 6 (b). The wetting transition
 283 would occur if $p_{\text{rad}} > p_{s,t}^c$, and a critical radius r_c can be extracted from the simulated
 284 intensity field whereby $p_{\text{rad}}(r_c) = p_{s,t}^c$. The predictions for r_c using the sliding and touch-
 285 down models presented above are compared with the experimental data in Figure 5 (c) for
 286 $\theta_a = 110^\circ$.

287 This simplified model predicts the beginning of the transition around $I_{\text{max}} = 900 \text{ W/cm}^2$
 288 for the sliding scenario, which is in good agreement with the experimental data. Moreover,
 289 the wetted radius R_w agrees well with the critical radius predicted in the range 1 – 2.5
 290 kW/cm^2 of I_{max} . The good agreement indicates that the wetting transition occurs where the
 291 acoustic beam is more intense and also validates the wetting transition driven by radiation
 292 pressure. It should be noted that the interference pattern starts to appear at a lower intensity
 293 (see Figure 5 (a) for $I_{\text{max}} = 0.59 \text{ kW/cm}^2$). This may suggest that the interface starts to slide
 294 at lower radiation pressure than predicted but does not reach the microstructure bottom. A
 295 more comprehensive analysis involving time dependence, similar to the one done for free
 296 surface in (Issenmann *et al.* 2011), is needed to better understand the interface motion under
 297 radiation pressure. In addition to developing such a complex model, a study of the influence
 298 of pulse duration and a better acoustic calibration would be needed to fully capture the
 299 interface dynamic in the future.

300 For larger intensity, the water penetration area is underestimated by the sliding model.
 301 This deviation coincides with the appearance of an intense cavitation cloud, which can reflect
 302 acoustic wave and also create strong pressure during its collapse. Therefore, the local acoustic
 303 field is expected to greatly differ from the simple combination of an incident and reflected
 304 wave, thereby modifying the radiation pressure on the surface. Note that the local acoustic
 305 field can be inferred from the imprint left on the SH surface. In Figure 5 (a), concentric grey
 306 circles surrounding the wetted area appear and are spaced by $\approx \lambda/4$. However, such circles
 307 cannot be explained by the secondary lobes of the incident beam, spaced by $\approx \lambda$ (see Figure
 308 6 (b)), which tends to support a strong modification of the acoustic field by the cavitation
 309 cloud.

310 4. Conclusions

311 We investigate the acoustic responses of superhydrophobic surfaces subjected to short intense
 312 pulses. Experiments at low amplitude reveal that when a SHS is able to stabilize an air layer
 313 (in a Cassie-Baxter state) the acoustic waves are reflected with a π phase-shift similar to an
 314 air-water interface. In a Wenzel state, a patterned surface behaves as a flat surface of the
 315 same material, and the microstructure has no influence on the acoustic reflection.

316 At high amplitude, intense cavitation is observed for the glass surface and SHS in (Cassie-
 317 Baxter) gas-trapping state, while almost no cavitation is detected for flat PDMS surface and
 318 PDMS SHS in a Wenzel state. This difference is mainly attributed to the acoustic boundary
 319 condition. For hard material, such as glass, the pressure on the solid surface is nearly doubled,
 320 leading to the appearance of a cavitation cloud on the surface. For the flat and wetted patterned
 321 PDMS surfaces (i.e., flat and SHS in Wenzel), the pressure on the surface is slightly lowered
 322 due to the close match in acoustic impedance with water. For SHS in a Cassie-Baxter state,
 323 the interference between the reflected and the incident wave results in a significant negative

pressure away from the surface (at $\lambda/4$ and $3\lambda/4$), where intense cavitation clouds form. Moreover, cavitation, in this case, is amplified by the conversion of the strong high pressure peaks arising from nonlinear propagation into great negative pressure by the reflection on the air layer.

The Wetting transition from Cassie to Wenzel state is observed at moderate intensity before cavitation appearance. The transition is shown to be driven by the acoustic radiation pressure, which overcomes the critical capillary pressure required to let the interface slide into the microstructure. The simplified model proposed well captures the transition and the size of Wenzel area at moderate intensities. For higher intensity, strong interaction with the cavitation cloud is expected to modify the local acoustic field, resulting in a deviation with the proposed model.

Underwater superhydrophobic surfaces are mainly studied in the context of drag reduction. In such an application, pressure on the plastron is governed by the hydrodynamic, and the flow can trigger a wetting transition. In this context, our results at low amplitude can contribute to developing non-destructive acoustic monitoring of the plastron stability. Moreover, the critical breakdown pressure of a superhydrophobic coating could be characterized and measured using acoustic pulses at moderate intensity. For future studies, an accurate measurement of this breakdown pressure would require a better calibration of the acoustic field and more extensive studies on the influence of the pulse duration and excitation frequency.

Acknowledgements. A.B. thanks Professor R. Wunnenburger for fruitful discussions.

Funding. This work was supported by the Collaborative Research and Development (CRD) of the Natural Sciences and Engineering Research Council of Canada (NSERC) and the Canadian Centre for Clean Coal/Carbon and Mineral Processing Technologies (C5MPT). P.A.T. holds a Canada Research Chair (CRC) in Fluids and Interfaces. This research was undertaken, in part, thanks to funding from the CRC Program.

Declaration of interest. The authors report no conflict of interest.

Appendix A. Acoustic calibration

The acoustic field is first mapped at low amplitude using a needle hydrophone mounted on a 3-axis stage. This field is then used to find the parameter of the HIFU transducer (focal length and radius) in the nonlinear simulation (Soneson 2009). The axial distribution, z , the distance from the transducer, is measured along the axisymmetric axis and shown in Figure 6 (a). The simulated field captures well the pressure field in the focal region and peripheral lobes. Nonetheless, a slight deviation is observed for z below 40 mm. The radial distribution shown in Figure 6 (b) is measured in a plane perpendicular to the z -axis at the maximum pressure, i.e., at $z = 62$ mm. The simulation results are in good agreement with the experimental measurements.

At higher amplitude, cavitation occurs in the focal region, and no direct measurement can be performed using the hydrophone (as the intense cavitation can damage the hydrophone). Therefore, the nonlinear simulation is used to obtain the pressure at high intensity. The unknown in the simulation is the pressure impose at the transducer surface (p_{sim}). In the experiment, we impose a voltage at the output of the generator (V_{gen}) which is then amplify and converted into pressure by the HIFU. To calibrate our experiment using the simulation we therefore need to find the relation between p_{sim} and V_{gen} . To find such relation we measured the maximum and minimum pressure ($p_{\text{max}}^{\text{foc}}$ and $p_{\text{min}}^{\text{foc}}$) at low amplitude at $z = 62$ mm (in the focal region) and over a large range of voltage in the secondary lobes ($p_{\text{max}}^{2\text{nd}}$ and $p_{\text{min}}^{2\text{nd}}$) located at $z = 81$ mm. Simulations were then performed for different amplitudes of p_{sim} , and the functions $p_{\text{max}}^{\text{foc}}(p_{\text{sim}})$, $p_{\text{min}}^{\text{foc}}(p_{\text{sim}})$, $p_{\text{max}}^{2\text{nd}}(p_{\text{sim}})$ and $p_{\text{min}}^{2\text{nd}}(p_{\text{sim}})$ were extracted. These functions were inverted to convert the experimental measurement into p_{sim} values. In Figure 6 (c), we show the results of this treatment as a function of V_{gen} . All the experimental points collapse into a single line, which is fitted with a 3rd-order polynomial without a constant term. Note that the curve tends to saturate, which seems to indicate a saturation of the voltage amplifier limited to 200 W (E&I 1020L).




Figure 6: Evolution of the maximum acoustic pressure in the axial (a) and radial (b) direction at low amplitude. The red lines correspond to the prediction of the acoustic simulation using the non-linear code (Soneson 2009), while the blue dots represent the experimental points. (c) Evolution of the input pressure of the simulation (p_{sim}) fitting the different maximum and minimum measurements as a function of the generator voltage (V_{gen}).

REFERENCES

- ALDHALEAI, AHMED & TSAI, PEICHUN AMY 2022 Evaporation dynamics of surfactant-laden droplets on a superhydrophobic surface: Influence of surfactant concentration. *Langmuir* **38** (1), 593–601.
- ATCHLEY, A. A. & PROSPERETTI, A. 1989 The crevice model of bubble nucleation. *The Journal of the Acoustical Society of America* **86** (3), 1065–1084.
- BARESCH, DIEGO, THOMAS, JEAN-LOUIS & MARCHIANO, RÉGIS 2013 Three-dimensional acoustic radiation force on an arbitrarily located elastic sphere. *The Journal of the Acoustical Society of America* **133** (1), 25–36.
- BARTOLO, DENIS, BOUAMRIRENE, FARID, VERNEUIL, EMILIE, BUGUIN, AXEL, SILBERZAN, PASCAL & MOULINET, SÉBASTIEN 2006 Bouncing or sticky droplets: Impalement transitions on superhydrophobic micropatterned surfaces. *EPL (Europhysics Letters)* **74** (2), 299.
- BICO, JOSÉ, THIELE, UWE & QUÉRÉ, DAVID 2002 Wetting of textured surfaces. *Colloids and Surfaces A: Physicochemical and Engineering Aspects* **206** (1-3), 41–46.
- BOBJI, MUSUVATHI S, KUMAR, S VIJAY, ASTHANA, ASHISH & GOVARDHAN, RAGHURAMAN N 2009 Underwater sustainability of the “cassie” state of wetting. *Langmuir* **25** (20), 12120–12126.
- BORGNIS, FE 1952 Acoustic radiation pressure of plane-compressional waves at oblique incidence. *The Journal of the Acoustical Society of America* **24** (5), 468–469.
- BORMASHENKO, EDWARD, POGREB, ROMAN, WHYMAN, GENE & ERLICH, MORDEHAI 2007 Cassie- wenzel wetting transition in vibrating drops deposited on rough surfaces: Is the dynamic cassie- wenzel wetting transition a 2d or 1d affair? *Langmuir* **23** (12), 6501–6503.
- BRUUS, HENRIK 2012 Acoustofluidics 7: The acoustic radiation force on small particles. *Lab on a Chip* **12** (6), 1014–1021.
- BUSSONNIÈRE, ADRIEN, BIGDELI, MASOUD B, CHUEH, DI-YEN, LIU, QINGXIA, CHEN, PEILIN & TSAI, PEICHUN AMY 2017 Universal wetting transition of an evaporating water droplet on hydrophobic micro- and nano-structures. *Soft matter* **13** (5), 978–984.
- BUSSONNIERE, ADRIEN, LIU, QINGXIA & TSAI, PEICHUN AMY 2020 Cavitation nuclei regeneration in a water-particle suspension. *Physical Review Letters* **124** (3), 034501.
- CASTAGNA, MARCO, MAZELLIER, NICOLAS & KOURTA, AZEDDINE 2018 Wake of super-hydrophobic falling spheres: influence of the air layer deformation. *Journal of Fluid Mechanics* **850**, 646–673.
- DUFOUR, RENAUD, SAAD, NADINE, CARLIER, JULIEN, CAMPISTRON, PIERRE, NASSAR, GEORGE, TOUBAL, MALIKA, BOUKHERROUB, RABAH, SENEZ, VINCENT, NONGAILLARD, BERTRAND & THOMY, VINCENT 2013 Acoustic tracking of cassie to wenzel wetting transitions. *Langmuir* **29** (43), 13129–13134.
- FENG, GUANG, LI, FENGPIG, XUE, WEI, SUN, KE, YANG, HUAN, PAN, QIAOFEI & CAO, YU 2019 Laser textured gfrp superhydrophobic surface as an underwater acoustic absorption metasurface. *Applied Surface Science* **463**, 741–746.
- HARVEY, E. N., BARNES, D. K., McELROY, W. D., WHITELEY, A. H., PEASE, D. C. & COOPER, K. W. 1944 Bubble formation in animals. i. physical factors. *Journal of Cellular and Comparative Physiology* **24** (1), 1–22.
- ISSENMAN, BRUNO, WUNENBURGER, RÉGIS, CHRAIBI, HAMZA, GANDIL, MORGANE & DELVILLE, J-P 2011

- Unsteady deformations of a free liquid surface caused by radiation pressure. *Journal of fluid mechanics* **682**, 460–490.
- JUNG, YONG CHAE & BHUSHAN, BHARAT 2007 Wetting transition of water droplets on superhydrophobic patterned surfaces. *Scripta Materialia* **57** (12), 1057–1060.
- KARATAY, ELIF, HAASE, A. SANDER, VISSER, CLAAS WILLEM, SUN, CHAO, LOHSE, DETLEF, TSAI, PEICHUN AMY & LAMMERTINK, ROB G. H. 2013 Control of slippage with tunable bubble mattresses. *PNAS* **110** (21), 8422–8426.
- LAFUMA, AURÉLIE & QUÉRÉ, DAVID 2003 Superhydrophobic states. *Nature materials* **2** (7), 457–460.
- LI, SIZHE, LAMANT, SEBASTIEN, CARLIER, JULIEN, TOUBAL, MALIKA, CAMPISTRON, PIERRE, XU, XIUMEI, VEREECKE, GUY, SENEZ, VINCENT, THOMY, VINCENT & NONGAILLARD, BERTRAND 2014 High-frequency acoustic for nanostructure wetting characterization. *Langmuir* **30** (25), 7601–7608.
- LV, PENGYU, XUE, YAHUI, SHI, YIPENG, LIN, HAO & DUAN, HUILING 2014 Metastable states and wetting transition of submerged superhydrophobic structures. *Physical review letters* **112** (19), 196101.
- MARUVADA, S., LIU, Y., SONESON, J. E., HERMAN, B. A. & HARRIS, G. R. 2015 Comparison between experimental and computational methods for the acoustic and thermal characterization of therapeutic ultrasound fields. *J. Acoust. Soc. Am.* **137** (4), 1704–1713.
- MATA, A., FLEISCHMAN, A. J. & ROY, S. 2005 Characterization of polydimethylsiloxane (pdms) properties for biomedical micro/nanosystems. *Biomed. Microdevices* **7** (4), 281–293.
- McHALE, GLEN, AQIL, SANAA, SHIRTCLIFFE, NJ, NEWTON, MI & ERBIL, H YILDIRIM 2005 Analysis of droplet evaporation on a superhydrophobic surface. *Langmuir* **21** (24), 11053–11060.
- MOULINET, S & BARTOLO, D 2007 Life and death of a fakir droplet: Impalement transitions on superhydrophobic surfaces. *The European Physical Journal E* **24** (3), 251–260.
- PAPADOPOULOS, PERIKLIS, MAMMEN, LENA, DENG, XU, VOLLMER, DORIS & BUTT, HANS-JÜRGEN 2013 How superhydrophobicity breaks down. *Proceedings of the National Academy of Sciences* **110** (9), 3254–3258.
- POETES, ROSA, HOLTZMANN, KATHRIN, FRANZE, KRISTIAN & STEINER, ULLRICH 2010 Metastable underwater superhydrophobicity. *Physical review letters* **105** (16), 166104.
- QUÉRÉ, DAVID 2008 Wetting and roughness. *Annual review of materials research* **38** (1), 71–99.
- REYSSAT, MATHILDE, YEOMANS, JULIA M & QUÉRÉ, DAVID 2007 Impalement of fakir drops. *EPL (Europhysics Letters)* **81** (2), 26006.
- ROTHSTEIN, JONATHAN P 2010 Slip on superhydrophobic surfaces. *Annual review of fluid mechanics* **42**, 89–109.
- SAAD, N, DUFOUR, R, CAMPISTRON, PIERRE, NASSAR, GEORGES, CARLIER, JULIEN, HARNOIS, M, MERHEB, B, BOUKHERROUB, R, SENEZ, V, GAO, J & OTHERS 2012 Characterization of the state of a droplet on a micro-textured silicon wafer using ultrasound. *Journal of Applied Physics* **112** (10), 104908.
- SEO, JONGMIN, GARCÍA-MAYORAL, RICARDO & MANI, ALI 2018 Turbulent flows over superhydrophobic surfaces: flow-induced capillary waves, and robustness of air–water interfaces. *Journal of Fluid Mechanics* **835**, 45–85.
- SHARDT, NADIA, BIGDELI, MASOUD BOZORG, ELLIOTT, JANET A. W. & TSAI, PEICHUN AMY 2019 How surfactants affect droplet wetting on hydrophobic microstructures. *J. Phys. Chem. Letts.* **10** (23), 7510–7515.
- SONESON, J. E 2009 A user-friendly software package for hifu simulation. In *AIP Conference Proceedings*, vol. 1113, pp. 165–169. American Institute of Physics.
- SUDEEPTHI, AREMANDA, YEO, LESLIE & SEN, AK 2020 Cassie–wenzel wetting transition on nanostructured superhydrophobic surfaces induced by surface acoustic waves. *Applied Physics Letters* **116** (9), 093704.
- TANTER, MICKAËL, THOMAS, JEAN-LOUIS, COULOUVRAT, FRANÇOIS & FINK, MATHIAS 2001 Breaking of time reversal invariance in nonlinear acoustics. *Physical review E* **64** (1), 016602.
- TONG, LEI, XIONG, ZHU, SHEN, YA-XI, PENG, YU-GUI, HUANG, XIN-YU, YE, LEI, TANG, MING, CAI, FEI-YAN, ZHENG, HAI-RONG, XU, JIAN-BIN & OTHERS 2020 An acoustic meta-skin insulator. *Advanced Materials* **32** (37), 2002251.
- TSAI, PEICHUN, LAMMERTINK, ROB G. H., WESSLING, MATTHIAS & LOHSE, DETLEF 2010 Evaporation-triggered wetting transition for water droplets upon hydrophobic microstructures. *Phys. Rev. Lett.* **104**, 116102.
- VERHO, TUUKKA, KORHONEN, JUUSO T, SAINIEMI, LAURI, JOKINEN, VILLE, BOWER, CHRIS, FRANZE, KRISTIAN, FRANSSILA, SAMI, ANDREW, PIERS, IKKALA, OLLI & RAS, ROBIN HA 2012 Reversible

- switching between superhydrophobic states on a hierarchically structured surface. *Proceedings of the National Academy of Sciences* **109** (26), 10210–10213.
- WESTERVELT, PETER J 1957 Acoustic radiation pressure. *The Journal of the Acoustical Society of America* **29** (1), 26–29.
- XIANG, YAOLEI, HUANG, SHENGLIN, LV, PENGYU, XUE, YAHUI, SU, QIANG & DUAN, HUILING 2017 Ultimate stable underwater superhydrophobic state. *Physical review letters* **119** (13), 134501.
- XU, GUANGYAO, NI, ZHENGYANG, CHEN, XIZHOU, TU, JUAN, GUO, XIASHENG, BRUUS, HENRIK & ZHANG, DONG 2020 Acoustic characterization of polydimethylsiloxane for microscale acoustofluidics. *Physical Review Applied* **13** (5), 054069.
- YOSHIMITSU, ZEN, NAKAJIMA, AKIRA, WATANABE, TOSHIYA & HASHIMOTO, KAZUHITO 2002 Effects of surface structure on the hydrophobicity and sliding behavior of water droplets. *Langmuir* **18** (15), 5818–5822.
- ZHENG, Q., DURBEN, D. J., WOLF, G. H. & ANGELL, C. A. 1991 Liquids at large negative pressures: water at the homogeneous nucleation limit. *Science* **254** (5033), 829–832.