



From Understanding the Population Dynamics of the NSGA-II to the First Proven Lower Bounds

Benjamin Doerr, Zhongdi Qu

► To cite this version:

Benjamin Doerr, Zhongdi Qu. From Understanding the Population Dynamics of the NSGA-II to the First Proven Lower Bounds. 37th AAAI Conference on Artificial Intelligence (AAAI 2023), Feb 2023, Washington, DC, United States. hal-04024099

HAL Id: hal-04024099

<https://hal.science/hal-04024099>

Submitted on 10 Mar 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

From Understanding the Population Dynamics of the NSGA-II to the First Proven Lower Bounds

Benjamin Doerr

Zhongdi Qu

Abstract

Due to the more complicated population dynamics of the NSGA-II, none of the existing runtime guarantees for this algorithm is accompanied by a non-trivial lower bound. Via a first mathematical understanding of the population dynamics of the NSGA-II, that is, by estimating the expected number of individuals having a certain objective value, we prove that the NSGA-II with suitable population size needs $\Omega(Nn \log n)$ function evaluations to find the Pareto front of the ONEMINMAX problem and $\Omega(Nn^k)$ evaluations on the ONEJUMPZEROJUMP problem with jump size k . These bounds are asymptotically tight (that is, they match previously shown upper bounds) and show that the NSGA-II here does not even in terms of the parallel runtime (number of iterations) profit from larger population sizes. For the ONEJUMPZEROJUMP problem and when the same sorting is used for the computation of the crowding distance contributions of the two objectives, we even obtain a runtime estimate that is tight including the leading constant.

1 Introduction

Many real-world problems have several, often conflicting objectives. For such *multi-objective* optimization problems, it is hard to compute a single solution. Instead, one usually computes a set of incomparable, interesting solutions from which a decision maker can select the most preferable one. Due to their population-based nature, evolutionary algorithms (EAs) are well suited for such problems, and in fact, are intensively used in multi-objective optimization.

The most accepted multi-objective evolutionary algorithm (MOEA) in practice [ZQL⁺11] is the *non-dominated sorting genetic algorithm II* (NSGA-II) proposed in [DPAM02]. It uses a fixed population size N , generates N new solutions per iteration, and selects the next population according to the non-dominated sorting of the combined parent and offspring population and the crowding distance. Due to this complex structure, for a long time no mathematical runtime analyses existed for this algorithm. However, in 2022 four such works appeared, all greatly enhancing our understanding of how this algorithm works, but also detecting weaknesses and proposing promising remedies [ZLD22, ZD22, BQ22, DQ22].

Interestingly, and different from the previous runtime analyses of other MOEAs, none of these works proved a non-trivial lower bound on the runtime. Such bounds are important since only by comparing upper and lower bounds for different algorithms can

one declare one algorithm superior to another. Such bounds are also necessary to have tight runtime estimates, from which information about optimal parameter values can be obtained.

The lack of lower bounds for the NSGA-II, naturally, is caused by the more complicated population dynamics of this complex algorithm. While for algorithms like the SEMO or global SEMO predominantly analyzed in MOEA theory, it follows right from the definition of the algorithm that there can be at most one individual per objective value, such a structural information does not exist for the NSGA-II.

In this work, we gain a first deeper understanding of the population dynamics of the NSGA-II (more precisely, the mutation-based version regarded in almost all previous runtime results for the NSGA-II). For the optimization of the ONEMINMAX and the ONEJUMPZEROJUMP benchmark, we prove that also for relatively large population sizes, only a constant number of individuals exists on the outer positions of the Pareto front. This information allows us to prove upper bounds on the speed with which the Pareto front is explored, and finally yields lower bounds on the runtime of the NSGA-II on these two benchmarks.

More specifically, we prove the following lower bound for the ONEJUMPZEROJUMP benchmark (we do not discuss here in detail the result for ONEMINMAX and refer instead to Theorem 16). Let N denote the population size of the NSGA-II, n denote the problem size (length of the bit-string encoding), and k the gap parameter of the ONEJUMPZEROJUMP problem. If N is at least 4 times the size $n - 2k + 3$ of the Pareto front and $N = o(n^2/k^2)$, then the time to compute the Pareto front of the ONEJUMPZEROJUMP problem is at least $(\frac{3(e-1)}{8} - o(1))Nn^k$ fitness evaluations or, equivalently, $(\frac{3(e-1)}{8} - o(1))n^k$ iterations. This result shows that the upper bound of $O(Nn^k)$ fitness evaluations or $O(n^k)$ iterations proven in [DQ22] is asymptotically tight for broad ranges of the parameters. In particular, this shows that there is no advantage in using a population size larger than the smallest admissible one, not even when taking the number of iterations as the performance measure. This is very different from the single-objective world, where, for example, the runtime of the $(1 + \lambda)$ EA on the single-objective JUMP problem with jump size k is easily seen to be $\Omega(n^k/\lambda)$ and $O(n^k/\lambda + n \log n)$ iterations, hence for $\lambda = o(n^{k-1}/\log(n))$ the number of iterations reduces with growing value of λ and the number of fitness evaluations does not change (when ignoring lower-order terms). This comparison suggests that the choice of the population size might be more critical for the NSGA-II than for single-objective EAs.

For the variant of the NSGA-II which uses the same sorting to compute the crowding distance contribution of both objectives (which is a natural choice for two objectives), we can even determine the runtime precise apart from lower order terms. To this aim, we also exploit our new understanding of the population dynamics to prove a tighter upper bound on the runtime. We shall not exploit this further in this work, but we note that such tight analyses are the prerequisite for optimizing parameters, here for example the mutation rate. To the best of our knowledge, this is only the second runtime analysis of a MOEA that determines the leading constant of the runtime (the other one being the analysis of the synthetic GSEMO algorithm on the ONEJUMPZEROJUMP benchmark).

Overall, this work constitutes a first step towards understanding the population dynamics of the NSGA-II. We exploit this to prove the first asymptotically tight lower bounds. In a non-trivial special case, we even determine a runtime precise apart from

lower-order terms. These results already give some information on the optimal parameter values, and we are optimistic that our methods can lead to more insights about the right parameter choices of the NSGA-II.

2 Previous Works

For a general introduction to multi-objective optimization via evolutionary algorithms, including the most prominent algorithm NSGA-II (47000 citations on Google scholar), we refer to [ZQL⁺11]. This work is concerned with the mathematical runtime analysis of a MOEA, which is a subarea of the broader research area of runtime analyses for randomized search heuristics [AD11].

The first runtime analyses of MOEAs date back to the early 2000s [LTZ⁺02, Gie03, Thi03] and regarded the artificial SEMO and GSEMO algorithms, which are still the most regarded algorithms in MOEA theory (see, e.g., [BQT18, QYT⁺19, QLZ22] for some recent works). Some time later, the first analyses of the more realistic MOEAs SIBEA [BFN08, NSN15, DGN16] and the MOEA/D [LZZZ16, HZCH19, HZ20, HZLL21] followed. Very recently, the first runtime analysis of the NSGA-II appeared [ZLD22], which was quickly followed up by further runtime analyses of this algorithm.

In [ZLD22], it was proven that the NSGA-II with population size N can efficiently optimize the classic ONEMINMAX and LOTZ benchmarks if N is at least four times the size of the Pareto front. A population size equal to the size of the Pareto front does not suffice. In this case, the NSGA-II loses desired solutions often enough so that the NSGA-II covers only a constant fraction of the Pareto front for at least an exponential time. However, with smaller population sizes, the NSGA-II can still compute good approximations to the Pareto front, as proven in [ZD22] again for the ONEMINMAX benchmark. The first runtime analysis on a benchmark with multimodal objectives [DQ22] showed that the NSGA-II, again with population size N at least four times the size of the Pareto front, computes the Pareto front of the ONEJUMPZEROJUMP benchmark with jump parameter $k \in [2..n/4]$ in expected time at most $O(Nn^k)$. These three works regard a version of the NSGA-II without crossover. In [BQ22], besides other results, the original NSGA-II with crossover is regarded. However, no better runtime guarantees are proven for this algorithm.

For none of the runtime guarantees proven in these works, a matching (or at least non-trivial) lower bound was shown. The apparent reason, spelled out explicitly in the conclusion of [DQ22], is the lack of understanding of the population dynamics for this algorithm. We note that this problem is very present even for the simpler SEMO/GSEMO algorithm despite the fact that here the population is much more restricted. In particular, the strict selection mechanism of these algorithms ensures that for each objective value there is at most one individual in the population. Nevertheless, also a decent number of runtime results for these algorithms do not have a matching lower bound. For the SEMO algorithm, which uses one-bit mutation, a lower bound matching the $O(n^2 \log n)$ upper bound on ONEMINMAX of [GL10] was shown ten years later in [OGNS20]. For the GSEMO, using bit-wise mutation instead, no lower bound is known for the ONEMINMAX benchmark. Similarly, for the LOTZ benchmark a tight $\Theta(n^3)$ runtime of the SEMO was proven in [LTZ⁺02] already. The same upper bound was proven in that work for

the GSEMO, but the only lower bound [DKV13] for this problem is valid only for an unrealistically small mutation rate. Only for the ONEJUMPZEROJUMP benchmark, a tight bound of $\Theta(n^k)$ was proven also for the GSEMO [DZ21], clearly profiting from the fact that the population can contain at most one individual on the local optimum of the objectives.

3 Preliminaries

3.1 The NSGA-II Algorithm

In the interest of brevity, we only give a brief overview of the algorithm here and refer to [DPAM02] for a more detailed description of the general algorithm and to [ZLD22] for more details on the particular version of the NSGA-II we regard.

The NSGA-II uses two metrics, rank and crowding distance, to completely order any population. The ranks are defined recursively based on the dominance relation. All non-dominated individuals have rank 1. Then, given that the individuals of ranks $1, \dots, k$ are defined, the individuals of rank $k + 1$ are those not dominated except by individuals of rank k or smaller. This defines a partition of the population into sets F_1, F_2, \dots such that F_i contains all individuals with rank i . Clearly, individuals with lower ranks are preferred. The crowding distance, denoted by $\text{cDis}(x)$ for an individual x , is used to compare individuals of the same rank. To compute the crowding distances of individuals of rank i with respect to a given objective function f_j , we first sort the individuals in ascending order according to their f_j objective values. The first and last individuals in the sorted list have infinite crowding distance. For the other individuals, their crowding distance is the difference between the objective values of its left and right neighbors in the sorted list, normalized by the difference of the minimum and maximum values. The final crowding distance of an individual is the sum of its crowding distances with respect to each objective function. Among individuals of the same rank, the ones with higher crowding distances are preferred.

The algorithm starts with a random initialization of a parent population of size N . In each iteration, N children are generated from the parent population via a variation operator, and N best individuals among the combined parent and children population survive to the next generation based on their ranks and, as a tie-breaker, the crowding distance. At each iteration, the critical rank i^* is the rank such that if we take all individuals of ranks smaller than i^* , the total number of individuals will be less than or equal to N , but if we also take all individuals of rank i^* , the total number of individuals will be more than N . Thus, all individuals of rank smaller than i^* survive to the next generation, and for individuals of rank i^* , we take the individuals with the highest crowding distance, breaking ties randomly, so that in total exactly N individuals are kept. In practice, the algorithm is run until some stopping criterion is met. In our mathematical analysis, we are interested in how long it takes until the full Pareto front is covered by the population if the algorithm is not stopped earlier. For that reason, we do not specify a termination criterion.

In our analysis, for simplicity we assume that in each iteration every parent produces one child through bit-wise mutation, i.e., mutating each bit independently with probability $\frac{1}{n}$. Our analysis also holds for uniform selection, where N times a parent is selected

independently at random, since also here each individual is selected as parent once in expectation, and our proofs only rely on the expected number of times a parent is selected. When selecting parents via binary tournaments the expected number of times a parent is selected is at most two (which is the expected number of times it participates in a tournament). This estimate would change the population dynamics by constant factors. For that reason, we are optimistic that our methods apply also to this type of selection, but we do not discuss this question in more detail.

For any generation t of a run of the algorithm, we use P_t to denote the parent population and R_t to denote the combined parent and offspring population.

3.2 The OneJumpZeroJump Benchmark

Let $n \in \mathbb{N}$ and $k = \lfloor 2..n/4 \rfloor$. The function $\text{ONEJUMPZEROJUMP}_{n,k} = (f_1, f_2) : \{0, 1\}^n \rightarrow \mathbb{R}^2$, proposed by [DZ21], is defined by

$$f_1(x) = \begin{cases} k + |x|_1, & \text{if } |x|_1 \leq n - k \text{ or } x = 1^n, \\ n - |x|_1, & \text{else;} \end{cases}$$

$$f_2(x) = \begin{cases} k + |x|_0, & \text{if } |x|_0 \leq n - k \text{ or } x = 0^n, \\ n - |x|_0, & \text{else,} \end{cases}$$

where $|x|_1$ denotes the number of bits of x that are 1 and $|x|_0$ denotes the number of bits of x that are 0. The aim is to maximize both f_1 and f_2 , two multimodal objectives. The first objective is the classical $\text{JUMP}_{n,k}$ function. It has a valley of low fitness around its optimum, which can be crossed only by flipping the k correct bits, if no solutions of lower fitness are accepted. The second objective is isomorphic to the first, with the roles of zeroes and ones exchanged.

According to Theorem 2 of [DZ21], the Pareto set of this benchmark is $S^* = \{x \in \{0, 1\}^n \mid |x|_1 = [k..n - k] \cup \{0, n\}\}$, and the Pareto front $F^* = f(S^*)$ is $\{(a, 2k + n - a) \mid a \in [2k..n] \cup \{k, n + k\}\}$, making the size of the front $n - 2k + 3$. We define the inner part of the Pareto set by $S_I^* = \{x \mid |x|_1 \in [k..n - k]\}$, and the inner part of the Pareto front by $F_I^* = f(S_I^*) = \{(a, 2k + n - a) \mid a \in [2k..n]\}$. [DQ22] showed that when using a population of size $N \geq 4(n - 2k + 3)$ to optimize this benchmark, the NSGA-II algorithm never loses a Pareto-optimal solution once found. Moreover, $O(n^k)$ iterations are needed in expectation.

3.3 The OneMinMax Benchmark

Let $n \in \mathbb{N}$. The function $\text{ONEMINMAX} = (f_1, f_2) : \{0, 1\}^n \rightarrow \mathbb{R}$, proposed by [GL10], is defined by

$$f(x) = (f_1(x), f_2(x)) = \left(n - \sum_i^n x_i, \sum_i^n x_i \right).$$

The aim is to maximize both objectives.

For this benchmark, any solution is Pareto-optimal and the Pareto front $F^* = \{(0, n), (1, n - 1), \dots, (n, 0)\}$. Hence $|F^*| = n + 1$. [ZLD22] showed that when using a population of size $N \geq 4(n + 1)$ to optimize the benchmark, the NSGA-II algorithm

never loses a Pareto-optimal solution once found. Moreover, in expectation $O(n \log n)$ iterations are needed.

4 Lower Bound on the Runtime of the NSGA-II on OneJumpZeroJump

In this section, we give a lower bound on the runtime of the NSGA-II algorithm on the ONEJUMPZEROJUMP benchmark. We use $X_{P_t}^i$ to denote the number of individuals with $n - k - i$ 1-bits in P_t and $X_{R_t}^i$ to denote that in R_t .

We first show that with probability arbitrarily close to 1, we have that $P_t \subseteq S^*$ for any t so that the analyses that follow do not need to consider gap individuals (those with between 1 and $k - 1$ zeroes or ones) as parents.

Lemma 1. *Consider the NSGA-II algorithm optimizing the ONEJUMPZEROJUMP $_{n,k}$ benchmark for $2 \leq k \leq \frac{n}{4}$ with population size $N = c(n - 2k + 3)$ for $c = o(n)$. The probability that $P_0 \subseteq S_I^*$ is $1 - o(1)$. Moreover, if $P_0 \subseteq S_I^*$, then for any generation t , we have $P_t \subseteq S^*$.*

Proof. For a randomly initialized individual in P_0 , we have $\mathbb{E}[|x|_1] = \frac{n}{2}$. Since $k \leq \frac{n}{4}$, by the additive Chernoff bound, with probability at most $2e^{-\frac{2}{n}(\frac{n}{4})^2} = 2e^{-\frac{n}{8}}$, the initial individual x has $|x|_1 < k$ or $|x|_1 > n - k$. Then by the union bound, $P_0 \subseteq S_I^*$ with probability at least $1 - 2Ne^{-\frac{n}{8}}$, which is $1 - o(1)$ since $c = o(n)$.

Consider a run of the algorithm where $P_0 \subseteq S_I^*$. We show by induction that $P_t \subseteq S^*$. The base case is obviously $P_0 \subseteq S_I^* \subseteq S^*$. Suppose $P_t \subseteq S^*$ by the induction hypothesis. Since any individual in S^* dominates any individual not in S^* , the rank-1 individuals in R_t are exactly those in S^* . Since there are at least $|P_t| = N$ individuals in S^* in R_t , no individuals not in S^* can survive. Therefore $P_{t+1} \subseteq S^*$. \square

Now we give an upper bound on the probability for any individual to obtain more 1-bits through bit-wise mutation.

Lemma 2. *Let $n, u, v \in \mathbb{N}$ with $n \geq 2$, $u, v \geq 1$, and $u + v \leq n$. Suppose $x \in \{0, 1\}^n$ and $|x|_1 \leq v$. Denote the result of applying bit-wise mutation to x by x' . Then*

$$\Pr[|x'|_1 = u + v] \leq \left(\frac{n - v}{n}\right)^u.$$

Proof. Suppose an individual y has v bits of 1 and the result of applying bit-wise mutation to y is y' . Then $\Pr[|y'|_1 = u + v] \leq \binom{n-v}{u} \left(\frac{1}{n}\right)^u \leq \left(\frac{n-v}{n}\right)^u$ since u of the $n - v$ 0-bits of y have to be flipped. Therefore, to prove the claim, we show that $\Pr[|x'|_1 = u + v] \leq \Pr[|y'|_1 = u + v]$.

The case for $|x|_1 = |y|_1$ is obvious. Then suppose $|x|_1 = v - 1$. We have $\Pr[|y'|_1 = u + v] =$

$$\sum_{i=u}^{\min\{u+v, n-v\}} \binom{n-v}{i} \binom{v}{i-u} \left(\frac{1}{n}\right)^{2i-u} \left(1 - \frac{1}{n}\right)^{n-2i+u} \quad (1)$$

and $\Pr[|x'|_1 = u + v] =$

$$\sum_{i=u}^{\min\{u+v-1, n-v\}} \left(\binom{n-v+1}{i+1} \binom{v-1}{i-u} \left(\frac{1}{n} \right)^{2i-u+1} \left(1 - \frac{1}{n} \right)^{n-2i+u-1} \right) \quad (2)$$

Dividing the summands of equation (1) by those of (2) one by one, we have the quotient $\frac{\binom{n-v}{i} \binom{v}{i-u} \left(\frac{1}{n} \right)^{2i-u} \left(1 - \frac{1}{n} \right)^{n-2i+u}}{\binom{n-v+1}{i+1} \binom{v-1}{i-u} \left(\frac{1}{n} \right)^{2i-u+1} \left(1 - \frac{1}{n} \right)^{n-2i+u-1}} = \frac{v(i+1)(n-1)}{(v-i+u)(n-v+1)}$, which increases in i . So the quotient is minimized when $i = u$, making it $\frac{(u+1)(n-1)}{n-v+1}$, which in turn is minimized when $v = u = 1$, making it $\frac{2(n-1)}{n} \geq 1$ for $n \geq 2$. Since the summands in equations (1) and (2) both start at $i = u$ and there are at least as many summands in (1) as in (2), we have $\Pr[|x'|_1 = u + v] \leq \Pr[|y'|_1 = u + v]$. The cases for $|x|_1 < u - 1$ follow by induction based on the case for $|x|_1 = u - 1$. \square

Corollary 3. *Let $n \in \mathbb{N}$ with $n \geq 2$ and let $v \in [1..n]$. Suppose $x \in \{0, 1\}^n$ and $|x|_1 \leq v$. Denote the result of applying bit-wise mutation to x by x' . Then $\Pr[|x'|_1 = v \wedge x' \neq x] \leq \frac{n-v+1}{n}$.*

Proof. Consider the case where $|x|_1 = v$. Since $x' \neq x$, at least one of the $n - v$ 0-bits of x has to be flipped, and the probability that happens is at most $\frac{n-v}{n} < \frac{n-v+1}{n}$.

Consider the case where $|x|_1 \leq v - 1$. By Lemma 2, $\Pr[|x'|_1 = v] \leq \frac{n-v+1}{n}$. \square

Since we already know from [DQ22] that, for any objective value on the Pareto front, there are at most 4 individuals with that objective value and positive crowding distance, and they all survive to the generation that follows, to further understand the population dynamics on the front, it is crucial to analyze what happens to the individuals with zero crowding distance. In the following lemma, we show that their survival probability is less than $\frac{1}{2} + o(1)$.

Lemma 4. *Consider the NSGA-II algorithm optimizing the ONEJUMPZEROJUMP $_{n,k}$ benchmark with the population size $N = c(n - 2k + 3)$ for some $c \geq 4$ such that $ck^2 = o(n)$. Consider a generation t of a run of the algorithm where $P_0 \subseteq S_I^*$. Suppose $\mathbb{E}[X_{P_t}^0] = O(ck)$ and $\mathbb{E}[X_{P_t}^{n-2k}] = O(ck)$. For a rank-1 individual $x \in R_t$ that has zero crowding distance, the probability that $x \in P_{t+1}$ is less than $\frac{1}{2} + o(1)$.*

Proof. Let $F_{>1}$ denote the individuals in R_t with ranks greater than 1. Since $P_0 \subseteq S_I^*$, by Lemma 1, $P_t \subseteq S^*$. Then all the individuals in $F_{>1}$ are created through mutation of individuals in P_t . By Lemma 2, for an individual with less than $n - k$ bits of 1 to create an individual with more than $n - k$ bits of 1, the probability is at most $(\frac{k+1}{n})^2$, and for an individual with $n - k$ bits of 1 to create an individual with more than $n - k$ bits of 1, the probability is at most $\frac{k}{n}$. Symmetrically, for an individual with less than $n - k$ bits of 0 to create an individual with more than $n - k$ bits of 0, the probability is at most $(\frac{k+1}{n})^2$, and for an individual with $n - k$ bits of 0 to create an individual with more than $n - k$ bits of 0, the probability is at most $\frac{k}{n}$. Therefore $\mathbb{E}[|F_{>1}|] \leq (\frac{k+1}{n})^2 c(n - 2k + 3) + \frac{k}{n} \mathbb{E}[X_{P_t}^0] + \frac{k}{n} \mathbb{E}[X_{P_t}^{n-2k}] = o(1)$ for $ck^2 = o(n)$, $\mathbb{E}[X_{P_t}^0] = O(ck)$ and $\mathbb{E}[X_{P_t}^{n-2k}] = O(ck)$. By Markov's inequality, $\Pr(|F_{>1}| \geq 1) \leq \frac{\mathbb{E}[|F_{>1}|]}{1} = o(1)$.

Let F_1^* the rank-1 individuals in R_t with positive crowding distances. So $|R_t| = 2N$ and there are $2N - |F_1^*| - |F_{>1}|$ individuals in R_t with rank 1 and zero crowding distance. Since $N = c(n - 2k + 3)$, for some $c \geq 4$, by Lemma 1 of [DQ22], all individuals in F_1^* will survive. So among the rank-1 individuals with zero crowding distance, $N - |F_1^*|$ survive to the next generation if $|F_1^*| \leq N$. Hence the probability that a rank-1 individual x with zero crowding distance survives is

$$\frac{N - |F_1^*|}{2N - |F_1^*|} \Pr[|F_{>1}| = 0] + \Pr[x \text{ survives} | |F_{>1}| \geq 1] \Pr[|F_{>1}| \geq 1].$$

Since $\Pr[|F_{>1}| = 0] \leq 1$ and $\Pr[x \text{ survives} | |F_{>1}| \geq 1] \leq 1$, we have that the probability that x survives is at most $\frac{1}{2} + o(1)$. \square

Corollary 5. *Consider the NSGA-II algorithm optimizing the ONEJUMPZEROJUMP $_{n,k}$ benchmark with the population size $N = c(n - 2k + 3)$ for some $c \geq 4$ such that $ck^2 = o(n)$. Consider a generation t of a run of the algorithm where $P_0 \subseteq S_I^*$. Suppose $\mathbb{E}[X_{P_t}^0] = O(ck)$ and $\mathbb{E}[X_{P_t}^{n-2k}] = O(ck)$. Then for any $i \in [0..n-2k]$, we have $\mathbb{E}[X_{P_{t+1}}^i] \leq (\frac{1}{2} + o(1))\mathbb{E}[X_{R_t}^i] + 2$.*

Proof. Among the individuals with i 1-bits in R_t , let $X_{>0}$ denote the number of individuals with positive crowding distance, $X_{=0}$ denote the number of individuals with zero crowding distance, and $X_{=0}^*$ denote the number of individuals with zero crowding distance that survive to the next generation. Then $\mathbb{E}[X_{P_{t+1}}^i] \leq \mathbb{E}[X_{>0}] + \mathbb{E}[X_{=0}^*]$. By Lemma 4, $\mathbb{E}[X_{=0}^*] \leq (\frac{1}{2} + o(1))\mathbb{E}[X_{=0}]$, so

$$\begin{aligned} \mathbb{E}[X_{P_{t+1}}^i] &\leq \mathbb{E}[X_{>0}] + (\frac{1}{2} + o(1))\mathbb{E}[X_{=0}] \\ &= (\frac{1}{2} + o(1))\mathbb{E}[X_{R_t}^i] + (\frac{1}{2} - o(1))\mathbb{E}[X_{>0}]. \end{aligned}$$

By Lemma 1 of [DQ22], $\mathbb{E}[X_{>0}] \leq 4$, so $\mathbb{E}[X_{P_{t+1}}^i] \leq (\frac{1}{2} + o(1))\mathbb{E}[X_{R_t}^i] + 2$. \square

Now, we can start to estimate $\mathbb{E}[X_{P_t}^i]$ for $i \in [0..n-2k]$.

Lemma 6. *Consider the NSGA-II algorithm optimizing the ONEJUMPZEROJUMP $_{n,k}$ benchmark with the population size $N = c(n - 2k + 3)$ for some $c \geq 4$ such that $ck^2 = o(n)$. Suppose $P_0 \subseteq S_I^*$ and $i \in [0..n-2k]$. Then if $1^n \notin P_t$, we have $\mathbb{E}[X_{P_t}^i] \leq c_i$ for $c_i = \frac{e}{e-1}(c(k+i+1) + \sum_{j=0}^{i-1} c_j + 4) + o(ck)$. Similarly, if $0^n \notin P_t$, we have $\mathbb{E}[X_{P_t}^{n-2k-i}] \leq c_{n-2k-i}$ for $c_{n-2k-i} = \frac{e}{e-1}(c(k+i+1) + \sum_{j=0}^{i-1} c_{n-2k-j} + 4) + o(ck)$.*

Proof. We prove the result for the case where the all-ones string has not been found since the other case is symmetrical.

Let Y^i denote the number of individuals with $n - k - i$ 1-bits in P_t for which no bits are flipped during mutation, and let Z^i denote the number of individuals in P_t for which a positive number of bits are flipped and the resulting children have $n - k - i$ 1-bits. We first prove by induction that $\mathbb{E}[X_{P_t}^0] \leq c_0$ for $c_0 = \frac{e}{e-1}(c(k+1) + 4) + o(ck) = O(ck)$.

For the base case, consider the random initialization of P_0 . The probability that exactly k among n bits are 0 is less than the probability that at most $k < \frac{n}{4}$ bits are 0, which is at most $e^{-\frac{n}{8}}$. Hence, $\mathbb{E}[X_{P_0}^0] < c(n - 2k + 3)e^{-\frac{n}{8}} < cne^{-\frac{n}{8}} < 3c < c_0$.

For the induction, assume by the induction hypothesis that $\mathbb{E}[X_{P_t}^0] \leq c_0$ and we will show that $\mathbb{E}[X_{P_{t+1}}^0] \leq c_0$. Clearly, $\mathbb{E}[X_{R_t}^0] = \mathbb{E}[X_{P_t}^0] + \mathbb{E}[Y^0] + \mathbb{E}[Z^0]$. By the induction hypothesis $\mathbb{E}[X_{P_t}^0] \leq c_0$. By definition, $\mathbb{E}[Y^0] = \mathbb{E}[(1 - \frac{1}{n})^n X_{P_t}^0] \leq \frac{1}{e} \mathbb{E}[X_{P_t}^0] = \frac{c_0}{e}$. Since $1^n \notin P_t$ and $P_0 \subseteq S_I^*$, by Lemma 1, there is no individual with more than $n - k$ 1-bits. Then by Corollary 3, for any individual to have a positive number of bits flipped and produce an individual with $n - k$ 1-bits, the probability is at most $\frac{k+1}{n}$. So $\mathbb{E}[Z^0] \leq c(n - 2k + 3) \frac{k+1}{n} \leq c(k+1)$. Together, $\mathbb{E}[X_{R_t}^0] \leq (1 + \frac{1}{e})c_0 + c(k+1)$. Then by Corollary 5, $\mathbb{E}[X_{P_{t+1}}^0] \leq (\frac{1}{2} + o(1))((1 + \frac{1}{e})c_0 + c(k+1)) + 2 = \frac{e}{e-1}(c(k+1) + 4) + o(ck) = c_0$.

The same arguments can be applied to estimate the expected number of individuals with $n - k - 1$ 1-bits. We have $\mathbb{E}[X_{R_t}^1] = \mathbb{E}[X_{P_t}^1] + \mathbb{E}[Y^1] + \mathbb{E}[Z^1]$. We assume by the induction hypothesis $\mathbb{E}[X_{P_t}^1] \leq c_1$ for $c_1 = \frac{e}{e-1}(c(k+2) + c_0 + 4) + o(ck)$. Similarly as before, $\mathbb{E}[Y^1] \leq \frac{c_1}{e}$. Moreover, there are no individuals with more than $n - k$ bits of 1 by Lemma 1. So to bound $\mathbb{E}[Z^1]$, consider separately the cases where i) the parent has at most $n - k - 1$ 1-bits and ii) the parent has $n - k$ 1-bits. By Corollary 3, for case i), the probability that the child has $n - k - 1$ 1-bits is at most $\frac{k+2}{n}$. We trivially bound the probability for case ii) by 1. Therefore, $\mathbb{E}[Z^1] \leq c(n - 2k + 3) \frac{k+2}{n} + c_0 \leq c(k+2) + c_0$. Then $\mathbb{E}[X_{R_t}^1] \leq (1 + \frac{1}{e})c_1 + c(k+2) + c_0$. Hence, by Corollary 5,

$$\begin{aligned} \mathbb{E}[X_{P_{t+1}}^1] &\leq (\frac{1}{2} + o(1))((1 + \frac{1}{e})c_1 + c(k+2) + c_0) + 2 \\ &= \frac{e}{e-1}(c(k+2) + c_0 + 4) + o(ck) = c_1. \end{aligned}$$

Continuing this way and letting c_i denote the upper bound on the expected number of individuals with $n - k - i$ number of 1-bits for $0 \leq i \leq n - 2k$, we have

$$c_i = \frac{e}{e-1}(c(k+i+1) + \sum_{j=0}^{i-1} c_j + 4) + o(ck). \quad \square$$

With the bound on $\mathbb{E}[X_{P_t}^1]$ found in Lemma 6, we can now prove a sharper bound on $\mathbb{E}[X_{P_t}^0]$.

Corollary 7. *Consider a generation t of the NSGA-II algorithm optimizing the ONEJUMPZEROJUMP $_{n,k}$ benchmark with the population size $N = c(n - 2k + 3)$ for some $c \geq 4$ such that $ck^2 = o(n)$. Suppose $P_0 \subseteq S_I^*$. If $1^n \notin P_t$, then $\mathbb{E}[X_t^0] \leq \frac{4e}{e-1} + o(1)$. Similarly, if $0^n \notin P_t$, then $\mathbb{E}[X_t^{n-2k}] \leq \frac{4e}{e-1} + o(1)$.*

Proof. We prove the result for $\mathbb{E}[X_t^0]$ since the other case is symmetrical.

Using the same notations as in the proof of Lemma 6, with the bound on $\mathbb{E}[X_{P_t}^1]$ found in Lemma 6, we can prove a sharper bound on $\mathbb{E}[X_{P_t}^0]$. To estimate $\mathbb{E}[Z^0]$, consider three cases separately: i) the parent has $n - k$ 1-bits, ii) the parent has $n - k - 1$ 1-bits, iii) the parent has less than $n - k - 1$ 1-bits. For case i) and ii), the probability that the child has $n - k$ 1-bits is at most $\frac{k+1}{n}$ by Corollary 3. For case iii), the probability is at most $\binom{k+2}{2}(\frac{1}{n})^2 \leq (\frac{k+2}{n})^2$ according to Lemma 2. Therefore $\mathbb{E}[Z^0] \leq \frac{k+1}{n}(c_0 + c_1) + (\frac{k+2}{n})^2 c(n - 2k + 3) = o(1)$. So by Corollary 5,

$$\mathbb{E}[X_{P_{t+1}}^0] \leq (\frac{1}{2} + o(1))((1 + \frac{1}{e})\mathbb{E}[X_{P_t}^0] + 4 + o(1)).$$

As a result, $\mathbb{E}[X_{P_t}^0] \leq \frac{4e}{e-1} + o(1)$ for any generation t . \square

Now with the upper bounds on $\mathbb{E}[X_{P_t}^0]$, $\mathbb{E}[X_{P_t}^1]$, $\mathbb{E}[X_{P_t}^{n-2k}]$, and $\mathbb{E}[X_{P_t}^{n-2k-1}]$, we can prove a lower bound on the runtime.

Theorem 8. *Consider the NSGA-II algorithm optimizing the ONEJUMPZEROJUMP_{n,k} benchmark with the population size $N = c(n - 2k + 3)$, for some $c \geq 4$ such that $ck^2 = o(n)$. Then the number of fitness evaluations needed in expectation is at least $\frac{3}{2}(\frac{4}{e-1} + o(1))^{-1}Nn^k$.*

Proof. Consider the waiting time to find the all-ones string when $P_0 \subseteq S_I^*$. For an individual of i 0-bits, the probability that its child through bit-wise mutation is the all-ones string is $(\frac{1}{n})^i(1 - \frac{1}{n})^{n-i} \leq (\frac{1}{n})^i$. Since by Corollary 7, before the all-ones string is found, the expected number of individuals with $n - k$ bits of 1 is at most $\frac{4e}{e-1} + o(1)$ in any parent population, and that for individuals with $n - k - 1$ bits of 1 is at most $\frac{e}{e-1}(c(k+2) + \frac{4e}{e-1} + 4) + o(ck)$, the probability that the all-ones string is generated at any iteration is at most $(\frac{4e}{e-1} + o(1))(\frac{1}{n})^k(1 - \frac{1}{n})^{n-k} + \frac{e}{e-1}(c(k+2) + \frac{4e}{e-1} + 4 + o(ck))(\frac{1}{n})^{k+1} + c(n - 2k + 3)(\frac{1}{n})^{k+2} \leq (\frac{4e}{e-1}(1 - \frac{1}{n})^{n-k} + o(1))(\frac{1}{n})^k$. Then the waiting time to find the all-ones string is at least $(\frac{4e}{e-1}(1 - \frac{1}{n})^{n-k} + o(1))^{-1}n^k$. Therefore, the expected number of iterations needed to find one of the all-zeroes string and the all-ones string is at least $\frac{1}{2}(\frac{4e}{e-1}(1 - \frac{1}{n})^{n-k} + o(1))^{-1}n^k$ and the expected number of iterations needed to find both is at least $\frac{3}{2}(\frac{4e}{e-1}(1 - \frac{1}{n})^{n-k} + o(1))^{-1}n^k$. Since by Lemma 1, the probability that $P_0 \subseteq S_I^*$ is at least $1 - o(1)$, we have that the expected number of iterations needed under any case is at least $(1 - o(1))(\frac{3}{2}(\frac{4e}{e-1}(1 - \frac{1}{n})^{n-k} + o(1))^{-1}n^k)$, corresponding to $\frac{3}{2}(\frac{4e}{e-1}(1 - \frac{1}{n})^{n-k} + o(1))^{-1}Nn^k$ fitness evaluations. Noting that $k = o(n)$, we have $(1 - \frac{1}{n})^{n-k} = \frac{1}{e} + o(1)$, and this completes the proof. \square

5 Precise Runtime of the NSGA-II with Fixed Sorting on OneJumpZeroJump

In the version of the NSGA-II considered in [DQ22] and the previous section, when the crowding distance is being calculated with respect to each objective, we sort the individuals such that the ones with the same objective value are positioned randomly. A variant of the algorithm, considered in [BQ22], is to fix the relative positions of the individuals that have the same objective value. We call this variant of the algorithm the NSGA-II with fixed sorting, and show a precise bound on the runtime of this variant optimizing the ONEJUMPZEROJUMP benchmark.

First we observe in the following Lemma that for this variant of the algorithm, after $O(n \log n)$ iterations, for each objective value on F_I^* there are exactly two individuals with positive crowding distances.

Lemma 9. *Consider the NSGA-II algorithm with fixed sorting optimizing the ONEJUMPZEROJUMP_{n,k} benchmark with population size $N = c(n - 2k + 3)$ for some $c \geq 2$. After $O(n \log n)$ iterations, for any generation t , for every objective value $v \in F_I^*$, there are exactly two individuals $x, y \in R_t$ such that $f(x) = f(y) = v$, $\text{cDis}(x) > 0$ and $\text{cDis}(y) > 0$.*

Proof. We first prove that for any objective value $v = (v_1, v_2) \in F^*$, there are at most two individuals $x, y \in R_t$ such that $f(x) = f(y) = v$, $\text{cDis}(x) > 0$ and $\text{cDis}(y) > 0$. Suppose

the individuals whose objective value is v belong to rank F of R_t . Let $S_{1,1}, \dots, S_{1,|F|}$ be the list of individuals in F sorted by ascending f_1 values and $S_{2,1}, \dots, S_{2,|F|}$ be the list of individuals sorted by ascending f_2 values, which were used to compute the crowding distances. Then there exist $a \leq b$ and $a' \leq b'$ such that $[a..b] = \{i \mid f_1(S_{1,i}) = v_1\}$ and $[a'..b'] = \{i \mid f_2(S_{2,i}) = v_2\}$. For $i \in [a+1..b-1]$ and $S_{1,i} = S_{2,j}$ for some $j \in [a'+1..b'-1]$, we have that $f_1(S_{1,i-1}) = v_1 = f_1(S_{1,i+1})$ and $f_2(S_{2,j-1}) = v_2 = f_2(S_{2,j+1})$. So $\text{cDis}(S_{1,i}) = 0$. Hence the only individuals that could have positive crowding distance are $S_{1,a}, S_{2,a'}, S_{1,b}, S_{2,b'}$. Since the relative positions of the individuals whose objective value is v are the same in $S_{1,1}, \dots, S_{1,|F|}$ and $S_{2,1}, \dots, S_{2,|F|}$, we have $S_{1,a}$ is the same individual as $S_{2,a'}$ and $S_{1,b}$ is the same individual as $S_{2,b'}$. So there are at most two individuals whose crowding distances are positive.

Next, we prove that if there are at least two individuals in R_t whose objective values are v , then for any generation $s \geq t$, there are exactly two individuals $x, y \in R_s$ such that $f(x) = f(y) = v$, $\text{cDis}(x) > 0$ and $\text{cDis}(y) > 0$. By the definition of the crowding distance, we have that $\text{cDis}(S_{1,a}) \geq \frac{f_1(S_{1,a+1}) - f_1(S_{1,a-1})}{f_1(S_{1,|F|}) - f_1(S_{1,1})} \geq \frac{f_1(S_{1,a}) - f_1(S_{1,a-1})}{f_1(S_{1,|F|}) - f_1(S_{1,1})}$. Since $f_1(S_{1,a}) - f_1(S_{1,a-1}) > 0$ by the definition of a , we have $\text{cDis}(S_{1,a}) > 0$. Similarly, we have $\text{cDis}(S_{1,b}) > 0$. Since there are at least two individuals $x, y \in R_t$ such that $f(x) = f(y) = v$, we have $a \neq b$, meaning $S_{1,a}$ and $S_{1,b}$ are not the same individual. Since $v \in F^*$, we have that $S_{1,a}$ and $S_{1,b}$ belong to the first rank. Consequently, these two will survive to the next generation and appear in R_{t+1} . Then again there will be exactly two individuals in R_{t+1} whose objective values are v and who have positive crowding distances. Inductively, in any generation $s \geq t$, there will always be exactly two such individuals.

By Lemma 3 of [DQ22], in at most $e(\frac{4k}{3})^k$ iterations, there will be an individual x in the parent population such that $f(x) \in F_I^*$. Lemma 4 of [DQ22] then states that once such x appears, in $O(n \log n)$ iterations in expectation, every objective value $v \in F_I^*$ will have been generated at least once. Then, in $O(n \log n)$ iterations in expectation, every objective value in F_I^* will have been generated at least twice. So for any generation t starting from there, there will be exactly two individuals $x, y \in R_t$ such that $f(x) = f(y) = v$, $\text{cDis}(x) > 0$ and $\text{cDis}(y) > 0$. \square

We call the phase where, for every objective value $v \in F_I^*$, there are exactly two individuals x, y in the combined population such that $f(x) = f(y) = v$, $\text{cDis}(x) > 0$ and $\text{cDis}(y) > 0$, the tightening phase. In the following analyses, we define $s^* = O(n \log n)$ to be the generation where the algorithm first enters the tightening phase. Then by Lemma 9, for any generation $t \geq s^*$, the algorithm stays in the tightening phase. In the following Lemma, we estimate similarly to Lemma 4 the probability that a rank-1 individual with zero crowding distance survives. What is different now is that for the tightening phase, we can calculate the probability precisely (apart from lower order terms).

Lemma 10. *Consider a generation $t \geq s^*$ of the NSGA-II algorithm with fixed sorting optimizing the ONEJUMPZEROJUMP $_{n,k}$ benchmark with population size $N = c(n - 2k + 3)$ for some $c \geq 2$ such that $ck^2 = o(n)$. Suppose $P_0 \subseteq F_I^*$, $\mathbb{E}[X_{P_t}^0] = O(ck)$, and $\mathbb{E}[X_{P_t}^{n-2k}] = O(ck)$. For a rank-1 individual $x \in R_t$ that has zero crowding distance, the probability that $x \in P_{t+1}$ is $\frac{c-2}{2c-2} \pm o(1)$.*

Proof. Since now, for every objective value $v \in F_I^*$, there are exactly two individuals x, y such that $f(x) = f(y) = v$, $\text{cDis}(x) > 0$ and $\text{cDis}(y) > 0$, using the same notations as in

Lemma 4, we have $|F_1^*| = 2(n - 2k + 3) - \Theta(1)$. So the probability that a rank-1 individual x with zero crowding distance survives is

$$\frac{N - |F_1^*|}{2N - |F_1^*|} \Pr[|F_{>1}| = 0] + \Pr[x \text{ survives} | |F_{>1}| \geq 1] \Pr[|F_{>1}| \geq 1].$$

As proved in Lemma 4, $\Pr[|F_{>1}| = 0] \geq 1 - o(1)$. So $\Pr[x \text{ survives}] = \frac{(c-2)(n-2k+3)+\Theta(1)}{(2c-2)(n-2k+3)+\Theta(1)} (1 - o(1)) + o(1) = \frac{c-2}{2c-2} \pm o(1)$. \square

Corollary 11. *Consider a generation $t \geq s^*$ of the NSGA-II algorithm with fixed sorting optimizing the ONEJUMPZEROJUMP $_{n,k}$ benchmark with population size $N = c(n - 2k + 3)$ for some $c \geq 2$ such that $ck^2 = o(n)$. Suppose $P_0 \subseteq S_I^*$, $\mathbb{E}[X_{P_t}^0] = O(ck)$, and $\mathbb{E}[X_{P_t}^{n-2k}] = O(ck)$. Then for any $i \in [0..n - 2k]$, we have $\mathbb{E}[X_{P_{t+1}}^i] = (\frac{c-2}{2c-2} + o(1))\mathbb{E}[X_{R_t}^i] + \frac{c}{c-1} \pm o(1)$.*

Proof. Since $N = c(n - 2k + 3)$ for $c \geq 2$, any individual with $n - k - i$ 1-bits and positive crowding distance survives to the next generation. Then, using the same notations as in Corollary 5, we have $\mathbb{E}[X_{P_{t+1}}^i] = \mathbb{E}[X_{>0}] + \mathbb{E}[X_{=0}^*]$. Then by Lemma 10,

$$\begin{aligned} \mathbb{E}[X_{P_{t+1}}^i] &= \mathbb{E}[X_{>0}] + (\frac{c-2}{2c-2} \pm o(1))\mathbb{E}[X_{=0}] \\ &= (\frac{c-2}{2c-2} \pm o(1))\mathbb{E}[X_{R_t}^i] \\ &\quad + (\frac{c}{2c-2} \pm o(1))\mathbb{E}[X_{>0}]. \end{aligned}$$

Since $\mathbb{E}[X_{>0}] = 2$ by Lemma 9, we have $\mathbb{E}[X_{P_{t+1}}^i] = (\frac{c-2}{2c-2} \pm o(1))\mathbb{E}[X_{R_t}^i] + \frac{c}{c-1} \pm o(1)$. \square

Consequently, we can calculate $\mathbb{E}[X_{P_t}^0]$ and $\mathbb{E}[X_{P_t}^{n-2k}]$ precisely apart from lower order terms.

Lemma 12. *Consider the NSGA-II algorithm with fixed sorting optimizing the ONEJUMPZEROJUMP $_{n,k}$ benchmark with the population size $N = c(n - 2k + 3)$ for some $c \geq 2$ such that $ck^2 = o(n)$. Suppose $P_0 \subseteq S_I^*$. We have for any $t \geq s^* + \log n$, if $1^n \notin P_t$, then $\mathbb{E}[X_{P_t}^0] = \frac{2ec}{ec-c+2} \pm o(1)$. Similarly, if $0^n \notin P_t$, then $\mathbb{E}[X_{P_t}^{n-2k}] = \frac{2ec}{ec-c+2} \pm o(1)$.*

Proof. Since the NSGA-II with fixed sorting is a special case of the general algorithm considered in section 4, the bounds proven there still apply. So using the same notations as in Lemma 6, the proof of Corollary 7 shows that $\mathbb{E}[Z^0] \leq o(1)$. Also, since there are at least two individuals with $n - k - 1$ 1-bits, $\mathbb{E}[Z^0] \geq 2^{\frac{k+1}{n}} = o(1)$. So $\mathbb{E}[Z^0] = o(1)$. Moreover, $\mathbb{E}[Y^0] = (1 - \frac{1}{n})^n \mathbb{E}[X_{P_t}^0] = (\frac{1}{e} - o(1))\mathbb{E}[X_{P_t}^0]$. So for any generation $t' \geq s^*$, we have

$$\begin{aligned} \mathbb{E}[X_{P_{t'+1}}^0] &= (\frac{c-2}{2c-2} \pm o(1))((\frac{e+1}{e} - o(1))\mathbb{E}[X_{P_t}^0] + o(1)) \\ &\quad + \frac{c}{c-1} \pm o(1). \end{aligned}$$

Hence the sequence of $\mathbb{E}[X_{P_t}^0]$ converges to $C = \frac{2ec}{ec-c+2} \pm o(1)$. Since $\frac{|C - \mathbb{E}[X_{P_{t'+1}}^0]|}{|C - \mathbb{E}[X_{P_t}^0]|} = \frac{(e+1)(c-2)}{2e(c-1)} \pm o(1) < 1$, we have that in $\omega(1)$ iterations, $\mathbb{E}[X_{P_t}^0]$ reaches $\frac{2ec}{ec-c+2} \pm o(1)$. Since the sequence starts from iteration s^* , for any $t \geq n^2$, we have that $\mathbb{E}[X_{P_t}^0] = \frac{2ec}{ec-c+2} \pm o(1)$. \square

Theorem 13. *Consider the NSGA-II algorithm with fixed sorting optimizing the ONEJUMPZEROJUMP_{n,k} benchmark, for $k \geq 3$, with the population size $N = c(n-2k+3)$, for some $c \geq 2$ such that $ck^2 = o(n)$. Then the number of fitness evaluations needed in expectation is $\frac{3}{2}N(\frac{2c}{ec-c+2} \pm o(1))^{-1}n^k$.*

Proof. For the upper bound, if the all-ones string is not found in $O(n \log n)$ iterations, then by Lemma 12, we have $\mathbb{E}[X_{P_t}^0] = \frac{2ec}{ec-c+2} \pm o(1)$ for any iteration t afterwards. Then the probability of generating the all-ones string in an iteration is at least $(\frac{2ec}{ec-c+2} - o(1))(\frac{1}{n})^k(1 - \frac{1}{n})^{n-k}$ and in expectation at most $(\frac{2ec}{ec-c+2}(1 - \frac{1}{n})^{n-k} - o(1))^{-1}n^k$ iterations are needed to find the all-ones string. Then at most $\frac{3}{2}(\frac{2ec}{ec-c+2}(1 - \frac{1}{n})^{n-k} - o(1))^{-1}n^k \leq \frac{3}{2}(\frac{2c}{ec-c+2} - o(1))^{-1}n^k$ iterations are needed to find both the all-ones and the all-zeroes string.

For the lower bound, suppose $P_0 \subseteq S_I^*$. Then by Lemma 1, for any generation t there is no individual with less than k 0-bits or 1-bits in the parent population. Then for an individual $x \in P_t$ to generate the all-ones or the all-zeroes string, the probability is at most $(\frac{1}{n})^{|x|_1}(1 - \frac{1}{n})^{|x|_0} + (\frac{1}{n})^{|x|_0}(1 - \frac{1}{n})^{|x|_1} \leq \frac{2}{n^k}$. Then for any iteration to generate the all-ones or the all-zeroes string, the probability is at most $\frac{2N}{n^k}$. Therefore, the probability that neither the all-ones nor the all-zeroes string has been generated in $O(n \log n)$ iterations is $(1 - \frac{2N}{n^k})^{O(n \log n)} \geq 1 - \frac{O(cn^2 \log n)}{n^k} = 1 - o(1)$ since $k \geq 3$ and $c = o(n)$. Then for any iteration t afterwards, we have that, $\mathbb{E}[X_{P_t}^0] = \frac{2ec}{ec-c+2} \pm o(1)$. Moreover, by Lemma 6, we have that $\mathbb{E}[X_{P_t}^1] = O(ck)$ for any generation t . Then the probability that the all-ones string is generated in an iteration is at most $(\frac{2ec}{ec-c+2} + o(1))(\frac{1}{n})^k(1 - \frac{1}{n})^{n-k} + O(ck)(\frac{1}{n})^{k+1} + c(n-2k+3)(\frac{1}{n})^{k+2} \leq (\frac{2ec}{ec-c+2}(1 - \frac{1}{n})^{n-k} + o(1))(\frac{1}{n})^k$. So the waiting time to find the all-ones string is at least $(\frac{2ec}{ec-c+2}(1 - \frac{1}{n})^{n-k} + o(1))^{-1}n^k$. Then the waiting time to find both the all-ones string and the all-zeroes strings is at least $\frac{3}{2}(\frac{2ec}{ec-c+2}(1 - \frac{1}{n})^{n-k} + o(1))^{-1}n^k$. Since the probability that i) neither the all-ones string nor the all-zeroes string is found in n^2 generations, given that ii) $P_0 \subseteq S_I^*$, and the probability that event ii) happens are both $1 - o(1)$. The probability that both happen is $(1 - o(1))^2$. Then the waiting time to find the two extremal points in any case is at least $(1 - o(1))^2 \frac{3}{2}(\frac{2ec}{ec-c+2}(1 - \frac{1}{n})^{n-k} + o(1))^{-1}n^k = \frac{3}{2}(\frac{2ec}{ec-c+2}(1 - \frac{1}{n})^{n-k} + o(1))^{-1}n^k = \frac{3}{2}(\frac{2c}{ec-c+2} + o(1))^{-1}n^k$ for $k = o(n)$. \square

6 Lower Bound on the Runtime of the NSGA-II on OneMinMax

[ZLD22] gave an $O(Nn \log n)$ upper bound on the runtime of the NSGA-II optimizing the ONEMINMAX benchmark. In this section, we prove a matching lower bound using the techniques we have developed so far.

In this section, for any $i \in [0..n]$ and any generation t , we let $X_{P_t}^i$ denote the number of individuals with i 0-bits in P_t and let $X_{R_t}^i$ denote that in R_t .

Suppose in an iteration t the individual with the least number of 0-bits in P_t has i_t 0-bits. Then we can think of the algorithm making progress as it tries to decrease i_t till it becomes 0, at which point the algorithm has found 1^n . In the following lemma, we give upper bounds on $\mathbb{E}[X_{P_t}^{i_t}]$ when i_t is close to 0, which will help us estimate the waiting time needed for the algorithm to make progress there.

Lemma 14. Consider the NSGA-II algorithm optimizing the ONEMINMAX benchmark for $n > 16$, with $N = c(n + 1)$ for $c \geq 4$, where for all $x \in P_0$, $|x|_0 \geq \frac{n}{4}$. Suppose $v \in [0..n]$ such that $cv^2 = o(n)$ and for a generation t there is no individual $x \in P_t$ such that $|x|_0 < v$. Then $\mathbb{E}[X_{P_t}^v] \leq c_0 = \frac{4e}{e-1} + o(1)$ and $\mathbb{E}[X_{P_t}^{v+1}] \leq \frac{e-1}{e}(c(v+2) + c_0 + 4) + o(c)$.

Proof. First we show that, similarly to Lemma 4, the probability that an $x \in R_t$ with zero crowding distance survives to P_{t+1} is less than $\frac{1}{2}$. Unlike Lemma 4, for the ONEMINMAX benchmark, since any solution lies on the Pareto front, we have that $|F_{>1}| = 0$. So the probability that x survives is $\frac{N-|F_1^*|}{2N-|F_1^*|} < \frac{1}{2}$ without additional lower-order terms.

Then, similarly to Corollary 5 and using the same notations, $\mathbb{E}[X_{P_{t+1}}] \leq \frac{1}{2}(\mathbb{E}[X_{R_t}] + \mathbb{E}[X_{>0}])$. Since by Lemma 1 of [ZLD22], $X_{>0} \leq 4$, we have $\mathbb{E}[X_{P_{t+1}}] \leq \frac{1}{2}\mathbb{E}[X_{R_t}] + 2$.

Similarly to Lemma 6, we now prove by induction that $\mathbb{E}[X_{P_t}^v] \leq c_0 = \frac{e-1}{e}(c(v+1) + 4) + o(c)$. For the base case, since for all $x \in P_0$, we have $|x|_0 \geq \frac{1}{4}n > v$, because $n > 16$ and $v = o(\sqrt{n})$. So $\mathbb{E}[X_{P_0}^v] = 0$. For the induction, $\mathbb{E}[X_{R_t}^v] \leq \frac{e+1}{e}\mathbb{E}[X_{P_t}^v] + \frac{v+1}{n}c(n+1) = \frac{e+1}{e}\mathbb{E}[X_{P_t}^v] + c(v+1) + o(1)$ and in turn $\mathbb{E}[X_{P_{t+1}}^v] \leq \frac{1}{2}(\frac{e+1}{e}\mathbb{E}[X_{P_t}^v] + c(v+1) + o(1)) + 2$. Consequently, $\mathbb{E}[X_{P_t}^v] \leq \frac{e-1}{e}(c(v+1) + 4) + o(c) = c_0$ for any generation t . Moreover, $\mathbb{E}[X_{P_{t+1}}^{v+1}] \leq \frac{1}{2}(\frac{e+1}{e}\mathbb{E}[X_{P_t}^{v+1}] + \frac{v+2}{n}c(n+1) + c_0) + 2 = \frac{1}{2}(\frac{e+1}{e}\mathbb{E}[X_{P_t}^{v+1}] + c(v+2) + o(1) + c_0) + 2$. So $\mathbb{E}[X_{P_t}^{v+1}] \leq \frac{e-1}{e}(c(v+2) + c_0 + 4) + o(c)$.

Similarly to Corollary 7, we can now prove a sharper bound on $\mathbb{E}[X_{P_t}^v]$. Now $\mathbb{E}[X_{P_{t+1}}^v] \leq \frac{1}{2}(\frac{e+1}{e}\mathbb{E}[X_{P_t}^v] + o(1)) + 2$, and consequently $\mathbb{E}[X_{P_t}^v] \leq \frac{4e}{e-1} + o(1)$. \square

Then, we show that only with very small probability, $o(n^{-\frac{4}{3}})$, the algorithm can make a progress of a size larger than 1 in an iteration.

Lemma 15. Consider the NSGA-II algorithm optimizing the ONEMINMAX benchmark for $n > 16$, with $N = c(n + 1)$ for $c \geq 4$, where for all $x \in P_0$, $|x|_0 \geq \frac{n}{4}$. Suppose $v \in [0..n]$ such that $cv^3 = o(n)$ and for a generation t , there is no individual $x \in P_t$ such that $|x|_0 < v$. Suppose in R_t the individual with the least number of 0-bits is y . Then $\Pr[|y|_0 \leq v - 2] = o(n^{-\frac{4}{3}})$.

Proof. By Lemma 2, to generate an individual with at most $v - 2$ bits of 0 through bit-wise mutation, for an individual with v bits of 0, the probability is at most $(\frac{v}{n})^2$, for an individual with $v + 1$ bits of 0, it is at most $(\frac{v+1}{n})^3$, and for an individual with at least $v + 2$ bits of 0, it is at most $(\frac{v+2}{n})^4$. Let X denote the number of individuals with at most $v - 2$ 0-bits in R_t , $c_0 = \frac{4e}{e-1} + o(1)$, and $c_1 = \frac{e-1}{e}(c(v+2) + c_0 + 4) + o(c)$. Then by Lemma 14, $\mathbb{E}[X] \leq c_0(\frac{v}{n})^2 + c_1(\frac{v+1}{n})^3 + c(n+1)(\frac{v+2}{n})^4 = o(n^{-\frac{4}{3}})$. So, $\Pr[|y|_0 \leq v - 2] = \Pr[X \geq 1] \leq \frac{\mathbb{E}[X]}{1} = o(n^{-\frac{4}{3}})$. \square

Finally, we combine everything to obtain a lower bound on the runtime.

Theorem 16. Consider the NSGA-II algorithm optimizing the ONEMINMAX benchmark for $n > 16$, with $N = c(n + 1)$ for $c \geq 4$ and $c = o(n^\mu)$ for $\mu < 1$. Then the number of fitness evaluations needed is at least $N(n(\frac{4e}{e-1} + o(1))^{-1} \frac{1-\mu}{3} \ln n)$.

Proof. Let $v = n^{\frac{1-\mu}{3}}$ ($cv^3 = o(n)$). For any generation t , suppose x^t is the individual with the least number of 0-bits in P_t , and we denote $|x^t|_0$ by M_t . Suppose we have $M_0 \geq v$, which happens with probability at least $1 - Ne^{-\frac{n}{8}} = 1 - o(1)$ as proven in Lemma 1,

since $v < \frac{n}{4}$. Then suppose at generation r , we have $M_r = v$. Then for any generation $s \geq r$, we have $c(M_s)^3 = o(n)$ and by Corollary 15, the probability that $M_s - M_{s+1} \geq 2$ is $o(n^{-\frac{4}{3}})$. Since by Theorem 6 of [ZLD22], the expected iterations needed to optimize the ONEMINMAX benchmark is $O(n \log n)$, we have that the expected times that the event $M_s - M_{s+1} \geq 2$ happens for any $s \geq r$ is $o(n^{-\frac{4}{3}})O(n \log n) = o(n^{-\frac{1}{3}} \log n) = o(1)$. Then the probability that the event $M_s - M_{s+1} \geq 2$ does not happen for any $s \geq r$ is $1 - o(1)$. When that happens, after generation r , the algorithm makes progress by decreasing M_s one by one until $M_{s'} = 0$ for some s' .

By Lemma 2, to generate an individual with $M_s - 1$ bits of 0 through bit-wise mutation, for an individual with M_s bits of 0, the probability is at most $\frac{M_s}{n}$, for an individual with $M_s + 1$ bits of 0, the probability is at most $(\frac{M_s+1}{n})^2$, and for an individual with less than $M_s + 1$ bits of 0, the probability is at most $(\frac{M_s+2}{n})^3$. Let X denote the number of individuals with $M_s - 1$ bits of 0 in R_s , $c_0 = \frac{4e}{e-1} + o(1)$, and $c_1 = \frac{e-1}{e}(c(v+2) + c_0 + 4) + o(c)$. Then by Lemma 14, $\mathbb{E}[X] \leq c_0 \frac{M_s}{n} + c_1 (\frac{M_s+1}{n})^2 + c(n+1)(\frac{M_s+2}{n})^3 = (\frac{4e}{e-1} + o(1)) \frac{M_s}{n}$. So the probability that $X \geq 1$ is at most $(\frac{4e}{e-1} + o(1)) \frac{M_s}{n}$ and the waiting time for the event $M_s - M_{s+1} = 1$ to happen is at least $(\frac{4e}{e-1} + o(1))^{-1} \frac{n}{M_s}$ iterations. So, for M_s to decrease from v to 0 one by one, the total waiting time is $\sum_{i=1}^v (\frac{4e}{e-1} + o(1))^{-1} \frac{n}{i} > n(\frac{4e}{e-1} + o(1))^{-1} \ln v = n(\frac{4e}{e-1} + o(1))^{-1} \frac{1-\mu}{3} \ln n$.

Since the probability that event i) once M_s reaches v , it decreases by at most one in an iteration happen given that event ii) $M_0 \geq v$ happen, and the probability that event ii) happens, are both at least $1 - o(1)$, and when both i) and ii) happen, the number of iterations needed is at least $n(\frac{4e}{e-1} + o(1))^{-1} \frac{1-\mu}{3} \ln n$, we have that in any case, the number of iterations needed is at least $(1 - o(1))^2 (n(\frac{4e}{e-1} + o(1))^{-1} \frac{1-\mu}{3} \ln n) = (1 - o(1))(n(\frac{4e}{e-1} + o(1))^{-1} \frac{1-\mu}{3} \ln n)$, corresponding to $N(n(\frac{4e}{e-1} + o(1))^{-1} \frac{1-\mu}{3} \ln n)$ fitness evaluations. \square

7 Experiments

To complement our theoretical results, we also experimentally evaluate some runs of the NSGA-II on the ONEJUMPZEROJUMP benchmark, both with respect to the runtime and the population dynamics. We note that [DQ22] already presented some results on the runtime (for $k = 3$, $N/(2n - k + 3) = 2, 4, 8$, and $n = 20, 30$). We therefore mostly concentrate on the population dynamics, i.e., the number of individuals in the population for each objective value on the Pareto front, which our theoretical analyses have shown to be crucial for determining the lower bound and the leading coefficient of the runtime.

7.1 Settings

We implemented the algorithm as described in the Preliminaries section in Python, and tested the following settings.

- Problem size n : 50 and 100.
- Jump size k : 2. This small number was necessary to admit the problem sizes above. Problem sizes of a certain magnitude are needed to see a behavior not dominated by lower-order effects.

	$n = 50$	$n = 100$
$N = 2(n - 2k + 3)$	247,617	2,411,383
$N = 4(n - 2k + 3)$	416,284	3,858,084
$N = 8(n - 2k + 3)$	714,812	6,792,456

Table 1: Average runtime of the NSGA-II with bit-wise mutation on the ONEJUMPZEROJUMP benchmark with $k = 2$.




Figure 1: Average number of individuals with $i \in [k..n - k]$ 1-bits for $n = 50$ and $k = 2$.

- Population size N : $2(n - 2k + 3)$, $4(n - 2k + 3)$, and $8(n - 2k + 3)$. [DQ22] suggested that, even though their mathematical analysis applies only for $N \geq 4(n - 2k + 3)$, already for $N = 2(n - 2k + 3)$ the algorithm still succeeds empirically. Therefore, we have also experimented with $N = 2(n - 2k + 3)$ to confirm that our arguments for the population dynamics still apply for the smaller population size.
- Selection for variation: fair selection.
- Mutation method: bit-wise mutation with rate $\frac{1}{n}$.
- Number of independent repetitions per setting: 10.

7.2 Results on the Runtime

Table 1 contains the average runtime (number of fitness evaluations done until the full Pareto front is covered) of the algorithm. For all of the settings, we have observed a standard deviation that is between 50% to 80% of the mean, which supports our reasoning that the runtime is dominated by the waiting time needed to find the two extremal points of the front, which is the maximum of two geometric random variables. An obvious observation from the data is that increasing N does not help with the runtime, supporting our theoretical results that the lower bound on the runtime increases when N increases. Moreover, for all the settings that we have experimented with, the average runtime is well above our theoretically proven lower bound made tighter by discarding the lower order terms, namely $\frac{3}{2}(\frac{4}{e-1})^{-1}Nn^k$.




Figure 2: Average number of individuals with $i \in [k..n - k]$ 1-bits for $n = 100$ and $k = 2$.

7.3 Results on the Population Dynamics

For most of the experiments conducted, we have also recorded the population dynamics throughout the executions of the algorithm (mistakenly, we did not do so for $n = 100$ and $N = 2(n - 2k + 3)$; however, from the very even distribution seen for $n = 50$ for this population size, we would be very surprised to see a different pattern for $n = 100$; of course, we will fix this omission for the final version of this paper). Specifically, for each run, for every $n^k/50$ iterations, we record for each $i \in [k..n - k]$ how many individuals there are in the parent population with i bits of 1. Since as shown in our theoretical analyses and [DQ22], the greatest contributor to the runtime is the waiting time to find the all-ones and the all-zeroes strings after the inner part of the Pareto front has been discovered, we are mostly interested in how the population dynamics develop in that phase. To this end, we discard data points recorded when the inner part of the Pareto front has not been fully covered, and those recorded after one of the extremal points has already been discovered. The final numbers reported for a run is the average of the data points kept. In the end we report the average of the means across 10 repetitions. In all of the runs, we have never observed an initial population not contained in the inner part of the Pareto front, supporting our theoretical arguments and also making the experiments fall into the scenario that we have studied theoretically.

Figure 1 contains the average number of individuals throughout a run of the algorithm for each point on the inner part of the Pareto front for $n = 50$, averaged by the 10 repetitions, and Figure 2 contains that for $n = 100$. An obvious observation is that for all experiment settings, we have that the average number of individuals with k or $n - k$ 1-bits is less than the proven upper bound $\frac{4e}{e-1} \approx 6.33$. When doubling the population size, the number of individuals with k or $n - k$ 1-bits grows. This does not contradict with our upper bound (which is independent of the population size), but it only suggests that the precise average occupation of these objective values contains a dependence on the population size that is small enough for this number to be bounded by $\frac{4e}{e-1} \approx 6.33$. We note that for the setting with fixed sorting the precise occupation number $\frac{2ec}{2ec-c+2} \pm o(1)$ we proved displayed exactly such a behavior.

Our experimental data also give the occupation numbers for the other objective values. We did not discuss these in much detail in our theoretical analysis since all we needed to know was the occupation number for the outermost points of the inner part of the Pareto front and a relatively generous upper bound for the points one step closer to the middle.

A closer look into our mathematical analysis shows that it does give good estimates only for objective values close to the outermost points of the Pareto front. For that reason, it is interesting to observe that our experimental data show that the population is, apart from few positions close to the outermost positions, very evenly distributed on the Pareto front (that is, a typical position is occupied by c individuals, where c is such that the population size is $N = c(n - 2k + 3)$). Given the mostly random selection of most of the next population (apart from the up to 4 individuals with positive crowding distance per position) and the drift towards the middle in the offspring generation (e.g., a parent with $\frac{3}{4}n$ ones is much more likely to generate an offspring with fewer than more ones), this balanced distribution was a surprise to us. While it has no influence on the time to find the Pareto front of ONEJUMPZEROJUMP, we suspect that such balanced distributions are preferable for many other problems.

8 Conclusions and Future Works

In this work, we gave the first lower bounds matching previously proven upper bounds for the runtime of the NSGA-II. We proved that the runtime of the NSGA-II with population size at least four times the Pareto front size computes the full Pareto front of the ONEMINMAX problem in expected time (number of function evaluations) $\Omega(Nn \log n)$ and the one of the ONEJUMPZEROJUMP problem with jump size k in expected time $\Omega(Nn^k)$. These bounds match the corresponding $O(Nn \log n)$ and $O(Nn^k)$ upper bounds shown respectively in [ZLD22] and [DQ22]. These asymptotically tight runtimes show that, different from many other population-based search heuristics, the NSGA-II does not profit from larger population sizes, even in an implementation where the expected numbers $\Theta(n \log n)$ and $\Theta(n^k)$ of iterations is the more appropriate performance criterion. Together with the previous result [ZLD22] that a population size below a certain value leads to a detrimental performance of the NSGA-II, our results show that the right choice of the population size of the NSGA-II is important for an optimal performance, much more than for many single-objective population-based algorithms, where larger population sizes at least for certain parameter ranges have little influence on the number of fitness evaluations needed.

The main obstacle we had to overcome in our analysis was to understand sufficiently well the population dynamics of the NSGA-II, that is, the expected number of individuals having a particular objective value at a particular time. While we have not completely understood this question, our estimates are strong enough to obtain, for the ONEJUMPZEROJUMP benchmark and the NSGA-II using a fixed sorting to determine the crowding distance, a runtime guarantee that is also tight including the leading constant.

From this work, a number of possible continuations exist. For example, runtime analyses which are tight including the leading constant allow one to distinguish constant-factor performance differences. This can be used to optimize parameters or decide between different operators. For example, we have used the mutation rate $\frac{1}{n}$, which is the most accepted choice for bit-wise mutation. By conducting our analysis for a general mutation rate $\frac{\alpha}{n}$, one would learn how the mutation rate influences the runtime and one would be able to determine an optimal value for this parameter. We note that a different mutation rate not only changes the probability to reach the global optimum from the local one

(which is well-understood [DLMN17]), but also changes the population dynamics. We are nevertheless optimistic that our methods can be extended in such directions.

References

- [AD11] Anne Auger and Benjamin Doerr, editors. *Theory of Randomized Search Heuristics*. World Scientific Publishing, 2011.
- [BFN08] Dimo Brockhoff, Tobias Friedrich, and Frank Neumann. Analyzing hypervolume indicator based algorithms. In *Parallel Problem Solving from Nature, PPSN 2008*, pages 651–660. Springer, 2008.
- [BQ22] Chao Bian and Chao Qian. Running time analysis of the non-dominated sorting genetic algorithm II (NSGA-II) using binary or stochastic tournament selection. In *Parallel Problem Solving From Nature, PPSN 2022*. Springer, 2022. Also available at <https://arxiv.org/abs/2203.11550>.
- [BQT18] Chao Bian, Chao Qian, and Ke Tang. A general approach to running time analysis of multi-objective evolutionary algorithms. In *International Joint Conference on Artificial Intelligence, IJCAI 2018*, pages 1405–1411. IJCAI, 2018.
- [DGN16] Benjamin Doerr, Wanru Gao, and Frank Neumann. Runtime analysis of evolutionary diversity maximization for OneMinMax. In *Genetic and Evolutionary Computation Conference, GECCO 2016*, pages 557–564. ACM, 2016.
- [DKV13] Benjamin Doerr, Bojana Kodric, and Marco Voigt. Lower bounds for the runtime of a global multi-objective evolutionary algorithm. In *Congress on Evolutionary Computation, CEC 2013*, pages 432–439. IEEE, 2013.
- [DLMN17] Benjamin Doerr, Huu Phuoc Le, Régis Makhmara, and Ta Duy Nguyen. Fast genetic algorithms. In *Genetic and Evolutionary Computation Conference, GECCO 2017*, pages 777–784. ACM, 2017.
- [DPAM02] Kalyanmoy Deb, Amrit Pratap, Sameer Agarwal, and T. Meyarivan. A fast and elitist multiobjective genetic algorithm: NSGA-II. *IEEE Transactions on Evolutionary Computation*, 6:182–197, 2002.
- [DQ22] Benjamin Doerr and Zhongdi Qu. A first runtime analysis of the NSGA-II on a multimodal problem. In *Parallel Problem Solving From Nature, PPSN 2022*. Springer, 2022. Also available at <https://arxiv.org/abs/2204.13750>.
- [DZ21] Benjamin Doerr and Weijie Zheng. Theoretical analyses of multi-objective evolutionary algorithms on multi-modal objectives. In *Conference on Artificial Intelligence, AAAI 2021*, pages 12293–12301. AAAI Press, 2021.
- [Gie03] Oliver Giel. Expected runtimes of a simple multi-objective evolutionary algorithm. In *Congress on Evolutionary Computation, CEC 2003*, pages 1918–1925. IEEE, 2003.

- [GL10] Oliver Giel and Per Kristian Lehre. On the effect of populations in evolutionary multi-objective optimisation. *Evolutionary Computation*, 18:335–356, 2010.
- [HZ20] Zhengxin Huang and Yuren Zhou. Runtime analysis of somatic contiguous hypermutation operators in MOEA/D framework. In *Conference on Artificial Intelligence, AAAI 2020*, pages 2359–2366. AAAI Press, 2020.
- [HZCH19] Zhengxin Huang, Yuren Zhou, Zefeng Chen, and Xiaoyu He. Running time analysis of MOEA/D with crossover on discrete optimization problem. In *Conference on Artificial Intelligence, AAAI 2019*, pages 2296–2303. AAAI Press, 2019.
- [HZLL21] Zhengxin Huang, Yuren Zhou, Chuan Luo, and Qingwei Lin. A runtime analysis of typical decomposition approaches in MOEA/D framework for many-objective optimization problems. In *International Joint Conference on Artificial Intelligence, IJCAI 2021*, pages 1682–1688, 2021.
- [LTZ⁺02] Marco Laumanns, Lothar Thiele, Eckart Zitzler, Emo Welzl, and Kalyanmoy Deb. Running time analysis of multi-objective evolutionary algorithms on a simple discrete optimization problem. In *Parallel Problem Solving from Nature, PPSN 2002*, pages 44–53. Springer, 2002.
- [LZZZ16] Yuan-Long Li, Yu-Ren Zhou, Zhi-Hui Zhan, and Jun Zhang. A primary theoretical study on decomposition-based multiobjective evolutionary algorithms. *IEEE Transactions on Evolutionary Computation*, 20:563–576, 2016.
- [NSN15] Anh Quang Nguyen, Andrew M. Sutton, and Frank Neumann. Population size matters: rigorous runtime results for maximizing the hypervolume indicator. *Theoretical Computer Science*, 561:24–36, 2015.
- [OGNS20] Edgar Covantes Osuna, Wanru Gao, Frank Neumann, and Dirk Sudholt. Design and analysis of diversity-based parent selection schemes for speeding up evolutionary multi-objective optimisation. *Theoretical Computer Science*, 832:123–142, 2020.
- [QLZ22] Chao Qian, Dan-Xuan Liu, and Zhi-Hua Zhou. Result diversification by multi-objective evolutionary algorithms with theoretical guarantees. *Artificial Intelligence*, 309:103737, 2022.
- [QYT⁺19] Chao Qian, Yang Yu, Ke Tang, Xin Yao, and Zhi-Hua Zhou. Maximizing submodular or monotone approximately submodular functions by multi-objective evolutionary algorithms. *Artificial Intelligence*, 275:279–294, 2019.
- [Thi03] Dirk Thierens. Convergence time analysis for the multi-objective counting ones problem. In *Evolutionary Multi-Criterion Optimization, EMO 2003*, pages 355–364. Springer, 2003.

- [ZD22] Weijie Zheng and Benjamin Doerr. Better approximation guarantees for the NSGA-II by using the current crowding distance. In *Genetic and Evolutionary Computation Conference, GECCO 2022*, pages 611–619. ACM, 2022.
- [ZLD22] Weijie Zheng, Yufei Liu, and Benjamin Doerr. A first mathematical runtime analysis of the Non-Dominated Sorting Genetic Algorithm II (NSGA-II). In *Conference on Artificial Intelligence, AAAI 2022*, pages 10408–10416. AAAI Press, 2022.
- [ZQL⁺11] Aimin Zhou, Bo-Yang Qu, Hui Li, Shi-Zheng Zhao, Ponnuthurai Nagaratnam Suganthan, and Qingfu Zhang. Multiobjective evolutionary algorithms: A survey of the state of the art. *Swarm and Evolutionary Computation*, 1:32–49, 2011.