



HAL
open science

Sensitivity analysis for tolerance allocation of over-constrained mechanisms

Sonia C. García, Vincent Delos, Denis Teissandier

► **To cite this version:**

Sonia C. García, Vincent Delos, Denis Teissandier. Sensitivity analysis for tolerance allocation of over-constrained mechanisms. *Procedia CIRP*, 2022, 114, pp.123-128. 10.1016/j.procir.2022.10.018 . hal-04037081

HAL Id: hal-04037081

<https://hal.science/hal-04037081v1>

Submitted on 20 Mar 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial - NoDerivatives 4.0 International License

17th CIRP Conference on Computer Aided Tolerancing

Sensitivity analysis for tolerance allocation of over-constrained mechanisms

Sonia C. García^{a,*}, Vincent Delos^b, Denis Teissandier^a

^aUniv. Bordeaux, I2M, UMR 5295, F-33400 Talence, France

^bCNRS, I2M, UMR 5295, F-33400 Talence, France

Abstract

During the manufacturing process of a product, variability in its parts is unavoidable. Tolerance analysis allows estimating the consequences of the component's deviation of a mechanism on its functionality. Nowadays, it is possible to determine the contribution of each surface and/or contact on the final result in isostatic mechanisms by using the tools already presented in the literature; however, it is still a challenge to do so in over-constrained mechanisms. In previous works, we introduced a method based on prismatic polyhedra to model over-constrained mechanisms. In this paper, several simulations based on the previous approach are performed, varying the tolerances of the surfaces and contacts of the mechanism. The use of statistical methods to analyze the previous simulations' data is proposed to quantify the contribution of local deviations with respect to the total variation of the mechanism. This analysis determines the most relevant contacts, hence the most critical parts of the mechanism. The process is applied to a pump as an over-constrained case study and uses the prismatic polyhedra method for tolerance analysis.

© 2022 The Authors. Published by Elsevier B.V.

This is an open access article under the CC BY-NC-ND license (<https://creativecommons.org/licenses/by-nc-nd/4.0>)

Peer-review under responsibility of the scientific committee of the 17th CIRP Conference on Computer Aided Tolerancing

Keywords: Tolerance analysis; Sets of constraints; Polyhedra-based method; Design of experiments; Factorial design; Sensitivity analysis

1. Introduction

Dimensional and geometrical deviations on the components of a mechanism are unavoidable due to manufacturing and measurement imperfections [21]. To limit those deviations, the designer must specify and allocate tolerances. The assigned tolerance values affect not only the functionality of the mechanical system but its quality, and the manufacturing cost of its parts [10].

Traditionally, there are two complementary approaches in tolerance design: i) the first approach, known as *tolerance analysis*, consists in analyzing the functionality of a product taking into account the variabilities of the individual parts, and calculating the resultant assembly variation and yield; ii) the second approach, called tolerance synthesis (or tolerance allocation), consists in allocating tolerances to maintain proper functionality of the final product [14, 12].

Among the literature, the methods developed to do tolerance analysis can be classified into two approaches: the meth-

ods based on parametric approaches [1, 5, 22] and the methods based on sets of constraints (SOCs) [6, 7, 11]. The main advantage of the methods based on SOC is that they allow to model over-constrained mechanisms and characterize the geometric variation and the contacts. Among these methods we can find domains [11], T-Maps [7], polytopes [3] and prismatic polyhedra [2, 9].

The prismatic polyhedral approach's main advantage is that it allows working directly with unbounded sets in the 6-dimensional space of deviations, taking into account the degrees of freedom (DoFs) and reducing the calculation time since it does not limit virtually the DoFs through cap half-spaces.

Tolerance allocation is usually done to minimize the direct manufacturing cost or the sensitivity of tolerances to variations (design for quality and design for reliability) [13]. The assignment of design tolerances is typically performed on a trial and error method [16]. The compliance of the tolerances with the requirements is verified using tolerance analysis methods and, in case of non-compliance, uncritical tolerances are modified to satisfy the functional requirement [10].

Detection of critical tolerances in a system is usually related to robust design and tolerance sensitivity. Robust design aims to improve the quality of a product by minimizing the effects

* Corresponding author.

E-mail address: sonia.garcia-gomez@u-bordeaux.fr (Sonia C. García).

of variations without removing the causes; this means the minimization of sensitivity of a *performance parameter* concerning one or more uncertain variables [18].

There are several researches in the application of statistics for the tolerance analysis. In [22, 15] the authors used the GapSpace approach to ensure the assembly conditions of assemblies of parts exhibiting statistical variability. In [19], Skowronski and Turner proposed a method of statistical tolerance analysis that calculates the effect of tolerance values on assembly dimension and provides an estimate of the gradient (design function sensitivities). In [13], Kusiak and Feng used the design of experiments (DOE) approach based on the fractional factorial experiment to minimize the sensitivity of tolerances with respect to manufacturing variations in a probabilistic case using statistical analysis (ANOVA). Shoukr et al. [17] also used DOE to minimize the manufacturing cost; and instead of solving the optimization problem for all dimensional tolerances, it is solved for the significant dimensions only and the insignificant dimensional tolerances are set at lower control levels, here the significant dimensions were also found using statistical analysis (in this case ANOM).

The former applications have been performed on isostatic mechanisms, and over-constrained mechanisms have not been treated yet. This paper aims to determine the critical tolerances of an over-constrained mechanism during the tolerance analysis by means of statistical methods. The polyhedral approach is used to model the tolerance variations and calculate the cumulative stack-up of variations in the system. A factorial design is used to define the number of simulations and the input set of tolerances in each simulation. Finally, a linear regression method and the statistical method (ANOVA) is used to determine which tolerances have a statistically significant effect on the resulting stack-up of variations of the mechanical system.

The article is subdivided into three major parts: firstly, section 2 presents the tolerance model that will be used to calculate the stack-up of variations in a study case that will be presented all along the paper to illustrate an application of the methodology. After, section 3 illustrates the creation of the factorial design, defining the independent variables and the response variable of the tolerance problem. Section 4 shows the results of the statistical analysis. Finally, the conclusions and future work are presented. The application is made taking as hypotheses: i) no form defect in surfaces, ii) no local strain due to the contact and iii) no deformable parts. It is important to specify that in this work, statistics is not used to model the statistical variability of the defects but the statistical significance of the operands in the stack-up of the tolerance analysis.

2. Polyhedral approach

The polyhedral approach, or prismatic polyhedra method, introduced in [9] models each SOC through a six-dimensional prismatic polyhedron. Prismatic polyhedra allow modelling the bounded displacements and the DoFs of a system simultaneously. Mathematically, a prismatic polyhedron Γ can be decomposed into a polytope P (bounded displacements) and a set of

straight-lines $\sum \Delta_j$ representing the degrees of freedom (DoFs),

$$\Gamma = P \oplus \sum_j \Delta_j \quad (1)$$

Once all the geometrical and contact polyhedra are calculated, the tolerance reduction of a mechanical system is made by combining them. Minkowsky sums are used for serial contacts and intersections for parallel contacts. In the end, it is possible to determine the relative location between the two handle surfaces (the surfaces among which the functional requirement is defined) in the mechanical system. Finally, the system conformity is verified if the resulting SOC is inside the functional SOC, modelling the functional requirement. Figure 1 depicts the former process.

A pump will be used as an example all along the paper to illustrate the method. This pump is conformed mainly of what we will call the shaft (impeller + the central rotating shaft) and the housing. The housing is made up of two parts joined through four pins (see Figure 2). Two degrees of mobility are allowed between the shaft and the housing (rotation and translation along x). No degree of mobility is permitted between the two parts of the housing, the type of joint between them is hyper-static. The proper functioning of the pump depends on the coaxiality between the impeller and the housing.

According to the enumeration of the parts and the surfaces (Figure 2), the topological model of the assembly is presented in Figure 3. In the contact graph, nodes designated as (α, β) represent the nominal model of the part when $\beta = 0$, and the substitute surfaces when $\beta \neq 0$. The geometrical and contact deviations presented in the contact graph are going to be represented by geometric and contact polyhedra respectively.

The reduction of the contact graph to simulate the relative position of the handle surfaces (surfaces 3.3 and 1.7 identified in red on Figure 2) is made as follows:

$$\Gamma_R = \Gamma_{1.0/3.0} \oplus \Gamma_{1.7} \oplus \Gamma_{3.3} \quad (2)$$

where, Γ_R is the resulting polyhedron, $\Gamma_{1.7}$ and $\Gamma_{3.3}$ are the handle surfaces, and

$$\begin{aligned} \Gamma_{1.0/3.0} &= \Gamma_{1.0/3.0a} \cap \Gamma_{1.0/3.0b} \\ \begin{cases} \Gamma_{1.0/3.0a} &= \Gamma_{1.0/2.0} \oplus \Gamma_{2.6} \oplus \Gamma_{2.6/3.1} \oplus \Gamma_{3.1} \\ \Gamma_{1.0/3.0b} &= \Gamma_{1.6} \oplus \Gamma_{1.6/3.2} \oplus \Gamma_{3.2} \end{cases} \end{aligned} \quad (3)$$




Figure 1: Tolerance analysis with the polyhedral approach




Figure 2: Pump: CAD model, enumeration of parts and surfaces(handle surfaces in red), and section view to illustrate the joints between the components




Figure 3: Contact graph of the pump

with,

$$\Gamma_{1.0/2.0} = \Gamma_{1.0/2.0a} \cap \Gamma_{1.0/2.0b} \cap \Gamma_{1.0/2.0c} \cap \Gamma_{1.0/2.0d} \cap \Gamma_{1.0/2.0e}$$

$$\begin{cases} \Gamma_{1.0/2.0a} = \Gamma_{1.1} \oplus \Gamma_{1.1/2.1} \oplus \Gamma_{2.1} \\ \Gamma_{1.0/2.0b} = \Gamma_{1.2} \oplus \Gamma_{1.2/2.2} \oplus \Gamma_{2.2} \\ \Gamma_{1.0/2.0c} = \Gamma_{1.3} \oplus \Gamma_{1.3/2.3} \oplus \Gamma_{2.3} \\ \Gamma_{1.0/2.0d} = \Gamma_{1.4} \oplus \Gamma_{1.4/2.4} \oplus \Gamma_{2.4} \\ \Gamma_{1.0/2.0e} = \Gamma_{1.5} \oplus \Gamma_{1.5/2.5} \oplus \Gamma_{2.5} \end{cases}$$

123 The projections of the geometrical polyhedra in the sub-
 124 space of the bounded displacements of the contact polyhedron
 125 of each edge is homothetic. The former means that the
 126 Minkowsky sum of the three elements of each edge is a homo-
 127 thetic transformation of its contact polyhedra. Equations 2, 3
 128 and 4 are simplified and rewritten to:

$$\Gamma_R = \Gamma_{1.0/3.0} \oplus \frac{\lambda_8}{2} \Gamma_{1.7} \oplus \frac{\lambda_9}{2} \Gamma_{3.3} \quad (5)$$

with,

$$\Gamma_{1.0/3.0} = \Gamma_{1.0/3.0a} \cap \frac{\lambda_1}{2} \Gamma_{1.6/3.2} \text{ with,}$$

$$\Gamma_{1.0/3.0a} = \Gamma_{1.0/2.0} \oplus \frac{\lambda_2}{2} \Gamma_{2.6/3.1}$$

$$\Gamma_{1.0/2.0} = \frac{\lambda_3}{2} \Gamma_{1.1/2.1} \cap \frac{\lambda_4}{2} \Gamma_{1.2/2.2} \cap \frac{\lambda_5}{2} \Gamma_{1.3/2.3} \cap \frac{\lambda_6}{2} \Gamma_{1.4/2.4} \cap \frac{\lambda_7}{2} \Gamma_{1.5}^1 \quad (6)$$

129 where each polyhedron operand is defined as

$$\Gamma = \bigcap_{i=1}^k \{ \mathbf{x} \in \mathbb{R}^6 : 1 + a_{i1}x_1 + \dots + a_{i6}x_6 \geq 0 \} \quad (7)$$

130 and, λ_i with $i = 1 \dots 9$ are the sums of the tolerances of
 (4)131 each edge. Changing the value of the λ_i coefficients in the for-

¹ The contact between the two planar surfaces is null and the two polyhedra, $\Gamma_{1.5}$ and $\Gamma_{2.5}$, are homothetic

mer equations results in a homothetic transformation of the operands without changing their topology.

Once the reduction of the contact graph is made, it is necessary to verify the compliance of the system with respect to the functional condition Γ_T . The calculation of the functional condition is made by doing the Minkowsky sum of the prismatic polyhedra of the handle surfaces, and the compliance verification is done in a two steps way[9] checking:

- the kinematic compliance of the mechanical system
- the functional tolerance compliance

All the operands involved in the Equations 5 and 6 are created with the open-source software PolitoCAT [8] and calculated at the point $M(5, 0, 0)$. Each feature with non-linear boundaries is discretized in 8 points. This number of points seems to be a good compromise between precision and computation efficiency, as discussed in [3].

3. Design of experiments

Design of experiments is a statistical tool that allows to manipulate multiple input factors and to determine their effect on a desired output (response)[4]. There are different types of design of experiments: one-at-a-time (OAT) analysis, Factorial designs, Taguchi's design and Space-filling design.

3.1. Factorial design methodology

To perform a factorial design, it is necessary first to define the independent variables, also known as *factors*, and the values that they are going to take along the experimentation (*levels*). The number of levels and factors will define the total amount of experiments required; for example, in a two-level full factorial design with M factors, the necessary amount of experiments is 2^M , in three-level designs it is 3^M , and so on. Once the factors and levels are set, the response variable, also called the dependent variable, must be identified.

In the pump, the factors are the tolerances and clearances that modify the prismatic polyhedra involved in the tolerance




Figure 4: Graphical representation of the independent variables in the contact graph of the pump

reduction, see Equation 5 and Figure 4. The factors ($\lambda_1 \dots \lambda_9$) are independent and can vary continuously in between their respective limits. The minimum value of the factors V_{min} is 0.002 to avoid some numerical issues while operating with null operands. The maximum value of the factors V_{max} were calculated using Least Material Condition (LMC), see Table 1.

The response variable of the “experiment” has to be related to the resulting polyhedron, but it cannot be the polyhedron itself because it is embedded in a 6-dimensional space. In section 2, it is highlighted that to achieve the compliance of the mechanical system with respect to the functional condition, it is necessary to verify the tolerance and the kinematic compliance. The kinematic compliance is directly related to the DoFs of the system, and the variation of the tolerances cannot modify it. On the other hand, tolerance compliance can be modified while varying the system’s tolerances since this variation changes the topology of the polytope of the resulting polyhedron. Hence, the volume of the polytope of the polyhedron seems a good indicator of the variation of the resulting polyhedron due to the set of tolerances of the system(the factors).

The objective of the “experiment”(simulation) is to ascertain the relative importance of each of the factors presented in Table 1 on the volume of polytope of the resulting polyhedron Vol_{P_R} . Here we will use a Two-level Full Factorial Design, meaning that there will be 2^9 different combinations of the levels.

Figure 5 illustrates the process to carry on two simulations (A and B). In the first step, the parameters (λ_i) are set, and the tolerance reduction is made to obtain the resulting polyhedron for each simulation. The 3D prismatic polyhedra presented in the figure, are 6D projections into the sub-space of translations in y (t_y) and z (t_z) and the rotation along x (r_x). Since r_x is a DoF of the system, both the target and the resulting polyhedron must include it to fulfill the kinematic compliance; in the Figure 5, this DoF is represented using a straight line. Finally, as the result of the simulation, the volume of the polytope (describing the bounded displacements) is obtained. Until here, it is possible to know which is the result of a tolerance reduction and determine if the resulting polyhedron is compliant with the target; however, it is still not possible to understand which parameters impact the variation of the resulting polyhedron.

Once all the simulations have been carried on, the statistical analysis can be made. Since the dependent variable of the simulations Vol_{P_R} is neither categorical nor ordinal, it is possible to use the analysis of variance (ANOVA) to determine which independent variables have a statistical impact on the dependent

Table 1: Independent variables for the DOE of the Pump

Variable	Edge or surface	V_{min}	V_{max}
λ_1	2.6 – 3.1	0.002	0.062
λ_2	1.6 – 3.2	0.002	0.062
λ_3	1.1 – 2.1	0.002	0.056
λ_4	1.2 – 2.2	0.002	0.056
λ_5	1.3 – 2.3	0.002	0.056
λ_6	1.4 – 2.4	0.002	0.056
λ_7	1.5 – 2.5	0.002	0.02
λ_8	1.7	0.002	0.015
λ_9	3.3	0.002	0.015




Figure 5: Process to follow to execute two simulations A and B, each one with its own set of parameters, and to obtain the correspondent response variable

variable. The results of the ANOVA is reliable if three assumptions about the dependent variable scores are fulfilled:

- Normality
- Independence
- Homoscedasticity

The resulting statistical tests can be misleading when the independence assumption is violated. Violations of normality are less problematic, “results from various studies that considered up to 10 variables and small or moderate sample sizes indicate that deviation from multivariate normality has only a small effect on type I error”[20].

In general, the null hypothesis for an ANOVA is that there is no significant difference among the groups, which means that the factor has no statistical effect on the dependent variable. The decision rule for accepting or rejecting a null hypothesis is:

- If the P-value is bigger than the significance level (usually 0.05), the null hypothesis cannot be rejected.
- If the P-value is equal to or smaller than the significance level, the null hypothesis is rejected

4. Results and discussion

The statistical analysis is performed using Python’s function Ordinary Least Squares (OLS). The results obtained are presented in Table 2. After running the test of independence, normality and homoscedasticity. Normality is not fulfilled; however, since normality violation has a small effect on the risk making error type I, this is not going to be considered.

In Table 2, it is possible to notice that some factors do not affect the dependent variable. The statistical analysis is performed again while eliminating the variable with a bigger p-value each time until obtaining a statistically significant set of variables, see Table 3.

The results obtained through the ANOVA show that the most significant edge is the one related to the cylindrical pair between the right housing and the shaft (factor λ_2). The two han-

Table 2: Summary of the complete statistical analysis with ANOVA (Factors: all the tolerances - Response variable: Vol_{P_R})

Variable	coef	p - value
λ_1	0.0443	0.17
λ_2	0.8402	0
λ_3	0.0262	0.378
λ_4	0.0027	0.927
λ_5	0.024	0.42
λ_6	-0.0061	0.838
λ_7	0.0424	0.153
λ_8	0.1833	0
λ_9	0.2332	0

R-squared	0.721
Adj. R-squared	0.713

Table 3: Summary of the complete statistical analysis with ANOVA (Factors: just the statistically significant tolerances - Response variable: Vol_{P_R})

Variable	coef	p - value
λ_2	0.8568	0
λ_8	0.1819	0
λ_9	0.2316	0

R-squared	0.716
Adj. R-squared	0.713

dle surfaces (λ_8 and λ_9) are also statistically significant, and the other variables do not seem to affect the dependent variable in a meaningful way.

The two handle surfaces were expected to be significant since they are the same surfaces with which the functional requirement is calculated, so this result validates the proposed method. Following this idea, the fact that λ_2 has a bigger significance value than the two handle surfaces was surprising; however, in Table 1 it is possible to notice that the range of variation of λ_2 is more than 4 times the range of variation of λ_8 and λ_9 what can justify this result.

The connection between the two parts of the housing seems not to be significant; this result is interesting because this is the part of the mechanism that makes it over-constrained. The former can be explained because the contact between the housing components and the contact between the housing-left and the shaft are in serie between them, and their Minkowski sum is in parallel with the one related to λ_2 . Since parallel architectures are reduced by means of the intersection of the operands and both operands (the one resulting of the Minkowski sum

and the one related to λ_2) are in the same subspace of bounding displacements, it is only the smaller polyhedron the one that is going to preponderate.

5. Conclusions and perspectives

In this paper, the DOE was proposed to be used to determine the most critical tolerances in over-constrained mechanisms. The polyhedral approach is used to model the stack-up of deviation of the mechanical system and the volume of the resulting polyhedron is used like response variable for the DOE.

In the results obtained with the statistical analysis (ANOVA), the handle surfaces were statistically significant, meaning that they are critical surfaces, as expected. In the study case used, the pump, it seems that the over-constrained joint between the two housing components is not critical. It is worth mentioning that this analysis is valid only for this mechanical system with this specific functional condition. If the functional condition and/or the mechanical system changes all the process has to be made again. As stated in the results, the assumption of normality has not been fulfilled; it can be worth it to do further studies by using non-parametric approaches or other statistical tools to treat this kind of data.

The results obtained in this paper are promising and can be used in future work related to tolerance synthesis. Since one of the tolerance synthesis's main objectives is optimizing the individual tolerances of the components of a mechanism, taking into account manufacturing and quality costs, detecting the critical tolerances can reduce the number of variables and simplify the optimization problem. Additionally, one of the biggest inconvenient while working with N-dimensional operands is to quantify the quality of the solution of a tolerance analysis process and not only the compliance with a given target; the introduction of the volume of the polytope as a criteria for the result can be a first step towards finding equivalent representation to criteria used normally in 1D such as range.

References

- [1] Anselmetti, B., 2013. CLIC: A Method for Geometrical Specification of Products. John Wiley & Sons, Inc. pp. 207–239. doi:10.1002/9781118587027.ch9.
- [2] Arroyave-Tobón, S., Teissandier, D., Delos, V., 2017a. Applying screw theory for summing sets of constraints in geometric tolerancing. Mechanism and Machine Theory 112, 255–271. URL: <http://www.sciencedirect.com/science/article/pii/S0094114X16305237>, doi:10.1016/j.mechmachtheory.2017.02.004.
- [3] Arroyave-Tobón, S., Teissandier, D., Delos, V., 2017b. Tolerance Analysis With Polytopes in HV-Description. Journal of Computing and Information Science in Engineering 17. doi:10.1115/1.4036558.
- [4] Box, G.E.P., Hunter, J.S., Hunter, W.G., 2005. Statistics for Experimenters: Design, Innovation, and Discovery. Wiley. Google-Books-ID: oYU-pAQAMAAJ.
- [5] Clozel, P., Rance, P.A., 2010. Mecamaster: a tool for assembly simulation from early design, industrial approach. Geometric Tolerancing of Products , 241–273.
- [6] Dantan, J.Y., Qureshi, A.J., 2009. Worst-case and statistical tolerance analysis based on quantified constraint satisfaction problems and Monte Carlo simulation. Computer-Aided Design 41, 1–12. doi:10.1016/j.cad.2008.11.003.
- [7] Davidson, J.K., Mujezinovic, A., Shah, J.J., 2002. A new mathematical model for geometric tolerances as applied to round faces. Journal of Mechanical Design , 609–622.
- [8] Delos, V., Teissandier, D., 2017. PolitoCAT and politopix. <http://i2m.u-bordeaux.fr/politopix.html>.
- [9] Delos, V., Teissandier, D., Malyshev, A., Nuel, G., García, S.C., 2021. Polyhedral-based Modeling and Algorithms for Tolerancing Analysis. Computer-Aided Design 141, 103071. URL: <https://www.sciencedirect.com/science/article/pii/S0010448521000828>, doi:10.1016/j.cad.2021.103071.
- [10] Dong, Z., Hu, W., Xue, D., 1994. New Production Cost-Tolerance Models for Tolerance Synthesis. Journal of Engineering for Industry 116, 199–206. doi:10.1115/1.2901931. publisher: American Society of Mechanical Engineers Digital Collection.
- [11] Giordano, M., Duret, D., Tichadou, S., Arrieux, R., 1992. Clearance space in volumic dimensioning. CIRP Annals , 565–568.
- [12] Karmakar, S., Maiti, J., 2012. A Review on Dimensional Tolerance Synthesis: Paradigm Shift from Product to Process. Assembly Automation 32. doi:10.1108/01445151211262438.
- [13] Kusiak, A., Feng, C.X., 1995. Deterministic tolerance synthesis: a comparative study. Computer-Aided Design 27, 759–768. doi:10.1016/0010-4485(94)00028-C.
- [14] Morse, E., Dantan, J.Y., Anwer, N., Söderberg, R., Moroni, G., Qureshi, A., Jiang, X., Mathieu, L., 2018. Tolerancing: Managing uncertainty from conceptual design to final product. CIRP Annals 67, 695–717. doi:10.1016/j.cirp.2018.05.009.
- [15] Morse, E.P., 2004. Statistical Analysis of Assemblies Having Dependent Fitting Conditions, American Society of Mechanical Engineers Digital Collection. pp. 91–95. URL: <https://asmedigitalcollection.asme.org/IMECE/proceedings/IMECE2004/47055/91/309031>, doi:10.1115/IMECE2004-61664.
- [16] Sfantsikopoulos, M., 1990. A cost-tolerance analytical approach for design and manufacturing. The International Journal of Advanced Manufacturing Technology 5, 126–134. doi:https://doi.org/10.1007/BF02601602.
- [17] Shoukr, D.S.L., Gadallah, M.H., Metwalli, S.M., 2017. The Reduced Tolerance Allocation Problem, American Society of Mechanical Engineers Digital Collection. doi:10.1115/IMECE2016-65848.
- [18] Singh, P.K., Jain, P.K., Jain, S.C., 2009. Important issues in tolerance design of mechanical assemblies. Part 2: Tolerance synthesis doi:10.1243/09544054jem1304b.
- [19] Skowronski, V.J., Turner, J.U., 1997. Using Monte-Carlo variance reduction in statistical tolerance synthesis. Computer-Aided Design 29, 63–69. URL: <https://www.sciencedirect.com/science/article/pii/S0010448596000504>, doi:10.1016/S0010-4485(96)00050-4.
- [20] Stevens, J.P., 2009. Applied Multivariate Statistics for the Social Sciences. Taylor & Francis. Google-Books-ID: QMGjsQLmUC.
- [21] Walter, M., Wartzack, S., 2013. Statistical Tolerance-Cost-Optimization of Systems in Motion Taking into Account Different Kinds of Deviations, in: Abramovici, M., Stark, R. (Eds.), Smart Product Engineering, Springer, Berlin, Heidelberg. pp. 705–714. doi:10.1007/978-3-642-30817-8_69.
- [22] Zou, Z., Morse, E., 2003. Statistical Tolerance Analysis Using GapSpace, in: Geometric Product Specification and Verification: Integration of Functionality: Selected Conference Papers of the 7th CIRP International Seminar on Computer-Aided Tolerancing, held at the École Normale Supérieure de Cachan, France, 24–25 April 2001. Springer Netherlands, Dordrecht, pp. 105–114. URL: https://doi.org/10.1007/978-94-017-1691-8_11, doi:10.1007/978-94-017-1691-8_11.