

ANALYSIS OF SCHWARZ METHODS FOR CONVECTED HELMHOLTZ LIKE EQUATIONS

Martin J. Gander, Antoine Tonnoir

► To cite this version:

Martin J. Gander, Antoine Tonnoir. ANALYSIS OF SCHWARZ METHODS FOR CONVECTED HELMHOLTZ LIKE EQUATIONS. SIAM Journal on Scientific Computing, 2024, 46 (1), pp.A1-A22. 10.1137/23M1560057 . hal-04038452

HAL Id: hal-04038452 https://hal.science/hal-04038452v1

Submitted on 20 Mar 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés. 1 2

3

35

36

37

38 39

40

41

ANALYSIS OF SCHWARZ METHODS FOR CONVECTED HELMHOLTZ LIKE EQUATIONS

M.J. GANDER, AND A. TONNOIR

Abstract. We present and analyze Schwarz domain decomposition methods for a general diffu-4 sion problem with complex advection. The complex advection term changes completely the nature 5 6 of the solution and makes it more Helmholtz like. We analyze in detail the influence of the outer boundary conditions on the performance of the Schwarz algorithm, including PML conditions to emulate free space problems, and optimized transmission conditions, also for multiple subdomains. 8 Our results show that the performance of Schwarz methods for such Helmholtz like problems is 9 much better on free space configurations than in waveguides or closed cavities. Equations with com-11 plex advection appear in diverse applications, for example the convected Helmholtz equation, the Gross-Pitaevskii equation, Schrödinger equations, and also as important component in the wave-ray 13 multigrid algorithm for Helmholtz problems. We show as an example the performance of our Schwarz 14methods for a potential flow around a schematic submarine.

15 Key words. Complex advection, convected Helmholtz equation, Schwarz methods.

16 **MSC codes.** 65M55, 65N55, 65F10.

17 1. Introduction. We are interested in solving numerically a partial differential 18 equation (PDE) with a complex (!) advection term of the form

19 (1.1)
$$-\operatorname{div}(A\nabla u) + i\mathbf{a} \cdot \nabla u + \mu u = f \quad \text{in} \quad \Omega, \quad i := \sqrt{-1},$$

where Ω is a subset of \mathbb{R}^2 , A is a 2 × 2 positive definite matrix function, μ is a real function and **a** is a vector function in \mathbb{R}^2 . We will assume that the source term f is compactly supported, and (1.1) must be equipped with appropriate boundary conditions that we will specify later. Equation (1.1) is very different from a classical advection diffusion equation with real advection term, and can have Helmholtz character even when μ has the good sign, i.e. $\mu \geq 0$. Equation (1.1) appears in various contexts:

• The convected Helmholtz equation: in this case, $\mu = -\omega^2$ with ω the pulsation of the wave, $\mathbf{a} = -2\omega\mathbf{v}$ with \mathbf{v} the underlying flow (with convention $e^{-i\omega t}$ for the time variable), and the solution u represents a pressure field. If the underlying flow is assumed to be incompressible, then we have

- $A = c_0^2 \mathrm{Id} \mathbf{v} \, \mathbf{v}^T,$
- with $c_0 > 0$ the sound speed, see e.g. [36, 3, 5]. Note that to ensure that the matrix A is positive definite, the flow speed **v** must be small enough with respect to the sound speed c_0 (under mach 1).
 - The Gross-Pitaevskii equation: equation (1.1) also appears as an intermediate problem for computing ground states of the Gross-Pitaevskii equation (which consists in solving a minimization problem), see [11, p.1107] or [2]. Solving equation (1.1) is an essential ingredient to compute the Sobolev gradient of the cost functional.
 - The linearized Schrödinger equation: when looking for traveling wave solutions of the form $\psi(t, \mathbf{x}) = u(\mathbf{x}-\mathbf{a}t)$ to the linearized Schrödinger equation

42
$$i\partial_t \psi + \frac{1}{2}\Delta \psi - V\psi = 0,$$

43 see [7] or [10, p.198], equation (1.1) appears with $A = \frac{1}{2}$ Id and $\mu = V$.

• The ray equation: equation (1.1) also appears as a fundamental ingredient in the wave-ray multigrid method for solving the Helmholtz equation [9, 33, 34, 38],

$$-\Delta \tilde{u} - \omega^2 \tilde{u} = 0,$$

4

44 45

46 47

48 when seeking the ray component of the form $\tilde{u}(\mathbf{x}) = e^{i\mathbf{k}\cdot\mathbf{x}}u$, where **k** is a given 49 direction in \mathbb{R}^2 satisfying the dispersion relation $\|\mathbf{k}\|_2^2 = \omega^2$. Then, u satisfies 50 equation (1.1) with A = Id, $\mathbf{a} = -2\mathbf{k}$ and $\mu = 0$.

51 When equipped with classical Dirichlet, Neumann or Robin (impedance) boundary 52 conditions (BCs), one can show that problem (1.1) is of Fredholm type, since the 53 operator $-\operatorname{div}(A\underline{\nabla}\cdot) + \cdot$ is coercive. We deduce then that the problem is of type 54 *coercive* + *compact*, see [3, p.6], and therefore admits a unique solution, except for at 55 most a countable set of parameters.

Depending on the situation of interest from the list above, we will consider Dirichlet, Neumann or Robin BCs. Furthermore, we will also consider the case where we have Perfectly Matched Layers (PMLs) surrounding the domain of interest, which is important for wave-like problems on unbounded domains. The derivation of the PML formulation is not straightforward for equations of the type (1.1), see for instance [5, 36] for the convected Helmholtz equation, and we will briefly recall the PML construction hereafter.

Our goal is to analyze convergence properties of a Schwarz Domain Decompo-63 sition Method (DDM) with overlap using classical Fourier analysis, see [23, 15]. In 64 particular, we wish to emphasize the impact of considering PML to truncate the com-66 putational domain. There is an important body of literature dedicated to the study of Schwarz methods for the Helmholtz equation, see [25, 27, 29, 24, 28, 23, 21, 22, 13] 67 and reference therein. However, only few results exist for the convected Helmholtz 68 equation; an exception is the recent paper [32], in which the authors study a non-69 overlapping DDM for the convected Helmholtz equation. In fact, in the case of con-70 71stant parameters A, **a** and μ , one can reformulate, as we explain hereafter, equation 72(1.1) as a classical Helmholtz equation, using an appropriate change of variables. This shows in particular that we will clearly face the same difficulties as in the Helmholtz 73 case [17] for solving (1.1), but we can also benefit from the results known for the 74 Helmholtz case. 75

The rest of our paper is organized as follows: First in section 2 we recall the 76 77 link between the classical Helmholtz equation and equation (1.1), and explain how we can derive a stable PML formulation and first order Absorbing BCs (ABCs). Then, 78in section 3 we present a Fourier analysis of a Schwarz DDM considering vertical 79 slicing and Robin transmission conditions. We study the impact of various outer 80 PML truncations on the performance of the method, and explain how to properly 81 take them into account in the implementation. Finally, in section 4 we give some 82 concluding remarks. 83

Remark 1.1. Schwarz methods have been intensively studied for a formally similar equation, namely the advection-diffusion equation, see [1, 26, 16], but the mathematical character of this equation with real advection term is very different from our equation (1.1). Also, the anisotropic aspect of diffusion was studied for Schwarz methods in [20, 19], but again without the fundamentally character changing term of the complex advection in (1.1).

2. Reformulation as a Helmholtz equation and related results. In this section, as well as for the analysis in the next section, we will suppose that A, a and μ are constant parameters. Note that for the construction of ABCs and for the PML formulation, a generalization to locally perturbed parameters is possible.

2.1. Link with the Helmholtz equation. For the convected Helmholtz equation, in the case of constant parameters, it is well-known that there exist coordinate transformations that map the convected Helmholtz equation into the Helmholtz equation, see [36, 30]. Let us explain a similar idea for (1.1), namely to consider $u(\mathbf{x}) = v(\mathbf{x})e^{i\mathbf{k}\cdot\mathbf{x}}$ with \mathbf{k} to be suitably chosen later. Then, we have

99
$$\nabla u = (\nabla v)e^{i\mathbf{k}\cdot\mathbf{x}} + ve^{i\mathbf{k}\cdot\mathbf{x}}i\mathbf{k},$$

100 and

div
$$(A\nabla u) = \operatorname{div}(A\nabla v)e^{i\mathbf{k}\cdot\mathbf{x}} + 2iA\nabla v\cdot\mathbf{k}e^{i\mathbf{k}\cdot\mathbf{x}} - v\|\mathbf{k}\|_A^2e^{i\mathbf{k}\cdot\mathbf{x}},$$

where we denote by $\|\mathbf{k}\|_A^2 := A\mathbf{k} \cdot \mathbf{k}$. Introducing these results into (1.1), we get that v satisfies

104 (2.1)
$$-\operatorname{div}(A\nabla v) + \nabla v \cdot (i\mathbf{a} - 2iA\mathbf{k}) + (\mu + \|\mathbf{k}\|_A^2 - \mathbf{a} \cdot \mathbf{k})v = e^{-i\mathbf{k} \cdot \mathbf{x}}f.$$

105 If we choose now $\mathbf{k} := \frac{1}{2}A^{-1}\mathbf{a}$, equation (2.1) simplifies to

106 (2.2)
$$-\operatorname{div}(A\nabla v) + (\mu - \frac{\|\mathbf{a}\|_{A^{-1}}^2}{4})v = e^{-iA^{-1}\frac{\mathbf{a}}{2}\cdot\mathbf{x}}f.$$

107

108 Remark 2.1. Note that (2.2) is a classical Helmholtz problem if $\mu - \frac{\|\mathbf{a}\|_{A^{-1}}^2}{4} < 0$, 109 so even for $\mu \ge 0$, (1.1) has a Helmholtz character if $\frac{\|\mathbf{a}\|_{A^{-1}}^2}{4}$ is large enough: the 110 complex convection term is the reason for this Helmholtz character of equation (1.1).

111 Now, from (2.2), using an appropriate linear coordinate transformation of the form

112 (2.3)
$$\mathbf{x}' = S\mathbf{x},$$

113 we can rewrite the operator $\operatorname{div}(A\nabla \cdot)$ as a Laplace operator, because

114 (2.4)
$$\nabla \cdot = S^T \nabla' \cdot \implies \operatorname{div}(A \nabla \cdot) = \operatorname{div}'(SAS^T \nabla' \cdot)$$

and since A is symmetric positive definite, we can use the Cholesky decomposition A = GG^T and thus take $S = G^{-1}$ to simplify (2.4). Equation (2.2) then simplifies to

117 (2.5)
$$-\Delta' v' + (\mu - \frac{1}{4} \|\mathbf{a}\|_{A^{-1}}^2) v' = \tilde{f}',$$

118 where
$$v'(\mathbf{x}') = v(\mathbf{x})$$
 and $\tilde{f}'(\mathbf{x}') = e^{-\imath A^{-1} \frac{\mathbf{a}}{2} \cdot S^{-1} \mathbf{x}'} f(S^{-1} \mathbf{x}')$

119 Remark 2.2. In our case, the change of variables (2.3) preserves the vertical 120 boundaries, because the matrix $S = G^{-1}$ is lower triangular, so that

121
$$\{x = \alpha\} \iff \{x' = s_{11}\alpha\},\$$

where $s_{ij} = [S]_{i,j}$. In contrast, horizontal boundaries are deformed into oblique boundaries (if $a_{12} \neq 0$), in the same spirit as in [37].

3



FIG. 1. Example of using the ABC (2.6) with a point source in the center of the domain.

2.2. Derivation of a simple Absorbing Boundary Condition. The reformulation (2.5) as a Helmholtz equation is used in the literature for constructing ABCs for the convected Helmholtz equation, see [4], or PMLs [5, 36], albeit using a different change of variables (the choice is not unique). Suppose that $\mu - \frac{1}{4} ||\mathbf{a}||_{A^{-1}}^2 < 0$, then we can easily deduce the equivalent of the classical ABC for the Helmholtz equation (taking the convention $e^{-i\omega t}$ for the time variable):

(2.6)

$$\nabla' v' \cdot \mathbf{n}' - i\widetilde{\omega}v' = 0 \iff S^{-T} \nabla v \cdot \mathbf{n}' - i\widetilde{\omega}v = 0,$$

$$\iff A \nabla v \cdot \underbrace{(G^{-T}\mathbf{n}')}_{=\mathbf{n}/||G^T\mathbf{n}||} -i\widetilde{\omega}v = 0,$$

$$\implies A \nabla u \cdot \mathbf{n} - i\frac{1}{2}\mathbf{a} \cdot \mathbf{n}u - i\widetilde{\omega}||\mathbf{n}||_A u = 0,$$

where $\tilde{\omega} := \sqrt{-\mu + \frac{1}{4} \|\mathbf{a}\|_{A^{-1}}^2}$, and **n** is the normal on a given boundary surrounding the domain of computations. Note that this ABC for equation (1.1) is valid for any straight boundary since the classical ABC for the Helmholtz equation is valid on any straight line, no matter the orientation. If on the contrary we consider this condition on a circular boundary for the Helmholtz equation, then the boundary for equation (1.1) is no more a circle, see for instance [4, 35] for more details and higher order ABCs.

138 As a numerical illustration, we consider the convected Helmholtz problem

139 (2.7)
$$\begin{array}{rcl} -\operatorname{div}\left(A\nabla u\right) - 2\imath\omega\mathbf{v}\cdot\nabla u - \omega^{2}u &= \delta & \text{in }\Omega = (0,4)^{2}, \\ A\nabla u\cdot\mathbf{n} + \imath\omega\mathbf{v}\cdot\mathbf{n}u - \imath\widetilde{\omega}\|\mathbf{n}\|_{A}u &= 0 & \text{on }\partial\Omega, \end{array}$$

140 where δ is the Dirac source term, and $A = \text{Id} - \mathbf{v}\mathbf{v}^T$. We show in Figure 1 the 141 solution u we obtain using the ABC (2.6) for the model problem (2.7) with problem 142 parameters

143 (2.8)
$$\mathbf{v} := \operatorname{Ma} \begin{bmatrix} \cos(\theta) \\ \sin(\theta) \end{bmatrix}, \quad \theta = \frac{\pi}{4}, \quad \operatorname{Ma} = \frac{1}{2}, \quad \omega = 10.$$

2.3. Derivation of a Cartesian PML formulation. In this subsection, we will also assume that A is a diagonal matrix so that the coordinate transformation

¹In what follows, we will always assume that $\mu - \frac{1}{4} \|\mathbf{a}\|_{A^{-1}}^2 < 0$, since otherwise, the problem is coercive and has lost its difficult Helmholtz character.

(2.3) preserves both horizontal and vertical boundaries, since the matrix S is diag-146onal, which simplifies the construction of a Cartesian PML. We refer to [12] for the 147construction of a PML on a polygonal domain. We emphasize that the assumptions 148that the parameters are constant and A is diagonal are necessary only in the PML 149

150region. 151Under these hypotheses, it is well-known that the PML formulation for the Helmholtz equation in (x', y') coordinates reads 152

153 (2.9)
$$-\operatorname{div}'(D'_{PML}\nabla'v') + s'_{x'}s'_{y'}(\mu - \frac{1}{4}\|\mathbf{a}\|^2_{A^{-1}})v' = \widetilde{f}',$$

where 154

155
$$D'_{PML} = \begin{bmatrix} s'_{y'}/s'_{x'} & 0\\ 0 & s'_{x'}/s'_{y'} \end{bmatrix}.$$

The complex valued functions $s'_{x'}$ and $s'_{y'}$ are defined by 156

157 (2.10)
$$s'_{x'}(x') := \begin{cases} 1 & \text{if } x' \in (a' + \ell', b' - \ell'), \\ 1 + i\sigma_x & \text{otherwise,} \end{cases}$$

158and

159 (2.11)
$$s'_{y'}(y') := \begin{cases} 1 & \text{if } y' \in (c' + \ell', d' - \ell'), \\ 1 + i\sigma_y & \text{otherwise,} \end{cases}$$

where $\sigma_x > 0$ and $\sigma_y > 0$ are the strength of the PML in each direction, and $\ell' > 0$ is 160

the depth of the PML. In (x', y') coordinates, the computational domain would then 161

be the square $(a', b') \times (c', d')$. Returning to the (x, y) coordinates, we get 162

(2.12)
$$-\operatorname{div}'(D'_{PML}\nabla'v') + s'_{x'}s'_{y'}(\mu - \frac{1}{4}\|\mathbf{a}\|^2_{A^{-1}})v' = \widetilde{f}',$$
$$\iff -\operatorname{div}(A_{PML}\nabla v) + s_xs_y(\mu - \frac{1}{4}\|\mathbf{a}\|^2_{A^{-1}})v = \widetilde{f},$$

where 164

165
$$A_{\rm PML} = \begin{bmatrix} a_{11}s_y/s_x & 0\\ 0 & a_{22}s_x/s_y \end{bmatrix},$$

and $s_x(x) = s'_{x'}(x')$ and $s_y(y) = s'_{y'}(y')$. Recalling that $v(\mathbf{x}) = u e^{-i\frac{1}{2}A^{-1}\mathbf{a}\cdot\mathbf{x}}$, we get 166

167
$$A_{\rm PML}\nabla v = \left(A_{\rm PML}\nabla u - \imath u \frac{1}{2} A_{\rm PML} A^{-1} \mathbf{a}\right) e^{-\imath \frac{1}{2} A^{-1} \mathbf{a} \cdot \mathbf{x}},$$

and, observing that A_{PML} depends on (x, y), 168

div
$$(A_{\text{PML}}\nabla v) = \left(\operatorname{div}(A_{\text{PML}}\nabla u) - i\frac{1}{2}\mathbf{a}_{\text{PML}}\cdot\nabla u -i\frac{1}{2}\operatorname{div}(u\mathbf{a}_{\text{PML}}) - u\frac{1}{4}\|\mathbf{a}\|_{\widetilde{A}_{\text{PML}}}^{2}\right)e^{-i\frac{1}{2}A^{-1}\mathbf{a}\cdot\mathbf{x}},$$

where 170171

$$\widetilde{A}_{\text{PML}}^{-1} := A^{-1} A_{\text{PML}} A^{-1}, \quad \mathbf{a}_{\text{PML}} := A_{\text{PML}} A^{-1} \mathbf{a}.$$



FIG. 2. Solution obtained using (on the left) the classical PML and (on the right) the modified PML.

Thus, inserting this expression into (2.12), we obtain the PML formulation for (1.1), namely

$$(2.13) -\operatorname{div}(A_{\mathrm{PML}}\nabla u) + i\frac{1}{2}\mathbf{a}_{\mathrm{PML}} \cdot \nabla u + i\frac{1}{2}\operatorname{div}(u\,\mathbf{a}_{\mathrm{PML}}) + s_x s_y (\mu - \frac{1}{4}\|\mathbf{a}\|_{A^{-1}}^2 + \frac{1}{4s_x s_y}\|\mathbf{a}\|_{\widetilde{A}_{\mathrm{PML}}^{-1}}^2) u = f.$$

Note that the PDE remains unchanged from the initial one in (1.1) in the physical region.

As a numerical illustration, let us consider once again problem (2.7), but this time with the problem parameters

179 (2.14)
$$\mathbf{v} := \mathcal{M}\begin{bmatrix}\cos(\theta)\\\sin(\theta)\end{bmatrix}, \quad \theta := 0, \quad \mathcal{M} := \frac{4}{5}, \quad \omega := 20$$

In Figure 2, we show the real part of the solution computed using a naive classical PML (left), which is known to have instabilites in some configurations, as we can clearly see here, and the PML formulation (2.13) (right), which works perfectly.

183 **3.** Fourier analysis of a classical Schwarz algorithm. We now present and 184 analyze Schwarz domain decomposition methods for (1.1) in a specific geometry: find 185 $u \in H^1(\Omega)$ satisfying

186 (3.1)
$$-\operatorname{div}(A\nabla u) + \iota \mathbf{a} \cdot \nabla u + \mu u = f \quad \text{in} \quad \Omega = (a, b) \times (c, d),$$

where A is a diagonal matrix, a < b and c < d with $\{a, b, c, d\} \in \mathbb{R}$. For the boundary conditions, we will consider four configurations:

- *Dirichlet-Dirichlet*: we impose homogeneous Dirichlet boundary conditions
 on both vertical and horizontal boundaries,
- Dirichlet-PML: we impose also homogeneous Dirichlet boundary conditions
 on the left and right but a PML on the bottom and top boundaries (which
 terminates with a homogeneous Dirichlet boundary condition),
 - *PML-Dirichlet*: the same idea but with PML on the vertical boundaries,
 - *PML-PML*: imposing PML on all sides of the domain.

194 195

The first case models a bounded domain, the second and third cases a waveguide with different orientation, and the last case a free space problem. We decompose the domain Ω first into two overlapping subdomains $\Omega_1 := (a, \beta) \times (c, d)$ and $\Omega_2 :=$ $(\alpha, b) \times (c, d)$ with $\alpha \leq \beta$, see Figure 3. We denote by $\Gamma_{1,2} := \{x = \beta\} \times (0, 1)$ the



FIG. 3. Domain decomposition for the model problem, from left to right: D-D, D-PML, PML-D and PML-PML. In blue we show the domain Ω_1 , in orange the domain Ω_2 and in gray the PML region. The overlapping area is delimited by the boundaries $\Gamma_{1,2}$ and $\Gamma_{2,1}$.

200 interface of Ω_1 (within Ω_2) and $\Gamma_{2,1} := \{x = \alpha\} \times (0,1)$ the interface of Ω_2 (within Ω_1).

201 Then, a general iterative Schwarz algorithm computes for iteration index n = 1, 2, ...

202 the subdomain solutions

$$(3.2) \quad \begin{array}{l} -\operatorname{div}(A\nabla u_{1}^{n}) + i\mathbf{a}\cdot\nabla u_{1}^{n} + \mu u_{1}^{n} = f_{1} & \text{in } \Omega_{1}, \\ u_{1}^{n} = 0 & \text{on } \partial\Omega_{1}\setminus\Gamma_{1,2}, \\ (a_{11}\partial_{x} + p_{1,2} - i\frac{a_{1}}{2})u_{1}^{n} = (a_{11}\partial_{x} + p_{1,2} - i\frac{a_{1}}{2})u_{2}^{n-1} & \text{on } \Gamma_{1,2}, \\ -\operatorname{div}(A\nabla u_{2}^{n}) + i\mathbf{a}\cdot\nabla u_{2}^{n} + \mu u_{2}^{n} = f_{2} & \text{in } \Omega_{2}, \\ u_{2}^{n} = 0 & \text{on } \partial\Omega_{2}\setminus\Gamma_{2,1}, \\ (-a_{11}\partial_{x} + p_{2,1} + i\frac{a_{1}}{2})u_{2}^{n} = (-a_{11}\partial_{x} + p_{2,1} + i\frac{a_{1}}{2})u_{1}^{n} & \text{on } \Gamma_{2,1}, \end{array}$$

where f^i is the restriction of f to Ω_i , $i \in \{1, 2\}$, and $p_{1,2}$, $p_{2,1}$ are complex constants. 204 We emphasize that when using PML, the algorithm should be written with complex 205 stretched coordinates, or equivalently with the PML formulation as described in sub-206section 2.3. Also, note that we consider here a particular Robin type transmission 207condition to get a condition similar to the ABC (2.6) at the interfaces. Moreover, in 208the PML formulation it is interesting to note that the boundary term coming from 209 the integration by parts of $\operatorname{div}(u\mathbf{a}_{PML})$ is canceled by this choice of transmission 210 condition, see Remark 3.3 for more details. 211

To study the convergence of the Schwarz algorithm (3.2) as n goes to infinity, we consider the error $u - u_i^n|_{\Omega_i}$, $i \in \{1, 2\}$, which amounts to consider the algorithm (3.2) with zero source terms. Using the equivalence with the Helmholtz equation, the iterative algorithm (3.2) for the error becomes

$$(3.3) \qquad \begin{array}{rcl} -\Delta'(v')_{1}^{n} - \widetilde{\omega}^{2}(v')_{1}^{n} &= 0 & \text{in } \Omega'_{1}, \\ (v')_{1}^{n} &= 0 & \text{on } \partial\Omega'_{1} \cap \Omega', \\ \left(\partial_{x'} + p'_{1,2}\right)(v')_{1}^{n} &= \left(\partial_{x'} + p'_{1,2}\right)(v')_{2}^{n-1} & \text{on } \Gamma'_{1,2}, \\ -\Delta'(v')_{2}^{n} - \widetilde{\omega}^{2}(v')_{2}^{n} &= 0 & \text{in } \Omega'_{2}, \\ (v')_{2}^{n} &= 0 & \text{on } \partial\Omega'_{2} \cap \Omega', \\ \left(-\partial_{x'} + p'_{2,1}\right)(v')_{2}^{n} &= \left(-\partial_{x'} + p'_{2,1}\right)(v')_{1}^{n} & \text{on } \Gamma'_{2,1}, \end{array}$$

217 where $\Gamma'_{1,2} := \{x' = \beta'\} \times (c', d')$ and $\Gamma'_{2,1} := \{x' = \alpha'\} \times (c', d')$, and

218 (3.4)
$$p'_{2,1} = \frac{p_{2,1}}{g_{11}}$$
 and $p'_{1,2} = \frac{p_{1,2}}{g_{11}}$,

and we recall that $(g_{ij})_{ij}$ are the coefficients of the lower triangular matrix G from the Cholesky decomposition $A = GG^T$. As a consequence, to study the convergence of the Schwarz algorithm (3.2), we will study the convergence of the algorithm rewritten for the Helmholtz equation (3.3). A similar idea of using an equivalent algorithm to remove the anisotropy and advection term can be found in [18]. 224 Remark 3.1. The choice of a diagonal matrix A ensures that in the reformulation 225 (3.3) the domain Ω' is still a square, which is important for the analytical solution we 226 use below.

227 Remark 3.2. From the reformulation (3.3) of the Schwarz algorithm (3.2), we can 228 obtain optimized transmission conditions, using the optimized parameters $p'_{1,2}$ and 229 $p'_{2,1}$ from [23] and relation (3.4).

230 Remark 3.3. For the implementation, in the PML context, the transmission con-231 ditions on $\Gamma_{1,2}$ and $\Gamma_{2,1}$ should be equivalently rewritten as

232
$$\frac{s_y}{s_x}a_{11}\partial_x u_1^n + \frac{s_y}{s_x}(p_{1,2} - i\frac{a_1}{2})u_1^n = \frac{s_y}{s_x}a_{11}\partial_x u_2^{n-1} + \frac{s_y}{s_x}(p_{1,2} - i\frac{a_1}{2})u_2^{n-1} \quad \text{on} \quad \Gamma_{1,2},$$

233 and

234
$$-\frac{s_y}{s_x}a_{11}\partial_x u_2^n + \frac{s_y}{s_x}(p_{2,1} + i\frac{a_1}{2})u_2^n = -\frac{s_y}{s_x}a_{11}\partial_x u_1^n + \frac{s_y}{s_x}(p_{2,1} + i\frac{a_1}{2})u_1^n \quad \text{on} \quad \Gamma_{2,1},$$

to get natural variational conditions. This is different from implementing the Després
like transmission conditions

237
$$\frac{s_y}{s_x}a_{11}\partial_x u_1^n + (p_{1,2} - i\frac{a_1}{2})u_1^n = \frac{s_y}{s_x}a_{11}\partial_x u_2^{n-1} + (p_{1,2} - i\frac{a_1}{2})u_2^{n-1} \quad \text{on} \quad \Gamma_{1,2},$$

238 and

239
$$-\frac{s_y}{s_x}a_{11}\partial_x u_2^n + (p_{2,1} + i\frac{a_1}{2})u_2^n = -\frac{s_y}{s_x}a_{11}\partial_x u_1^n + (p_{2,1} + i\frac{a_1}{2})u_1^n \quad \text{on} \quad \Gamma_{2,1},$$

which can lead to a divergent algorithm when algorithm (3.2) is convergent!

3.1. Computation of the convergence factor in the two subdomain case. We show the computations for the *PML-PML* case, the other cases can be deduced by simply taking $\sigma_x = 0$ or $\sigma_y = 0$, see equation (2.10) for the definition of σ_x and σ_y . We introduce the complex stretched coordinates in the modified coordinate system (x', y'),

246 (3.5)
$$\widetilde{x}'(x') = \begin{cases} x' + \imath \sigma (x' - (a' + \ell')) & \text{if } x' \in (a', a' + \ell'), \\ x' & \text{if } x' \in (a' + \ell', b' - \ell'), \\ x' + \imath \sigma (x' - (b' - \ell')) & \text{if } (b' - \ell', b'), \end{cases}$$

247 and

248 (3.6)
$$\widetilde{y}'(y') = \begin{cases} y' + i\sigma_y(y' - (c' + \ell')) & \text{if } y' \in (c', c' + \ell'), \\ y' & \text{if } y' \in (c' + \ell', d' - \ell'), \\ y' + i\sigma_y(y' - (d' - \ell')) & \text{if } y' \in (d' - \ell', d'). \end{cases}$$

Due to the rectangular geometry of the domain Ω' , and since A is assumed to be diagonal, we can use separation of variables to analytically obtain the errors in the Schwarz algorithm (3.3),

252 (3.7)
$$(v')_i^n = \sum_{k \in \mathbb{N}^*} \psi_k(y') \left(A_i^n(k) e^{i\lambda(\xi_k)\widetilde{x}'(x')} + B_i^n(k) e^{-i\lambda(\xi_k)\widetilde{x}'(x')} \right), \quad i \in \{1, 2\},$$

where $\lambda(\xi_k) = \sqrt{\tilde{\omega}^2 - \xi_k^2}$. The functions ψ_k and the complex numbers ξ_k are the eigenfunctions and eigenvalues of the eigenvalue problem

255 (3.8)
$$\begin{cases} -\partial_{\widetilde{y}'\widetilde{y}'}^{2}\psi_{k} = \xi_{k}^{2}\psi_{k} & \text{for } y' \in (c',d'), \\ \psi_{k} = 0 & \text{on } y' \in \{c',d'\}, \end{cases}$$

and we have, up to normalization 256

257 (3.9)
$$\psi_k \propto \sin(\xi_k (y' - c'))$$
 and $\xi_k = \frac{k\pi}{d' - c'}$ if $\sigma_y = 0$,

258and

259 (3.10)
$$\psi_k \propto \sin(\xi_k(\widetilde{y}'(y') - \widetilde{y}'(0)))$$
 and $\xi_k = \frac{k\pi}{d' - c' + 2i\ell'\sigma_y}$ if $\sigma_y > 0$.

260

Remark 3.4. If there is no horizontal PML ($\sigma_y = 0$), then the family $(\psi_k)_k$ is an 261 orthonormal basis of $L^2((c', d'))$. This does not hold any more when considering PML 262 $(\sigma_y > 0)$. In fact, although one can show that the family is a complete basis [31], it 263 264is neither an orthonormal basis nor a Riesz basis. A consequence of this result is that 265the decomposition (3.7) is still justified, but cannot be computed in practice given an 266 arbitrary Robin data on $\Gamma_{1,2}$ or $\Gamma_{2,1}$.

In the expressions (3.7), the amplitudes $A_i^n(k)$ and $B_i^n(k)$ should be chosen to satisfy 267the vertical BCs, namely 268

269

on Γ'₀ = {x' = a'} × (c', d') and Γ_{1,2} for i = 1,
and on Γ'₂ = {x' = b'} × (c', d') and Γ_{2,1} for i = 2, 270

the horizontal BCs on $(a', b') \times \{c', d'\}$ being already satisfied. To ensure these BCs, 271we must impose 272

273
$$B_1^n(k) = -A_1^n(k)e^{2i\lambda(\xi_k)(a'-i\sigma_x\ell')} \quad \text{and} \quad B_2^n(k) = -A_2^n(k)e^{2i\lambda(\xi_k)(b'+i\sigma_x\ell')}.$$

Now, the BC on $\Gamma'_{1,2}$ (on $x' = \beta'$) implies 274

275

$$A_{1}^{n}(k) \left[i\lambda(\xi_{k}) \left(e^{i\lambda(\xi_{k})\beta'} + e^{2i\lambda(\xi_{k})(a'-i\sigma_{x}\ell')}e^{-i\lambda(\xi_{k})\beta'} \right) + p_{1,2}' \left(e^{i\lambda(\xi_{k})\beta'} - e^{2i\lambda(\xi_{k})(a'-i\sigma_{x}\ell')}e^{-i\lambda(\xi_{k})\beta'} \right) \right]$$

$$= A_{2}^{n-1}(k) \left[i\lambda(\xi_{k}) \left(e^{i\lambda(\xi_{k})\beta'} + e^{2i\lambda(\xi_{k})(b'+i\sigma_{x}\ell')}e^{-i\lambda(\xi_{k})\beta'} \right) + p_{1,2}' \left(e^{i\lambda(\xi_{k})\beta'} - e^{2i\lambda(\xi_{k})(b'+i\sigma_{x}\ell')}e^{-i\lambda(\xi_{k})\beta'} \right) \right],$$

276so that

277

281

$$A_1^n(k) = \rho_1(k) A_2^{n-1}(k),$$

with the first convergence factor component 278

279 (3.11)
$$\rho_1(k) = \frac{\left(i\lambda(\xi_k) + p'_{1,2}\right) + e^{2i\lambda(\xi_k)(b' + i\sigma_x \ell' - 2\beta')} \left(i\lambda(\xi_k) - p'_{1,2}\right)}{\left(i\lambda(\xi_k) + p'_{1,2}\right) + e^{2i\lambda(\xi_k)(a' - i\sigma_x \ell' - 2\beta')} \left(i\lambda(\xi_k) - p'_{1,2}\right)}.$$

In the same way, we get using the BC on $\Gamma'_{2,1}$ (on $x' = \alpha'$) that 280

$$\begin{aligned} A_{2}^{n}(k) \left[-i\lambda(\xi) \left(e^{i\lambda(\xi_{k})\alpha'} + e^{2i\lambda(\xi_{k})(b'+i\sigma_{x}\ell')}e^{-i\lambda(\xi_{k})\alpha'} \right) \\ + p_{2,1}' \left(e^{i\lambda(\xi_{k})\alpha'} - e^{2i\lambda(\xi_{k})(b'+i\sigma_{x}\ell')}e^{-i\lambda(\xi_{k})\alpha'} \right) \right] \\ = A_{1}^{n}(k) \left[-i\lambda(\xi_{k}) \left(e^{i\lambda(\xi_{k})\alpha'} + e^{2i\lambda(\xi_{k})(a'-i\sigma_{x}\ell')}e^{-i\lambda(\xi_{k})\alpha'} \right) \\ + p_{2,1}' \left(e^{i\lambda(\xi_{k})\alpha'} - e^{2i\lambda(\xi_{k})(a'-i\sigma_{x}\ell')}e^{-i\lambda(\xi_{k})\alpha'} \right) \right], \end{aligned}$$



FIG. 4. Convergence factor ρ^{DD} (on the left) with $\rho^{DD}(1) \simeq 1.11$ (in blue), $\rho^{DD}(2) \simeq 0.463$ (in orange) and $\rho^{DD}(3) \simeq 0.202$ (in green). Error evolution versus iterations (on the right) initializing the error system with mode 1, 2 and 3 (curves in blue, orange and green respectively).

282 so that

283
$$A_2^n(k) = \rho_2(k) A_1^n(k),$$

285 (3.12)
$$\rho_2(k) = \frac{\left(-i\lambda(\xi_k) + p'_{2,1}\right) - e^{2i\lambda(\xi_k)(a' - i\sigma_x \ell' - \alpha')} \left(i\lambda(\xi_k) + p'_{2,1}\right)}{\left(-i\lambda(\xi_k) + p'_{2,1}\right) - e^{2i\lambda(\xi_k)(b' + i\sigma_x \ell' - \alpha')} \left(i\lambda(\xi_k) + p'_{2,1}\right)}.$$

Thus, the convergence factor of the Schwarz method is $\rho(k) = \rho_1(k)\rho_2(k)$. Let us emphasize once again that the convergence factor depends on the case considered (*D-D*, *D-PML*, *PML-D* or *PML-PML*) through σ_x but also through the eigenvalue problem (3.8).

As a numerical illustration, let us consider the wave-ray equation,

291 (3.13)
$$\begin{aligned} -\Delta u + i\mathbf{a} \cdot \nabla u &= 0 \quad \text{in } \Omega = (0,1)^2, \\ u &= 0 \quad \text{on } \partial\Omega, \end{aligned}$$

with $\mathbf{a} := (10,0)$. To solve this problem, we implemented algorithm (3.2) (not its equivalent Helmholtz formulation (3.3)) with the parameters

294 (3.14)
$$p_{12} = -i\widetilde{\omega}g_{11}$$
 and $p_{21} = -i\widetilde{\omega}g_{11}$,

which corresponds to $p_{12}' = p_{21}' = -i\widetilde{\omega}$ (and to the ABC (2.6)). We took $\alpha = 0.45$ 295and $\beta = 0.55$ so that the overlap is of size 0.1. In the *D-D* case, the convergence 296factor is shown in Figure 4 (where the variable k is "continuified" in the abscissa). 297 298Since we have $\rho(-k) = \rho(k)$, we show the convergence factor only for $k \ge 0$. The vertical dotted lines correspond to integer values of k. We see that the algorithm 299 is not convergent, since for the first (non-zero) mode, we have $\rho^{DD}(1) \simeq 1.115$. In 300 the same Figure, we also show the error evolution versus the iterations initializing 301 the error equations with mode k = 1, 2 and 3. We see that for modes 2 and 3, the 302 algorithm is convergent (as expected from the convergence factor) up to a point where 303 the round-off error makes the first mode appear, like in power iterations. Computing 304 the slopes of the three lines on the right gives the convergence factors $\rho^{DD}(1) \simeq 1.115$, 305 $\rho^{DD}(2) \simeq 0.463$ and $\rho^{DD}(3) \simeq 0.202$, matching well the theoretical prediction on the 306 left. 307

For the same example, we show the convergence factors ρ^{DD} , ρ^{DPML} , ρ^{PMLD} and ρ^{PMLPML} in Figure 5. For the PML parameters, we took $\sigma_x = \sigma_y = 10$ and



FIG. 5. Convergence factor ρ^{DD} (top left), ρ^{DPML} (top right), ρ^{PMLD} (bottom left) and ρ^{PMLPML} (bottom right).

 $\ell' = 0.1$. We see that the convergence factor is highly influenced by using a PML on 310 the outer boundary. In particular, the more we open the domain by adding PMLs, 311 the better the convergence factor becomes. This can be understood for wave like 312 problems in the sense that when the domain is open, error components can leave the 313 314 domain to infinity, or equivalently they are damped by the PML which emulates the unbounded domain. Other boundary conditions reflect these error components and 315 inject them back into the iteration, leading to worse convergence, or even divergence. 316 A second remark we can make for waveguide problems, corresponding to the D-317 *PML* and *PML-D* cases, is that cutting the waveguide in the infinite direction or in 318 the transverse direction is very different. Indeed, in the *PML-D* case, the convergence 319 factor is good for small k, whereas in the the D-PML case, the convergence factor is 320 better for larger k, 321

A last remark is the fact that computing the convergence factor in a vertical 322 waveguide $\Omega' = (a', b') \times \mathbb{R}$ using a Fourier transform in the y'-direction would lead 323 exactly to the same convergence factor as in the D-D case, since the only change is the continuous summation with eigenfunctions $e^{i\xi y}$ which replaces the discrete 325 summation, but the computed solution and performance of the Schwarz method is 326 327 very different in an open wave guide or a closed cavity. In contrast, using a horizontal PML as in the *D-PML* case leads to a very different convergence factor, whereas the 328 computed Schwarz iterates in the physical domain correspond to the solution in the 329 unbounded domain! This shows that the two-subdomain analysis is very different if 330 we consider the PML or not. 331

Remark 3.5. Note that if the PML parameters σ_x and σ_y are too large, then the convergence factor deteriorates. In particular, if $\sigma_x = \sigma_y = \sigma \to +\infty$, we do not recover the convergence factor one would get in the full space \mathbb{R}^2 , as in [23]. However, we recover this convergence factor if the length of the PML tends to $+\infty$.

336 **3.2. Generalization to more subdomains.** The Fourier analysis above can 337 be generalized to more subdomains if we still consider vertical slicing of the domain 338 to allow us to use separation of variables. Let us consider N_s subdomains $\Omega_i =$ 339 $(\alpha_i, \beta_i) \times (c, d), i \in \{1, \dots, N_S\}$, where

340
$$a = \alpha_1 < \alpha_2 < \beta_1 < \alpha_2 < \dots < \alpha_{N_s} < \beta_{N_s-1} < \beta_{N_s} = b.$$

In that case, for simplicity we will consider the parallel version of algorithm (3.2), which gives for its equivalent Helmholtz formulation the error equations

$$(3.15) \qquad \begin{array}{rcl} -\Delta'(v')_{i}^{n} - \widetilde{\omega}^{2}(v')_{i}^{n} &= 0 & \text{in } \Omega'_{i}, \\ (v')_{i}^{n} &= 0 & \text{on } \partial \Omega'_{i} \cap \Omega', \\ (\partial_{x'} + p'_{i,i+1})(v')_{i}^{n} &= (\partial_{x'} + p_{i,i+1})(v')_{i+1}^{n-1} & \text{on } \Gamma'_{i,i+1}, \\ (-\partial_{x'} + p'_{i,i-1})(v')_{i}^{n} &= (-\partial_{x'} + p_{i,i-1})(v')_{i-1}^{n-1} & \text{on } \Gamma'_{i,i-1}, \end{array}$$

where $\Gamma'_{i,i-1} := \{x' = \alpha'_i\} \times (c', d') \text{ and } \Gamma'_{i,i+1} := \{x' = \beta'_i\} \times (c', d').$ Then, with separation of variables, we still have as in (3.7), for all $i \in \{1, \dots, N_s\}$

346 (3.16)
$$(v')_i^n = \sum_{k \in \mathbb{N}^*} \psi_k(y') \left(A_i^n(k) e^{i\lambda(\xi_k)\tilde{x}'(x')} + B_i^n(k) e^{-i\lambda(\xi_k)\tilde{x}'(x')} \right).$$

Here again, the horizontal BCs are satisfied by definition of ψ_k . For each mode, the BC on $\{x' = a'\} \times (c', d')$ imposes that

349 (3.17)
$$B_1^n(k) = -A_1^n(k)e^{2i\lambda(\xi_k)(a'-i\sigma_x\ell')},$$

350 whereas the BC on $\{x' = b'\} \times (c', d')$ imposes that

351 (3.18)
$$B^{N_s,n}(k) = -A^{N_s,n}(k)e^{2i\lambda(\xi_k)(b'+i\sigma_x\ell')}.$$

352 The transmission conditions on $\Gamma'_{i,i+1}$ give

353

$$\begin{aligned} A_i^n(k) \left(i\lambda(\xi_k) + p'_{i,i+1} \right) e^{i\lambda(\xi_k)\widetilde{x}'(\beta_i)} \\ &+ B_i^n(k) \left(-i\lambda(\xi_k) + p'_{i,i+1} \right) e^{-i\lambda(\xi_k)\widetilde{x}'(\beta_i)} \\ &= A_{i+1}^{n-1}(k) \left(i\lambda(\xi_k) + p'_{i,i+1} \right) e^{i\lambda(\xi_k)\widetilde{x}'(\beta_i)} \\ &+ B_{i+1}^{n-1}(k) \left(-i\lambda(\xi_k) + p'_{i,i+1} \right) e^{-i\lambda(\xi_k)\widetilde{x}'(\beta_i)}, \end{aligned}$$

and similarly the transmission conditions on $\Gamma'_{i,i-1}$ give

355

$$\begin{aligned} A_{i}^{n}(k) \left(-i\lambda(\xi_{k})+p_{i,i-1}'\right) e^{i\lambda(\xi_{k})\widetilde{x}'(\alpha_{i})} \\ &+B_{i}^{n}(k) \left(i\lambda(\xi_{k})+p_{i,i-1}'\right) e^{-i\lambda(\xi_{k})\widetilde{x}'(\alpha_{i})} \\ &=A_{i-1}^{n-1}(k) \left(-i\lambda(\xi_{k})+p_{i,i-1}'\right) e^{i\lambda(\xi_{k})\widetilde{x}'(\alpha_{i})} \\ &+B_{i-1}^{n-1}(k) \left(i\lambda(\xi_{k})+p_{i,i-1}'\right) e^{-i\lambda(\xi_{k})\widetilde{x}'(\alpha_{i})}.\end{aligned}$$

356 Combining these relations, we get for the mode k the iteration relation

357
$$\mathbf{c}^{n}(k) = I(k) \mathbf{c}^{n-1}(k), \text{ where } I(k) = D^{-1}(k)K(k),$$

12

where $\mathbf{c}^{n}(k) := \begin{bmatrix} A_{1}^{n}(k) & B_{1}^{n}(k) & \cdots & A^{N_{s},n}(k) & B^{N_{s},n}(k) \end{bmatrix}^{T}$. The matrix D is block diagonal $\begin{bmatrix} D_{1} & 0 & \cdots & \cdots & 0 \end{bmatrix}$

$$D = \begin{bmatrix} D_1 & 0 & \cdots & \cdots & 0 \\ 0 & D_2 & \ddots & & \vdots \\ \vdots & \ddots & \ddots & \ddots & \vdots \\ \vdots & & \ddots & \ddots & 0 \\ 0 & \cdots & \cdots & 0 & D_{\mathrm{N_s}} \end{bmatrix},$$

361 where the matrices D_i are 2×2 matrices s.t. for all $i \in \{2, \dots, N_s - 1\}$

362
$$D_{i} = \begin{bmatrix} (-i\lambda(\xi_{k}) + p'_{i,i-1})e^{2i\lambda(\xi_{k})\widetilde{x'}(\alpha_{i})} & i\lambda(\xi_{k}) + p'_{i,i-1} \\ (i\lambda(\xi_{k}) + p'_{i,i+1})e^{2i\lambda(\xi_{k})\widetilde{x'}(\beta_{i})} & -i\lambda(\xi_{k}) + p'_{i,i+1} \end{bmatrix},$$

and, to take into account the Dirichlet BCs (3.17) and (3.18), we have

364
$$D_{1} = \begin{bmatrix} e^{2i\lambda(\xi_{k})\tilde{x'}(\alpha_{1})} & 1\\ (i\lambda(\xi_{k}) + p'_{1,2})e^{2i\lambda(\xi_{k})\tilde{x'}(\beta_{1})} & -i\lambda(\xi_{k}) + p'_{1,2} \end{bmatrix}$$

365 and

360

366
$$D_{N_{s}} = \begin{bmatrix} (-i\lambda(\xi_{k}) + p'_{N_{s},N_{s}-1})e^{2i\lambda(\xi_{k})\tilde{x'}(\alpha_{N_{s}})} & i\lambda(\xi_{k}) + p'_{N_{s},N_{s}-1} \\ e^{2i\lambda(\xi_{k})\tilde{x'}(\beta_{N_{s}})} & 1 \end{bmatrix}.$$

367 Similarly, the matrix K is given by

368
$$K = \begin{bmatrix} 0 & K_{1,2} & 0 & \cdots & 0 \\ K_{2,1} & 0 & K_{2,3} & & \vdots \\ 0 & \ddots & \ddots & \ddots & \vdots \\ \vdots & & \ddots & \ddots & K_{N_{s}-1,N_{s}} \\ 0 & \cdots & \cdots & K_{N_{s},N_{s}-1} & 0 \end{bmatrix},$$

369 where

370
$$K_{i,i-1} = \begin{bmatrix} (-\imath\lambda(\xi_k) + p'_{i,i-1})e^{2\imath\lambda(\xi_k)\tilde{x'}(\alpha_i)} & \imath\lambda(\xi_k) + p'_{i,i-1} \\ 0 & 0 \end{bmatrix}$$

371 and

372
$$K_{i,i+1} = \begin{bmatrix} 0 & 0 \\ (i\lambda(\xi_k) + p'_{i,i+1})e^{2i\lambda(\xi_k)\tilde{x'}(\beta_i)} & -i\lambda(\xi_k) + p'_{i,i+1} \end{bmatrix}$$

373 Thus the convergence factor is the spectral radius of the matrix I(k),

374 (3.19)
$$\rho(k) = \rho(I(k)).$$

375

376 Remark 3.6. In the two subdomain case, $N_s = 2$, if we eliminate $B_1^n(k)$ and 377 $B_2^n(k)$ using the outer Dirichlet BCs, the iteration matrix becomes

$$\begin{bmatrix} 0 & \rho_1(k) \\ \rho_2(k) & 0 \end{bmatrix}$$
13



FIG. 6. Convergence factor ρ^{DD} (top left), ρ^{DPML} (top right), ρ^{PMLD} (bottom left) and ρ^{PMLPML} (bottom right) in the case of 5 subdomains.

where $\rho_1(k)$ and $\rho_2(k)$ are defined in (3.11) and (3.12). In particular, the convergence factor is in that case the square root of the convergence factor defined in the previous section. Note that this is simply linked to the fact that in this section, we have considered the parallel version of the Schwarz algorithm, whereas before we studied the alternating version for two subdomains.

Remark 3.7. Let us also note that the matrix D(k) is not invertible if (and only if) $p'_{i,i-1} = -p'_{i,i+1} = \pm i\lambda(\xi_k)$, which corresponds to the case where the subproblem in Ω_i is not well-posed: the mode k is a non zero solution of the homogeneous problem. Moreover, if $p'_{i,i-1} = p'_{i,i+1} = -i\lambda(\xi_k)$, then D(k) is diagonal and one can show that $\rho(k) \to 0$ as the length ℓ of the PML tends to $+\infty$.

As a numerical illustration, let us consider again example (3.13) of the previous section with the same parameters, except that this time the domain is split into 5 subdomains. The subdomains are defined by

$$\begin{array}{ll} 392 \quad (3.20) \\ & \alpha_1 = 0, \quad \alpha_i = 0.2(i-1) - 0.05 \quad \text{for} \quad i \in \{2, \cdots, 5\}, \\ & \beta_5 = 1, \quad \beta_i = 0.2i + 0.05 \quad \text{for} \quad i \in \{1, \cdots, 4\}. \end{array}$$

For the parameters $p_{i,i+1}$ and $p_{i,i-1}$, we chose them s.t. $p'_{i,i+1} = p'_{i,i-1} = -i\widetilde{\omega}$, as before. In Figure 6, we show the convergence factor $\rho(k)$ for the *D-D*, *D-PML*, *PML-D* and *PML-PML* configurations. As one could expect, the convergence factor is less good than for the two subdomain case, but the remarks for the two subdomain case still hold. In particular, the more we open up the domain with PML outer boundary conditions, the better the convergence becomes.

399 **3.3. Optimized transmission conditions.** Now that we have obtained the 400 convergence factor, we can look for optimized parameters $p'_{i,i+1}$ and $p'_{i,i-1}$, and deduce



FIG. 7. Convergence factor ρ^{DD} (top left), ρ^{DPML} (top right), ρ^{PMLD} (bottom left) and ρ^{PMLPML} (bottom right) in the case of 5 subdomains for the Helmholtz equation. Comparison between the classical transmission conditions $-i\omega$ (in blue) and optimized parameters (in red).

401 $p_{i,i+1}$ and $p_{i+1,i}$ from equation (3.4). More precisely, we have to solve the classical 402 min-max problem

403 (3.21)
$$\min_{\substack{(p'_{1,2}, p'_{2,1}, p'_{2,3}, \cdots, p'_{N_s, N_s - 1}) \in \mathbb{C}^{2N_s}} \max_{k \in \mathbb{N}^+} |\rho(k)|.$$

In particular, the optimized parameters will be different depending on the outer BCs. 404 Also, in contrast to the usual convergence factor in free space, see [23] for instance, here 405 the convergence factor can be smaller than 1 at the cut-off frequency $\xi_k = \widetilde{w}$. This is 406 407 due to the fact that we consider a bounded domain for the analysis. As a consequence, the optimization can be done for all k, as in [8], where the equation contained damping. 408Finally, note that solving analytically this min-max problem is difficult, so we use a 409 simple optimization process and the function fmin of scipy.optimize. For first 410results on a many subdomain optimization for a diffusive problem, see [14]. 411

412 As a first numerical example, we consider the case of the Helmholtz equation, so 413 that u = v',

414 (3.22)
$$-\Delta u - \omega^2 u = 0 \quad \text{in } \Omega = (0, 1)^2.$$

We split the domain into 5 subdomains defined as before in equation (3.20). Taking $\omega = 50$, we show in Figure 7 the convergence factor with $p_{i,i+1} = p_{i,i-1} = -i\omega$ and with optimized parameters in the different cases (for the PML cases, we take $\ell = 0.02$ and $\sigma_x = \sigma_y = 10$). In particular for the *PML-D* case, one can see that optimized parameters allow us to get a convergent algorithm.

In Figure 8, we show the error evolution versus the iterations using either the Schwarz algorithm as iterative solver, or as preconditioner for GMRES. As we can



FIG. 8. Relative residual versus iterations in the D-D case (top left), D-PML case (top right), PML-D (bottom left) and in the PML-PML case (bottom right).

422 see, in each case the optimized parameters improve the convergence for the Schwarz 423 algorithm. Yet, this is no more true for GMRES. This can be explained since the 424 optimization problem (3.21) optimizes the convergence of the iterative Schwarz algo-425 rithm. Therefore, when using it as a preconditioner for GMRES, a priori, we are not 426 ensured that the optimized parameters are optimized parameters for GMRES.

Remark 3.8. Let us emphasize that for the mesh discretization, one must consider
a sufficiently fine mesh to get accurate results that match the theoretical convergence
properties. In particular, if the mesh in the PML is too coarse, then the Schwarz
algorithm can be divergent even if the continuous convergence factor is less than one.

431 As a second, more realistic example, let us consider the case of the convected 432 Helmholtz equation

433 (3.23)
$$-\operatorname{div}(A\nabla u) - 2\iota\omega \mathbf{v} \cdot \nabla u - \omega^2 u = \delta \quad \text{in } \Omega = (0,1)^2 \setminus \mathcal{O}, \\ A\nabla u \cdot \mathbf{n} = 0 \quad \text{on } \partial\Omega,$$

434 where the obstacle \mathcal{O} has the rough shape of a submarine, see Figure 9. We consider 435 a potential flow $\mathbf{v} = \nabla \varphi$ coming from the left, which we compute solving the Laplace 436 problem

437

$$\begin{aligned}
-\Delta\varphi &= 0 & \text{in } \Omega, \\
\nabla\varphi \cdot \mathbf{n} &= 0 & \text{on } \partial\mathcal{O} \cup (0,1) \times \{0,1\} \\
\nabla\varphi \cdot \mathbf{n} &= -1 & \text{on } \{0\} \times (0,1), \\
\nabla\varphi \cdot \mathbf{n} &= 1 & \text{on } \{1\} \times (0,1),
\end{aligned}$$

with the same mesh. Note that to get a well-posed problem, we simply impose a value of φ inside Ω . We compute the gradient of φ inside each cell of the mesh to get **v**.



FIG. 9. Potential flow around a submarine on the left (the background color corresponds to the norm of $v/||v||_{\infty}$). Diffracted field from a Dirac point source on the right.

440 Then, the velocity is normalized

441
$$\widetilde{\mathbf{v}} = \operatorname{Ma} \frac{\mathbf{v}}{\|\mathbf{v}\|_{\infty}}, \quad \text{where} \quad \|\mathbf{v}\|_{\infty} = \sup_{(x,y)\in\Omega} \|\mathbf{v}(x,y)\|_2,$$

442 where Ma is the mach number, i.e. the ratio between the velocity of the fluid and the 443 sound speed in the medium. Thus, the matrix A in (3.23) is given by

444
$$A = \operatorname{Id} - \widetilde{\mathbf{v}}\widetilde{\mathbf{v}}^T.$$

For this example, we took² Ma = 0.7 and $\omega = 200$. For the PML, we took $\ell = 0.02$ and $\sigma_x = \sigma_y = 15$. Also, we assume the flow to be constant and horizontal in the PML region $\tilde{\mathbf{v}} = (\tilde{v}_{ext}, 0)^T$, although this is not exact: the flow is almost horizontal and constant. The domain is decomposed into 5 subdomains defined by

449 (3.24)
$$\begin{aligned} \alpha_1 &= 0, \quad \alpha_i = 0.2(i-1) - 0.015 \quad \text{for} \quad i \in \{2, \cdots, 5\}, \\ \beta_5 &= 1, \quad \beta_i = 0.2i + 0.015 \quad \text{for} \quad i \in \{1, \cdots, 4\}, \end{aligned}$$

which corresponds to an overlap of size 0.03. The mesh we use is unstructured, so that the interfaces between the subdomains are not perfectly straight any more. Moreover, since **a** is no more constant in the physical domain, a natural generalization of the transmission conditions, similar to the ABC (2.6), is

454
$$\mathbf{A}_{PML} \nabla u \cdot \mathbf{n} - \imath \frac{1}{2} \mathbf{a}_{PML} \cdot \mathbf{n} + p_{i,i\pm 1} u.$$

In particular, we compare in this example the following choices of the parameters $p_{i,i\pm 1}$:

• First, a classical ABC condition as in (2.6),

458 (ABC)
$$p_{i,i\pm 1} = -i\widetilde{\omega} \|\mathbf{n}\|_A$$
 where $\widetilde{\omega} = \sqrt{-\mu + \frac{1}{4} \|\mathbf{a}\|_{A^{-1}}^2}$.

459 Note that \widetilde{w} and $\|\mathbf{n}\|_A$ are variable.

 $^{^{2}}$ This value is in fact not realistic since in water the sound speed is much larger than in air. As far as we know, the fastest speed one can reach in water is around mach 0.075 with supercavitation. Nevertheless, this very high speed is only obtained close to corners of the submarine, where the velocity increases a lot. In the rest of the domain, the speed is more realistic.



FIG. 10. *GMRES* residual versus iterations for the three types of transmission conditions (ABC), (ABC PML) and (OPT).

460 461	• Second, a similar Remark 3.3,	r one but taking the F	PML appro	ximately into account, see
462	(ABC PML)	$p_{i,i\pm 1} = -\frac{s_y}{s_x} \widetilde{\omega} \ \mathbf{n}\ _A$	where $\hat{\boldsymbol{\omega}}$	$\tilde{\boldsymbol{\boldsymbol{\omega}}} = \sqrt{-\mu + \frac{1}{4} \ \mathbf{a} \ _{A^{-1}}^2},$

463 where we recall that s_y and s_x are the PML parameters.

• Third, a condition that takes the PML into account,

465 (OPT)
$$p_{i,i\pm 1} = \frac{s_y}{s_x} q_{i,i\pm 1},$$

466 where $q_{i,i\pm 1}$ are (numerical) solutions of the min-max problem (3.21) consid-467 ering the medium with no obstacle and with $\mathbf{a} = -2\omega(\tilde{v}_{ext}, 0)^T$ constant.

In Figure 10, we show the evolution of the residual considering these three transmission
conditions. The best results are obtained with the condition ABC PML and OPT.
We see that clearly, taking into account the PML coefficient in the parameter is very
important, as already mentioned in Remark 3.3.

4. Concluding remarks. We studied Schwarz domain decomposition methods 472 for a general diffusion problem with complex advection, which appears in several im-473portant applications. The complex advection term changes fundamentally the nature 474 of the diffusion problem and makes it Helmholtz like. We have shown that for such 475 problems the outer boundary conditions imposed on the global domain have a strong 476 influence on the convergence of the Schwarz method, and on how one should choose 477 optimized parameters. Not taking into account the PML coefficients in the trans-478479mission conditions deteriorates the convergence of the Schwarz algorithm, both when used as iterative solver and as preconditioner for GMRES. Our analysis covers both 480481 two subdomain and many subdomain situations for decompositions into strips, and allowed us to formulate the min-max problem one has to solve to compute optimized 482parameters, which turns out to be difficult to treat theoretically. Furthermore, com-483 puting optimized parameters for GMRES is currently out of reach, for a special case 484 485in a splitting method, see [6].

486 Acknowledgments. This research was supported by the Swiss National Science 487 Foundation.

488			REFERENCES
489 490 491	[1]	Y.	ACHDOU, P. LE TALLEC, F. NATAF, AND M. VIDRASCU, A domain decomposition precon- ditioner for an advection-diffusion problem, Computer methods in applied mechanics and engineering, 184 (2000), pp. 145–170.
492 493 494	[2]	Х.	ANTOINE, W. BAO, AND C. BESSE, Computational methods for the dynamics of the nonlinear Schrödinger/Gross-Pitaevskii equations, Computer Physics Communications, 184 (2013), pp. 2621–2633.
495 496 497	[3]	Η.	BARUCQ, N. ROUXELIN, AND S. TORDEUX, <i>HDG and HDG+ methods for harmonic wave problems with convection</i> , tech. report, Inria Bordeaux-Sud-Ouest; LMAP UMR CNRS 5142; Université de Pau et des Pays de l'Adour, 2021.
498 499 500	[4]	Н.	BARUCQ, N. ROUXELIN, AND S. TORDEUX, Prandtl-Glauert-Lorentz based absorbing bound- ary conditions for the convected Helmholtz equation, tech. report, Inria Bordeaux-Sud- Ouest; LMAP UMR CNRS 5142; Université de Pau et des Pays de l'Adour, 2021.
501 502 503	[5] [6]	E.	 BÉCACHE, A. BB. DHIA, AND G. LEGENDRE, Perfectly matched layers for the convected Helmholtz equation, SIAM Journal on Numerical Analysis, 42 (2004), pp. 409–433. BENZI, M. J. GANDER, AND G. H. GOLUB, Optimization of the Hermitian and skew-
504 505 506	[7]	F.	Hermitian splitting iteration for saddle-point problems, BIT Numerical Mathematics, 43 (2003), pp. 881–900. BETHIEL AND JC. SAUT. Travelling waves for the Gross-Pitaevskii equation I. Annales de
507 508 509	[8]	М	 I'IHP, section A, 70 (1999), pp. 147–238. BOUAJAJI, V. DOLEAN, M. J. GANDER, AND S. LANTERI, Optimized Schwarz methods for the time-harmonic maxwell equations with damping SIAM Journal on Scientific Computing
510 511 512	[9]	А.	34 (2012), pp. A2048–A2071. BRANDT AND I. LIVSHITS, <i>Wave-ray multigrid method for standing wave equations</i> , Electron. Trans. Numer. Anal. 6 (1997), p. 91
513 514 515	[10]	D.	CHIRON AND C. SCHEID, Travelling waves for the nonlinear Schrödinger equation with general nonlinearity in dimension two, Journal of Nonlinear Science, 26 (2016), pp. 171–231
516 517 518	[11]	I.	DANAILA AND B. PROTAS, Computation of ground states of the Gross-Pitaevskii func- tional via Riemannian optimization, SIAM Journal on Scientific Computing, 39 (2017), pp. B1102-B1129
519 520 521	[12]	E.	DEMALDENT AND S. IMPERIALE, Perfectly matched transmission problem with absorbing layers: Application to anisotropic acoustics in convex polygonal domains, International Journal for Numerical Methods in Engineering, 96 (2013), pp. 689–711.
522 523 524	[13] [14]	B. V	DESPRÉS, Domain decomposition method and the Helmholtz problem., Mathematical and Numerical aspects of wave propagation phenomena, (1991), pp. 44–52. DOLEAN M. J. GANDER AND A. KYRIAKIS, Closed form ontimized transmission conditions
525 526 527	[15]	V.	for complex diffusion with many subdomains, SIAM J. on Sci. Comput., (2023). in print. DOLEAN, P. JOLIVET, AND F. NATAF, An introduction to domain decomposition methods: alagrithms theory and namelel implementation SIAM 2015.
528 529 530	[16]	0.	DUBOIS, Optimized Schwarz methods with Robin conditions for the advection-diffusion equa- tion, in Domain decomposition methods in science and engineering XVI, Springer, 2007, pp. 181–188
531 532	[17]	О.	G. ERNST AND M. J. GANDER, Why it is difficult to solve Helmholtz problems with classical iterative methods, Numerical analysis of multiscale problems, (2011), pp. 325–363.
533 534 535	[18] [19]	M	 J. GANDER AND O. DUBOIS, Optimized Schwarz methods for a alifusion problem with discontinuous coefficient, Numerical Algorithms, 69 (2015), pp. 109–144. J. GANDER, L. HALPERN, F. HUBERT, AND S. KRELL, Discrete optimization of Robin trans-
536 537 538	[20]	М	mission conditions for anisotropic diffusion with Discrete Duality Finite Volume methods, Vietnam Journal of Mathematics, 49 (2021), pp. 1349–1378. J. GANDER, L. HALPERN, F. HUBERT, AND S. KRELL, Optimized Schwarz methods with gen-
539 540 541			eral Ventcell transmission conditions for fully anisotropic diffusion with Discrete Duality Finite Volume discretizations, Moroccan Journal of Pure and Applied Analysis, 7 (2021), pp. 182–213.
542 543 544	[21]	М	J. GANDER, L. HALPERN, AND F. MAGOULES, An optimized Schwarz method with two- sided Robin transmission conditions for the Helmholtz equation, International journal for numerical methods in fluids, 55 (2007), pp. 163–175.

- [22] M. J. GANDER, F. MAGOULES, AND F. NATAF, Optimized Schwarz methods without overlap for the Helmholtz equation, SIAM Journal on Scientific Computing, 24 (2002), pp. 38–60.
- [23] M. J. GANDER AND H. ZHANG, Optimized Schwarz methods with overlap for the Helmholtz
 equation, SIAM Journal on Scientific Computing, 38 (2016), pp. A3195–A3219.
- [24] M. J. GANDER AND H. ZHANG, A class of iterative solvers for the Helmholtz equation: Factorizations, sweeping preconditioners, source transfer, single layer potentials, polarized traces, and optimized Schwarz methods, SIAM Review, 61 (2019), pp. 3–76.
- [25] M. J. GANDER AND H. ZHANG, Schwarz methods by domain truncation, Acta Numerica, 31
 (2022), pp. 1–134.
- L. GERARDO-GIORDA AND F. NATAF, Optimized Schwarz methods for unsymmetric layered problems with strongly discontinuous and anisotropic coefficients, J. Numer. Math., 13
 (2005), pp. 265–294.
- [27] S. GONG, M. J. GANDER, I. G. GRAHAM, D. LAFONTAINE, AND E. A. SPENCE, Convergence of parallel overlapping domain decomposition methods for the Helmholtz equation, Numerische Mathematik, (2022), pp. 1–48.
- [28] I. GRAHAM, E. SPENCE, AND E. VAINIKKO, Domain decomposition preconditioning for highfrequency Helmholtz problems with absorption, Mathematics of Computation, 86 (2017), pp. 2089–2127.
- [29] I. G. GRAHAM, E. A. SPENCE, AND J. ZOU, Domain decomposition with local impedance conditions for the Helmholtz equation with absorption, SIAM Journal on Numerical Analysis, 565 58 (2020), pp. 2515–2543.
- [30] F. Q. HU, M. E. PIZZO, AND D. M. NARK, On the use of a Prandtl-Glauert-Lorentz transformation for acoustic scattering by rigid bodies with a uniform flow, Journal of Sound and Vibration, 443 (2019), pp. 198–211.
- [31] L. F. KNOCKAERT AND D. DE ZUTTER, On the completeness of eigenmodes in a parallel plate
 waveguide with a perfectly matched layer termination, IEEE Transactions on Antennas
 and Propagation, 50 (2002), pp. 1650–1653.
- [32] A. LIEU, P. MARCHNER, G. GABARD, H. BERIOT, X. ANTOINE, AND C. GEUZAINE, A nonoverlapping Schwarz domain decomposition method with high-order finite elements for flow acoustics, Computer Methods in Applied Mechanics and Engineering, 369 (2020),
 p. 113223.
- [33] I. LIVSHITS, An algebraic multigrid wave-ray algorithm to solve eigenvalue problems for the Helmholtz operator, Numerical linear algebra with applications, 11 (2004), pp. 229–239.
- [34] I. LIVSHITS AND A. BRANDT, Accuracy properties of the wave-ray multigrid algorithm for Helmholtz equations, SIAM Journal on Scientific Computing, 28 (2006), pp. 1228–1251.
- [35] P. MARCHNER, X. ANTOINE, C. GEUZAINE, AND H. BÉRIOT, Construction and numerical assessment of local absorbing boundary conditions for heterogeneous time-harmonic acoustic problems, SIAM Journal on Applied Mathematics, 82 (2022), pp. 476–501.
- [36] P. MARCHNER, H. BERIOT, X. ANTOINE, AND C. GEUZAINE, Stable Perfectly Matched Layers
 with Lorentz transformation for the convected Helmholtz equation, Journal of Computational Physics, 433 (2021), p. 110180.
- [37] A. TONNOIR, Dirichlet-to-Neumann operator for diffraction problems in stratified anisotropic
 acoustic waveguides, Comptes Rendus Mathematique, 354 (2016), pp. 383–387.
- [38] VERBURG, Multi-level Wave-Ray method for 2d Helmholtz equation, master's thesis, University
 of Twente, 2010.