



HAL
open science

Urban freight transport using passenger rail network: Scientific issues and quantitative analysis

Walid Behiri, Sana Belmokhtar-Berraf, Chengbin Chu

► To cite this version:

Walid Behiri, Sana Belmokhtar-Berraf, Chengbin Chu. Urban freight transport using passenger rail network: Scientific issues and quantitative analysis. *Transportation Research Part E: Logistics and Transportation Review*, 2018, 115, pp.227-245. 10.1016/j.tre.2018.05.002 . hal-04056086v1

HAL Id: hal-04056086

<https://hal.science/hal-04056086v1>

Submitted on 3 Apr 2023 (v1), last revised 22 Jan 2024 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Urban freight transport using passenger rail network: Scientific issues and quantitative analysis

Walid Behiri ^{a,b}, Sana Belmokhtar-Berraf ^c, Chengbin Chu^{a,c}

^a Université Paris-Est, Laboratoire d'Informatique Gaspard-Monge UMR 8049, UPEMLV, ESIEE Paris, ENPC, CNRS, F-93162 Noisy-le-Grand France

^b Laboratoire Génie Industriel, CentraleSupélec, Université Paris-Saclay, Gif-sur-Yvette, France

^c Université Paris-Est, ESIEE Paris, Département Ingénierie des Systèmes. 2, boulevard Blaise Pascal Cité DESCARTES BP 99 93162 Noisy le Grand CEDEX

Corresponding author.

Walid BEHIRI

E-mail: walid.behiri@esiee.fr or walid.behiri@gmail.com

Tel: +33 6 05 96 30 50

Urban freight transport using passenger rail network: Scientific issues and quantitative analysis

ABSTRACT:

This paper addresses a real-life problem arising in the ongoing "Grand Paris" project. We investigate an environment-friendly urban freight transportation alternative using passenger rail network, by providing a decision support tool for decision makers to assess the technical feasibility, the impact on services to passengers, the needs in infrastructure and hence in investment. We identify relevant scientific issues that need to be addressed in this topic at strategical, tactical and operational levels. Then we focus on the Freight-Rail-Transport-Scheduling Problem which provides valuable information to and constitutes a basis for other related problems. This problem is first formulated into a MIP. We prove its NP-hardness and hence propose a heuristic based on dispatching rules and a single-train-based decomposition heuristic. The performances of these heuristics are evaluated via employing a discrete-event simulation approach, which also provides a general framework which supports decision-makers in modelling and evaluating the dynamics of such a system for various alternative solutions under various scenarios.

KEYWORDS: *Urban freight; Rail transport; Paris rail network; Discrete-event simulation; Mixed Integer Program "MIP".*

1 INTRODUCTION

The European Union targets a carbon-dioxide-and-greenhouse-emissions reduction by 20% in 2020 from their 1990 level, in order to cope with climate change (OECD, 2014). This target has to be met in a context of population concentration in cities, e-commerce development and increase of the world population (Comi and Nuzzolo, 2016). Indeed, 73% of the European population now lives in urban areas with an expected even higher rate in the future (United Nations, 2015). As a direct consequence, according to Van Audenhove et al. (2015), it is expected that the generated urban traffic measured in travel distance would triple by 2050, including urban goods distribution. Nevertheless, urban freight transport is necessary to support efficient economic and social development in urban areas (Taniguchi et al., 2001). For urban freight transport, road has been predominant despite its significant weaknesses such as worsening congestion, low safety and negative environmental impacts (Limbourg and Jourquin, 2009). A quarter of the carbon-dioxide emissions are caused by transportation activities (Nanaki et al., 2016). For several decades, although freight transport by trucks has been representing only 10% of the total traffic, it has accounted for 40% of pollutant emissions in big cities (European Cooperation in the Field of Scientific and Technical Research, 1998; Tang et al., 2017). In many European cities, the authorities regulate urban transport through restrictive policies such as progressive ban on the most polluting vehicles, or even by introducing a toll proportional to the pollution degree of vehicles (in Milan for instance). Moreover, the European Union coordinates its actions through the Transport Committee of the EU by setting ambitious targets for member states such as zero-pollutant emissions related to goods transport in urban areas until 2030 (European Commission, 2011). In December 2015, the United Nations conference on climate change "COP21" fixed a more ambitious environmental target, which will surely have an impact on urban freight transport.

The above-mentioned context requires changes toward more environment-friendly transportation systems to cope with increasing demand for mobility in urban areas. Introducing freight transport into passenger rail network is one of the ways to absorb a significant part of the current road traffic. Goods deliveries can be ensured by combining other sustainable modes such as Electro-Mobility "E-Mobility" (MacHaris et al., 2007; Köhler et al., 2009; Offer et al., 2010; Van Wee et al., 2012; Van Duin et al., 2013). The main idea here is to mitigate ground traffic by shifting as much road traffic as possible toward rail and get a better use of the currently under-exploited passenger trains' capacity.

This work aims to provide a decision-support tool to investigate the feasibility and to evaluate the potential benefits and other impacts of such practices in Parisian metropolitan area. The challenge comes from coordinating freight and passenger flows using existing and forthcoming urban passenger rail infrastructure, which is actually in extension through the ambitious "Grand Paris" project. This challenging project aims to shift toward a resilient and smart city by innovating in terms of offers in services and infrastructure. The existing Parisian rail network is one of the largest in

57 Europe and aims to add 200km rail lines and 68 stations. This project promotes sustainable development and
58 improvement of life quality in Paris and its periphery. One of the most relevant ideas is integration of urban freight flow
59 with the passenger one. For example, a passenger that wants to send a parcel by post should be able to deposit it at the
60 metro/tram station before traveling. This pick-up system has been experimented in several countries and is expected to
61 be deployed in the near future in France. The objective of this work is to take this opportunity to explore the possibility
62 of expanding the urban rail infrastructure to freight transport, by evaluating the technical feasibility, the impact on
63 services to passengers and financial viability, while considering technical and organizational constraints. This
64 evaluation will enable the project managers to envision different options. For this purpose, they need a decision support
65 tool capable of proposing optimized solutions and evaluating various alternatives under different scenarios. This paper
66 aims to provide such a tool.

67
68 The first step is to identify the scientific issues in decision-making for such a configuration, from short-term
69 operational decisions to long-term strategic decisions. From this analysis, we investigate the Freight-Rail-Transport
70 Scheduling Problem (“FRTSP” for short), since its solution provides valuable information to other decision-making
71 problems and thus constitutes the basis to address such a system. For this problem, we propose a MIP formulation and
72 several heuristics to solve the problem. A simulation model is used in order to evaluate the performance of these
73 heuristics and the dynamics of such transportation systems which is essential for practitioners and decision makers and
74 for academics to better understand and address the system.

75
76 The remainder of this paper is organized as follows. Section 2 reviews the related literature. Section 3 is devoted to
77 the identification of relevant scientific issues at different levels of decision making. Section 4 describes in detail the
78 FRTSP. In section 5, the FRTSP is mathematically formulated into a MIP and its computational complexity is analyzed.
79 Section 6 presents the solution methods: a dispatching-rule-based heuristic and a single-train-based decomposition
80 heuristic. Section 7 describes the simulation framework we develop to model and evaluate urban freight transport using
81 passenger rail network. In section 8, the simulation results are reported and analyzed. These results include the
82 performance of different solution methods and the impact of freight transport on various core components of rail
83 networks: trains, stations and rail lines. Finally, section 9 concludes the study and discusses future research directions.

84 2 LITERATURE REVIEW

85 2.1 *Urban freight transport: road mode predominance*

86 Freight transport in European cities is mainly related to goods flows from producers, wholesalers and distribution
87 centers toward retailers such as stores, outlets and markets (Nuzzolo and Comi, 2014). The freight transport is still road
88 predominant (Lindholm and Behrends, 2012). In France, for instance, it is estimated between 85% and 90% by the
89 National Institute of Statistics (2015). However, cities' ground transport has limited capacity and trucks cause very high
90 level of nuisance (e.g.: noise, gas emissions, increased traffic...). Dablanc (2007) notes that transport-related operations
91 in cities generate between 20% and 30% of the road traffic but, depending on the pollutant considered, it produces
92 between 16% and 50% of air pollutants. For example, Paris statistics show that 90% of freight is carried out by trucks,
93 representing 20% of urban traffic and 1/3 of pollutant emissions in the city (Mairie de Paris, 2009).

94
95 The idea of mixing freight with passenger flows using urban road transportation is studied in Trentini and Malhene
96 (2012) where the possibility of sharing passenger buses is suggested. In particular, they analyze urban passenger and
97 freight flows and demonstrate that there is enough room in passenger service to transport a part of the urban freight.
98 They propose to use the spare capacity of passenger buses to transport goods from bus depots to different bus stops
99 inside cities. This study is completed by Masson et al. (2015), where the authors optimize, with a mathematical model,
100 goods deliveries from bus stops to final customers, using near-zero-emissions vehicles.

101
102 A research team working on physical internet proposes to redesign the logistics system to consider sustainability
103 and traceability issues and goes toward an open global logistics system where supply networks are interconnected
104 (Sallez et al., 2016). They propose to use a set of collaborative protocols, modular containers and intelligent interface
105 standards to increase efficiency and sustainability. The principle of this approach is to pool all transport resources for
106 commodities from different carriers between countries, cities and inside cities. The European Technology Platform
107 ALICE plans the deployment of physical internet approach by 2050 (ALICE and ERTRAC, 2015). In spite of the
108 potentially interesting benefit of such concepts, the physical internet requires changing current practices and
109 infrastructures of the whole supply chain and developing new ones, which must take a very long time.

110

111 2.2 *Urban underground space for freight transport: future solutions*

112 To cope with the sustainability issue and meet the European target on CO₂ emissions reduction, one interesting
113 perspective is the use of cities' underground space to transport goods and reduce their carbon footprint. For Delmastro et
114 al. (2016), cities' underground capacity should be used for reducing the pressure on land use, which is mainly due to the
115 growth in urban population. In 1991, Japanese researchers propose to develop a dedicated underground goods
116 distribution system based on passenger rail network in order to overcome some urban environmental issues, which are
117 related to the continuous increase of traffic congestion in Tokyo (Kashima et al., 1993). A more advanced solution is
118 proposed by Dietrich Stein and some other researchers on a system called CargoCap (CargoCap, 2002), which consists
119 of unmanned electric vehicles on rails that travel through underground pipelines. For Egbunike and Potter (2011), there
120 are opportunities for the use of underground freight transport. In January 2016, "Cargo Sous Terrain" (CST), an
121 innovative underground goods transport solution, was launched in Switzerland (CST, 2016). It consists of developing a
122 new distribution system by creating an underground transportation system, exclusively dedicated to freight transport
123 among Swiss cities. The goods will be transported by autonomous electric vehicles. The feasibility study shows that this
124 transport system is feasible both from technical and economic points of view. CST could come into operations in 2030.

125 126 2.3 *Urban freight by rail as an alternative environment-friendly transportation mode*

127 The use of rail network, equipment and infrastructure for urban freight transport is studied in some research papers.
128 Dinwoodie (2006) highlights the market potential and the economies of scale of rail freight in the UK and analyses the
129 economic and business opportunities of this environment-friendly transportation system. Browne et al. (2014) compare
130 rail freight activity in London and Paris (Ile de France) and report some other European initiatives in the use of rail for
131 urban supply chain. The authors underline some difficulties and indicate the obvious benefit and potentials but without
132 any quantitative analysis when rail becomes an environment-friendly mode for urban goods transport. Behrends (2012a,
133 2012b) studies an intermodal road-rail transport and identifies possible actions at a local level to improve both the
134 competitiveness and environmental benefits. On the other hand, Diziain et al. (2014) study the modal shift in French
135 and Japanese urban areas to keep the best practices. They study urban logistics by rail and waterways, and conclude that
136 the modal shift from road to these two modes is expensive and would be profitable only if many conditions are met (e.g.
137 congested road networks, existing multimodal infrastructure, available terminals in the city center...). De Langhe
138 (2014) analyses the role of rail in urban freight, provides a literature review, and reports a series of interviews with
139 experts from academia and industry. In addition, this work identifies the success factors of deploying urban freight
140 solutions by rail.

141 To evaluate freight transport by trams in the Parisian region, Gonzalez (2014) performs an assessment of urban rail
142 logistics' suitability using a socio-economic cost-benefit analysis. This study shows the potential of this logistic
143 alternative and provides the conditions to make it profitable. Motraghi and Marinov (2012) and Dampier and Marinov
144 (2015), analyse urban freight in Newcastle metro system. These studies show that the concept of using an urban railway
145 network to transport freight is viable, but it requires further research before actual implementation. As an application,
146 Brice et al. (2015) and Reece and Marinov (2015) investigate transportation systems for baggage from the city center to
147 Newcastle airport using the metro, instead of an existing baggage service. They demonstrate the feasibility of such a
148 new baggage transfer solution and underline the higher cost than the existing service. Nuzzolo et al. (2007) study the
149 possibility of delivering goods using passenger train infrastructures, between Naples and Sorrento, Italy. They propose
150 to use existing infrastructure, such as railways and stations, and old passenger trains after removing equipment, such as
151 seats and inside doors, to leave more room for goods. They propose to transport goods during off-peak periods. For
152 such a solution, the mixed freight-passenger flows is limited to the use of rail track and dedicated space in stations.
153 Abril et al. (2008) indicate that railway capacity determination depends very much on various parameters such as
154 infrastructure, traffic, and operating parameters. They suggest to use analytical, optimization or simulation methods to
155 overcome the system complexity. For more information on urban freight by rail, the reader may refer to Robinson and
156 Mortimer (2003). Based on some European examples, they realize a state-of-the-art review in urban rail freight
157 transport.

158 Besides previous research papers, there are few application cases of using rail in urban logistics. There are for
159 instance three successful implementations (MONOPRIX in Paris, New York subway and Cargo Tram in Dresden), in
160 addition to the new project under construction in Paris called "Chapelle International". These cases are described as
161 follows:

- 162 • **Case 1: MONOPRIX in Paris (Dablanc, 2009) & (MONOPRIX, 2007)**
163 MONOPRIX is a French supermarket chain, SNCF (Société Nationale des Chemins de Fer français, the largest
164 French rail operator) has been delivering a small part of goods to some supermarkets of this chain. This is done
165 using the commuter line D (RER D) in Paris, for the transport of a number of goods such as soft drinks, textiles,
166

169 cosmetics, household goods, and leisure products, from MONOPRIX warehouses outside Paris (Combs-la-Ville and
170 Lieusaint) to Bercy station inside Paris. Thereafter, the products are transported to stores by trucks running on NGV
171 fuel (Natural Gas Vehicle), to comply with the emissions reduction principle along the logistics line. This is a quite
172 large-scale implementation, since this line is 30 km long and can carry 210 000 pallets (equivalent to 120 000 tons)
173 each year, with 5 trains of 20 cars per week (one daily train in the morning).

- 174 • **Case 2: New York subway (Metropolitan Transportation Authority, 2014)**

175 This case concerns the subway waste collection in New York City through stations using modified subway cars. The
176 collect is done overnight, and as the New York subway runs 24/7, it is mixed between freight transport (waste in this
177 case) and passenger transport. This solution enables the collect of 14 000 tons of waste per year, with 11 dedicated
178 subway trains, covering 359 stations with 567 stops.

- 179 • **Case 3: Cargo Tram of Dresden (Quak, 2008)**

180 A portion of 4 km tram line in Dresden is used to transport automotive parts and modules, from a Volkswagen
181 warehouse near a rail terminal in the city, toward their factory located in the city center. This solution can cope with
182 limited storage space in order to ensure daily production. This line can deliver 300 000 tons of products per year
183 with 10 daily trips, which significantly reduces CO₂ emissions.

- 184 • **Case 4: Chapelle International (SOGARIS, 2016)**

185 This is a global urban logistic solution based on an urban rail shuttle and the multi-modal logistics hub “Chapelle
186 International” (under construction). An important warehouse located in the north of the “Ile-de-France” region
187 (Greater Paris region) is interconnected to “Chapelle International” with a railway. Goods will be transported by
188 trains and each train will transport 60 mobile boxes. Thereafter, trucks running on NGV fuel would carry the
189 products to stores. This solution will save nearly 10 000 trucks per year in the center of Paris.

191 2.4 Optimization techniques for freight and rail problems

192 Many researchers have proposed such models for freight transport (by road, rail, sea or air), and particularly
193 addressed the complexity generated by urban freight. Crainic and Laporte (1996) identify and present the main issues
194 encountered at various decision-making levels (strategic, tactical and operational) in freight transport planning and
195 operations, and give an overview of appropriate operations-research-oriented models and methods.

197 Planning optimization is addressed using mathematical programming in the works of Gao *et al.* (2017) who provide
198 a bi-objective MIP model to adjust train timetable in order to insert new trains in high-speed rail corridor. A three-stage
199 optimization method is proposed. The first stage minimizes the travel time of each new train. In the second stage, the
200 total deviation of existing trains is minimized. Finally, the third stage minimizes the total travel time of the additional
201 trains. Another application of ILP (integer linear programming) is also suggested by Besinovic *et al.* (2016) to provide a
202 robust train plan for the Netherlands rail network. An integrated iterative micro-macro approach is proposed to
203 determine stable and robust railway timetables to face the increasing demand for passengers and freight transport.

205 For long-haul transportation of containerized goods (in heterogeneous boxes) where automated terminals are used
206 for metro-cargo through a complex rail network, Anghinolfi *et al.* (2011) study the offline planning of customer
207 requests so that each request which may involve several boxes has to be assigned to a single route composed of
208 segments crossed by several trains. The set of routes are determined in advance. Hence, boxes travel from a departure
209 terminal to their arrival by transshipment, considering the loading and packing of boxes in train wagons. The authors
210 propose a 0-1 linear programming formulation to solve this NP-hard generalized assignment problem. They develop
211 two metaheuristics operating with a MIP solver to obtain near-optimal solutions. For bulk commodity deliveries by rail,
212 Lawley *et al.* (2007) developed a MIP model considering customer demand, rail network characteristics (the routes
213 between every origin-destination pair), loading/unloading hours in stations for each customer demand, the maximum
214 number of trains simultaneously in each station for loading/unloading operations, etc. The objective is to maximize the
215 satisfied demand while minimizing the total waiting time at stations. Unlike our study where the train schedule is
216 predefined, they aim to determine the best train schedule by avoiding saturation at rail tracks and stations.

218 Optimization or simulation models have also been used to solve urban transportation problems. Russo and Comi
219 (2010) present recent developments in simulating urban goods flow. They propose a modelling system capable of
220 assessing ex-ante measures and linking consumers’ and retailers’ choices. Inspired from a vehicle-routing problem,
221 Figliozzi (2007) develops a simulation tool for measuring the economic impact of urban commercial vehicle tours. In a
222 later work, Figliozzi (2010) studies the impact of congestion on indicators such as costs of commercial vehicle tours.
223 Benjelloun and Crainic (2008) present an overview on concepts, models, and planning issues in city logistics and
224 identify trends, challenges, and research directions. Their work is based on an analysis of a large number of projects and
225 proposals. Fatnassi *et al.* (2015) study the sharing of goods and passenger transport using a rapid transit system, a sort of
226 automated guide-way transit composed of small battery-fed electric vehicles and dedicated transport lines. They
227 propose two mathematical formulations to model the problem with the objective of minimizing the average number of

228 empty moves per period, considering some specific constraints such as the battery capacity and recharges. However, the
229 main problem considered is determining the vehicle routes between stations. They use a dynamic optimization approach
230 and develop algorithms to solve the dynamic problem and demonstrate the applicability of this transportation mode.
231

232 2.5 Summary

233 This literature review shows that freight transport, especially in urban areas, is shifting toward innovative and
234 sustainable solutions with crucial environmental challenges. Some of them, such as CargoCap or CST, are designed for
235 far future, due to the technological obstacles and heavy investment they require. Existing literature shows interesting
236 perspectives of using underground for freight transport, especially in crowded large cities with advanced rail networks.
237 Optimization techniques (such as mathematical modelling, heuristics and metaheuristics, ...) are used to solve various
238 transportation problems (scheduling, routing, assignment, ...). This paper considers scheduling of goods transport using
239 passenger trains. In this context, various constraints have to be taken into account such as waiting time in stations, spare
240 space available inside trains. Especially train routes and timetables are predefined. The literature review shows that no
241 work has even been carried out considering all these features. Furthermore, the goods to transport could be any nature,
242 as soon as they are packed into standard-size boxes as recommended by physical internet (Sallez et al., 2016).
243

244 Before implementing such a transportation mode, several issues at different decision-making levels must be
245 identified and addressed. This paper identifies these issues and then focuses on one of them, which is the basis of all
246 related issues, by using mathematical modelling and quantitative analysis for the decision-making. This decision-
247 making process consists of assessing various alternatives regarding existing and soon-available technologies and
248 infrastructure. As a consequence, this paper contributes to the field of urban freight by rail in three aspects:

- 249 • First, as reported in the literature, relatively little work has been devoted to urban freight by rail. As indicated
250 by Comi and Nuzzolo (2015), only few studies have explored modelling freight demand for rail in urban
251 context. This paper seems to be the first to address such a system by identifying the scientific issues at
252 different decision-making levels that need quantitative analysis
- 253 • Second, to the best of our knowledge, this paper is the first to formulate the goods transport using urban
254 passenger rail network into a MIP and solve it efficiently.
- 255 • Finally, it develops a simulation model which is crucial to evaluate and analyse ex ante the impact of
256 introducing freight transport service into the passenger one.

257 3 STRATEGICAL, TACTICAL AND OPERATIONAL ISSUES IN URBAN FREIGHT TRANSPORT WITH 258 PASSENGER RAIL NETWORK

259 In this section, we investigate the global problem of integrating urban freight transport into passenger rail network
260 and identify major issues that need to be addressed both from scientific and operations points of view at various
261 decision-making levels. This will not only position the main topic of this study into its real-life context but also shows
262 its relevance to further address other issues.

263 Urban rail network has two important specificities, with respect to road transportation networks:

- 264 • All lines are physically independent in terms of infrastructure and operations.
- 265 • There are indirect interconnections between certain lines, through connection points with possible transshipment.
266

267 A hypothetical example shown in Figure 1 illustrates goods transportation using the Paris urban rail network. This
268 example shows the important coverage potential when several rail lines are used. This route is composed of two
269 sequential segments corresponding to two lines (D and E). Each segment corresponds to a portion of the route using a
270 single line and a single train.
271

272 Figure 2 presents nine interrelated subproblems dealing with the global issue, from long-term strategic decisions to
273 short-term operational ones. These problems are numbered from strategical level to operational level.
274

275 • At the strategic level:

- 276 ○ Storage-space-sizing in stations: Problems 1 and 2 in Figure 2 define the appropriate space needed to
277 store goods before and after their transport by train. This long-term decision should be studied for the
278 new stations that are to be built in the “Grand Paris” project. This issue is crucial since it becomes
279 very expensive to expand these areas once it is built. In order to accurately determine the size of these
280 storage areas, many data should be collected. In particular, the needed information is related to the
281 forecast of the potential demand and supply, the potentially available area in existing stations, the
282 definition of the transport process to evaluate the time spent by goods in stations before and after the
283 transport...
284




Figure 1: An illustration of freight transport using Paris passenger rail network.

285
286
287
288




Figure 2: The temporal hierarchical schema decomposing the global issue into 9 sub-problems.

289
290

- 291
- 292
- 293
- 294
- 295
- 296
- 297
- 298
- 299
- 300
- 301
- 302
- 303
- 304
- 305
- 306
- 307
- 308
- 309
- 310
- 311
- 312
- 313
- 314
- 315
- 316
- 317
- 318
- 319
- 320
- 321
- 322
- 323
- 324
- 325
- 326
- 327
- 328
- 329
- 330
- 331
- 332
- 333
- 334
- 335
- 336
- **At the tactical level:**
 - Trains frequency and sizing: It is noted as problem 3 and it determines the number of railcars to purchase for freight transport and the frequency of these cars must be used on a daily basis. This frequency must be quite stable over time. For the time being, it is impossible to transform a passenger car into a freight one or reversely. In the future, it will certainly be possible to design flexible railcars to serve passengers in peak periods and freight in off-peak periods. But such cars will certainly have a higher purchase cost than dedicated ones and cost more during the operating phase because of the additional cost for adjustment. In any case, the number of cars of each type (flexible or dedicated) must be decided as accurately as possible in order to maximize profitability. However, the number of cars in trains allocated for freight during a period can be fixed or variable. For example, it could be interesting to dedicate more space to freight when the passenger traffic is less important (e.g. on weekend mornings). At the opposite, there can be fewer or even no cars dedicated to freight when passenger traffic is important such as weekend evenings.
 - **At the operational level:**
 - 2D/3D bin packing problem: Problems 4 and 5 in Figure 2 are related to the temporary storage areas. These problems aim to: 1- optimize the use of space in order to maximize the number of transported boxes, 2- minimize the material-handling operations.
 - Train timetabling: it is problem 6 which is to determine the optimal timetable of trains during an operating period. To adjust the goods transport capacity during a period, the planning should be defined in terms of number of trains that should be planned whereas their starting and arrival times are determined. The timetable could be very close to the one without freight transport since there is a very strong constraint about the impact on passenger traffic. However, it should be regularly recomputed regarding to freight demand and updated if necessary in order to respond to new freight demand.
 - 2D/3D bin packing problem in freight cars: Problem 7 is one of the most difficult one. Indeed, the main difficulty lies in choosing the best place for a box that has just been loaded into the train in order to facilitate its handling when unloading it later so that as many as boxes will be loaded in the meantime.
 - Goods delivery in the departure station: Problem 8 regulates the upstream flow (inbound goods flow at the departure rail-station). Hence, the transport company would like to maximize the goods volume during an operating period, in accordance with the transport capacity of the whole system. The main issue here is to regulate the upstream flow so that the transport company could propose a commercial offer with different rates to balance the demand arrivals within a day. For example, it could be relevant to charge less for goods transport during off-peak periods. The load balance could also be performed among stations so that if an important volume arrives to one station, some boxes could be loaded in other stations to smooth working load regarding to stations' capacity.
 - Freight Rail Transport Scheduling or Dispatching: This problem noted as problem 9 determines the time and the train to load each demand so that the total waiting time is minimized. The waiting time of a demand is measured as the difference between the time it is loaded into the train and the time it arrives at its departure station (called arrival time or ready-for-departure time). This goal allows to maximize the turnover of goods in stations which is equivalent to minimizing the temporary storage area in the stations. In this problem, several technical and operational constraints or parameters must be taken into account such as the time / space limits for the goods loaded into the trains. The results of this problem are essential to solve other problems such as problems 1, 2, and 3.

337

338

339

340

341

342

343

344

345

346

347

348

This paper focuses on the Freight Rail Transport Scheduling Problem. The main contribution is to provide decision makers with a tool enabling them to evaluate and assess, through quantitative analysis and discrete-event simulation, the impacts on various aspects under various scenarios, of integrating freight flow with passenger one. Moreover, since the traffic of passengers remains the priority, this new service could be relevant only if it does not disturb the passenger traffic. Furthermore, the “Grand Paris” project with new lines and stations focuses on the capacity of trains to transport this freight flow since the size of stations, hence the temporary storage area, is not fixed yet. However, it is important to evaluate the additional investment for plausible scenarios. That is why optimization tools as well as simulation tools are necessary to optimize the use of resources on the one hand and evaluate the additional resources required under various scenarios on the other hand. Sections 4, 5 and 6 are dedicated to the description of the FRTSP, the optimization models and methods for the use of resources. And Section 7 describes the simulation environment that can be used to not only evaluate the performances of these models and methods but also provide information about the impact of additional resources.

349 4 FREIGHT RAIL TRANSPORT SCHEDULING PROBLEM: DESCRIPTION AND ASSUMPTIONS

350 The current Paris rail network is already complex with three modes described as follows:

- 351 • The subway, covering mainly the city center, has a network of 220 km and serving 302 stations.
- 352 • The tram which is actually around the city center and in some departments of “Ile de France” (outskirts of Paris),
- 353 with a network of 104 km and serving 181 stations.
- 354 • The commuter rail (RER) linking the localities of “Ile de France” to Paris city center, with a network of 587 km
- 355 and serving 257 stations.

356 All these three transport modes are characterized by the following physical components:

- 357 • Stations: there are three types of stations: underground stations, at ground level stations and elevated stations.
- 358 • Railway: same as for stations.
- 359 • Trains: subways or metro, trams and suburban or commuter trains.

360 Mixing freight with passenger transport using rail network involves the sharing of at least one of these resources.

361
362 In the remainder of the paper, we consider the complete sharing of these three physical components. Consequently,
363 the operating time is also shared since some trains will transport freight and passengers simultaneously. Indeed, with
364 passengers in the train, the travel must meet the operating constraints for passenger transport, such as the strong limits
365 on the stopping time at stations. Moreover, the current legislation in France forbids conflating freight with the passenger
366 transport in a same car for various reasons. Consequently, it is proposed to reserve some cars at the end of trains for
367 freight with a separate and inaccessible space dedicated to freight loading/unloading operations. In this case, the sharing
368 would be more appropriate during off-peak periods to avoid loading/unloading goods when the stations are crowded.

369
370 The FRTSP considers a single line in the rail network illustrated in Figure 3. On this line, S passenger stations can
371 be used for loading and unloading goods and the travel time between two successive stations is known and fixed. The
372 goods are packed in identical standardized boxes. All trains are able to transport goods with a pre-determined capacity
373 which is expressed as the maximum number of standardized boxes. Goods correspond to customer orders or demands.
374 Each order or demand may involve different number of boxes. The orders have independent ready-for-departure times
375 at the departure station. Figure 3 provides an illustration of this problem, showing the demands and train queues. In this
376 paper, we only consider the problem involving a single rail line. The approaches can be used when several lines are
377 involved, since the lines are independent one of another, except at connecting stations. This extension can be done by
378 solving a coordinating problem which consists of synchronizing the transshipment operations with usual
379 loading/unloading operations.

380 We make the following assumptions and introduce some notation for the FRTSP:

- 381 • Transport demands are known in advance and there are J of them per day.
- 382 • Goods are put in standardized boxes. Although each customer may require different products in different quantities,
383 standardization of boxes allows to measure the transport demand of each customer in number of boxes. The number
384 of boxes of demand j is noted Q_j .
- 385 • Demand j becomes ready for departure from its departure station at time r_j , called ready-for-departure time.
- 386 • Goods transport takes place during off-peak periods.
- 387 • The train departure time from station 1 is known in advance, it is given by l_t for train t . T trains are available to
388 connect S stations through the line during the day.
- 389 • The capacity allocated for goods in train t is given by cap_t . If a train is fully dedicated to passenger transport, it
390 must be eliminated from the input timetable for passenger transport.
- 391 • The time needed for loading and unloading each box is considered as the same and is noted h , independent of
392 demands, trains, and stations.
- 393 • Any station of the line is a potential station to load or unload goods. So, the goods have to be delivered to their
394 respective departure stations and recovered from their respective arrival stations.
- 395 • The storage area for departing demands at each station s is of limited capacity C_s in terms of maximum number of
396 boxes stored simultaneously, even though this capacity is set to a very large value in the experiments to investigate
397 new lines and new stations. Actually the rail-network operator is more concerned by train capacity in this context.
- 398 • When a demand arrives at its destination, it is immediately evacuated from the station. As a consequence, there is no
399 need to consider storage capacity for arriving demands
- 400 • The travel time between two successive stations is considered to be known and given by tt_s .
- 401 • The maximum waiting time of a train at each station is given by $Wait_{max}$.
- 402 • The minimum waiting time which is necessary to board passengers at each station is known and fixed, it is $Wait_{min}$.




Figure 3: An illustration of trains and demand queues in the FRTSP.

406
407
408
409
410
411
412
413
414
415

Without loss of generality and for the sake of convenience, the demands are assumed to be numbered in nondecreasing order of the ready-for-departure times; in other words,

$$r_1 \leq r_2 \leq \dots \leq r_j$$

Table 1 summarizes the notation used throughout the paper.

Table 1

Notation.

Indexes	$j : 1, \dots, J$	for demands
	$t : 1, \dots, T$	for trains
	$s : 1, \dots, S$	for stations
And Parameters	r_j	ready-for-departure time for demand j
	d_j	departure station for demand j
	a_j	arrival station for demand j
	l_t	train t 's departure time from the station 1
	J	number of demands
	T	number of trains
	S	number of stations
	C_s	Storage capacity at station s
	tt_s	travel time from station s to the next one
	J_s	set of demands needing to pass by station s
	J'_s	set of demands departing from or arriving at station s
	D_j	set of demands departing from the same station as demand j and is ready for departure earlier than j : $D_j = \{i < j d_i = d_j\}$
	Q_j	number of boxes required to pack demand j
	cap_t	goods transport capacity of train t
	$Wait_{max}$	maximum waiting time of trains at any station
	$Wait_{min}$	minimum waiting time of trains at any station
	Decision Variables	h
M		A large positive number
$x_{j,t,s}$		1 if demand j is in train t at station s , 0 otherwise
$y_{i,j}$		1 if $i \in D_j$ and i is not yet loaded when j becomes ready for departure
$C_{t,s}$	waiting time of train t at station s	
R_j	time at which demand j is loaded (at station d_j)	

416

417 **5 A MIXED INTEGER MATHEMATICAL PROGRAMMING MODEL AND COMPLEXITY ANALYSIS**

418 The problem described above can be formulated into a mixed integer program as follows.

419
$$\text{Minimize } \sum_{j=1}^J \sum_{t=1}^T (R_j - r_j x_{j,t,d_j}) \quad (1)$$

420 subject to

421
$$\sum_{t=1}^T x_{j,t,d_j} = 1 \quad j = 1, 2, \dots, J \quad (2)$$

422
$$x_{j,t,s} - x_{j,t,s+1} = 0 \quad s \in [d_j, a_j - 1], j = 1, 2, \dots, J \quad (3)$$

423
$$\sum_{j \in J_s} x_{j,t,s} \times Q_j \leq \text{cap}_t \quad t = 1, \dots, T, s = 1, \dots, S \quad (4)$$

424
$$x_{j,t,d_j} \times r_j \leq l_t + \sum_{s=1}^{d_j-1} (C_{t,s} + tt_s) \quad j = 1, \dots, J, t = 1, \dots, T \quad (5)$$

425
$$C_{t,s} \geq \text{Wait}_{\min} \quad t = 1, \dots, T, s = 1, \dots, S \quad (6)$$

426
$$C_{t,s} \geq \sum_{j \in J'_s} h \times Q_j x_{j,t,s} \quad t = 1, \dots, T, s = 1, \dots, S \quad (7)$$

427
$$C_{t,s} \leq \text{Wait}_{\max} \quad t = 1, \dots, T, s = 1, \dots, S \quad (8)$$

428
$$R_j \geq l_t + \sum_{s=1}^{d_j-1} (C_{t,s} + tt_s) - M(1 - x_{j,t,d_j}) \quad j = 1, \dots, J, t = 1, \dots, T \quad (9)$$

429
$$R_i \leq r_j + M y_{i,j} \quad i \in D_j, j = 1, \dots, J \quad (10)$$

430
$$\sum_{i \in D_j} y_{i,j} \times Q_i \leq C_{d_j} - Q_j \quad j = 1, \dots, J \quad (11)$$

431
$$x_{j,t,s} \in \{0, 1\}, C_{t,s} \geq 0, R_j \geq 0 \quad t = 1, \dots, T, s = 1, \dots, S, j = 1, \dots, J \quad (12)$$

432
$$y_{i,j} \in \{0, 1\}, \quad i \in D_j, j = 1, \dots, J \quad (13)$$

433 where $J_s = \{j | d_j \leq s < a_j\}$ and $J'_s = \{j | s \in \{d_j, a_j\}\}$ represent the set of demands needing to pass by station s and the
434 set of demands such that station s is either a departure or an arrival station, respectively.

435
436 In this model, the objective function expresses the minimization of the total waiting time of all demands in their
437 departure stations. Constraint set (2) assigns each demand to exactly one train at its departure station. Constraint set (3)
438 imposes train continuity for each demand so that each demand's transport is ensured to be performed by the same train
439 throughout the portion of the line between its departure and arrival stations. Constraint set (4) deals with the capacity or
440 space limit in the train. Since at arrival stations goods are unloaded from the train, constraint set (4) considers only
441 those remaining in the train. Constraint set (5) respects the arrival times of demands, so that a demand can only be
442 assigned to a train arriving later at the departure station of the demand. Constraints sets (6), (7) and (8) determine the
443 waiting time of train t at station s . Constraint set (9) determines the earliest time at which demand j is loaded into train t .
444 Constraints (10) ensure the consistency of the definition of $y_{i,j}$. For any couple of demands i and j such that $i \in D_j$, if i
445 departs after demand j becomes ready for departure; i.e., $R_i > r_j$, constraints (10) require that $y_{i,j} = 1$, which is
446 consistent with the definition. Constraints (11) express the storage capacity at each station. When demand j becomes
447 ready for departures at its departure station, the number of boxes that are available but have not yet been loaded must
448 not exceed the storage capacity of this station.

449 The computational complexity of this problem can be evaluated by considering the following special case:

- 450
451 • All demands are available at time 0, at the same departure station with the same arrival station: $r_j = 0, d_j = 1$ and a_j
452 $= 2, \forall j \in J$.
453 • Each demand should be transported by exactly one train.
454 • Trains' timetable is known in advance together with the frequency of trains.
455 • The travel time between the departure and arrival stations is the same for all trains regardless of the number of
456 loaded boxes.
457 • The trains can carry several demands at the same time, but with a limited capacity.
458 • The waiting time of trains at stations is unlimited.
459 • The storage capacity at the stations are unlimited

460
461 In this special case, the waiting time of demand j is equal to the departure time of the train it is loaded into. The
462 previous MIP model with these assumptions becomes:

463
$$\text{Minimize } \sum_{j=1}^J \sum_{t=1}^T (x_{j,t} \times l_t) \quad (14)$$

464
$$\sum_{t=1}^T x_{j,t} = 1 \quad j = 1, 2, \dots, J \quad (15)$$

465
$$\sum_{j=1}^J Q_j \times x_{j,t} \leq cap_t \quad t = 1, 2, \dots, T \quad (16)$$

466
$$x_{j,t} \in \{0,1\} \quad j = 1, 2, \dots, J, t = 1, 2, \dots, T$$

467 Thus, the problem of transporting goods as soon as possible is reduced to a generalized assignment problem, where
 468 the objective is to minimize the total cost of assigning J jobs to T agents (14), so that each job, which corresponds to a
 469 demand, is assigned to exactly one agent, which corresponds to a train in our case (15), subject to the capacity
 470 constraints of the agents - “trains” (16). Because the generalized assignment problem is NP-hard (Fisher et al., 1986),
 471 the studied problem is therefore also NP-hard.

472 **6 SOLUTION METHODS TO THE FRTSP**

473 Because of the NP-hardness of the FRTSP, it cannot be solved in a reasonable amount of time for real-life instances
 474 which are often very large. On the other hand, the problem being at an operational level, it requires a very short
 475 response time. Furthermore, the decision must be frequently recomputed, due to random events, for instance, that render
 476 the decision made previously far from optimum and even infeasible. Therefore, heuristics that require very short
 477 computation times, which is a major issue for practitioners in addition to their ease of understanding regarding the
 478 solution-building process, are commonplace in industry for operational decision making. In the following subsections,
 479 we propose two heuristics.

480 Both heuristics assign the demands into the trains so that the following operating constraints are ensured:

- 481 • The limits on the waiting time of each train in each station.
 482 • The train capacity.
 483 • The arrival time of each demand at its departure station.
 484 • The travel time of trains through the line.
 485 • The storage capacity at each station

486 Both heuristics consider the trains one after another in the order of their arrivals at station 1 and a single train is
 487 considered in each iteration. The difference between them lies in the way of selecting the demands at each station to be
 488 loaded into the considered train. One of them, called BDH for best-dispatching-rule heuristic, consists of using three
 489 dispatching rules and then selecting the best among the obtained solutions. The other, called STH for single-train-based
 490 heuristic, optimally selects the demands to load into the train. We now describe each of these heuristics, we only focus
 491 on how to select the demands to load into the considered train.

492 *6.1 Heuristics based on dispatching rules*

493 When a train is considered, the stations are examined from upstream to downstream in the order of 1, 2, ..., S . At
 494 each station s , we identify the set of demands that can be loaded into the train; in other words, the demands in this set
 495 must satisfy the following conditions:

- 496 1. It has not been loaded into earlier trains
 497 2. Station s is their departure station
 498 3. They are available at the time when the train arrives at station s

499 Then some of these demands are selected to be loaded into the train according to one of three dispatching rules. In
 500 practice, the before-mentioned set of demands is arranged into a list in decreasing order of the priority defined by the
 501 dispatching rule. This list of demands is then scanned, and the first demand in the list such that the remaining capacity
 502 and the remaining waiting time of the train are sufficient to load it is actually loaded into the train and then removed
 503 from the list.

504 The dispatching rules considered are the following:

- 505 • FIFO: The earlier a demand becomes ready for departure, the higher priority it has. The idea is to avoid waiting of
 506 the demands.
 507 • Largest-volume-first: The more boxes a demand involves, the higher priority it has. The underlying idea is to
 508 occupy as little as possible the storage areas in the stations.
 509 • Smallest-volume-first: The fewer boxes a demand contains, the higher priority it has. The intuitive idea is that the
 510 smallest demands have the highest chance to be transported and this allows to transport the most demands as quickly
 511 as possible.

517 6.2 Single-train-based heuristic

518 One shortcoming of the previous rule-based heuristic is its myopic nature, since each demand is loaded into a train
519 without considering other demands especially those at the downstream stations. In addition, regarding the combinatorial
520 nature of the problem, the solutions obtained with this heuristic are very likely to be far from being optimal. We
521 therefore develop a more elaborate method with some looking-ahead attitude. As shown previously, the problem is
522 NP-hard and fast algorithms are needed for large instances. The complexity of the problem is related to the numbers of
523 demands, trains and stations. Nevertheless, if the single-train-related subproblems are small enough to be solved into
524 optimality, which is the case in the experiments reported in Section 8, it is preferable to do so. In this case, we should
525 not consider the stations separately. We therefore identify the set of demands Ω_t satisfying the following conditions:

- 526 1. They have not been loaded into earlier trains
- 527 2. They are available when the train arrives at their respective departure station: $r_j \leq l_t + \sum_{s=1}^{d_j-1} (Wait_{max} + tt_s)$

528
529
530 So-defined sub-problem related to a single train t can be formulated as follows.

$$531 \quad \text{Minimize } \sum_{j \in \Omega_t} (R_j - r_j x_{j,d_j}) \quad (17)$$

532 subject to

$$533 \quad x_{j,d_j} \leq 1, \quad j \in \Omega_t \quad (18)$$

$$534 \quad x_{j,s} - x_{j,s+1} = 0 \quad s \in [d_j, a_j - 1], j \in \Omega_t \quad (19)$$

$$535 \quad \sum_{j \in J_s} x_{j,s} \times Q_j \leq cap_t \quad s = 1, 2, \dots, S \quad (20)$$

$$536 \quad x_{j,d_j} \times r_j \leq l_t + \sum_{s=1}^{d_j-1} (C_s + tt_s) \quad j \in \Omega_t \quad (21)$$

$$537 \quad C_s \geq Wait_{min} \quad s = 1, \dots, S \quad (22)$$

$$538 \quad C_s \geq \sum_{j \in J_s} h \times Q_j x_{j,s} \quad s = 1, \dots, S \quad (23)$$

$$539 \quad C_s \leq Wait_{max} \quad s = 1, \dots, S \quad (24)$$

$$540 \quad R_j \geq l_t + \sum_{s=1}^{d_j-1} (C_s + tt_s) - M(1 - x_{j,d_j}) \quad j \in \Omega_t \quad (25)$$

$$541 \quad \sum_{i \in D_j \cap \Omega_t} (1 - x_{i,d_i}) \times Q_i \leq C_{d_j} - Q_j \quad j \in \Omega_t \quad (26)$$

$$542 \quad x_{j,s} \in \{0,1\}, C_s \geq 0, R_j \geq 0 \quad j \in \Omega_t, s = 1, \dots, S \quad (27)$$

543
544 Note that constraint (18), which comes from constraint (2), is an inequality, instead of an equality as in (2), because
545 we cannot require all the demands in Ω_t to be loaded into train t . Because of this constraint, as it is, there is a trivial
546 optimal solution to this single-train-related subproblem defined by (17) to (27), by setting all decision variables to 0; in
547 other words, by loading no demand at all! Obviously, this is not what we are looking for, since the most important
548 resource – the train – would not be used. Actually, an (even more) important objective function which is maximizing
549 the number of transported demands is missing in this model. That is why for each train t , instead of solving the problem
550 defined by (17) to (27), we add a primary objective aiming to maximize the number of transported demands, to
551 transform the problem into a bi-objective decision-making problem. To be more specific, this problem can be rewritten
552 as follows.

$$553 \quad \text{Primary objective: Maximize } \sum_{j \in \Omega_t} x_{j,d_j} \quad (28)$$

$$554 \quad \text{Secondary objective Minimize } \sum_{j \in \Omega_t} (R_j - r_j x_{j,d_j}) \quad (29)$$

555 subject to (18) --- (27)

556
557 This bi-objective problem can be solved by solving successively two single-objective problems P1 and P2 defined
558 as follows.

559 **Problem P1:** Maximize $\sum_{j \in \Omega_t} x_{j,d_j}$ subject to (18)---(27).

560 **Problem P2:** Minimize $\sum_{j \in \Omega_t} (R_j - r_j x_{j,d_j})$ subject to (18)---(27) and $\sum_{j \in \Omega_t} x_{j,d_j} = \omega$

561 where ω is the optimal objective value of Problem P1.

562 Both problems P1 and P2 being single-objective MIPs, they can be solved using standard MIP solvers such as
563 CPLEX. Note that solving P1 and P2 using CPLEX can solve to optimality the problem defined in (28) and (29) which

564 is related to a single train. The concatenation of so-obtained solutions to single-train subproblems cannot be guaranteed
 565 to be optimal to the problem defined by (1)---(13) because of the decomposition. That is why it is only a heuristic.

566 **7 PROBLEM MODELING AND SIMULATION USING ARENA**

567 This section describe the simulation model we develop, on the one hand, to fulfil operational requirement for
 568 practitioners, and on the other hand, to make sure, from an academic point of view, that the mathematical model is close
 569 to the reality and to evaluate and simulate the dynamics, the behavior of the system. From an operational standpoint, a
 570 full-scale experimentation in real life would need a heavy investment in terms of finance, time, disturbances and risks.
 571 Computer simulation is therefore essential to anticipate various scenarios. Furthermore, simulation models are also
 572 widely used in academic research by combining them with other tools (Borodin, 2014) as we do here. Actually,
 573 mathematical models often require explicit expressions of constraints and objectives in decision variables, which is not
 574 always possible. Simulation can then be used to evaluate these indicators. Furthermore, mathematical models cannot
 575 take into account all the aspects of a problem then simulation is a very useful complement, especially when some
 576 parameters are not accurate.

577 As Dessouky and Leachman (1995) put it, “the rail networks are complex, compound delays and ripple effects from
 578 conflicts at complex junctions, stations, and railroad-railroad crossings at grade and other factors in some rail networks
 579 make it difficult to develop analytical models to study delays and capacity”. Motraghi and Marinov (2012) explain that
 580 “the complexity of the real world systems makes it hard for analytical models to provide clear analysis and are often not
 581 economically viable to use. On the other hand, simulation models enable low-cost experimentation and the modeling of
 582 this complexity which can lead to accurate results and conclusions”.

583 Simulation for rail transport was studied by Motraghi and Marinov (2012), Grube et al. (2010), Dessouky and
 584 Leachman (1995), Marinov et al. (2010). Several specific simulation software packages are available for modeling and
 585 simulating rail networks (Furtado, 2011), such as Rail Traffic Controller, Open Track and Railsys. However, to consider
 586 the queuing nature of the FRTSP, discrete-event simulation software packages are more suitable. ARENA, WITNESS
 587 and SIMUL 8 are such tools.

589 In this study, we develop a very general framework to model rail networks. This framework can be easily adapted
 590 to all cities. We take advantage of this framework to model all issues related to rail network, especially the FRTSP we
 591 focus on in this paper. ARENA Software is used for this purpose. For more information about this software, the reader
 592 may refer to Rossetti (2010) or Altioek and Melamed (2007). One major reason for this choice is its ability to consider
 593 all the identified technical and operational constraints. In addition, the compatibility with a programming script such as
 594 Visual Basic (VBA) allows implementing various decision-making problems defined at the beginning of the paper. The
 595 developed model for FRTSP is composed of three parts as shown in Figure 4 and described hereafter.
 596




Figure 4: The ARENA Model.

597
598

599 7.1 Part 1: Freight transport demand generator

600 This part of the model generates J demands during the pre-operating period. For each demand j , the following
601 characteristics are generated according to a given probability distribution: the departure station, the arrival station, the
602 arrival or ready-for-departure time at its departure station, and the number of boxes required to pack it.

603 All generated data are saved in a “demand” matrix in VBA environment. During an operating period, at its arrival
604 time, a demand is added to the queue of its departure station, in order to be transported.

606 7.2 Part 2: Train generator

607 This part of the model generates a timetable involving T mixed freight / passenger trains during an operating period
608 while making sure that the timetable is periodic. To simulate the timetable of trains for the next operating period, all
609 trains are generated at the same time (they are not dynamically generated).

610 VBA block is used to save all parameters for the subsequent calculations. ARENA blocks Queue, Seize, Delay and
611 Release simulate the process of train arrivals into the railway line according to the timetable. The time at which train t is
612 introduced into the line is calculated in the delay block according to the operation: $l_t - l_{t-1}$.

614 7.3 Part 3: Railway line

615 This part of the model represents the railway line that is composed of:

- 616 • Railroads (or interconnection line “rail” in Figure 4): modeled by a “DELAY” block that expresses the time required
617 to travel the distance between two successive stations.
- 618 • Stations: this is the physical place where the trains stop to board passengers and load / unload goods. Depending on
619 the freight load in the train and the algorithm implemented in the Arena VBA blocks, the boxes in this station are
620 loaded or not. Thus, depending on the number of boxes to be transported, the waiting time of train t at station s is
621 calculated and saved in the delay block of the ARENA block “stationS” which is a dynamic Arena process.

622 8 EXPERIMENTAL STUDY AND SIMULATION

623 One of major difficulties when studying a new system, including the one investigated in this work, is the lack of
624 data such as freight demand because of the absence of historical data. However, to run a simulation model, instances are
625 needed and should be as realistic as possible. In this experimental study, we use instances generated randomly but on
626 the basis of some available data such as trains' timetables and capacity. For the other parameters, random values are
627 generated on the basis of transport company projections. The simulation model aims to evaluate the performance of the
628 transportation system under study when optimized decisions are integrated into the system's dynamics. As the studied
629 problem is NP-hard, in order to compare the performance of heuristics with the optimal solution, the instances' size
630 must be reasonable (simulation duration, number of demands, trains and stations). The simulation process provides an
631 important stream of output which is reported and analyzed.

633 8.1 Simulating parameters and instance generation

634 A typical line is considered with ten stations which are indexed from 1 to 10. The goods travel through the line
635 from the lowest-indexed station to the highest one. The duration of the simulation is 300 minutes during which there are
636 30 trains which pass through the line with a frequency defined as one train every 10 minutes. The capacity allocated to
637 freight in any train is 15 boxes representing 30% of the total train capacity. The travel time between two successive
638 stations is estimated at 5 minutes. The maximum waiting time of a train at any station is 1 minute and the minimum
639 waiting time for passenger boarding is 30 seconds. The time required to load or unload each box is 10 seconds. For the
640 other parameters, they are generated as follows:

- 641 • The arrival (or ready-for-departure) times of demands are generated using a uniform distribution $r_j \in U[0,240]$
642 minutes where 0 corresponds to the initial time which could be 10 am for instance. The upper bound fixed to 240
643 minutes corresponds to the latest possible arrival time for any demand.
- 644 • Demand sizes " Q_j ": the size of a demand is between 1 and 5 ($U[1,5]$) measured in number of standard boxes.
- 645 • Departure and arrival stations: randomly generated between the first station and the last one for each demand.

647 8.2 Numerical results

648 The experiments are run on an Intel Xeon CPU E3-1245 v3 @ 3.40 GHz with 8 GB RAM. The simulation software
649 used is ARENA version 14.7. CPLEX 12.5 is used for MIP solving. Default parameters are used for the experiments.
650 BDH is implemented in VBA and is launched when the entity “train” passes through VBA block before each station.

651 Thus, the demands to be transported from this station by the current train are identified and their loading is performed
 652 when the entity “train” stops in the corresponding station (ARENA block “stationS”).

653 The generated instances are classified into categories according to the number of demands. Each category is
 654 composed of 25 instances. The computational results for each category are reported in Table 2 which gives the mean
 655 value of the average waiting time (in seconds) per demand over the 25 instances of that category.
 656

657 **Table 2**

658 Computational results of MIP, Best-Dispatching-Rule Heuristic and Single-Train-based Heuristic.

Number of demands	Number of Variables	Number of Constraints	C.T. MIP (CPU sec.)	W.T. MIP	Gap (BDH vs MIP)	Gap (STH vs MIP)	C.T. STH (CPU sec.)
10	3 600	4 510	0.1	251	56.22%	0.04%	~0
20	6 900	7 820	0.2	316	28.32%	1.11%	~0
30	10 200	11 130	0.4	365	26.56%	3.60%	~0
40	13 500	14 400	0.5	401	23.48%	4.55%	~0
50	16 800	17 750	0.6	421	23.89%	9.45%	~0
60	20 100	21 060	1.0	470	29.26%	13.06%	~0
70	23 400	24 370	1.5	491	30.29%	17.53%	0.1
80	26 700	27 680	3.0	574	43.36%	24.66%	0.1
90	30 000	30 990	3.5	577	40.76%	27.41%	0.1
100	33 300	34 300	14.9	704	36.71%	31.29%	0.1

659 For the MIP model, this table gives the numbers of variables and constraints, the mean computation time, and the
 660 mean waiting time. It reports for the heuristics BDH and STH, the mean waiting time and the mean gap versus the
 661 optimal solution measured in relative terms.
 662

663 This table clearly shows a direct correlation between the waiting time and the number of demands. Regarding the
 664 MIP model, it quickly finds optimal solutions for the instances with up to 50 demands (the solutions are found in less
 665 than 1 second). For the instances with up to 100 demands the average computation time is less than 15 seconds, even
 666 though the computation time is as long as about 90 seconds for one of the instances with 100 demands. This table also
 667 shows the advantage of using STH, especially for small size instances. The computation time is very short, but the
 668 solution obtained is much closer to the optimum. It seems to be a good trade-off between standard MIP solvers and
 669 dispatching rules.
 670

671 The gap between BDH and optimal solutions is caused by two factors. One of them is the fact that the optimal
 672 waiting time may be close to 0. In this case, even if the waiting time given by BDH is small in absolute terms, the gap
 673 can be very large in relative terms. Another factor comes from the decomposition of the problem into train-related
 674 subproblems. When solving each of such subproblems, the demands which need to be transported during few number of
 675 stations (with small values of $a_j - d_j$) are selected since this will maximize the number of demands transported. As a
 676 consequence, the demands which need to be transported along a large number of stations have to wait for a long time,
 677 which leads to a large total waiting time for the global problem. We are continuing working on this point for fix it.
 678

679 To evaluate the limits of the MIP model, instances with up to 150 demands (all other parameters are the same) are
 680 tested, with a limit of 30 minutes on the computation time.
 681

682 Table 3 summarizes the computational results for these instances. Column 1 shows the number of demands.
 683 Column “#Inf.” gives the number of instances without any feasible solution, due to the impossibility of transporting all
 684 demands for instance. Column “#Solved” shows the number of instances solved to optimality by CPLEX within 30
 685 minutes and Column “C.T. MIP” gives the average computation times for those instances and column “Gap (Cplex)”
 686 gives the average optimality gap in percentage for the instances which are feasible but failed to be solved to optimality
 687 within 30 minutes. Column “#Inc.” shows the number of instances where some demands are unloaded in the solution
 688 provided by STH. Such a solution is referred to as incomplete in the remainder. Column “C.T. STH” gives the average
 689 computation times of STH. Finally, the last column gives the mean gap measured in relative terms between the solution
 690 provided by STH (considering only instances for which all demands are loaded) and the best solution given by MIP
 691 within 30 minutes.
 692

693 On the one hand, the computational results reported in Table 3 show that with 150 demands, the MIP model is not
 694 able to solve all instances to optimality. On the other hand, we observe that STH gives solutions very quickly (within
 695 less than a second), with a gap of around 40%. However, it is not able to find a complete solution to most instances with
 696 all demands loaded while such solutions exist, particularly for instances with 150 demands.
 697
 698

699
700

Table 3

Computational results of MIP and Single-Train-based Heuristic for instances with 110 to 150 demands

<i>J</i>	MIP results				STH results		Gap STH vs MIP (best sol.)
	#Inf.	#Solved	C.T. MIP (CPU sec.)	Gap (Cplex)	#Inc.	C.T. STH (CPU sec.)	
110	0	25	43	-	1	0.34	41.87
120	0	25	265	-	1	0.38	44.06
130	0	24	395	2.22	7	0.41	37.57
140	2	12	732	1.54	12	0.47	41.43
150	3	0	-	6.52	20	0.82	45.07

701
702
703
704
705
706
707

To evaluate the computational limits of STH, we have tested additional instances with more demands to be transported. For almost all instances, the yielded solutions are incomplete. Note that the computation times do not exceed 5 seconds even for instances with 1,000 demands. An analysis of these results shows that the two constraints on train capacity and waiting time in stations lead to very few possibilities of loading demands into each train, which explains the ability of STH to provide solutions very quickly, even with a large number of demands.

708
709
710
711

To confirm these conclusions, we have increased the train capacity to 100 boxes and reduced the time required to lead one box to 1 second, even though such values are unrealistic. The test on 25 instances with 1,000 demands shows a relative slight increase in computation times. A solution is nevertheless obtained in less than 7 minutes on average.

712
713
714

We further evaluate the impact of the algorithms on the different core components of the railway system. Hence, this impact is studied regarding the dynamics of the demands, the use of trains and stations. Thus, we propose several performance measures to highlight the behavior of each algorithm.

715

8.2.1 *Impact on transported demands:*

716
717
718
719
720

To characterize the goods waiting time, the average waiting times of the demands at stations are computed and reported in the column "Mean" of Table 4. However, it is also important to have a certain balance of performance between the stations of the line. Thus, it is suggested to compute the average waiting times for the first three stations, the three middle stations and the last three ones as shown in Figure 5 (noted respectively, MS, MM and ME in Table 4).

721
722
723
724
725
726

The optimization of the total waiting time generates solutions with imbalanced waiting times in stations. Indeed, the waiting time at each station increases during the trip. This phenomenon could be explained partly by the fact that the train is empty at the beginning and is gradually filled up as it moves to the end of the line. Moreover, at the first stations there are generally no unloading operations whereas in the middle of the line, both loading and unloading operations are necessary and the limit on waiting time therefore quickly runs out, which limits the number of boxes to load and unload.

727
728

Table 4

Simulation results on average waiting times (in seconds).

Demand Sizes	MIP				BDH				STH			
	Mean	MS	MM	ME	Mean	MS	MM	ME	Mean	MS	MM	ME
10	172	186	139	191	253	204	247	308	172	186	139	191
20	303	302	264	343	369	314	306	486	306	305	267	347
30	352	318	310	430	450	307	412	632	365	329	321	445
40	402	353	333	522	488	336	378	749	420	369	348	546
50	409	327	334	565	521	336	413	813	448	358	366	618
60	466	363	391	644	605	345	468	1003	527	410	442	728
70	495	390	409	685	641	365	490	1069	582	458	481	805
80	564	447	481	763	830	394	531	1564	703	557	600	951
90	571	452	529	733	818	393	597	1464	727	576	674	934
100	678	474	631	928	939	374	630	1813	890	622	828	1218




Figure 5: Waiting times measures for the railway line.

729
730
731
732

Balancing waiting time in stations makes the total waiting time longer. In practice, the majority of demands depart at the first stations of the line. It is interesting to note the ability of the BDH and STH to reproduce the same behavior than the MIP model. The analysis of detailed results in Table 4 shows that the waiting time of demands increases sharply when the index of station increases and the waiting times increase in all stations with the number of demands.

733
734
735
736
737
738
739
740
741

An interesting feature of the MIP model is its ability to quickly identify infeasible instances mainly due to the impossibility of transporting all demands. In practice, decision makers could expand the temporal horizon in order to artificially increase the capacity by considering next trains for loading the surplus demand.

742
743
744

For the 250 solved instances, the MIP model gives optimal solutions, which means that all instances are feasible. Heuristic BDH fails to find a feasible solution for only one instance, furthermore with only one non-transported demand, due to the lack of space inside the train or because of the limit on the waiting time (hence loading time) at stations.

8.2.2 Impact on trains:

745
746
747
748
749
750
751
752
753

The train efficiency is evaluated through their capacity-use rate. This rate is relative to each train and is obtained by dividing the number of boxes effectively transported by the maximum-possible number of boxes within a train noted as " UB_t ". To determine UB_t , an idealized case in which we can best use the train capacity is considered where all demands (each composed of one box) have to be transported from one station to the next station starting from the first station of the line. This case occurs when all boxes are available at the train arrival; in other words, they can be assumed to be available at time 0. In order for UB_t not to be far from reality, both temporal loading/unloading constraint and space constraint are taken into account. The formula (30) determines the value of the maximal number of boxes that could be transported as follows:

754

$$UB_t = \min(cap_t, Wait_{max}/h) \times S/2 \quad (30)$$

755
756
757
758
759

Figure 6 gives an illustration of UB_t calculation regarding the previously defined parameters. The average trains' capacity-use rate is 33% for instances with 100 demands. However, as it is said previously, some demands cannot be transported, due to demands' ready-for-departure times at their departure station. Actually, some demands' ready-for-departure times are close to the end of the operating period while the remaining space in the trains is not sufficient.




Figure 6: An illustration of UB_t calculation based on the case study.

760
761

762
763
764
765
766
767
768
769
770

771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786

One way to resorb the congestion at the end of the line is to balance the loading of boxes by smoothing their arrival times at departure stations. As said in section 4, this issue could be addressed within problem 8 of Figure 3.

The minimum waiting time of trains at stations to board passengers is fixed to $Wait_{min} = 30$ seconds. Due to loading operations, the average waiting time increases to 37 seconds (for instances with 100 demands). Also, the average time needed for trains to run through the line from the first station to the last one varies from 49.5 minutes to 50.5 minutes, corresponding to cases with no and many (100) demands, respectively. Thus, the simulation shows that the impact of transporting goods using passenger trains on travel time is very limited with only a 2% increase.

8.2.3 *Impact on stations:*

Table 5 reports for each solution method the observed average/maximum number of demands in stations, simultaneously waiting to be transported. Moreover, the second column shows the observed average/maximum number of boxes in stations, simultaneously waiting to be picked up or to be loaded into a train. This number increases as the number of demands increases in accordance with the MIP model results. However, the boxes remain together generally for a few seconds, 5 minutes in some cases.

There is an interesting finding about the limits on the storage space. These results allow to study the boxes' dynamic flow throughout the line. An analysis of the simulation results could be used to determine the required storage space for a given set of demands. In addition, there is a correlation between the use of space in stations and parameters such as the total number of demands, the longest waiting time of trains in stations, the capacity of trains and the time needed to load/unload a box. This table also shows the interest of using MIP to obtain an optimal solution, since it can lead to an up to 25% reduction in storage space.

Table 5
Simulation results about stations use.

Number of demands	MIP		BDH		STH	
	Avg/Max Dem.	Avg/Max Box.	Avg/Max Dem.	Avg/Max Box.	Avg/Max Dem.	Avg/Max Box.
10	1 / 2	2 / 6	1 / 2	2 / 6	1 / 2	2 / 6
20	1 / 3	3 / 9	1 / 3	3 / 9	1 / 3	3 / 9
30	1 / 3	4 / 10	1 / 3	4 / 10	1 / 3	4 / 10
40	1 / 4	4 / 14	1 / 4	4 / 14	1 / 4	4 / 14
50	2 / 4	5 / 14	2 / 4	5 / 16	2 / 4	5 / 15
60	2 / 4	5 / 15	2 / 5	5 / 15	2 / 5	5 / 15
70	2 / 4	6 / 16	2 / 6	6 / 25	2 / 5	6 / 22
80	2 / 5	7 / 18	2 / 7	8 / 29	2 / 5	8 / 21
90	2 / 5	7 / 19	3 / 7	8 / 23	3 / 6	8 / 23
100	3 / 7	8 / 27	3 / 9	9 / 38	3 / 9	9 / 38

787 **9 CONCLUSION AND FUTURE RESEARCH**

788 This paper addresses an environment-friendly urban freight transportation alternative using the passenger rail
789 infrastructure. This alternative seems to represent an important potential that still needs to be evaluated, especially from
790 technical and financial perspectives. This idea is drawing growing attention in Europe regarding the number of case
791 studies highlighting the ecological and socio-economic benefits. Based on the case of Paris rail network, we propose a
792 general framework to model and simulate such systems and develop some optimization methods to solve an important
793 problem which is the basis to address the global issue.

794
795 More specifically we identify relevant issues that need to be addressed with optimization methods. Then we
796 investigate the FRTSP which considers the most general case in resource sharing (train, rail and stations) and
797 constitutes the basis to further address other related issues. This problem is mathematically formulated into a MIP and
798 its computational complexity is analyzed. We propose two heuristics to obtain near-optimal solutions. The impact of
799 these methods on different parts of the infrastructure and the dynamic behavior are evaluated using a simulation
800 framework. A discrete-event simulation model is developed using ARENA Software. This model improves the
801 understanding of the system's dynamics, which helps better analyze the solution. It allows to study the impact of the

802 decisions on various core components of the transportation system.

803

804 The proposed decision-making process is a necessary step in order to evaluate the benefit for transportation
805 companies of offering such services. It is relevant and necessary to anticipate the needs in different resources especially
806 during network extension as it is the case of the “Grand Paris” project. Furthermore, the approach combining
807 optimization with simulation proposed in this paper could also be used to help decision-makers to gradually schedule
808 customer demands by finding the best loading time considering an existing load. In addition, the simulation model
809 could be also used to take into account disturbances in operations such as train delays or incidents on the network.

810

811 Due to the simulation results, we identify some drawbacks of BDH and STH due to the decomposition into single-
812 train-related subproblems. The next step consists of addressing the links between the trains. Another interesting
813 direction is the generalization of the FRTSP to the multi-line problem where transshipment could be possible via
814 transition hubs. This extension can improve the coverage rate but needs more handling operations in transition hubs.
815 Another promising and relevant extension to get a better coverage rate is incorporating multimodal transportation by
816 considering other transportation modes such as bus or self-service electric cars.

817

818 ACKNOWLEDGMENTS

819

820 The authors would like to express their gratitude to Prof. Jiu-Biing Sheu (Editor-in-Chief) and the anonymous
821 reviewers for their constructive remarks and which have significantly helped improve this paper.

822

823 REFERENCES

824

- 825 Abril, M., F. Barber, L. Ingolotti, M.A. Salido, P. Tormos and A. Lova, 2008. An assessment of railway capacity.
826 *Transportation Research Part E: Logistics and Transportation Review*, 44 (5), p. 774-806.
- 827 ALICE and ERTRAC Urban mobility WG, 2015. Urban freight research roadmap. Publication of Alliance for Logistics
828 Innovation through Collaboration in Europe “ALICE” and European Road Transport Research Advisory Council
829 “ERTRAC”.
- 830 Altiok, T. and B. Melamed, 2007. *Simulation modeling and analysis with ARENA*. Academic Press, Elsevier.
- 831 Anghinolfi, D., M. Paolucci, S. Sacone and S. Siri, 2011. Freight transportation in railway networks with automated
832 terminals: A mathematical model and MIP heuristic approaches. *European Journal of Operational Research*, 214 (3),
833 p. 588-594.
- 834 Behrends, S., 2012a. The urban context of intermodal road-rail transport – Threat or opportunity for modal shift?.
835 7th International Conference on City Logistics, Procedia – Social and Behavioral Sciences, 39, Mallorca, Spain,
836 p. 463-475.
- 837 Behrends, S., 2012b. The significance of the urban context for the sustainability performance of intermodal road-rail
838 transport. 15th meeting of the EURO Working Group on Transportation, Procedia – Social and Behavioral Sciences,
839 39, Paris, France, p. 375-386.
- 840 Benjelloun A. and T.G. Crainic, 2008. Trends, challenges, and perspectives in city logistics. *Transportation and land
841 use interaction*, proceedings TRANSLU, 8, p. 269-284.
- 842 Besinovic N., R.M.P. Goverde, E. Quaglietta and R. Roberti, 2016. An integrated micro-macro approach to robust
843 railway timetabling. *Transportation Research Part B: Methodological*, 87, p.14-32.
- 844 Borodin, V., 2014. *Optimisation et simulation d’une chaîne logistique : application au secteur de l’agriculture*. Thèse de
845 Doctorat, Université de technologie Troyes, France.
- 846 Brice, D., M. Marinov and B. Rüger, 2015. A newly designed baggage transfer system implemented using event-based
847 simulations. *Urban Rail Transit*, 1(4), p. 194-214.
- 848 Browne, M., J. Allen, A. Woodburn and M. Piotrowska, 2014. The potential for non-road modes to support
849 environmentally friendly urban logistics. 1st International Conference Green Cities 2014 – Green Logistics for
850 Greener Cities, London, UK, p. 29-36.
- 851 Cargo Cap, 2002. Automated underground transportation of cargo: The 5th transportation alternative for the transport of
852 goods in congested urban areas. www.cagocap.com, 2016.
- 853 Comi, A. and A. Nuzzolo, 2015. Modelling challenges to forecast urban goods demand for rail. *Transport problems*,
854 10(4), p. 75-91.
- 855 Comi, A. and A. Nuzzolo, 2016. Exploring the Relationships between E-Shopping Attitudes and Urban Freight
856 Transport. *Transportation Research Procedia*, 12, p. 399-412.
- 857 Crainic, T.G. and G. Laporte, 1996. Planning models for freight transportation. *European Journal of Operational
858 Research*, 97, p. 409-438.
- 859 CST, 2016. Cargo sous terrain: The goods transport system of the future. Press release 26th January 2016.
860 <http://www.cargosousterain.ch>, 2016.

861 Dablan, L., 2007. Goods transport in large European cities: difficult to organize, difficult to modernize. *Transportation*
862 *Research Part A: Policy and Practice*, 41(3), p. 280-285.

863 Dablan, L., 2009. Freight transport for development toolkit: Urban freight. Department for International Development,
864 The World Bank.

865 Dampier, A. and M. Marinov, 2015. A study of the feasibility and potential implementation of metro-based freight
866 transportation in Newcastle upon Tyne. *Urban Rail Transit*, 1(3), p. 164-182.

867 De Langhe, K., 2014. Analysing the role of rail in urban freight distribution. *Next Generation Supply Chains: Trends*
868 *and Opportunities*, epubli GmbH, Berlin.

869 Delmastro, C., E. Lavagno and L. Schranz, 2016. Underground urbanism: Master plans and sectorial plans. *Tunnelling*
870 *and Underground Space Technology*, 55, p. 103-111.

871 Dessouky, M. and R. Leachman, 1995. A simulation modeling methodology for analyzing large complex rail network.
872 *Simulation*, 65 (2), p. 131-142.

873 Dinwoodie, J., 2006. Rail freight and sustainable urban distribution: potential and practice. *Journal of Transport*
874 *Geography*, 14, p. 309-320.

875 Diziain, D., E. Taniguchi and L. Dablan, 2014. Urban logistics by rail and waterways in France and Japan. 8th
876 *International Conference on City Logistics, Procedia - Social and Behavioral Sciences*, 125(2014), p. 159-170.

877 Egbunike, O.N. and A.T. Potter, 2011. Are freight pipelines a pipe dream? A critical review of the UK and European
878 perspective. *Journal of Transport Geography*, 19(4), p. 499-508.

879 European Commission, 2011. White Paper - Roadmap to a single European transport area - Towards a competitive and
880 resource efficient transport system, COM/2011/0144 final. European Commission.

881 European Cooperation in the Field of Scientific and Technical Research, 1998. COST 321 Urban goods transport – final
882 report of the action. Official Publication of the European Communities.

883 Fatnassi, E., J. Chaouachi and W. Klibi, 2015. Planning and operating a shared goods and passengers on-demand rapid
884 transit system for sustainable city-logistics. *Transportation Research Part B: Methodological*, 81 (2), p. 440-460.

885 Figliozzi, M.A., 2007. Analysis of the efficiency of urban commercial vehicle tours: Data collection, methodology, and
886 policy implications. *Transportation Research Part B: Methodological*, 41 (9), p. 1014-1032.

887 Figliozzi, M.A., 2010. The impacts of congestion on commercial vehicle tour characteristics and costs. *Transportation*
888 *Research Part E: Logistics and Transportation Review*, 86 (4), p. 496-506.

889 Fisher, M., R. Jaikumar and L. Van Wassenhove, 1986. A multiplier adjustment method for the generalized assignment
890 problem. *Management Science*, 32(9), p. 1095-1103.

891 Furtado, F., 2011. ICT and management tools for railway freight. Work document - Instituto Superior Técnico /
892 Massachusetts Institute of technology (unpublished).

893 Gao, Y., L. Kroon, L. Yang and Z. Gao, 2017. Three stage optimization method for the problem of scheduling
894 additional trains on a high-speed rail corridor. *Omega*, <https://doi.org/10.1016/j.omega.2017.08.018>

895 Gonzalez-Feliu, J., 2014. Costs and benefits of railway urban logistics: a prospective social cost benefit analysis.
896 <<https://halshs.archives-ouvertes.fr/halshs-01056135>>.

897 Grube, P., F. Nunez and A. Cipriano, 2010. An event-driven simulator multi-line metro systems and its application to
898 Santiago de Chile metropolitan rail network. *Simulation Modelling Practice and Theory*, 19 (1), p. 393-405.

899 Kashima, S., R. Nakamura, M. Matano, T. Taguchi and T. Shigenaga, 1993. Study of an underground physical
900 distribution system in a high-density, built-up area. *Tunnelling and Underground Space Technology*, 8(1), p. 53-59.

901 Köhler, J., L. Whitmarsh, B. Nykvist, M. Schilperoord, N. Bergman and A. Haxeltine, 2009. A transitions model for
902 sustainable mobility. *Ecological Economics*, 68(12), p. 2985-2995.

903 Lawley, M., V. Parmeshwaran, J.P. Richard, A. Turkcan, M. Dalal and D. Ramcharan, 2007. A time-space scheduling
904 model for optimizing recurring bulk railcar deliveries. *Transportation Research Part B: Methodological*, 42 (5), p.
905 438-454.

906 Limbourg, S. and B. Jourquin, 2009. Optimal rail-road container terminal locations on the European network.
907 *Transportation Research Part E: Logistics and Transportation Review*, 45 (4), p. 551-563.

908 Lindholm, M. and S. Behrends, 2012. Challenges in urban freight transport planning – a review in the Baltic Sea
909 Region. *Journal of Transport Geography*, 22, p. 129-136.

910 MacHarris, C., J. Van Mierlo and P. Van Den Bossche, 2007. Combining intermodal transport with electric vehicles:
911 towards more sustainable solutions. *Transportation Planning and Technology*, 30(2-3), p. 311-323.

912 Mairie de Paris, 2009. Le transport de marchandises dans la ville de Paris. Direction de la Voirie & des Déplacements,
913 Agence de la Mobilité - Usagers & Marchandises.

914 Marinov, M., T. Zunder and D. Islam, 2010. Concepts, models and methods for rail freight and logistics performances:
915 an inception paper. *Proceedings Media of the 12th World Conference on Transport Research*, Lisbon, Portugal.

916 Masson, R., A. Trentini, F. Lehuédé, N. Malhéné, O. Péton and T. Houda, 2015. Optimization of a city logistics
917 transportation system with mixed passengers and goods. *EURO Journal on Transportation and Logistics*, (2015), p.
918 1-29.

919 Metropolitan Transportation Authority, 2014. NYCT Trash Can Free Stations Pilot Update. Report Presentation,
920 January, Metropolitan Transportation Authority.

921 MONOPRIX, 2007. L'acheminement des marchandises par voie ferrée et véhicules roulant au GNV vers les magasins
922 monoprix et MONOP' de Paris. Dossier de Presse Ferroviaire, July 04, MONOPRIX.

923 Motraghi, A. and M.V. Marinov, 2012. Analysis of urban freight by rail using event based simulation. *Simulation*
924 *Modelling Practice and Theory*, 25, p. 73-89.

925 Nanaki, E. A., C. J. Koroneos and G. A. Xydis, 2016. Environmental impact assessment of electricity production from
926 lignite. *Environmental Progress & Sustainable Energy*, 35, p. 1868–1875.

927 National Institute of Statistics and Economic Studies, <http://www.insee.fr>, 2015.

928 Nuzzolo, A. and A. Comi, 2014. Urban freight demand forecasting: A mixed quantity/delivery/vehicle-based model.
929 *Transportation Research Part E: Logistics and Transportation Review*, 65, p. 84-98.

930 Nuzzolo, A., U. Crisalli and A. Comi, 2007. Metropolitan freight distribution by railways. 5th International Conference
931 on City Logistics, Crete, Greece.

932 OECD, 2014. OECD Economic Surveys: European Union 2014. OECD Publishing.

933 Offer, G.J., D. Howey, M. Contestabile, R. Clague and N.P. Brandon, 2010. Comparative analysis of battery electric,
934 hydrogen fuel cell and hybrid vehicles in a future sustainable road transport system. *Energy Policy*, 38(1), p. 24-29.

935 Quak, H., 2008. Sustainability of urban freight transport. Retail distribution and local regulations in cities. PhD Thesis,
936 Erasmus Universiteit Rotterdam.

937 Reece, D. and M. Marinov, 2015. Modelling the implementation of a Baggage Transport System in Newcastle upon
938 Tyne for passengers using Mixed-Mode Travel. *Transport Problems*, 10(4), p. 149-155.

939 Robinson, M. and P. Mortimer, 2003. Urban freight and rail – the state of the art. *Logistics & Transport Focus*,
940 January/February 2003, p. 46-51.

941 Rossetti M., 2010. *Simulation Modelling and Arena*. John Wiley and Sons.

942 Russo, F. and A. Comi, 2010. A modelling system to simulate goods movements at an urban scale. *Transportation*, 37
943 (6), p. 987-1009.

944 Sallez, y., S. Pan, B. Montreuil, T. Berger and E. Ballot, 2016. On the activeness of intelligent Physical Internet
945 containers. *Computers in Industry*, 81, p. 96-104.

946 SOGARIS, XPOLogistics and EURORAIL, 2016. Chapelle International : Sogaris, Eurorail et XPOLogistics signent
947 un accord de collaboration pour la mise en place de la première Navette Ferroviaire Urbaine à Paris. Press release
948 22nd March 2016. <http://fr.xpo.com>, 2016.

949 Tang, J. , A. McNabola, B. Misstear and Brian Caulfield, 2017. An evaluation of the impact of the Dublin Port Tunnel
950 and HGV management strategy on air pollution emissions. *Transportation Research Part D: Transport and*
951 *Environment*, 52 (A), p. 1-14.

952 Taniguchi, E., R. G. Thompson, T. Yamada, and R. van Duin, 2001. *City Logistics – Network Modelling and Intelligent*
953 *Transport Systems*, Pergamon.

954 Trentini, A. and N. Malhene, 2012. Flow management of passengers and goods coexisting in the urban environment:
955 Conceptual and operational points of view. 7th International Conference on City Logistics, *Procedia - Social and*
956 *Behavioral Sciences*, 39(2012), p. 807-817.

957 United Nations, 2015. *World Urbanization Prospects - The 2014 Revision*. United Nations Department of Economic
958 and Social Affairs/Population Division.

959 Van Audenhove, F.J., S. De Jongh and M. Durance, 2015. *Urban Logistics – How to unlock value from last mile*
960 *delivery for cities, transporters and retailers*. Arthur D. Little Future of Urban Mobility Lab.

961 Van Duin, J.H.R., L.A. Tavasszy and H.J. Quak, 2013. Towards E(lectric)- urban freight: first promising steps in the
962 electric vehicle revolution. *European Transport \ Trasporti Europei*, 54, Paper n° 9.

963 Van Wee, B., K. Maat and C. De Bont, 2012. Improving Sustainability in Urban Areas: Discussing the Potential for
964 Transforming Conventional Car-based Travel into Electric Mobility. *European Planning Studies*, 20(1), p. 95-110.